

Lecture 17: Exceptions

11:00 AM, Mar 1, 2021

Contents

| | | |
|----------|---|----------|
| 1 | Motivating Context | 2 |
| 2 | Handling Rlogin Poorly with If-statements | 2 |
| 3 | Exceptions | 3 |
| 3.1 | Creating and Throwing Exceptions | 3 |
| 3.2 | Catching Exceptions | 4 |
| 3.3 | Understanding Exceptions by Understanding Call Stacks | 5 |
| 3.4 | Housekeeping: annotating intermediate methods | 6 |
| 4 | Summarizing Try/Catch blocks | 6 |
| 4.1 | Handling Incorrect Passwords | 6 |
| 5 | Checked Versus Unchecked Exceptions | 7 |

Motivating Question

How can we modify the banking code to handle login failures by prompting people to try logging in again?

Objectives

By the end of these notes, you will know:

- when to create and manage your own exceptions
- how exceptions are actually processed when programs run

By the end of these notes, you will be able to:

- create your own exceptions
- use try, catch, and throws statements to manage your own exceptions
- understand which lines of code do and don't get executed when exceptions are thrown

1 Motivating Context

Our last version of the banking example (see website for starter code) doesn't handle login errors well. It either accepts the login or crashes the system with a null pointer exception. Ideally, we need something more nuanced – if someone enters an invalid username or password, we would ideally prompt them to log in again.

2 Handling Relogin Poorly with If-statements

What might a revised `loginScreen` method look like if we did these checks with if-statements?

```
public class BankingConsole {
    public void loginScreen() {
        Scanner keyboard = new Scanner(System.in);
        System.out.println("Welcome to the Bank. Please log in.");
        System.out.print("Enter your username: ");
        String username = keyboard.next();
        System.out.print("Enter your password: ");
        String password = keyboard.next();
        if (controller.login(username, password))
            System.out.println("Thanks for logging in!");
        else {
            System.out.println("Login failed. Please try again");
            this.loginScreen();
        }
    }
}
```

This would require the `login` method to change to return a boolean, which would in turn require checking whether `findCustomer` had returned null.

```
public boolean login(String custname, String withPwd) {
    Customer cust = customers.findCustomer(custname);
    if (cust == null)
        return false;
    else if (cust.checkPwd(withPwd)) {
        this.loggedIn.addFirst(cust);
        return true;
    } else {
        return false;
    }
}
```

Notice how the code is getting a bit cluttered with the nested `if` statements? It would be much nicer to have the `login` method be clean and streamlined, focusing on the core logic of logging in. Something like:

```
public void login(String custname, String withPwd) {
    Customer cust = customers.findCustomer(custname);
    if (cust.checkPwd(withPwd)) {
```

```
        this.loggedIn.addFirst(cust);  
    }  
}
```

This is the code we will have (with one small addition) at the end of the lecture.

3 Exceptions

Right now, `findCustomer` returns `null`, as a way of saying "no answer". While this approach gets past the compiler, it is not a good solution because it clutters up the code of other methods that call `findCustomer`. The better approach is to raise an error that our program can handle (rather than crashing, as a `RuntimeException` would). Exceptions are designed to help programs flag and handle situations that would otherwise complicate the normal logic of the program you are trying to write.

Exceptions (or some similar notion) exist in most mainstream programming languages. Intuitively, if a function encounters a situation that is not expected, it does not try to return a normal value. Instead, it announces that a problem occurred (by *throwing* or *raising* an exception). Other methods watch for announcements and try to recover gracefully.

3.1 Creating and Throwing Exceptions

Our goal is to replace the `return null` statement from the current `findCustomer` code with an exception to alert to the rest of the code that something unexpected happened (in this case, the customer was not found). The Java construct that raises alerts is called `throw`. Our first step, then, is to replace the `return null` statement with a `throw` statement:

```
public Customer findCustomer(String custname) {  
    for (Customer cust : customers) {  
        if (cust.nameMatches(custname)) {  
            return cust;  
        }  
    }  
    // replace return null with a report of an error  
    throw new CustomerNotFoundException(custname);  
}
```

`CustomerNotFoundException` is a new class that we will create to hold information relevant to the error that occurred (in this case, which customer couldn't be found – we might want to print this information out as part of error message later). We create a subclass of `Exception` for each different type of alert that we want to raise in our program.

```
class CustNotFoundException extends Exception {  
    String unfoundName;  
  
    CustNotFoundException(String name) {  
        this.unfoundName = name;  
    }  
}
```

An exception subclass should store any information that might be needed later to respond to the exception. In this case, we store the name of the customer that could not be found. This info would be useful, for example, in printing an error message that indicated which specific customer name could not be found.

Summarizing: we modify `findCustomer` to throw a `CustNotFoundException` if it fails to find the customer. Three modifications are required:

- The `throw` statement needs to be given an object of the `CustNotFoundException` class to throw.
- The `findCustomer` method must declare that it can throw that exception (the compiler needs this information). This occurs in a new `throws` declaration within the method header, as shown below.
- The `ICustomerSet` interface, which has the `findCustomer` method header, must also include the `throws` statement.

```
interface ICustomerSet {
    Customer findCustomer(String name) throws CustNotFoundException;
}

class CustomerList implements ICustomerSet {
    ...
    // return the Customer whose name matches the given name
    public Customer findCustomer(String custname)
        throws CustomerNotFoundException {
        for (Customer cust : customers) {
            if (cust.nameMatches(custname)) {
                return cust;
            }
        }
        // replace return null with a report of an error
        throw new CustomerNotFoundException(custname);
    }
}
```

3.2 Catching Exceptions

Exceptions are neat because they let us (as programmers) control what part of the code handles the errors that exceptions report. Think about what happens when you encounter a login error when using a modern web-based application: the webpage (your user interface) tells you that your username or password was incorrect and prompts you to try logging in again. That's the same behavior we want to implement here.

To do this at the level of code, we will use another new construct in Java called a `try-catch` block. We "try" running some method that might result in an exception. If the exception is thrown, we "catch" it and handle it. Here's a `try-catch` pair within the `loginScreen` (which is where we already said we want to handle the error:

```
public void loginScreen() {
    Scanner keyboard = new Scanner(System.in);
    System.out.println("Welcome to the Bank. Please log in.");
    System.out.print("Enter your username: ");
    String username = keyboard.next();
    System.out.print("Enter your password: ");
    String password = keyboard.next();
    try {
        controller.login(username, password);
        System.out.println("Thanks for logging in!");
    } catch (CustomerNotFoundException e) {
        // what to do when this happens
        System.out.println("No user " + e.custname);
        this.loginScreen();
    }
}
```

Notice the `try` encloses both the call to `login` and the `println` that login succeeded. When you set up a `try`, you have it enclose the entire sequence of statements that should happen if the exception does NOT get thrown. As Java runs your program, if any statement in the `try` block yields an exception, Java ignores the rest of the `try` block and hops down to the `catch` block. Java runs the code in the `catch` block, and continues from there.

The `e` after `CustomerNotFoundException` in the `catch` line refers to the exception object that got thrown. As the code shows, we could look inside that object to retrieve information that is useful for handling the error (like printing an error message).

Note: if you've only typed in the code to this point and try to compile, you will get errors regarding the `login` method – hang on – we're getting to those by way of the next section.

3.3 Understanding Exceptions by Understanding Call Stacks

To understand how exceptions work, you need to understand a bit more about how Java evaluates your programs.

Exceptions aside, what happens "under the hood" when Java runs your program and someone tries to log in? Our main method started by calling the `loginScreen` method; this method calls other methods in turn, with methods often waiting on the results of other methods to continue their own computations. Java maintains a *stack* (we discussed those briefly in the data structures lectures) of method calls that haven't yet completed. When we kick off `loginScreen`, this stack contains just the call to that method.

Separately from the stack, Java starts running the code in your method statement by statement. Imagine an arrow alongside your code that tracks which statement Java is currently evaluating (statements above the arrow are already completed).

Switch now to the following PDF, which walks through how Java executes programs with `try/catch` blocks, showing what we mean by the "arrow alongside code".

<http://cs.brown.edu/courses/csci0180/content/lectures/aux/ExceptionControlFlow.pdf>

The slideshow you just saw simplifies a couple of details. There may be multiple `try` markers on the stack (because you can have multiple `try` blocks), and the stack has ways of "remembering"

where it left off in pending method calls. We ignore those details here in the hopes of giving you the bigger picture.

3.4 Housekeeping: annotating intermediate methods

As our demonstration of the stack just showed, the `CustomerNotFoundException` "passes through" certain classes as it comes back from the `findCustomer` method. The Java compiler needs every method to acknowledge what exceptions might get thrown while it is running. We therefore have to add the same `throws` annotations to each method that does not want to catch the exception as it passes through on the way to the marker. For example, the `login` method needs to look as follows:

```
public String login(String custname, String withPwd)
    throws CustomerNotFoundException, LoginFailedException {
    Customer cust = customers.findCustomer(custname);
    if (cust.checkPwd(withPwd)) {
        System.out.println('Login Successful');
        this.loggedIn.addFirst(cust);
    } else {
        System.out.println('Login Failed');
    }
}
```

Once you put these additional `throws` annotations on the code, the code should compile and Java will report failed logins through the `loginScreen`.

4 Summarizing `try/catch` blocks

At this point, you should understand that `throw` statements go hand-in-hand with `try/catch` blocks. Whenever a method declares that it can throw an exception, any method that calls it needs a `try/catch` statement to process the exception.

More generally, a `try-catch` block looks as follows:

```
try {
    <the code to run, assuming no exceptions>
} catch <Exception> {
    <how to recover from the exception>
}
```

You can have multiple `catch` phrases, one for each kind of exception that you need to handle differently (or you can have two kinds of exceptions get handled the same way, as we will show shortly).

4.1 Handling Incorrect Passwords

Now that you've seen one example of exceptions, let's try another. As an exercise for yourself, change the `login` method in the `CustomerList` class (which checks the password) so that it throws an exception called `LoginFailedException` if the passwords don't match.

Try it before reading further.

You should have ended up with the following:

```
public String login(String custname, String withPwd)
    throws CustomerNotFoundException, LoginFailedException {
    Customer cust = customers.findCustomer(custname);
    if (!cust.checkPwd(withPwd))
        throw new LoginFailedException(custname);
    this.loggedIn.addFirst(cust);
}
```

In addition, we have to add this exception to the catch used to prompt a user to log in again.

```
public void loginScreen() {
    Scanner keyboard = new Scanner(System.in);
    System.out.println("Welcome to the Bank. Please log in.");
    System.out.print("Enter your username: ");
    String username = keyboard.next();
    System.out.print("Enter your password: ");
    String password = keyboard.next();
    try {
        controller.login(username, password);
        System.out.println("Thanks for logging in!");
    } catch (CustomerNotFoundException | LoginFailedException e) {
        // what to do when this happens
        System.out.println("Login Failed");
        this.loginScreen();
    }
}
```

As with the CustNotFoundException, you have to put throws annotations on all methods that can either throw or pass along the FailedLoginException. You'll see this in the final posted code.

5 Checked Versus Unchecked Exceptions

What we have done so far with try/catch and throw statements are called *Checked Exceptions*: exceptions that you are using within your application to respond to special situations that arise within your code. With checked exceptions, Java analyzes your code at compile time to make sure that the exceptions will actually be caught (and handled).

Sometimes, however, your code fails because of a bug in your code. Null pointer exceptions, array index out of bounds exceptions, and division by zero exceptions are examples of exceptions that alert you to bugs when they are thrown. You don't want to catch these – you want to fix your code so that they can't happen again. Put differently, the fix for such situations is to debug your code before you run it. Checked exceptions, in contrast, are for situations you can't control (because they arise from user behavior, for example) that arise while your application is running.

These “code-error” exceptions are special cases of RuntimeExceptions, which we saw earlier in the course. When you throw a runtime exception, you shouldn't catch and manage it (and the compiler won't expect you to). Runtime exceptions are handy when you are working on your code and just

want to throw something so you can get past the compiler and test the code you're currently working on. In production code, you only use them for situations in which the program needs to terminate. As a general rule, you should write (and catch) checked exceptions from here on out in homeworks and projects.

Please let us know if you find any mistakes, inconsistencies, or confusing language in this or any other CS18 document by filling out the anonymous feedback form: <https://cs.brown.edu/courses/cs018/feedback>.