Introductionary + advanced R course

Berry Boessenkool, berry-b@gmx.de
Hints and corrections are very welcome!

Download the current slides, source code and datasets at

github.com/brry/course

These slides are licenced under CC BY,
so you can use the material freely as long as you cite me.

PDF created on 2017-11-21, 11:22

Outline

R course info
1. One-Session-Intro
2. Getting started: Background, GUI and first steps
3. Objects
4. "Real" data
5. Plotting
6. Character Operations
7. Conditions & loops
8. Functions & packages
9. Distributions
10. Statistics
11. Time series handling and analysis
12. Spatial data and GIS functionality
13. Final tasks
Course plan

Outline

R course info
1. One-Session-Intro
   Intro, objects, vectors
   Files, data.frames
   Plotting
   Packages, regression
2. Getting started: Background, GUI and first steps
3. Objects
4. "Real" data
5. Plotting
6. Character Operations
7. Conditions & loops
8. Functions & packages
9. Distributions
10. Statistics
11. Time series handling and analysis
12. Spatial data and GIS functionality
13. Final tasks
Course plan

print("Hello world!")

- Berry Boessenkool → berry-b@gmx.de
- Geoecology @ Potsdam University
- R Fanatic since 2010
  - Teaching: RclickHandbuch.wordpress.com (German) + this course
  - Programming: `extremeStat`, `berryFunctions`, `rdwd`, `OSMscale`
  - Community: BERLIN R USER GROUP
- These slides were originally based on a one week course held in 2013 for CaWa with Mathias Seibert (GFZ) in Bishkek, Kyrgyzstan
- R installation instructions: github.com/brry/course#install
- If we're proceeding too fast, please interrupt!

Why programming?

- Data analysis
- Plotting *Excel could do that, but is lacking*
- Awesomeness
  - efficiency
  - flexibility
  - automatization
  - transparency, reproducibility
  - complex statistical procedures
  - job chance advantage

Why R? (and not matlab, python, java, html, C++, fortran)

- Open Source → free!
- Large community → stunning lots of methods!
- Interpreter language → no compilation, human readable code
- The standard for data analysis in many universities and industries

In the future, programming will save you time!

I find that when someone's taking time to do something right in the present, they're a perfectionist with no ability to prioritize, whereas when someone took time to do something right in the past, they're a master artisan of great foresight. (xkcd.com/974)

Course plan

Jump to plan Session 1

One slide about Rstudio, and then we'll finally start...

Integrated Development Environment (IDE): RStudio

Get started in R

Exercise 1: R is an awesome calculator

In the console, calculate 21+21 , 7*6 and $\frac{0{,}3}{4} * \sqrt{313600}$

If you don't know how to compute a square root in R, you can google it!

```
21+21 ; 7*6 ; 0.3/4*sqrt(313600)
```

- objects: assignment with $<-$ Rstudio Keyboard shortcut: `ALT + -`

  ```
  nstudents <- 15
  nstudents
  nstudents > 12
  ```

- What's a good object name? → short, but explanatory, lowerCamelStandard_or_underscore are good naming conventions
- comments: `# everything after a hashtag is not executed.`
- scripts: Rstudio

Objects: vectors

- To create a vector with values, use the syntax
  `values <- c(3, -11, 13, 5.94) # concatenate, combine`
- To obtain a subset (=indexing), use square brackets: `values[2]`

Exercise 2: Vector indexing

1. Create a vector with body sizes of people around you. You can also use the values 1.75, 1.76, 1.83, 1.84, 1.77, 1.76, 1.77, 1.66, 1.86, 1.76. Assign it to an object with a useful name (`YourObject` is not one!).
2. What does `3:6` create? What does `YourObject[3:6]` do?
3. What does `YourObject[-4]` do?
4. BONUS (for fast people): Analyze the descriptive statistics: `mean(YourObject), median, min, max, range, quantile`
5. BONUS 2: Help your peers - there's no reason to be bored ;-)

Vector task solutions

```
size <- c(1.75, 1.76, 1.83, 1.84, 1.77, 1.76,
          1.77, 1.66, 1.86, 1.76)
3:6 # A vector with consecutive integers
size[3:6] # Select the corresponding elements of a vector
size[-4] # Select all but the fourth value
```

```
c(mean(size), median(size), min(size), max(size)); range(size); quantile(size)
```

```
## [1] 1.776 1.765 1.660 1.860
## [1] 1.66 1.86
##    0%   25%   50%   75%  100%
## 1.660 1.760 1.765 1.815 1.860
```

`mean` and `median` are similar, hinting at a symmetric data distribution
`range` returns a composite of `min`imum and `max`imum
`quantile` returns quantiles (now that is surprising...)

Outline

R course info
1. One-Session-Intro
   Intro, objects, vectors
   Files, data.frames
   Plotting
   Packages, regression
2. Getting started: Background, GUI and first steps
3. Objects
4. "Real" data
5. Plotting
6. Character Operations
7. Conditions & loops
8. Functions & packages
9. Distributions
10. Statistics
11. Time series handling and analysis
12. Spatial data and GIS functionality
13. Final tasks
Course plan

Reading files

Exercise 3: Reading files

Copy the file treesize.txt *(rightclick **Raw**, save as)* and tell R where to look for it with:

```
setwd("C:/path/to/input") # change back- to forwardslashes
```

Read the file into R with the command `read.table`, assigning it to an object with a good name.

Use the documentation to find out the correct settings of the arguments: `help(read.table)`, `?read.table`, or press F1.

If R tells you "no such file" exists, check the output of `dir()`.

Check the object with `head(YourObject)`.

`str(YourObject)` must yield the column data types: `num, num, factor`.

You need to set the argument `header`.

Solution to exercise 3: Reading files

```
treesize <- read.table(file="treesize.txt", header=TRUE)
```

Objects: data.frames

- For tables with different data types (numbers, characters, categories, integers), R has the object type data.frame:
  `data.frame(count=c(2,6,5), type=c("a","k","k"))`
- `read.table` also returns a data.frame
- If we have the object `df`, we can subset with `df[rows,columns]`
- `df[1,2:4]; df[2, ]; df[ ,"name"]; df$name`
- Logical values: `vect[c(TRUE,TRUE,FALSE,FALSE,TRUE,FALSE)]`

Exercise 4: Data.frame indexing

From the dataset `treesize` from the previous exercise, obtain:

1. The first 5 values in column 2
2. The maximum "Height" (the maximum of the values in that column)
3. For each entry: is the measurement equal to (==) A?
4. BONUS 1: The height entries for trees older than 23.5 years
5. BONUS 2: All rows, excluding rows 3,7,8,9,...,90

Solution to exercise 4: subsetting data.frames I

```
treesize[1:5, 2]

## [1] 32.7 26.0 27.9 35.4 26.4

max(treesize$height)  ;   max(treesize[ ,"age"])

## [1] 40.1
## [1] 24.8

treesize$measurement=="A"

##   [1]  TRUE  TRUE  TRUE  TRUE FALSE FALSE  TRUE  TRUE  TRUE  TRUE  TRUE FALSE
##  [13]  TRUE  TRUE  TRUE FALSE  TRUE FALSE FALSE FALSE  TRUE FALSE  TRUE  TRUE
##  [25]  TRUE FALSE  TRUE FALSE FALSE FALSE FALSE  TRUE  TRUE FALSE FALSE FALSE
##  [37] FALSE  TRUE FALSE  TRUE FALSE FALSE  TRUE  TRUE  TRUE FALSE FALSE FALSE
##  [49]  TRUE FALSE  TRUE  TRUE  TRUE  TRUE FALSE FALSE  TRUE  TRUE FALSE FALSE
##  [61]  TRUE  TRUE FALSE FALSE  TRUE FALSE  TRUE FALSE  TRUE FALSE FALSE FALSE
##  [73] FALSE FALSE FALSE FALSE  TRUE FALSE  TRUE FALSE FALSE  TRUE  TRUE  TRUE
##  [85] FALSE FALSE FALSE FALSE  TRUE FALSE  TRUE  TRUE FALSE  TRUE  TRUE FALSE
##  [97]  TRUE FALSE  TRUE  TRUE
```

Solution to exercise 4: subsetting data.frames II

```
treesize[ treesize$age >= 23.5 , "height"]

##  [1] 32.7 38.4 40.1 34.0 32.3 32.6 34.4 23.2 34.6
## [10] 35.9
```

```
treesize[ -c(3,7:90) , ]

##     age height measurement
## 1  24.4   32.7           A
## 2  13.6   26.0           A
## 4  21.2   35.4           A
## 5  19.8   26.4           B
## 6   7.7    7.2           B
## 91 23.1   39.0           A
## 92 24.6   34.6           A
## 93  7.7    9.2           B
## 94 10.1   10.3           A
## 95 23.8   35.9           A
## 96  7.7    7.4           B
## 97 17.8   31.6           A
## ...
```

Outline

R course info
1. One-Session-Intro
   Intro, objects, vectors
   Files, data.frames
   Plotting
   Packages, regression
2. Getting started: Background, GUI and first steps
3. Objects
4. "Real" data
5. Plotting
6. Character Operations
7. Conditions & loops
8. Functions & packages
9. Distributions
10. Statistics
11. Time series handling and analysis
12. Spatial data and GIS functionality
13. Final tasks
Course plan

Plotting I

General code for scatterplots: `plot(x, y, ...)`

```
plot(x=Indometh$time, y=Indometh$conc,
     col="orange", pch=16, main="Awesome Graph!")
```

Plotting I

General code for scatterplots: `plot(x, y, ...)`

```
points(4, 1.5, pch=22, bg="yellow", cex=4, col="red")
# PointCHaracter, BackGround, Character EXpansion
```

Plotting I

General code for scatterplots: `plot(x, y, ...)`

```
lines(x=c(2,5,6,7), y=c(1,2.3,-3,1),
      col=4, type="b", lwd=5)
```

Plotting II: Our treesize dataset

```
treesize <- read.table(file="data/treesize.txt", header=TRUE)
```

```
plot(x=xvalues, y=y_values, xlab="nice axis label",
     main="graph title", las=1)
```

Exercise 5: Scatterplots, sample distribution graphs

1. Plot tree height over age.
2. Add labels to the plot.
3. Change the point character (`pch`) and color (`col`).
4. BONUS 1: Use a vector for colors, e.g. treesize$measurement
5. BONUS 2: Compare the histogram (`hist`) of the heights with the `boxplot` and `quantile(x, probs=c(0.1, 0.8))`.

Solution for exercise 5: Scatterplots

```
treesize <- read.table(file="data/treesize.txt", header=TRUE)

plot(treesize$age, treesize$height)
plot(treesize$age, treesize$height, las=1, ylab="Tree height [m]",
     xlab="Tree age [years]", col=treesize$measurement,
     main="Older trees are larger", pch=3)
quantile(treesize$height, probs=c(0.1, 0.8))

##   10%   80%
##  8.93 32.36
```

Solution for exercise 5: Scatterplot

Solution for exercise 5: Histogram

```
hist(treesize$height, col=6, breaks=20, las=1)
```

Solution for exercise 5: Boxplot

```
boxplot(treesize$height, col=5, horizontal=TRUE, notch=TRUE)
```

commonly needed plot arguments

```
plot(x, y, # point coordinates
col="lightblue", # point color
pch=0, # point character (symbol)
xlab="My label  [km]", ylab="", # axis labels
main="Graph title", # title
cex=1.8, # character expansion (symbol size)
type="l", # draw lines instead of points
lwd=3, # line width (thickness of lines)
las=1, # label axis style (axis numbers upright)
xaxt="n" # axis type (none to suppress axis)
)
```

Outline

R course info
1. One-Session-Intro
   Intro, objects, vectors
   Files, data.frames
   Plotting
   Packages, regression
2. Getting started: Background, GUI and first steps
3. Objects
4. "Real" data
5. Plotting
6. Character Operations
7. Conditions & loops
8. Functions & packages
9. Distributions
10. Statistics
11. Time series handling and analysis
12. Spatial data and GIS functionality
13. Final tasks
Course plan

R Packages

- Many people write code for specific tasks and publish it on CRAN, the Comprehensive R Archive Network
- Packages for a range of topics: cran.r-project.org/web/views
- All >10'500 available packages: cran.r-project.org/web/packages
- `install.packages("ggplot2")` to download and install.
  (only needs to be executed once, works on user level, no admin rights required)

  You can do this in Rstudio
- `library("ggplot2")` to load it

  (needed in every new R session) Put this in the script for reproducibility
- Better to use the `package::function` syntax
- Regularly run `update.packages()` or use the Rstudio button
- Rarely needed: `remove.packages("packagename")`

Packages and linear regression

Exercise 6: Packages, linear regression

1. Install and load the package `berryFunctions`
2. How can we pass the treesize data to `?linReg` with a formula?
   Hint: Read the "Examples" section of the function manual.
3. Describe the resulting graph (height vs age).
4. Look into the source code of `linReg`. *If you don't know how to view the source code of a function in R, you can google it!* What is actually the backbone for the calculation of the function?
5. Feed the data into `lm`, assign the output to an object (useful name!).
6. Briefly explain the `summary` of the linear model.
7. BONUS: install rskey (via github), set a keyboard shortcut for `funSource` and use it to get the source code of some function.

Solution for exercise 6: Linear regression

```
library("berryFunctions")
linReg(height~age, data=treesize)
linReg
browseURL("https://github.com/brry/berryFunctions")
# go to R/linReg.R  -  working horse: lm
linear_model <- lm(height~age, data=treesize)
summary(linear_model)
```

blog.yhathq.com/posts/r-lm-summary.html

stats.stackexchange.com/questions/5135/interpretation-of-rs-lm-output

Time to put all of this into practice

Exercise 7: Reading files, subsetting, comparison

1. Start a new session of R. Read in the tree size data.
2. Check that everything is read correctly with `str`.
3. `which` rows of the data.frame have measurement equal to (`==`) B?
4. Plot the linear regression for measurement method B, then add the points and regression line for A in a different color and shape.
5. BONUS 1: use `boxplot` with a formula (`height~measurement`) for an automatic boxplot comparison with median difference notches.
6. BONUS 2: Visually compare the effect of Girth and Height on Volume in the dataset `trees`. Here's one idea (of many possible): Plot with two panels below each other (`par(mfrow=c(2,1))`), with the linear regression plots (`berryFunctions::linReg`) for each variable. Make it look nice with the graphical `par`ameters `mar` and `mgp`, as well as by specifying some of the linReg arguments.

Solution for exercise 7: Reading files, subsetting

```r
setwd("D:/my/path")
treesize <- read.table(file="data/treesize.txt", header=TRUE)
str(treesize)
```

```r
which(treesize$measurement=="B")

##  [1]  5  6 12 16 18 19 20 22 26 28 29 30 31 34 35
## [16] 36 37 39 41 42 46 47 48 50 55 56 59 60 63 64
## [31] 66 68 70 71 72 73 74 75 76 78 80 81 85 86 87
## [46] 88 90 93 96 98

treeA <- treesize[treesize$measurement=="A", ]
treeB <- treesize[treesize$measurement=="B", ]
library("berryFunctions")
linReg(height~age, data=treeA, pos1="topleft")
linReg(height~age, data=treeB, add=T, col=4,
       pos1="bottomright", inset=0.05)
points(height~age, data=treeB, pch=3, col=4)
```

Solution for exercise 7: Plotting, linear Regression

Solution for exercise 7.BONUS 1

```
boxplot(height~measurement, data=treesize,
        col=c("blue","orange"), notch=TRUE)
```

Solution for exercise 7.BONUS 2

```
par(mfrow=c(2,1), mar=c(3,3,1.5,0.5), mgp=c(1.9,0.7,0), las=1)
linReg(Volume~Height, data=trees, col="blue", pos1="topleft")
linReg(Volume~Girth, data=trees, col="forestgreen", pos1="topleft")
```

Outline

R course info
1. One-Session-Intro
2. Getting started: Background, GUI and first steps
   Background information
   Graphical user interfaces
   Getting help
   R syntax
   Source code of R commands
3. Objects
4. "Real" data
5. Plotting
6. Character Operations
7. Conditions & loops
8. Functions & packages
9. Distributions
10. Statistics
11. Time series handling and analysis
12. Spatial data and GIS functionality
13. Final tasks
Course plan

R - What and Why?

- R is a standard environment for statistical computing
- and an object-oriented programming language.
- It is developed and maintained by the R development core team
- and has thousands of add-on packages written by the community.
- There are mailing lists where users (& developers) help users
- and blogs to communicate analysis and coding to the public.
- R allows complex data analysis of big data sets with current methods
- and the creation of advanced professional (even interactive) graphics.
- Coding and programming forces you to keep track of your work
- and allows you to efficiently customize and automatize your analysis.
- R is very versatile: you can write your own functions and packages,
- implement new methods and make them available to everyone.
- Being capable of programming helps finding a job
- and the best part: R is open source and free!

fantasyfootballanalytics.net/2014/01/why-r-is-better-than-excel.html
thegrantlab.org/bio3d/tutorials/79-static-content/85-why-use-r

interpreter language - no compilation

xkcd.com/303

Where to get R

Instructions online: github.com/brry/course#install

- Editor alternative to Rstudio: Tinn-R
- Only for Windows OS, but flexible window arrangement
- Needs some initial tweaking, see Berry's TinnR Page
- Since Rstudio has become so incredibly awesome, you should use it!

Outline

R course info
1. One-Session-Intro
2. Getting started: Background, GUI and first steps
   - Background information
   - Graphical user interfaces
   - Getting help
   - R syntax
   - Source code of R commands
3. Objects
4. "Real" data
5. Plotting
6. Character Operations
7. Conditions & loops
8. Functions & packages
9. Distributions
10. Statistics
11. Time series handling and analysis
12. Spatial data and GIS functionality
13. Final tasks

Course plan

RStudio

RUN CODE
SCRIPTS
OBJECTS IN WORKSPACE
DOCUMENTATION
PLOTS
CODE EXECUTION

RStudio configuration

keyboard shortcuts (ALT+SHIFT+K)

Recommended settings for reproducible research under
Tools - Global Options - General
OFF: Restore .Rdata into workspace at startup
Save workspace to .RData on exit: **NEVER**

Instead use `save(object, file="object.Rdata")` *after long computations. You can load them later with* `load("object.Rdata")`.

More at github.com/brry/course#settings

Tinn R

Figure: screenshot Tinn-R

```
# enable sending of blocks up to the next blank line:
.trPaths <- paste(Sys.getenv('LOCALAPPDATA'),
'\\Temp\\Tinn-R', c('', 'search.txt', 'objects.txt',
'file.r', 'selection.r', 'block.r','lines.r'),sep='\\')
# write this in  C:/Program Files/R/R-3.2.2/etc/Rprofile.site
```

Outline

R course info
1. One-Session-Intro
2. Getting started: Background, GUI and first steps
   - Background information
   - Graphical user interfaces
   - Getting help
   - R syntax
   - Source code of R commands
3. Objects
4. "Real" data
5. Plotting
6. Character Operations
7. Conditions & loops
8. Functions & packages
9. Distributions
10. Statistics
11. Time series handling and analysis
12. Spatial data and GIS functionality
13. Final tasks

Course plan

Getting help: Inside R

R-Help

```
help("apply") # get help for the function
?apply # The same. saves typing effort.
# Press F1 while the cursor is at a command.

apropos("apply")
help.search("apply")
??apply

help.start() # html help Manuals, Material, search engine
```

Getting help: Outside R

- R-Manuals for introduction to the language
- R Wiki: rwiki.sciviews.org
- Ref Cards: base and advanced cheatsheets from Rstudio, RefCards originally by Tom Short from Stein (recommended), Baggot, Tanbakuchi, cuni or Joergensen
- rseek.org for R related internet search
- StackOverflow for programming questions <– main resource
- CrossValidated for statistical questions
- Mailing lists: ask other experienced users for help
  - R-help mailing list
  - Nabble: Forum-like view of the r-help mailing list
  - ONLY post on mailing lists when all other options are exploited and you are sure there's no answer out there. FIRST read the posting guide.

Good References, books

- Grolemund & Wickham (2017) R for Data Science
- J. Adler (2010): R in a Nutshell
- U. Ligges (2008): Programmieren mit R (German)
- M. Crawley (2007): The R-book
- H. Wickham (2014) Advanced R
- H. Wickham (2015) R Packages
- domain specific: Chapman and Hall R Series
- Many more listed at github.com/RomanTsegelskyi/rbooks
- Review list at ecotope.org, through the wayback machine

Tutorials:

- Microsoft + Datacamp (best course I know of, with login, but free)
- tryR.codeschool.com (interactive)
- STAT 545

Outline

R course info
1. One-Session-Intro
2. Getting started: Background, GUI and first steps
   - Background information
   - Graphical user interfaces
   - Getting help
   - R syntax
   - Source code of R commands
3. Objects
4. "Real" data
5. Plotting
6. Character Operations
7. Conditions & loops
8. Functions & packages
9. Distributions
10. Statistics
11. Time series handling and analysis
12. Spatial data and GIS functionality
13. Final tasks

Course plan

get started, comments

Please start R via the editor you like.

Comments start with a hash key #

```
17-42 # This is a comment, thus not executed

## [1] -25
```

Please calculate the following tasks

Exercise 8: Basic operators

1. 4 * 9
2. 2 + 4,8 (International decimal sign: ".")
3. 3^2
4. $\frac{\pi}{2}$
5. sinus of 15 °. Must be 0.26. Remember: $radians = degrees * \frac{\pi}{180\,^\circ}$
6. $\sqrt{81}$ (square root)
7. $|-12|$ (absolute value)
8. log(100) (–> should return 2, as $10^2 = 100$)
9. 5! (factorial)
10. e^3 (exponential function)
11. Bonus: How is 3.91 * 10^{-3} written in scientific notation?

Solution for exercise 8.1-8: Basic operators

```r
4*9 # this is our first calculation with a comment
2 + 4.8
3^2
pi/2
sin(15*pi/180)
?sqrt # get the offline help about the function sqrt
sqrt(81) # square root
abs(-12) # absolute value
log(100)
help(log) # natural logarithm
log10(100) # log base 10
log(100, base=10) # another way
```

Solution for exercise 8.9-11: Basic operators

```r
factorial(5)
e^3 # does not work
??exponential
exp(3) # exponential function
exp(1) # the value of e
3.91 * 10^-3
3.91e-3 # no spaces possible in scientific notation
help.start() # offline search, manuals, etc
```

Outline

R course info
1. One-Session-Intro
2. Getting started: Background, GUI and first steps
   Background information
   Graphical user interfaces
   Getting help
   R syntax
   Source code of R commands
3. Objects
4. "Real" data
5. Plotting
6. Character Operations
7. Conditions & loops
8. Functions & packages
9. Distributions
10. Statistics
11. Time series handling and analysis
12. Spatial data and GIS functionality
13. Final tasks
Course plan

Source code: github.com/wch/r-source/src/library/base (or stats, utils, ...)
CRAN packages source code: github.com/cran
HTML Documentation: www.rdocumentation.org

excellent post
ncol - .Primitive("dim") - NROW head.matrix
https://github.com/wch/r-source/blob/trunk/src/library/utils/R/head.R
https://github.com/wch/r-source/blob/trunk/src/library/base/R/matrix.R

Outline

R course info
1. One-Session-Intro
2. Getting started: Background, GUI and first steps
3. Objects
   Assignments
   Vectors, indexing
   Data.frames
   Matrices
   Lists, lapply/sapply functions
   Classes, methods, functions
4. "Real" data
5. Plotting
6. Character Operations
7. Conditions & loops
8. Functions & packages
9. Distributions
10. Statistics
11. Time series handling and analysis
12. Spatial data and GIS functionality
13. Final tasks
Course plan

Assignment: Create an object with data in the workspace I

```
a <- 15.4
```

```
a

## [1] 15.4
```

```
a > 2 # is a bigger than 2?  --> logical value (boolean)

## [1] TRUE
```

```
A # not an existing object (R is case sensitive)

## Error in eval(expr, envir, enclos):  object 'A' not found
```

Assignment: Create an object with data in the workspace II

Don't assign to existing objects or functions like `mean, c, T, data, sin`; Later on, you will hardly be able to distinguish what object (original or custom) you are referring to.
As R is Case SeNsitivE, `Data` would be OK, but it's not useful. Use object names that are short, but still meaningful.
One convention is lowerCamel:
`dailyRainBerlin` is short and readable through capital letters.

```
# Rstudio: press 'ALT' + '-'  for   " <- "
```

Don't use `=` for assignments. Most R users connotate "=" with function arguments and prefer " <- " for objects (style guide). Also, "=" is only allowed on the top level:
`median(x <- 1:10)` also creates the object in `globalenv()`, while `median(x=1:10)` does not. This is used in `NCOL`, for example.

http://blog.revolutionanalytics.com/2008/12/use-equals-or-arrow-for-assignment.html

https://csgillespie.wordpress.com/2010/11/16/assignment-operators-in-r-vs/

Outline

R course info
1. One-Session-Intro
2. Getting started: Background, GUI and first steps
3. Objects
   - Assignments
   - Vectors, indexing
   - Data.frames
   - Matrices
   - Lists, lapply/sapply functions
   - Classes, methods, functions
4. "Real" data
5. Plotting
6. Character Operations
7. Conditions & loops
8. Functions & packages
9. Distributions
10. Statistics
11. Time series handling and analysis
12. Spatial data and GIS functionality
13. Final tasks

Course plan

Vectors I

In R, Vectors are not geometric constructs, but an ordered set of values. Create a vector with c (stands for Combine or Concatenate), separating each entry with a comma:

```
b <- c(3, 7, -2.5, 11, 3.8, 9)
```

spaces make code easier to read:

```
b<-c(3,7,-2.5,11,3.8,9)
b <- c(3, 7, -2.5, 11, 3.8, 9)
```

```
print(b) # or just write   b

## [1]  3.0  7.0 -2.5 11.0  3.8  9.0
```

Vectors II: Other ways to generate vectors

```
1:5  # integer numbers  from : to

## [1] 1 2 3 4 5
```

```
rep(1:4, times=3) # repeat entries several times

##  [1] 1 2 3 4 1 2 3 4 1 2 3 4
```

```
v <- rep(1:3, each=3, times=2)
v

##  [1] 1 1 1 2 2 2 3 3 3 1 1 1 2 2 2 3 3 3
```

Vectors III: Yet other ways to generate vectors

```
seq(from=5, to=-1, by=-0.5) # Sequence
# by must be negative for descending sequences

##  [1]  5.0  4.5  4.0  3.5  3.0  2.5  2.0  1.5  1.0
## [10]  0.5  0.0 -0.5 -1.0
```

```
seq(1.32, 6.1, length.out=15) # 15 elements

##  [1] 1.320000 1.661429 2.002857 2.344286 2.685714
##  [6] 3.027143 3.368571 3.710000 4.051429 4.392857
## [11] 4.734286 5.075714 5.417143 5.758571 6.100000
```

```
seq(1.32, 6.1, len=15) # abbreviate argument names
?seq # read more about it...
```

Indexing on vectors (subsets) I: square brackets

```
b # remember b?

## [1]  3.0  7.0 -2.5 11.0  3.8  9.0

b[1] # first element

## [1] 3
```

```
b[2:4] # several elements

## [1]  7.0 -2.5 11.0

b[ c(2,5,1,6,1) ] # flexible

## [1] 7.0 3.8 3.0 9.0 3.0
```

Indexing on vectors (subsets) II

```
b

## [1]  3.0  7.0 -2.5 11.0  3.8  9.0

b[-2] # all but the second element

## [1]  3.0 -2.5 11.0  3.8  9.0
```

```
a <- seq(from=1, to=100, by=0.1)

head(a) # only first 6 elements (or rows)

## [1] 1.0 1.1 1.2 1.3 1.4 1.5
```

Indexing on vectors (subsets) III

```r
head(a)

## [1] 1.0 1.1 1.2 1.3 1.4 1.5

a[2] <- 87 # manipulate single elements of object
head(a)

## [1]  1.0 87.0  1.2  1.3  1.4  1.5
```

```r
ls() # list objects in workspace

## [1] "a" "b" "v"

rm(b) # remove an object
```

Data types

R can handle data of a variety of types: Numbers like `42.6`, characters like `"R rocks"`, complex numbers like `8+4i`, categories with `as.factor(c("blue", "green"))`, logical or boolean values `c(TRUE, FALSE)` and a few others. They should usually not be mixed. For example, you can't perform algebraic computation on characters:

```
(p9 <- "1.3")     # show assignment result
2*p9              # error, as p9 is a character
2*as.numeric(p9)  # make it a number first
p9                # p9 itself has not changed
is.numeric(p9)    # FALSE
mode(p9)          # character
```

Integer vs decimal numbers: arithmetic precision

```
6  ==  3 + 3            # TRUE
```

```
0.5 - 0.2  ==  0.3      # TRUE
```

```
0.4 - 0.1  ==  0.3      # FALSE
```

```
print(0.4-0.1 , digits=22)

## [1] 0.30000000000000004
```

```
round(0.4-0.1, digits=6)  ==  round(0.3, 6)

## [1] TRUE
```

Test for equality only with integers / with rounding (see also `signif`), or use `all.equal`. More pitfalls like this in the R inferno.

Exercise 9: Vectors and statistics

1. Repeat your favorite number 6 times using `rep`.
2. With `sequence`, generate one vector from -1 to 4 in steps of 0.5 and one with a length of 21 elements. Then add a number to the vector.
3. Assign a vector with the body heights of a few people around you to an object with a useful name.
4. Print only the 4th and 2nd element (one single vector). BONUS: All but the 2nd to 4th elements.
5. `sort` the numbers decreasingly.
6. Calculate the average size (`mean`), the variance (`var`) and the standard deviation (`sd`) of this dataset, as well as the `min`, `max`, `median` and 80% `quantile` (20% of the entries are larger than this value).
7. BONUS 1: Explain what `length` does.
8. BONUS 2: Generate the numbers from 1 to 10 in three different ways.
9. BONUS 3: Explain and relate to each other: mean, var, sd, median, quantile.

Solution for exercise 9.1-2: Vectors

```
# repeat and sequence:
rep(5, times=6)
seq(from=-1, to=4, by=0.5)
vec2 <- seq(-1, 4, length.out=21)
seq(-1, 4, len=21)
```

You can leave argument names away, if you specify their content in the right order. If it is unambiguous, you can use partial argument names.

```
# add a number to a vector:
c(vec2, 8) # does not change vec2
vec3 <- c(vec2, 8) # creates a new object
vec2 <- c(vec2, 8) # changes the object vec2
# Another way:
vec2 <- seq(-1, 4, length.out=21)
vec2[21] <- 5 # changing one element
vec2
vec2[22] # returns NA - there is no value here
vec2[26] <- 8
vec2 # is now changed
```

Solution for exercise 9.3-6: Vectors

```
# vector with body heights:
heights <- c(192, 171, 178, 175, 185, 145, 164) # cm
# print selected elements:
heights[ c(4,2) ]
# sort:
sort(heights, decreasing=T)
# statistics:
mean(heights)
var(heights) # cm^2
sd(heights) # cm
min(heights)
max(heights)
median(heights)
quantile(heights, probs=0.80)
```

Solution for exercise 9.BONUS: Vectors

```
length(heights) # number of elements in vector
# Numbers from 1 to 10:
1:10  ;  seq(1,10)  ;  c(1,2,3,4,5,6,7,8,9,10)
# mean vs median:
mean(   replace(heights, 1, 292) ) # subject to outliers
median( replace(heights, 1, 292) ) # indifferent to extrema
```

70% of values in a normal distribution lie between mean-sd and mean+sd:

Outline

R course info
1. One-Session-Intro
2. Getting started: Background, GUI and first steps
3. Objects
   - Assignments
   - Vectors, indexing
   - Data.frames
   - Matrices
   - Lists, lapply/sapply functions
   - Classes, methods, functions
4. "Real" data
5. Plotting
6. Character Operations
7. Conditions & loops
8. Functions & packages
9. Distributions
10. Statistics
11. Time series handling and analysis
12. Spatial data and GIS functionality
13. Final tasks

Course plan

data.frames

`data.frame`s are the most common form of tables in R. Each column can have a different data type (numeric, character, factor, etc), but within a column, it stays the same.
Columns as well as rows can have names (`colnames, rownames`). If these start with a number, an "X" will be prefixed. This may happen when reading data, which is usually stored as a `data.frame` in R.

```
?data.frame
```

Creating data.frames

```
df <- data.frame(col_a=11:14, ColName2=letters[1:4],
                 LogicalCol=(1:4)>2)
df

##   col_a ColName2 LogicalCol
## 1    11        a      FALSE
## 2    12        b      FALSE
## 3    13        c       TRUE
## 4    14        d       TRUE

str(df)

## 'data.frame': 4 obs. of  3 variables:
##  $ col_a     : int  11 12 13 14
##  $ ColName2  : Factor w/ 4 levels "a","b","c","d": 1 2 3 4
##  $ LogicalCol: logi  FALSE FALSE TRUE TRUE
```

Subsetting data.frames by index numbers

```
nrow(df)

## [1] 4

ncol(df) # see also dim(df)

## [1] 3
```

```
df[ 3 , 1] # 3rd row, 1st column

## [1] 13

df[   , 2] # all rows, 2nd column (as vector)

## [1] a b c d
## Levels: a b c d
```

Subsetting data.frames by names

```
df[ "LogicalCol" ] # no comma -> data.frame

##   LogicalCol
## 1      FALSE
## 2      FALSE
## 3       TRUE
## 4       TRUE
```

Bad practice, unclear whether rows or columns are indexed!

```
df[ , "LogicalCol", drop=FALSE ]  # better
```

```
df$col_a

## [1] 11 12 13 14
```

```
df[2, ] # full row

##   col_a ColName2 LogicalCol
## 2    12        b      FALSE
```

Some hints about data.frames

- If `nrow(df)` returns `NULL`, `df` might in fact be a vector.
- `NROW(df)` will show `length(df)` if `df` is a vector.
- Also, remember you can check the object with `class` and `mode`, as well as `is.vector`.
- `colnames(df)` will show the column names. (see also `rownames`)

Exercise 10: data.frames

Working with the dataset `state.x77`

1. Change the object type to a data.frame
2. What are the 3 ways to select the population column? Which one doesn't work for Life expectancy? Why not?
3. How can you subset a single column, without the result being simplified to a vector? (you want to keep it as a data.frame, but with one single column only. Hint: `?"["`)
4. How could the `$` subsetting method be dangerous when misspelling columns?
5. By which two ways can you select the Income and Illiteracy columns?
6. How can you select all the states (=rows) with an income above 5000?
7. BONUS: Why does `state.x77$Income` not work on the original dataset? (use `rm(state.x77$Income)` to remove your changed object from the workspace, if you didn't assign it to a different name.)

Solution to exercise 10: subsetting data.frames

```
state <- as.data.frame(state.x77)
state[,1] # not safe, columns could be in different position
state[ , "Population"] # safe and readable
state$Population # quicker to type, has autocomplete
# $  doesn't work (at least not without quotation marks)
   # with a space, it's an invalid column name
state[ , "Population", drop=FALSE]
state$Illeeteeraacyy # does not give an error!!!
state[ , c("Income","Illiteracy")]
state[ , 2:3]
state[state$Income>=5000, ]
# Because it is a matrix, not a data.frame
```

Outline

R course info
1. One-Session-Intro
2. Getting started: Background, GUI and first steps
3. Objects
   - Assignments
   - Vectors, indexing
   - Data.frames
   - Matrices
   - Lists, lapply/sapply functions
   - Classes, methods, functions
4. "Real" data
5. Plotting
6. Character Operations
7. Conditions & loops
8. Functions & packages
9. Distributions
10. Statistics
11. Time series handling and analysis
12. Spatial data and GIS functionality
13. Final tasks

Course plan

Creating matrices

```
matrix(data=1:6 , nrow=2, ncol=3)

##      [,1] [,2] [,3]
## [1,]    1    3    5
## [2,]    2    4    6
```

```
m <- matrix(1:6 , nrow=2, ncol=3, byrow=T)
print(m)

##      [,1] [,2] [,3]
## [1,]    1    2    3
## [2,]    4    5    6
```

Manipulating matrices, row and column names

```
colnames(m) <- c("A", "B", "C")
m[1,1] <- c(989)
print(m)

##        A B C
## [1,] 989 2 3
## [2,]   4 5 6
```

```
rownames(m) <- c("row1", "row2")
m

##        A B C
## row1 989 2 3
## row2   4 5 6
```

Matrices only have one single data type

```
m[1,1] <- "a"
m

##      A   B   C
## row1 "a" "2" "3"
## row2 "4" "5" "6"
```

Outline

R course info
1. One-Session-Intro
2. Getting started: Background, GUI and first steps
3. Objects
   - Assignments
   - Vectors, indexing
   - Data.frames
   - Matrices
   - Lists, lapply/sapply functions
   - Classes, methods, functions
4. "Real" data
5. Plotting
6. Character Operations
7. Conditions & loops
8. Functions & packages
9. Distributions
10. Statistics
11. Time series handling and analysis
12. Spatial data and GIS functionality
13. Final tasks

Course plan

Lists

Lists store every R data type (vectors, data.frames, . . .) in one variable

```
list("df"=df[c(1:2), ], matrix=m, character="TEXT")

## $df
##   col_a ColName2 LogicalCol
## 1    11        a      FALSE
## 2    12        b      FALSE
##
## $matrix
##      A   B   C
## row1 "a" "2" "3"
## row2 "4" "5" "6"
##
## $character
## [1] "TEXT"
```

List basics I

```
# create a list: an object with several 'objects' inside it
L1 <- list(first="result of function 'list'",
           second=345:287, third=rnorm(10),
           fourth=data.frame(a=6:3, b=rexp(4)),
           fifth=LETTERS, sixth=letters,
           seventh=sample(300), eigth="goodbye")
```

```
# print the whole thing:
L1
```

```
# print only the first 4 elements of the list
head(L1,4)
tail(L1) # or the last n elements (by default 6)
```

List basics II

```r
# Structure of the list
str(L1, max.level=1, vec.len=3)

## List of 8
##  $ first  : chr "result of function 'list'"
##  $ second : int [1:59] 345 344 343 342 341 340 339 338 ...
##  $ third  : num [1:10] 1.083 0.953 0.269 1.076 ...
##  $ fourth :'data.frame': 4 obs. of  2 variables:
##  $ fifth  : chr [1:26] "A" "B" "C" ...
##  $ sixth  : chr [1:26] "a" "b" "c" ...
##  $ seventh: int [1:300] 19 216 192 48 161 46 73 117 ...
##  $ eigth  : chr "goodbye"
```

List basics II

```r
# str down to each level of the list
str(L1, vec.len=3) # see the df for the difference

## List of 8
##  $ first  : chr "result of function 'list'"
##  $ second : int [1:59] 345 344 343 342 341 340 339 338 ...
##  $ third  : num [1:10] 1.083 0.953 0.269 1.076 ...
##  $ fourth :'data.frame': 4 obs. of  2 variables:
##   ..$ a: int [1:4] 6 5 4 3
##   ..$ b: num [1:4] 0.275 0.441 1.693 0.96
##  $ fifth  : chr [1:26] "A" "B" "C" ...
##  $ sixth  : chr [1:26] "a" "b" "c" ...
##  $ seventh: int [1:300] 19 216 192 48 161 46 73 117 ...
##  $ eigth  : chr "goodbye"
```

List indexing I

```
# Assessing list elements (indexing) with double square brackets:
L1[[3]]

##  [1]  1.08270524  0.95297954  0.26906649
##  [4]  1.07597085 -0.86401751  0.06248087
##  [7]  0.13752332  0.01085314  0.75895050
## [10] -1.11800498
```

```
# What's different if you use only single brackets?
L1[3]

## $third
##  [1]  1.08270524  0.95297954  0.26906649
##  [4]  1.07597085 -0.86401751  0.06248087
##  [7]  0.13752332  0.01085314  0.75895050
## [10] -1.11800498

# HINT: look at the class of the results
```

List indexing II

```
# Assesing elements by name
L1$eight # NULL if not existent, so watch out with spelling!

## NULL

L1$eigth

## [1] "goodbye"
```

```
names(L1) # as with names(VECTOR) or rownames(DATAFRAME)

## [1] "first"   "second"  "third"   "fourth"
## [5] "fifth"   "sixth"   "seventh" "eigth"

names(L1)[2] <- "second elem."
```

List indexing III

```
# Several elements of the list (the result is still a list):
L1[4:5]

## $fourth
##   a         b
## 1 6 0.2754568
## 2 5 0.4412032
## 3 4 1.6930600
## 4 3 0.9602851
##
## $fifth
##  [1] "A" "B" "C" "D" "E" "F" "G" "H" "I" "J" "K"
## [12] "L" "M" "N" "O" "P" "Q" "R" "S" "T" "U" "V"
## [23] "W" "X" "Y" "Z"
```

List indexing IV

```
# changing elements:
L1[c(3,6)]  <- c(77777777, 3333333)
head(L1)
```

L-apply

```r
typeof(L1[[1]])

## [1] "character"
```

```r
# Apply a function to each element of the list:
lapply(X=L1, FUN=typeof)
```

```
## $first
## [1] "character"
##
## $`second elem.`
## [1] "integer"
##
## $third
## [1] "double"
##
## $fourth
## [1] "list"
```

```
## $fifth
## [1] "character"
##
## $sixth
## [1] "character"
##
## $seventh
## [1] "integer"
##
## $eigth
## [1] "character"
```

S-apply I

```r
# simplify that output (if possible):
    sapply(X=L1, FUN=typeof)

##        first second elem.        third       fourth
##  "character"    "integer"     "double"       "list"
##        fifth        sixth      seventh        eigth
##  "character"  "character"    "integer"  "character"
```

```r
# simplifying not possible if FUN(L1[[1]]) and FUN(L1[[2]])
# return different results:
sapply(X=L1, FUN=head)
```

S-apply II

```r
# List with vectors:
L2 <- list(3:7, 8:4, 5:9)
L2

## [[1]]
## [1] 3 4 5 6 7
##
## [[2]]
## [1] 8 7 6 5 4
##
## [[3]]
## [1] 5 6 7 8 9
```

```r
sapply(L2, I)

##      [,1] [,2] [,3]
## [1,]    3    8    5
## [2,]    4    7    6
## [3,]    5    6    7
## [4,]    6    5    8
## [5,]    7    4    9
```

`I` basically returns the input as is. This is useful for `tapply` results!

S-apply III

```
# That doesn't work for vectors of different lengths:
L3 <- list(AB=c(6,9,2,6), BC=1:8, CD=c(-3,2) )
sapply(L3, I)

## $AB
## [1] 6 9 2 6
##
## $BC
## [1] 1 2 3 4 5 6 7 8
##
## $CD
## [1] -3  2
```

S-apply IV

```r
# the solution: berryFunctions::l2df
# list to data.frame conversion
if(!require(berryFunctions)) install.packages("berryFunctions")
library(berryFunctions)

l2df(L3)

##    V1 V2 V3 V4 V5 V6 V7 V8
## AB  6  9  2  6 NA NA NA NA
## BC  1  2  3  4  5  6  7  8
## CD -3  2 NA NA NA NA NA NA

# vectors are padded with NAs, names are kept
```

S-apply V

```
L3

## $AB
## [1] 6 9 2 6
##
## $BC
## [1] 1 2 3 4 5 6 7 8
##
## $CD
## [1] -3  2

# nested subsetting: get the third element of each vector:
sapply(L3, "[", 3)

## AB BC CD
##  2  3 NA
```

apply functions to vectors & further arguments

```
sample(x=1:100, size=5)

## [1] 49 39 35 98 74
```

```
lapply(c(6,2,13), sample, x=1:100)

## [[1]]
## [1] 10 35 87 80 88 39
##
## [[2]]
## [1] 76 98
##
## [[3]]
##  [1] 16 80 73  9 90  8 64 74 99 45 53 71 77
```

Practice matrices and lists

Exercise 11: matrix, list

1. Create a matrix with some numbers you like, with a useful amount of rows and columns.
2. Create a list (with meaningful element names!) that contains the previous matrix, your name, the current `Sys.time()`, the number of this exercise, and the haircolors of at least two of your neighbours.
3. BONUS 1: Using `sapply`, get the `length` for each element. What is surprising about he result?
4. BONUS 2: Make the haircolors element a `factor`. Inspect the result with `str`.

matrix + list: solutions

```
mat <- matrix(c(42,007,123,7777,-17,88), ncol=2)
mylist <- list(matrix=mat, creator="Berry",
     created=Sys.time(), exerciseNumber=11,
     haircolor=c("brunette", "red", "blonde", "blonde")  )
sapply(mylist, length) # matrix length is 6 (=ncol*nrow)
mylist$haircolor <- as.factor(mylist$haircolor)
str(mylist)
```

Outline

R course info
1. One-Session-Intro
2. Getting started: Background, GUI and first steps
3. Objects
   - Assignments
   - Vectors, indexing
   - Data.frames
   - Matrices
   - Lists, lapply/sapply functions
   - Classes, methods, functions
4. "Real" data
5. Plotting
6. Character Operations
7. Conditions & loops
8. Functions & packages
9. Distributions
10. Statistics
11. Time series handling and analysis
12. Spatial data and GIS functionality
13. Final tasks

Course plan

Determine the class of an object

Everything is an object that belongs to an existing class!!

```
class(v)

## [1] "integer"

class(df)

## [1] "data.frame"

class(m)

## [1] "matrix"
```

Usage of class in functions

```
x <- 10
class(x) <- c("a", "b")
# error:
if( class(x) == "b"   ) message("class of x contains b")

## Warning in if (class(x) == "b") message("class of x
contains b"):  the condition has length > 1 and only the
first element will be used

# use this instead
if( inherits(x, "b")  ) message("good coding!")

## good coding!
```

Examining objects

Every object class has attributes and methods:

```
str(v)

##  int [1:18] 1 1 1 2 2 2 3 3 3 1 ...

str(df)

## 'data.frame': 4 obs. of  3 variables:
##  $ col_a     : int  11 12 13 14
##  $ ColName2  : Factor w/ 4 levels "a","b","c","d": 1 2 3 4
##  $ LogicalCol: logi  FALSE FALSE TRUE TRUE

str(m)

##  chr [1:2, 1:3] "a" "4" "2" "5" "3" ...
##  - attr(*, "dimnames")=List of 2
##   ..$ : chr [1:2] "row1" "row2"
##   ..$ : chr [1:3] "A" "B" "C"
```

Overview of some useful functions

```
length(v)

## [1] 18

names(df)

## [1] "col_a"       "ColName2"   "LogicalCol"

dim(m)

## [1] 2 3

which(v > 4)

## integer(0)
```

Please note ...

Parentheses and square brackets of functions and objects

objects are variables and contain your data. The indexing (accessing of items) is done by brackets `[ ]`

functions are methods (built-in or self-made) and they perform an analysis or start a process. When functions are called, you have to use parentheses `( )`, in which the arguments are put.

With `newtable <- edit(oldtable)`, you can change cells in a table by hand. As this is not reproducible, this is bad practice!. `fix` is even worse, as it changes the object itself.
With `View`, you can look at a table in an external viewer. This is useful for large tables, as the console is not cluttered with data.

Overview: data types

In order of coercion (if mixed, TRUE is converted to 1, 3.14 to "3.14" etc)

Description	example	`typeof`	`class`
empty set	NULL	NULL	NULL
not available	NA	logical	logical
logical	c(T, F, FALSE, TRUE)	logical	logical
category	factor("left")	integer	**factor**
integer number	4:6	integer	integer
decimal	8.7	double	**numeric**
complex	5+3i	complex	complex
character string	"homer rocks"	character	character
time	Sys.time()	double	**POSIXct**
date	as.Date("2017-05-02")	double	**Date**
function	ncol	closure	**function**

adv-r.had.co.nz/Data-structures. `as.character(3.14)` converts a data type; `is.integer(4:6)` checks. `str` shows an abbreviation of `class`. `mode` (for users) is like `typeof` (R internal), but combines integer and double to numeric (& closure, special and builtin to function). Other rare typeofs: raw, environment, promise, ... When mixing date/time with others, the order of appearance determines the output class.

Overview: Object types

Object	example	`typeof`	`class`
vector	*see data types*	...	...
matrix	matrix(9:15, ncol=2)	...	matrix
array	array(letters[1:24], dim=c(2,6,4))	...	array
data.frame	data.frame(C1=4:5, C2=c("a","b"))	list	data.frame
list	list(el1=7:15, el2="big")	list	list
function	function(x) 12+0.5*x	closure	function
...	lm(b ∼ a)	list	lm

A `matrix` consists of only one data type. If you accidentally change one element to a character, all are converted and calculations are not possible any more (See coercion order in previous slide).

`data.frame`s can have multiple data types, but a column in itself also has only one type.

`list`s can combine anything, even other lists.

`is.atomic(Object)` returns TRUE (vector, matrix, array) or FALSE

`as.matrix(Object)` converts the class of an object by force.

Outline

R course info
1. One-Session-Intro
2. Getting started: Background, GUI and first steps
3. Objects
4. "Real" data
   Reading and writing data
   Factors, tapply function
   Merging data.frames
   Management of NAs, apply function
   Reproducible coding
5. Plotting
6. Character Operations
7. Conditions & loops
8. Functions & packages
9. Distributions
10. Statistics
11. Time series handling and analysis
12. Spatial data and GIS functionality
13. Final tasks
Course plan

Data I/O functions (Input / Output)

R **reads and writes** data formats like ASCII files, GEOTIFF, GRIB, NETCDF, HDF ...

```
read.csv("relative/path/to/input/file.csv")
# Combined with a variable assignment:
mydata <- read.table("C:/path/to/input/file.txt")
write.table(x=mynewdata, file="output.txt")
```

Windows users: change all \ to \\ or /

Relative file names (minimal changing of working directory):

```
setwd("C:/Users/berry/Desktop") # set working directory
dir() # show files in current folder
mydata <- read.table("filename.txt", header=TRUE, sep="\t")
# use a better object name!
```

Folder management

```r
setwd("..") # sets working directory path up one level
getwd() # shows the current wd path
dir(recursive=TRUE) # also list items in subfolders
dir("../other_subfolder") # list files in different folder
file.create() # some file operations
file.rename()
file.remove() # see also unlink()
file.copy()
dir.create() # some folder (directory) operations
file.exists()
dir.exists()
```

Some of the arguments for read.table

header = TRUE	read first line as column names
dec = ","	comma as decimal mark
sep = "_"	underscore as column separator ("\t" for tabstop)
fill = T	fill incomplete rows with NAs at the end
skip = 12	ignore the first 12 lines (eg with meta data)
comment.char = "%"	omit (rest of) lines that start with % (like R's #)
na.strings = c(-999, "NN")	identify NA entries (missing values)
stringsAsFactors=FALSE	do not convert characters to factors
as.is=TRUE	the same, but less typing, and potentially columnwise

Alternatives to read.table:

scan	At the core of read.table - for complicated things
read.csv	comma separated values (different defaults than read.table)
read.fwf	fixed width formatted data
read_excel	Excel files (install package, see github.com/hadley/readxl)

Practice reading tables and subsetting data.frames

Exercise 12: data.frames - working with tables

1. Read the file animals.txt *(rightclick **Raw**, save as)* with the correct settings for each needed argument and assign it to an object.
2. Check whether everything is read correctly with `str`.
3. Print only the first column (BONUS: in 3 different ways of subsetting).
4. `which` element of this vector is equal to (==) "Sparrow"?
5. Can the elephant fly? Find out with a logical query.
6. Find out how many legs the mammals have on average. Interpret the result.
7. BONUS 1: Use `tapply` to find the average cuteness score for each animal class.
8. BONUS 2: Read the file "days.txt" in a way that days, months, and years each have their own column. What other function besides `read.table` might be useful for that?

Solution for exercise 12.1-2: data.frames

```
# set working directory to path with files:
setwd("C:/Dokumente und Einstellungen/hydro/Desktop")
# which files are there:
dir()
# step by step, specify the arguments of read.table...
animals <- read.table("data/animals.txt", sep="\t",
                      header=TRUE, dec=",")
animals
str(animals) # ... until all numbers are num.
```

Solution for exercise 12.3-5: data.frames

```
# first column, and which is Sparrow:
animals$Name
animals[ ,"Name"] # more typing
animals[ ,1] # hard to interpret later on
animals$Name == "Sparrow"
which( animals$Name == "Sparrow" )

# Can the elephant fly? Automatic query:
animals[4,3]
animals[ animals$Name == "Elephant" , 3 ]
animals[ animals$Name == "Elephant" , "can.fly" ]
animals[ animals$Name == "Sparrow"  , "can.fly" ]
```

Solution for exercise 12.6-7: data.frames

```r
# How many legs do the mammals have on average?
animals[ animals$Class == "Mammal" , "n.legs" ]
mean( animals[ animals$Class == "Mammal" , "n.legs" ] )
# How cute are they, on average?
mean( animals[ animals$Class == "Mammal" , "cuteness" ] )

# How cute is each category of animals?
tapply(X=animals$cuteness, INDEX=animals$Class, FUN=mean)
# separates cuteness into groups, categorized by Class,
# then calculates mean for each group
```

Solution for exercise 12.8: data.frames

```r
# Read "days.txt" with columns for days, months and years
dir()
days <- read.table("days.txt", sep=".")
head(days)
str(days)

# custom names of columns
colnames(days) <- c("day", "month", "year")
head(days)

# other way:
read.fwf("data/days.txt", widths=c(2,1,2,1,4))

# usage example: return months for e.g. vegetation index:
days$month
```

Frequent mistakes with `read.table`

Error in scan(file, what, nmax, sep, dec, quote, skip, nlines, na.strings, : line _ did not have _ elements	usually `header`, `sep` or `fill` is given incorrectly.
Warning message: In read.table("_.txt", _) : incomplete final line found by readTableHeader on 'C:_.txt'	Open the file and at the end, add a line break (with ENTER) = line feed = newline = carriage return.
`str(DataframeIreadIn)` yields "factor" in some numeric columns	Check data file! `dec` may need to be corrected

```
as.numeric( as.character(df$col) )
as.numeric( gsub(pattern=",", replacement=".", x=df$col) )
# If you try to read data in the format "3,590.18", run
df$col <- as.numeric(gsub(",", "", df$col))
```

Note: errors stop function execution, warnings can influence function performance and should only be ignored if you know what they really mean.

Outline

R course info
1. One-Session-Intro
2. Getting started: Background, GUI and first steps
3. Objects
4. "Real" data
   - Reading and writing data
   - Factors, tapply function
   - Merging data.frames
   - Management of NAs, apply function
   - Reproducible coding
5. Plotting
6. Character Operations
7. Conditions & loops
8. Functions & packages
9. Distributions
10. Statistics
11. Time series handling and analysis
12. Spatial data and GIS functionality
13. Final tasks

Course plan

Factors = categorical variables

```
iris$Species[63] # how factors are printed

## [1] versicolor
## Levels: setosa versicolor virginica

class(iris$Species)

## [1] "factor"

levels(iris$Species)

## [1] "setosa"     "versicolor" "virginica"

# R saves factors as numbers internally
as.numeric(iris$Species)[c(1,63,105)]

## [1] 1 2 3
```

factors, explained with animals.txt: the danger

```
ac <- read.table(file="data/animals.txt", sep="\t", header=T)$cuteness
ac # R calls  print.factor ,  see methods(print)

## [1] 1,3 6,5 9,8 6,3 5,8 4,5
## Levels: 1,3 4,5 5,8 6,3 6,5 9,8
```

```
class(ac); typeof(ac)

## [1] "factor"
## [1] "integer"
```

```
as.numeric(ac) # don't ever do this!!

## [1] 1 5 6 4 3 2
```

```
char <- as.character(ac)
as.numeric(sub(",",".", char))

## [1] 1.3 6.5 9.8 6.3 5.8 4.5
```

factors, explained with animals.txt: the solution

```
df <- read.table(file="data/animals.txt", sep="\t", header=T, as.is=TRUE)
str(df)

## 'data.frame': 6 obs. of  6 variables:
##  $ Name    : chr  "Frog" "Merl" "Doe" "Elephant" ...
##  $ Class   : chr  "Amphibian" "Bird" "Mammal" "Mammal" ...
##  $ can.fly : logi  FALSE TRUE FALSE FALSE TRUE FALSE
##  $ color   : chr  "green" "black" "brown" "gray" ...
##  $ n.legs  : int  4 2 4 4 4 2
##  $ cuteness: chr  "1,3" "6,5" "9,8" "6,3" ...
```

Now Name and cuteness are character strings instead of factors. `as.is=TRUE` is a special case of `stringsAsFactors=FALSE`: with the first you can specify the latter per column (I use it because I can type it more quickly).

factors are very useful to apply a function per group

```
str(PlantGrowth)

## 'data.frame': 30 obs. of  2 variables:
##  $ weight: num  4.17 5.58 5.18 6.11 4.5 4.61 5.17 4.53 5.33 5.14 ...
##  $ group : Factor w/ 3 levels "ctrl","trt1",..: 1 1 1 1 1 1 1 1 1 1 ...
```

```
tapply(X=PlantGrowth$weight, INDEX=PlantGrowth$group, FUN=mean)

##  ctrl  trt1  trt2
## 5.032 4.661 5.526
```

This part of Hadley's book is a good intro to factors.

factors are also useful for plotting specifics

col can be a factor vector, integers correspond to `palette()`

```
plot(rate~conc, data=Puromycin, col=state, pch=16, las=1)
legend("bottomright", levels(Puromycin$state), col=1:2, pch=16)
```

practice working with categories

Exercise 13: Factors, tapply

1. Plot the Puromycin dataset, but use the 3rd and 4th color of the default `palette()`
2. BONUS 1: Use custom colors.
   Hint: create a vector with the colors, then index from it.
3. BONUS 2: In the `iris` dataset, add a row for the *Iris sintenisii*.
   Hint: add a level to the factor first.
4. Using `tapply`, find out what you should feed chickens according to the measurements in `chickwts`.

Solution for exercise 13: factors, tapply

```
plot(rate~conc, data=Puromycin, col=as.integer(state)+2, pch=16)

mycol <- c("orange", "mediumpurple2")
plot(rate~conc, data=Puromycin, col=mycol[state], pch=16)

levels(iris$Species) <- c(levels(iris$Species), "sintensii" )
iris[151, ] <- c(6,3,5,2,"sintensii")
```

```
sort(tapply(chickwts$weight, chickwts$feed, median))

## horsebean   linseed   soybean  meatmeal sunflower    casein
##     151.5     221.0     248.0     263.0     328.0     342.0

sort(tapply(chickwts$weight, chickwts$feed, min))

## horsebean   linseed  meatmeal   soybean    casein sunflower
##       108       141       153       158       216       226
```

Outline

R course info
1. One-Session-Intro
2. Getting started: Background, GUI and first steps
3. Objects
4. "Real" data
   - Reading and writing data
   - Factors, tapply function
   - Merging data.frames
   - Management of NAs, apply function
   - Reproducible coding
5. Plotting
6. Character Operations
7. Conditions & loops
8. Functions & packages
9. Distributions
10. Statistics
11. Time series handling and analysis
12. Spatial data and GIS functionality
13. Final tasks

Course plan

Merge (join) tables

If you haven't already, now is a good time to download (and unzip!) all datasets.

Exercise 14: Merge

1. Read the files mergeApples1.txt *(rightclick **Raw**, save as)* and mergeApples2.txt into separate data.frames.
2. Use `rbind` to combine both tables line-wise and assign the output to e.g. `apples`.
3. Read mergeAge.txt into e.g. `age`.
4. Describe what `merge(age, apples, by.x="Name", by.y="Person")` does.
5. What happens if you set `all` or `all.x` = TRUE?
6. BONUS 1: What is the difference between `cbind` and `rbind`?
7. BONUS 2: Why does `cbind` not work with age and apples?

Solution for exercise 14: Merge

```
ma1 <- read.table("data/mergeApples1.txt", header=T)
ma2 <- read.table("data/mergeApples2.txt", header=T)
apples <- rbind(ma1, ma2)
apples
age <- read.table("data/mergeAge.txt", header=T)

merge(age, apples, by.x="Name", by.y="Person")
# combine the information from both datasets
# for names that occur in both tables

merge(age, apples, by.x="Name", by.y="Person", all=T)
# Keep all entries, pad with NAs

# rbind: combine rows below each other
# cbind: bind columns beside each other
# dimensions and names must be correct
```

Outline

R course info
1. One-Session-Intro
2. Getting started: Background, GUI and first steps
3. Objects
4. "Real" data
   - Reading and writing data
   - Factors, tapply function
   - Merging data.frames
   - Management of NAs, apply function
   - Reproducible coding
5. Plotting
6. Character Operations
7. Conditions & loops
8. Functions & packages
9. Distributions
10. Statistics
11. Time series handling and analysis
12. Spatial data and GIS functionality
13. Final tasks

Course plan

NA-values (NA=not available)

Creating a table with **NA** values

```
# create some test data. "c" around ":" is not necessary
df <- data.frame(x= c(1:10), y=11:20 )
df[3,2] <- NA
head(df)

##   x  y
## 1 1 11
## 2 2 12
## 3 3 NA
## 4 4 14
## 5 5 15
## 6 6 16
```

NA-values

Handling of **NA** values

```
plot(df$x, df$y, pch=19, col="red")
```

NA-values

Checking for **NA** values

```r
is.na(df)
```

```
##            x     y
##  [1,] FALSE FALSE
##  [2,] FALSE FALSE
##  [3,] FALSE  TRUE
##  [4,] FALSE FALSE
##  [5,] FALSE FALSE
##  [6,] FALSE FALSE
##  [7,] FALSE FALSE
##  [8,] FALSE FALSE
##  [9,] FALSE FALSE
## [10,] FALSE FALSE
```

```r
na.omit(df)
```

```
##     x  y
## 1   1 11
## 2   2 12
## 4   4 14
## 5   5 15
## 6   6 16
## 7   7 17
## 8   8 18
## 9   9 19
## 10 10 20
```

NA-values

```
##     x  y
## 1   1 11
## 2   2 12
## 3   3 NA
## 4   4 14
## 5   5 15
## 6   6 16
## 7   7 17
## 8   8 18
## 9   9 19
## 10 10 20
```

```r
mean(df$x) ; mean(df$y)
```

```
## [1] 5.5
## [1] NA
```

```r
mean(df$y, na.rm=TRUE) # dangerous with sums
```

```
## [1] 15.77778
```

apply: execute a function on each row (col) of a matrix

```
# Compute the column- and row sums of a data.frame (df)
apply(X=df, MARGIN=2, FUN=sum) # column wise

##  x  y
## 55 NA
```

```
apply(df, 1, sum) # line by line

##  [1] 12 14 NA 18 20 22 24 26 28 30
```

```
apply(df, 2, sum, na.rm=TRUE) # with further arguments

##   x   y
##  55 142
```

Exercise 15: apply

Compute the median of each column in the dataset `iris`.
Hint: leave out the non-numeric column.

apply practice solution

```
apply(iris[ ,-5], MARGIN=2, median)

## Sepal.Length  Sepal.Width Petal.Length  Petal.Width
##         5.80         3.00         4.35         1.30
```

```
apply(iris[ ,-5], MARGIN=2, mean)

## Sepal.Length  Sepal.Width Petal.Length  Petal.Width
##     5.843333     3.057333     3.758000     1.199333
```

Outline

R course info
1. One-Session-Intro
2. Getting started: Background, GUI and first steps
3. Objects
4. "Real" data
   - Reading and writing data
   - Factors, tapply function
   - Merging data.frames
   - Management of NAs, apply function
   - Reproducible coding
5. Plotting
6. Character Operations
7. Conditions & loops
8. Functions & packages
9. Distributions
10. Statistics
11. Time series handling and analysis
12. Spatial data and GIS functionality
13. Final tasks

Course plan

Working with Scripts

For any real data analysis, you should work with scripts that save your code.
For that reason, you don't have to save your workspace when you close R.
If you save it, you don't know where it is stored by default.
In the next R session, all objects will be available again, which is convenient, but dangerous, as it reduces reproducibility.
Scripts can easily be exchanged with research partners, clients or employers.
They may also develop into packages...
Before sending, close R, open a clean (!) session, and check whether everything is running.
Scripts should have lots of comments! `# seriously.`

Creating documents, Organizing your files

Rstudio - file - new -
- R HTML (no LaTeXrequired on system)
- R markdown (easy to learn, creates .pdf or .docx)
- R sweave (very powerful through LaTeX. This is what I use for these slides.)

I use knitr, as it is more advanced than the default sweave. For that, set:
Rstudio - tools - global options - Sweave - weave using: knitr
Save as .Rnw file. See the knitr demo files: yihui.name/knitr/demo

There are tips online on how to organize data, scripts, plots etc.
stackoverflow: How to organize large R programs
stackexchange: How to efficiently manage a statistical analysis project?
Here are some tips by Hadley: http://r-pkgs.had.co.nz/style.html

Real Datasets online

- NOAA (USA) weather data: www1.ncdc.noaa.gov/pub/data/normals
- DWD Climate Data Center: CDC/observations_germany/climate

```
library(rdwd) # github.com/brry/rdwd
clim <- dataDWD(selectDWD(id=02080, res="daily", var="kl",
                          time="hist"), dir=tempdir())
```

- data.unicef.org (potentially add .xls etc as file extension)
- https://github.com/okulbilisim/awesome-datascience#data-sets
- https://github.com/caesar0301/awesome-public-datasets
- http://ropensci.org/packages/index.html
- http://dataviz.tools/category/data-sources/

Exercise 16: Real Data

Download a dataset that interests you, read it into R and do some analyzing / plotting.

Outline

R course info
1. One-Session-Intro
2. Getting started: Background, GUI and first steps
3. Objects
4. "Real" data
5. Plotting
   Syntax, adjustments, labeling
   Lines
   Limits, adding to graphics
   saving plots, multiple figures
6. Character Operations
7. Conditions & loops
8. Functions & packages
9. Distributions
10. Statistics
11. Time series handling and analysis
12. Spatial data and GIS functionality
13. Final tasks
Course plan

Plot I: the dataset

```
head(beaver2, 4)

##   day time  temp activ
## 1 307  930 36.58     0
## 2 307  940 36.73     0
## 3 307  950 36.93     0
## 4 307 1000 37.15     0

str(beaver2)

## 'data.frame': 100 obs. of  4 variables:
##  $ day  : num  307 307 307 307 307 307 307 307 307 307 ...
##  $ time : num  930 940 950 1000 1010 1020 1030 1040 1050 1100 ...
##  $ temp : num  36.6 36.7 36.9 37.1 37.2 ...
##  $ activ: num  0 0 0 0 0 0 0 0 0 0 ...
```

Plot II

```r
# The basic syntax is plot(x, y, adjustments)
plot(beaver2$time, beaver2$temp)
#
```

Plot III

```
plot(beaver2$time, beaver2$temp, ylab="Body temperature  [ \U00B0 C]",
     main="Beavers get warm late in the evening",
     xlab="Observation time [0330 for 3:30AM]", col="red")
```

Plot IV

```
plot(beaver2$time, beaver2$temp, pch=2, cex=2.8, las=1)
# pch: PointCHaracter, cex: CharacterEXpansion
# las: LabelAxisStyle (numbers upright)
```

Overview of Point CHaracters (more in bF Anhang)

plot (x, y, pch = _)

Outline

R course info
1. One-Session-Intro
2. Getting started: Background, GUI and first steps
3. Objects
4. "Real" data
5. Plotting
   Syntax, adjustments, labeling
   Lines
   Limits, adding to graphics
   saving plots, multiple figures
6. Character Operations
7. Conditions & loops
8. Functions & packages
9. Distributions
10. Statistics
11. Time series handling and analysis
12. Spatial data and GIS functionality
13. Final tasks
Course plan

Plot with lines I

```
k <- c(3,0,-10,8,6,3)   ; l <- c(-4,2,-6,-12,7,-3)
plot(k)  # standard (default) type: "p" for points
```

Plot with lines II

```r
plot(k, type="l")
# type="l" for lines
```

Plot with lines III

```
plot(k, type="b", lwd=4)
# type="b" for both points and lines. # lwd: line width
```

Plot with lines IV

```
plot(k, type="o", lty=2)
# type="o" for both overplotted. # lty: line type
```

Overview of types (more in bF Anhang)

plot (x, y, type = _)

Overview of line types (more in bF Anhang)

plot (x, y, lty = _)

Outline

R course info
1. One-Session-Intro
2. Getting started: Background, GUI and first steps
3. Objects
4. "Real" data
5. Plotting
   Syntax, adjustments, labeling
   Lines
   Limits, adding to graphics
   saving plots, multiple figures
6. Character Operations
7. Conditions & loops
8. Functions & packages
9. Distributions
10. Statistics
11. Time series handling and analysis
12. Spatial data and GIS functionality
13. Final tasks
Course plan

One data.frame instead of two vectors

Default method if x is a data.frame:

```
plot( beaver2[ ,2:3] )
```

Plot limits I

xlim with a two-value vector with lower and upper limit.

```
plot(beaver2[ ,2:3], xlim=c(-1000,3000),  ylim=c(36,40))
```

Plot limits II

xaxis decreasing (can be very misleading!):

```
plot(beaver2[ ,2:3], xlim=c(3000,-1000), ylim=c(36,40))
```

Adding datapoints

```
plot(beaver2[ ,2:3])
points(100, 37.5, pch=21, bg=5, cex=4, col=2, lwd=3)
lines(x=c(5,120,514,918), y=c(37,39,38,37.5), col=3, type="b")
```

Now it's your turn...

Exercise 17: Plotting

1. Plot a dataset of your choice (eg from `library(help = "datasets")`).
2. Add some red dotted lines between big quadratic points, filled with blue color.
3. Label the axis and give your graph a big italic header with `cex.main`, `font.main`, see `?par`.
4. Plot with a logarithmic scale on one axis.
5. Set the axis to a certain limit. With `yaxs`, suppress the default 4% range extension.
6. Using `xaxt`, plot without an x-axis. Look in the help of `par` how this can be done. Then add a custom `axis`.
7. Add a `legend` to the plot and thick-lined `box` around the final plot.

Solution for exercise 17: Plotting I

```
# generate "random" data:
set.seed(42) ; numbers <- cumsum(rnorm(40)) + 20
x <- c(10, 15, 31, 33); y <- c(19, 22, 17, 23)
# Basic plot:
plot(numbers, type="l", xlab="Time",
     main="Fake Time Series", cex.main=3, font.main=3,
     log="y", xlim=c(0,50), xaxs="i", xaxt="n" )
# Add points and lines
points(x=x, y=y, pch=22, type="p", cex=3, col="orange",
      bg="green")
lines(x=c(10, 15, 31, 33), y=c(-6, -3, -8, -2)+25, col=2,
      lty="dashed")
# Custom axis, legend and box around plot:
axis(side=1, at=c(0, 15, 30, 45)  )
legend("topright", legend=c("ts", "more fake stuff"),
       lty=c(1,2), col=c(1,2) )
box(lwd=5)
```

Solution for exercise 17: Plotting II

Outline

R course info
1. One-Session-Intro
2. Getting started: Background, GUI and first steps
3. Objects
4. "Real" data
5. Plotting
   Syntax, adjustments, labeling
   Lines
   Limits, adding to graphics
   saving plots, multiple figures
6. Character Operations
7. Conditions & loops
8. Functions & packages
9. Distributions
10. Statistics
11. Time series handling and analysis
12. Spatial data and GIS functionality
13. Final tasks
Course plan

Saving plots to a file

In the menu of the graphics window, you can save the current plot by hand. For reproducible sizes and if you're creating many plots, use

```
png("FileName.png", width=12, height=9, units="in",
           res=300, bg="transparent", pointsize=14)
  plot(1:20)
  title(main="Plot title")
  points(5,9)
dev.off() # to close the external device
```

The functions `pdf`, `jpeg`, etc. are also available.

multiple figure layout I

```
# 3 rows, 2 columns:
par(mfrow=c(3,2), mar=c(3,3,1,1), mgp=c(1.9, 0.7, 0), las=1)
plot(stackloss[ ,1:2]) # 6 plot commands
```

multiple figure layout II

```
lay <- layout(matrix(c(1,1,2,2,
                       5,5,2,2,
                       3,3,4,4,
                       3,3,4,4), ncol=4, byrow=TRUE),
              widths=c(6,6,4,4))
layout.show(lay)
```

multiple figure layout III

From the example in `?layout`:

Box

Y−Axis
0.8
0.6
0.4
0.2
0.0
1
2
3
4
5
6
box(_)
1.4
1.0
0.6
'plot'
'figure', after par(mfrow) or layout()
'inner'
'outer', if outer margins were set by par(oma)

Enough talk, action...

Exercise 18: Export (multipanel) plots

1. Read Zugspitze.txt *(rightclick **Raw**, save as)* with monthly weather records
2. With `par(mfrow=...)`, set up a figure with two panels (left and right)
3. Plot a histogram of the LUFTTEMPERATUR records in the left panel
4. Plot a line graph of the first 50 months in the right panel
5. Now export this graph as png with useful size and resolution
6. BONUS 1: also export as a vector graph (e.g. PDF, EPS, SVG, svglite package)
7. BONUS 2: Set smaller margins (`mar`) around each panel
8. BONUS 3: Set an outer margin (`oma`) with an outer `title` for the entire figure

Solution for exercise 18: Export (multipanel) plots I

```
wzug <- read.table("data/Zugspitze.txt", header=TRUE)

pdf("fig/zugspitze.pdf", height=4)
par(mfrow=c(1,2), mar=c(3,3,1,1), oma=c(0,0,2,0), las=1)
hist(wzug$LUFTTEMPERATUR, col="coral", breaks=25,
     main="Histogram monthly values")
plot(wzug$LUFTTEMPERATUR[1:50], type="l", lwd=2,
     col="darkorchid", main="First 50 months")
title(main="Temperature Zugspitze 1900:2015", outer=TRUE)
dev.off()

## pdf
##   2
```

Solution for exercise 18: Export (multipanel) plots II

Graphing paths: NA lines between entry groups

```
library("berryFunctions") # >= 1.9.2 (2015-10-22) for insertRows, colPoints
tfile <- system.file("extdata/rivers.txt", package="berryFunctions")
rivers <- read.table(tfile, header=TRUE, dec=",")
colPoints(x,y,n, data=rivers, add=FALSE, lines=TRUE, lwd=3,
          legargs=c(y1=0.8,y2=1, density=FALSE) )
```

Base R vs ggplot2

This has all been graphing with the possibilities of base R.
There is also the package `ggplot2` which a lot of people love to use.
I get everything done with base R and don't see a need to learn ggplot grammar.
You can do whatever you want - it's both R, both have their advantages.
A very good place to start learning ggplot2 is:
http://minimaxir.com/2017/08/ggplot2-web/
To compare both paradigms, see:
http://flowingdata.com/2016/03/22/comparing-ggplot2-and-r-base-graphics/
Be sure to follow the links in the beginning of the article...

Outline

R course info
1. One-Session-Intro
2. Getting started: Background, GUI and first steps
3. Objects
4. "Real" data
5. Plotting
6. Character Operations
   Character strings: Intro
7. Conditions & loops
8. Functions & packages
9. Distributions
10. Statistics
11. Time series handling and analysis
12. Spatial data and GIS functionality
13. Final tasks
Course plan

Character strings I

```r
paste("NiceThing", 3:5) # Creates vector of Mode character

## [1] "NiceThing 3" "NiceThing 4" "NiceThing 5"

paste(2, "hot", 4, "U", sep="_")

## [1] "2_hot_4_U"

letvec <- c("some different", "let", "ters")
letvec

## [1] "some different" "let"
## [3] "ters"
```

Character strings II

```
length(letvec)

## [1] 3

nchar(letvec)

## [1] 14  3  4

paste("nice", letvec, sep="_")

## [1] "nice_some different" "nice_let"
## [3] "nice_ters"
```

Character strings III

```
paste(letvec, sep="")

## [1] "some different" "let"
## [3] "ters"

paste(letvec, collapse="")

## [1] "some differentletters"

# remove spaces: substitute " " in letvec with ""
sub(" ", "", letvec)

## [1] "somedifferent" "let"
## [3] "ters"
```

Character strings IV

```
substr("Monster Party", start=2, stop=5)

## [1] "onst"

# If you need several string segments:
substring("Monster Party", first=c(1,3,5), last=c(2,5,9) )

## [1] "Mo"    "nst"   "ter P"

strsplit("Die Aerzte - Monster Party", split=" - ")[[1]]

## [1] "Die Aerzte"    "Monster Party"
```

Backslash "\" : Escape Character

"\n" for return or line break (newline), eg in graphictitles and -texts
"\t" for Tabstop, e.g. for `write.table("path/file.txt", yourdata, sep="\t")`
"\\" for Backslash as symbol in `title, text, legend` etc.
"\"" for " as character
"\U" for Unicode, e.g.:

```
plot(1)
# average symbol without using "expression":
mtext(paste("\U00D8", 5.4, "\U00B0 C"), col=2)
```

Time to practice...

Exercise 19: character string operations

In the German chocolate industry, we love

```
schoko <- c("Ritter Sport", "Lindor", "Frigor", "Milka", "Frey",
"More Lindor")
```

1. which element **is** or **contains** "Lindor"?
   Find out with `match`, `grep`, `%in%` and `grepl`. What are the differences between those?
2. Replace "or" with "nicor" using `sub` and `gsub`.
3. What's the problem with `"Ritter sport" %in% schoko`?
4. What does `"Ritter [s,S]port" %in% schoko` do?

Solution for exercise 19.1: Character strings

```r
schoko <- c("Lindor", "Ritter Sport", "Frigor", "Milka",
            "Frey", "More Lindor")
# Which element in schoko IS Lindor
match("Lindor", schoko)
match(schoko, "Lindor")
match(schoko, c("Lindor", "Frigor") )

# Which element in schoko CONTAINS Lindor
grep("Lindor", schoko)
grep("or", schoko)
grepl("Lindor", schoko) # logical value

# Is one of the elements of schoko == "Lindor" at all?
"Lindor" %in% schoko
any(  grepl("Lindor", schoko)  ) # any TRUE?
all(  grepl("Lindor", schoko)  ) # All TRUE
! grepl("Lindor", schoko)
```

Solution for exercise 19.2-41: Character strings

```r
# Replace Character strings (substitute)
sub(pattern="or", replacement="nicor", schoko)
# Replace all occurences (global substitution)
gsub(pattern="or", replacement="nicor", schoko)

# Avoid capitalization issues with
tolower(schoko)
"Ritter [s,S]port" %in% schoko
# Does not work!!
```

Outline

R course info
1. One-Session-Intro
2. Getting started: Background, GUI and first steps
3. Objects
4. "Real" data
5. Plotting
6. Character Operations
7. Conditions & loops
   Conditions
   For Loops
   lapply, Rcpp
   Repeat + While Loops
8. Functions & packages
9. Distributions
10. Statistics
11. Time series handling and analysis
12. Spatial data and GIS functionality
13. Final tasks
Course plan

Conditional execution I

Syntax for a single logical value:

```
if(this_is_true) {do_something} else {do_other_thing}
```

Syntax for a vector with several T/F values:

```
ifelse(condition, expression1, expression2)
```

If condition == TRUE, then expression1 is evaluated, if condition == FALSE, then expression2 is evaluated.

`7-3 > 2`	TRUE
`class(7-3 > 2 )`	logical = truth value, boolean
`if(7-3 > 2) 18`	Condition is TRUE, so 18 is returned
`if(7-3 > 5) 18`	Condition is FALSE, so nothing happens
`if(7-3 > 5) 18 else 17`	Condition FALSE, so 17 is returned.

Conditional execution II

```
# Several commands must be held together with curly braces:
if(TRUE)
  {
  plot(1:10, main="TRUE in code")
  box("figure", col=4, lwd=3)
  } else
# do something else: plot random numbers
    {
    plot(rnorm(500), main="FALSE in code")
    }
# these last brackets can (but should not) be left away
# indenting code makes it readable for humans

par(mfrow=c(1,2), cex=1, las=1)
```

Conditional execution III

Vectorising: if(c) e1 else e2 vs ifelse(c, e1, e2)

```
v <- c(13, 14, 15, 16, 17)
v>14

## [1] FALSE FALSE  TRUE  TRUE  TRUE
```

```
ifelse(v>14, v+10, NA) # can handle vector of input

## [1] NA NA 25 26 27
```

```
if(v>14) v+10 else NA

## Warning in if (v > 14) v + 10 else NA: the condition has
length > 1 and only the first element will be used

## [1] NA
```

Time to practice

Exercise 20: if else - Conditional code execution

1. `sqrt` returns NaN for the negative values in `v <- -3:5` and warns about it. With a conditional expression, pass 0 instead of negative values to `sqrt`.
2. Construct a statement that checks whether the variable `input <- 4` is a number smaller than 3. Let it write a useful `message` to the console (for both cases). Now test it with `input <- 1.8` and `input <- -17`.
3. Now restrict the correct value of input to *positive* numbers <3, i.e. the number must be <3 AND ≥ 0.
4. BONUS 1: What happens if `input <- "2"` or if `input <- "b"`?
5. BONUS 2: Create a character variable that, depending on the result of `rnorm(1)`, is initiated with probable or unlikely.
6. BONUS 3: `replicate` this experiment 1000 times and examine the result with `table`.
7. BONUS 4: How could you do this with `ifelse`?

Solution for exercise 20.1: if else

```
v <- -3:5
sqrt(v)

## Warning in sqrt(v):  NaNs produced

## [1]    NaN    NaN    NaN 0.0000 1.0000 1.4142 1.7321 2.0000 2.2361
```

```
ifelse( v >= 0, sqrt(v), 0)

## Warning in sqrt(v):  NaNs produced

## [1] 0.0000 0.0000 0.0000 0.0000 1.0000 1.4142 1.7321 2.0000 2.2361
```

```
sqrt(ifelse( v >= 0, v, 0))

## [1] 0.0000 0.0000 0.0000 0.0000 1.0000 1.4142 1.7321 2.0000 2.2361
```

Solution for exercise 20.2: if else

```
input <- 4
if( input >= 3 ) message("Input was wrong.
                         It should be <3") else
                 message("Input OK")

## Input was wrong.
##                         It should be <3

# run it again after
input <- 1.8
input <- -17
```

Solution for exercise 20.3: if else

```
# three different solutions:
if( input >= 3 ) message("Input is > 3") else
if( input < 0 )  message("Input is < 0") else
                 message("Input OK")

if( input >= 3 |  input < 0)
   message("Input outside 0...3") else
   message("Input OK")

if( input > 0  &  input <= 3 )   message("Input OK") else
           message("Input (",input,") outside 0...3")
```

Solution for exercise 20.3: if else BONUS

```
result <- if(rnorm(1)>2) "unlikely" else "probable"

result <- replicate(n=1000, expr=
             if(rnorm(1)>2) "unlikely" else "probable")
table(result)

result <- ifelse(rnorm(1000)>2, "unlikely", "probable")
table(result)
```

Notes on logical values

- as you might have seen in `read.table(header=T)`, logical values (TRUE, FALSE) can be abbreviated.
- If you want to play a mean prank on someone, write `T <- FALSE; F <- TRUE` in their Rprofile (see `?Startup`).
- Logical (boolean) values F and T internally are often converted to integers 0 and 1, thus `sum(c(T,F,F,T,T,T,F,F,T))` is the number of TRUEs in a vector, `mean` yields the proportion of TRUEs.
- `which(logicalVec)` gives the indices (positions) of TRUE values.
- `Vec[logicalVec]` returns only the values of vec corresponding to TRUE in logicalVec (No need to wrap it into `which`).
- Logical operators: `!`, `&`, `|`, `xor()` (not, and, or, exclusive or)

Notes on conditional code execution

- `if(c){ex1}` is valid code, thus R doesn't expect else anymore.
- If you execute code line by line (in a script, for example), } and else must be on the same line.
- Many people consider it good practice to do this in functions as well, but for machine-readability, it is technically fine to write

```
if(cond)
  {
  ex1a
  ex1b
  }
else
  ex2
```

- `if(logicalValue==TRUE) ...` is usually unnecessary, you can write `if(logicalValue) ...`, but sometimes, `if(isTRUE(logicalValue)) ...` helps to deal with NAs.

Actual usage of if else statements

See the `hist` source code:
github.com/wch/r-source -> src / library / graphics / R / hist.R

```
mad
```

Multiple nested conditionals
`if(a) b else if(c) d else e`
can be avoided with `switch`.

Outline

R course info
1. One-Session-Intro
2. Getting started: Background, GUI and first steps
3. Objects
4. "Real" data
5. Plotting
6. Character Operations
7. Conditions & loops
   - Conditions
   - For Loops
   - lapply, Rcpp
   - Repeat + While Loops
8. Functions & packages
9. Distributions
10. Statistics
11. Time series handling and analysis
12. Spatial data and GIS functionality
13. Final tasks

Course plan

For loops

Execute a block of code several times, with different input values.
Syntax: `for(aRunningVariable in aSequence){ doSomething }`
Often, i (for index) is used, thus `for(i in 1:n) doThis(i)`

```
help("for") # needs quotation marks!
```

```
print(1:2)
print(1:5)
print(1:9)
```

This is easier and less prone to human errors with:

```
for(i in c(2,5,9) ) { print(1:i) }

## [1] 1 2
## [1] 1 2 3 4 5
## [1] 1 2 3 4 5 6 7 8 9
```

For loops: fill a vector

```
v <- vector(mode="numeric", length=20)
v

##  [1] 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0
```

```
for(i in 3:17)  {  v[i] <- (i+2)^2  }
```

```
v # this code was executed once for each i

##  [1]   0   0  25  36  49  64  81 100 121
## [10] 144 169 196 225 256 289 324 361   0
## [19]   0   0
```

See Rclick 10.4 for a realistic for loop example.
In R, `for` loops are slow. Always try to vectorize (the best option, not always possible) or use `lapply` (saves you the initiation of the empty vector, easier to parallize).

For loops: execute code multiple times I

$$y = f(x, n) = \frac{12.5 * n}{(n-1)!} * \left(\frac{nx}{8}\right)^{(n-1)} * e^{-\frac{nx}{8}}$$

For loops: execute code multiple times II

```
x <- seq(0,25,0.1)
plot(x,x, type="n", ylab="y = f(x,n)")
lines(x, 12.5*5/factorial(5-1)*(x/8*5)^(5-1)*exp(-x/8*5), col=2)
lines(x, 12.5*6/factorial(6-1)*(x/8*6)^(6-1)*exp(-x/8*6), col=2)
```

For loops: execute code multiple times III

```
x <- seq(0,25,0.1)
plot(x,x, type="n", ylab="y = f(x,n)")
for (n in 5:25)
lines(x, 12.5*n/factorial(n-1)*(x/8*n)^(n-1)*exp(-x/8*n), col=2)
```

stocks data from finance.yahoo.com

```
# Download current datasets:
if(!requireNamespace("quantmod")) install.packages("quantmod")
if(!requireNamespace("pbapply"))  install.packages("pbapply")
dummy <- pbapply::pblapply(c("F","VLKAY", "AMZN","AAPL","GOOG","MSFT"),
   function(x) zoo::write.zoo(x=quantmod::getSymbols(x, auto.assign=FALSE)[,6],
                              file=paste0("data/finance/",x,".txt"), col.names=T))

# read single files to R and merge into one file:
stocks <- lapply(dir("data/finance", full=TRUE),
                 read.table, as.is=TRUE, header=TRUE)
stocks <- Reduce(function(...) merge(..., all=T), stocks)

# Get nicer column names:
names <- sapply(strsplit(colnames(stocks), ".", fix=TRUE),"[", 1)
colnames(stocks) <- c(Index="Date", F="FORD", VLKAY="VOLKSWAGEN",
         AMZN="AMAZON", AAPL="APPLE", GOOG="GOOGLE", MSFT="MICROSOFT")[names]

# Save to disc:
write.table(stocks, file="data/stocks.txt", row.names=F, quote=F)
```

For loops: multipanel graphics: the task

Exercise 21: for loop

1. Read stocks.txt *(rightclick **Raw**, save as)*, so that there are no factors in the data.frame
2. Change the first column type from `char` to `date` with `?as.Date`
3. What do you get with `plot(stocks[ ,1:2])`? Make it a line graph.
4. With `par(mfrow...`, set up a two by three panel plot
5. With a for loop, fill those with each stock time series
6. BONUS 1: Make good annotations, including a main title (par oma, `mtext` with the outer argument)
7. BONUS 2: Make the plot margins smaller (par mar), turn y axis labels upright (las) and move the axis labels closer to the plots (mgp).
8. BONUS 3: Understand and comment each line of the data preparation.

For loops: multipanel graphics: the solution

```
stocks <- read.table("data/stocks.txt", header=T, as.is=T)
stocks$Date <- as.Date(stocks$Date)
par(mfrow=c(2,3), mar=c(2,4,1,1), mgp=c(2.5,0.7,0),oma=c(0,0,2,0),las=1)
for(i in 2:7) plot(stocks[ ,c(1,i)], type="l")
mtext("stocks this decade", line=0, outer=TRUE)
```

For loops: multipanel graphics: beautifuller

```
par(mfrow=c(1,2), mar=c(4,4,2,0.1), mgp=c(2.5,0.7,0), cex=0.7, las=1)
for(i in 2:3)
 {
 plot(stocks[ stocks$Date>as.Date("2016-04-01") , c(1,i) ],
      main=colnames(stocks)[i], xaxt="n", type="l", xlab=" ",
      ylab=if(i==2) "Adjusted daily share price  [USD]" else "")
 berryFunctions::monthAxis(1)
 }
```

Outline

R course info
1. One-Session-Intro
2. Getting started: Background, GUI and first steps
3. Objects
4. "Real" data
5. Plotting
6. Character Operations
7. Conditions & loops
   - Conditions
   - For Loops
   - lapply, Rcpp
   - Repeat + While Loops
8. Functions & packages
9. Distributions
10. Statistics
11. Time series handling and analysis
12. Spatial data and GIS functionality
13. Final tasks

Course plan

for -> lapply I: basics

```
files <- dir("../rawdata", pattern="*.csv", full=TRUE)

# bad and slow way:
dfs <- list() # initiate empty list
for(i in 1:length(files))
   dfs[[i]] <- read.csv(files[i], as.is=TRUE)

# much better way: apply function to each file
dfs <- lapply(X=files, FUN=read.csv, as.is=TRUE)

# single data.frame if all files have n columns:
df <- do.call(rbind, dfs)

# PS: much faster in this example could be
library("data.table")
dfs <- lapply(X=files, FUN=fread, sep=",")
df <- rbindlist(dfs)
```

for -> lapply II: progress bar, names, indexing etc

```
dfs <-   lapply(X=files, FUN=read.csv, as.is=TRUE)

# progress bar with remaining time
library("pbapply")
dfs <- pblapply(X=files, FUN=read.csv, as.is=TRUE)

# nice additional stuff:
names(dfs) <- files
str(dfs, max.level=1)
dfs[[2]] # second list element

# get third column / fifth row from each df:
sapply(dfs, "[",  , j=3)
sapply(dfs, "[", 5,    )
```

lapply exercise

Exercise 22: lapply

1. Get the average of each element in the built-in dataset `Harman23.cor` with `lapply`.
2. Now use `sapply` instead. What changes?
3. BONUS: Do this again with a `for` loop.
4. Please create `max_n <- function(...)  max(rnorm(1e7))`. Now run this 10 times with an `sapply` loop.
5. Display a progress bar along with it.
6. BONUS: From each element of `Harman74.cor`, get the first 5 values.

lapply exercise solution I

```
lapply(Harman23.cor, mean)

## $cov
## [1] 0.578875
##
## $center
## [1] 0
##
## $n.obs
## [1] 305

sapply(Harman23.cor, mean) # simplified into a vector

##        cov     center      n.obs
##   0.578875   0.000000 305.000000
```

lapply exercise solution II

```
harmeans <- rep(NA,length(Harman23.cor))
for(i in 1:length(Harman23.cor) )
    harmeans[i] <- mean(Harman23.cor[[i]])
names(harmeans) <- names(Harman23.cor)
harmeans

##         cov      center       n.obs
##   0.578875   0.000000 305.000000

max_n <- function(...) max(rnorm(1e5))
pbapply::pbsapply(1:10, max_n)

##  [1] 4.624598 4.204675 5.079964 4.255254 4.401126
##  [6] 4.625683 4.250512 4.160242 4.281924 4.644114
```

```
lapply(Harman74.cor, "[", 1:5)
```

for -> lapply IIIa: parallel on multiple CPU cores

```
library("parallel") # already comes with R
# -> don't try to  install.packages("parallel")
nc <- detectCores()-1

# multicore parallel execution
dfs <-        lapply(X=files, FUN=read.csv, as.is=TRUE)
dfs <-      mclapply(X=files, FUN=read.csv, as.is=TRUE,
                     mc.cores=nc) # easy on linux

# more code needed on windows:
cl <- makePSOCKcluster(nc)
dfs <- parLapply(cl, X=files, fun=read.csv, as.is=TRUE)
stopCluster(cl)

# sometimes needed before parLapply call:
clusterExport(cl, c("files","otherObjects"))
clusterEvalQ(cl, library("somePackage"))
```

for -> lapply IIIb: parallel AND progress bar

```
library(parallel)
library(pbapply) # (>2016-10-30)
cl <- makeCluster( detectCores()-1 )
myfun <- function(...) mean(rnorm(1e6))
clusterExport(cl, "myfun")
dfs1 <- pblapply(X=1:500, FUN=myfun) # 36 sec on 1 CPU core
dfs2 <- pblapply(X=1:500, FUN=myfun, cl=cl) # 10 s on 7
stopCluster(cl)

# selects windows or linux method for you!
# Peter Solymos and Zygmunt Zawadzki are awesome!
```

for -> lapply IV: code timing

```
begintime <- Sys.time(); begintime
parLapply(cl, X, fun)
Sys.time() - begintime ; rm(cl, begintime)
```

```
#install.packages("microbenchmark")
library(microbenchmark)
forbad <- function(n)  # fibonacci
  {
  fibvals <- c(1,1)
  for (i in 3:n) fibvals[i] <- fibvals[i-1]+fibvals[i-2]
  fibvals
  }
forgood <- function(n)
  {
  fibvals <- rep(1,n)
  for (i in 3:n) fibvals[i] <- fibvals[i-1]+fibvals[i-2]
  fibvals
  }
mb <- microbenchmark(forbad(2000), forgood(2000))  ;  mb
```

```
## Unit: microseconds
##            expr     min       lq     mean  median       uq      max neval
##   forbad(2000) 711.676 736.8235 986.0070 778.085 874.7620 5340.731   100
##  forgood(2000) 264.131 268.1965 402.9358 273.015 279.4905 4951.312   100
```

for -> C++ code: Rcpp

Loops are fast in C++, so outsource that part of your code into C. The package Rcpp will compile it for you and make it available as a normally accessible R function.
Start learning at https://adv-r.had.co.nz/Rcpp.html
Speed gain is highly variable, of course, but you might be able to reduce your computing time from 2 hours to 20 seconds!

To find the slow parts of your code, you perform a process called "profiling":
https://www.r-bloggers.com/profiling-r-code
https://www.rdocumentation.org/packages/utils/topics/Rprof?
https://adv-r.had.co.nz/Profiling.html
New and very promising:
https://blog.rstudio.org/2016/05/23/profiling-with-rstudio-and-profvis
https://support.rstudio.com/hc/en-us/articles/218221837-Profiling-with-RStudio

For loop: Fibonacci

The Fibonacci sequence consists of the following integers:
1, 1, 2, 3, 5, 8, 13, 21, 34, 55, 89, 144, ...
The first two values are 1, the following values are always the sum of the previous two elements.

Exercise 23: Fibonacci

1. Create the first 100 numbers of the fibonacci sequence with a for loop
2. BONUS 1: "forget" to create an empty vector of the correct length first, and compare the computational time of the two expressions. Hint: Use `install.packages("microbenchmark"); library(microbenchmark); mb <- microbenchmark(...)`
3. BONUS 2: Can you also do this with sapply?
4. BONUS 3: Find a fast fibonacci creator function online and compare the timings of that as well
5. BONUS 4: With the package `Rcpp`, write the for loop in C++ and compare the speed with the other variants

Fibonacci solution

```
len <- 20
fn <- rep(1, len)
for(i in 3:len)  fn[i] <- fn[i-1] + fn[i-2]
fn

##  [1]    1    1    2    3    5    8   13
##  [8]   21   34   55   89  144  233  377
## [15]  610  987 1597 2584 4181 6765
```

Fibonacci solution II

```
#install.packages("microbenchmark")
library(microbenchmark)
#install.packages("numbers")
suppressWarnings(library(numbers))
forbad <- function(n)
  {fibvals <- c(1,1)
  for (i in 3:len) fibvals[i] <- fibvals[i-1]+fibvals[i-2]
  fibvals
  }
forgood <- function(n)
  {fibvals <- rep(1,n)
  for (i in 3:len) fibvals[i] <- fibvals[i-1]+fibvals[i-2]
  fibvals
  }
numfib <- function(n) suppressWarnings(fibonacci(n, seq=T))
applfib <- function(n)
  {fibvals <- rep(1,n)
  sapply(3:n, function(i) {fibvals[i]<<-fibvals[i-1]+fibvals[i-2]})
  }
mb <- microbenchmark(numfib(2000), forbad(2000), forgood(2000), applfib(2000))
mb


## Unit: microseconds
##           expr      min        lq        mean    median        uq        max neval
##   numfib(2000)  386.103  404.7765   684.79159  437.0010  534.1300  18523.326   100
##   forbad(2000)    8.132   10.8425    56.71100   13.8545   20.1790   4137.209   100
##  forgood(2000)    6.325    7.2290    57.59042    9.3365   13.4025   4547.105   100
##  applfib(2000) 4687.151 4921.0120 10810.46794 5080.4825 5273.6850 119569.480   100
```

Outline

R course info
1. One-Session-Intro
2. Getting started: Background, GUI and first steps
3. Objects
4. "Real" data
5. Plotting
6. Character Operations
7. Conditions & loops
   Conditions
   For Loops
   lapply, Rcpp
   Repeat + While Loops
8. Functions & packages
9. Distributions
10. Statistics
11. Time series handling and analysis
12. Spatial data and GIS functionality
13. Final tasks
Course plan

Repeat loops

Syntax: `repeat {expressions}`

```
next  # jump to next iteration
break # leave the loop
```

```
i <- 0 # Create object i with the value 0
repeat # keep repeating the following block of code
   {                        # Codeblock begins
   i <- i + 1               # overwrite object i with new number
   if (i < 3)  print(i) # conditional output to console
   if (i == 3)   break  # conditional leaving of loop
   }                        # Codeblock ends

## [1] 1
## [1] 2
```

What is now the value of i? i is now 3, because in the last iteration, 1 was added to 2 and the result saved as i.

While loops

Syntax: `while(condition){expressions}`

The following code is executed as long as (while) i is lesser then 3:

```
i <- 0
while(i < 3) i <- i + 1
i

## [1] 3
```

repeat loops are hardly ever used in R, and while loops fairly seldom as well.

Practice while loops

Exercise 24: while loop

1. Why is the character string `folder <- "path/to/file///"` unsuitable for reading in a file?
2. With a while loop, make it suitable. Hints: `substring`, `nchar`
3. BONUS: enable your solution to deal with \\ at the end as well. Hint: `%in%`.

Solution to exercise 24: while loop

`folder <- "path/to/file///"` would link to empty-named subfolders at the end

```
folder <- "path/to/file///"
while(substring(folder, nchar(folder))=="/")
     folder <- substring(folder, 1, nchar(folder)-1)

while( substring(folder, nchar(folder)) %in% c("/", "\\") )
     folder <- substring(folder, 1, nchar(folder)-1)
```

The grand duel (http://www.janko.at/Raetsel/Mathematik/095.a.htm)

Sir Adam and Sir Bart confront each other in a duel with pistols. By good old English custom, the two shoot at each other alternately, until one of them dies. Being gentlemen, they decide that the worse shooter may fire the first shot. Sir Adam has a hit ratio of 30% and Sir Bert one of 40%. What are the chances of survival for each of the two?

Exercise 25: while loop duel

1. BONUS 1: Derive the probabilities mathematically.
2. Simulate the duel numerically. Hint: repeat the experiment `while` both are alive. In each step, let Sir Bert die with a 30% change; if he survives, let Sir Adam die with a 40% change.
3. BONUS 2: Write a function simulating the duel and returning the outcome.
4. Run the simulation 1000 (10k) times and assess Sir Bert's chance of survival.
5. BONUS 3: How many rounds are fought on average? (How is that quantity distributed?)

The grand duel - resolved

```
plot(cumsum(sapply(0:20, function(i) 0.42^i*0.3)), type="l",
     ylim=c(0.26,0.58), main="cumulative death chance per round")
lines(cumsum(sapply(0:20, function(i) 0.42^i*0.7*0.4)), col=2)
```

The grand duel - resolved

```
duel_simulation <- function()
{
a <- b <- TRUE # TRUE = 1 = alive
n <- 0 # number of rounds
while(a&b)
  {
  if(  runif(1)<0.3) b <- FALSE # = 0 = dead
  if(b&runif(1)<0.4) a <- FALSE
  n <- n+1
  }
# return simulation result
c(a=a,b=b, n=n)
}
```

The grand duel - resolved

```
simu_res <- replicate(10000, duel_simulation())
# head(t(simu_res), 30)
apply(simu_res, 1, table) # / 10000 *100

## $a
##
##    0    1
## 4857 5143
##
## $b
##
##    0    1
## 5143 4857
##
## $n
##
##    1    2    3    4    5    6    7    8    9   10   13   19
## 5736 2437 1040  447  189   85   41   14    8    1    1    1
```

Outline

R course info
1. One-Session-Intro
2. Getting started: Background, GUI and first steps
3. Objects
4. "Real" data
5. Plotting
6. Character Operations
7. Conditions & loops
8. Functions & packages
   - Functions
   - Writing R packages
   - Debugging
   - Programming exercise
9. Distributions
10. Statistics
11. Time series handling and analysis
12. Spatial data and GIS functionality
13. Final tasks

Course plan

Functions I

http://r4ds.had.co.nz/functions.html

`?"function"`

Syntax:

`Functionobjectname <- function(argument1, argument2, ...) {"DoSomething"}`

```
myfunct <- function(grappig)
       {plot(grappig, type="l"); return(grappig*7)  }
```

After `return()`ing, the execution of the function is terminated, so it should only be positioned at the end. It can also be left away, the last instruction ("expression") will then be returned.

Functions II

```
myfunct(   c(5,11,3,7)  )

## [1] 35 77 21 49
```

Functions with more arguments

```
myfunct <- function(x, type="o", ...) plot(x, type=type, ...)
# type="o" is now the default, thus used unless specified
# The ellipsis (...) passes arguments to other functions
myfunct(  c(5,11,3,7) , col="red", las=1)
```

Functions: example I

If you needed to find the zeros of quadratic functions very often, you could use

```
pq <- function(p,q) # y = x^2 + px + q
               {
               w <- sqrt( p^2 / 4 - q )
               c(-p/2-w, -p/2+w)
               } # End of function

pq(3, -12)

## [1] -5.2749  2.2749
```

Functions: example II

```
x <- seq(-10, 10, len=100)
plot(x,  x^2 +3*x -12, type="l", col=2)
abline(h=0, v=0)
```

Exercise: add circles with given radius

```
plot(1:10, asp=1) # aspect ratio y/x of graph range
grid(col=1) # the next part sould go into a function:
x <- 8 ;  y <- 6 ;  r <-2
p <- seq(0, 2*pi, len=50)
cx <- x+r*cos(p) ;  cy <- y+r*sin(p)
polygon(cx, cy)
```

Time to practice programming

Exercise 26: Writing functions

Write a function that

1. - draws a circle with a certain radius at user-specified locations of an existing plot (see last slide).
2. - uses ellipsis to allow the user to customize the appearance
3. - checks all the arguments and gives useful warnings if the wrong type of input is provided
4. - has useful explanations for each argument (documentation)
5. - has readable indentation, spacing and comments explaining the code
6. Now let your neighbor use it without explaining how it is to be used (this should be inferred from the code and comments!)
7. Use your neighbor's function with a vector to draw several circles at once. (unintended use?) What happens?

```r
# Small helper function drawing circles into existing graphics
# Berry Boessenkool, berry-b@gmx.de, 2012
circle <- function(
  x, # x-coordinate of points, numeric value of length 1
  y, # ditto for y
  r, # radius of the circle, in the graphic's units
  locnum=100, # number of points on circle (more means smoother but slower)
  ...) # Further Arguments passed to polygon, like col, border, lwd
 {
 # input checking - only one circle can be drawn:
 if(length(x) >1 | length(y) >1 | length(r) >1 | length(locnum) >1)
   {
   warning("Only the first element of the vectors is used.")
   x <- x[1]; y <- y[1]; r <- r[1]; locnum <- locnum[1]
   }
 # input checking - is every value numeric?
 if(!is.numeric(x)) stop("x must be numeric")
 if(!is.numeric(y)) stop("y must be numeric")
 if(!is.numeric(r)) stop("r must be numeric")
 # prepare circle line coordinates:
 cx <- x+r*cos( seq(0,2*pi,len=locnum) )
 cy <- y+r*sin( seq(0,2*pi,len=locnum) )
 polygon(cx, cy, ...) # actually draw it
 }
# Note: if circles look like ellipsis, use plot(... asp=1)
```

Solution for exercise 26 II: functions

```
plot(1:20, type="n", asp=1, cex=2)
circle(5,5, r=3)
circle(15,10, r=4, locnum=12, col=2, border=4, lwd=3)
```

Solution for exercise 26 III: functions

```
# can not be vectorized:
x <- sample(1:20, 15) ;  y <- sample(1:20, 15) ; r <- runif(20)*4
circle(x,y,r, col=rgb(1,0.5,0,alpha=0.4), border=NA)

## Warning in circle(x, y, r, col = rgb(1, 0.5, 0, alpha = 0.4), border = NA):
Only the first element of the vectors is used.

for(i in 1:15) circle(x[i],y[i],r[i], col=rgb(1,0.5,0,alpha=0.4), border=NA)
```

Coding elegance I

Suppose you have two related vectors, perhaps as a result from `approx`:

```
a:   1    2    3    4    5 ...
b:   1 2 3 4 5 6 7 8 9 ...
```

For any element *i* in a, you want to select the corresponding surrounding values of b. Example: if i=3, you want to select the elements 4,5 and 6. However, at the border, you cannot select with negative indices.

Exercise 27: Elegant Coding: surrounding indices

1. Write a function using conditionals that performs the task described above.
2. BONUS: If it's not a "one-liner", try to find a different approach.

Coding elegance II

Here is how to write this with conditional statements:

```
index_1 <- function(i)
{
if(i == 1)                          1 : 2
else if(i == length(a))  ((i-1)*2) : (i*2-1)
else                     ((i-1)*2) : (i*2)
}
```

Here's the elegant way:

```
index_2 <- function(i)
  pmax((i-1)*2, 1) : pmin(i*2, length(a)*2-1)
```

Coding elegance III

Both functions yield the same result:

```
a <- 1:5
index_1(1); index_2(1)

## [1] 1 2
## [1] 1 2

index_1(3); index_2(3)

## [1] 4 5 6
## [1] 4 5 6

index_1(5); index_2(5)

## [1] 8 9
## [1] 8 9
```

Outline

R course info
1. One-Session-Intro
2. Getting started: Background, GUI and first steps
3. Objects
4. "Real" data
5. Plotting
6. Character Operations
7. Conditions & loops
8. Functions & packages
   - Functions
   - Writing R packages
   - Debugging
   - Programming exercise
9. Distributions
10. Statistics
11. Time series handling and analysis
12. Spatial data and GIS functionality
13. Final tasks

Course plan

Why you should write R packages

- Collect your own functions in one place
- Combine functions and documentation in the right way
- Share code with others
- Make your research reproducible !

Good introductions linked here: github.com/brry/misc

Package development: devtools + github

We'll create a cat package together following the instructions in packdev.R *(rightclick **Raw**, save as)*.

Version control with git:

- Once only: Create a github account (free), set up git on your computer, connect it to Rstudio. This is all very unfun and tedious, but at least there is a good guide that also includes a first test of the system: r-bloggers.com/rstudio-and-github. See also kbroman.org/github_tutorial for a good intro.
- github.com, log in, on "+" in top-right select "New repository", initialize with readme!
- On the green field "clone or download": copy link
- Rstudio - file - new project - version control - git: paste url and create
- `devtools::setup()` instead of `create`, choose option number to Overwrite 'yourPackage.Rproj'
- Work. Commit. Push. Repeat.

Package exercise

Exercise 28: create LSC package (solutions on next 2 slides)

1. Create a package for linear storage cascade functions (lsc)
2. BONUS: Use git from the beginning, commit often!
3. Check the package, correct description file and check again
4. Now add the functions in lsc_functions.zip to the R folder
5. Done? Help your peers.
6. Document the nse function (we'll do this one together)
7. Create datasets within the package (following instructions in data.R)
8. Document the rmse function
9. Check and install the package

Solution for exercise 28: create LSC package

```r
library(devtools)
create("lsc") # or devtools::setup() if using git
document() # calls roxygen2::roxygenise()
check() # will also update documentation
install() # install the package locally
load_all(".") # CTRL + SHIFT + L    - faster than install!
```

Solution for exercise 28: Documenting functions

```
#' @title       Nash-Sutcliffe efficiency
#' @description Nash-Sutcliffe efficiency as a measure of goodness of fit.
#'              Removes incomplete observations with a warning.
#' @return      Single numerical value
#' @export
#' @seealso     \code{\link{rmse}}
#' @references  based on eval.NSeff in RHydro Package
#'              \url{https://r-forge.r-project.org/R/?group_id=411}
#' @examples
#' x <- rnorm(20) ; y <- 2*x + rnorm(20)
#' x[2:4] <- NA
#' nse(x,y)
#'
#' @param obs Numerical vector with observed values
#' @param sim Simulated values (Num vector with same length as \code{obs})
#'
nse <- function(obs, sim)
{
if(!(is.vector(obs) & is.vector(sim))) stop("Input is not a vector.")
if(length(obs) != length(sim)) stop("Vectors are not of equal length.")
#[...]
1 - ( sum((obs - sim)^2) / sum((obs - mean(obs))^2) )
}
```

Outline

R course info
1. One-Session-Intro
2. Getting started: Background, GUI and first steps
3. Objects
4. "Real" data
5. Plotting
6. Character Operations
7. Conditions & loops
8. Functions & packages
   - Functions
   - Writing R packages
   - Debugging
   - Programming exercise
9. Distributions
10. Statistics
11. Time series handling and analysis
12. Spatial data and GIS functionality
13. Final tasks

Course plan

Debugging

- Your code throws an error. You didn't call the mentioned function. Obviously, your code calls some function calling some function calling some function calling [you get the idea] which in the end creates an error. To trace back this path, you can use `traceback()`.
- Now that you know where the error originates from, you set `options(error=recover)`. You run your code again, but this time R waits at the level creating an error. You examine the environment within the function, play around with the objects and internal function code, until the bug has been fixed. You have just debugged a function.
- You want to step into the function you are developing at a specific point. You add `browser()` at that point of the code. You want to go line by line in one specific function. You set `debug(thatFunction)`.
- You want to learn about lexical scoping (Where does R find variables?). http://trestletech.com/2013/04/package-wide-variablescache-in-r-package/ http://adv-r.had.co.nz/Environments.html

Debugging: useful functions

source("projectFuns.R")	execute complete file
traceback()	find error source in sequence of function calls
options(warn=2)	warnings to error. default 0
browser()	go into function environment: `n`, `s`, `f`, `c`, `Q`
options(error=recover)	open interactive session where error occurred
debug(funct)	toggle linewise function execution
undebug(funct)	after calling and fixing funct

```
if(length(input)>1) stop("length must be 1, not ", length(input))
```

`stop`: Interrupts function execution and gives error
`warning`: continues but gives warning
`message`: to inform instead of worry the user

R. Peng (2002): Interactive Debugging Tools in R
D. Murdoch (2010): Debugging in R
H. Wickham (2015): Advanced R: debugging
Example: Pete Werner Blog Post (2013)

Practice debugging, lsc_functions.R *(rightclick **Raw**, save as)*

Exercise 29: Debugging

1. Load your package and the datasets. Correct the functions until `lsc(calib$P, calib$Q, area=1.6)` returns the result below.
2. BONUS: commit each change to git.

Solution for exercise 29: Debugging

- `stupid error you can easily remove` - traceback - find location of error - lsc#75 - just comment it out
- `harder to find but still stupid` - traceback - nse#22 - ditto
- `Error in plot:  need finite 'ylim' value` - debug/browser/options(error=recover) - lsc#107 - NAs in Q - range(Q, na.rm=TRUE) - also in other applicable locations
- `There were 50 or more warnings` - come from rmse being called in optimization - add argument quietNA (or similar) to lsc that is passed to rmse in lsc#81

Outline

R course info
1. One-Session-Intro
2. Getting started: Background, GUI and first steps
3. Objects
4. "Real" data
5. Plotting
6. Character Operations
7. Conditions & loops
8. Functions & packages
   - Functions
   - Writing R packages
   - Debugging
   - Programming exercise
9. Distributions
10. Statistics
11. Time series handling and analysis
12. Spatial data and GIS functionality
13. Final tasks

Course plan

Chapter practice: sample size dependency

Exercise 30: Programming part 1 - functions

1. Write a function (#1) that computes the backtransformed arithmetic average of logtransformed values. It should `stop` with a useful error message if there are `any` negative values in the input vector.
2. Write a second function (#2) taking a vector of values that returns the mean, sd, coefficient of variation and the output of function #1.
3. It should return these values with names as in `c(a=5,b=-3)`.
4. If the average is zero, it should inform the user that the CV cannot be computed. Remember to check only rounded values for equality.
5. Test both functions with `c(88,31,73,21,08,52,66,48)`, with `c(4,7,5,6,4,5,3,NA,6,4,5,6,8,5)` and with `c(0,0,0)`.
6. Write a function (#3) taking **`n`**, **`mean`** and **`sd`** that
   - breaks if **`n`** is not a single value
   - draws **`n`** random numbers from the normal distribution with **`mean`** and **`sd`**
   - returns the output of function #2 of that sample.

Programming practice solutions part 1 - functions 1

backtransformed arithmetic average of logtransformed values

```
logmean <- function(x)
  {
  if(any(x<0)) stop("x has ", sum(x<0), " negative values.")
  lx <- log10(x)
  10^mean(lx)
  }

logmean(c(88,31,73,21,08,52,66,48))

## [1] 39.14336

#logmean(c(4,7,5,6,4,5,3,NA,6,4,5,6,8,5))
logmean(c(0,0,0))

## [1] 0
```

Programming practice solutions part 1 - functions 2

Statistical properties of a vector

```
meanvar <- function(vals)
  {
  m <- mean(vals) # average
  s <- sd(vals) # root of variation
  if(round(m)==0) stop("mean is 0, CV cannot be computed")
  c(mean=m, sd=s, CV=s/m, logmean=logmean(vals))
  }

meanvar(c(88,31,73,21,08,52,66,48))

##       mean          sd          CV    logmean
## 48.3750000 27.2078639  0.5624365 39.1433623

#meanvar(c(4,7,5,6,4,5,3,NA,6,4,5,6,8,5))
#meanvar(c(0,0,0))
```

Programming practice solutions part 1 - functions 3

Dependency on sample size

```
dep_n <- function(n, mean, sd)
  {
  if(length(n)!=1) stop("n must be a single value, not ",
                        length(n))
  # draw n numbers randomly from normal distribution:
  v <- rnorm(n, mean=mean, sd)
  meanvar(v)
  }

dep_n(20, 70,5)

##        mean          sd          CV     logmean
## 70.95960010  6.56314211  0.09249125 70.65816749

#
```

Chapter practice: sample size dependency

Exercise 31: Programming part 2 - debugging

1. Test function #3 with `n=20:30, mean=70,sd=5`
2. What happens if you use it with `n=NA, mean=70,sd=5`?
3. After you call it with `n=20, mean=-70,sd=5`, run `traceback()` Explain the result.
4. What is the result of `ls.str()`?
5. Set you upper level function #3 to `debug`ging mode. Now call it again. What happens? What is now the result of `ls.str()`?

- With enter, you can now execute the function line by line and observe how objects (variables) in functions change over execution time, thus making it easier to find the source of an error.
- Don't forget to `undebug` your function again.
- If you only want to step into the function at a certain point, write `browser()` at that position, redefine the function and call it again.

Programming practice solutions part 2 - debugging

```
dep_n(20, -70,5)

## Error in logmean(vals):  x has 20 negative values.
```

```
traceback()
```

```
4:  stop("x has ", sum(x < 0), " negative values.") at #3
3:  logmean(vals) at #6
2:  meanvar(v) at #5
1:  dep_n(20, -70, 5)
```

In debugging mode, you step into the function when it is called (visible by `Browse[2]>` in the console). `ls.str()` now returns the structures of the objects defined within the function environment.

Chapter practice: sample size dependency

Exercise 32: Programming part 3 - loops for computation

For this task, use `n <- rep(1:50, each=100)`

1. Create an empty `data.frame` with the column names according to the output of function #3.
2. With a for loop, fill each row with the result of the n-corresponding call to function #3.
3. Obtain the computing time by either wrapping it in `system.time` or calling `Sys.time()` before and afterwards and computing the `difftime`.
4. Time the usage of `sapply` for the same task. How many times is it faster? What does that imply for a 5-hour for loop computation?
5. BONUS: Get uncertainties on the computing time estimation with `microbenchmark` (You might want to reduce the length of n for that).

Programming practice solutions part 3 - loops computation

```
n <- rep(1:50, each=100)
results_for <- data.frame(mean=NA, sd=NA, CV=NA, logmean=NA)
system.time( for(i in 1:length(n))
  {results_for[i, ] <- dep_n(n[i], 70,5)})

##    user  system elapsed
##    2.41    0.00    2.68

tail(results_for, 5)

##          mean       sd         CV  logmean
## 4996 70.07647 4.851932 0.06923768 69.90943
## 4997 70.30274 4.788358 0.06811055 70.14381
## 4998 69.69953 5.420097 0.07776375 69.49969
## 4999 69.35405 4.780247 0.06892527 69.19216
## 5000 68.47572 4.488871 0.06555420 68.32956
```

Programming practice solutions part 3 - loops computation

```
system.time(res_lapply <- sapply(n, dep_n, mean=70,sd=5)  )

##    user  system elapsed
##    0.23    0.00    0.34
```

In this case with (only) 5000 iterations, lapply is ca 7 times faster than the badly initiated for loop. 5 hrs of computation would reduce to 40 minutes. Notice you get similar to lapply speed results for properly initiated data.frames with the correct dimension.
For more speed hints, read win-vector.com efficient accumulation in R.
Remember: your code is much cleaner with lapply:

```
results <- matrix(NA, ncol=4, nrow=length(n2))
for(i in 1:length(n2)) results[i, ] <- dep_n(n2[i], 70,5)

results <- sapply(n2, dep_n, mean=70,sd=5)
```

Programming practice solutions part 3 - loops computation

```
n2 <- rep(1:50, each=10)

dep_n_for <- function()
 {results <- data.frame(mean=NA, sd=NA, CV=NA, logmean=NA)
  for(i in 1:length(n2)) results[i, ] <- dep_n(n2[i], 70,5)}

dep_n_for_good <- function()
 {results <- matrix(NA, ncol=4, nrow=length(n2))
  for(i in 1:length(n2)) results[i, ] <- dep_n(n2[i], 70,5)}

dep_n_sapply <- function()
{results <- sapply(n2, dep_n, mean=70,sd=5)}

mb <- microbenchmark(dep_n_for(), dep_n_for_good(),
                     dep_n_sapply())
save(mb, file="data/mb.Rdata")
```

Programming practice solutions part 3 - loops computation

```
load("data/mb.Rdata"); library(microbenchmark)
boxplot(mb, yaxt="n"); berryFunctions::logAxis(2)
```

Chapter practice: sample size dependency

Exercise 33: Programming part 4 - loops for plotting

1. Plot the mean estimate over sample size, using fully colored but semitransparent dots (see `rgb` or `berryFunctions::addAlpha`).
2. Add a nicely visible horizontal line at the population mean. (we drew random samples from some defined distribution, which is the general population whose parameters are usually unknown in real life).
3. BONUS: add lines limiting the 90% confidence region.
4. Set up a multipanel plot to automatically hold a figure for each of the rows of the previous results (mean, sd, CV, logmean). To automatically dimension the panels, you could use `berryFunctions::panelDim(n)`
5. With a for loop, fill each of the panels and add nice annotations.

Programming practice solutions part 4 - loops plotting

```
transp <- rgb(0,0,0, alpha=0.1)
plot(n, res_lapply["mean", ], pch=16, col=transp, cex=0.6)
abline(h=70, col=4, lwd=2)
```

Programming practice solutions part 4 - loops plotting

```
conf <- tapply(res_lapply["mean", ], n, quantile, probs=c(0.05, 0.95))
conf <- sapply(conf, I)
conf_x <- as.numeric(colnames(conf))
for(i in 1:2) lines(conf_x, conf[i, ], col=2, lwd=2)
```

Programming practice solutions part 4 - loops plotting

```
library(berryFunctions) # for panelDim

par(mfrow=panelDim(nrow(res_lapply)), mar=c(2,4,1,1),
    mgp=c(2.5,0.7,0), las=1 )

truevals <- c(mean=70, sd=5, CV=5/70, logmean=70)
for(nm in rownames(res_lapply))
  {
  plot(n, res_lapply[nm, ], ylab=nm, pch=16, col=transp)
  abline(h=truevals[nm], col=4, lwd=2)
  if(nm=="sd") points(60,2, col=2)
  }
```

Programming practice solutions part 4 - loops plotting

Outline

R course info
1. One-Session-Intro
2. Getting started: Background, GUI and first steps
3. Objects
4. "Real" data
5. Plotting
6. Character Operations
7. Conditions & loops
8. Functions & packages
9. Distributions
   Exploratory Data Analysis (EDA)
   Normal distribution
   Other distribution functions
   Beta distribution
10. Statistics
11. Time series handling and analysis
12. Spatial data and GIS functionality
13. Final tasks
Course plan

A quick example I

```
grades <- c(3.0, 2.3, 5, 1.3, 4, 1.7)
grades          # Show the object

## [1] 3.0 2.3 5.0 1.3 4.0 1.7

mode(grades)    # numeric

## [1] "numeric"

sum(grades)     # sum of all values

## [1] 17.3

diff(grades)    # difference from one value to the next

## [1] -0.7  2.7 -3.7  2.7 -2.3
```

```r
mean(grades)   # Average

## [1] 2.883333

median(grades) # median*

## [1] 2.65

var(grades)    # variance

## [1] 1.997667

sd(grades)     # Standard deviation

## [1] 1.413388
```

* If you sort all the numbers ascendingly, the median is in the middle. Thus, it is not as sensitive to outliers as the mean. We'll get back to this later on.

The dataset we'll be looking at

sources: mirlab.org, desirableplants.com, 3.bp.blogspot.com

iris data set

```r
head(iris)

##   Sepal.Length Sepal.Width Petal.Length Petal.Width Species
## 1          5.1         3.5          1.4         0.2  setosa
## 2          4.9         3.0          1.4         0.2  setosa
## 3          4.7         3.2          1.3         0.2  setosa
## 4          4.6         3.1          1.5         0.2  setosa
## 5          5.0         3.6          1.4         0.2  setosa
## 6          5.4         3.9          1.7         0.4  setosa
```

Exercise 34: EDA - Exploratory Data Analysis

1. Look at `iris` with `summary`.
2. Assign `iris$Sepal.Length` to an object with a short name.
3. Calculate `min` and `max`, the `median` and the median absolute deviation (`mad`), the quartiles and octiles (via `quantile`), the fourthspread (`IQR`) and `diff(range)` of the iris values.
4. With `par(mfrow=c(2,1))`, set the graphic device to contain two graphics.
5. Draw a horizontal `boxplot` in the upper window and compare it with the statistics calculated above. Interpret them.
6. What happens when the argument `notch` is set to true?
7. Draw a `hist`ogram with the bars filled with orange color, and experiment with the number of breaks.
8. BONUS: What are the (dis-)advantages of boxplots and histograms?

Mean vs. Median etc.

mathwithbaddrawings.com/2016/07/13/why-not-to-trust-statistics

Similar boxplots...

... different distributions!

Outline

R course info
1. One-Session-Intro
2. Getting started: Background, GUI and first steps
3. Objects
4. "Real" data
5. Plotting
6. Character Operations
7. Conditions & loops
8. Functions & packages
9. Distributions
   - Exploratory Data Analysis (EDA)
   - Normal distribution
   - Other distribution functions
   - Beta distribution
10. Statistics
11. Time series handling and analysis
12. Spatial data and GIS functionality
13. Final tasks

Course plan

Random numbers

R has a very good random number generator. If you want to set a starting point for it, you can use `set.seed(n)`, with n being some number you like. After R has set the seed, it will always generate the same "random" numbers. This creates reproducible numbers.

Exercise 35: Random numbers

1. With `sample`, put the numbers 5 to 15 in random order. Out of the possible numbers 1:3, draw 25 realizations.
2. Via `?Distributions`, find out how to generate 200 random numbers from the exponential distribution and look at those with a boxplot and a histogram (BONUS: look at `ecdf` and `density`).

Solution for exercise 35: random numbers

```
sample(5:15)  ;  sample(1:3, 25, replace=TRUE)  ;  r <- rexp(200)
par(mfrow=c(2,1), mar=c(2,2,0,0))
hist(r, breaks=20, col=3)
boxplot(r, horizontal=T, notch=T, col=3)
lines(density(r)$x, density(r)$y +par("usr")[3], lwd=3)
lines(0:50/10, dexp(0:50/10) +par("usr")[3], col=2)
```

Distributions: normal distribution I

Distributions: normal distribution II

`pnorm(q=1, mean=0, sd=1)` $=$ 84% of the values of a standard normal distribution (SND) with $\mu = 0$ and $\sigma = 1$ are smaller than 1.

Get familiar with the Gaussian distribution

Exercise 36: normal distribution

In 1981, Fries and Crapo estimated future life expectancy to be 85 years with a standard deviation of 4.5 years.

Fries, J., Crapo, L.: Vitality and Aging: Implications of the Rectangular Curve. Freeman & Co Publishers, San Francisco (1981)

1. Plot the distribution density curve
2. Plot it again using `normPlot` in the package `berryFunctions`.
3. What proportion of people would die before age 75?
   Is that a realistic likelihood?
4. How many Germans (pop ~80 mio) would exceed 90 years?
5. In which symmetric age range would 95% of the people die?
   Give the rough estimate and the exact number.
6. How likely is it to die at age 85.3?
7. What are the biggest problems with this task?

Solution for exercise 36: Normal distribution I

Examples taken from: Wolfgang Tschirk (2014): Statistik: Klassisch oder Bayes - Zwei Wege im Vergleich

```
plot(70:100, dnorm(70:100, 85, 4.5), type="l")
berryFunctions::normPlot(85, 4.5)
pnorm(75, 85, 4.5)*100 #  1.3%
(1-pnorm(90, 85, 4.5))*80e6   # 10.7 mio
85-4.5*2; 85+4.5*2 # 76, 94
qnorm(c(0.025, 0.975), 85, 4.5) # 76.2 - 93.8
```

The probability to die at age 85.3 is 0 percent, as there are infinite possibilities in a continuous distribution. (You could also die at 85.331761 years). That's why we look at probability "density" in intervals.
But: we don't know if life expectancy is normally distributed. We also don't know whether it is parametrized correctly.

Solution for exercise 36: Normal distribution II

```
## [1] 1.313415
## [1] 10660821
## [1] 76.18016 93.81984
```

Test for normality of a distribution

```
data <- rnorm(1000, mean=97, sd=8.9)
shapiro.test(data)
ks.test(data, "pnorm", mean(data), sd(data))
# if p > 0.05: accept Nullhypothesis
# (that data are normally distributed.)
```

More on slide 322 et sequentes.

Outline

R course info
1. One-Session-Intro
2. Getting started: Background, GUI and first steps
3. Objects
4. "Real" data
5. Plotting
6. Character Operations
7. Conditions & loops
8. Functions & packages
9. Distributions
   - Exploratory Data Analysis (EDA)
   - Normal distribution
   - Other distribution functions
   - Beta distribution
10. Statistics
11. Time series handling and analysis
12. Spatial data and GIS functionality
13. Final tasks

Course plan

Get familiar with the discrete Binomial distribution

Exercise 37: binomial distribution

149'291 of 279'371 students in Austria are female. Statistik Austria: Studierende in OEsterreich im Wintersemester 2009/10. Statistik Austria, Wien (2010). This is a population for which we know the actual proportion, which happens rarely in inferential statistics. 100 students are randomly chosen.

1. Guess how likely it is that the majority (at least half) of those are female.
2. Plot the probability for each reasonable possible outcome using `dbinom`. (This is the actual probability, not probability density, for each discrete number of females in a group of 100 randomly chosen students). Now guess again.
3. Actually calculate the probability.
4. At which proportion of females would you accuse the experimenter of selection bias (or cheating)?

Solution for exercise 37: Binomial distribution

```
plot(30:70, dbinom(x=30:70, size=100, prob=149291/279371))
abline(v=c(49.5, 53.438), h=0.025)
1-pbinom(q=49.5, size=100, prob=149291/279371)

## [1] 0.7852772
```

If the probability of the result happening by chance is under 5%, in this case ≤ 45 or ≥ 61 females (two-sided confidence interval).

Other distributions: density

Other distributions: cumulated

Overview of distributions in R

prefix	meaning	usage
d	**d**ensity	calculate probability (density) for value x
p	cumulated **p**robability	area under density curve up until value x
q	**q**uantile	reciprocal to p: calculate value x for a given cumulated probability
r	**r**andom	draw random numbers from distribution

distribution	parameters	type
binom	size, prob	discrete
pois	lambda	
norm	mean, sd	continuous
exp	rate	
beta	shape1, shape2	

Exercise 38: classical statistical analysis

1. Calculate `mean`, `var`, `sd` and standard error of the mean (SEM $= \frac{\sigma}{\sqrt{n}}$) of the `iris` sepal length data and interpret these values.
2. Visualize the theoretical distribution of the dataset. Use a sequence of values and calculate `pnorm` and `dnorm` on it with mean and sd according to the previous task.
3. Compare this with the actual distribution of the sample. First draw a histogram with `freq=FALSE`, then add the theoretical distribution with `lines`.
4. If this distribution were from the general and complete "population" of iris sepal lengths, we could say: 20% of the sepal lengths are smaller than a certain value. Use `qnorm` to find out this value. What is the limit of this approach?
5. BONUS: What are the (dis-)advantages of mean and median?

Outline

R course info
1. One-Session-Intro
2. Getting started: Background, GUI and first steps
3. Objects
4. "Real" data
5. Plotting
6. Character Operations
7. Conditions & loops
8. Functions & packages
9. Distributions
   - Exploratory Data Analysis (EDA)
   - Normal distribution
   - Other distribution functions
   - Beta distribution
10. Statistics
11. Time series handling and analysis
12. Spatial data and GIS functionality
13. Final tasks

Course plan

Beta distribution: motivating example

Imagine you are the scientific advisor to the government of India.
It has recently been found that some of the millions (yes, millions) of wells contain dangerous levels of arsenic.
If more than 25% of the wells are affected, the government will pass a law constraining well construction.
You sample 10 wells and find that 2 surpass the safety limit of arsenic concentration. What will you do?
To graph the uncertainty, you want to use the beta distribution.
You remember (from this class) that for a binomial trial, the two parameters can be defined as:
$\alpha - 1 =$ number of successes
$\beta - 1 =$ number of failures
What are the parameters in this case?

$$\alpha = 2 + 1 = 3$$
$$\beta = 10 - 2 + 1 = 9$$

Beta distribution: some theory + density plot

- Continuous, values between 0 and 1
- Suitable for proportions and probabilities
- Very versatile, different shapes
- Used extensively in Bayesian statistics, see e.g. Liu and Kong (2015).
- Two parameters: a=alpha=`shape1` and b=beta=`shape2`.

Exercise 39: Beta distribution density

1. Plot the beta distribution density (`dbeta`) for alpa=3 and beta=9.
2. If this describes the true distribution of contaminated well proportions across subregions of India, how likely is it to have a sample with 25% or more of the wells contaminated?
3. BONUS: Plot the distribution with `polygon`.

Two hints:

Hint 1: Create a vector from 0 to 1 with, say, 200 values.

Hint 2: Plot `dbeta(x)` over x using `type="l"`.

Solution to exercise 39: Beta density

```
proportion <- seq(0,1, len=200)
plot(proportion, dbeta(proportion, 3,9), type="l")
segments(x0=0.25, y0=-1, y1=3.097, col=2)
```

```
1-pbeta(0.25, 3,9)

## [1] 0.4552009
```

Beta parameters

Large α: HDI (Highest Density Interval) more to the right
Large β: HDI rather left, lower values
Both large: (*more samples*) narrow HDI

```
install.packages("berryFunctions")
```

```
library(berryFunctions) # >= version 1.9.6 (2015-12-18)
betaPlot(shape1=alpha, shape2=beta, ...)
betaPlotComp()
```

Beta parameters

```
betaPlot(14, 2.4, ylim=lim0(5))
```

Beta parameters

```
betaPlot(6, 16, ylim=lim0(5))
```

Beta parameters

```
betaPlot(10, 10, ylim=lim0(5))
```

Beta parameters

```
betaPlot(3, 3, ylim=lim0(5))
```

Beta parameters

```
betaPlot(1, 1, ylim=lim0(5))
```

Beta parameters

```
betaPlot(0.8, 2, ylim=lim0(5))
```

Beta parameters

```
betaPlot(0.4, 0.4, ylim=lim0(5))
```

a = 0.5
a = 1
a = 2
a = 3
a = 4
a = 10
b = 0.5
b = 1
b = 2
b = 3
b = 4
b = 10
a=0.5, b=0.5
a=1, b=0.5
a=2, b=0.5
a=3, b=0.5
a=4, b=0.5
a=10, b=0.5
a=0.5, b=1
a=1, b=1
a=2, b=1
a=3, b=1
a=4, b=1
a=10, b=1
a=0.5, b=2
a=1, b=2
a=2, b=2
a=3, b=2
a=4, b=2
a=10, b=2
a=0.5, b=3
a=1, b=3
a=2, b=3
a=3, b=3
a=4, b=3
a=10, b=3
a=0.5, b=4
a=1, b=4
a=2, b=4
a=3, b=4
a=4, b=4
a=10, b=4
a=0.5, b=10
a=1, b=10
a=2, b=10
a=3, b=10
a=4, b=10
a=10, b=10
0
1
2
3
4
0.0
0.5
1.0

Beta distribution properties

$$mean = \mu = \frac{a}{a+b} \qquad variance = \sigma^2 = \frac{ab}{(a+b)^2 * (a+b+1)}$$

With these formulas, if a and b $\gg 1$, you can estimate an approximation to the normal distribution.

$$mode = density\ peak = m = \frac{a-1}{a+b-2} \qquad for\ a, b > 1$$

If you want to set the mode at a certain value, you can compute beta with

$$b = \frac{a-1}{m} - a + 2 \qquad \text{and alpha with} \qquad a = \frac{(2-b-1/m)*m}{m-1}$$

Beta distribution specification

Exercise 40: Beta distribution parameter determination

You want to specify a distribution with the peak at 90%, reached in a sample of 100.

1. What are the parameters?
2. What does the distribution look like? (Graph it)
3. BONUS: How does the HDI (highest density interval) width change for a sample size of 10?

Beta distribution parametrization solution

```
v <- seq(0,1, len=200)
plot(v, dbeta(v, 91,11), type="l", las=1)
lines(v, dbeta(v, 10,2), col=2)
points(qbeta(c(0.1, 0.9), 91,11), rep(-0.5,2), pch=3)
points(qbeta(c(0.1, 0.9), 10,2), rep(-0.5,2), pch=3, col=2)
```

Bayesian inference with beta distribution

Prior: weak knowledge that true proportion of cats among pets must be around 10 to 30%, but may also be more.
Data: observation in survey: 35 of 100 households with a pet have a cat.
Posterior beta parameters: a_prior + successes, b_prior + failures

```
betaPlot(3, 9, ylim=lim0(10), cum=F, mar=c(2,2,0,0), keeppar=T)
lines(x, dbeta(x, 3+35, 9+65), lwd=2, col=3)
```

Shift + scale values

If values do not lie between 0 and 1, but between m and n, you can transform the raw values (y) to the 0:1 space (y') with

$$y' = \frac{(y-m)}{(n-m)}$$

and beta values (y') to raw values (y) with

$$y = y' * (n - m) + m$$

Outlook: used for beta regression, see Liu and Kong (2015): zoib: An R Package for Bayesian Inference for Beta Regression and Zero/One Inflated Beta Regression. In: the R Journal Vol. 7/2, December 2015

Shift + scale values

```
x <- 400:580; m <- 120 ; n <- 570
plot(x, dbeta((x-m)/(n-m),30,4), type="l")
lines(x, dnorm((x-m)/(n-m),30/34, sd=sqrt(120/(34^2*35))), col=2)
```

Shift + scale values

```
m <- 120 ; n <- 570; set.seed(1)
x <- rbeta(800,30,4) * (n-m)+m
library(extremeStat) # github.com/brry/extremeStat
plotLfit(distLfit(x, quiet=T), breaks=30, nbest=11, legargs=c(x="left"))
```

Outline

R course info
1. One-Session-Intro
2. Getting started: Background, GUI and first steps
3. Objects
4. "Real" data
5. Plotting
6. Character Operations
7. Conditions & loops
8. Functions & packages
9. Distributions
10. Statistics
    Simpsons Paradox
    Normality tests
    Confidence Intervals
    Linear regression
11. Time series handling and analysis
12. Spatial data and GIS functionality
13. Final tasks
Course plan

Simpson's Paradox

- Kievit et al (2015): Simpson's paradox in psychological science: a practical guide (Frontiers in Psychology)
- vudlab app
- Wikipedia entry
- 2016 example: development of crime rates in the USA
- minutephysics video (2017)

Simpson's Paradox: Kidney stone treatment success rate

	open surgery	small puncture
small stones	$\frac{81}{87} = \mathbf{93\%}$	$\frac{234}{270} = 87\%$
large stones	$\frac{192}{263} = \mathbf{73\%}$	$\frac{55}{80} = 69\%$
together	$\frac{273}{350} = 78\%$	$\frac{289}{350} = \mathbf{83\%}$

Wikipedia, Julious + Mullee (1994)

In less severe cases (small kidney stones), doctors favor percutaneous nephrolithotomy (which involves only a small puncture). Doctors tend to give the severe cases (large stones) the better treatment (open surgery). The success rate is more strongly influenced by the severity of the case than by the choice of treatment. When the less effective treatment (small puncture) is applied more frequently to less severe cases, it can appear to be a more effective treatment.

Simpson's Exercise

Exercise 41: Simpson

Visualize farming.txt *(rightclick **Raw**, save as)*, a fictional dataset measuring crop yield on 30 study fields after pesticide application.

Farming solution I

Farming solution II

Outline

R course info
1. One-Session-Intro
2. Getting started: Background, GUI and first steps
3. Objects
4. "Real" data
5. Plotting
6. Character Operations
7. Conditions & loops
8. Functions & packages
9. Distributions
10. Statistics
    - Simpsons Paradox
    - Normality tests
    - Confidence Intervals
    - Linear regression
11. Time series handling and analysis
12. Spatial data and GIS functionality
13. Final tasks

Course plan

Normality Test: Kolmogorov-Smirnov

- If a population is normally distributed, it is described by only two parameters: the mean (position) and the sd (width, dispersion) of the bell shaped curve.
- This is an important assumption for many classical statistical methods.
- Whether a dataset is normally distributed can be checked with a histogram (visually effective, but the class limits are subjective), with qqplots (I don't find them very intuitive), or with statistical tests.
-

```
data <- rnorm(1000, mean=97, sd=8.9)
shapiro.test(data)
ks.test(data, "pnorm", mean(data), sd(data))
# if p > 0.05: accept Nullhypothesis that data are normally distributed.

if(!requireNamespace("nortest")) install.packages("nortest")
library(nortest)          # with Lilliefors-correction!
help(package="nortest")
lillie.test(data)  # Lilliefors (Kolmogorov-Smirnov) test for normality
ad.test(data)      # Anderson-Darling test for normality
cvm.test(data)     # Cramer-von Mises test for normality
pearson.test(data) # Pearson chi-square test for normality
sf.test(data)      # Shapiro-Francia test for normality
```

Normality Test: Kolmogorov-Smirnov

KS Hypothesis Test: Reject the null hypothesis (H0) that the values are drawn from a normal distribution if $D < \frac{k_\alpha}{\sqrt{n}}$.

$D = max(\mid F_{(n)}(x) - F(x) \mid)$ *Difference between empirical and statistical (theoretical, population) Cumulated Density Function (CDF)*

$k_\alpha = \frac{\sqrt{-0.5 * ln(\frac{\alpha}{2})}}{\sqrt{n}}$ $(for\ n > 35)$ α often 0.05 (95% confidence)

Normality Test: Kolmogorov-Smirnov

Outline

R course info
1. One-Session-Intro
2. Getting started: Background, GUI and first steps
3. Objects
4. "Real" data
5. Plotting
6. Character Operations
7. Conditions & loops
8. Functions & packages
9. Distributions
10. Statistics
    Simpsons Paradox
    Normality tests
    Confidence Intervals
    Linear regression
11. Time series handling and analysis
12. Spatial data and GIS functionality
13. Final tasks
Course plan

Background confidence intervals

- About 70% of the values in a Gaussian distribution lie between mean-1sd and mean+1sd, as is shown by `pnorm(1) - pnorm(-1)`: `0.6826895`.
- 95% of the values are between mean $\pm$ 1.96 sd, as is shown by `qnorm(0.975)`: `1.959964`. (As the bell curve is symmetrical, we want to know below what value 97.5% of the values are in the cumulated density).
- This is the famous parameter in calculating the limits of confidence intervals (CI).

$$CI = \mu \pm p * \frac{sd}{\sqrt{n}}$$

$$p = \texttt{qt(1-alpha/2, df=n-1)}$$

Parameter confidence intervals

en.wikipedia.org/wiki/Student's_t-distribution#Table_of_selected_values
For a two-sided confidence interval with `qt(1-alpha/2, df=n-1)`:

	a=0.01	a=0.05	a=0.10
n=10	3.2498	2.2622	1.8331
n=30	2.7564	2.0452	1.6991
n=50	2.6800	2.0096	1.6766
n=100	2.6264	1.9842	1.6604
n=1000	2.5808	1.9623	1.6464

code for generating this table:

```
alpha <- c(0.01, 0.05, 0.10)
n <- c(10, 30, 50, 100, 1000)
ttab <- t(sapply(n, function(x) qt(1-alpha/2 ,df=x-1)))
colnames(ttab) <- paste0("a=",alpha)
rownames(ttab) <- paste0("n=",n)
ttab
```

CI example

Exercise 42: Confidence intervals

1. Comment the code below.
2. plot the points along a number line and add the mean value with `points` and the confidence interval with `arrows` with `angle=90, code=3`. BONUS: plot the points as filled dots in a semitransparent color, see `rgb`.

```
values <- rnorm(80, 53, 4)
m <- mean(values)   ; m #
v <- var(values)    ; v #
n <- length(values) ; n #
p <- qnorm(0.975)   ; p #
p <- qt(0.975, df=n-1)  ; p #
cl <- m - p * sqrt(v/n) ; cl #
cu <- m + p * sqrt(v/n) ; cu #
```

CI in a faster way

Scripting this manually would take too long:

```
m <- mean(values)
v <- var(values)
n <- length(values)
p <- qt(0.975, df=n-1)

m + c(-1,1)* p * sqrt(v/n)

## [1] 52.34151 54.00713
```

You can use the side effect of `t.test`:

```
t.test(values, conf.level=.95)$conf.int

## [1] 52.34151 54.00713
## attr(,"conf.level")
## [1] 0.95
```

Outline

R course info
1. One-Session-Intro
2. Getting started: Background, GUI and first steps
3. Objects
4. "Real" data
5. Plotting
6. Character Operations
7. Conditions & loops
8. Functions & packages
9. Distributions
10. Statistics
    Simpsons Paradox
    Normality tests
    Confidence Intervals
    Linear regression
11. Time series handling and analysis
12. Spatial data and GIS functionality
13. Final tasks
Course plan

Linear Regression

This section (linear models) was originally written by Matthias Seibert (GFZ).
It is excluded from this main document and can be obtained as pdf.

Storks Deliver Babies ($p = 0.008$)

Outline

R course info
1. One-Session-Intro
2. Getting started: Background, GUI and first steps
3. Objects
4. "Real" data
5. Plotting
6. Character Operations
7. Conditions & loops
8. Functions & packages
9. Distributions
10. Statistics
11. Time series handling and analysis
    Date and time formatting
    Time series
12. Spatial data and GIS functionality
13. Final tasks
Course plan

Task

Your professor asks you to visually examine temperature and precipitation trends at certain meteorological stations in Germany. She hands you the files Potsdam.txt and Zugspitze.txt *(rightclick **Raw**, save as)*. How do you approach the project?

Data selection, download, processing and saving:

```
library(rdwd) # github.com/brry/rdwd # not yet on CRAN
links <- selectDWD(c("Potsdam","Zugspitze"), current=TRUE,
                   res="monthly", var="kl", time="hist", outvec=TRUE)
clim <- dataDWD(links, dir="data")
write.table(clim[[1]], file="data/Potsdam.txt", row.names=F, quote=F)
write.table(clim[[2]], file="data/Zugspitze.txt", row.names=F, quote=F)
```

```
potsdam$date <- as.Date(as.character(potsdam$MESS_DATUM_BEGINN), "%Y%m%d")
```

Outline

R course info
1. One-Session-Intro
2. Getting started: Background, GUI and first steps
3. Objects
4. "Real" data
5. Plotting
6. Character Operations
7. Conditions & loops
8. Functions & packages
9. Distributions
10. Statistics
11. Time series handling and analysis
    Date and time formatting
    Time series
12. Spatial data and GIS functionality
13. Final tasks
Course plan

Authorship note

This section (time series) was originally written by Matthias Seibert (GFZ). It is currently excluded from this main document but can be obtained as pdf.

```
library(xts)
```

Outline

R course info
1. One-Session-Intro
2. Getting started: Background, GUI and first steps
3. Objects
4. "Real" data
5. Plotting
6. Character Operations
7. Conditions & loops
8. Functions & packages
9. Distributions
10. Statistics
11. Time series handling and analysis
12. Spatial data and GIS functionality
    Geostatistics: Kriging
    R as GIS
13. Final tasks
Course plan

Kriging: Overview

Geostatistics: Kriging - spatial interpolation between points, using semivariance

1. Packages
2. read shapefile
3. Variogram
4. Kriging
5. Plotting

Kriging: packages

```r
install.packages("rgeos")
install.packages("sf")
install.packages("geoR")
```

```r
library(sf)    # for st_read (read shapefiles),
               # st_centroid, st_area, st_union
library(geoR) # as.geodata, variog, variofit,
               # krige.control, krige.conv, legend.krige
```

Kriging: read shapefile / few points for demonstration

```
x <- c(1,1,2,2,3,3,3,4,4,5,6,6,6)
y <- c(4,7,3,6,2,4,6,2,6,5,1,5,7)
z <- c(5,9,2,6,3,5,9,4,8,8,3,6,7)
plot(x,y, pch="+", cex=z/4)
```

Kriging: read shapefile II

```
GEODATA <- as.geodata(cbind(x,y,z))
plot(GEODATA)
```

Kriging: Variogram I

```
EMP_VARIOGRAM <- variog(GEODATA)

## variog: computing omnidirectional variogram

FIT_VARIOGRAM <- variofit(EMP_VARIOGRAM)

## variofit: covariance model used is matern
## variofit: weights used: npairs
## variofit: minimisation function used: optim

## Warning in variofit(EMP_VARIOGRAM): initial values not provided - running the
default search

## variofit: searching for best initial value ... selected values:
##                sigmasq phi    tausq kappa
## initial.value "9.19"  "3.65" "0"   "0.5"
## status        "est"   "est"  "est" "fix"
## loss value: 401.578968904954
```

Kriging: Variogram II

```
plot(EMP_VARIOGRAM)
lines(FIT_VARIOGRAM)
```

Kriging: Kriging

```
res <- 0.1
grid <- expand.grid(seq(min(x),max(x),res),
                    seq(min(y),max(y),res))
krico <- krige.control(type.krige="OK",
                       obj.model=FIT_VARIOGRAM)
krobj <- krige.conv(GEODATA,
                    locations=grid, krige=krico)

## krige.conv: model with constant mean
## krige.conv: Kriging performed using global neighbourhood

# KRigingObjekt
```

Kriging: Plotting I

```
image(krobj, col=rainbow2(100))
legend.krige(col=rainbow2(100),
             x.leg=c(6.2,6.7), y.leg=c(2,6),
             vert=T, off=-0.5,
             values=krobj$predict)
contour(krobj, add=T)
colPoints(x,y,z, col=rainbow2(100), legend=F)
points(x,y)
```

Kriging: Plotting II

Kriging: Plotting III

```
library("berryFunctions") # scatterpoints by color
colPoints(x,y,z, add=F, cex=2, legargs=list(y1=0.8,y2=1))
```

Kriging: Plotting IV

```
colPoints(grid[ ,1], grid[ ,2], krobj$predict, add=F,
          cex=2, col2=NA, legargs=list(y1=0.8,y2=1))
```

Time for a real dataset

Precipitation from ca 250 gauges in Brandenburg as Thiessen Polygons with steep gradients at edges:

Time for a real dataset

Exercise 43: Kriging

1. Load and plot the shapefile in PrecBrandenburg.zip with `sf::st_read`.
2. With `colPoints` in the package `berryFunctions`, add the precipitation values at the centroids of the polygons.
3. Calculate the variogram and fit a semivariance curve.
4. Perform kriging on a grid with a useful resolution (keep in mind that computing time rises exponentially with grid size).
5. Plot the interpolated values with `image` or an equivalent (Rclick 4.15) and add contour lines.
6. What went wrong? (if you used the defaults, the result will be dissatisfying.) How can you fix it?

Solution for exercise 43.1-2: Kriging Data

```
# Shapefile:
p <- sf::st_read("data/PrecBrandenburg/niederschlag.shp",
                 quiet=TRUE)
# Plot prep
pcol <- colorRampPalette(c("red","yellow","blue"))(50)
clss <- berryFunctions::classify(p$P1, breaks=50)$index
# Plot
par(mar = c(0,0,1.2,0))
plot(p, col=pcol[clss], max.plot=1) # P1: Precipitation
# kriging coordinates
cent <- sf::st_centroid(p)
berryFunctions::colPoints(cent$x, cent$y, p$P1, add=T, cex=0.7,
                          legargs=list(y1=0.8,y2=1), col=pcol)
points(cent$x, cent$y, cex=0.7)
```

Solution for exercise 43.3: Variogram

```
library(geoR)
# Semivariance:
geoprec <- as.geodata(cbind(cent$x,cent$y,p$P1))
vario <- variog(geoprec, max.dist=130000)

## variog: computing omnidirectional variogram

fit <- variofit(vario)

## variofit: covariance model used is matern
## variofit: weights used: npairs
## variofit: minimisation function used: optim

## Warning in variofit(vario):  initial values not provided - running the default
search

## variofit: searching for best initial value ... selected values:
##                sigmasq   phi        tausq kappa
## initial.value "1326.72" "19999.93" "0"   "0.5"
## status        "est"     "est"      "est" "fix"
## loss value: 107266266.76371
```

Solution for exercise 43.3: Variogram

```
plot(vario) ; lines(fit)
# distance to closest other point:
d <- sapply(1:nrow(cent), function(i) min(berryFunctions::distance(
                          cent$x[i], cent$y[i], cent$x[-i], cent$y[-i])))
hist(d/1000, breaks=20, main="distance to closest gauge [km]")
mean(d) # 8 km

## [1] 8165.633
```

Solution for exercise 43.4-5: Kriging

```
# Kriging:
res <- 1000 # 1 km, since stations are 8 km apart on average
grid <- expand.grid(seq(min(cent$x),max(cent$x),res),
                    seq(min(cent$y),max(cent$y),res))
krico <- krige.control(type.krige="OK", obj.model=fit)
krobj <- krige.conv(geoprec, locations=grid, krige=krico)

## krige.conv: model with constant mean
## krige.conv: Kriging performed using global neighbourhood

# Set values outside of Brandenburg to NA:
grid_sf <- sf::st_as_sf(grid, coords=1:2, crs=sf::st_crs(p))
isinp <- sapply(sf::st_within(grid_sf, p), length) > 0
krobj2 <- krobj
krobj2$predict[!isinp] <- NA
```

Solution for exercise 43.5: Kriging Visualization

```
geoR:::image.kriging(krobj2, col=pcol)

## Error in image.default(x = c(3252470, 3253470, 3254470,
3255470, 3256470, :  object 'pcol' not found

colPoints(cent$x, cent$y, p$P1, col=pcol, zlab="Prec", cex=0.7,
     legargs=list(y1=0.1,y2=0.8, x1=0.78, x2=0.87, horizontal=F))

## Error in plot.xy(xy.coords(x, y), type = type, ...):  plot.new
has not been called yet

plot(p, add=T, col=NA, border=8)#; points(cent$x,cent$y, cex=0.7)

## Error in polypath(p_bind(x[[i]]), border = border[i], lty =
lty[i], lwd = lwd[i], :  plot.new has not been called yet
```

Outline

R course info
1. One-Session-Intro
2. Getting started: Background, GUI and first steps
3. Objects
4. "Real" data
5. Plotting
6. Character Operations
7. Conditions & loops
8. Functions & packages
9. Distributions
10. Statistics
11. Time series handling and analysis
12. Spatial data and GIS functionality
    Geostatistics: Kriging
    R as GIS
13. Final tasks
Course plan

R geo, further material

Use the sf, mapview, osmar and osmplotr packages!

Combine city names with geolocations:
blog.revolutionanalytics.com/2015/11/marriott.html

For this section (spatial data / GIS), a lot was originally written by Matthias Seibert (GFZ). With the advance of the `sf` package (late 2016), that material is mostly outdated. Until new material is created here, his slides can be obtained as pdf.

Outline

R course info
1. One-Session-Intro
2. Getting started: Background, GUI and first steps
3. Objects
4. "Real" data
5. Plotting
6. Character Operations
7. Conditions & loops
8. Functions & packages
9. Distributions
10. Statistics
11. Time series handling and analysis
12. Spatial data and GIS functionality
13. Final tasks
    Practice tasks
    Exam task
Course plan

Exercise 44: Final exercises to solve at home I

1. What is the difference between `c(5,3,-8)` and `vec <- c(5,3,-8)`?
2. What methods do you know to generate a vector?
3. What are object, element, command, argument, assignment, Workspace, Working Directory?
4. What data and object types do you know?
5. How do you call the help about the `lines` command?
6. How do you read a text file? What are the main arguments of the function?
7. How do you examine the imported table?
8. How do you obtain / change subsets of the table (column, row, element)?

Exercise 45: Final exercises to solve at home II

1. How often is Peter Pan mentioned in the E-book? peterpan.txt *(rightclick **Raw**, save as)*. Exclude the meta data about the book!
2. Interpret the results from `pairs(iris)` and `cor(iris[ ,1:4])`. Why does `cor(iris)` not work?
3. What are the most important functions and arguments for creating graphics?
4. Write a for loop including a while statement to distribute points randomly, but with a certain minimal distance to each other, along a line (segment sampling design). A solution is in my RclickHandbuch Chapter 10.4.
5. What functions and packages are useful for dealing with time series?

Outline

R course info
1. One-Session-Intro
2. Getting started: Background, GUI and first steps
3. Objects
4. "Real" data
5. Plotting
6. Character Operations
7. Conditions & loops
8. Functions & packages
9. Distributions
10. Statistics
11. Time series handling and analysis
12. Spatial data and GIS functionality
13. Final tasks
    Practice tasks
    Exam task
Course plan

Exercise 46: Final exam

1. Download a long time series of weather data (e.g. DWD, NOAA), see slide 141.
2. Read the data into R and control the data types. Change the date (or time) to appropriate types with `as.Date`, `as.POSIXct` or `strptime`.
3. Write a subsection of the data (eg your birth year) to a tab-separated file so it's easy to copypaste this to Excel/Calc.
4. Plot the development of some aggregate (e.g. monthly 90% Quantile of windspeed, annual precipitation sum or temperature mean depending on hour of the day). Hints: `tapply`, `strftime`, `berryFunctions::monthLab`
5. Examine `cor`relations between variables.
6. Write a small report on your data analysis project with max 3 pages, including (beautiful) graphs. You can mail the code in a separate file.
   This is a requirement for the participation certificate with credit points.
7. BONUS 1: Write the report via Rnw, Rhtml, Rmd or Rpres (see slide 140).
8. BONUS 2: Make some interactive stuff (e.g. user can choose decade of analysis), e.g. via HTMLwidgets or Shiny (see more). This is a lot of initial effort, but you'll enable an awesome interactive graphical analyses!

Outline

R course info
1. One-Session-Intro
2. Getting started: Background, GUI and first steps
3. Objects
4. "Real" data
5. Plotting
6. Character Operations
7. Conditions & loops
8. Functions & packages
9. Distributions
10. Statistics
11. Time series handling and analysis
12. Spatial data and GIS functionality
13. Final tasks

Course plan
- Session 1/7: Why R, read file, select and plot data
- Session 2/7: Objects, file reading, NAs, data merging
- Session 3/7: publication-ready graphics, if-else conditionals
- Session 4/7: for loops, apply functions
- Session 5/7: functions
- Session 6/7: statistics
- Session 7/7: shapefiles (R as GIS)
- Feedback, additional material

Session 1: Aim (Chapter 1)

get a general impression on how R works, without going too much into technical detail
afterwards, you should be able to:

- start a new script in Rstudio and execute lines of code
- read a data file into R
- select a column and rows that fullfill a certain criterion
- generate basic graphics with annotation and added elements
- open and read the documentation for R functions

Jump to Rstudio

Session 1: Recap (They tried to make me go to recap and I said, 'Yes, yes, yes.')

- R is awesome. You're here, thus you will be R-some, too
- Console for code execution (R), ready with `>`, waiting with `+`
- Script for code writing (you) + exchange
- Objects are created with the assignment operator `<-`
- Get help with `help(median)`, `?matrix`, or pressing F1
- Create vectors with `c(42,3,-4)`, `1:n`, `seq(2,5,len=30)`
- `data.frame`s hold tables with one data type per column
- `read.table`, with header=T to read files into R
- Index objects with `values[8:5]`, `tab[4,2:6]`
- df columns with `tab[ ,3]`, `tab[ ,"precip"]`, `tab$wind`
- `hist(vals)`; `plot(x,y, las=1, pch=16, type="b")`

Session 1: Homework

- If not already done, install R and Rstudio (see github.com/brry/course#install)
- If you still need it, get a PC-Pool Account (Laptop with WLAN access is fine, too)
- Complete all unfinished exercises from today
- Print a RefCard (see slide 47) and mark all the items that you have understood

Outline

R course info
1. One-Session-Intro
2. Getting started: Background, GUI and first steps
3. Objects
4. "Real" data
5. Plotting
6. Character Operations
7. Conditions & loops
8. Functions & packages
9. Distributions
10. Statistics
11. Time series handling and analysis
12. Spatial data and GIS functionality
13. Final tasks

Course plan
- Session 1/7: Why R, read file, select and plot data
- Session 2/7: Objects, file reading, NAs, data merging
- Session 3/7: publication-ready graphics, if-else conditionals
- Session 4/7: for loops, apply functions
- Session 5/7: functions
- Session 6/7: statistics
- Session 7/7: shapefiles (R as GIS)
- Feedback, additional material

Session 2: Aim (Chapters 2 - 4.3)

- itensify and fortify the knowledge obtained in session 1
- learn about NAs and data merging

afterwards, you should be able to:

- install and load add-on packages written by the R community
- perform and visualize linear regression
- find the appropriate place and way to get help if you're stuck
- find an overview of common data and object types
- merge two datasets together
- ignore NAs
- apply a function to each column / row of a dataset

Repetition / application of content from last week

In groups of two or three, please take turns solving the following tasks. Pseudo-Code is fine, als long as the syntax is correct. This is for real life, not school, so feel free to use any source of help and inspiration ;-)

1. What program do we use to access R and what is typically in the four panels?
2. Assign a vector with the names of your group members (character strings!) to an object with a useful name.
3. Return all values of that vector except for the second.
4. What is the easiest way to open the help documentation of a command?
5. In a project handling several files, where, why and how do you use `setwd()`?
6. Read the data in the imaginary file `Wolf_Observations.txt` into R.
7. What are the two important functions to check whether it was read correctly?
8. Code two ways to select a column from a `data.frame`.
9. Get all the data in the 6th and 8th row of a df.
10. How would you plot the wolf pack size over the distance from the coast?
11. With which arguments to `plot()` would you make the graph more informative and appealing?

Recap solutions

1. Rstudio: Scripts, Code execution, Workspace/history, help/packages/plots
2. groupnames <- c("AA","BB","CC","DD")
3. groupnames[-2]
4. put the cursor on it, press key F1
5. At top of script, setwd("C:/Some/path"), so we can use relative filenames because they are short and make scripts easier to share
6. wolf <- read.table("Wolf_Observations.txt", header=TRUE)
7. head(wolf); str(wolf)
8. df$column; df[,"column"]
9. df[c(6,8),]
10. plot(wolf$packsize, wolf$distance_coast)
11. main="Title", las=1, xlab="label", ylab="label"

Please judge the difficulty of the previous tasks

```
plot(1:10, type="n", xlim=c(-1,11), ann=FALSE, axes=FALSE)
axis(side=1, at=c(0,5,10))
text(x=c(0,5,10), y=rep(6,3), c("too\neasy",
     "just\nright", "too\nhard"))
```

Session 2: Take home message

- Packages are basically (documented) scripts from other people → `install.packages` and `library`
- Reading data: `setwd`, `dir`, `read.table`, `str`
- Function documentation with `help` (or F1), StackOverflow for questions, Reference Cards (slide 47) for an overview and books / tutorials (slide 48) for self-learning
- Objects (vector, data.frame, matrix, list, function) can have several data types (numeric, logical, character), see slide 108
- `rbind` and `cbind` to join data.frames, `merge` to (surprise) merge them.
- `na.rm` argument in many functions, `na.omit` command otherwise

Session 2: Homework

1. Complete all unfinished exercises up to Nr 12.
2. Update your RefCard: mark all the items you learned about today
3. BONUS 1: How can you get `tab[x==7, "ColName"]` in $ notation?
4. BONUS 2: From the Rstudio keyboard shortcuts, choose a few that seem useful to you and try them out. Prepare to tell your classmates about them next week.
5. BONUS 3: Solve exercise 13 (factors, tapply) using chapter 4.2

You can send me your homework if you want comments.

Outline

R course info
1. One-Session-Intro
2. Getting started: Background, GUI and first steps
3. Objects
4. "Real" data
5. Plotting
6. Character Operations
7. Conditions & loops
8. Functions & packages
9. Distributions
10. Statistics
11. Time series handling and analysis
12. Spatial data and GIS functionality
13. Final tasks

Course plan
- Session 1/7: Why R, read file, select and plot data
- Session 2/7: Objects, file reading, NAs, data merging
- Session 3/7: publication-ready graphics, if-else conditionals
- Session 4/7: for loops, apply functions
- Session 5/7: functions
- Session 6/7: statistics
- Session 7/7: shapefiles (R as GIS)
- Feedback, additional material

to R or not to R

Lucius Annaeus Seneca (4BC - 65AD):

To err is human

to R is better

Session 3: Aim (Chapter 5 + 7.1)

- export publication-ready graphics
- conditional code execution (if-else)

afterwards, you should be able to:

- create a plot with multiple panels
- reproducibly save figures with useful settings
- make reasonable guesses about logical values by looking at code
- write conditionally executed code using if/else
- decide whether to use `if(cond) A else B` or `ifelse(cond, A, B)`

Recap from last two sessions

Please fill out the recap online:

bit.ly/recapR

Session 3: Recap

- Multiple figures in one graph with `par(mfrow)` / `par(mfcol)` or `layout`
- Export graphics with `png` or `pdf` with good size and resolution settings.
- `if(TRUE) message("Yo!") else message("Dude...")`
- `ifelse(c(T,T,F,T), 7, else 7.3)` for vectors

Session 3: Homework

1. Complete all unfinished exercises we started
2. What is the difference between `par(mfrow)`, `mfcol` and `layout`?
3. Find some data (e.g. attenu, freeny or rock from `datasets`) and plot several images in one multipanel graphic (e.g. scatterplots, line graphs, histograms, boxplots, pie charts, ...)
4. Update your RefCard: mark all the items you learned about today
5. BONUS 1: What is the source code difference between `points` and `lines`? You will need `methods(points)` to figure out what the default `UseMethod` is.
6. BONUS 2: On your RefCard, find something new that you want to present to your peers next week

Outline

R course info
1. One-Session-Intro
2. Getting started: Background, GUI and first steps
3. Objects
4. "Real" data
5. Plotting
6. Character Operations
7. Conditions & loops
8. Functions & packages
9. Distributions
10. Statistics
11. Time series handling and analysis
12. Spatial data and GIS functionality
13. Final tasks

Course plan
- Session 1/7: Why R, read file, select and plot data
- Session 2/7: Objects, file reading, NAs, data merging
- Session 3/7: publication-ready graphics, if-else conditionals
- Session 4/7: for loops, apply functions
- Session 5/7: functions
- Session 6/7: statistics
- Session 7/7: shapefiles (R as GIS)
- Feedback, additional material

Unicode

Collaborative editing can quickly become a textual rap battle fought with increasingly convoluted invocations of U+202a to U+202e (xkcd.com/1137)

Session 4: Aim (Chapter 7.2)

- repetitional coding (for-loops)
afterwards, you should be able to:

- explain the concept of a loop
- write simple for-loops
- structurally know how to use the lapply function

bit.ly/recapRif

Session 4: Recap

- loops repeat a block of code with a different `i` each time
- `for(i in 1:20) plot(df[,i], main=colnames(df)[i])`
- `for(cn in colnames(df)) plot(df[,cn], main=cn)`
- for loops should not be called too often, as they are slow
- instead: vectorize, use lapply, write C++ code

Session 4: Homework

1. Finish all the started exercises
2. Update your RefCard: mark all the items you learned about today

Outline

R course info
1. One-Session-Intro
2. Getting started: Background, GUI and first steps
3. Objects
4. "Real" data
5. Plotting
6. Character Operations
7. Conditions & loops
8. Functions & packages
9. Distributions
10. Statistics
11. Time series handling and analysis
12. Spatial data and GIS functionality
13. Final tasks

Course plan
- Session 1/7: Why R, read file, select and plot data
- Session 2/7: Objects, file reading, NAs, data merging
- Session 3/7: publication-ready graphics, if-else conditionals
- Session 4/7: for loops, apply functions
- Session 5/7: functions
- Session 6/7: statistics
- Session 7/7: shapefiles (R as GIS)
- Feedback, additional material

Today's plan

1. if else + for loop Recap
2. writing functions
3. debugging functions

recap if else I

1. Create a new R file and write `x <- 3.14` into it.
2. Now assign the absolute value of x to `y` by using conditional code execution (control structures).
3. `source` the complete document.
4. Test the result of y by setting `x <- -007` and running the document again.
5. BONUS: Make it also work for vectors like `x <- (-5):8` .

```
x <- -5:8
y <- ifelse(x<0, -x, x)
y

##  [1] 5 4 3 2 1 0 1 2 3 4 5 6 7 8
```

recap if else II

```
(  requireNamespace("some_package", quietly=TRUE)  )

## [1] FALSE
```

invisibly returns TRUE if it succeeds loading a package. The outer brackets are for printing in the slides.

1. Use it to conditionally install the package quantmod (i.e. if it is not already available).

```
if(!requireNamespace("quantmod")) install.packages("quantmod")

## Loading required namespace:  quantmod
```

Small research project

Please write down the answers to the following questions / instructions as pseudocode

- What do you do to start a (small) research project?
- Read a file into R where columns are tab-separated and the decimal marker is German.
- In a data set with monthly weather records (Potsdam.txt *(rightclick **Raw**, save as)*): Get the average temperature of months with more than 90 mm rainfall.
- Visually compare wind speed and rainfall.
- Describe and visualize the distribution of relative humidity.

for loop

- Plot the Apple stocks over date (stocks.txt *(rightclick **Raw**, save as)*) as a line graph.
- With a for loop, add all other companies in the same plot
- BONUS: First create a vector with 6 different colors, then use that in the for loop to color the lines
- BONUS: Add a legend with the same colors

Recap, Homework

Please select the topic(s) for next week online:

bit.ly/selectR

Outline

R course info
1. One-Session-Intro
2. Getting started: Background, GUI and first steps
3. Objects
4. "Real" data
5. Plotting
6. Character Operations
7. Conditions & loops
8. Functions & packages
9. Distributions
10. Statistics
11. Time series handling and analysis
12. Spatial data and GIS functionality
13. Final tasks

Course plan
- Session 1/7: Why R, read file, select and plot data
- Session 2/7: Objects, file reading, NAs, data merging
- Session 3/7: publication-ready graphics, if-else conditionals
- Session 4/7: for loops, apply functions
- Session 5/7: functions
- Session 6/7: statistics
- Session 7/7: shapefiles (R as GIS)
- Feedback, additional material

Outline

R course info
1. One-Session-Intro
2. Getting started: Background, GUI and first steps
3. Objects
4. "Real" data
5. Plotting
6. Character Operations
7. Conditions & loops
8. Functions & packages
9. Distributions
10. Statistics
11. Time series handling and analysis
12. Spatial data and GIS functionality
13. Final tasks

Course plan
- Session 1/7: Why R, read file, select and plot data
- Session 2/7: Objects, file reading, NAs, data merging
- Session 3/7: publication-ready graphics, if-else conditionals
- Session 4/7: for loops, apply functions
- Session 5/7: functions
- Session 6/7: statistics
- Session 7/7: shapefiles (R as GIS)
- Feedback, additional material

Outline

R course info
1. One-Session-Intro
2. Getting started: Background, GUI and first steps
3. Objects
4. "Real" data
5. Plotting
6. Character Operations
7. Conditions & loops
8. Functions & packages
9. Distributions
10. Statistics
11. Time series handling and analysis
12. Spatial data and GIS functionality
13. Final tasks

Course plan
- Session 1/7: Why R, read file, select and plot data
- Session 2/7: Objects, file reading, NAs, data merging
- Session 3/7: publication-ready graphics, if-else conditionals
- Session 4/7: for loops, apply functions
- Session 5/7: functions
- Session 6/7: statistics
- Session 7/7: shapefiles (R as GIS)
- Feedback, additional material

Feedback

Please fill out the feedback form at

goo.gl/jVgqge

(it only takes 2 minutes)

Thanks!