



# introduction

## start your programming journey in 1 hour



ENCOURAGED



use freely, cite me

Berry Boessenkool, June 2018

`berry-b@gmx.de`

[github.com/brry/hour](https://github.com/brry/hour)

*Presentation template generated with `berryFunctions::createPres`*

```
print("Hello world!")
```

- ▶ Berry Boessenkool → [berry-b@gmx.de](mailto:berry-b@gmx.de)

```
print("Hello world!")
```

- ▶ Berry Boessenkool → berry-b@gmx.de
- ▶ Geoecology @ Potsdam University

```
print("Hello world!")
```

- ▶ Berry Boessenkool → berry-b@gmx.de
- ▶ Geoecology @ Potsdam University
- ▶ R Fan

```
print("Hello world!")
```

- ▶ Berry Boessenkool → berry-b@gmx.de
- ▶ Geoecology @ Potsdam University
- ▶ R Fanatic

```
print("Hello world!")
```

- ▶ Berry Boessenkool → berry-b@gmx.de
- ▶ Geoecology @ Potsdam University
- ▶ R Fanatic since 2010

```
print("Hello world!")
```

- ▶ Berry Boessenkool → berry-b@gmx.de
- ▶ Geoecology @ Potsdam University
- ▶ R Fanatic since 2010
- ▶ Teaching, programming, consulting, community




```
print("Hello world!")
```

- ▶ Berry Boessenkool → berry-b@gmx.de
- ▶ Geoecology @ Potsdam University
- ▶ R Fanatic since 2010
- ▶ Teaching, programming, consulting, community






```
print("Hello world!")
```

- ▶ Berry Boessenkool → berry-b@gmx.de
- ▶ Geoecology @ Potsdam University
- ▶ R Fanatic since 2010
- ▶ Teaching, programming, consulting, community
- ▶  is free,





```
print("Hello world!")
```


- ▶ Berry Boessenkool → berry-b@gmx.de
- ▶ Geoecology @ Potsdam University
- ▶ R Fanatic since 2010
- ▶ Teaching, programming, consulting, community
- ▶  is free, open source,



```
print("Hello world!")
```


- ▶ Berry Boessenkool → berry-b@gmx.de
- ▶ Geoecology @ Potsdam University
- ▶ R Fanatic since 2010
- ▶ Teaching, programming, consulting, community 
- ▶  is free, open source, has a large user community,

```
print("Hello world!")
```

- ▶ Berry Boessenkool → berry-b@gmx.de
- ▶ Geoecology @ Potsdam University
- ▶ R Fanatic since 2010
- ▶ Teaching, programming, consulting, community
- ▶  is free, open source, has a large user community, will make your work efficient and productive





```
print("Hello world!")
```

- ▶ Berry Boessenkool → berry-b@gmx.de
- ▶ Geoecology @ Potsdam University
- ▶ R Fanatic since 2010
- ▶ Teaching, programming, consulting, community
- ▶  is free, open source, has a large user community, will make your work efficient and productive and is the standard for data analysis in many universities and industries



```
print("Hello world!")
```

- ▶ Berry Boessenkool → berry-b@gmx.de
- ▶ Geoecology @ Potsdam University
- ▶ R Fanatic since 2010
- ▶ Teaching, programming, consulting, community 
- ▶  is free, open source, has a large user community, will make your work efficient and productive and is the standard for data analysis in many universities and industries
- ▶ R installation instructions: [github.com/brry/course#install](https://github.com/brry/course#install)

```
print("Hello world!")
```

- ▶ Berry Boessenkool → berry-b@gmx.de
- ▶ Geoecology @ Potsdam University
- ▶ R Fanatic since 2010
- ▶ Teaching, programming, consulting, community 
- ▶  is free, open source, has a large user community, will make your work efficient and productive and is the standard for data analysis in many universities and industries
- ▶ R installation instructions: [github.com/brry/course#install](https://github.com/brry/course#install)
- ▶ Today:

```
print("Hello world!")
```

- ▶ Berry Boessenkool → berry-b@gmx.de
- ▶ Geoecology @ Potsdam University
- ▶ R Fanatic since 2010
- ▶ Teaching, programming, consulting, community 
- ▶  is free, open source, has a large user community, will make your work efficient and productive and is the standard for data analysis in many universities and industries
- ▶ R installation instructions: [github.com/brry/course#install](https://github.com/brry/course#install)
- ▶ Today: wide but shallow introduction, no deep understanding





```
print("Hello world!")
```

- ▶ Berry Boessenkool → berry-b@gmx.de
- ▶ Geoecology @ Potsdam University
- ▶ R Fanatic since 2010
- ▶ Teaching, programming, consulting, community 
- ▶  is free, open source, has a large user community, will make your work efficient and productive and is the standard for data analysis in many universities and industries
- ▶ R installation instructions: [github.com/brry/course#install](https://github.com/brry/course#install)
- ▶ Today: wide but shallow introduction, no deep understanding
- ▶ Brief inputs followed by short exercises (for max learning)

```
print("Hello world!")
```

- ▶ Berry Boessenkool → berry-b@gmx.de
- ▶ Geoecology @ Potsdam University
- ▶ R Fanatic since 2010
- ▶ Teaching, programming, consulting, community 
- ▶  is free, open source, has a large user community, will make your work efficient and productive and is the standard for data analysis in many universities and industries
- ▶ R installation instructions: [github.com/brry/course#install](https://github.com/brry/course#install)
- ▶ Today: wide but shallow introduction, no deep understanding
- ▶ Brief inputs followed by short exercises (for max learning)
- ▶ Don't hesitate to ask the helpers

```
print("Hello world!")
```

- ▶ Berry Boessenkool → berry-b@gmx.de
- ▶ Geoecology @ Potsdam University
- ▶ R Fanatic since 2010
- ▶ Teaching, programming, consulting, community 
- ▶  is free, open source, has a large user community, will make your work efficient and productive and is the standard for data analysis in many universities and industries
- ▶ R installation instructions: [github.com/brry/course#install](https://github.com/brry/course#install)
- ▶ Today: wide but shallow introduction, no deep understanding
- ▶ Brief inputs followed by short exercises (for max learning)
- ▶ Don't hesitate to ask the helpers
- ▶ If we're proceeding too fast, please interrupt!

# Integrated Development Environment (IDE): RStudio

The screenshot shows the RStudio IDE with the following components:

- Scripts (shareable .R files):** The top-left pane shows an R script with code for reading a shapefile, transforming coordinates, and plotting. A callout box highlights this area.
- Graphical output and more:** The bottom-right pane shows a scatter plot of 'sort(as.Date(first))' on the y-axis (ranging from 1850 to 1950) against 'Index' on the x-axis (ranging from 0 to 150). A callout box highlights this area.
- The console to the actual R:** The bottom-left pane shows the R console output, including the execution of the script and the resulting data frame. A callout box highlights this area.

**Environment pane (top right):** Shows the Global Environment with two data frames: 'statlocsp' (178 obs. of 2 variables) and 'statnames' (178 obs. of 2 variables). The 'Values' section shows the first few rows of the data.

# Get started in R

## Get started in R

### Exercise 1: R is an awesome calculator

In the console, calculate  $21+21$  ,  $7*6$  and  $\frac{0,3}{4} * \sqrt{313600}$

*If you don't know how to compute a square root in R, you can google it!*

## Get started in R

### Exercise 1: R is an awesome calculator

In the console, calculate  $21+21$  ,  $7*6$  and  $\frac{0,3}{4} * \sqrt{313600}$

*If you don't know how to compute a square root in R, you can google it!*

```
21+21 ; 7*6 ; 0.3/4*sqrt(313600)
```

## Get started in R

### Exercise 1: R is an awesome calculator

In the console, calculate  $21+21$  ,  $7*6$  and  $\frac{0.3}{4} * \sqrt{313600}$

*If you don't know how to compute a square root in R, you can google it!*

```
21+21 ; 7*6 ; 0.3/4*sqrt(313600)
```

- objects: assign with `<-` Rstudio Keyboard shortcut: **ALT** + `-`  
`nstudents <- 15`  
`nstudents`  
`nstudents > 12`



## Get started in R

### Exercise 1: R is an awesome calculator

In the console, calculate  $21+21$  ,  $7*6$  and  $\frac{0.3}{4} * \sqrt{313600}$

*If you don't know how to compute a square root in R, you can google it!*

```
21+21 ; 7*6 ; 0.3/4*sqrt(313600)
```

- ▶ objects: assign with `<-` Rstudio Keyboard shortcut: **ALT** + `-`  
`nstudents <- 15`  
`nstudents`  
`nstudents > 12`
- ▶ What's a good object name?

## Get started in R

### Exercise 1: R is an awesome calculator

In the console, calculate  $21+21$  ,  $7*6$  and  $\frac{0,3}{4} * \sqrt{313600}$

*If you don't know how to compute a square root in R, you can google it!*

```
21+21 ; 7*6 ; 0.3/4*sqrt(313600)
```

- ▶ objects: assign with `<-` Rstudio Keyboard shortcut: **ALT** + `-`  
`nstudents <- 15`  
`nstudents`  
`nstudents > 12`
- ▶ What's a good object name? → short, but explanatory,

## Get started in R

### Exercise 1: R is an awesome calculator

In the console, calculate  $21+21$  ,  $7*6$  and  $\frac{0,3}{4} * \sqrt{313600}$

*If you don't know how to compute a square root in R, you can google it!*

```
21+21 ; 7*6 ; 0.3/4*sqrt(313600)
```

- ▶ objects: assign with `<-` Rstudio Keyboard shortcut: **ALT** + `-`  
`nstudents <- 15`  
`nstudents`  
`nstudents > 12`
- ▶ What's a good object name? → short, but explanatory,  
lowerCamelStandard\_or\_underscore are good naming conventions

## Get started in R

### Exercise 1: R is an awesome calculator

In the console, calculate  $21+21$  ,  $7*6$  and  $\frac{0.3}{4} * \sqrt{313600}$

*If you don't know how to compute a square root in R, you can google it!*

```
21+21 ; 7*6 ; 0.3/4*sqrt(313600)
```

- ▶ objects: assign with `<-` Rstudio Keyboard shortcut: **ALT** + `-`  
`nstudents <- 15`  
`nstudents`  
`nstudents > 12`
- ▶ What's a good object name? → short, but explanatory,  
lowerCamelStandard\_or\_underscore are good naming conventions
- ▶ comments: `# everything after a hashtag is not executed.`

## Get started in R

### Exercise 1: R is an awesome calculator

In the console, calculate  $21+21$  ,  $7*6$  and  $\frac{0.3}{4} * \sqrt{313600}$

*If you don't know how to compute a square root in R, you can google it!*

```
21+21 ; 7*6 ; 0.3/4*sqrt(313600)
```

- ▶ objects: assign with `<-` Rstudio Keyboard shortcut: **ALT** + `-`  
`nstudents <- 15`  
`nstudents`  
`nstudents > 12`
- ▶ What's a good object name? → short, but explanatory,  
lowerCamelStandard\_or\_underscore are good naming conventions
- ▶ comments: **# everything after a hashtag is not executed.**
- ▶ scripts: Rstudio

## Preparation to reading files

### Exercise 2: Set up folder and script

1. Create a folder for this course
2. With `rightclick` on `Raw + save as`, download the weather `dataset` and `metadata` into that folder
3. Create an R script in the same folder  
(Rstudio: `CTRL + SHIFT + N`, then `CTRL + S`)
4. Tell R where to look for data through  
Rstudio: Session - Set Working Directory - To Source File Location
5. Copy the command thus sent to the console into the beginning of the script. This makes it reproducible later on.  
`setwd("C:/path/to/input")` # change back- to forwardslashes

## Reading files into R, opening the help documentation

- ▶ Read the climate data file into R with the command `read.table`

## Reading files into R, opening the help documentation

- ▶ Read the climate data file into R with the command `read.table`
- ▶ Assign it to an object with a good name



## Reading files into R, opening the help documentation

- ▶ Read the climate data file into R with the command `read.table`
- ▶ Assign it to an object with a good name

```
clim <- read.table(file="clim.txt")
```

## Reading files into R, opening the help documentation

- ▶ Read the climate data file into R with the command `read.table`
- ▶ Assign it to an object with a good name

```
clim <- read.table(file="clim.txt")
```

- ▶ If R tells you "no such file" exists, check the output of `dir()`.

## Reading files into R, opening the help documentation

- ▶ Read the climate data file into R with the command `read.table`
- ▶ Assign it to an object with a good name

```
clim <- read.table(file="clim.txt")
```

- ▶ If R tells you "no such file" exists, check the output of `dir()`.
- ▶ Check the object with `head(YourObject)`.

## Reading files into R, opening the help documentation

- ▶ Read the climate data file into R with the command `read.table`
- ▶ Assign it to an object with a good name

```
clim <- read.table(file="clim.txt")
```

- ▶ If R tells you "no such file" exists, check the output of `dir()`.
- ▶ Check the object with `head(YourObject)`.
- ▶ `str(YourObject)` must yield 19 columns with data types: `int`, `factor`, `num`.

## Reading files into R, opening the help documentation

- ▶ Read the climate data file into R with the command `read.table`
- ▶ Assign it to an object with a good name

```
clim <- read.table(file="clim.txt")
```

- ▶ If R tells you "no such file" exists, check the output of `dir()`.
- ▶ Check the object with `head(YourObject)`.
- ▶ `str(YourObject)` must yield 19 columns with data types: int, factor, num.
- ▶ Use the documentation to find out settings for the arguments:

```
help(read.table) ; ?read.table # or press F1.
```

## Reading files into R, opening the help documentation

- ▶ Read the climate data file into R with the command `read.table`
- ▶ Assign it to an object with a good name

```
clim <- read.table(file="clim.txt")
```

- ▶ If R tells you "no such file" exists, check the output of `dir()`.
- ▶ Check the object with `head(YourObject)`.
- ▶ `str(YourObject)` must yield 19 columns with data types: int, factor, num.
- ▶ Use the documentation to find out settings for the arguments:

```
help(read.table)      ;      ?read.table      #      or press F1.
```

```
clim <- read.table(file="clim.txt", header=TRUE)
```

## Reading files into R

### Exercise 3: Reading files

1. Read the metadata file into R with the command `read.table`, again assigning it to an object with a good name.
2. You need to set the arguments `file`, `sep`, `header`, `stringsAsFactors`.
3. `str(YourObject)` must yield 5 chr (character) columns
4. BONUS: what does `tail(clim)` return?

## Solution to exercise 3: Reading files

```
clim <- read.table(file="clim.txt", header=TRUE)
meta <- read.table(file="meta.txt", header=TRUE,
                   sep=";", stringsAsFactors=FALSE)
```

```
tail(Clim) # last rows of an object
```

##	STATIONS_ID	MESS_DATUM	QN_3	FX	FM	QN_4	RSK
## 545	3987	2018-06-20	1	7.6	2.5	1	0.0
## 546	3987	2018-06-21	1	19.3	5.9	1	1.0
## 547	3987	2018-06-22	1	17.2	5.8	1	3.4
## 548	3987	2018-06-23	1	15.6	7.0	1	2.1
## 549	3987	2018-06-24	1	10.3	4.8	1	2.9
## 550	3987	2018-06-25	1	10.0	3.6	1	0.0



## Objects: data.frames

- For tables with different data types (numbers, characters, categories, integers), R has the object type data.frame

## Objects: data.frames

- ▶ For tables with different data types (numbers, characters, categories, integers), R has the object type data.frame
- ▶ `read.table` also returns a data.frame

## Objects: data.frames

- ▶ For tables with different data types (numbers, characters, categories, integers), R has the object type data.frame
- ▶ `read.table` also returns a data.frame
- ▶ If we have the object `df`, we can subset with `df[rows,columns]`

## Objects: data.frames

- ▶ For tables with different data types (numbers, characters, categories, integers), R has the object type `data.frame`
- ▶ `read.table` also returns a `data.frame`
- ▶ If we have the object `df`, we can subset with `df[rows,columns]`
- ▶ `df[1,2:4]` ;

## Objects: data.frames

- ▶ For tables with different data types (numbers, characters, categories, integers), R has the object type `data.frame`
- ▶ `read.table` also returns a `data.frame`
- ▶ If we have the object `df`, we can subset with `df[rows, columns]`
- ▶ `df[1,2:4]; df[2, ];`

## Objects: data.frames

- ▶ For tables with different data types (numbers, characters, categories, integers), R has the object type data.frame
- ▶ `read.table` also returns a data.frame
- ▶ If we have the object `df`, we can subset with `df[rows,columns]`
- ▶ `df[1,2:4]; df[2, ]; df[, "name"];`

## Objects: data.frames

- ▶ For tables with different data types (numbers, characters, categories, integers), R has the object type `data.frame`
- ▶ `read.table` also returns a `data.frame`
- ▶ If we have the object `df`, we can subset with `df[rows, columns]`
- ▶ `df[1,2:4]; df[2, ]; df[, "name"]; df$name`

## Objects: data.frames

- ▶ For tables with different data types (numbers, characters, categories, integers), R has the object type `data.frame`
- ▶ `read.table` also returns a `data.frame`
- ▶ If we have the object `df`, we can subset with `df[rows,columns]`
- ▶ `df[1,2:4]`; `df[2, ]`; `df[, "name"]`; `df$name`

### Exercise 4: Data.frame indexing

From the climate dataset, obtain:

1. The first 5 values in column 4
2. The column UPM (relative humidity)
3. BONUS 1: The maximum sunshine duration (SDK)
4. BONUS 2: What command do you need to get the number of rows?
5. BONUS 3: What is better and worse in `df[, "name"]` vs `df[, 3]`?



## Solution to exercise 4: subsetting data.frames

```
clim[1:5, 4]

## [1] 10.0 13.9 17.1 22.2 22.6

Clim$UPM

## [1] 96.13 87.92 93.29 79.63 76.00 96.17 93.13 93.96 83.38 82.92 94.33 93.04
## [13] 87.13 77.33 83.08 79.96 94.46 95.54 81.13 82.71

max(clim$SDK) ; max(clim[, "SDK"])

## [1] 15.933
## [1] 15.933

nrow(clim)

## [1] 550
```

`df[, "name"]` is better understandable for humans and still returns the same if the order of the columns is changed. But it takes more typing.


## Plotting

General code for scatterplots: `plot(x, y, ...)`

## Plotting

General code for scatterplots: `plot(x, y, ...)`

```
plot(x=Indometh$time, y=Indometh$conc,  
     col="orange", pch=16, main="Awesome Graph!")
```



## Plotting

Please convert the date column with



```
clim$MESS_DATUM <- as.Date(clim$MESS_DATUM, format="%Y-%m-%d")
```

### Exercise 5: Scatterplots, line plots

1. Generate a figure with `plot(clim$VPM, clim$TMK)`
2. Improve the axis labels. Use the metadata to figure out the column name meanings.
3. BONUS: Add an informative graph title
4. Plot a time series of the daily temperature maximum. What value do you need to give to the argument `type`? Again, use the documentation of `?plot()` to find out.

## Solution to exercise 5: Scatterplots, line plots

```
plot(clim$TMK, clim$VPM, xlab="Lufttemperatur", ylab="Dampfdruck",  
     main="Korrelation Tagesmittelwerte\nPotsdam 2016-2018, DWD")  
plot(clim$MESS_DATUM, clim$TXK, type="l", main="Saisonalitaet sichtbar")
```




## Plotting live demo I


```
par(mar=c(2,3,2,1), mgp=c(2,0.7,0))
plot(clim$TMK, clim$VPM, xlab="Lufttemperatur", ylab="Dampfdruck",
     main="Der maximale Dampfdruck ist Temperatur-limitiert
     (Korrelation Tagesmittelwerte Potsdam 2016-2018, DWD)",
     las=1, pch=3, cex=2, col="red", cex.main=0.9)
#
#
# install.packages("berryFunctions")
plot(clim$MESS_DATUM, clim$TXK, type="l", xlab="", xaxt="n", las=1, lwd=3)
berryFunctions::monthAxis()
```

## Plotting live demo II

**Der maximale Dampfdruck ist Temperatur-limitiert  
(Korrelation Tagesmittelwerte Potsdam 2016–2018, DWD)**



## Plotting live demo III





## commonly needed plot arguments

```
plot(x, y, # point coordinates
col="lightblue", # point color
pch=0, # point character (symbol)
xlab="My label [km]", ylab="", # axis labels
main="Graph title", # title
cex=1.8, # character expansion (symbol size)
type="l", # draw lines instead of points
lwd=3, # line width (thickness of lines)
las=1, # label axis style (axis numbers upright)
xaxt="n" # axis type (none to suppress axis)
)
```

## Preparing for for loops

Please give your metadata rownames as follows:


```
rownames(meta) <- meta$Par
```

### Exercise 6: using objects to subset

1. Create an object `var` with the character string "FX".
2. Get the meta value for row `var` and column "Label".
3. Plot the `var` column of `clim` as a time series.
4. Use the output from task 2 to give the plot a title.
5. BONUS: make the x-axis nicer by suppressing the default axis (`xaxt="n"`) and adding a monthAxis from the `berryFunctions` package.

## Solution to exercise 6: using objects to subset

```
var <- "FX"  
meta[var, "Label"]  
  
## [1] "Windspitze [m/sec]"  
  
plot(clim$MESS_DATUM, clim[,var], type="l", xaxt="n",  
      main=meta[var, "Label"], ylab="", xlab="")  
berryFunctions::monthAxis()
```



## For loops

A for loop creates a variable, sets it to a value, runs some code,

## For loops

A for loop creates a variable, sets it to a value, runs some code, then sets the variable to the next value, runs the code with that, and so on.

## For loops

A for loop creates a variable, sets it to a value, runs some code, then sets the variable to the next value, runs the code with that, and so on.

```
for(var in meta$Par)
{
  plot(clim$MESS_DATUM, clim[,var], type="l", xaxt="n",
       main=meta[var, "Label"], ylab="", xlab="")
  berryFunctions::monthAxis()
}
```

## Selected resources

### Books:

## Selected resources

### Books:

- ▶ Grolemund & Wickham (2017) [R for Data Science](#)



## Selected resources

### Books:

- ▶ Grolemund & Wickham (2017) [R for Data Science](#)
- ▶ J. Adler (2010): R in a Nutshell

## Selected resources

### Books:

- ▶ Grolemund & Wickham (2017) [R for Data Science](#)
- ▶ J. Adler (2010): R in a Nutshell
- ▶ U. Ligges (2008): Programmieren mit R (German)

## Selected resources

### Books:

- ▶ Grolemund & Wickham (2017) [R for Data Science](#)
- ▶ J. Adler (2010): R in a Nutshell
- ▶ U. Ligges (2008): Programmieren mit R (German)

### Tutorials:

## Selected resources

### Books:

- ▶ Grolemund & Wickham (2017) [R for Data Science](#)
- ▶ J. Adler (2010): R in a Nutshell
- ▶ U. Ligges (2008): Programmieren mit R (German)

### Tutorials:

- ▶ [Microsoft + Datacamp](#) (best course I know of, with login, but free)

## Selected resources

### Books:

- ▶ Grolemund & Wickham (2017) [R for Data Science](#)
- ▶ J. Adler (2010): R in a Nutshell
- ▶ U. Ligges (2008): Programmieren mit R (German)

### Tutorials:

- ▶ [Microsoft + Datacamp](#) (best course I know of, with login, but free)
- ▶ [STAT 545](#)

## Selected resources

### Books:

- ▶ Grolemund & Wickham (2017) [R for Data Science](#)
- ▶ J. Adler (2010): R in a Nutshell
- ▶ U. Ligges (2008): Programmieren mit R (German)

### Tutorials:

- ▶ [Microsoft + Datacamp](#) (best course I know of, with login, but free)
- ▶ [STAT 545](#)
- ▶ [github.com/brry/course](https://github.com/brry/course)

## Selected resources

### Books:

- ▶ Grolemund & Wickham (2017) [R for Data Science](#)
- ▶ J. Adler (2010): R in a Nutshell
- ▶ U. Ligges (2008): Programmieren mit R (German)

### Tutorials:

- ▶ [Microsoft + Datacamp](#) (best course I know of, with login, but free)
- ▶ [STAT 545](#)
- ▶ [github.com/brry/course](https://github.com/brry/course)

### Reference cards:

## Selected resources

### Books:

- ▶ Grolemund & Wickham (2017) [R for Data Science](#)
- ▶ J. Adler (2010): R in a Nutshell
- ▶ U. Ligges (2008): Programmieren mit R (German)

### Tutorials:

- ▶ [Microsoft + Datacamp](#) (best course I know of, with login, but free)
- ▶ [STAT 545](#)
- ▶ [github.com/brry/course](https://github.com/brry/course)

### Reference cards:

- ▶ [base](#) and [advanced](#) cheatsheets from [Rstudio](#)



## Selected resources

### Books:

- ▶ Grolemund & Wickham (2017) [R for Data Science](#)
- ▶ J. Adler (2010): R in a Nutshell
- ▶ U. Ligges (2008): Programmieren mit R (German)

### Tutorials:

- ▶ [Microsoft + Datacamp](#) (best course I know of, with login, but free)
- ▶ [STAT 545](#)
- ▶ [github.com/brry/course](https://github.com/brry/course)

### Reference cards:

- ▶ [base](#) and [advanced](#) cheatsheets from [Rstudio](#)
- ▶ [RefCard](#) by Tom Short & Jonas Stein

## Selected resources

### Books:

- ▶ Grolemund & Wickham (2017) [R for Data Science](#)
- ▶ J. Adler (2010): R in a Nutshell
- ▶ U. Ligges (2008): Programmieren mit R (German)

### Tutorials:

- ▶ [Microsoft + Datacamp](#) (best course I know of, with login, but free)
- ▶ [STAT 545](#)
- ▶ [github.com/brry/course](https://github.com/brry/course)

### Reference cards:

- ▶ [base](#) and [advanced](#) cheatsheets from [Rstudio](#)
- ▶ [RefCard](#) by Tom Short & Jonas Stein

### The internet:

## Selected resources

### Books:

- ▶ Grolemund & Wickham (2017) [R for Data Science](#)
- ▶ J. Adler (2010): R in a Nutshell
- ▶ U. Ligges (2008): Programmieren mit R (German)

### Tutorials:

- ▶ [Microsoft + Datacamp](#) (best course I know of, with login, but free)
- ▶ [STAT 545](#)
- ▶ [github.com/brry/course](https://github.com/brry/course)

### Reference cards:

- ▶ [base](#) and [advanced](#) cheatsheets from [Rstudio](#)
- ▶ [RefCard](#) by Tom Short & Jonas Stein

### The internet:

- ▶ [StackOverflow](#) for programming questions <- **main resource**