

Part of Speech Tagging with LSTM Networks

Project Presentation

Zeming Lin

Department of Computer Science at University of Virginia

04/30/2015

Table of Contents

Background

POS Tagging

Recurrent Neural Networks

Methods and Results

LSTM Networks


Network Structure

Results and Discussion

Results

Discussion

Part of Speech



Penn Treebank Dataset

- ▶ We use 93915 words, from NLTK. Only consider sentences with length > 4 .
- ▶ Already tokenized.
- ▶ Example:
 - ▶ Pierre Vinken , 61 years old , will join the board as a nonexecutive director Nov. 29 .
 - ▶ NNP NNP , CD NNS JJ , MD VB DT NN IN DT JJ NN NNP CD .

State of the art

Author	Model	Accuracy
Brants (2000)	Hidden Markov Model	96.46%
Giménez and Márquez (2004)	SVM	97.16%
Spoustová et al. (2009)	Averaged Perceptron	97.44%
Manning (2011)	Dependency Network	97.32%
Søgaard (2011)	Condensed Nearest Neighbors	97.50%

State of the art

- ▶ Human disagreement is $\sim 3.5\%$
- ▶ Why is this interesting?
 - ▶ Machines often make very obvious mistakes
 - ▶ Single error tends to cascade to downstream modules for NLP

Table of Contents

Background

POS Tagging

Recurrent Neural Networks

Methods and Results

LSTM Networks


Network Structure

Results and Discussion


Results

Discussion

Neural Networks




Recurrent Networks



Recurrent networks

- ▶ Hard to train!
- ▶ Backpropagation through time is used to approximate training



Recurrent Networks

- ▶ BPTT algorithm not guaranteed to converge to a *local* minimum
 - ▶ Very sensitive to learning rate changes
- ▶ Exploding / vanishing gradients




Table of Contents

Background

POS Tagging

Recurrent Neural Networks

Methods and Results

LSTM Networks

Network Structure


Results and Discussion

Results


Discussion

Long-short term memory

- ▶ Fixes the gradients problem, so we can train on longer time steps!
- ▶ LSTM Cell:



LSTM Cell



$$i_t = \sigma(W_i x_t + U_i h_{t-1} + b_i)$$

$$\tilde{C}_t = \tanh(W_c x_t + U_c h_{t-1} + b_c)$$


$$f_t = \sigma(W_f x_t + U_f h_{t-1} + b_f)$$

$$C_t = i_t \odot \tilde{C}_t + f_t \odot C_{t-1}$$

$$o_t = \sigma(W_o x_t + U_o h_{t-1} + V_o C_t + b_f)$$


$$h_t = o_t \odot \tanh C_t$$

LSTM Cell




$$i_t = \sigma(W_i x_t + U_i h_{t-1} + b_i)$$

LSTM Cell




$$\tilde{C}_t = \tanh(W_c x_t + U_c h_{t-1} + b_c)$$

LSTM Cell




$$f_t = \sigma(W_f x_t + U_f h_{t-1} + b_f)$$

LSTM Cell



$$C_t = i_t \odot \tilde{C}_t + f_t \odot C_{t-1}$$

LSTM Cell



$$o_t = \sigma(W_o x_t + U_o h_{t-1} + V_o C_t + b_f)$$

$$h_t = o_t \odot \tanh C_t$$

LSTM Network

Error gradients no longer vanish / explode!




Table of Contents

Background

POS Tagging

Recurrent Neural Networks

Methods and Results

LSTM Networks


Network Structure

Results and Discussion

Results


Discussion

Layers




- Embedding is a $E = 50$ dim vector, trained from wikipedia, lookuptable of 130k by 50.

Layers




- Embedding is a $E = 50$ dim vector, trained from wikipedia, lookuptable of 130k by 50.
- R is the size of output

Layers




- ▶ Embedding is a $E = 50$ dim vector, trained from wikipedia, lookuptable of 130k by 50.
- ▶ R is the size of output
- ▶ C is the memory of the network, the “error carousel”

Layers



- ▶ Embedding is a $E = 50$ dim vector, trained from wikipedia, lookuptable of 130k by 50.
- ▶ R is the size of output
- ▶ C is the memory of the network, the “error carousel”
- ▶ V is number of tags to label, or 46.

Running scheme



- ▶ Run sequence through twice: Only consider the second run through
 - ▶ “Read entire sequence” before considering POS labels.
 - ▶ 2-time slowdown, but $\sim 1\text{-}2\%$ extra accuracy

Table of Contents

Background

POS Tagging

Recurrent Neural Networks

Methods and Results

LSTM Networks

Network Structure

Results and Discussion

Results

Discussion

Results

L	R	T	Accuracy	Speed (wps)
2	100	40	.942	319
2	250	40	.952	88
2	500	40	.953	25
2	100	400	.942	363
2	100	10	.932	394
3	100	40	.936	239
4	100	40	.924	171

- ▶ Each network has L layers
- ▶ Consider T -length sequences
- ▶ Cells memory of R units.

Table of Contents

Background

POS Tagging

Recurrent Neural Networks

Methods and Results

LSTM Networks

Network Structure

Results and Discussion

Results

Discussion

Discussion

L	R	T	Accuracy	Speed (wps)
2	100	40	.942	319
2	250	40	.952	88
2	500	40	.953	25
2	100	400	.942	363
2	100	10	.932	394
3	100	40	.936	239
4	100	40	.924	171

- ▶ More layers == worse performance?
- ▶ Increase number of training iterations?

Discussion

L	R	T	Accuracy	Speed (wps)
2	100	40	.942	319
2	250	40	.952	88
2	500	40	.953	25
2	100	400	.942	363
2	100	10	.932	394
3	100	40	.936	239
4	100	40	.924	171

- ▶ High T doesn't impact, but low T does
- ▶ Memory units R had large impact, 100 \rightarrow 250 gave 1% accuracy!

Future Work

- ▶ Find the full Treebank dataset, see if we get state of the art 97.5% results
- ▶ Test larger models, use GPU to parallelize matrix computation
- ▶ Batch gradient descent to parallelize training, can use Mapreduce

Thank you!