


Digital Repeater Controller V2 – Radio Interface Board

Copyright (C) Bruce MacKinnon KC1FSZ, 2025

This design is licensed under the terms of the TAPR Open Hardware License (OHL) and is intended for AMATEUR RADIO USE ONLY. Commercial use of this design is prohibited.

- NOTES:
- * This is an analog board that interfaces with two radios. A separate digital board based on the RP2040 is also required. A ribbon cable connects the two boards.
 - * The goal of this design is to do as little as possible in hardware.
 - * Many things that usually happen in hardware (or FPGA) will happen in software:
 - Audio routing between the two radios will happen in software.
 - Audio pre-emphasis/de-emphasis (if needed) will happen using DSP using digital filters.
 - CTCSS decoding (if needed) will happen in DSP.
 - CTCSS encoding (if needed) will happen in DSP.
 - DTMF decoding will happen in DSP.
 - CWID and other tone prompts will happen in DSP/software.
 - Voice IDs will happen in DSP/software.
 - Other digital audio interfaces like EchoLink (or DMR/D-Star in the future) will be directly integrated.




- H1 MountingHole
- H2 MountingHole
- H3 MountingHole
- H4 MountingHole

NOT FOR COMMERCIAL USE
Copyright (C) Bruce MacKinnon, 2025
Bruce MacKinnon KC1FSZ
Sheet: /
File: if-2.kicad_sch

Title: Digital Repeater Controller

Size: USLetter Date: 2025-05-13
KiCad E.D.A. 9.0.0

Rev: 2
Id: 1/11



NOT FOR COMMERCIAL USE
Copyright (C) Bruce MacKinnon, 2025
Bruce MacKinnon KC1FSZ
Sheet: /Audio In 0/
File: audio_in_0.kicad_sch

Title: COS/CTCSS/PTT Controls (Radio 0)

Size: USLetter Date: 2025-05-13
KiCad E.D.A. 9.0.0

Rev: 2
Id: 3/11

AC-coupled audio input from radio.
Expected to be in the 100–1000mVpp range.

RFI Filter
(–3dB at 160kHz)

Audio input level trim. Adjust
attenuation for ADC full-scale.

Approximately 2.5V

Audio Input Buffer
Gain=5x

We will use large solder pads and a
thru-hole part for this resistor to
make it easy to change in the field
if the gain is way off.

Op Amp Supply Filter

Approximately 2.5V
center voltage from ADC.

This is not a pre/de-emphasis filter.
That is handled in the DSP.

Differential audio signal
centered at +2.5V

Create differential audio, a low-impedance drive,
and noise filter for differential analog input to ADC.
(See page 30 of TI PCM1804 datasheet)

<https://www.ti.com/lit/ds/symlink/pcm1804.pdf>

(Should be a copy of R0 audio input)

NOT FOR COMMERCIAL USE

Copyright (C) Bruce MacKinnon, 2025

Bruce MacKinnon KC1FSZ

Sheet: /Audio In 1/

File: audio_in_1.kicad_sch

Title: COS/CTCSS/PTT Controls (Radio 1)

Size: USLetter Date: 2025-05-13

KiCad E.D.A. 9.0.0

Rev: 2

Id: 4/11

The TI PCM1804 is a 24-bit stereo analog to digital converter designed for audio applications. It contains an integrated low-pass anti-aliasing filter on the front-end with a cut-off around 20 kHz. Sample rate (f_s) will be 48,000 samples/second. Narrower filtering will be achieved in DSP.







Figure 18.

Configuration Solder Bridges



NOT FOR COMMERCIAL USE
Copyright (C) Bruce MacKinnon, 2025
Bruce MacKinnon KC1FSZ
Sheet: /ADC/
File: adc.kicad_sch

Title: COS/CTCSS/PTT Controls (Radio 1)

Size: USLetter Date: 2025-05-13
KiCad E.D.A. 9.0.0

Rev: 2
Id: 5/11

The TI PCM5100 is a 24-bit stereo digital to analog converter designed for audio applications. It contains an integrated low-pass interpolation filter on the back-end with a cut-off around 20 kHz. Sample rate (f_s) will be 48,000 samples/second. Narrower filtering will be achieved in DSP.






Figure 16. Normal x8 Interpolation Filter Frequency Response

Configuration Solder Bridges




NOT FOR COMMERCIAL USE
Copyright (C) Bruce MacKinnon, 2025
Bruce MacKinnon KC1FSZ
Sheet: /DAC/
File: dac.kicad_sch

Title: COS/CTCSS/PTT Controls (Radio 1)

Size: USLetter Date: 2025-05-13
KiCad E.D.A. 9.0.0

Rev: 2
Id: 6/11






NOT FOR COMMERCIAL USE
Copyright (C) Bruce MacKinnon, 2025
Bruce MacKinnon KC1FSZ
Sheet: /Audio Out 0/
File: audio_out_0.kicad_sch

Title: COS/CTCSS/PTT Controls (Radio 0)

Size: USLetter Date: 2025-05-13
KiCad E.D.A. 9.0.0

Rev: 2
Id: 7/11

Radio Side



Controller Side

NOT FOR COMMERCIAL USE
Copyright (C) Bruce MacKinnon, 2025
Bruce MacKinnon KC1FSZ
Sheet: /Controls 0/
File: controls_0.kicad_sch




Title: COS/CTCSS/PTT Controls (Radio 0)

Size: USLetter Date: 2025-05-13
KiCad E.D.A. 9.0.0

Rev: 2
Id: 9/11

Radio Side

Controller Side



(Should be a copy of R0 controls)

NOT FOR COMMERCIAL USE
Copyright (C) Bruce MacKinnon, 2025
Bruce MacKinnon KC1FSZ
Sheet: /Controls 1/
File: controls_1.kicad_sch

Title: COS/CTCSS/PTT Controls (Radio 1)

Size: USLetter Date: 2025-05-13
KiCad E.D.A. 9.0.0

Rev: 2
Id: 10/11

