Digital Repeater Controller V2

NOTES:
* This is an analog board that interfaces with two radios. A separate digital board based on the RP2040 is also required. A ribbon cable connects the two boards.
* The goal of this design is to do as little as possible in hardware.
* Many things that usually happen in hardware (or FPGA) will happen in software:
  - Audio routing between the two radios will happen in software.
  - Audio pre-emphasis/de-emphasis (if needed) will happen using DSP using digital filters.
  - CTCSS decoding (if needed) will happen in DSP.
  - CTCSS encoding (if needed) will happen in DSP.
  - DTMF decoding will happen in DSP.
  - CWID and other tone prompts will happen in DSP/software.
  - Voice IDs will happen in DSP/software.

Audio In 0
File: audio_in_0.kicad_sch

Audio In 1
File: audio_in_1.kicad_sch

ADC
File: adc.kicad_sch

DAC
File: dac.kicad_sch

Audio Out 0
File: audio_out_0.kicad_sch

Audio Out 1
File: audio_out_1.kicad_sch

Controls 0
File: controls_0.kicad_sch

Controls 1
File: controls_1.kicad_sch

Connectors

Power
File: power.kicad_sch

H1 MountingHole
H2 MountingHole
H3 MountingHole
H4 MountingHole

Bruce MacKinnon KC1FSZ

Sheet: /
File: if-2.kicad_sch

Title: Digital Repeater Controller

Size: USLetter	Date: 2025-03-16	**Rev: 2**
KiCad E.D.A. 9.0.0		Id: 1/11



DB25 To Radios



Ribbon Cable to Digital Board



5.5mm Power Connector
+12V on center pin

Bruce MacKinnon KC1FSZ

Sheet: /Connectors/
File: connectors.kicad_sch

Title: Connectors

Size: USLetter	Date: 2025-03-16	**Rev: 2**
KiCad E.D.A. 9.0.0		Id: 2/11



Bruce MacKinnon KC1FSZ

Sheet: /Audio In 0/
File: audio_in_0.kicad_sch

Title: Audio Input Processing (Radio 0)

Size: USLetter	Date: 2025-03-16	**Rev: 2**
KiCad E.D.A. 9.0.0		Id: 3/11

(Will Be Copy of R0 Audio Input)

Bruce MacKinnon KC1FSZ

Sheet: /Audio In 1/
File: audio_in_1.kicad_sch

Title: Audio Input Processing (Radio 1)

Size: USLetter	Date: 2025-03-16	**Rev: 2**
KiCad E.D.A. 9.0.0		Id: 4/11

The TI PCM1804 is a 24-bit stereo analog to digital converter designed for audio applications. It contains an integrated low-pass anti-aliasing filter on the front-end with a cut-off around 20 kHz. Sample rate (f_s) will be 48,000 samples/second. Narrower filtering will be achieved in DSP.





HPF enabled by default, can be disabled for testing using this jumper block. NOTE: When HPF is enabled it's not possible to test the ADC with DC levels.



Figure 18.

Configuration Solder Bridges



FMT=I2S by default

OSR=010, 384*f_s by default

Slave by default

Bruce MacKinnon KC1FSZ

Sheet: /ADC/
File: adc.kicad_sch

Title: Analog To Digital Converter

Size: USLetter	Date: 2025-03-16	**Rev: 2**
KiCad E.D.A. 9.0.0		Id: 5/11

The TI PCM5100 is a 24-bit stereo digital to analog converter designed for audio applications. It contains an integrated low-pass interpolation filter on the back-end with a cut-off around 20 kHz. Sample rate (f_s) will be 48,000 samples/second. Narrower filtering will be achieved in DSP.





Figure 16. Normal x8 Interpolation Filter Frequency Response

Configuration Solder Bridges



Bruce MacKinnon KC1FSZ

Sheet: /DAC/
File: dac.kicad_sch

Title: Digital to Analog Converter

Size: USLetter	Date: 2025-03-16	**Rev: 2**
KiCad E.D.A. 9.0.0		Id: 6/11



NOT FOR COMMERCIAL USE
Copyright (C) Bruce MacKinnon, 2025
Bruce MacKinnon KC1FSZ

Sheet: /Audio Out 0/
File: audio_out_0.kicad_sch

Title: Audio Output Processing (Radio 0)

Size: USLetter	Date: 2025-03-16	**Rev: 2**
KiCad E.D.A. 9.0.0		Id: 7/11

(Will Be Copy of R0 Audio Output)

Bruce MacKinnon KC1FSZ

Sheet: /Audio Out 1/
File: audio_out_1.kicad_sch

Title: Audio Output Processing (Radio 0)

Size: USLetter	Date: 2025-03-16	**Rev: 2**
KiCad E.D.A. 9.0.0		Id: 8/11

Controller Side

Radio Side



Converts radio COS signals to 3.3V logic.

TODO: Validate max current on LTV-353T input.



Converts radio CTCSS signals to 3.3V logic.

TODO: Validate max current on LTV-353T input.



Converts 3.3V logic to pull PTT to ground.

Bruce MacKinnon KC1FSZ

Sheet: /Controls 0/

File: controls_0.kicad_sch

Title: COS/CTCSS/PTT Controls (Radio 0)

Size: USLetter	Date: 2025-03-16	**Rev: 2**
KiCad E.D.A. 9.0.0		Id: 9/11

(Will Be Copy of R0 Controls)

Bruce MacKinnon KC1FSZ

Sheet: /Controls 1/
File: controls_1.kicad_sch

Title:

Size: USLetter	Date: 2025-03-16	**Rev: 2**
KiCad E.D.A. 9.0.0		Id: 10/11



Bruce MacKinnon KC1FSZ

Sheet: /Power/
File: power.kicad_sch

Title: Power

Size: USLetter	Date: 2025-03-16	**Rev: 2**
KiCad E.D.A. 9.0.0		Id: 11/11