

[home](#) [articles](#) [quick answers](#) [discussions](#) [features](#) [community](#) [help](#)

# CAtlBitmapButton - ATL/WTL Ownerdraw Superclassed Bitmap Button



Amit Dey, 12 Jun 2001

Rate:

★★★★☆ 3.29 (6 votes)

An owner drawn ATL/WTL bitmap button

&lt;!-- Download Links --&gt;



[Download source files - 84 Kb](#)

## Introduction

Recently, in one of my projects, I needed to build a simple user interface consisting of a series of bitmap buttons in a dialog. Something simple and probably easy to use. About the same time, I came across **David Pizzolato's** very nice article on skinned button at [codeproject.com](http://codeproject.com), that got me thinking. What came out of the whole endeavour was [CAtlBitmapButton](#) - an ATL/WTL ownerdrawn superclassed bitmap button. The class is not really complete and represents work in progress. I'll be glad if any of you find this useful 😊.

The [CAtlBitmapButton](#) class is very friendly and you can learn to use it in no time. The hardest part might be drawing the bitmaps (if you are as artistically challenged as I am !).

Now let's get down to the basics. We'll be building an ATL/WTL Dialog-based application so I assume you are slightly familiar with ATL/WTL and ATL Windowing.



## How to use

To build the client, fire up Visual C++ and create a new Win32 application . Next we shall rig up ATL support to the project. Since we'd like to have ATL Wizard support, just follow the instructions step-by-step. If you already know how to do this, you can skip this part. First, in project's stdafx.h file, replace

```
#include <ltwindows.h>
```

[Hide](#) [Copy Code](#)

with

```
#define RICHEDIT_VER 0x0100
#include <atlbase.h>
extern CComModule _Module;
#include <atlcom.h>
#include <atlwin.h>
#include <atlapp.h>
#include <atlctrls.h>
```

[Hide](#) [Copy Code](#)

Now add a new IDL file to the project that contains a blank library definition block like

```
library <Project Name>
{
};
```

[Hide](#) [Copy Code](#)

Now, in the ClassView, right-click the IDL file you just added, and choose **Settings**. In the **General** tab of the project settings dialog, check the **Exclude file from build** option.

Next modify your projects .cpp file so that it looks like:

```
CComModule _Module;

BEGIN_OBJECT_MAP(ObjectMap)
END_OBJECT_MAP()

int APIENTRY WinMain(HINSTANCE hInstance,
                    HINSTANCE hPrevInstance,
                    LPSTR lpCmdLine,
```

[Hide](#) [Copy Code](#)

```

        int nCmdShow)
{
    // TODO: Place code here.
    _Module.Init(0, hInstance);

    _Module.Term();
    return 0;
}

```

Having rigged up ATL/WTL support, goto **Insert->New ATL Object**. In the **Miscellaneous** category, choose **Dialog** and click on **Next**. Enter the short name as **Dialog**.

In the dialog resource, add 4 buttons (**IDC\_BUTTON1**, **IDC\_BUTTON2**, **IDC\_BUTTON3** and **IDC\_BUTTON4**) and set the **Ownerdraw** properties of these buttons to true. You would also need to add a few bitmaps to the project such that each button has three state bitmaps (Selected, Down and Over).

Add the file, *CAtlBitmapButton.h* to the project. In ClassView, right click the dialog class and add four member variables of type CAtlBitmapButton to it like

[Hide](#) [Copy Code](#)

```
CAtlBitmapButton m_button1, m_button2, m_button3, m_button4;
```

In the dialog's OnInitDialog(), add the following code :

[Hide](#) [Copy Code](#)

```

m_button1.SubclassWindow(GetDlgItem(IDC_BUTTON1));
m_button1.LoadStateBitmaps(IDB_LOADU, IDB_LOADD, IDB_LOAD);

m_button2.SubclassWindow(GetDlgItem(IDC_BUTTON2));
m_button2.LoadStateBitmaps(IDB_PLAYU, IDB_PLAYD, IDB_PLAY);

m_button3.SubclassWindow(GetDlgItem(IDC_BUTTON3));
m_button3.LoadStateBitmaps(IDB_SAVEU, IDB_SAVED, IDB_SAVE);

m_button4.SubclassWindow(GetDlgItem(IDC_BUTTON4));
m_button4.LoadStateBitmaps(IDB_QUITU, IDB_QUITD, IDB_QUIT);

```

CAtlBitmapButton has a method LoadStateBitmaps() to load the state bitmaps. The last thing to do is to add the ATL macro REFLECT\_NOTIFICATIONS() to the dialog's message map like:

[Hide](#) [Copy Code](#)

```

BEGIN_MSG_MAP(CDialog)
MESSAGE_HANDLER(WM_INITDIALOG, OnInitDialog)
COMMAND_ID_HANDLER(IDOK, OnOK)
COMMAND_ID_HANDLER(IDCANCEL, OnCancel)
COMMAND_ID_HANDLER(ID_QUIT, OnQuit)
REFLECT_NOTIFICATIONS()
END_MSG_MAP()

```

Build the project and run it. Check that the buttons are displaying the correct state bitmap. To handle button-clicks. use ATL macro COMMAND\_ID\_HANDLER() in the message map as shown in above code for the OK and Cancel button. OnCancel looks like:

[Hide](#) [Copy Code](#)

```

LRESULT OnCancel(WORD wNotifyCode, WORD wID, HWND hWndCtl, BOOL& bHandled)
{
    EndDialog(wID);
    return 0;
}

```

That's it. Yippee!  
Have fun.

## Acknowledgements

David Pizzolato.

## License

This article has no explicit license attached to it but may contain usage terms in the article text or the download files themselves. If in doubt please contact the author via the discussion board below.

A list of licenses authors might use can be found [here](#)

## Share

EMAIL

## About the Author



### Amit Dey

Web Developer

India

Amit Dey is a freelance programmer from Bangalore, India. Chiefly programming VC++/MFC, ATL/COM and PocketPC and Palm platforms. Apart from programming and CP, he is a self-taught guitar and keyboard player.

He can be contacted at [visualcdev@hotmail.com](mailto:visualcdev@hotmail.com)

## You may also be interested in...

[Reach: Intel® Edison based device is making highly precise GPS affordable for everyone](#)

[Looking Back: One Year of Microsoft Edge](#)

[A Lap Around @ChakraCore](#)

[Getting to Know the Arduino 101 Platform](#)

[Visual COBOL New Release: Small point. Big deal](#)

[Non-Tech Factors to Consider When Choosing Your Tech Stack](#)

## Comments and Discussions

Add a Comment or Question



Search Comments


Go


First Prev Next


Need Help 📌


Why not use the CBitmapButton class? 📌


Last Visit: 22-Jun-16 16:55    Last Update: 22-Jun-16 17:17    Refresh    1


 General


 News


 Suggestion


 Question


 Bug

 Answer

 Joke

 Praise

 Rant

 Admin

Use Ctrl+Left/Right to switch messages, Ctrl+Up/Down to switch threads, Ctrl+Shift+Left/Right to switch pages.

[Permalink](#) | [Advertise](#) | [Privacy](#) | [Terms of Use](#) | [Mobile](#)

Layout: [fixed](#) | [fluid](#)

Article Copyright 2001 by Amit Dey

Everything else Copyright © [CodeProject](#), 1999-2016