Resources ▾

iskeyword

Determine if input is MATLAB keyword

Syntax

```
tf = iskeyword(s)
k = iskeyword
```

Description

`tf = iskeyword(s)` returns logical `1` (`true`) if the input is a keyword in the MATLAB® language and logical `0` (`false`) otherwise. For more information about MATLAB keywords, see Keywords. example

`k = iskeyword` returns a list of all MATLAB keywords. example

Examples

collapse all

Determine If Input Is MATLAB Keyword

Test if the word `while` is a MATLAB keyword.

Open in MATLAB Online

Copy Command

```
s = "while";
tf = iskeyword(s)
```

Get

```
tf = logical
   1
```

Test if the word `myStr` is a MATLAB keyword.

```
s2 = "myStr";
tf = iskeyword(s2)
```

Get

```
tf = logical
   0
```

Query MATLAB Keywords

Get a list of all MATLAB keywords.

Open in MATLAB Online

Copy Command

```
k = iskeyword
```

Get

```
k = 20×1 cell
    {'break'     }
    {'case'      }
    {'catch'     }
    {'classdef'  }
    {'continue'  }
    {'else'      }
    {'elseif'    }
    {'end'       }
    {'for'       }
    {'function'  }
    {'global'    }
    {'if'        }
    {'otherwise' }
    {'parfor'    }
    {'persistent'}
    {'return'    }
    {'spmd'      }
    {'switch'    }
    {'try'       }
    {'while'     }
```

Input Arguments

collapse all

s — Potential MATLAB keyword
string scalar | character vector

Potential MATLAB keyword, specified as a string scalar or character vector.

Output Arguments

collapse all

`tf` — True or false result
1 | 0

True or false result, returned as a `1` or `0` of data type `logical`.

k — MATLAB keywords
cell array of character vectors

MATLAB keywords, returned as a cell array of character vectors.

More About

collapse all

Keywords

Keywords are identifiers in MATLAB code that have a reserved meaning, so they cannot be used as variable names. See Query MATLAB Keywords for a list of all MATLAB keywords.

Extended Capabilities

expand all

C/C++ Code Generation
Generate C and C++ code using MATLAB® Coder™.

GPU Code Generation
Generate CUDA® code for NVIDIA® GPUs using GPU Coder™.

Thread-Based Environment
Run code in the background using MATLAB® `backgroundPool` or accelerate code with Parallel Computing Toolbox™ `ThreadPool`.

Version History

Introduced before R2006a

See Also

Functions

`isvarname` | `matlab.lang.makeValidName` | `matlab.lang.makeUniqueStrings`

Topics

Use is* Functions to Detect State