

The diagram illustrates a 1Hz square wave generator circuit. It features a central ICM7555 timer (U1) configured in astable mode. The power supply is +9V, connected to the VCC pin (pin 8) and the GND pin (pin 1). The TR pin (pin 2) and CV pin (pin 5) are connected to each other and to the GND pin. The R pin (pin 4) is connected to the GND pin. The Q pin (pin 3) is connected to the GND pin. The DIS pin (pin 7) is connected to the GND pin. The THR pin (pin 6) is connected to the GND pin. The timing network consists of a resistor R1 (10k) and a capacitor C1 (10uF) connected between the Q pin and the GND pin. The output of the timer (Q pin) is connected to the anode of LED D1. The cathode of LED D1 is connected to the anode of LED D2. The cathode of LED D2 is connected to the GND pin. The output signal is labeled 1Hz_Output1. The circuit is powered by a +9V source connected to the VCC pin (pin 8) and the GND pin (pin 1). The TR pin (pin 2) and CV pin (pin 5) are connected to each other and to the GND pin. The R pin (pin 4) is connected to the GND pin. The Q pin (pin 3) is connected to the GND pin. The DIS pin (pin 7) is connected to the GND pin. The THR pin (pin 6) is connected to the GND pin. The timing network consists of a resistor R1 (10k) and a capacitor C1 (10uF) connected between the Q pin and the GND pin. The output of the timer (Q pin) is connected to the anode of LED D1. The cathode of LED D1 is connected to the anode of LED D2. The cathode of LED D2 is connected to the GND pin. The output signal is labeled 1Hz_Output1.

Circuito Integrado 555:Montagem em Astável, Blinking LEDs	
By: Bruna Madeira	
IEEP- Automação, Robotica e Controle Industrial	
Sheet: 7	
File: CL555.kicad_sch	
Title: Circuito Integrado 555	
Size: A4	Rev: 1.0
Date:	Id: 1/1
KiCad E.D.A. 9.0.5	