

EV_ParkingSensor_Shield_REV.2

The schematic diagram illustrates the wiring for the EV_ParkingSensor_Shield_REV.2. It features an Arduino Uno microcontroller connected to several peripheral components:

- LCD-SS16002L:** Connected to the Arduino's DB0-DB7 pins. The LCD's VDD is connected to the 5V pin, and its GND is connected to the GND pin.
- Andasho_LIN0:** Connected to the Arduino's D0-D13 pins. The module's VIN is connected to the 5V pin, and its GND is connected to the GND pin.
- Buzzer:** Connected to the Arduino's GND and a 5V pin.
- Ultrasonic Sensor:** Connected to the Arduino's GND, VCC, and TRIG pins.
- Power Regulation:** A 5V regulator is connected to the 5V pin, and a 10k potentiometer is connected to the 5V pin.

EV_ParkingSensor_Shield

By: Bruna Madeira
IEFP – Técnico Especialista em Automação, Robótica e Controlo Industrial
Sheet: /
File: EV_ParkingSensor_Shield_rev2.kicad_sch
Title: EV_ParkingSensor_Shield
Size: A4 Date: Rev: 2.0
KiCad E.D.A. 9.0.7 Id: 1/1

By: Bruna Madeira
IEFP – Técnico Especialista em Automação, Robótica e Controlo Industrial
Sheet: /
File: EV_ParkingSensor_Shield_rev2.kicad_sch

Title: EV_ParkingSensor_Shield

Size: A4	
KiCad E.D.A. 9.0.7	

Date:

Rev: 2.0
Id: 1/1