

Maintenance Scheduling System

Christian Brunbjerg Jespersen

Technical University of Denmark

January 1, 1980

Agenda

- ▶ Introduction to Maintenance Scheduling
- ▶ Architecture of a Scheduling System
- ▶ Possible Contributions to Operation Research

Mathematical Notation: Sets

$a \in$

$A_{b,c}^m(t, x, y)$

- ▶ a: set element
- ▶ A: set itself
- ▶ b: set element from set B
- ▶ c: set element from set C
- ▶ m: model formulation m
- ▶ t: time
- ▶ x: value of decision variable from a different model
- ▶ y: value of decision variable from a different model

Mathematical Notation: Parameters

*name_of_parameter*_{a,b}(*t*, *x*, *y*)

- ▶ parameters are functions of set elements and input parameters
- ▶ a: set element from A
- ▶ b: set element from B
- ▶ t: time
- ▶ x: value of decision variable from another model
- ▶ y: value of decision variable from another model

Mathematical Notation: Variables

$$x_{a,b}^m(t)$$

- ▶ variables are functions of set elements, specified model, and time
- ▶ x: decision variable
- ▶ a: set element from A
- ▶ b: set element from B
- ▶ m: specifying the model
- ▶ t: time
- ▶ Notice: decision variables cannot depend on other decision variables as it would make them belong to the same model.

Strategic

Meta variables:

$$s \in S \quad (1)$$

$$\tau \in [0, \infty] \quad (2)$$

Minimize:

$$\begin{aligned} & + \sum_{w \in W(\tau)} \sum_{p \in P(\tau)} \text{strategic_urgency}_{wp}(\tau) \cdot \alpha_{wp}(\tau) \\ & + \sum_{p \in P(\tau)} \sum_{r \in R(\tau)} \text{strategic_resource_penalty} \cdot \epsilon_{pr}(\tau) \\ & - \sum_{p \in P(\tau)} \sum_{w1 \in W(\tau)} \sum_{w2 \in W(\tau)} \text{clustering_value}_{w1, w2} \cdot \alpha_{w1p}(\tau) \cdot \alpha_{w2p}(\tau) \end{aligned} \quad (3)$$

Subject to:

$$\begin{aligned} \sum_{w \in W(\tau)} \text{work_order_workload}_{wr} \cdot \alpha_{wp}(\tau) & \leq \sum_{t \in T(\tau)} \psi_{prt}(\tau) + \epsilon_{pr}(\tau) \\ \forall p \in P(\tau) \quad \forall r \in R(\tau) \end{aligned} \quad (4)$$

$$\sum_{r \in R(\tau)} \psi_{prt}(\tau) \leq \text{technician_work}_{pt}(\tau, \beta(\tau)) \quad \forall p \in P(\tau) \quad \forall t \in T(\tau) \quad (5)$$

$$\sum_{p \in P(\tau)} \psi_{prt}(\tau) \leq \text{technician_skills}_{rt}(\tau) \quad \forall r \in R(\tau) \quad \forall t \in T(\tau) \quad (6)$$

$$\sum_{w \in W(\tau)} \alpha_{wp}(\tau) = 1 \quad \forall p \in P(\tau) \quad (7)$$

$$\alpha_{wp}(\tau) = 0, \quad \text{if } \text{exclude}_{wp}(\tau) \quad \forall w \in W(\tau) \quad \forall p \in P(\tau) \quad (8)$$

$$\alpha_{wp}(\tau) = 1, \quad \text{if } \text{include}_{wp}(\tau) \quad \forall w \in W(\tau) \quad \forall p \in P(\tau) \quad (9)$$

$$\alpha_{wp}(\tau) \in \{0, 1\} \quad \forall w \in W(\tau) \quad \forall p \in P(\tau) \quad (10)$$

$$\psi_{prt}(\tau) \in \mathbb{R}^+ \quad \forall p \in P(\tau) \quad \forall r \in R(\tau) \quad \forall t \in T(\tau) \quad (11)$$

$$\epsilon_{pr}(\tau) \in \mathbb{R}^+ \quad \forall p \in P(\tau) \quad \forall r \in R(\tau) \quad (12)$$

Meta variables:

$$s \in S \quad (13)$$

$$\alpha(\tau) \quad (14)$$

$$\tau \in [0, \infty] \quad (15)$$

Minimize:

$$\begin{aligned} & + \sum_{o \in O(\tau, \alpha(\tau))} \sum_{d \in D(\tau)} \text{tactical_value}_{do}(\tau) \cdot \beta_{do}(\tau) \\ & + \sum_{r \in R(\tau)} \sum_{d \in D(\tau)} \text{tactical_penalty} \cdot \mu_{rd}(\tau) \end{aligned} \quad (16)$$

Subject to:

$$\sum_{o \in O(\tau, \alpha(\tau))} \text{work}_o(\tau) \cdot \beta_{do}(\tau) \leq \Psi_{drt}(\tau) + \mu_{rd}(\tau) \quad \forall d \in D(\tau) \quad \forall r \in R(\tau) \quad (17)$$

$$\sum_{r \in R(\tau)} \Psi_{drt}(\tau) \leq \text{tactical_resource}_{dr}(\tau) \quad \forall d \in D(\tau) \quad \forall t \in T(\tau) \quad (18)$$

$$\sum_{d \in D(\tau)} \Psi_{drt}(\tau) \leq \text{technician_skills}_{rt}(\tau) \quad \forall r \in R(\tau) \quad \forall t \in T(\tau) \quad (19)$$

$$\beta_{do}(\tau) \leq \text{number}_o(\tau) \cdot \text{operating_time}_o \cdot \sigma_{do}(\tau) \quad \forall d \in D(\tau) \quad \forall o \in O(\tau, \alpha(\tau)) \quad (20)$$

$$\sum_{d = \text{latest_finish}_o(\tau)} \sigma_{do}(\tau) = \text{duration}_o(\tau) \quad \forall o \in O(\tau, \alpha(\tau)) \quad (21)$$

$$\sum_{d^* \in D_{\text{duration}_o(\tau)}(\tau)} \sigma_{d^*o}(\tau) = \text{duration}_o(\tau) \cdot \eta_{do}(\tau) \quad \forall o \in O(\tau, \alpha(\tau)) \quad \forall d \in D(\tau) \quad (22)$$

$$\sum_{o \in O(\tau, \alpha(\tau))} \eta_{do}(\tau) = 1, \quad \forall d \in D(\tau) \quad (23)$$

$$\sum_{d \in D(\tau)} d \cdot \sigma_{do1}(\tau) + \Delta_o(\tau) = \sum_{d \in D(\tau)} d \cdot \sigma_{do2}(\tau) \quad \forall (o1, o2) \in \text{finish_start}_{o1, o2} \quad (24)$$

$$\sum_{d \in D(\tau)} d \cdot \sigma_{do1}(\tau) = \sum_{d \in D(\tau)} d \cdot \sigma_{do2}(\tau) \quad \forall (o1, o2) \in \text{start_start}_{o1, o2} \quad (25)$$

$$\beta_{do}(\tau) \in \mathbb{R} \quad \forall d \in D(\tau) \quad \forall o \in O(\tau, \alpha(\tau)) \quad (26)$$

$$\mu_{rd}(\tau) \in \mathbb{R} \quad \forall r \in R(\tau) \quad \forall d \in D(\tau) \quad (27)$$

$$\sigma_{do}(\tau) \in \{0, 1\} \quad \forall d \in D(\tau) \quad \forall o \in O(\tau, \alpha(\tau)) \quad (28)$$

$$\eta_{do}(\tau) \in \{0, 1\} \quad \forall d \in D(\tau) \quad \forall o \in O(\tau, \alpha(\tau)) \quad (29)$$

$$\Delta_o(\tau) \in \{0, 1\} \quad \forall o \in O(\tau, \alpha(\tau)) \quad (29)$$

Supervisor

Meta variables:

$$z \in Z \quad (30)$$

$$\alpha(\tau) \quad (31)$$

$$\theta(\tau) \quad (32)$$

$$\tau \in [0, \infty] \quad (33)$$

Maximize:

$$\sum_{a \in A(\tau, \alpha(\tau))} \sum_{t \in T(\tau)} \text{supervisor_value}_{at}(\tau, \lambda_t(\tau), \Lambda_t(\tau)) \cdot \gamma_{at}(\tau) \quad (34)$$

Subject to:

$$\sum_{a \in A_o(\tau, \alpha(\tau))} \rho_a(\tau) = \text{work}_o(\tau) \quad \forall o \in O(\tau, \alpha(\tau)) \quad (35)$$

$$\sum_{t \in T(\tau)} \sum_{a \in A_o(\tau, \alpha(\tau))} \gamma_{at}(\tau) = \phi_o(\tau) \cdot \text{number}_o(\tau) \quad \forall o \in O(\tau, \alpha(\tau)) \quad (36)$$

$$\sum_{o \in O_w(\tau, \alpha(\tau))} \phi_o(\tau) = |O_w(\tau, \alpha(\tau))| \cdot \Phi_w(\tau) \quad \forall w \in W(\tau, \alpha(\tau)) \quad (37)$$

$$\sum_{a \in A_o(\tau, \alpha(\tau))} \gamma_{at}(\tau) \leq 1 \quad \forall o \in O(\tau, \alpha(\tau)) \quad \forall t \in T(\tau) \quad (38)$$

$$\gamma_{at}(\tau) \leq \text{feasible}_{at}(\theta(\tau)) \quad \forall a \in A_o(\tau, \beta) \quad (\tau) \forall o \in O(\tau, \alpha(\tau)) \quad \forall t \in T(\tau) \quad (39)$$

$$\gamma_{at}(\tau) \in \{0, 1\} \quad \forall o \in O(\tau, \alpha(\tau)) \quad \forall t \in T(\tau) \quad (40)$$

$$\phi_o(\tau) \in \{0, 1\} \quad \forall o \in O(\tau, \alpha(\tau)) \quad (41)$$

$$\Phi_w(\tau) \in \{0, 1\} \quad \forall w \in W(\tau, \alpha(\tau)) \quad (42)$$

$$\rho_a(\tau) \in [\text{lower_activity_work}_a(\tau), \text{work}_a(\tau)] \quad \forall a \in A(\tau, \alpha(\tau)) \quad (43)$$

Operational

Meta variables:

$$t \in \mathcal{T}(\tau) \quad (44)$$

$$\alpha(\tau) \quad (45)$$

$$\gamma(\tau) \quad (46)$$

$$\tau \in [0, \infty] \quad (47)$$

Maximize:

$$\sum_{a \in A(\tau, \gamma_t(\tau))} \sum_{k \in K(\gamma(\tau))} \delta_{ak}(\tau) \quad (48)$$

Subject to:

$$\sum_{k \in K(\gamma(\tau))} \delta_{ak}(\tau) \cdot \pi_{ak}(\tau) = \text{activity_work}_a(\tau, \rho(\tau)) \cdot \theta_a(\tau) \quad \forall a \in A(\tau, \gamma_t(\tau)) \quad (49)$$

$$\lambda_{a21}(\tau) \geq \Lambda_{a1, \text{last}(a1)}(\tau) + \text{preparation}_{a1, a2} \quad \forall a1 \in A(\tau, \gamma_t(\tau)) \quad \forall a2 \in A(\tau, \gamma_t(\tau)) \quad (50)$$

$$\begin{aligned} \lambda_{ak}(\tau) &\geq \Lambda_{ak-1}(\tau) - \text{constraint_limit} \cdot (2 - \pi_{ak}(\tau) + \pi_{ak-1}(\tau)) \\ &\quad \forall a \in A(\tau, \gamma_t(\tau)) \quad \forall k \in K(\gamma(\tau)) \end{aligned} \quad (51)$$

$$\delta_{ak}(\tau) = \Lambda_{ak}(\tau) - \lambda_{ak}(\tau) \quad \forall a \in A(\tau, \gamma_t(\tau)) \quad \forall k \in K(\gamma(\tau)) \quad (52)$$

$$\begin{aligned} \lambda_{ak}(\tau) &\geq \text{event}_{ie} + \text{duration}_{ie} - \text{constraint_limit} \cdot (1 - \omega_{akie}(\tau)) \\ &\quad \forall a \in A(\tau, \gamma_t(\tau)) \quad \forall k \in K(\gamma(\tau)) \quad \forall i \in I(\tau) \quad \forall e \in E(\tau) \end{aligned} \quad (53)$$

$$\begin{aligned} \Lambda_{ak}(\tau) &\leq \text{event}_{ie} + \text{constraint_limit} \cdot \omega_{akie}(\tau) \\ &\quad \forall a \in A(\tau, \gamma_t(\tau)) \quad \forall k \in K(\gamma(\tau)) \quad \forall i \in I(\tau) \quad \forall e \in E(\tau) \end{aligned} \quad (54)$$

$$\lambda_{a1}(\tau) \geq \text{time_window_start}_a(\beta(\tau)) \quad \forall a \in A(\tau, \gamma_t(\tau)) \quad (55)$$

$$\Lambda_{a, \text{last}(a)}(\tau) \leq \text{time_window_finish}_a(\beta(\tau)) \quad \forall a \in A(\tau, \gamma_t(\tau)) \quad (56)$$

$$\pi_{ak}(\tau) \in \{0, 1\} \quad \forall a \in A(\tau, \gamma_t(\tau)) \quad \forall k \in K(\gamma(\tau)) \quad (57)$$

$$\begin{aligned} \lambda_{ak}(\tau) &\in [\text{availability_start}(\tau), \text{availability_finish}(\tau)] \\ &\quad \forall a \in A(\tau, \gamma_t(\tau)) \quad \forall k \in K(\gamma(\tau)) \end{aligned} \quad (58)$$


$$\begin{aligned} \Lambda_{ak}(\tau) &\in [\text{availability_start}(\tau), \text{availability_finish}(\tau)] \\ &\quad \forall a \in A(\tau, \gamma_t(\tau)) \quad \forall k \in K(\gamma(\tau)) \end{aligned} \quad (59)$$

$$\delta_{ak}(\tau) \in [0, \text{work}_{a_to_o(a)}(\tau)] \quad \forall a \in A(\tau, \gamma_t(\tau)) \quad \forall k \in K(\gamma(\tau)) \quad (60)$$

$$\omega_{akie}(\tau) \in \{0, 1\} \quad \forall a \in A(\tau, \gamma_t(\tau)) \quad \forall k \in K(\gamma(\tau)) \quad \forall i \in I(\tau) \quad \forall e \in E(\tau) \quad (61)$$

$$\theta_a(\tau) \in \{0, 1\} \quad \forall a \in A(\tau, \gamma_t(\tau)) \quad (62)$$

Architecture



Managing metahe


Solution sharing (

Actor-based Optim

Data storage (Me

Message passing (

Architecture



Managing metahe

Solution sharing (


Actor-based Optim

Data storage (Me

Message passing (



1. Reactive Versus Static Constraints
2. Dynamic
3. Business
4. Technical
5. Academic

Dynamic versus Static Models



- ▶ Mathematical models guide direction but does not provide direct solutions.
- ▶ Static solutions are rarely fully executable.
- ▶ Dynamic models are less constrained and ensure a contained optimal solution.
- ▶ Remember: The real optimal solution is ever knowable at time $= 0$

Model setup



Persistence



Atomic Point

Metaheuristi

Orchestratio

User interfac

Model setup



Persistence


Atomic Point

Metaheuristic

Orchestration

User interface

Model setup



Persistence



Atomic Point

Metaheuristi



Orchestratio

User interfacer

Model setup



Model setup



Persistence

Atomic Point


Metaheuristi

Orchestratio


User interface

The Story of Zaabalawi


Quality of Solutions



Business




Atomic Pointer Swapping




Thread one finds a better solution and swaps it in

Atomic Pointer Swapper



Thread two and three loads the new Shared Solution at the top of their optimization loop



Shared Solution 1 is dropped from memory when is it no longer referenced by any threads

