

PRD: Lesson Quiz Formats

1. Overview

5Mins currently offers only single-answer multiple-choice questions (MCQ) at the end of its ~5-minute micro-lessons. This format is passive, highly guessable, and does little to reinforce learning material — a critical shortcoming for a platform serving frontline and shift workers in hospitality, finance, and healthcare who need to retain compliance knowledge. Drag-and-drop / mix-and-match is the most-requested new quiz type from users, and many prospects migrating from competitor Skillcast expect richer interaction formats.

This initiative is research-led and design-focused. It defines a small, accessible, tap/select-only core of new quiz formats — **Match-the-Pairs**, **Fill-in-the-Blank (word bank with free-type toggle)**, and **Sequence Assembly** — layered on the existing MCQ/true-false backbone. All formats share a single reusable question-renderer component, are mobile-first (tap-only, no drag), meet WCAG 2.2 AA, and integrate with existing 5Mins gamification primitives (streaks, points). True drag-and-drop, open-ended/video grading, and AI-assisted question generation are explicitly out of scope for v1.

2. Jobs To Be Done

Main Job

When I finish a 5-minute compliance lesson on my phone during a break, I want the end-of-lesson quiz to actively test whether I understood the material — not just let me guess my way through — so I can feel confident that I actually learned something and my time was well spent.

The learner is "hiring" new quiz formats to replace the current passive MCQ tap-through. The current solution is being "fired" because it fails to create a sense of active engagement, provides no meaningful retrieval practice, and makes the quiz feel like a checkbox rather than a learning moment.

Job Map

Stage	What the Learner Does Today	Where It Falls Short	Opportunity
Define	Learner opens a lesson knowing a quiz follows	No expectation of challenge — "I'll just guess through it"	Set a curiosity-gap hook that pulls learners into the quiz (Brilliant pattern)
Locate	Reaches the quiz at lesson end	Single format every time — no variety, no surprise	Introduce format variety so each quiz feels fresh

Prepare	Reads the MCQ question and options	Can often eliminate wrong answers without understanding content	Formats like fill-in-the-blank and sequence assembly require genuine recall, not elimination
Confirm	Selects an answer (single tap)	No active processing — recognition only, not production	Tap-to-select matching and word-bank assembly require constructive effort
Execute	Submits answer	Binary right/wrong with no partial credit	Partial credit for matching/sequencing rewards partial understanding and reduces frustration
Monitor	Sees result	Minimal feedback — no explanation of why	Instant per-answer feedback with correct answer + one-line "why" explanation
Resolve	Moves on / completes lesson	No sense of accomplishment beyond streak	Tie completion into existing streak/points; celebrate correct answers with micro-interactions

Related Jobs

- **Admin/Instructor authoring job:** "When I create a lesson quiz, I want to produce engaging questions quickly without needing specialized tooling, so I can focus on content quality rather than interaction design." The reusable question-renderer and structured data model must make authoring simple across all formats.
- **Compliance officer verification job:** "When I assign compliance training, I want to trust that learners genuinely engaged with the material, so I can satisfy regulatory requirements." More rigorous formats (beyond guessable MCQ) provide better evidence of comprehension.
- **Repeat learner retention job:** "When I retake a compliance module in a new cycle, I want the quiz to feel different enough that I can't just memorize the pattern, so I actually re-engage with the content." Format variety and the fill-in-the-blank free-type toggle support this.

Emotional & Social Dimensions

- **Emotional:** Learners want to feel *capable and progressing*, not patronized by trivially easy questions. Mistakes should feel like part of learning, not failure. Partial credit and gentle "bounce-back" animations on wrong taps reduce anxiety and build confidence.
- **Social:** Frontline workers doing compliance training during shifts want to feel that their employer respects their time — that the 5 minutes spent are genuinely useful, not performative box-ticking. Active quiz formats signal that the training is real and worthwhile.
- **Identity:** Learners want to see themselves as competent professionals who know their compliance obligations, not as people being tested. The quiz should feel like practice, not examination.

3. Goals

1. **Increase active engagement** in end-of-lesson quizzes by replacing passive single-tap MCQ with formats that require constructive effort (matching, assembly, recall).
2. **Reduce guessability** so quiz completion becomes a meaningful signal of comprehension rather than a coin flip.
3. **Maintain the 5-minute lesson format** — new quiz types must fit within the existing time envelope (~10–15 short items max).
4. **Ship accessible-by-construction interactions** that meet WCAG 2.2 AA (SC 2.5.7 Dragging Movements, SC 2.5.8 Target Size) using tap/select mechanics, not drag-and-drop.
5. **Deliver mobile-first** — all interactions work on small phone screens with discrete taps, no conflict with native scroll.
6. **Build a reusable question-renderer architecture** — one component per format, one data model, usable across lesson quizzes and (later) assessments.
7. **Integrate with existing gamification** (streaks, points) rather than building parallel reward systems.

4. Job Stories

Engagement & Variety

- **When** I reach the quiz at the end of a lesson, **I want** the format to feel different from yesterday's quiz, **so I can** stay curious and engaged rather than going through the motions.
- **When** I see a matching exercise with term-definition pairs, **I want** to tap items to connect them rather than drag them across the screen, **so I can** complete the exercise comfortably on my phone without fighting scroll behavior.
- **When** I encounter a fill-in-the-blank question with a word bank, **I want** to tap chips into gaps, **so I can** actively recall and place the right term rather than just recognizing it in a list.

Feedback & Learning from Mistakes

- **When** I get a matching pair wrong, **I want** my selection to bounce back gently with the correct answer shown, **so I can** learn from the mistake without feeling punished.
- **When** I submit a sequence assembly answer with some steps in the right order, **I want** to receive partial credit for the correct portions, **so I can** feel that my partial understanding is recognized and I'm motivated to improve.
- **When** I answer any question incorrectly, **I want** to immediately see the correct answer plus a brief explanation of why, **so I can** correct my understanding in the moment rather than at the end of the quiz.

Accessibility & Mobile

- **When** I use a screen reader or keyboard to navigate a matching exercise, **I want** to Tab between tokens, press Enter to select, and hear an announcement of what I selected and placed, **so I can** complete the quiz with the same experience as sighted tap users.
- **When** I take a quiz on my phone during a work break, **I want** all tap targets to be large enough to hit accurately, **so I can** move through questions quickly without mis-taps.

Progressive Difficulty & Compliance Recall

- **When** I retake a compliance module I've passed before, **I want** the fill-in-the-blank to challenge me with free-type recall instead of a word bank, **so I can** prove (and reinforce) that I truly know the statutory phrasing.
- **When** I encounter a scenario-based question describing a workplace situation, **I want** to apply judgment to select the correct response, **so I can** practice decision-making in realistic compliance contexts.

Admin Authoring

- **When** I create a matching question for a lesson, **I want** to simply enter pairs of terms and definitions in a structured form, **so I can** author engaging content without learning a complex interaction builder.
- **When** I create quiz content for a lesson, **I want** confidence that the same question will render correctly in assessments later, **so I can** author once and reuse across learning contexts.

5. Requirements

Functional Requirements

FR1: Match-the-Pairs

ID	Requirement
FR1.1	The system shall present two columns (or groups) of items that the learner must pair by tapping.
FR1.2	Interaction model: tap an item to select it (highlighted in —selected amber), then tap its match to pair them. Tap a paired item to unpair and return both to the pool.
FR1.3	Matched pairs shall animate out (fade or slide) to reduce visual clutter and show progress.
FR1.4	Scoring shall use equal-weight-per-pair partial credit (e.g., 4 pairs = 25% each), following the Blackboard precedent.

FR1.5	On incorrect pairing, the wrong item shall "bounce back" to its original position with a brief incorrect-state indicator (red flash).
FR1.6	Support a minimum of 3 and a maximum of 8 pairs per question.
FR1.7	Each item target shall be ≥ 44 CSS px on mobile (≥ 24 CSS px minimum per WCAG 2.2 SC 2.5.8).

FR2: Fill-in-the-Blank (Word Bank)

ID	Requirement
FR2.1	The system shall display a sentence or passage with one or more gaps, and a word bank of tappable chip tokens below.
FR2.2	Learners tap a chip to select it, then tap a gap to place it (or the system auto-places into the next empty gap). Tap a placed chip to return it to the bank.
FR2.3	The word bank shall include distractors (incorrect options) to prevent trivial completion.
FR2.4	A toggle shall allow switching from assisted word-bank mode to free-type recall mode (keyboard input), configurable by the admin per question.
FR2.5	Free-type mode shall accept case-insensitive matching with configurable tolerance for minor typos.
FR2.6	Scoring: each gap scored independently; partial credit across multiple gaps in one question.

FR3: Sequence / Sentence Assembly

ID	Requirement
FR3.1	The system shall present a shuffled set of token chips that the learner must tap in the correct order to assemble a sentence, process, or sequence.
FR3.2	Tapped tokens move from the bank to an answer area in the order tapped. Tap a placed token to return it to the bank.
FR3.3	Scoring shall support two configurable modes: (a) position-based (exact slot match — for regulatory step-by-step procedures) and (b) pairwise/relative-order (more forgiving — for prioritization tasks).
FR3.4	Support 3–10 tokens per question.

FR4: Scenario-Anchored MCQ

ID	Requirement
FR4.1	The system shall support a content pattern where a short vignette (2–4 sentences describing a workplace situation) precedes a standard single- or multi-select MCQ.

FR4.2	This is a content/template pattern layered on the existing MCQ renderer — no new interaction mechanic required.
FR4.3	Admin authoring UI shall provide a dedicated "scenario" text field above the question stem.

FR5: Instant Feedback

ID	Requirement
FR5.1	Every question type shall provide instant per-answer feedback upon submission: green/correct flash or red/incorrect flash.
FR5.2	On incorrect answers, the system shall always reveal the correct answer plus a one-line "why" explanation (authored by admin).
FR5.3	For matching and word-bank formats, wrong taps shall bounce back with low penalty — no harsh error states.
FR5.4	Feedback shall be reactive and in-the-moment, not deferred to end-of-quiz summary.

FR6: Accessibility (WCAG 2.2 AA)

ID	Requirement
FR6.1	All interactions shall be tap/select only — no drag-and-drop. This satisfies WCAG 2.2 SC 2.5.7 (Dragging Movements) by construction.
FR6.2	Full keyboard operability: Tab between tokens/targets, Enter/Space to select and place, Esc to cancel selection.
FR6.3	Use semantic <code><button></code> elements with <code>aria-pressed</code> or <code>aria-selected</code> states. Do not use deprecated <code>aria-grabbed</code> / <code>aria-dropeffect</code> .
FR6.4	Each question widget shall include an <code>aria-live</code> region that announces select, place, and return actions to screen readers.
FR6.5	Interactive targets ≥ 24 CSS px (WCAG SC 2.5.8 minimum); ≥ 44 CSS px recommended and required on mobile viewports.
FR6.6	Selected state shall use the project's <code>--selected</code> amber token. Never indicate selection via opacity alone.

FR7: Reusable Question Renderer Architecture

ID	Requirement
FR7.1	Each format shall be implemented as a single reusable question-renderer component — one implementation of interaction, scoring, and feedback.

FR7.2	The question data model shall carry: question type, answer structure (ordered list, pair mapping, gap/word-bank fills), content fields, scoring metadata (partial-credit weights, scoring mode), and admin-authored explanation.
FR7.3	The same renderer and grader shall serve lesson quizzes and (later) assessments and other learning contexts — no per-context forks.
FR7.4	The data model shall be structured so that AI-generated content could target any format in a future initiative.

FR8: Gamification Integration

ID	Requirement
FR8.1	Quiz completion and scoring shall feed into the existing 5Mins streak and points system.
FR8.2	Correct-answer celebrations shall use micro-interactions (animation) consistent with existing gamification UI.
FR8.3	No parallel or new reward system shall be introduced.

FR9: Microlearning Constraints

ID	Requirement
FR9.1	A quiz shall contain a maximum of 10–15 items to protect the 5-minute lesson format.
FR9.2	Mixed-format quizzes (e.g., 2 MCQ + 1 matching + 1 fill-in-blank) shall be supported.

6. Research & Best Practices

Synthesis

The research strongly validates the decision to use **tap/select interactions rather than true drag-and-drop**. WCAG 2.2 SC 2.5.7 (Level AA) requires every drag-based function to be achievable with a single pointer without dragging; button-based tap-to-select combined with keyboard shortcuts provides the most accessible pattern ([TestParty WCAG 2.5.7 Guide](#)). This is not merely a theoretical concern: approximately 15 million Americans have conditions affecting upper limb mobility that prevent precise drag-and-drop control, and the European Accessibility Act became effective June 2025, making compliance a near-term legal requirement ([AccessiCart Dragging Movements Guide](#)). Manual testing remains essential, as automated tools detect only 30–40% of WCAG 2.2 EdTech accessibility issues — all drag alternatives should be tested with keyboard-only navigation ([Hireplicity EdTech Accessibility Tests](#)).

Duolingo's interaction model is the primary benchmark. Its lesson flow uses progressive difficulty: challenges 1–3 are multiple choice (recognition), 4–7 use word bank tap-to-select (constrained production), 8–11 require typing (full production), and 12–14 mix formats. The word bank interaction is

fully reversible — tap to select, tap again to remove — supporting user control and reducing anxiety ([925 Studios Duolingo Breakdown](#)). Duolingo's "play first, profile second" approach and its streak-based loss aversion are the most powerful retention tools ([Blake Crosley Duolingo Guide](#)), validating 5Mins' existing gamification primitives as the right reward system to integrate with.

Partial credit scoring is strongly supported by evidence. A study of partial credit on MCQs in pharmacology found it improved student performance and created a more encouraging assessment experience, with lower-performing students showing greater score increases. Themes included recognition of effort, reduced pressure, increased confidence, and motivation to learn from mistakes ([Schneid et al., BJCP 2025](#)). Blackboard Ultra's matching questions distribute credit as a percentage across matching pairs by default, providing the standard LMS precedent ([Blackboard Matching Questions](#)).

SC Training (formerly EdApp), a leading mobile-first microlearning platform for frontline workers, offers matching, fill-in-the-blank, sequencing, and categorization quiz types with 10–15 questions per quiz and 80%+ completion rates — their use case closely mirrors 5Mins ([SC Training Quiz Types](#)). The broader eLearning landscape recommends eight interactive formats including match-the-pair, fill-in-the-blanks, sequencing, and sorting/classification ([eLearning Industry Quiz Formats](#)). Question variety itself is a key engagement driver for digitally distracted workforces, and retrieval practice — testing knowledge by asking learners to recall information — is particularly powerful when spaced after training sessions ([Qstream Microlearning](#)).

UX References

App	Flow / Screen	Mobbin URL	Pattern Description	Relevance
Duolingo	Quiz matching pairs — tap to select	View	Match-the-pairs interaction with tap-to-select	Direct reference for the match-the-pairs format; shows tap-based pair matching UI on mobile
Duolingo	Matching pairs exercise variant	View	Match-the-pairs with visual feedback on selection	Shows how matched pairs are visually indicated and remaining pairs presented
Duolingo	Matching exercise with progress	View	Match-the-pairs mid-exercise state	Demonstrates progress indicator and mid-quiz state for matching exercises
Quizlet	Quiz matching/flashcard interaction	View	Card-based matching quiz	Alternative matching pattern from a study/quiz-focused app
Nibble	Learning quiz with tap selection	View	Tap-to-select quiz in compliance learning app	Nibble targets compliance/financial

				learning — close to 5Mins persona
Duolingo	Fill-in-the-blank with word bank	View	Word bank chips below sentence gap	Core reference for fill-in-the-blank: tappable chips placed into sentence gaps
Duolingo	Word bank sentence completion	View	Tap word chips to fill sentence	Shows the chip-in-gap interaction mid-completion with placed and available tokens
Duolingo	Word bank with free-type toggle	View	Word bank with keyboard input option	Critical reference: shows the toggle between assisted word-bank and free-type recall
Duolingo	Sentence completion feedback	View	Fill-in-blank result with correct/incorrect feedback	Shows the instant feedback state after submitting a fill-in-the-blank answer
Duolingo	Sentence assembly from shuffled bank	View	Full sentence construction from chips	Direct reference for sequence/sentence assembly format
Imprint	Fill-in-the-blank learning interaction	View	Word bank fill-in-blank in knowledge app	Alternative fill-in-blank implementation from a learning-focused app
Vocabulary	Word completion quiz	View	Fill-in-blank for vocabulary/terminology recall	Shows fill-in-blank applied to terminology recall
Duolingo	Sentence ordering / tap to assemble	View	Tap chips to order sentence	Core reference for sequence assembly: tap tokens in order to build answer
Duolingo	Sentence ordering in progress	View	Sequence assembly mid-state	Shows partially assembled sentence with remaining chips in bank
Duolingo	Sentence ordering completion	View	Completed sequence assembly	Shows fully assembled answer ready for submission
Babbel	Word ordering exercise	View	Tap-to-order sentence construction	Alternative implementation of sequence assembly from Babbel

Nibble	Correct answer feedback screen	View	Green checkmark instant correct feedback	Instant positive feedback with explanation — matches the "reveal correct answer + why" pattern
Quizlet	Quiz result feedback	View	Quiz answer result with correct/incorrect state	Answer feedback with correct answer revealed
Brilliant	Quiz interaction with feedback	View	Interactive quiz with curiosity-gap pattern	Brilliant's approach to quiz engagement with explanatory feedback
Duolingo ABC	Correct answer celebration	View	Celebration animation on correct answer	Reward micro-interaction after correct answer — relevant for gamification

Built for Mars Lessons

Title	Type	builtformars.com URL	Lesson	Relevance
Time-Limited Onboarding (Queue)	UX Bite	View	Queue limits matching exercises to 30 seconds, reframing the task as "what can you get done in 30 seconds?" — time constraints reduce decision fatigue, increase interactions, and improve input quality versus open-ended matching.	Directly applicable to keeping quiz interactions within the 5-minute lesson; a time-bounded matching exercise prevents the interaction from dragging on and maintains microlearning pacing.
Mobbin's 404 Quiz	UX Bite	View	Gamification and play can transform even negative moments into engagement opportunities; quiz mechanics create engagement through play rather than passive consumption.	Validates the principle that varied quiz formats are engagement drivers rather than assessment tools — supports the core thesis of this initiative.
Onboarding Proof of Value (Arc)	UX Bite	View	Interactive demonstrations outperform passive instruction: users who actively interact with a feature discover value	Reinforces the core thesis: active quiz formats (matching, fill-in-blank, sequencing) will outperform passive MCQ because learners

			themselves, creating stronger conviction through curiosity-driven "Aha! Moments."	who <i>do</i> something retain better than those who merely <i>select</i> .
How to Stop People Skipping Your Onboarding (YNAB)	Case Study	View	Making engagement feel optional rather than mandatory — letting users engage directly with features while providing contextual guidance — produces better retention than blocking access behind required tutorials.	New quiz types should be introduced contextually within the lesson flow rather than requiring learners to read instructions upfront; the interaction should be self-explanatory through visual hierarchy and microcopy.
Learn UX Design from Duolingo	Company Page	View	Covers engagement mechanics, habit formation, gamification (streaks, rewards, progress), and mobile UX optimization. Specific: nudging friends in a single tap, early-day streak extensions, breaking daily records as motivation shots.	Validates Duolingo as the primary UX benchmark; confirms the gamification patterns (streak/points) that 5Mins should integrate with rather than building parallel reward systems.

7. Plan of Action

Phase 1: Architecture & Data Model (Weeks 1–2)

- ☐ Design the extended question data model supporting: question type enum (MCQ, true-false, match-pairs, fill-blank, sequence-assembly, scenario-MCQ), variable answer structures (ordered lists, pair mappings, gap/word-bank fills), scoring metadata (partial-credit weights, position-based vs. pairwise scoring mode), and admin-authored explanation text
- ☐ Define the reusable question-renderer component interface — input contract (question model), output contract (answer submission, score), and callback hooks (feedback display, gamification events)
- ☐ Validate the data model can be targeted by future AI question generation (structured enough for LLM output)
- ☐ Engineering spike: assess impact on existing quiz engine (currently assumes fixed single-answer MCQ) and identify migration/extension path

- ☐ Define API contracts for question CRUD, answer submission, and scoring

Phase 2: Core Interaction Components — Design & Build (Weeks 3–5)

- ☐ **Match-the-Pairs:** Design and build the tap-to-select, tap-to-pair interaction component with fade-out animation for matched pairs, bounce-back for incorrect pairings, and `--selected` amber highlight state
- ☐ **Fill-in-the-Blank (Word Bank):** Design and build the chip-in-gap interaction with word bank, distractor support, and the free-type toggle for progressive difficulty
- ☐ **Sequence Assembly:** Design and build the tap-to-order token assembly interaction with answer area and return-to-bank mechanics
- ☐ **Scenario-Anchored MCQ:** Add scenario text field to existing MCQ authoring and renderer (content pattern, minimal new UI)
- ☐ Implement shared interaction primitives: `<button>` semantics with `aria-pressed` / `aria-selected`, `aria-live` announcement region, keyboard navigation (Tab/Enter/Space/Esc), and ≥ 44 CSS px touch targets

Phase 3: Scoring & Feedback Engine (Week 5–6)

- ☐ Implement per-pair partial credit scoring for Match-the-Pairs (equal weight distribution)
- ☐ Implement configurable scoring for Sequence Assembly (position-based exact slot vs. pairwise relative order)
- ☐ Implement per-gap partial credit for Fill-in-the-Blank
- ☐ Build instant feedback layer: green/correct flash, red/incorrect flash, correct-answer reveal with one-line explanation, bounce-back animation for wrong taps
- ☐ Integrate scoring output with existing 5Mins streak and points system (no new reward UI)

Phase 4: Admin Authoring UI (Weeks 6–7)

- ☐ Build authoring form for Match-the-Pairs: structured pair entry (term $\leftrightarrow$ definition), 3–8 pairs, explanation field per pair
- ☐ Build authoring form for Fill-in-the-Blank: sentence editor with gap markers, word bank entry with distractors, free-type toggle setting
- ☐ Build authoring form for Sequence Assembly: ordered token list entry, scoring mode selector (position vs. pairwise), 3–10 tokens
- ☐ Add scenario text field to existing MCQ authoring form
- ☐ Support mixed-format quiz composition (admin selects format per question within a quiz of 10–15 items)

Phase 5: Accessibility & Mobile QA (Week 7–8)

- ☐ Manual keyboard-only navigation testing for all new formats (automated tools detect only 30–40% of WCAG 2.2 issues)
- ☐ Screen reader testing (JAWS, NVDA, VoiceOver) — validate `aria-live` announcements for select/place/return actions across all formats
- ☐ WCAG 2.2 AA compliance audit: SC 2.5.7 (Dragging Movements — confirm no drag required), SC 2.5.8 (Target Size — verify ≥ 24 CSS px minimum, ≥ 44 CSS px on mobile)
- ☐ Mobile device testing matrix: small-screen phones (320px width), mid-range, tablets — verify no scroll conflicts, all tap targets reachable
- ☐ Verify selected states use `--selected` amber token, never opacity-only indication

Phase 6: Pilot & Iteration (Weeks 8–10)

- ☐ Deploy to a pilot cohort of learners (select 2–3 customer accounts across hospitality, finance, healthcare)
- ☐ Instrument quiz engagement analytics: completion rate, time-per-question, format-level drop-off, partial-credit distribution
- ☐ Collect qualitative feedback from pilot learners and admins
- ☐ Iterate on interaction polish, feedback copy, and scoring calibration based on pilot data
- ☐ Prepare for general availability rollout

8. Risks & Mitigations

Risk	Impact	Mitigation
Data model extension breaks existing MCQ quiz engine	High — could disrupt current lesson quizzes in production	Engineering spike in Phase 1 to assess migration path; feature-flag new formats; ensure backward compatibility with existing MCQ data
New interactions are not self-explanatory to learners	Medium — learners confused by unfamiliar formats may abandon quiz	Follow YNAB/BFM principle: make interactions self-explanatory through visual hierarchy and microcopy, not upfront instructions; test with real frontline workers in pilot
Accessibility gaps despite tap-only design	High — legal risk (European Accessibility Act effective June 2025) and user exclusion	Build from semantic <code><button></code> elements by construction; manual screen reader and keyboard testing (not just automated); dedicated accessibility QA phase

Quiz formats extend lesson beyond 5 minutes	Medium — breaks the core microlearning value proposition	Cap at 10–15 items per quiz; time-test during pilot; consider time-limit cues inspired by BFM Queue pattern
Admin authoring complexity increases for new formats	Medium — admins resist creating matching/sequencing content if it's too complex	Design simple structured forms (pair entry, gap markers); scenario-MCQ is near-free (just a text field); validate with admin usability testing
Partial credit scoring confuses learners or admins	Low — unfamiliar scoring model may create support queries	Clear in-quiz indication of partial credit ("3 of 4 correct"); admin-facing documentation of scoring logic per format
Free-type fill-in-the-blank has typo/matching edge cases	Medium — strict matching frustrates learners; loose matching undermines accuracy	Case-insensitive by default; configurable typo tolerance; pilot testing to calibrate strictness per compliance domain
Scope creep toward AI generation, open-ended grading, or categorization	Medium — delays v1 delivery	Explicitly scoped out in this PRD; data model designed to support future formats without blocking current delivery