
Data sheet

valid from: 6/25/25





ChlorFIT Schedule 80 CORZAN® CPVC Plain End Pipe - 20 Ft Lengths

- Max Water Pressure at 73°F (22.7°C) with solvent-cemented joints

Size (inch)	P/L	Plain End Code	Lift Qty (ft)	Average O.D. (inch)	min. wall (inch)	Weight (kg)	max Pressure (psi)
¼	H06	**H0800025CG2000**	5700	0.540	0.119	0.015	1130
⅜	H06	**H0800038CG2000**	5700	0.675	0.126	0.021	920
½	H06	**H0800050CG2000**	5700	0.840	0.147	0.031	850
¾	H06	**H0800075CG2000**	5260	1.050	0.154	0.042	690
1	H06	**H0800100CG2000**	4280	1.315	0.179	0.062	630
1 ¼	H06	**H0800125CG2000**	2360	1.660	0.191	0.085	520
1 ½	H06	**H0800150CG2000**	2060	1.900	0.200	0.104	470
2	H06	**H0800200CG2000**	1660	2.375	0.218	0.144	400
2 ½	H06	**H0800250CG2000**	1080	2.875	0.276	0.218	420
3	H06	**H0800300CG2000**	840	3.500	0.300	0.294	370
3 ½	H06	**H0800350CG2000**	680	4.000	0.318	0.360	350
4	H06	**H0800400CG2000**	520	4.500	0.337	0.429	320
5	H06	**H0800500CG2000**	400	5.563	0.375	0.600	290
6	H06	**H0800600CG2000**	340	6.625	0.432	0.820	280
8	H06	**H0800800CG2000**	220	8.625	0.500	1.251	250
10	H06	**H0801000CG2000**	80	10.750	0.593	1.857	230
12	H06	**H0801200CG2000**	60	12.750	0.687	2.552	230
14	H06	**H0801400CG2000**	60	14.000	0.750	3.073	220
16	H06	**H0801600CG2000**	60	16.000	0.843	3.948	220
18	H06	**H0801800CG2000**	40	18.000	0.937	4.942	220
20	H06	**H0802000CG2000**	40	20.000	1.031	6.225	220
24	H06	**H0802400CG2000**	40	24.000	1.218	8.831	210

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/SwitzerlandPhone +41 -(0)52-631 1111e-mail: info.ps@georgfischer.comInternet: http://www.gfps.com