

# Category Theory for Quantum Natural Language Processing



Alexis TOUMI  
Wolfson College  
University of Oxford

A thesis submitted for the degree of  
*Doctor of Philosophy*

December 8, 2021



# Contents

<b>Introduction</b>	<b>1</b>
What are quantum computers good for? . . . . .	1
Why should we make NLP quantum? . . . . .	4
How can category theory help? . . . . .	8
<b>References</b>	<b>13</b>



# Introduction

## What are quantum computers good for?

Nature isn't classical, dammit, and if you want to make a simulation of nature, you'd better make it quantum mechanical, and by golly it's a wonderful problem, because it doesn't look so easy.

---

*Simulating Physics with Computers,*  
Feynman (1981)

Quantum computers harness the principles of quantum theory such as superposition and entanglement to solve information-processing tasks. In the last 42 years, quantum computing has gone from theoretical speculations to the implementation of machines that can solve problems beyond what is possible with classical means. This section will sketch a brief and biased history of the field and of its future challenges.

In 1980, Benioff [Ben80] takes the abstract definition of a computer and makes it physical: he designs a quantum mechanical system whose time evolution encodes the computation steps of a given Turing machine. In retrospect, this may be taken as the first proof that quantum mechanics can simulate classical computers. The same year, Manin [Man80] looks at the opposite direction: he argues that it would take exponential time for a classical computer to simulate a generic quantum system. Feynman [Fey82; Fey85] comes to the same conclusion and suggests a way to simulate quantum mechanics much more efficiently: building a quantum computer!

So what are quantum computers good for? Feynman's intuition gives us a first, trivial answer: at least quantum computers could simulate quantum mechanics efficiently. Deutsch [Deu85] makes the question formal by defining quantum Turing machines and the circuit model. Deutsch and Jozsa [DJ92] design the first quantum algorithm and prove that it solves *some* problem exponentially faster than any classical *deterministic* algorithm.<sup>1</sup> Simon [Sim94] improves on their result by designing a problem that a quantum computer can solve exponentially faster than any classical algorithm. Deutsch-Jozsa and Simon relied on oracles<sup>2</sup> and promises<sup>3</sup> and their problems have little practical use. However, they inspired Shor's algorithm [Sho94] for prime factorisation and discrete logarithm. These two problems are believed to require exponential time for a classical computer and their hardness is at the basis of the public-key cryptography schemes currently used on the internet.

---

<sup>1</sup>A classical *randomised* algorithm solves the problem in constant time with high probability.

<sup>2</sup>An oracle is a black box that allows a Turing machine to solve a certain problem in one step.

<sup>3</sup>The input is promised to satisfy a certain property, which may be hard to check.

In 1997, Grover provides another application for quantum computers: “searching for a needle in a haystack” [Gro97]. Formally, given a function  $f : X \rightarrow \{0, 1\}$  and the promise that there is a unique  $x \in X$  with  $f(x) = 1$ , Grover’s algorithm finds  $x$  in  $O(\sqrt{|X|})$  steps, quadratically faster than the optimal  $O(|X|)$  classical algorithm. Grover’s algorithm may be used to brute-force symmetric cryptographic keys twice bigger than what is possible classically [BBD09]. It can also be used to obtain quadratic speedups for the exhaustive search involved in the solution of NP-hard problems such as constraint satisfaction [Amb04]. Independently, Bennett et al. [Ben+97] prove that Grover’s algorithm is in fact optimal, adding evidence to the conjecture that quantum computers cannot solve these NP-hard problems in polynomial time. Chuang et al. [CGK98] give the first experimental demonstration of a quantum algorithm, running Grover’s algorithm on two qubits.

Shor’s and Grover’s discovery of the first real-world applications sparked a considerable interest in quantum computing. The core of these two algorithms has then been abstracted away in terms of two subroutines: phase estimation [Kit95] and amplitude amplification [Bra+02], respectively. Making use of both these subroutines, the HHL<sup>1</sup> algorithm [HHL09] tackles one of the most ubiquitous problems in scientific computing: solving systems of linear equations. Given a matrix  $A \in \mathbb{R}^{n \times n}$  and a vector  $b \in \mathbb{R}^n$ , we want to find a vector  $x$  such that  $Ax = b$ . Under some assumptions on the sparsity and the condition number of  $A$ , HHL finds (an approximation of)  $x$  in time logarithmic in  $n$  when a classical algorithm would take quadratic time simply to read the entries of  $A$ . This initiated a new wave of enthusiasm for quantum computing with the promise of exponential speedups for machine learning tasks such as regression [WBL12], clustering [LMR13], classification [RML14], dimensionality reduction [LMR14] and recommendation [KP16]. The narrative is appealing: machine learning is about finding patterns in large amounts of data represented as high-dimensional vectors and tensors, which is precisely what quantum computers are good at. The argument can be formalised in terms of complexity theory: HHL is BQP-complete<sup>2</sup> hence if there is an exponential advantage for quantum algorithms at all there must be one for HHL.

However, the exponential speedup of HHL comes with some caveats, thoroughly analysed by Aaronson [Aar15]. Two of these challenges are common to many quantum algorithms: 1) the efficient encoding of classical data into quantum states and 2) the efficient extraction of classical data via quantum measurements. Indeed, what HHL really takes as input is not a vector  $b$  but a quantum state  $|b\rangle = \sum_{i=1}^n b_i |i\rangle$  called its amplitude encoding. Either the input vector  $b$  has enough structure that we can describe it with a simple, explicit formula. This is the case for example in the calculation of electromagnetic scattering cross-sections [CJS13]. Or we assume that our classical data has been loaded onto a quantum random-access memory (qRAM) that can prepare the state in logarithmic time [GLM08]. Not only is qRAM a daunting challenge from an engineering point of view, in some cases it also requires too much error correction for the state preparation to be efficient

<sup>1</sup>Named after its discoverers Harrow, Hassidim and Lloyd.

<sup>2</sup>A BQP-complete problem is one that is polynomial-time equivalent to the circuit model, the hardest problem that a quantum computer can solve with bounded error in polynomial time.

[Aru+15]. Symmetrically, the output of HHL is not the solution vector  $x$  itself but a quantum state  $|x\rangle$  from which we can measure some observable  $\langle x|M|x\rangle$ . If preparing the state  $|b\rangle$  requires a number of gates exponential in the number of qubits, or if we need exponentially many measurements of  $|x\rangle$  to compute our classical output, then the quantum speedup disappears.

Shor, Grover and HHL all assume *fault-tolerant* quantum computers [Sho96]. Indeed, any machine we can build will be subject to noise when performing quantum operations, errors are inevitable: we need an error correcting code that can correct these errors faster than they appear. This is the content of the *quantum threshold theorem* [AB08] which proves the possibility of fault-tolerant quantum computing given physical error rates below a certain threshold. One noteworthy example of such a quantum error correction scheme is Kitaev’s toric code [Kit03] and the general idea of topological quantum computation [Fre+03] which offers the long-term hope for a quantum computer that is fault-tolerant “by its physical nature”. However this hope relies on the existence of quasi-particles called Majorana zero-modes, which as of 2021 has yet to be experimentally demonstrated [Bal21].

The road to large-scale fault-tolerant quantum computing will most likely be a long one. So in the meantime, what can we do with the noisy intermediate-scale quantum machines we have available today, in the so-called NISQ era [Pre18]? Most answers involve a hybrid classical-quantum approach where a classical algorithm is used to optimise the preparation of quantum states [McC+16]. Prominent examples include the quantum approximate optimisation algorithm (QAOA [FGG14]) for combinatorial problems such as maximum cut and the variational quantum eigensolver (VQE [Per+14]) for approximating the ground state of chemical systems. These variational algorithms depend on the choice of a parameterised quantum circuit called the *ansatz*, based on the structure of the problem and the resources available. Some families of ansätze such as instantaneous quantum polynomial-time (IQP) circuits are believed to be hard to simulate classically even at constant depth [SB09], opening the door to potentially near-term NISQ speedups.

Although the hybrid approach first appeared in the context of machine learning [Ban+08], the idea of using parameterised quantum circuits as machine learning models went mostly unnoticed for a decade [BLS19]. It was rediscovered under the name of quantum neural networks [FN18] then implemented on two-qubits [Hav+19], generating a new wave of attention for quantum machine learning. The idea is straightforward: 1) encode the input vector  $x \in \mathbb{R}^n$  as a quantum state  $|\phi_x\rangle$  via the ansatz of our choice, 2) initialise a random vector of parameters  $\theta \in \mathbb{R}^d$  and encode it as a measurement  $M_\theta$ , again via some choice of ansatz 3) take the probability  $y = \langle \phi(x)|M_\theta|\phi(x)\rangle$  as the prediction of the model. A classical algorithm then uses this quantum prediction as a subroutine to find the optimal parameters  $\theta$  in some data-driven task such as classification.

One of the many challenges on the way to solving real-world problems with parameterised quantum circuits is the existence of *barren plateaus* [McC+18]: with random circuits as ansatz, the probability of non-zero gradients is exponentially small in the number of qubits and our classical optimisation gets lost in a flat landscape. One can help but notice the striking similarity with the vanishing gradient problem

for classical neural networks, formulated twenty years earlier [Hoc98]. Barren plateaus do not appear in circuits with enough structure such as quantum convolutional networks [Pes+21], they can also be mitigated by structured initialisation strategies [Gra+19]. Another direction is to avoid gradients altogether and use *kernel methods* [SK19]: instead of learning a measurement  $M_\theta$ , we use our NISQ device to estimate the distance  $|\langle \phi_{x'} | \phi_x \rangle|^2$  between pairs of input vectors  $x, x' \in \mathbb{R}^n$  embedded in the high-dimensional Hilbert space of our ansatz. We then use a classical support vector machine to find the optimal hyperplane that separates our data, with theoretical guarantees to learn quantum models at least as good as the variational approach [Sch21].

Random quantum circuits may be unsuitable for machine learning, but they play a crucial role in the quest for *quantum advantage*, the experimental demonstration of a quantum computer solving a task that cannot be solved by classical means in any reasonable time. We are back to Feynman’s original intuition: sampling from a random quantum circuit is the perfect candidate for such a task. The end of 2019 saw the first claim of such an advantage with a 53-qubit computer [Aru+19]. The claim was almost immediately contested by a classical simulation of 54 qubits in two and a half days [Ped+19] then in five minutes [Yon+21]. Zhong et al. [Zho+20] made a new claim with a 76-photon linear optical quantum computer followed by another with a 66-qubit computer [Wu+21; Zhu+21]. They estimate that a classical simulation of the sampling task they completed in a couple of hours would take at least ten thousand years.

Now that quantum computers are being demonstrated to compute something beyond classical, the question remains: can they compute something *useful*?

## Why should we make NLP quantum?

A girl operator typed out on a keyboard the following Russian text in English characters: “Mi pyeryedayem mislyi posryedstvom ryechi”. The machine printed a translation almost simultaneously: “We transmit thoughts by means of speech.” The operator did not know Russian.

---

*New York Times* (8th January 1954)

The previous section hinted at the fact that quantum computing cannot simply solve any problem faster. There needs to be some structure that a quantum computer can exploit: its own structure in the case of physics simulation or the group-theoretic structure of cryptographic protocols in Shor’s algorithm. So why should we expect quantum computers to be any good at natural language processing (NLP)? This section will argue that natural language shares a common structure with quantum theory, in the form of two linguistic principles: *compositionality* and *distributionality*.

The history of artificial intelligence (AI) starts in 1950 with a philosophical question from Turing [Tur50]: “Can machines think?” reformulated in terms of a game, now known as the Turing test, in which a machine tries to convince a



human interrogator that it is human too. In order to put human and machine on an equal footing, Turing suggests to let them communicate only via written language: his thought experiment actually defined an NLP task. Only four years later, NLP goes from philosophical speculation to experimental demonstration: the IBM 701 computer successfully translated sentences from Russian to English such as “They produce alcohol out of potatoes.” [Hut04]. With only six grammatical rules and a 250-word vocabulary taken from organic chemistry and other general topics, this first experiment generated a great deal of public attention and the overly-optimistic prediction that machine translation would be an accomplished task in “five, perhaps three” years.

Two years later, Chomsky [Cho56; Cho57] proposes a hierarchy of models for natural language syntax which hints at why NLP would not be solved so fast. In the most expressive model, which he argues is the most appropriate for studying natural language, the parsing problem is in fact Turing-complete. Let alone machine translation, merely deciding whether a given sequence of words is grammatical can go beyond the power of any physical computer. Chomsky’s parsing problem is a linguistic reinterpretation of an older problem from Thue [Thu14], now known as the *word problem for monoids*<sup>1</sup> and proved undecidable by Post [Pos47] and Markov [Mar47] independently. This reveals a three-way connection between theoretical linguistics, computer science and abstract algebra which will pervade much of this thesis. But if we are interested in solving practical NLP problems, why should we care about such abstract constructions as formal grammars?

Most NLP tasks of interest involve natural language *semantics*: we want machines to compute the *meaning* of sentences. Given the grammatical structure of a sentence, we can compute its meaning as a function of the meanings of its words. This is known as the *principle of compositionality*, usually attributed to Frege.<sup>2</sup> It was already implicit in Boole’s *laws of thought* [Boo54] and then made explicit by Carnap [Car47]. From a philosophical principle, compositionality became the basis of the symbolic approach to NLP, also known as *good old-fashioned AI* (GOFAI) [Hau89]. Word meanings are first encoded in a machine-readable format, then the machine can compose them to answer complex questions. This approach culminated in 2011 with IBM Watson defeating a human champion at *Jeopardy!* [LF11].

The same year, Apple deploy their virtual assistant in the pocket of millions of users, soon followed by internet giants Amazon and Google. While Siri, Alexa and their competitors have made NLP mainstream, none of them make any explicit use of formal grammars. Instead of the complex grammatical analysis and knowledge representation of expert systems like Watson, the AI of these next-generation NLP machines is powered by deep neural networks and machine learning of big data. Although their architecture got increasingly complex, these neural networks implement a simple statistical concept: *language models*, i.e. probability distributions over sequences of words. Instead of the compositionality of symbolic

<sup>1</sup>Historically, Thue, Markov and Post were working with *semigroups*, i.e. unitless monoids.

<sup>2</sup>Compositionality does not appear in any of Frege’s published work [Pel01]. What Frege [Fre84] did state is now known as the *context principle*: “it is enough if the sentence as whole has meaning; thereby also its parts obtain their meanings”. This can be taken as a kind of dual to compositionality: the meanings of the words are functions of the meaning of the sentence.

AI, these statistical methods rely on another linguistic principle, *distributionality*: words with similar distributions have similar meanings. Intuitively,

This principle may be traced back to Wittgenstein’s *Philosophical Investigations*: “the meaning of a word is its use in the language” [Wit53], usually shortened into the slogan *meaning is use*. It was then formulated in the context of computational linguistics by Harris [Har54], Weaver [Wea55] and Firth [Fir57], who coined the famous quotation: “You shall know a word by the company it keeps!” Before deep neural networks took over, the standard way to formalise distributionality had been *vector space models* [SWY75]. We have a set of  $N$  words appearing in a set of  $M$  documents and we simply count how many times each word appears in each document to get a  $M \times N$  matrix. We normalise it with a weighting scheme like tf-idf (term frequency by inverse document frequency), factorise it (via e.g. singular value decomposition or non-negative matrix factorisation) and we’re done! The columns of the matrix encode the meanings of words, taking their inner product yields a measure of word similarity which can then be used in tasks such as classification or clustering. This method has the advantage of simplicity and it works surprisingly well in a wide range of applications from spam detection to movie recommendation [TP10]. Its main limitation is that a sentence is represented not as a sequence but as a *bag of words*, the word vectors will be the same whether the corpus contained “dog bites man” or “man bites dog”. A standard way to fix this is to compute vectors not for words in isolation but for  $n$ -grams, windows of  $n$  consecutive words for some fixed size  $n$ . However the fix has its own limits: if  $n$  is too small we cannot detect any long-range correlations, if it is too big then the matrix is so sparse that we cannot detect anything at all.

In contrast, the recurrent neural networks (RNNs) of Rumelhart, Hinton and Williams [RHW86] are inherently sequential and their internal state can encode arbitrarily long-range correlations. At each step, the network processes the next word in a sequence and updates its internal state. This internal memory can then be used to predict the rest of the sequence, or fed as input to another network e.g. for translation into another language. Once the obstacles to training were overcome (such as the vanishing gradients mentioned above), RNN architectures such as long short-term memory (LSTM) [HS97] set records in a variety of NLP tasks such as language modeling [SMH11], speech recognition [GMH13] and machine translation [SVL14]. The purely sequential approach of RNNs turned out to be limited: when the network is done reading, the information from the first word has to propagate through the entire text before it can be translated. Bidirectional RNNs [SP97] fix this issue by reading both left-to-right and right-to-left. Nonetheless, it is somewhat unsatisfactory from a cognitive perspective (humans manage to understand text without reading backward, why should a machine do that?) and also harder to use in online settings where words need to be processed one at a time.

Attention mechanisms provide a much more elegant solution: instead of assuming that the “company” of a word is its immediate left and right neighbourhood, we let the neural network itself learn which words are relevant to which. First introduced as a way to boost the performance of RNNs on translation tasks [BCB16], attention has then become the basis of the *transformer model* [Vas+17]: a stack

of attention mechanisms which process sequences without recurrence altogether. Starting with BERT [Dev+19], transformers have replaced RNNs as the state-of-the-art NLP model, culminating with the GPT-3 language generator authoring its own article in *The Guardian* [GPT20]: “A robot wrote this entire article. Are you scared yet, human?”

Indeed *why* should we be scared? Because we are ignorant of *how* the robot wrote the article and we cannot explain what in its billions of parameters made it write the way it did. Transformers and neural networks in general are *black boxes*: we can probe the way they map inputs to outputs, but if we look at the terabytes of weights in between, we find no interpretation of the mapping. Moreover without explainability there can be no fairness: if we cannot explain how its decisions are made, we can hardly prevent the network from reproducing the discriminations present both in the datasets and in the assumptions of the data scientist. We argue that explainable AI requires to make the distributional black boxes transparent by endowing them with a compositional structure: we need *compositional distributional* (DisCo) models that reconcile symbolic GOFAI with deep learning.

DisCo models have their roots in neuropsychology rather than AI. Indeed, they first appeared as models of the brain rather than architectures of learning machines. In their seminal work [MP43], McCulloch and Pitts give the first formal definition of neural networks and show how their “all-or-nothing” behaviour<sup>1</sup> allow them to encode a fragment of propositional logic. Hebb [Heb49] then introduced the first biological mechanism to explain learning and structured perception: “neurons that fire together, wire together”. These computational models of the brain became the basis of *connectionism* [Smo87; Smo88] and the *neurosymbolic* [Hil97] approach to AI: high-level symbolic reasoning emerges from low-level neural networks. An influential example is Smolensky’s *tensor product representation* [Smo90], where discrete structures such as lists and trees are embedded into the tensor product of two vector spaces, one for variables and one for values. Concretely, a list  $x_1, \dots, x_n$  of  $n$  vectors of dimension  $d$  is represented as a tensor  $\sum_{i \leq n} |i\rangle \otimes x_i \in \mathbb{R}^n \otimes \mathbb{R}^d$ . Smolensky [Smo90] is also the first to make the analogy between the distributional representations of compositional structures in AI and the group representations of quantum physics. He argues that symbolic structures embed in neural networks in the same way that the symmetries of particles embed in their state space: via *representation theory*, a precursor of *category theory* which we discuss in the next section.

Clark and Pulman [CP07b] propose to apply this tensor product representation to NLP, but they note its main weakness: lists of different lengths do not live in the same space, which makes it impossible to compare sentences with different grammatical structures. The categorical compositional distributional (DisCoCat) models of Clark, Coecke and Sadrzadeh [CCS08; CCS10] overcome this issue by taking the analogy with quantum one step further. Word meanings and grammatical structure are to linguistics what quantum states and entanglement structure are to physics. DisCoCat word meanings live in vector spaces and they compose with tensor products: the states of quantum theory do too. Grammar tells you how words are connected and how information flows in a sentence

---

<sup>1</sup>A neuron’s response is either maximal or zero, regardless of the stimulus strength.

and in the same way, entanglement connects quantum states and tells you how information flows in a complex quantum system. This analogy allows to borrow well-established mathematical tools from quantum theory, and it was implemented on classical hardware with some empirical success on small-scale tasks such as sentence comparison [Gre+10] and word sense disambiguation [GS11; KSP13]. However representing the meaning of sentences as quantum processes comes with a price: they can be exponentially hard to simulate classically.

If DisCoCat models are intractable for classical computers, why not use a quantum computer instead? Zeng and Coecke [ZC16] answered this question with the first quantum natural language processing (QNLP) algorithm<sup>1</sup> and the proof of a quadratic speedup on a sentence classification task. Wieber et al. [Wie+19] later defined a QNLP algorithm based on a generalisation of the tensor product representation and proved it is BQP-complete: if any quantum algorithm has an exponential advantage, then in principle there must be one for QNLP. However promising they may be, both algorithms assume fault-tolerance and they are at least as far away from solving real-world problems as Grover and HHL.

This is where the work presented in this thesis comes in: we show it is possible to implement DisCoCat models on the machines available today. The author and collaborators [Mei+20b; Coe+20] introduced the first NISQ-friendly framework for QNLP by translating DisCoCat models into variational quantum algorithms. We then implemented this framework and demonstrated the first QNLP experiment on a toy question-answering task [Mei+20a] and more recent experiments showed empirical success on a larger-scale classification task [Lor+21]. Our framework was later applied to machine translation [Abb+21; VN21], word-sense disambiguation [Hof21] and even to generative music [Mir+21]. Future experiments will have to demonstrate that QNLP is more than a mere analogy and that it can achieve *quantum advantage on a useful task*. But before we can discuss our implementation in detail, we have to make the DisCoCat analogy formal.

## How can category theory help?

A striking aspect of the notation is that it is pictorial rather than sequential or alphabetical. This made it difficult to print, which partly explains why no rigorous theory was developed.

---

*The Geometry of Tensor Calculus,*  
Joyal and Street (1991)

“Every sufficiently good analogy is yearning to become a functor” [Bae06] and we will see that the analogy behind DisCoCat models is indeed a functor. Coecke et al. [CGS13] make a meta-analogy between their models of natural language and *topological quantum field theories* (TQFTs). Intuitively, there is an analogy between regions of spacetime and quantum processes: both can be composed either

---

<sup>1</sup>We do not consider previous algorithms that are inspired by quantum theory but run on classical computers such as the frameworks of Chen [Che02] and Blacoe et al. [BKL13].

in sequence or in parallel. TQFTs formalise this analogy: they assign a quantum system to each region of space and a quantum process to each region of spacetime, in a way that respects sequential and parallel composition. In the same structure-preserving way, DisCoCat models assign a vector space to each grammatical type and a linear map to each grammatical derivation. Both TQFTs and DisCoCat can be given a one-sentence definition in terms of category theory: they are examples of *functors into the category of vector spaces*.

How can the same piece of general abstract nonsense (category theory’s nickname) apply to both quantum gravity and natural language processing? And how can this nonsense be of any help in the implementation of QNLP algorithms? This section will answer with a brief and biased history of category theory and its applications to quantum physics and computational linguistics, from an abstract framework for meta-mathematics to a concrete toolbox for NLP on quantum hardware. First, a short philosophical digression on the etymology of the words “functor” and “category” shall bring some light to their divergent meanings in mathematics and linguistics.

The word “functor” first appears in Carnap’s *Logical syntax of language* [Car37] to describe what would be called a *function symbol* in a modern textbook on first-order logic. He introduces them as a way to reduce the laws of empirical sciences like physics to the pure syntax of his formal logic, taking the example of a *temperature functor*  $T$  such that  $T(3) = 5$  means “the temperature at position 3 is 5”<sup>1</sup>. In the linguistics community, this meaning has then drifted to become synonymous with *function words* such as “such”, “as”, “with”, etc. These words do not refer to anything in the world but serve as the grammatical glue between the *lexical words* that describe things and actions. They represent less than one thousandth of our vocabulary but nearly half of the words we speak [CP07a].

Categories (from the ancient Greek *κατηγορία*, “that which can be said”) have a much older philosophical tradition. In his *Categories* [Ari66], Aristotle first makes the distinction between the simple forms of speech (the things that are “said without any combination” such as “man” or “arguing”) and the composite ones such as “a man argued”. He then classifies the simple, atomic things into ten categories: “each signifies either substance or quantity or qualification or a relative or where or when or being-in-a-position or having or doing or being-affected”. A common explanation [Ryl37] for how Aristotle arrived at such a list is that it comes from the possible *types of questions*: the answer to “What is it?” has to be a substance, the answer to “How much?” a quantity, etc. Although he was using language as a tool, his system of categories aims at classifying things in the world, not forms of speech: it was meant as an *ontology*, not a grammar. In his *Critique of Pure Reason* [Kan81], Kant revisits Aristotle’s system to classify not the world, but the mind: he defines categories of understanding rather than categories of being. The idea that every object (whether in the world or in the mind) is an object of a certain type has then become foundational in mathematical logic and Russell’s *theory of types* [Rus03]. The same idea has also had a great influence in linguistics and especially in the *categorial grammar* tradition initiated by Ajdukiewicz [Ajd35]

---

<sup>1</sup>MacLane [Mac38] would later remark that Carnap’s formal language cannot express the coordinate system for positions, nor the scale in which temperature is measured.

and Bar-Hillel [Bar53; Bar54], where categories have now become synonymous with *grammatical types* such as nouns, verbs, etc.

Independently of their use in linguistics, Eilenberg and MacLane [EM42a; EM42b; EM45] gave categories and functors their current mathematical definition. Inspired by Aristotle’s categories of things and Kant’s categories of thoughts, they defined categories as types of *mathematical structures*: sets, groups, spaces, etc. Their great insight was to focus not on the content of the objects (elements, points, etc.) but on the composition of the *arrows* between them: functions, homomorphisms, continuous maps, etc. Applying the same insight to categories themselves, what really matters are the arrows between them: *functors*, maps from one category to another that preserve the form of arrows.<sup>1</sup> A prototypical example is Poincaré’s construction of the fundamental group of a topological space [Poi95], which can be defined as a functor from the category of (pointed) topological spaces to that of groups: every continuous map between spaces induces a homomorphism between their fundamental groups, in a way that respects composition and identity. Thus, the abstraction of category theory allowed to formalise the analogies between topology and algebra, proving results about one using methods from the other. It was then used as a tool for the foundation of algebraic geometry by the school of Grothendieck [GD60], which brought the analogy between geometric shapes and algebraic equations to a new level of abstraction and led to the development of *topos theory*.

The establishment of category theory as an independent branch of mathematics, and as an alternative foundation for mathematics, owes much to the work of Lawvere. His influential Ph.D. thesis [Law63] introduced *functorial semantics*, a framework for model theory where logical theories are categories and their models are functors. He then set out to give an axiomatisation of the category of sets [Law64] and the category of categories [Law66]. His definition of elementary topoi as cartesian closed categories subsumed the notion of Grothendieck topos and put an emphasis on the foundational concept of *adjunction* [Law69]. “Adjoint functors arise everywhere” then became the slogan of MacLane’s classic textbook *Categories for the working mathematician* [Mac71]. In parallel, Lambek [Lam68; Lam69; Lam72] extended the Curry-Howard correspondance between logic and computation to a form a holy trinity with category theory: proofs and programs are arrows, logical formulae and data types are objects in cartesian closed categories. The discovery of this three-fold connection resulted in a wide range of applications of category theory to theoretical computer science, see Scott [Sco00] for a survey.

As the computer science community became a haven for applied category theorists, it should not come as a surprise that *categorical quantum mechanics* (CQM) was first introduced by Abramsky and Coecke [AC04; AC08] in order to formalise quantum computation. In quantum theory as in formal logic, the notion of adjunction plays a central role: it gives an abstract definition of entanglement and a correctness proof of the teleportation protocol.

monoidal categories and String diagrams, Hotz, Penrose, Joyal and Street

---

<sup>1</sup>We can play the same game again: what matters are not so much the functors themselves but the *natural transformations* between them, which is what category theory was originally meant to define. To keep playing that game is to fall in the rabbit hole of infinity category theory [RV16].

pregroup diagrams and DisCoCat  
Lambek on categories for linguistics  
Wrap up?





# References

- [Aar15] Scott Aaronson. “Read the Fine Print”. In: *Nature Phys* 11.4 (Apr. 2015), pp. 291–293.
- [Abb+21] Mina Abbaszade, Vahid Salari, Seyed Shahin Mousavi, Mariam Zomorodi, and Xujuan Zhou. “Application of Quantum Natural Language Processing for Language Translation”. In: *IEEE Access* 9 (2021), pp. 130434–130448.
- [AC04] Samson Abramsky and Bob Coecke. “A Categorical Semantics of Quantum Protocols”. In: *CoRR* quant-ph/0402130 (2004).
- [AC08] Samson Abramsky and Bob Coecke. “Categorical Quantum Mechanics”. In: *arXiv:0808.1023 [quant-ph]* (Aug. 2008). arXiv: 0808.1023 [quant-ph].
- [AB08] Dorit Aharonov and Michael Ben-Or. “Fault-Tolerant Quantum Computation with Constant Error Rate”. In: *SIAM J. Comput.* 38.4 (Jan. 2008), pp. 1207–1282.
- [Ajd35] Kazimierz Ajdukiewicz. “Die Syntaktische Konnexität”. In: *Studia Philosophica* (1935).
- [Amb04] A. Ambainis. “Quantum Search Algorithms”. In: *SIGACT News* 35.2 (June 2004), pp. 22–35.
- [Ari66] Aristotle. *Categories, and De Interpretatione*. Trans. by J. L. Ackrill. Oxford [England] : Clarendon Press ; New York : Oxford University Press, 1966.
- [Aru+15] Srinivasan Arunachalam, Vlad Gheorghiu, Tomas Jochym-O’Connor, Michele Mosca, and Priyaa Varshinee Srinivasan. “On the Robustness of Bucket Brigade Quantum RAM”. In: *New J. Phys.* 17.12 (Dec. 2015), p. 123010.
- [Aru+19] Frank Arute et al. “Quantum Supremacy Using a Programmable Superconducting Processor”. In: *Nature* 574.7779 (Oct. 2019), pp. 505–510.
- [Bae06] John Baez. “Quantum Quandaries: A Category-Theoretic Perspective”. In: *The Structural Foundations of Quantum Gravity*. Oxford: Oxford University Press, 2006.
- [BCB16] Dzmitry Bahdanau, Kyunghyun Cho, and Yoshua Bengio. “Neural Machine Translation by Jointly Learning to Align and Translate”. In: *arXiv:1409.0473 [cs, stat]* (May 2016). arXiv: 1409.0473 [cs, stat].
- [Bal21] Philip Ball. *Major Quantum Computing Strategy Suffers Serious Setbacks*. <https://www.quantamagazine.org/major-quantum-computing-strategy-suffers-serious-setbacks-20210929/>. Sept. 2021.

- [Ban+08] Jeongho Bang, James Lim, M. S. Kim, and Jinhyoung Lee. “Quantum Learning Machine”. In: *arXiv:0803.2976 [quant-ph]* (Mar. 2008). arXiv: 0803.2976 [quant-ph].
- [Bar53] Yehoshua Bar-Hillel. “A Quasi-Arithmetical Notation for Syntactic Description”. In: *Language* 29.1 (Jan. 1953), p. 47.
- [Bar54] Yehoshua Bar-Hillel. “Logical Syntax and Semantics”. In: *Language* 30.2 (Apr. 1954), p. 230.
- [BLS19] Marcello Benedetti, Erika Lloyd, and Stefan Sack. “Parameterized Quantum Circuits as Machine Learning Models”. In: *arXiv:1906.07682 [quant-ph]* (June 2019). arXiv: 1906.07682 [quant-ph].
- [Ben80] Paul Benioff. “The Computer as a Physical System: A Microscopic Quantum Mechanical Hamiltonian Model of Computers as Represented by Turing Machines”. In: *J Stat Phys* 22.5 (May 1980), pp. 563–591.
- [Ben+97] Charles H. Bennett, Ethan Bernstein, Gilles Brassard, and Umesh Vazirani. “Strengths and Weaknesses of Quantum Computing”. In: *SIAM J. Comput.* 26.5 (Oct. 1997), pp. 1510–1523.
- [BBD09] Daniel J Bernstein, Johannes Buchmann, and Erik Dahmén. *Post-Quantum Cryptography*. Berlin: Springer, 2009.
- [BKL13] William Blacoe, Elham Kashefi, and Mirella Lapata. “A Quantum-Theoretic Approach to Distributional Semantics”. In: *Proceedings of the 2013 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies*. Atlanta, Georgia: Association for Computational Linguistics, June 2013, pp. 847–857.
- [Boo54] George Boole. *An Investigation of the Laws of Thought on Which Are Founded the Mathematical Theories of Logic and Probabilities*. London : Walton and Maberly, 1854.
- [Bra+02] Gilles Brassard, Peter Hoyer, Michele Mosca, and Alain Tapp. “Quantum Amplitude Amplification and Estimation”. In: *arXiv:quant-ph/0005055* 305 (2002), pp. 53–74. arXiv: quant-ph/0005055.
- [Car37] Rudolf Carnap. *Logical Syntax of Language*. London: Kegan Paul and Co., Ltd, 1937.
- [Car47] Rudolf Carnap. *Meaning and Necessity: A Study in Semantics and Modal Logic*. University of Chicago Press, 1947.
- [Che02] Joseph CH Chen. “Quantum Computation and Natural Language Processing”. PhD thesis. Staats-und Universitätsbibliothek Hamburg Carl von Ossietzky, 2002.
- [Cho56] Noam Chomsky. “Three Models for the Description of Language”. In: *IRE Transactions on Information Theory* 2.3 (Sept. 1956), pp. 113–124.
- [Cho57] Noam Chomsky. *Syntactic Structures*. The Hague: Mouton and Co., 1957.
- [CGK98] Isaac L. Chuang, Neil Gershenfeld, and Mark Kubinec. “Experimental Implementation of Fast Quantum Searching”. In: *Phys. Rev. Lett.* 80.15 (Apr. 1998), pp. 3408–3411.

- [CP07a] Cindy Chung and James Pennebaker. “The Psychological Functions of Function Words”. In: *Social communication* (Jan. 2007).
- [CJS13] B. D. Clader, B. C. Jacobs, and C. R. Sprouse. “Preconditioned Quantum Linear System Algorithm”. In: *Phys. Rev. Lett.* 110.25 (June 2013), p. 250504.
- [CCS08] Stephen Clark, Bob Coecke, and Mehrnoosh Sadrzadeh. “A Compositional Distributional Model of Meaning”. In: *Proceedings of the Second Symposium on Quantum Interaction (QI-2008)*. 2008, pp. 133–140.
- [CCS10] Stephen Clark, Bob Coecke, and Mehrnoosh Sadrzadeh. “Mathematical Foundations for a Compositional Distributional Model of Meaning”. In: *Festschrift for Jim Lambek*. Ed. by J. van Benthem, M. Moortgat, and W. Buszkowski. Vol. 36. Linguistic Analysis. 2010, pp. 345–384. arXiv: 1003.4394.
- [CP07b] Stephen Clark and Stephen Pulman. “Combining Symbolic and Distributional Models of Meaning”. In: *Quantum Interaction, Papers from the 2007 AAI Spring Symposium, Technical Report SS-07-08, Stanford, California, USA, March 26-28, 2007*. AAI, 2007, pp. 52–55.
- [CGS13] B. Coecke, E. Grefenstette, and M. Sadrzadeh. “Lambek vs. Lambek: Functorial Vector Space Semantics and String Diagrams for Lambek Calculus”. In: *ArXiv e-prints* (2013). arXiv: 1302.0393.
- [Coe+20] Bob Coecke, Giovanni de Felice, Konstantinos Meichanetzidis, and Alexis Toumi. “Foundations for Near-Term Quantum Natural Language Processing”. In: *ArXiv e-prints* (2020). arXiv: 2012.03755.
- [Deu85] David Deutsch. “Quantum Theory, the Church–Turing Principle and the Universal Quantum Computer”. In: *Proceedings of the Royal Society of London. A. Mathematical and Physical Sciences* 400.1818 (1985), pp. 97–117.
- [DJ92] David Deutsch and Richard Jozsa. “Rapid Solution of Problems by Quantum Computation”. In: *Proceedings of the Royal Society of London. Series A: Mathematical and Physical Sciences* 439.1907 (Dec. 1992), pp. 553–558.
- [Dev+19] Jacob Devlin, Ming-Wei Chang, Kenton Lee, and Kristina Toutanova. “BERT: Pre-Training of Deep Bidirectional Transformers for Language Understanding”. In: *arXiv:1810.04805 [cs]* (May 2019). arXiv: 1810.04805 [cs].
- [EM42a] Samuel Eilenberg and Saunders MacLane. “Group Extensions and Homology”. In: *Annals of Mathematics* 43.4 (1942), pp. 757–831.
- [EM42b] Samuel Eilenberg and Saunders MacLane. “Natural Isomorphisms in Group Theory”. In: *Proceedings of the National Academy of Sciences of the United States of America* 28.12 (1942), p. 537.
- [EM45] Samuel Eilenberg and Saunders MacLane. “General Theory of Natural Equivalences”. In: *Trans. Amer. Math. Soc.* 58 (1945), pp. 231–294.

- [FGG14] Edward Farhi, Jeffrey Goldstone, and Sam Gutmann. “A Quantum Approximate Optimization Algorithm”. In: *arXiv:1411.4028 [quant-ph]* (Nov. 2014). arXiv: 1411.4028 [quant-ph].
- [FN18] Edward Farhi and Hartmut Neven. “Classification with Quantum Neural Networks on Near Term Processors”. In: *arXiv:1802.06002 [quant-ph]* (Aug. 2018). arXiv: 1802.06002 [quant-ph].
- [Fey82] Richard P. Feynman. “Simulating Physics with Computers”. In: *Int J Theor Phys* 21.6 (June 1982), pp. 467–488.
- [Fey85] Richard P Feynman. “Quantum Mechanical Computers”. In: *Optics news* 11.2 (1985), pp. 11–20.
- [Fir57] John R Firth. “A Synopsis of Linguistic Theory, 1930-1955”. In: *Studies in linguistic analysis* (1957).
- [Fre+03] Michael Freedman, Alexei Kitaev, Michael Larsen, and Zhenghan Wang. “Topological Quantum Computation”. In: *Bulletin of the American Mathematical Society* 40.1 (2003), pp. 31–38.
- [Fre84] Gottlob Frege. “The Foundations of Arithmetic”. In: *JL Austin. New York: Philosophical Library* (1884).
- [GLM08] Vittorio Giovannetti, Seth Lloyd, and Lorenzo Maccone. “Quantum Random Access Memory”. In: *Phys. Rev. Lett.* 100.16 (Apr. 2008), p. 160501.
- [GPT20] GPT-3. “A Robot Wrote This Entire Article. Are You Scared yet, Human?”. In: *The Guardian* (Sept. 2020).
- [Gra+19] Edward Grant, Leonard Wossnig, Mateusz Ostaszewski, and Marcello Benedetti. “An Initialization Strategy for Addressing Barren Plateaus in Parametrized Quantum Circuits”. In: *Quantum* 3 (Dec. 2019), p. 214.
- [GMH13] Alex Graves, Abdel-rahman Mohamed, and Geoffrey Hinton. “Speech Recognition with Deep Recurrent Neural Networks”. In: *2013 IEEE International Conference on Acoustics, Speech and Signal Processing*. Ieee. 2013, pp. 6645–6649.
- [GS11] Edward Grefenstette and Mehrnoosh Sadrzadeh. “Experimental Support for a Categorical Compositional Distributional Model of Meaning”. In: *arXiv:1106.4058 [cs, math]* (2011), pp. 1394–1404. arXiv: 1106.4058 [cs, math].
- [Gre+10] Edward Grefenstette, Mehrnoosh Sadrzadeh, Stephen Clark, Bob Coecke, and Stephen Pulman. “Concrete Sentence Spaces for Compositional Distributional Models of Meaning”. In: *arXiv:1101.0309 [cs]* (Dec. 2010). arXiv: 1101.0309 [cs].
- [GD60] Alexandre Grothendieck and Jean Dieudonné. “Eléments de Géométrie Algébrique”. In: *Publications Mathématiques de l’Institut des Hautes Études Scientifiques* 4.1 (1960), pp. 5–214.
- [Gro97] Lov K. Grover. “Quantum Mechanics Helps in Searching for a Needle in a Haystack”. In: *Phys. Rev. Lett.* 79.2 (July 1997), pp. 325–328. arXiv: quant-ph/9706033.

- [Har54] Zellig S. Harris. “Distributional Structure”. In: *WORD* 10.2-3 (Aug. 1954), pp. 146–162.
- [HHL09] Aram W. Harrow, Avinatan Hassidim, and Seth Lloyd. “Quantum Algorithm for Linear Systems of Equations”. In: *Phys. Rev. Lett.* 103.15 (Oct. 2009), p. 150502.
- [Hau89] John Haugeland. *Artificial Intelligence: The Very Idea*. MIT press, 1989.
- [Hav+19] Vojtech Havlicek et al. “Supervised Learning with Quantum Enhanced Feature Spaces”. In: *Nature* 567.7747 (Mar. 2019), pp. 209–212. arXiv: 1804.11326.
- [Heb49] Donald Olding Hebb. *The Organisation of Behaviour: A Neuropsychological Theory*. Science Editions New York, 1949.
- [Hil97] Melanie Hilario. “An Overview of Strategies for Neurosymbolic Integration”. In: *Connectionist-Symbolic Integration: From Unified to Hybrid Approaches* (1997), pp. 13–36.
- [Hoc98] Sepp Hochreiter. “The Vanishing Gradient Problem During Learning Recurrent Neural Nets and Problem Solutions”. In: *Int. J. Unc. Fuzz. Knowl. Based Syst.* 06.02 (Apr. 1998), pp. 107–116.
- [HS97] Sepp Hochreiter and Jürgen Schmidhuber. “Long Short-Term Memory”. In: *Neural computation* 9 (Dec. 1997), pp. 1735–80.
- [Hof21] Thomas Hoffmann. “Quantum Models for Word- Sense Disambiguation”. In: (2021).
- [Hut04] W John Hutchins. “The Georgetown-Ibm Experiment Demonstrated in January 1954”. In: *Conference of the Association for Machine Translation in the Americas*. Springer. 2004, pp. 102–114.
- [Kan81] Immanuel Kant. *Critique of Pure Reason*. Trans. by Norman Kemp Smith. Read Books Ltd. (2011), 1781.
- [KSP13] Dimitri Kartsaklis, Mehrnoosh Sadrzadeh, and Stephen Pulman. “Separating Disambiguation from Composition in Distributional Semantics”. In: (2013), p. 10.
- [KP16] Iordanis Kerenidis and Anupam Prakash. “Quantum Recommendation Systems”. In: *arXiv:1603.08675 [quant-ph]* (Mar. 2016). arXiv: 1603.08675 [quant-ph].
- [Kit95] A. Yu Kitaev. “Quantum Measurements and the Abelian Stabilizer Problem”. In: *arXiv:quant-ph/9511026* (Nov. 1995). arXiv: quant-ph/9511026.
- [Kit03] A. Yu. Kitaev. “Fault-Tolerant Quantum Computation by Anyons”. In: *Annals of Physics* 303.1 (Jan. 2003), pp. 2–30.
- [LF11] Adam Lally and Paul Fodor. “Natural Language Processing with Prolog in the IBM Watson System”. In: *The Association for Logic Programming (ALP) Newsletter* 9 (2011).
- [Lam68] Joachim Lambek. “Deductive Systems and Categories”. In: *Mathematical Systems Theory* 2.4 (1968), pp. 287–318.

- [Lam69] Joachim Lambek. “Deductive Systems and Categories II. Standard Constructions and Closed Categories”. In: *Category Theory, Homology Theory and Their Applications I*. Springer, 1969, pp. 76–122.
- [Lam72] Joachim Lambek. “Deductive Systems and Categories III. Cartesian Closed Categories, Intuitionist Propositional Calculus, and Combinatory Logic”. In: *Toposes, Algebraic Geometry and Logic*. Springer, 1972, pp. 57–82.
- [Law63] F. William Lawvere. “Functorial Semantics of Algebraic Theories”. In: *Proceedings of the National Academy of Sciences of the United States of America* 50.5 (1963), pp. 869–872.
- [Law64] F. William Lawvere. “An Elementary Theory of the Category of Sets”. In: *Proceedings of the National Academy of Sciences of the United States of America* 52.6 (1964), p. 1506.
- [Law66] F. William Lawvere. “The Category of Categories as a Foundation for Mathematics”. In: *Proceedings of the Conference on Categorical Algebra*. Ed. by S. Eilenberg, D. K. Harrison, S. MacLane, and H. Röhrli. Springer Berlin Heidelberg, 1966, pp. 1–20.
- [Law69] F. William Lawvere. “Adjointness in Foundations”. In: *Dialectica* 23.34 (1969), pp. 281–296.
- [LMR13] Seth Lloyd, Masoud Mohseni, and Patrick Rebentrost. “Quantum Algorithms for Supervised and Unsupervised Machine Learning”. In: *arXiv:1307.0411 [quant-ph]* (Nov. 2013). arXiv: 1307.0411 [quant-ph].
- [LMR14] Seth Lloyd, Masoud Mohseni, and Patrick Rebentrost. “Quantum Principal Component Analysis”. In: *Nature Physics* 10.9 (Sept. 2014), pp. 631–633. arXiv: 1307.0401.
- [Lor+21] Robin Lorenz, Anna Pearson, Konstantinos Meichanetzidis, Dimitri Kartsaklis, and Bob Coecke. “QNLP in Practice: Running Compositional Models of Meaning on a Quantum Computer”. In: *arXiv:2102.12846 [quant-ph]* (Feb. 2021). arXiv: 2102.12846 [quant-ph].
- [Mac38] Saunders MacLane. “Carnap on Logical Syntax”. In: *Bulletin of the American Mathematical Society* 44.3 (1938), pp. 171–176.
- [Mac71] Saunders MacLane. *Categories for the Working Mathematician*. Graduate Texts in Mathematics. Springer New York, 1971.
- [Man80] Yuri Manin. “Computable and Uncomputable”. In: *Sovetskoye Radio, Moscow* 128 (1980).
- [Mar47] A. Markov. “On Certain Insoluble Problems Concerning Matrices”. In: *Doklady Akad. Nauk SSSR*. Vol. 57. 6. 1947, pp. 539–542.
- [McC+16] Jarrod R. McClean, Jonathan Romero, Ryan Babbush, and Alán Aspuru-Guzik. “The Theory of Variational Hybrid Quantum-Classical Algorithms”. In: *New J. Phys.* 18.2 (Feb. 2016), p. 023023.
- [McC+18] Jarrod R. McClean, Sergio Boixo, Vadim N. Smelyanskiy, Ryan Babbush, and Hartmut Neven. “Barren Plateaus in Quantum Neural Network Training Landscapes”. In: *Nat Commun* 9.1 (Dec. 2018), p. 4812. arXiv: 1803.11173.

- [MP43] Warren S McCulloch and Walter Pitts. “A Logical Calculus of the Ideas Immanent in Nervous Activity”. In: *The bulletin of mathematical biophysics* 5.4 (1943), pp. 115–133.
- [Mei+20a] Konstantinos Meichanetzidis, Alexis Toumi, Giovanni de Felice, and Bob Coecke. “Grammar-Aware Question-Answering on Quantum Computers”. In: *ArXiv e-prints* (2020). arXiv: 2012.03756.
- [Mei+20b] Konstantinos Meichanetzidis et al. “Quantum Natural Language Processing on Near-Term Quantum Computers”. In: *Quantum Physics and Logic (QPL)*. 2020. arXiv: 2005.04147.
- [Mir+21] Eduardo Reck Miranda, Richie Yeung, Anna Pearson, Konstantinos Meichanetzidis, and Bob Coecke. “A Quantum Natural Language Processing Approach to Musical Intelligence”. In: *arXiv:2111.06741 [quant-ph]* (Nov. 2021). arXiv: 2111.06741 [quant-ph].
- [Ped+19] Edwin Pednault, John A. Gunnels, Giacomo Nannicini, Lior Horesh, and Robert Wisnieff. “Leveraging Secondary Storage to Simulate Deep 54-Qubit Sycamore Circuits”. In: *arXiv:1910.09534 [quant-ph]* (Oct. 2019). arXiv: 1910.09534 [quant-ph].
- [Pel01] Francis Jeffrey Pelletier. “Did Frege Believe Frege’s Principle?” In: *Journal of Logic, Language and information* 10.1 (2001), pp. 87–114.
- [Per+14] Alberto Peruzzo et al. “A Variational Eigenvalue Solver on a Photonic Quantum Processor”. In: *Nat Commun* 5.1 (July 2014), p. 4213.
- [Pes+21] Arthur Pesah et al. “Absence of Barren Plateaus in Quantum Convolutional Neural Networks”. In: *Phys. Rev. X* 11.4 (Oct. 2021), p. 041011.
- [Poi95] Henri Poincaré. *Analysis Situs*. Gauthier-Villars Paris, France, 1895.
- [Pos47] Emil L. Post. “Recursive Unsolvability of a Problem of Thue”. In: *Journal of Symbolic Logic* 12.1 (Mar. 1947), pp. 1–11.
- [Pre18] John Preskill. “Quantum Computing in the NISQ Era and Beyond”. In: *Quantum* 2 (Aug. 2018), p. 79.
- [RML14] Patrick Rebentrost, Masoud Mohseni, and Seth Lloyd. “Quantum Support Vector Machine for Big Data Classification”. In: *Phys. Rev. Lett.* 113.13 (Sept. 2014), p. 130503.
- [RV16] Emily Riehl and Dominic Verity. “Infinity Category Theory from Scratch”. In: *arXiv preprint arXiv:1608.05314* (2016). arXiv: 1608.05314.
- [RHW86] David E. Rumelhart, Geoffrey E. Hinton, and Ronald J. Williams. “Learning Representations by Back-Propagating Errors”. In: *Nature* 323.6088 (Oct. 1986), pp. 533–536.
- [Rus03] Bertrand Russell. *The Principles of Mathematics*. Routledge, 1903.
- [Ryl37] G. Ryle. “Categories”. In: *Proceedings of the Aristotelian Society* 38 (1937), pp. 189–206.
- [SWY75] G. Salton, A. Wong, and C. S. Yang. “A Vector Space Model for Automatic Indexing”. In: *Commun. ACM* 18.11 (1975), pp. 613–620.

- [Sch21] Maria Schuld. “Quantum Machine Learning Models Are Kernel Methods”. In: *arXiv:2101.11020 [quant-ph, stat]* (Jan. 2021). arXiv: 2101.11020 [quant-ph, stat].
- [SK19] Maria Schuld and Nathan Killoran. “Quantum Machine Learning in Feature Hilbert Spaces”. In: *Phys. Rev. Lett.* 122.4 (Feb. 2019), p. 040504. arXiv: 1803.07128.
- [SP97] M. Schuster and K.K. Paliwal. “Bidirectional Recurrent Neural Networks”. In: *IEEE Transactions on Signal Processing* 45.11 (Nov. 1997), pp. 2673–2681.
- [Sco00] Phill J Scott. “Some Aspects of Categories in Computer Science”. In: *Handbook of Algebra*. Vol. 2. Elsevier, 2000, pp. 3–77.
- [SB09] Dan Shepherd and Michael J. Bremner. “Temporally Unstructured Quantum Computation”. In: *Proceedings of the Royal Society A: Mathematical, Physical and Engineering Sciences* 465.2105 (May 2009), pp. 1413–1439.
- [Sho96] Peter W Shor. “Fault-Tolerant Quantum Computation”. In: *Proceedings of 37th Conference on Foundations of Computer Science*. IEEE. 1996, pp. 56–65.
- [Sho94] P.W. Shor. “Algorithms for Quantum Computation: Discrete Logarithms and Factoring”. In: *Proceedings 35th Annual Symposium on Foundations of Computer Science*. Santa Fe, NM, USA: IEEE Comput. Soc. Press, 1994, pp. 124–134.
- [Sim94] D. Simon. “On the Power of Quantum Computation”. In: *2013 IEEE 54th Annual Symposium on Foundations of Computer Science*. Los Alamitos, CA, USA: IEEE Computer Society, Nov. 1994, pp. 116–123.
- [Smo87] P. Smolensky. “Connectionist AI, Symbolic AI, and the Brain”. In: *Artif Intell Rev* 1.2 (1987), pp. 95–109.
- [Smo88] Paul Smolensky. “On the Proper Treatment of Connectionism”. In: *Behavioral and Brain Sciences* 11.1 (Mar. 1988), pp. 1–23.
- [Smo90] Paul Smolensky. “Tensor Product Variable Binding and the Representation of Symbolic Structures in Connectionist Systems”. In: *Artificial Intelligence* 46.1 (Nov. 1990), pp. 159–216.
- [SMH11] Ilya Sutskever, James Martens, and Geoffrey E Hinton. “Generating Text with Recurrent Neural Networks”. In: *ICML*. 2011.
- [SVL14] Ilya Sutskever, Oriol Vinyals, and Quoc V Le. “Sequence to Sequence Learning with Neural Networks”. In: *Advances in Neural Information Processing Systems*. Vol. 27. Curran Associates, Inc., 2014.
- [Thu14] Axel Thue. *Probleme Über Veränderungen von Zeichenreihen Nach Gegebenen Regeln*. na, 1914.
- [Tur50] A. M. Turing. “Computing Machinery and Intelligence”. In: *Mind* LIX.236 (Oct. 1950), pp. 433–460.
- [TP10] P. D. Turney and P. Pantel. “From Frequency to Meaning: Vector Space Models of Semantics”. In: *Journal of Artificial Intelligence Research* 37 (Feb. 2010), pp. 141–188.



- [Vas+17] Ashish Vaswani et al. “Attention Is All You Need”. In: *arXiv:1706.03762 [cs]* (Dec. 2017). arXiv: 1706.03762 [cs].
- [VN21] Irene Vicente Nieto. *Towards Machine Translation with Quantum Computers*. 2021.
- [Wea55] Warren Weaver. “Translation”. In: *Machine translation of languages* 14.15-23 (1955), p. 10.
- [WBL12] Nathan Wiebe, Daniel Braun, and Seth Lloyd. “Quantum Algorithm for Data Fitting”. In: *Phys. Rev. Lett.* 109.5 (Aug. 2012), p. 050505.
- [Wie+19] Nathan Wiebe, Alex Bocharov, Paul Smolensky, Matthias Troyer, and Krysta M. Svore. “Quantum Language Processing”. In: *arXiv:1902.05162 [quant-ph]* (Feb. 2019). arXiv: 1902.05162 [quant-ph].
- [Wit53] Ludwig Wittgenstein. *Philosophical Investigations*. Oxford: Basil Blackwell, 1953.
- [Wu+21] Yulin Wu et al. “Strong Quantum Computational Advantage Using a Superconducting Quantum Processor”. In: *Phys. Rev. Lett.* 127.18 (Oct. 2021), p. 180501.
- [Yon+21] Yong et al. “Closing the "Quantum Supremacy" Gap: Achieving Real-Time Simulation of a Random Quantum Circuit Using a New Sunway Supercomputer”. In: *Proceedings of the International Conference for High Performance Computing, Networking, Storage and Analysis* (Nov. 2021), pp. 1–12. arXiv: 2110.14502.
- [ZC16] William Zeng and Bob Coecke. “Quantum Algorithms for Compositional Natural Language Processing”. In: *Electronic Proceedings in Theoretical Computer Science* 221 (Aug. 2016), pp. 67–75. arXiv: 1608.01406.
- [Zho+20] Han-Sen Zhong et al. “Quantum Computational Advantage Using Photons”. In: *Science* 370.6523 (Dec. 2020), pp. 1460–1463. arXiv: 2012.01625.
- [Zhu+21] Qingling Zhu et al. “Quantum Computational Advantage via 60-Qubit 24-Cycle Random Circuit Sampling”. In: *Science Bulletin* (Oct. 2021).