
BISS0001 PIR CONTROLLER

BISS0001 GENERAL DESCRIPTION

BISS0001 is a PIR (passive infra-red) controller, using analog mixing digital design technique and manufactures by CMOS process. With special noise immunity technique, BISS0001 is the most stable PIR controller you can find on the market. More than this, there are few components needed in its application circuit which can reduce material cost and increase competitive.



BISS0001 Absolute Maximum Ratings

Parameter	SYMBOL	VALUE	Units
POWER SUPPLY Vdd WITH REPECT TO Vss	Vdd-Vss	5.0	V
VOLTAGE ON ANY PIN		-0.3-5.6	V
OPERATING TEMPERATURE	Тор	0-70	С
STORAGE TEMPERATURE		-65-150	С

BISS0001 ELECTRICAL CHARACTERISTICS

Symbol	Parameter	Condition	Min.	Тур.	Max.	Unit
Vdd	SUPPLY VOLTAGE		3	5	6	V
lst	STANDY CURRENT		0.9	1.0	1.2	mA
ldd	OPERATING CURRENT	1.8mA, TRIAC 2.5mA, RELAY	1.8		2.5	mA
Vref	STABLE VOLTAGE	Vdd>4.2V	3.0	3.2	3.4	V
Iref	SOURCE CURRENT OF Vref		200			uA
	RIPPLE OF Vref				0.5	mV
	INPUT AND OUTPUT REGULATION OF Vref				0.3%	
Ftb	TIME BASE OPERATING FREQUENCY		15	16	17	KHZ
Vt+	CDS OPERATING TRIGGER		1.3	1.7	2.1	V
Vt-	CDS OPREATING TRIGGER		0.6	0.9	1.1	V
lcds	CDS SOURCE CURRENT		2.6	3.5	4.4	uA
Isource	CDS OUTPUT SOURCE CURRENT		9	10.4	17.4	mA
Isink	CDS OUTPUT SINK CURRENT		11.6	13	21	mA

BISS0001 PIR CONTROLLER

Irs	RELAY SOURCE CURRENT			5	mA
Irsink	RELAY SINK CURRENT			5	mA
Vro	RELAY OPERATING VOLTAGE	18.8V: RELAY ON 13.1V: RELAY OFF	13.1	18.8	V
Itsink	TRIAC SINK CURRENT			15	mA
Itsource	TRIAC SOURCE CURRENT			50	uA

BISS0001 TYPICAL APPLICATION

