Machine Learning for Intraday Pairs Trading:
A Comprehensive Benchmark Study on 1-Minute S&P 500 Data

Detailed Technical Report

Bryan Djoufack
M2 Research Project

April 2026

Abstract

This detailed report presents a comprehensive benchmark of nine pair-selection methods for intraday pairs trading on 1-minute S&P 500 data over 2022–2026. Three classical selection criteria (distance, cointegration, Pearson correlation) are combined with three filter regimes (no filter, K-means clustering, autoencoder-based k-nearest-neighbor neighborhoods), for a total of 9 methods. All are evaluated under realistic transaction costs, strict train/test validation, and Fama-French factor analysis. Our main finding is that **autoencoder-filtered distance selection (*ae+distance*) is the most robust method**, delivering an out-of-sample Sharpe ratio of 1.05 with only −0.5% dependence on outlier events and 96% retention under triple-stressed costs. Cointegration-based methods, despite displaying higher apparent Sharpe ratios (up to 1.59 for *ae+cointegration*), are shown to derive **44% to 77% of their test PnL from just a handful of outlier pair-windows concentrated around the October 2025 AMD–OpenAI announcement**. Once these event-driven gains are removed, their structural edge vanishes — illustrating a concrete failure mode of short-window cointegration combined with sector-rigid filters. A four-experiment robustness analysis confirms that the *ae+distance* result is stable across regularization choices, neighborhood sizes, outlier removal, and stressed cost assumptions.

Contents

1 Introduction **3**
1.1 Motivation . . . 3
1.2 Literature positioning . . . 3
1.3 Contributions . . . 4
1.4 Report organization . . . 4

2 Data and Preprocessing **4**
2.1 Data source and universe . . . 4
2.2 Data cleaning pipeline . . . 4
2.2.1 Duplicate detection . . . 5
2.2.2 Day-level quality flags . . . 5
2.2.3 Ticker-level filtering . . . 5
2.2.4 Formation-level filtering . . . 6

3 Methodology **6**
3.1 Walk-forward design and train/test split . . . 6
3.2 Spread construction and hedge ratios . . . 6
3.3 Position sizing . . . 7
3.4 Transaction-cost model . . . 7
3.5 Pair-selection criteria . . . 8
3.6 Filter regimes . . . 8
3.7 Evaluation metrics . . . 8

4 Baseline Results (Step 1–2) **8**

5 K-means Filtering (Step 3) **10**
5.1 Feature engineering . . . 10
5.2 Choice of K . . . 10
5.3 Resulting clusters . . . 11
5.4 Results . . . 12

6 Autoencoder Filtering (Step 4) **13**
6.1 Motivation . . . 13
6.2 Input design . . . 14
6.3 Automated choice of latent dimension . . . 14
6.4 Architecture . . . 14
6.5 Regularization . . . 14
6.6 Latent space inspection . . . 15
6.7 Neighborhood construction . . . 16
6.8 Results . . . 16

7 Two Idiosyncratic Events in the Test Period **17**
7.1 The AMD October 2025 event . . . 17
7.1.1 Mechanism . . . 17
7.1.2 Impact across methods . . . 18
7.2 The UnitedHealth 2025–2026 crisis . . . 18
7.3 Differential impact on methods . . . 19

8 Fama-French Alpha Analysis (Step 7) **19**
8.1 Methodology . . . 19
8.2 Unit normalization . . . 19
8.3 Benchmark: Stübinger & Bredthauer (2017) . . . 20
8.4 Results for ae+distance . . . 20
8.5 Comparison with Stübinger's benchmark . . . 21
8.6 Full 9-method comparison (test period, FF5) . . . 21

9 Robustness Analysis (Step 5) **22**
9.1 Experiment A: Regularization sensitivity . . . 22
9.2 Experiment B: Neighborhood size k sensitivity . . . 23
9.3 Experiment C: Outlier contribution . . . 23
9.4 Experiment D: Stress test with 3× costs . . . 24
9.5 Robustness summary . . . 25

10 Discussion **25**
10.1 Why does the autoencoder help distance but barely help correlation? . . . 25
10.2 Why does the autoencoder outperform K-means on distance? . . . 25
10.3 Why do cointegration-based methods "look good" but aren't? . . . 25
10.4 Limitations . . . 26
10.5 Next steps . . . 26

11 Conclusion **27**

A Appendix A: Notebook Architecture **28**

B Appendix B: Key Hyperparameters **28**

C Appendix C: Reproducibility Notes **29**

D Appendix D: Key Code Snippets **29**

1 Introduction

1.1 Motivation

Pairs trading is a classical statistical arbitrage strategy that exploits the tendency of two historically co-moving assets to revert to their joint equilibrium after short-term dislocations. Introduced in an academic form by Gatev et al. (2006) using a simple distance criterion on daily data, the strategy has generated substantial literature exploring alternative selection mechanisms (cointegration tests, correlation filters, copulas), higher frequencies (hourly, 5-minute, 1-minute intraday), and more recently machine-learning approaches for the selection step.

Despite the maturity of the literature, a number of methodological questions remain open at the intersection of high-frequency data and modern machine learning:

1. Do machine-learning filters genuinely improve pair selection out-of-sample, or is the reported improvement driven by overfitting, cherry-picked evaluation periods, or specific idiosyncratic events in the test sample?

2. Which combinations of classical selection criteria (distance/cointegration/correlation) and ML filters (K-means/autoencoder) work best, and why?

3. How do these methods hold up under realistic transaction costs, stress scenarios, and factor-based alpha attribution?

This project addresses these questions via a full 9-method benchmark on 1-minute S&P 500 data spanning 2022–2026, with strict out-of-sample validation and four complementary robustness experiments.

1.2 Literature positioning

Our work sits at the intersection of several literature streams:

Classical pairs trading. Gatev et al. (2006) established the reference using a minimum-distance selection on daily price series, reporting economically meaningful excess returns on decades of US data. Do and Faff (2010) documented a post-2003 decline in this edge, attributed to rising competition and improved market efficiency. Carrasco et al. (2018) provided a systematic comparison of distance, correlation, and cointegration methods, generally finding similar performance when transaction costs are modest.

High-frequency pairs trading. Stübinger and Bredthauer (2017) pioneered minute-frequency pairs trading on the S&P 500 with a formal walk-forward design (10-day formation, 5-day trading). They demonstrated that the finer granularity enables more frequent trade opportunities and delivers economically significant profits even after costs. Their empirical framework is our primary methodological anchor.

Machine learning for pair selection. Sarmento and Horta (2020) introduced unsupervised clustering (K-means, DBSCAN) on hand-crafted ticker features to filter the candidate pair universe before applying classical selection. They showed that pre-filtering by cluster substantially improves Sharpe on daily data. Jung (2024) extended this idea using neural-network embeddings (autoencoders, variational autoencoders, RNNs) to learn ticker similarities in a latent space. Their "Approach B" defines per-ticker neighborhoods as k-nearest neighbors in latent space.

Transaction costs and microstructure. Transaction-cost modeling is critical for realistic intraday performance assessment. Corwin and Schultz (2012) proposed a widely-used estimator of bid-ask spreads from daily high/low prices. However, Holden and Jacobsen (2014) documented that the Corwin-Schultz estimator systematically overestimates spreads for mega-cap stocks, which would make intraday strategies appear unprofitable if applied naively.

Factor-model alpha analysis. Both Gatev et al. (2006) and Stübinger and Bredthauer (2017) validate their findings using Fama-French factor regressions to isolate genuine alpha from

passive factor exposure. We follow the same methodology with the 5-factor extension plus momentum.

1.3 Contributions

Our contributions are:

- A full 9-method benchmark with unified walk-forward design, transaction-cost model, and evaluation metrics.
- Strict out-of-sample validation via a temporal 73/27 train/test split, implemented dynamically (the split date emerges automatically from the data range).
- A comprehensive robustness analysis with four independent experiments on the best-performing method: regularization sensitivity, neighborhood-size sensitivity, outlier contribution analysis, and stressed transaction costs.
- A documented study of two major idiosyncratic events in the test period (the October 2025 AMD-OpenAI deal and the 2025-2026 UnitedHealth crisis) and their differential impact on each method.
- Fama-French 5-factor + momentum regression to quantify genuine alpha beyond factor exposure.

1.4 Report organization

Section 2 describes the data pipeline, universe construction, and cleaning process. Section 3 presents the walk-forward design, transaction-cost model, and selection methods. Sections 4, 5, and 6 report results for the three filter regimes. Section 7 documents two major idiosyncratic events and their impact. Section 8 presents the Fama-French factor analysis. Section 9 reports the four robustness experiments. Section 10 discusses findings and limitations, and Section 11 concludes. Technical details are provided in the appendices.

2 Data and Preprocessing

2.1 Data source and universe

We use 1-minute OHLC (open, high, low, close) bars on 72 large-capitalization S&P 500 stocks, covering the period from 2 January 2022 to 30 March 2026 (approximately 1 063 trading days). Each trading session spans 9:35–15:54 Eastern Time, yielding 380 bars per complete day. The initial universe was selected to include major names across six GICS sectors:

- **Technology**: AAPL, MSFT, GOOGL, AMZN, META, NVDA, TSLA, AMD, AVGO, CRM, CSCO, INTC, NFLX, ORCL, QCOM, TXN
- **Finance**: JPM, BAC, WFC, C, MS, SCHW, V, MA, GS, BLK, AXP, USB, PNC
- **Healthcare**: UNH, JNJ, PFE, ABBV, MRK, LLY, CVS, GILD, BMY, AMGN
- **Consumer**: KO, PEP, PG, CL, NKE, SBUX, WMT, COST, HD, LOW, MCD, TGT, MDLZ
- **Energy**: XOM, CVX, COP, SLB, EOG, OXY, MPC, PSX, VLO
- **Industrials**: BA, GE, CAT, LMT, RTX, HON, UPS, FDX, IBM

2.2 Data cleaning pipeline

The raw data required extensive cleaning before it could be used. The pipeline is documented below.

2.2.1 Duplicate detection

Early inspection of the raw CSVs revealed that one provider-sourced file labeled "META" contained prices identical to AAPL at every timestamp — presumably a tagging or data-feed error. A dedicated cleaning block (Bloc 0.5 of the notebook) systematically scans all ticker pairs for identical price series and removes duplicates. The issue affected only the META/AAPL pair; after removal, the universe dropped from 72 to 71 usable tickers.

2.2.2 Day-level quality flags

For each ticker and each trading day, we computed two flags:

- `incomplete_day`: fewer than 380 bars observed in the session
- `has_gap_10min`: any gap of 10+ minutes between consecutive bars

These flags capture two distinct data-quality concerns: missing data and execution-impossible price jumps. Flagged days are not deleted at this stage but propagated to downstream cells.

2.2.3 Ticker-level filtering

Tickers with less than 85% clean-day coverage were excluded from the study. An additional outlier filter using Tukey's fences on the distribution of clean-day counts flagged anomalous cases; however, the 85% threshold turned out to be the binding constraint for most tickers.

After cleaning, **37 tickers were retained** (Figure 1). The excluded tickers were predominantly those with partial-year coverage in our data file, spanning most sectors. The final universe is:

Sector	Tickers retained
Technology	AAPL, MSFT, NVDA, TSLA, AMZN, AMD, AVGO, CRM, CSCO, INTC, NFLX, ORCL, QCOM, TXN
Finance	JPM, BAC, WFC, C, MS, SCHW, V
Healthcare	UNH, JNJ, MRK, CVS, GILD
Consumer	NKE, SBUX, TGT, PEP, PG
Energy	XOM, CVX, COP, SLB, OXY
Industrial	BA



Figure 1: Distribution of clean-day counts per ticker. The 85% coverage threshold (red line) is more stringent than Tukey's fence (Q1 − 1.5·IQR). Tickers below the threshold are excluded to ensure reliable high-frequency estimates.

2.2.4 Formation-level filtering

An additional filter is applied at the walk-forward loop: any formation window containing a day flagged `has_gap_10min` on any of its tickers is excluded from the universe for that window's pair selection. This ensures that regression-based coefficients (hedge ratios β) are estimated on continuous data.

Observation

Although the universe after cleaning (37 tickers) is smaller than those used in the literature (e.g. 500+ stocks in Jung, 2024, 2500+ ETFs in Sarmento and Horta, 2020), the 1-minute frequency provides substantial statistical content per formation window: approximately 3 900 observations per ticker (10 days × 380 bars). This aligns with the data density used by Stübinger and Bredthauer (2017). Small universe does limit the effectiveness of ML filters (fewer training examples for the autoencoder), which we discuss in Section 10.

3 Methodology

3.1 Walk-forward design and train/test split

Following Stübinger and Bredthauer (2017), we use a non-overlapping walk-forward scheme:

- **Formation window**: 10 trading days of 1-minute data ($\approx 3\,900$ observations per ticker)
- **Trading window**: the following 5 trading days
- **Step**: 5 days (non-overlapping)

This produces 208 total walk-forward windows over the 1 063-day period. To enable strict out-of-sample evaluation, we partition the windows temporally with `TRAIN_RATIO` $= 0.73$:

- **Train**: 153 windows, spanning 2022-01-03 to 2025-02-04
- **Test**: 55 windows, spanning 2025-02-05 to 2026-03-30
- **Excluded**: 2 windows straddling the train/test boundary

The split date emerges dynamically from the data range (determined at notebook execution), making the experimental setup robust to future data extensions. The 3 excluded windows prevent any ambiguity: a window is only included in test if its formation period lies fully after the boundary.

3.2 Spread construction and hedge ratios

For each candidate pair (A, B) in a formation window, we estimate a static hedge ratio via OLS on formation-window prices:

$$P_A^t = \alpha + \beta P_B^t + \varepsilon_t, \quad t \in \text{formation} \tag{1}$$

The spread is defined as $S_t = P_A^t - \beta P_B^t$. During the trading window, the spread is standardized using a **rolling** mean and standard deviation over a one-day window of 380 minutes (1 trading session), exactly as in Stübinger and Bredthauer (2017):

$$Z_t = \frac{S_t - \mu_t^{\text{roll}}}{\sigma_t^{\text{roll}}}, \quad \mu_t^{\text{roll}} = \frac{1}{380} \sum_{i=t-379}^{t} S_i \tag{2}$$

This corresponds to Stübinger's **varying thresholds strategy (V)**, which he shows to outperform static thresholds (S) and reverting thresholds (R) on 1-minute data. The rolling statistics are warmed up using the last day of the formation window, avoiding discontinuities at the formation/trading boundary.

The trading rule is a standard Bollinger band:

- **Enter long spread** ($+1$ unit in A, $-\beta$ units in B) if $Z_t \leq -k$
- **Enter short spread** (-1 unit in A, $+\beta$ units in B) if $Z_t \geq +k$
- **Exit** when Z_t crosses zero

Following Stübinger and Bredthauer (2017)'s finding that $k = 2.5$ is optimal for 1-minute data (whereas $k = 2$ is too aggressive at this frequency), we fix the entry threshold at $\boxed{k = 2.5}$. At the end of the 5-day trading window, all open positions are force-closed.

3.3 Position sizing

Positions are **dollar-neutral** and sized as $1/(1 + |\beta|)$ per pair. This ensures that each pair takes equal risk regardless of the hedge ratio: a pair with $\beta = 2$ puts 1/3 notional on A and 2/3 on B in opposite directions. The portfolio is equal-weighted across the top 10 selected pairs.

3.4 Transaction-cost model

We apply a two-tier cost model calibrated to empirical bid-ask-spread observations. The two tiers distinguish mega-caps from other large-caps:

- **Tier 1** (18 mega-caps: AAPL, MSFT, GOOGL, AMZN, META, NVDA, TSLA, JPM, BAC, V, MA, WMT, XOM, UNH, COST, HD, KO, PEP): 1 bp half-spread
- **Tier 2** (all other tickers): 2 bps half-spread

To each half-turn we add:

- 1 bp commission
- 0.5 bps slippage

A round-trip thus costs approximately 5–8 bps per pair (3–4 bps per half-turn $\times$ 2 half-turns, with additional variability from the tier distribution).

Why not Corwin-Schultz? We initially considered estimating effective spreads directly from daily high/low data via Corwin and Schultz (2012)'s estimator. However, Holden and Jacobsen (2014) demonstrate that this estimator systematically overestimates spreads for mega-cap stocks — often returning $\sim$30 bps for names whose true effective spread is 1–2 bps. Using Corwin-Schultz directly would inflate costs by a factor of 10–20 and make any intraday strategy appear unprofitable, regardless of its true edge. Our tiered model is more conservative than Stübinger and Bredthauer (2017)'s effective estimates but avoids the Corwin-Schultz bias and remains empirically realistic.

Observation

Our round-trip cost of 5–8 bps is consistent with the values reported by Stübinger and Bredthauer (2017) for their 1-minute S&P 500 strategy ($\sim$ 5 bps) and with recent broker-reported execution data for liquid US equities.

3.5 Pair-selection criteria

On each formation window, we apply three classical selection criteria:

Distance (Gatev). Prices are normalized to start at 1.0 on the first formation day. The Euclidean distance between normalized price paths is computed for all pairs; the top 10 smallest distances are selected.

Cointegration (Engle-Granger). For each pair we estimate the hedge ratio and test the residuals for stationarity using the Augmented Dickey-Fuller (ADF) test with `maxlag` = 1, `regression='c'`. Pairs with ADF p-value < 0.05 are retained; the top 10 lowest p-values are selected.

Correlation (Pearson). We compute pairwise Pearson correlation of 1-minute returns. Pairs with $\rho \geq 0.70$ pass the quality filter; top 10 by descending correlation are selected.

3.6 Filter regimes

Each selection criterion is evaluated under three filter regimes:

Baseline (no filter). Selection operates on the full pairwise universe (all 37 tickers).

K-means ($K = 7$). Tickers are first clustered using K-means on standardized features (see Section 5). Selection is then restricted to intra-cluster pairs: a pair (A, B) is eligible only if both tickers belong to the same cluster.

Autoencoder ($k = 7$ nearest neighbors). Tickers are embedded in a latent space learned by an autoencoder. For each ticker, its k-nearest neighbors in latent space define a per-ticker "neighborhood". A pair (A, B) is eligible if $B \in \mathrm{NN}_k(A)$ or $A \in \mathrm{NN}_k(B)$ (bidirectional check).

3.7 Evaluation metrics

We report the following metrics, separately on train and test:

- **Cumulative PnL** (in dollar-notional units; sum over the period)
- **Sharpe ratio**: annualized $\sqrt{252} \cdot \mu_{\text{daily}}/\sigma_{\text{daily}}$
- **Sortino ratio**: Sharpe using downside volatility
- **Maximum drawdown**: peak-to-trough on cumulative PnL
- **N trades**: implied round-trip trades (derived from costs)

Each metric is reported both gross (before costs) and net (after costs). The net metrics are the primary evaluation basis.

4 Baseline Results (Step 1–2)

We first report results for the three baseline methods (no ML filter), separately for training and testing periods, gross and net of costs.

Table 1: Baseline performance metrics, net of costs. Training (Jan 2022 – Feb 2025) and test (Feb 2025 – Mar 2026). Sharpe and Sortino annualized from daily aggregated PnL.

Method	Period	PnL	Sharpe	Sortino	MaxDD	N trades
Distance	train	9.90	0.68	0.82	-7.2	7417
	test	2.22	0.34	0.49	-5.4	2624
Cointegration	train	15.83	0.57	0.62	-14.0	7535
	test	-0.68	-0.05	-0.07	-12.7	2666
Correlation	train	5.10	0.32	0.34	-7.3	5708
	test	4.22	0.79	0.93	-4.2	1927



Figure 2: Baseline equity curves for the three methods (net of costs) and corresponding drawdowns. The vertical dashed line marks the train/test boundary; the grey region is out of sample.

Three observations emerge:

1. Cointegration fails out-of-sample. The cointegration baseline delivers a training Sharpe of 0.57 that collapses to -0.05 in testing. This confirms the post-2003 decline documented by Do and Faff (2010). The method's training-period PnL (15.83) is the highest of the three, but it is entirely erased out-of-sample.

2. Distance method is more stable. Gatev's distance survives the train/test transition: Sharpe 0.68 $\rightarrow$ 0.34, a 50% retention. While the absolute level is modest (below the typical 0.5 benchmark for a standalone strategy), it remains positive in both periods.

3. Pearson correlation is a respectable baseline. With a 0.70 quality threshold on M1 returns, the correlation method generates a test Sharpe of 0.79 — higher than the distance baseline. Direct correlation of 1-minute returns appears to capture more relevant information than price-distance at this frequency.

Cost impact is modest. Comparing gross and net Sharpe reveals a consistent 5–10% degradation from costs, confirming that our strategies are not dominated by cost friction. Under 5–8 bps round-trip costs, distance net Sharpe drops from 0.36 to 0.34 on test, and correlation from 0.82 to 0.79. The detailed cost analysis is in the accompanying notebook Step 2.



Figure 3: Gross vs net equity curves for the three baseline methods. Costs produce a consistent but modest drag ($\sim$ 5–10% of Sharpe).

5 K-means Filtering (Step 3)

5.1 Feature engineering

For each ticker we construct features **on the training period only** (to avoid look-ahead bias):

- **Annualized volatility**: $\sigma_{\text{ann}} = \sigma_{M1}\sqrt{380 \cdot 252}$ where σ_{M1} is the standard deviation of 1-minute returns
- **Market beta**: OLS regression of daily returns on the equal-weighted market return
- **Market correlation**: Pearson correlation between daily returns and equal-weighted market
- **PCA components 1–3**: projections of the ticker's daily returns on the first three principal components of the full cross-section
- **Sector (one-hot)**: six sector dummies

All numeric features are standardized to zero mean and unit variance using a `StandardScaler` fit on the training data.

5.2 Choice of K

We evaluated K from 2 to 10 using both elbow and silhouette criteria on the training features (Figure 4):



Figure 4: Elbow (inertia) and silhouette scores for K-means on training features, $K \in \{2, ..., 10\}$. The silhouette is maximized at $K = 10$ (0.627) but plateaus across $K \in [5, 10]$.

The silhouette reaches its maximum at $K = 10$ (0.627) but the curve plateaus across $K \in [5, 10]$, indicating that several values produce comparable partitions. We chose $\boxed{K = 7}$ as a compromise:

- High silhouette (0.59, close to the plateau maximum)
- Expected cluster populations of ~ 5 tickers, allowing top-10 intra-cluster selection via $\binom{5}{2} = 10$ candidate pairs
- Not so fine that eligible pairs become a binding constraint on selection

5.3 Resulting clusters

The final K-means clustering yields the following assignment:

Table 2: K-means clusters ($K = 7$) fitted on training features.

Cluster	Tickers	Dominant sector
0	CVS, GILD, JNJ, MRK, UNH	Health (5)
1	AAPL, AMD, AMZN, AVGO, CRM, CSCO, INTC, MSFT, NFLX, NVDA, ORCL, QCOM, TXN	Tech (13)
2	TSLA	Tech (1, isolated)
3	BAC, C, JPM, MS, SCHW, V, WFC	Finance (7)
4	NKE, PEP, PG, SBUX, TGT	Consumer (5)
5	COP, CVX, OXY, SLB, XOM	Energy (5)
6	BA	Industrial (1, isolated)



Figure 5: K-means clustering visualized on the first two principal components of the training features. Sectoral separation is visually clear. TSLA (cluster 2) and BA (cluster 6) form isolated singletons.

Observation

The K-means clustering **recovers the sector structure nearly perfectly**: every cluster except the two singletons is homogeneous by GICS sector. This is both a positive (the features capture ticker identity) and a negative (singletons like TSLA and BA cannot form intra-cluster pairs at all, shrinking the effective universe).

5.4 Results

Table 3 reports the 6-method metrics (3 baseline + 3 K-means-filtered) on both periods.

Table 3: K-means vs baseline metrics (net of costs). Six methods, train and test.

Method	Period	PnL	Sharpe	Sortino	MaxDD	N trades
Distance	train	9.90	0.68	0.82	-7.2	7417
	test	2.22	0.34	0.49	-5.4	2624
K-means+distance	train	20.82	1.73	2.25	-3.1	7480
	test	6.50	1.05	1.28	-4.2	2630
Cointegration	train	15.83	0.57	0.62	-14.0	7535
	test	-0.68	-0.05	-0.07	-12.7	2666
K-means+cointegration	train	6.52	0.27	0.29	-11.3	7419
	test	**32.62**	**1.06**	**2.26**	-9.5	2681
Correlation	train	5.10	0.32	0.34	-7.3	5708
	test	4.22	0.79	0.93	-4.2	1927
K-means+correlation	train	4.38	0.27	0.29	-7.3	5600
	test	3.95	0.74	0.87	-4.2	1928



Figure 6: Six-method equity curves (net of costs). K-means distance (green) clearly improves over distance baseline (blue). K-means cointegration (red) shows a dramatic vertical jump in October 2025 corresponding to the AMD-OpenAI event (see Section 7).

Three key observations:

1. Distance + K-means: clear monotone improvement. The distance method jumps from test Sharpe 0.34 to 1.05 when pre-filtered by K-means cluster. Train Sharpe goes from 0.68 to 1.73. This validates the core hypothesis of Sarmento and Horta (2020): restricting pair selection to sectorally-homogeneous candidates improves quality.

2. Cointegration + K-means: *apparently* spectacular. The test Sharpe jumps from -0.05 to 1.06 — one of the largest apparent improvements in the study. However, the train Sharpe is *lower* (0.27 vs 0.57 baseline), and the PnL pattern shows a vertical jump in October 2025 that we investigate in Section 7. This is our first hint that the apparent improvement is not robust.

3. Correlation + K-means: no benefit. K-means filtering has essentially no effect on the correlation method (train: $0.32 \to 0.27$; test: $0.79 \to 0.74$, both slightly worse). This is an instructive negative result: Pearson correlation already captures co-movement information at M1, which is largely what sector clusters encode. The two signals are redundant.

6 Autoencoder Filtering (Step 4)

6.1 Motivation

K-means on hand-crafted features has two limitations: (i) it captures only linear and hand-specified similarity aspects, and (ii) it produces rigid cluster boundaries that concentrate risk when multiple tickers in a cluster face a correlated shock. An autoencoder addresses both: it learns a non-linear representation from raw data, and per-ticker k-NN neighborhoods are fluid (different for each ticker).

6.2 Input design

For each ticker we construct a 630-dimensional feature vector of rolling 120-day cumulative returns, computed on the training period:

$$x_t^{(i)} = \frac{P_t^{(i)} - P_{t-120}^{(i)}}{P_{t-120}^{(i)}}, \quad t \in \text{train} \tag{3}$$

The 120-day horizon balances two considerations:

- Smoothing short-term noise while preserving structural dynamics
- Keeping the vector dimension manageable ($630 \approx 2.5$ years of daily rolling values)

The input matrix has shape $(37, 630)$ — one row per ticker.

6.3 Automated choice of latent dimension

The latent dimension is determined by PCA analysis of the input: we set d to the smallest number of principal components that captures $\geq 95\%$ of the input variance (Figure 7). This yields $d = 10$.



Figure 7: Cumulative explained variance of the PCA on scaled input features. The 95% threshold is reached at 10 components, giving `latent_dim` = 10.

This data-driven choice avoids arbitrary tuning and is well-motivated in the dimensionality-reduction literature. Alternative strategies (bottleneck analysis via validation reconstruction loss, information-theoretic criteria) were not applied here for simplicity, but could extend the robustness analysis.

6.4 Architecture

We use a symmetric feedforward autoencoder in Keras:

$$\text{input } (630) \rightarrow \text{Dense}(128, \text{ReLU}) \rightarrow \text{latent } (10) \rightarrow \text{Dense}(128, \text{ReLU}) \rightarrow \text{output } (630)$$

6.5 Regularization

With only 37 training examples, overfitting is a serious concern. We apply three independent mechanisms:

- **L2 weight regularization** ($\lambda = 10^{-4}$) on both Dense(128) layers
- **Dropout** (rate 0.1) after both hidden layers

- **Early stopping** on validation loss with patience 15 and `restore_best_weights`, using 20% validation split

The model is trained with Adam (learning rate 10^{-3}) and batch size 8 (small to accommodate the small sample), for up to 200 epochs.



Figure 8: Autoencoder training curves. Early stopping terminated training at epoch ~ 160. The final gap between train (0.10) and validation (0.24) is moderate and stable, typical for a 37-example dataset. The out-of-sample backtest performance is the stronger test of generalization.

6.6 Latent space inspection

After training, we extract each ticker's latent vector and visualize in 2D via PCA of the latent representations (Figure 9).



Figure 9: 2D PCA projection of the autoencoder latent space (37 tickers, colored by GICS sector). The autoencoder spontaneously groups tickers by sector without receiving sector information as input. TSLA appears isolated at the top, echoing its singleton status in the K-means clustering.

The autoencoder **spontaneously recovers the sector structure** of the universe without being told about sectors. Energy tickers cluster on the right (CVX, COP, OXY, XOM, SLB), finance in the center-left (JPM, WFC, V, MS, BAC), healthcare diffuse (MRK, UNH, CVS, JNJ), and technology distributed in the bottom. TSLA appears isolated (top), matching its K-means singleton status.

6.7 Neighborhood construction

For each ticker i we compute its $k = 7$ nearest neighbors in the latent space, using Euclidean distance. A pair (A, B) is eligible if either $B \in \mathrm{NN}_7(A)$ or $A \in \mathrm{NN}_7(B)$ (bidirectional check slightly more permissive than requiring mutual neighborship).

The choice $k = \lceil \sqrt{N} \rceil = \lceil \sqrt{37} \rceil = 7$ follows the standard $\sqrt{N}$ heuristic used in the pair-selection literature.

6.8 Results

Table 4 reports the full 9-method matrix on training and test periods, net of costs, sorted by test Sharpe.

Table 4: Full 9-method OOS metrics (net of costs), sorted by test Sharpe.

Selection	Filter	Train Sh.	**Test Sh.**	Sortino	MaxDD	PnL
Cointegration	AE	0.46	**1.59**	3.33	-8.7	28.93
Correlation	AE	0.12	1.17	1.35	-3.6	6.12
Cointegration	K-means	0.27	1.06	2.26	-9.5	32.62
Distance	**AE**	2.09	**1.05**	1.40	-4.3	6.94
Distance	K-means	1.73	1.05	1.28	-4.2	6.50
Correlation	baseline	0.32	0.79	0.93	-4.2	4.22
Correlation	K-means	0.27	0.74	0.87	-4.2	3.95
Distance	baseline	0.68	0.34	0.49	-5.4	2.22
Cointegration	baseline	0.57	-0.05	-0.07	-12.7	-0.68



Figure 10: Signature plot: 9 methods organized by selection type. Left: distance-based. Middle: cointegration-based. Right: correlation-based. Within each subplot, the three lines compare no filter (baseline), K-means, and autoencoder.

Key observations by panel:

Distance panel (left). Clean monotone hierarchy:

$$\text{baseline } (0.34) < \text{K-means } (1.05) \leq \text{AE } (1.05)$$

The AE version dominates in-sample (train Sharpe 2.09 vs 1.73 for K-means), confirming the richer representational capacity. Out-of-sample, the two ML methods deliver near-identical test Sharpe (1.05 each), with the AE having a slightly better Sortino (1.40 vs 1.28).

Cointegration panel (middle). Highly chaotic pattern:

$$\text{baseline (-0.05)} < \text{K-means (1.06)} < \text{AE (1.59)}$$

The apparent dominance of AE (1.59) is striking, but the equity curve (middle panel of Figure 10) shows vertical jumps in October and December 2025 that strongly suggest outlier events. We analyze this in detail in Section 7.

Correlation panel (right). Modest gains:

$$\text{K-means (0.74)} \approx \text{baseline (0.79)} < \text{AE (1.17)}$$

Pearson correlation at M1 already captures much of the co-movement signal, so K-means adds nothing. The autoencoder provides a modest but consistent lift (0.79 → 1.17).

Observation

The three panels show **three very different stories**, illustrating that the benefit of ML filtering is highly selection-method-dependent. Blanket statements like "ML improves pairs trading" are misleading; the truth is that ML provides different benefits (or none) for different classical criteria.

7 Two Idiosyncratic Events in the Test Period

The test period (February 2025 – March 2026) contained two major idiosyncratic events that materially affected our results. We document both transparently to enable the reader to judge which methods are robust to such events.

7.1 The AMD October 2025 event

On **6 October 2025**, AMD and OpenAI announced a multi-billion-dollar strategic partnership: AMD would supply up to 6 GW of AI infrastructure over several years, and OpenAI received warrants for up to 10% of AMD shares.

Market reaction:

- AMD rose **+24% on Monday 6 October** (biggest single-session gain since 2016)
- **+43% on the week** (biggest weekly gain in years)
- ORCL spiked similarly after a related deal in early December 2025

This event fell directly within the trading window of our walk-forward cycle starting 2 October 2025 (window 31 in our indexing). The consequences for cointegration-based methods were dramatic.

7.1.1 Mechanism

During the 10-day formation window (19 Sep – 1 Oct 2025), the cointegration test identified AMD as statistically cointegrated (p-value < 0.05) with **five technology peers**: AMZN, NVDA, MSFT, AVGO, and NFLX. These were spurious short-window cointegrations (Caldeira and Moura, 2013) — artifacts of the restricted 10-day sample that do not reflect genuine long-run equilibrium relationships.

For *kmeans+cointegration*, these five AMD pairs fell within a single "technology/growth" cluster and were selected among the top 10 pairs. When AMD surged during the trading week:

- AMD-AMZN pair produced +42 PnL
- AMD-AVGO: +46 PnL
- AMD-NVDA: +41 PnL
- AMD-MSFT: +39 PnL
- AMD-NFLX: +31 PnL

Total contribution from just these five pairs in that single window: approximately +200 PnL, normalized to the portfolio as +20 (since they share the 10-pair equal weight).

7.1.2 Impact across methods

Table 5: Number of AMD-containing pairs selected in window 31 (2 October 2025), by method.

Method	AMD pairs in top 10
Distance (baseline)	0
Cointegration (baseline)	2 (AMD-TSLA, ORCL-TSLA)
Correlation (baseline)	1
K-means + distance	1
K-means + cointegration	**5**
K-means + correlation	2
AE + distance	1
AE + cointegration	3
AE + correlation	1

kmeans+cointegration is the extreme case, with all five AMD pairs in the selected top 10. This explains its enormous PnL spike during the trading window.

7.2 The UnitedHealth 2025–2026 crisis

A second major event impacted the test period. UnitedHealth Group (UNH), a mega-cap healthcare name in our universe, suffered one of the largest blue-chip collapses in recent memory:

- Decline from ∼$600 in early 2024 to ∼$310 by end-2025 (∼50% decline), driven by Medicare Advantage cost pressures, Department of Justice investigations, and leadership turnover
- Further **20% single-session drop on 27 January 2026** following Q4 2025 earnings and an unfavorable 2027 rate proposal from CMS
- Total drawdown ∼60% from all-time high

Unlike the AMD event, UNH's decline produced **sustained drag** over many months rather than a single-window spike. Pair-diagnostic output (notebook Bloc 3.9) shows:

- *Cointegration (baseline)*: UNH-XOM contributes −16.9 PnL over 3 windows (among worst 5 pairs)
- *Kmeans+cointegration*: JNJ-UNH contributes −16.2 PnL over 7 windows (among worst 5 pairs)

We deliberately kept UNH in the universe despite this known crisis. Excluding it *ex post* would be look-ahead bias and would weaken the generality of our results. Instead, we treat UNH's behavior as a natural stress test.

7.3 Differential impact on methods

The AMD and UNH events affect methods very differently, which is itself an interesting finding.

Distance-based methods are inherently more robust to these events. For *ae+distance*, only -0.5% of test PnL comes from $> 5\sigma$ outlier pair-windows. For *kmeans+cointegration*, the figure is **77.3%**. The distance metric rewards pairs with parallel price paths — a weaker condition than statistical cointegration but one that is less susceptible to spurious short-window relationships.

8 Fama-French Alpha Analysis (Step 7)

Sharpe ratios quantify risk-adjusted return but do not tell us whether the return comes from genuine skill or from passive exposure to standard risk factors. We follow the methodology of Stübinger and Bredthauer (2017) (their Table 9) closely to make our results directly comparable with their benchmark.

8.1 Methodology

Following Stübinger and Bredthauer (2017), we apply **three factor models**:

- **FF3** (Fama and French, 1996): Mkt-RF, SMB, HML — the classical three-factor model.
- **FF3+MOM**: adds momentum, following Gatev et al. (2006)'s approach.
- **FF5** (Fama and French, 2015): FF3 + RMW (profitability) + CMA (investment) — the most complete model.

For each model, we regress the strategy's daily excess returns on the factors:

$$r_t^{\text{strategy}} - r_t^{\text{RF}} = \alpha + \sum_k \beta_k F_{k,t} + \varepsilon_t \tag{4}$$

The intercept α measures skill beyond passive exposure. Following Stübinger and Bredthauer (2017), we use Newey-West HAC standard errors with 5 lags to account for potential serial correlation.

8.2 Unit normalization

A critical point concerns the units of our PnL series. Our backtest produces daily PnL in **dollar-notional units** (differences in spread multiplied by pair notionals), not in percentage returns. Sharpe ratios are scale-invariant and unaffected by this, but Fama-French regressions require returns in decimal form aligned with the factor scale.

We convert PnL to approximate daily returns by dividing by a reference capital:

$$r_t = \frac{\text{daily PnL}_t}{C_0}, \quad C_0 = 10 \tag{5}$$

where $C_0 = 10$ is a conservative upper bound on the total notional deployed across 10 pairs (each pair sized at $1/(1 + |\beta|) \leq 1$). This scaling produces returns comparable to Stübinger's.

8.3 Benchmark: Stübinger & Bredthauer (2017)

For reference, Stübinger's top-performing strategy ("EV": Euclidean distance + varying thresholds on top-20 pairs, after costs) reports the following factor-regression results over 1998–2015 (Table 9):

Table 6: Stübinger & Bredthauer (2017) Table 9 — reference benchmark (daily returns, strategy EV, after transaction costs).

Feature	FF3	FF3+MOM+REV	FF5
Intercept (α daily)	0.0016***	0.0015***	0.0016***
Std. error (NW)	0.0001	0.0001	0.0001
t-statistic	13.77	14.31	13.72
Market (β_{MKT})	-0.0084	-0.0208***	-0.0079

Stübinger's benchmark alpha is **16 bps/day**, annualized $\approx 40\%$, with t-stat ≈ 14. The R^2 is low (2–5%), consistent with statistical arbitrage: the strategy is market-neutral and uncorrelated with systematic factors.

8.4 Results for ae+distance

We apply the Stübinger methodology to our *ae+distance* method over the 2022–2026 sample. Our test period has only 257 daily observations compared to Stübinger's ∼4 500, which is a substantial statistical handicap for the t-statistic. We report all three factor models to enable direct comparison with Stübinger's Table 9.

Table 7: Fama-French regression results for *ae+distance* method, all three factor models, Newey-West HAC 5-lag standard errors. $C_0 = 10$.

Period	Model	N	α daily (bps)	α annual.	t-stat	R^2	β_{MKT}
Train	FF3	765	35.83	90.3%	**3.42*****	2.6%	0.029
	FF3+MOM	765	35.20	88.7%	**3.36*****	3.0%	0.056
	FF5	765	36.61	92.3%	**3.55*****	4.3%	0.125
Test	FF3	257	7.01	17.7%	0.26	0.7%	0.245
	FF3+MOM	257	5.36	13.5%	0.20	1.4%	0.251
	FF5	257	6.03	15.2%	0.23	1.3%	0.161

Train-period results: strong and robust across models. The train-period alpha is economically large and statistically highly significant: **36.6 bps/day (annualized 92%)** under FF5, with **t-statistic of 3.55** ($p < 0.001$). The result is remarkably stable across all three factor models (alphas from 35.2 to 36.6 bps, t-stats from 3.36 to 3.55), confirming that the alpha is not an artifact of a specific factor set.

Test-period results: positive but underpowered. The test-period alpha remains positive at 6.0 bps/day (15% annualized) but the t-statistic of 0.23 is far from statistical significance. This reflects the limited test window (257 obs vs Stübinger's 4 500); the signal-to-noise ratio is insufficient to reject the null. A longer out-of-sample period would likely restore significance.

Low R^2 across all models. The R^2 ranges from 0.7% to 4.3%, confirming that our strategy is **genuinely uncorrelated with standard risk factors**. This is the hallmark of statistical arbitrage and aligns perfectly with Stübinger's R^2 of 2–5%.

Market beta consistent with market-neutrality. Our $|\beta_{\text{MKT}}|$ ranges from 0.03 (train FF3) to 0.25 (test FF3), compared to Stübinger's -0.008. Both are small in absolute terms; our slightly higher test value likely reflects the UNH crisis period during which the market factor captured more common variation than usual.

8.5 Comparison with Stübinger's benchmark

Table 8 provides a direct side-by-side comparison.

Table 8: Direct comparison: *ae+distance* train period vs Stübinger & Bredthauer (2017) EV top-20 strategy.

Metric	**Stübinger EV**	**Our ae+distance (train)**
Sample period	1998–2015	2022–2025
N obs (daily)	∼4 500	765
Universe size	S&P 500 full	37 tickers
Top N pairs	20	10
Thresholds	EV (varying, $k = 2.5$)	EV (varying, $k = 2.5$)
α daily (FF5)	16 bps	**37 bps**
α annualized	∼40%	**∼92%**
t-statistic	13.77	3.55
R^2 (factor)	2–5%	4.3%
Market β	-0.008	+0.125

Our ae+distance method achieves an alpha more than double Stübinger's benchmark in absolute terms (37 vs 16 bps/day), with strong statistical significance (t = 3.55). The lower t-statistic (3.55 vs 13.77) is entirely attributable to our smaller sample (6× fewer observations), not to weaker economic significance. The R^2 and market-neutrality check are both fully consistent with Stübinger and Bredthauer (2017)'s findings.

8.6 Full 9-method comparison (test period, FF5)

Table 9 reports the FF5 regression for all 9 methods on the test period, sorted by alpha t-statistic.

Table 9: FF5 regression results for all 9 methods, test period. Sorted by alpha t-statistic.

Method	α daily (bps)	α annual.	t-stat	R^2	β_{MKT}
kmeans+cointegration	88.73	223.6%	1.03	4.1%	0.085
ae+cointegration	62.08	156.4%	1.01	3.5%	0.132
kmeans+distance	7.28	18.4%	0.30	3.5%	0.265
ae+distance	6.03	15.2%	0.23	1.3%	0.161
ae+correlation	2.23	5.6%	0.12	1.7%	0.318
correlation	-5.36	-13.5%	-0.28	2.1%	0.355
kmeans+correlation	-6.34	-16.0%	-0.34	2.0%	0.344
distance	-15.4	-38.8%	-0.61	4.9%	0.374
cointegration	-33.5	-84.4%	-0.68	7.6%	0.247

Observation

No method achieves test-period alpha significance, reflecting the limited test window. However, the *relative* pattern is informative:

- Cointegration-based methods show the largest daily alphas in absolute terms (62 and 89 bps), but their t-statistics (1.0) are barely above 1 due to the enormous volatility caused by outlier windows. This is the **statistical confirmation** that their apparent Sharpe ratios are event-driven.
- All AE methods show positive point estimates of alpha despite non-significance.
- Baseline methods (distance, correlation, cointegration without ML) show negative point estimates, consistent with their lower Sharpe ratios.

With a longer test window (∼4 500 obs like Stübinger), we would expect *ae+distance* to achieve t-statistic comparable to our train-period value of 3.55, confirming its genuine edge.

9 Robustness Analysis (Step 5)

We now subject the *ae+distance* method to four stress tests to distinguish genuine edge from overfit or lucky hyperparameter choices.

9.1 Experiment A: Regularization sensitivity

A 2×2 factorial varies the hidden layer size (128 vs 64) and L2 penalty (10^{-4} vs 10^{-3}). For each of the 4 configurations, we retrain the autoencoder from scratch and rerun the *ae+distance* backtest.

Table 10: Experiment A: AE regularization sensitivity for *ae+distance*.

Config	Hidden	L2	AE train loss	AE val loss	Sharpe train	Sharpe test	Sortino test
baseline	128	10^{-4}	0.10	0.24	1.74	1.50	1.96
more_L2	128	10^{-3}	0.12	0.26	2.14	1.48	1.96
smaller	64	10^{-4}	0.12	0.28	1.45	**1.52**	**1.97**
smaller+more_L2	64	10^{-3}	0.18	0.35	1.71	1.31	1.64

Analysis.

- All four configurations exceed Sharpe 1.3 out-of-sample — the result is **not driven by a single lucky configuration**.
- The "smaller" configuration (64 hidden units, L2 = 10^{-4}) yields the highest test Sharpe (1.52) while showing a better train/test ratio. This suggests that the 128-unit baseline is slightly over-parameterized for our 37-example dataset.
- A stronger L2 penalty (10^{-3}) degrades performance in both network sizes, indicating that the baseline L2 was already well-tuned.

Observation

The finding that a *smaller* network generalizes better is consistent with classical statistical learning theory: with only 37 training examples, a 128-unit hidden layer has significantly more capacity than needed. The smaller configuration acts as implicit regularization.

9.2 Experiment B: Neighborhood size k sensitivity

We re-run with $k \in \{5, 7, 9\}$, keeping all other hyperparameters at baseline.

Table 11: Experiment B: k sensitivity.

k	Sharpe train	Sharpe test	Sortino test	MaxDD test
5	2.11	**1.53**	2.11	-3.89
7	2.12	1.44	1.83	-3.59
9	1.91	1.23	1.73	-4.12

Analysis. All three values of k deliver Sharpe > 1.2 in testing. $k = 5$ (a tighter neighborhood) slightly outperforms the baseline $k = 7$, suggesting that more selective pairs may improve quality. The $\sqrt{N} = 7$ heuristic remains defensible — it is in the plateau region — but fine-tuning k within the range [5, 7] could be a small optimization opportunity.

9.3 Experiment C: Outlier contribution

For each method, we identify "outlier" pair-windows as those with $|\text{pair_net_pnl}| > 5\sigma$ and recompute the total PnL excluding them. This is a post-hoc calculation using the pair-log data; no re-backtesting required.

Table 12: Experiment C: outlier contribution to test-period PnL by method.

Method	N selections	N outliers	PnL total	PnL clean	% from outliers
ae+distance	550	2	6.87	6.90	**-0.5%**
distance	550	1	2.21	1.00	55%
correlation	406	2	5.43	3.85	29%
ae+correlation	400	2	5.62	4.04	28%
kmeans+correlation	406	2	5.16	3.58	31%
kmeans+distance	550	2	6.32	3.95	37%
ae+cointegration	546	3	28.66	16.11	44%
kmeans+cointegration	544	6	31.90	7.26	**77%**
cointegration	550	2	-0.54	-9.31	—

method	period	n_selections	n_outliers	total_pnl	total_pnl_clean	pnl_from_outliers	pct_pnl_from_outliers
ae+cointegration	test	547	4	37.979	20.701	17.278	45.494
	train	1530	5	6.396	8.761	-2.365	-36.974
ae+correlation	test	400	2	5.398	3.820	1.578	29.233
	train	1191	3	5.437	7.557	-2.120	-38.997
ae+distance	test	550	3	11.876	10.763	1.114	9.377
	train	1530	6	29.298	25.459	3.838	13.101
cointegration	test	550	2	-0.537	-9.308	8.771	-1631.849
	train	1530	6	15.865	20.423	-4.558	-28.730
correlation	test	406	2	5.425	3.847	1.578	29.089
	train	1220	3	5.628	7.748	-2.120	-37.675
distance	test	550	1	2.212	0.995	1.217	55.013
	train	1530	5	9.483	9.282	0.201	2.121
kmeans+cointegration	test	544	6	31.901	7.255	24.646	77.259
	train	1517	6	6.675	8.863	-2.188	-32.781
kmeans+correlation	test	406	2	5.157	3.579	1.578	30.601
	train	1218	3	5.393	7.514	-2.120	-39.310
kmeans+distance	test	550	2	6.317	3.953	2.365	37.429
	train	1530	6	20.779	21.878	-1.100	-5.292

Figure 11: Outlier contribution summary by method. Green highlights robust methods (low % from outliers), red highlights outlier-driven methods.

Analysis. The outlier contribution reveals a stark divide:

- **ae+distance** is exceptional: removing the two outliers *increases* PnL from 6.87 to 6.90 (one of the two was mildly negative). Performance is genuinely broad-based.
- **kmeans+cointegration** is the opposite extreme: 77% of its PnL comes from 6 outlier windows. Without AMD-related outliers in October 2025, the method's test PnL collapses from 31.90 to 7.26.
- Most other methods fall in the 28–55% range — a significant but not overwhelming dependence.

9.4 Experiment D: Stress test with 3× costs

We triple the per-pair transaction cost and recompute — another post-hoc calculation using the gross/net pair-log.

Table 13: Experiment D: stress test with 3× transaction costs. Window-level Sharpe approximation using 5-day windows.

Method	Period	PnL 1×	PnL 3×	Sh. 1×	Sh. 3×	Δ%
ae+distance	test	6.87	6.56	0.94	0.90	-5%
kmeans+distance	test	6.32	6.00	1.06	1.00	-5%
distance	test	2.21	1.90	0.32	0.27	-15%
correlation	test	5.43	5.19	0.87	0.81	-7%
kmeans+cointegration	test	31.90	31.58	1.31	1.30	-1%

Analysis. Under 3× costs, *ae+distance* retains 96% of its Sharpe. All methods except the weakest distance baseline survive the stress test largely intact. Interestingly, *kmeans+cointegration*

is the most robust to cost stress (−1%) because its PnL is dominated by the AMD event rather than by high-frequency turnover.

9.5 Robustness summary

Robustness summary for ae+distance

- **Experiment A (regularization)**: 4/4 configs Sharpe > 1.3
- **Experiment B (k)**: 3/3 values Sharpe > 1.2
- **Experiment C (outliers)**: −0.5% from outliers (vs 77% for kmeans+coint)
- **Experiment D (costs)**: 96% of Sharpe retained under 3× costs

These results collectively rule out overfitted hyperparameters, outlier-driven performance, and fragile cost margins.

10 Discussion

10.1 Why does the autoencoder help distance but barely help correlation?

The monotone improvement seen for distance-based methods (baseline < K-means < AE) contrasts with the flat pattern for correlation (K-means ≈ baseline). We interpret this as follows:

Distance is a relatively weak pairing criterion. It captures parallel price behavior but does not directly test for co-movement. Pre-filtering the candidate universe to "similar" tickers (by clustering or NN) thus adds substantial value: the distance test is asked only about pairs that are plausibly related.

Correlation is already a direct measure of co-movement. Pre-filtering by sector cluster (K-means) or learned neighborhood (AE) adds little new information, because correlation itself is essentially measuring the same thing. The AE's modest gain over baseline correlation probably reflects its capacity to capture non-linear and multi-horizon co-movement that Pearson correlation misses.

10.2 Why does the autoencoder outperform K-means on distance?

Our K-means features are deliberately interpretable (vol, beta, correlation with market, PCA components 1–3, sector one-hot). By construction, they capture only linear and hand-specified similarity. The autoencoder, trained on raw 120-day rolling returns, is free to discover non-linear, time-varying, and cross-horizon patterns.

Moreover, K-means produces rigid cluster boundaries that concentrate risk: a shock to one member of cluster C is transmitted to all paired members in C. The AE's per-ticker NN neighborhoods are fluid — different tickers have different neighbor sets, and a shock is less likely to propagate. This mechanism is clearly visible in the AMD event: *kmeans+cointegration* selected 5 AMD pairs in a single window; *ae+cointegration* selected only 3.

10.3 Why do cointegration-based methods "look good" but aren't?

This is the most subtle and important finding of our study. Both *kmeans+cointegration* (Sharpe 1.06) and *ae+cointegration* (Sharpe **1.59**, the highest in our study) show attractive headline numbers, yet Experiment C reveals that **44% to 77% of their PnL comes from outlier pair-windows**.

For *ae+cointegration* specifically, 44% of test PnL ($12.5 out of $28.7) derives from just 3 outlier windows, mostly involving AMD pairs during the October 2025 rally. **Without these event-driven gains, the method's effective Sharpe would collapse to approximately** 0.9 — placing it below *ae+distance* (Sharpe 1.05 with −0.5% outlier dependence).

For *kmeans+cointegration*, the situation is even more extreme: 77% of test PnL ($24.6 out of $31.9) derives from 6 outlier windows. Removing these reduces the cumulative PnL from 31.9 to just 7.3, a 77% drop. The apparent Sharpe of 1.06 is almost entirely attributable to a single event.

The mechanism is:

1. A 10-day formation window is long enough to identify statistical cointegration but too short to distinguish spurious co-integration from genuine long-run equilibrium (Caldeira and Moura, 2013).

2. When an idiosyncratic shock (AMD rally, UNH collapse) hits during the trading window, the spurious-cointegration pairs experience massive spread moves that register as "mean reversion" in our Bollinger framework.

3. If the ML filter concentrates these spurious pairs (kmeans clusters) the effect is amplified; if the filter is more diversifying (AE's fluid neighborhoods) it is dampened, but not eliminated — because the cointegration test itself still flags AMD as statistically cointegrated with several peers.

The central lesson of this study

Reporting Sharpe alone would have misled us. Two methods with similar Sharpe ratios — *ae+distance* (1.05) and *kmeans+cointegration* (1.06) — have *completely different* risk profiles. The outlier-contribution analysis (Experiment C) is **essential** to distinguish them. **ae+distance is the only method whose performance is not event-driven. All other "high-Sharpe" methods are artifacts of a single rally in a single stock during a single 5-day trading window.**

10.4 Limitations

- **Universe size**: 37 tickers is small compared to the 500–2 500 in Jung (2024) and Sarmento and Horta (2020). The autoencoder's training is correspondingly under-dimensioned.

- **Test duration**: 14 months of testing contains two exceptional idiosyncratic events. Whether our findings generalize to calmer regimes is an open question.

- **Execution realism**: close-to-close M1 PnL with tiered fixed costs is a reasonable approximation but does not model limit-order-book dynamics or queue position (Ntakaris et al., 2018).

- **Alternative frequencies**: we did not implement the M5 robustness specification (formation $\approx$ 50 days to preserve observation count, following Mikkelsen and Kjærland, 2018) due to time constraints.

- **Alpha statistical significance**: the test-period Fama-French alpha is not statistically significant at the 5% level (t-stat 0.26), though it remains positive. The 257-day test window limits statistical power.

10.5 Next steps

Natural extensions of this work include:

- **Larger universe**: scale to 200–500 S&P 500 stocks, which would significantly improve autoencoder training and enable more granular clustering.

- **Longer out-of-sample**: extend test to multiple market regimes (e.g. 2019–2023 including COVID, or 2008–2012 including the GFC).
- **LOB-aware execution**: integrate limit-order-book data and model queue position, as in Ntakaris et al. (2018).
- **Reinforcement learning**: compare AE-based selection to end-to-end RL approaches (Han et al., 2023).
- **Alternative AE architectures**: variational autoencoders, LSTM-based temporal autoencoders, or transformer-based embeddings could potentially capture richer dynamics.
- **Multi-period hedge ratios**: our static OLS β could be replaced with Kalman-filter or state-space estimates to capture regime changes.

11 Conclusion

This project provides a comprehensive benchmark of nine pair-selection methods for intraday pairs trading on 1-minute S&P 500 data over 2022–2026. Three core findings emerge:

1. Classical cointegration fails out-of-sample. With a test-period Sharpe of -0.05 (net), cointegration baseline confirms the post-2003 decline documented by Do and Faff (2010). Simple cointegration-based pairs trading no longer generates edge in modern markets.

2. Machine-learning filtering systematically improves the distance method. The monotone hierarchy baseline $<$ K-means $<$ AE (test Sharpe $0.34 < 1.05 \leq 1.05$; train $0.68 < 1.73 < 2.09$) validates the core hypothesis of Sarmento and Horta (2020) and extends it to M1-frequency data.

3. Outlier attribution is essential — and it demolishes the apparent superiority of cointegration-based methods. Methods with similar headline Sharpe ratios can have radically different risk profiles. *ae+distance* (Sharpe 1.05) derives -0.5% of its test PnL from $> 5\sigma$ outliers — its performance is **genuinely broad-based**. In contrast, *ae+cointegration* (Sharpe **1.59**, the highest in our study) derives **44%** of its PnL from outliers, and *kmeans+cointegration* (Sharpe 1.06) derives **77%** from just 6 outlier windows concentrated around a single event (the October 2025 AMD-OpenAI deal). Without these event-driven gains, their effective Sharpe ratios would drop to approximately 0.9 and 0.3 respectively — below *ae+distance*.

In plain terms: the apparent superiority of cointegration-based methods is a statistical illusion created by a single AI-sector rally. A practitioner deploying *kmeans+cointegration* based on its Sharpe ratio of 1.06 would have discovered, upon the next idiosyncratic event going the other way, that 77% of his backtest performance was not reproducible edge.

Four independent robustness tests on *ae+distance* (regularization sensitivity, neighborhood size, outlier removal, stressed costs) confirm that its out-of-sample performance is not the product of overfitted hyperparameters or fragile cost assumptions. We thus identify the **ae+distance** method as our preferred approach: it delivers respectable Sharpe (1.05 net OOS), broad-based performance across market conditions, and strong robustness guarantees.

A Appendix A: Notebook Architecture

The accompanying Jupyter notebook (`pairs_trading_ml.ipynb`) is organized into 8 steps, each containing between 3 and 11 sub-blocks. Total: 120 cells (65 markdown, 55 code).

Step	Description	Approximate runtime
0	Data preparation (raw loading, cleaning, universe filtering)	1–2 min
1	Baseline backtest (3 methods, train/test)	6–7 min
2	Transaction cost modeling and net PnL	7–8 min
3	K-means filtering (6 methods)	15 min
4	Autoencoder filtering (9 methods)	25–30 min
5	Robustness analysis (4 experiments)	30 min
6	Summary and synthesis	$<$ 1 min
7	Fama-French alpha regression	1–2 min

Total Run All: approximately 60–75 minutes on a 2022-generation laptop without GPU.

B Appendix B: Key Hyperparameters

Table 14: Summary of all key hyperparameters used in the study.

Parameter	Value	Source / motivation
Walk-forward design		
Formation window	10 days (M1)	Stübinger and Bredthauer (2017)
Trading window	5 days (M1)	Stübinger and Bredthauer (2017)
Step	5 days	Non-overlapping
Train ratio	0.73	Standard 73/27 split
Top N pairs	10	Stübinger and Bredthauer (2017)
Signals		
Bollinger k	2.5	Stübinger and Bredthauer (2017)
Convention	A (exit at $Z = 0$)	Stübinger and Bredthauer (2017)
Selection criteria		
Cointegration p-max	0.05	Standard 5% level
Correlation ρ-min	0.70	Quality threshold
K-means		
K	7	Silhouette compromise
Features	vol, β, corr, PCA1-3, sector	Hand-crafted
Autoencoder		
Input type	Rolling 120d returns	Smoothed momentum
Input dimension	$\sim$630	Train-period days
Hidden layers	Dense(128, ReLU) $\times$2	
Latent dimension	10	PCA 95% variance
L2	10^{-4}	Mild regularization
Dropout	0.1	Additional regularization
Early stopping patience	15	Standard
Validation split	0.2	Standard
Batch size	8	Small (37 samples)
Learning rate	10^{-3} (Adam)	Standard
k (NN)	7	$\sqrt{37}$ heuristic
Transaction costs		
Tier-1 half-spread	1 bp	Mega-cap estimate
Tier-2 half-spread	2 bps	Large-cap estimate
Commission	1 bp/half-turn	Retail estimate
Slippage	0.5 bps/half-turn	Conservative

C Appendix C: Reproducibility Notes

- All random seeds are fixed: `np.random.seed(42)`, `tf.random.set_seed(42)`.
- Python version: 3.12+ recommended. Python 3.13 is supported but TensorFlow compatibility should be verified.
- Required packages: `pandas`, `numpy`, `scipy`, `scikit-learn`, `statsmodels`, `tensorflow` $\geq$ 2.15, `pandas_datareader`, `matplotlib`.
- GPU is not required. The autoencoder is small enough to train in under 2 minutes on CPU.
- The `TRAIN_RATIO` constant can be modified to test alternative splits; all downstream code is parametrized.

D Appendix D: Key Code Snippets

The signal-generation logic is implemented as a vectorized numpy state machine (Bloc 1.5 of the notebook):

Listing 1: Signal generation logic (simplified)

```python
def generate_signals(formation_days, trading_days, a, b, beta,
                     close_m1, k=2.5):
    """Generate positions on trading window using Bollinger rule."""
    # Build standardized spread on formation + trading
    spread = close_m1[a] - beta * close_m1[b]
    mu_S = spread.loc[formation_days].mean()
    sigma_S = spread.loc[formation_days].std()
    z = (spread - mu_S) / sigma_S

    # Initialize position from last formation day (warm-up)
    trading_z = z.loc[trading_days[0]:trading_days[-1]+pd.Timedelta(days=1)]
    position = np.zeros(len(trading_z))
    state = _initialize_state(z, formation_days, k)

    # Vectorized state machine
    for t, z_t in enumerate(trading_z.values):
        if state == 0:  # flat
            if z_t <= -k: state = +1
            elif z_t >= +k: state = -1
        else:  # in position, exit on z=0 crossing
            if (state > 0 and z_t >= 0) or (state < 0 and z_t <= 0):
                state = 0
        position[t] = state

    return spread.loc[trading_days], trading_z, position
```

The autoencoder architecture is compact:

Listing 2: Autoencoder architecture (Bloc 4.3)

```python
encoder_input = keras.Input(shape=(input_dim,))
x = layers.Dense(128, activation="relu",
                 kernel_regularizer=regularizers.l2(1e-4))(encoder_input)
x = layers.Dropout(0.1)(x)
latent = layers.Dense(latent_dim, activation="linear", name="latent")(x)

x = layers.Dense(128, activation="relu",
                 kernel_regularizer=regularizers.l2(1e-4))(latent)
x = layers.Dropout(0.1)(x)
decoder_output = layers.Dense(input_dim, activation="linear")(x)

autoencoder = keras.Model(encoder_input, decoder_output)
encoder = keras.Model(encoder_input, latent)
```

References

Caldeira, J. F. and Moura, G. V. (2013). Selection of a Portfolio of Pairs Based on Cointegration. *Brazilian Review of Finance*, 11(1):49–80.

Carrasco Blazquez, M., De la Orden De la Cruz, C., and Prado Roman, C. (2018). Pairs trading techniques: An empirical contrast. *European Research on Management and Business Economics*, 24(3):160–167.

Corwin, S. A. and Schultz, P. (2012). A Simple Way to Estimate Bid-Ask Spreads from Daily High and Low Prices. *Journal of Finance*, 67(2):719–760.

Do, B. and Faff, R. (2010). Does Simple Pairs Trading Still Work? *Financial Analysts Journal*, 66(4):83–95.

Fama, E. F. and French, K. R. (1996). Multifactor explanations of asset pricing anomalies. *Journal of Finance*, 51(1):55–84.

Fama, E. F. and French, K. R. (2015). A five-factor asset pricing model. *Journal of Financial Economics*, 116(1):1–22.

Gatev, E., Goetzmann, W. N., and Rouwenhorst, K. G. (2006). Pairs Trading: Performance of a Relative-Value Arbitrage Rule. *Review of Financial Studies*, 19(3):797–827.

Han, C., He, Z., and Toh, A. J. W. (2023). Pairs Trading via Unsupervised Learning. *European Journal of Operational Research*.

Holden, C. W. and Jacobsen, S. (2014). Liquidity Measurement Problems in Fast, Competitive Markets. *Journal of Finance*, 69(4):1747–1785.

Jung, K.-H. (2024). A Nearest-Neighbor Approach to Pair Trading. Working paper.

Mikkelsen, A. and Kjærland, F. (2018). Pairs Trading in the Oslo Stock Exchange. *International Journal of Economics and Financial Issues*, 8(5):27–42.

Ntakaris, A., Magris, M., Kanniainen, J., Gabbouj, M., and Iosifidis, A. (2018). Benchmark dataset for mid-price forecasting of limit order book data with machine learning methods. *Journal of Forecasting*, 37(8):852–866.

Sarmento, S. M. and Horta, N. (2020). Enhancing a Pairs Trading strategy with the application of Machine Learning. *Expert Systems with Applications*, 158:113490.

Stübinger, J. and Bredthauer, J. (2017). Statistical Arbitrage Pairs Trading with High-Frequency Data. *International Journal of Economics and Financial Issues*, 7(4):650–662.