

### Semantic Design Language, Sedela

To specify semantic designs generally, I've created a meta-language called SEDELA (for Semantic Design Language). First, we present the definition of SEDELA, then an example semantic design for MetaFunctions (a replacement for Microservices) in terms of SEDELA. Although I may aim to write a parser and type-checker for SEDELA, there will never be a compiler or interpreter. Thus, SEDELA will have no syntax for **if** expressions and the like. The only Meanings (SEDELA's nomenclature for functions) defined in the Prelude will be combinators such as `id`, `const`, `flip`, and etc. SEDELA's primitive types are all defined in terms of Axioms (types without formal definitions) with no available operations.

## Sedela Language Definition

<b>Axiom</b> :=	Axiom[!] "Informal definition."	where ! denotes intended effectfulness
<b>Meaning Type</b> :=	A -> ... -> Z	where A ... Z are <b>Type Expressions</b>
<b>Meaning Defn</b> :=	f (a : A) ... (z : Z) : R = <b>Expression</b>   <b>Axiom</b>	where f is the <b>Meaning Identifier</b> and a ... z are <b>Parameter Identifiers</b> and A ... Z, R are <b>Type Expressions</b>
<b>Expression</b> :=	<b>Example:</b> f a (g b)	where f and g are a <b>Meaning Identifiers</b> and a and b are <b>Paremeter Identifiers</b>
<b>Product</b> :=	MyProduct<...> = A   (A : A, ..., Z : Z)   <b>Axiom</b>	where MyProduct<...> is the <b>Product Identifier</b> and A ... Z are <b>Field Identifiers</b> and A ... Z are <b>Type Expressions</b>
<b>Sum</b> :=	MySum<...> =   A of (A   <b>Axiom</b> )   ...   Z of (Z   <b>Axiom</b> )	where MySum<...> is the <b>Sum Identifier</b> and A ... Z are <b>Case Identifiers</b> and A ... Z are <b>Type Expressions</b>
<b>Type Identifier</b> :=	<b>Product Identifier</b>   <b>Sum Identifier</b>	
<b>Type Expression</b> :=	<b>Meaning Type</b>   <b>Type Identifier</b>	
<b>Type Parameters</b> :=	<b>Type Identifier</b> < A, ..., Z; A<A, ..., Z>; ...; Z<...>>	where A ... Z are <b>Type Expressions</b> and A ... Z are <b>Category Identifiers</b> used for constraining A ... Z
<b>Category</b> :=	category MyCat<...> =   f : A   ...   g : Z	where MyCat<...> is the <b>Category Identifier</b> and f ... g are <b>Equivilence Identifiers</b> and A ... Z are <b>Types Expressions</b>
<b>Witness</b> :=	witness A =   f (a : A) ... (z : Z) : R = <b>Expression</b>   ...   g (a : A) ... (z : Z) : R = <b>Expression</b>	where A is a <b>Category Identifier</b> and f ... g are <b>Equivilence Identifiers</b> and a ... z are <b>Parameter Identifiers</b> and A ... Z, R are <b>Type Expressions</b>
<b>Categorization</b> :=	<b>Rule:</b> iff type A has a witness for category A, A is allowable for type parameter categorized as A	

<b>Line Comment</b> :=	<b>Example:</b> // comment text
<code>fun a b ... z -&gt; expr :=</code>	<code>\a (\b (... \z.expr))</code>
<code>a -&gt; b :=</code>	<code>_ = (_ : a) : b</code>
<code>() :=</code>	<b>Explanation:</b> The unit type / value.
<code>f . g :=</code>	<b>Explanation:</b> Function composition.

## Sedela Language Prelude

```
Bool = Axiom "A binary type."
Real = Axiom "A real number type."
Whole = Axiom "A whole number type."
String = Axiom "A textual type."
Maybe<a> = | Some of a | None
Either<a, b> = | Left of a | Right of b
List<a> = | Nil | Link of (a, List<a>)
Map<a, b> = | Leaf of (a, b) | Node of (Map<a, b>, Map<a, b>)

category Semigroup<a> =
  | append : a -> a -> a

category Monoid<m; Semigroup<m>> =
  | empty : m

category Pointed<p> =
  | pure<a> : a -> p<a>

category Functor<f; Pointed<f>> =
  | map<a, b> : (a -> b) -> f<a> -> f<b>

category Applicative<p; Functor<p>> =
  | apply<a, b> : p<a -> b> -> p<a> -> p<b>

category Monad<m; Applicative<m>> =
  | bind<a, b> : m<a> -> (a -> m<b>) -> m<b>

category Alternative<l; Applicative<l>> =
  | empty<a> : l<a>
  | choice : l<a> -> l<a> -> l<a>

category Comonad<c; Functor<c>> =
  | extract<a> : c<a> -> a
  | duplicate<a, b> : c<a> -> c<c<a>>
  | extend<a, b> : (c<a> -> b) -> c<a> -> c<b>

category Foldable<f> =
  | fold<a, b> : (a -> b -> b) -> b -> f<a> -> b

category Traversable<t; Functor<t>; Foldable<t>> =
  | traverse<a, b, p; Applicative<f>> : (a -> p<b>) -> t<a> -> p<t<b>>
```

```
// TODO: define the Arrow categories.
```

```
id a = a
```

```
const a _ = a
```

```
flip f a b = f b a
```

## Semantic Design for Nu Script

```
witness Monoid =  
  | append = +  
  | empty = toEmpty -t-
```

```
witness Monad =  
  | pure = toPure -t-  
  | map = map  
  | apply = app  
  | bind = bind
```

```
witness Foldable =  
  | fold = fold
```

```
// TODO: define traverse so we can make a witness for Traversable.
```

```
Property = Axiom "A property of a simulant."
```

```
Relation = Axiom "Indexes a simulant or event relative to the local simulant."
```

```
Address = Axiom "Indexes a global simulant or event."
```

```
get<a> : Property -> Relation -> a = Axiom "Retrieve a property of a simulant indexed by Relation."
```

```
set<a> : Property -> Relation -> a -> a = Axiom! "Update a property of a simulant indexed by Relation, then returns its value."
```

```
Stream<a> = Axiom "A stream of simulant property or event values."
```

```
getAsStream<a> : Property -> Relation -> Stream<a> = Axiom "Construct a stream of values from a simulant property."
```

```
setToStream<a> property relation stream = foldStream (fun _ -> set<a> property relation) stream
```

```
eventStream<a> : Address -> Stream<a> = Axiom "Construct a stream of values from event data."
```

```
foldStream<a, b> : (b -> a -> b) -> Stream<a> -> b = Axiom "Fold over a stream."
```

```
productStream<a, b> : Stream<a> -> Stream<b> -> Stream<(a, b)> = Axiom "Combines two streams into a single product stream"
```

```
sumStream<a, b> : Stream<a> -> Stream<b> -> Stream<Either<a, b>> = Axiom "Combines two streams into a single sum stream."
```

```
mapStream<a, b> mapper stream = foldStream (fun _ -> mapper a) stream
```

```
witness Comonad =  
  | map = mapStream  
  | extract = fun f a -> f a  
  | duplicate = fun f -> f f  
  | extend = fun f -> map f . duplicate
```

## Semantic Design for MetaFunctions (a replacement for micro-services - unrelated to Nu)

Any = Axiom "The universal base type."

Symbol =

- | Atom of String
- | Number of String
- | String of String
- | Quote of Symbol
- | Symbols of List<Symbol>

symbolToString (symbol : Symbol) : String = Axiom "Convert a symbol to string."

symbolFromString (str : String) : Symbol = Axiom "Convert a string to a symbol."

Vsync<a> = Axiom "The potentially asynchronous monad such as the one defined by Prime."

vsyncBind<a, b> (vsync : Vsync<a>) (f : a -> Vsync<b>) : Vsync<b> = Axiom "Create a potentially asynchronous operation."

vsyncReturn<a> (a : a) : Vsync<a> = Axiom "Create a potentially asynchronous operation that return the result 'a'."

witness Monad =

- | bind = vsyncBind
- | return = vsyncReturn

IPAddress = String

NetworkPort = Whole

Endpoint = (IPAddress, NetworkPort)

Intent = String // the intended meaning of a MetaFunction (indexes a MetaFunction from a Provider - see below)

Container = Intent -> Symbol -> Vsync<Symbol>

Provider = | Endpoint | Container

MetaFunction = Provider -> Intent -> Symbol -> Vsync<Symbol>

makeContainer (asynchrinous : Bool) (repositoryUrl : String) (credentials : (String, String)) (envDeps : Map<String, Any>) :  
Container = Axiom "Make a container configured with its Vsync as asynchronous or not, built from source pulled from the givern  
GIT url, and provided the given environmental dependencies."

attachDebugger (container : Container) = Axiom! "Attach debugger to code called inside the given container."

call (mfn : MetaFunction) provider intent args : Vsync<Symbol> = mfn provider intent args