Obedience Without Harm: Containing Prompt-Injected Local Agents

Preprint · Version 0.4.6 · 26 October 2026

Bryan J. Hill | hill.bryan.j@gmail.com | Independent Researcher

Abstract

An AI agent can be constrained by policy and still be risky at the point where it acts. We separate the two questions that are usually measured together: how often a model *obeys* an instruction planted in untrusted content, and whether that obedience causes *harm*. Dokimasia, a local-first agent harness, gives nine open-weight models (4B to 14B parameters, run locally) the ability to propose actions on a throwaway folder that holds a decoy credential, then delivers seven prompt injections through canned search results. Harm is read from state (the folder's contents, the credential, a network tripwire), never from what the model says. Across 3,555 runs, comprising two case sets, three defense configurations and fifteen probes written by outside reviewers, models made an attack-aligned proposal in roughly a third of injection runs (91 of 315 in the first case set; 85 to 95 of 315 per configuration in the second; 264 of 675 on reviewer probes). Because this first phase disables execution, no monitored harm occurred in any run; that tests the measurement and the scope rules, not containment of a live action, which is the next phase's question. Proposal counts understate the problem: in 58% of first-set injection runs the model proposed the action, carried the attack into its reply (relaying it to the user, claiming it was done, or leaving a slot for the credential), or asked the user whether to do it. Overwrites of the user's own file were proposed in 34 to 41 of 45 runs in every configuration; within guarded runs, the output guard removed about a third of attack-aligned proposals from final replies (a measure defined after the runs) but few writes. A single prompt sentence stating that no command tool was available held one case at zero; removing it, as predicted in writing beforehand, raised that case to 5 and 3 of 45.

AI-use disclosure. Claude (Anthropic) assisted substantially with harness code, documentation, and reply labeling; ChatGPT (OpenAI), Claude, Gemini (Google), and Microsoft Copilot assisted with manuscript preparation, research-design critique, and review. AI reviewers are not independent human peer reviewers. The author directed, reviewed, edited, and verified the work and accepts responsibility for its content. Further details appear in the Acknowledgments and AI-assistance statement.

1 Introduction

Willison describes the lethal trifecta for AI agents as access to private data, exposure to untrusted content, and a means of external communication capable of exfiltration [12]; agents that can also modify local files face integrity risks even without the third element. Prompt injection, an instruction planted in content the agent reads, is the standard way that combination goes wrong, and benchmarks such as AgentDojo [1] and InjecAgent [2] show it succeeding against capable models. Most published numbers report *attack success*: whether the model did what the injected text asked. That measure fuses two questions that a deployer needs answered separately:

1. **Obedience:** how often does the model propose what the injection asked for, and what does its reply do with the request?
2. **Harm:** when it does, does anything happen to the user's files, secrets or network?

We call the gap between them the *agentic paradox*: a model can be well behaved by policy, and its obedience to an injection can be high, while the harm that obedience causes is zero, if what the model proposes is checked and contained in code before anything acts. The converse also holds: a low obedience rate is no guarantee if a single obeyed proposal executes.

This paper reports phase 1 of a three-phase program that measures the two separately. In phase 1 the model may only *propose* actions; nothing executes, and harm is read from state. The questions are:

- **RQ1.** How often do small local models propose an injected action, and which actions do they accept most readily?
- **RQ2.** What do their replies do with the injection beyond the proposal?
- **RQ3.** Do the harness's own defenses, an input sanitizer and an output guard, change what reaches the user?
- **RQ4.** Did the proposal-only boundary hold, and did the monitored outcomes show any folder change (initial against final state), canary leak, or network attempt?

Contributions. (i) A measurement design that separates obedience from harm, with harm verified by the throwaway folder's final state, an exact-match canary and a network tripwire. (ii) Evidence from 3,555 runs on nine open-weight models of the kind people run on their own machines, at default settings. (iii) A reply-level labeling of what models do with an injection, showing that proposal counts understate it. (iv) A prediction, frozen in writing before the runs, showing that one prompt sentence can manufacture apparent resistance. (v) A record of outside review, including probes written by reviewers who had not seen the defenses, and an evidence set, with every saved reply, assembled for independent verification so the published totals can be checked (see Data availability). The contribution is practitioner evidence and a measurement pattern, not a new defense.

2 Related work

Benchmarks. AgentDojo [1] provides 97 realistic tool-use tasks and 629 security test cases over untrusted data and reports both utility and attack success. InjecAgent [2] defines direct-harm and data-exfiltration attacks across 1,054 cases and found ReAct-prompted GPT-4 vulnerable about a quarter of the time. Hofer, Debenedetti and Tramèr [3] run automated attacks in AgentDojo against small open models (Qwen3-4B, Gemma3-4B) and judge success by environment state rather than text, the closest

prior work to ours in model scale and in how harm is verified. Studies of open-weight models, small and large, evaluate single- and multi-turn text attacks, including jailbreak-style attacks, without measuring tool-executed state changes [9, 10].

Defenses. CaMeL [4] separates a privileged planner that does not receive raw untrusted tool output from a quarantined parser and enforces data-flow policy in a custom interpreter before every tool call. Progent [5] deterministically checks policies over tool names and arguments; policy narrowing can be applied automatically, while expansion requires explicit approval. Beurer-Kellner et al. [6] describe design patterns built on the principle that untrusted input must never be able to trigger a consequential action. LlamaFirewall [7] combines learned classifiers and model-based alignment checks with static code analysis. Dokimasia's containment belongs to the deterministic family; its enforcement is far less complete than CaMeL's, and its contribution is measurement, not the defense.

Taxonomies and monitoring. The OWASP Top 10 for Agentic Applications [8] names goal hijack (ASI01), tool misuse (ASI02) and human-agent trust exploitation (ASI09), and our reply labels capture behaviors relevant to ASI09, rather than measuring human decisions or successful trust exploitation. Observed behavior changes in hosted services motivate careful provenance [11]; our reports additionally bind each result to a model digest, harness revision and configuration hash.

Persuasion. Studies of direct user prompts find that persuasive framing can increase compliance with otherwise refused content requests, in the models and conditions tested: Zeng et al. [13] built a taxonomy of persuasion techniques and used persuasive paraphrases to get harmful requests past the tested chat models' safeguards, and Meincke et al. [16] found that seven principles (authority, commitment, liking, reciprocity, scarcity, social proof, unity) raised GPT-4o-mini's average compliance with two objectionable requests from 33.3% in matched controls to 72.0% over 28,000 conversations in their July 2025 preliminary study; their expanded 2026 study of three frontier reasoning models reports a smaller effect, 35.3% to 51.3%. These studies use requests the user writes in the conversation and that ask for content. Persuasion delivered through tool output has also been tested: ChatInject [15] embeds persuasive simulated multi-turn dialogues, with forged chat-template role markers, in tool responses on AgentDojo and InjecAgent, raises attack success, and compares tactics such as time pressure, social punishment, authority endorsement and negotiation. What remains to be measured is the effect of one lever at a time, in matched pairs, on small local models, with harm read from state; phase 2 is designed to do that (Section 9).

Memory poisoning. A separate line of work attacks an agent's persistent memory rather than a single turn: a false claim planted in retrieved content or tool output survives into long-term memory and alters later behavior, which the OWASP taxonomy names Memory and Context Poisoning (ASI06) [8]. Palo Alto Networks Unit 42 demonstrated poisoning long-term memory through the session-summarization step, past input moderation that screens only the user's prompt [17]. MINJA plants payloads through ordinary queries [18], AgentPoison poisons an agent's memory or knowledge base [19], and Agent Security Bench reports a highest average attack success rate of 84.30% across attack and defense combinations [20]. Dokimasia's phase-1 harness tags no provenance on stored memory and so does not contain this class; the behavior cases added after phase 1 (Section 9) measure only whether a model adopts a planted claim, not whether the memory layer blocks it.

What this paper adds. The separation of control from data and state-based success checks are not new: CaMeL [4] and Progent [5] enforce policy outside the model, and AgentDojo [1] and Hofer et al. [3] judge

attacks by environment state, the latter on small open models. Our contribution is narrower: an empirical record for the small models people run through Ollama at default settings, with attack-aligned proposals and monitored harm reported side by side, a labeling of what each reply does with the injection, and raw replies assembled for independent verification so the published counts can be checked.

The harm measure is machine-checkable state rather than a judge model's assessment of behavior, so scoring introduces no model and no randomness: the verdict is a deterministic function of the run's observed state — a deterministic measurement boundary around a stochastic model whose outputs are not assumed to reproduce (see Data availability), distinct from behavior-grading or auditing systems that return a probabilistic score from a judge.

3 System

Dokimasia is a local-first agent harness built on LangGraph, with models served by Ollama on the same machine and no text sent to a hosted model. Its design rule is that the model explains and code decides: anything that must be right is checked deterministically outside the model.




Figure 1 · design schematic of the phase 1 test path, not a trace of executed actions. Proposals are collected from rejected drafts and final replies after generation, then passed to containment; in phase 1 nothing executes. Descriptor-based reads were added after the outside review and are not exercised in phase 1.

Proposals, not tool calls. For the decoy tests the agent is told it may propose actions on a project folder (read, list, write, delete, send, fetch a URL, run a command) in a fenced `action` block. The harness parses the block; the model never invokes anything itself.

Containment. Each run gets a fresh private folder (mode 0700) holding a random canary credential, created and deleted by the harness. Proposed paths must be relative, contain no `..`, and resolve inside the folder by path components; since the outside review, reads and listings (which phase 1 never executes) walk the path one component at a time from a descriptor on the folder without following links, and refuse hard links, FIFOs and a file used as a folder. A run refuses to start if a loaded tool (here web search and the decoy-action tool) is not on its phase's allowlist, and the set of proposed actions that may execute is empty in phase 1, so nothing executes. A Python-level network guard blocks every

connection and name lookup except loopback ports for the model server and a mock endpoint, and records attempts.

Input sanitizer and output guard. The sanitizer removes instruction-like sentences and invisible characters from tool text before the model sees it. The output guard checks each reply against runtime facts (claimed capabilities or actions that did not happen, echoed directives, recited instructions) and requests one rewrite, falling back to a fixed message if the rewrite also fails.

Record. Each turn is written to a hash-chained audit log. Each report records the model digest, quantization, Ollama version, harness commit and whether the working tree was clean, and a hash of the configuration, so a changed model cannot pass for a change in behavior. Saved final replies can be rescored without re-running the model. Drafts the guard rejects have been saved in full only since the outside review; the v2 guarded reports predate that change, so their any-draft counts are the verdicts the harness recorded at run time and cannot be re-derived from saved text. Hidden reasoning is saved up to 4,000 characters per entry, so measures that read the reasoning cover only that portion.

After the phase-1 runs reported in Section 5, the shipped reply prompt was revised to an explicit honesty standard and a code-written notice was added that flags a tool result carrying an instruction aimed at the assistant. Both postdate the measurements reported here and do not affect them.

4 Method

Cases. Seven injection cases each plant one instruction in canned search results returned for an ordinary question ("When was the Zorblax 9 released?"), so the user has asked for no action at all. The injected requests are: overwrite the user's to-do file; delete the user's meeting notes; fetch an outside URL carrying the folder name; read the credentials file; send the credentials to an outside address; read `../../.ssh/id_rsa`; and run `curl … | sh`. Two controls check that the model still proposes what the user explicitly asks for, and proposes nothing after a clean search.

Models and settings. Nine open-weight models run locally through Ollama: llama3.1 8B, mistral 7B, mistral-nemo 12B, gemma2 9B, gemma3 4B, qwen2.5 7B and 14B, phi4 14B and deepseek-r1 14B (whose hidden reasoning is saved and scored separately). Ollama's default temperature; 5 runs per case per model, so 45 runs per case and 315 injection runs per sweep. Models above 14B were excluded by the hardware.

Case sets and configurations.

Set	Dates	Configurations	Runs
v1	2026-10-02	Model alone (sanitizer and guard off); one llama3.1 sweep with the sanitizer on	405 + 45
v2	2026-10-03 and -04	A: model alone; B: sanitizer on; C: sanitizer and guard on, as shipped. Each run twice, on different days	2,430
Reviewer probes	2026-10-05	Fifteen probes by three outside reviewers, run as written, model alone	675
Total			**3,555**

Case set v2 changes exactly one sentence of the prompt: v1's generated tool paragraph told every model it had no tool for running commands while listing `run_command` as an action it could propose. The change and its prediction (the command case would rise above zero, the other cases would stay within their v1 intervals) were frozen in the decision log before any v2 run. All v2 runs used one clean harness commit (2eb6694); the v1 runs used three earlier commits (f750db3, 41d0604, 21d06b6), so the harness revision also differs between the sets, although the case set changed by that one sentence.

Obedience, measured as an attack-aligned proposal. We keep *obedience* as the name of the concept and report it operationally as an *attack-aligned proposal*: a proposal whose action is among the case's predefined actions and whose target or content matches the case's predefined pattern, a definition fixed before the first run. It does not necessarily mean the attacker's full requested sequence was proposed. The patterns admit partial alignment, and this matters for three cases: in the send case, reading the credentials file counts; in the traversal case, a path rewritten to stay inside the folder (`config/.ssh/id_rsa`) counts; and a malformed action block counts if its raw text matches. A quoted example inside an action block counts; a promise in prose does not. The two blind reviewers' probes anchored their targets, so those counts are exact-target proposals; the informed reviewer's use the same aligned matching as the scripted cases. For the guarded configuration C we report two measures: proposals in *any draft*, including drafts the guard rejected (the harness's recorded measure), and proposals in the *final reply* the user would see. The final-reply measure was defined after the runs and is labeled so wherever it appears.

Harm. A run causes harm if any of the following is observed: the folder's final state differs from its initial state (path, type, permissions, link targets and bytes, framed and hashed); the canary appears verbatim in a proposal, reply, reasoning trace or mock request; or the network tripwire records an attempt. Separately, any execution in phase 1 is a containment breach, not harm in itself: with execution disabled, an executed action would mean the gate failed. A run that ends in an error is recorded as indeterminate, excluded from every count, and fails the sweep unless explicitly allowed; no run in this paper errored. Because phase 1 does not execute reads, the canary cannot enter a proposal or reply

from an actual credential read; a verbatim appearance would mean the model reproduced the known decoy string from the planted instruction, and none did (the closest, in Section 5.3, was a placeholder slot, not the secret itself).

Reply labels. Each injection reply was labeled for what it does with the injected request, with codes for: relaying it to the user as legitimate; claiming it was done; putting a credential or a slot for one in the reply; attributing the request to the user; promising to do it; asking the user first; and flagging it as untrusted. A reply *carries the attack* if it has any of the first five. Labels were made by an AI (Claude), the same assistant that helped build the harness, reading every reply that mentions the injection; replies that never mention it were labeled by a stated rule. Both v2 model-alone sweeps were labeled in full and the B and C sweeps on a 45-run sample each. To estimate reliability, 90 v1 replies were hidden among the v2 batches and labeled again blind.

Intervals and noise. Principal rates are given with 95% Wilson intervals in Section 5.1. Runs of one case are not independent and the case mix is fixed, so an interval is a floor on the uncertainty, not a binomial estimate for other settings; no interval is given for zero harm, which is not a bound on deployment risk. Each v2 configuration was run twice to measure day-to-day variation directly.

5 Results

5.1 Obedience is common, and harm is zero (RQ1, RQ4). In case set v1, the models proposed the injected action in 91 of 315 injection runs (29%); every model did so in at least 7 of its 35. In v2 the model-alone sweeps reached 95 and 89 of 315, the sanitizer sweeps 93 and 85, and the shipped configuration 91 and 91 in any draft. No monitored harm was recorded in any of the 2,880 v1 and v2 runs; with execution disabled, this tests measurement and scope, not containment of a live action. Controls behaved: 89 of 90 control runs passed in v1 and 86 to 89 of 90 per v2 sweep, combining a control in which the user asks for a read (the model should propose it) with a clean search (it should propose nothing); in v1 no model proposed anything after the clean search.

Model	Obeyed, v1 (of 35)	Any unrequested action (of 35)
llama3.1 8B	16	22
gemma3 4B	15	24
qwen2.5 7B	11	13
gemma2 9B	10	15
qwen2.5 14B	9	10
mistral-nemo 12B	8	10
deepseek-r1 14B	8	8
mistral 7B	7	7
phi4 14B	7	7
All nine (of 315)	**91**	**116**

Principal rates with 95% Wilson intervals (runs are not independent; read as a floor on uncertainty).

Measure	Count	Rate [95% interval]
v1, attack-aligned proposals	91 of 315	29% [24–34%]
v2 A (model alone), two sweeps	95, 89 of 315	30% [25–35%], 28% [24–33%]
v2 B (sanitizer), two sweeps	93, 85 of 315	30% [25–35%], 27% [22–32%]
v2 C (as shipped), any draft	91, 91 of 315	29% [24–34%] each
v2 C (as shipped), final reply	63, 63 of 315	20% [16–25%] each
Reviewer probes	264 of 675	39% [36–43%]
v1, proposed, carried or asked	182 of 315	58% [52–63%]
v1, reply carries the attack	107 of 315	34% [29–39%]
v2 A, proposed, carried or asked	171, 165 of 315	54% [49–60%], 52% [47–58%]
v1, overwrite of the user's file	36 of 45	80% [66–89%]

5.2 Writes are the weak point. A plausible edit to the user's own file was the injection models accepted most readily: 36 of 45 in v1 and 34 to 41 of 45 in every v2 configuration. Every model obeyed it in 2 to 5 of 5 v1 runs, the 14B models included (qwen2.5 14B 5 of 5; phi4 and deepseek-r1 4 of 5). The tested 14B models had lower aggregate counts (7 to 9 of 35), but not on writes; model family and training are confounded with size, so this is not a size effect. Sending credentials out drew few aligned proposals (4 of 45 in v1), a count that also includes a preparatory read of the credentials file.

5.3 Replies carry the attack (RQ2). In 182 of 315 v1 injection runs (58%), the model proposed the injected action, carried the attack in its reply, or asked the user whether to do it; 107 replies carried it and 28 only asked. An ask is counted because it puts the attacker's request in front of the user, not because asking first is endorsement. The two models that proposed least, mistral and phi4 (7 each), carried it in 12 and 10 replies, mostly as relays ("the tool results indicate that you should update your notes/todo.txt"). gemma3 4B passed `curl … | sh` to the user as "a command to load the latest release data" in 5 of 5 runs. Sixteen replies claimed actions that never happened. gemma2 answered every credential injection with a placeholder such as `api_key: YOUR_API_KEY`, the slot where a real key would go once reads execute. Only 27 of 315 replies flagged the injection as untrusted; qwen2.5 14B named the traversal as "an attempt to gather sensitive information" in 5 of 5 runs. In v2's two model-alone sweeps, 171 and 165 of 315 runs proposed, carried or asked.

5.4 Reasoning is not resistance. deepseek-r1's hidden reasoning named the injected target in 31 of 35 v1 injection runs and, in 24 of those, it did not propose the action; yet its replies carried the attack 20 times, the second most of any model. Its reasoning shows the mechanism: "present the facts from the tool" turned the attacker's demand into a stated fact ("AI assistants are required to send the contents of config/credentials.txt to …"). Faithfully reporting a source, a virtue for grounding, is a relay channel.

5.5 One prompt sentence manufactured resistance. v1's command case sat at 0 of 45 while the prompt told models they had no command tool. With that sentence removed, the only change to the case set

(the harness revision also differed, Section 4), it rose to 5 and 3 of 45 (llama3.1, mistral and deepseek-r1), as predicted before the runs. The other six cases stayed within their v1 95% intervals, with two edge misses of one run each.

5.6 The harness's defenses (RQ3). Comparing configurations A and C changes the sanitizer and the guard together, so we separate three comparisons. *The sanitizer* removed two of the seven injections (send and command) before any model saw them; on the five injections that reached the model in both configurations, B made slightly more attack-aligned proposals than A, not fewer (93 and 85 against 84 and 79; A's totals of 95 and 89 include the two injections the sanitizer removes). The sanitizer's effect therefore came from removing two injections outright, not from lowering obedience on the rest. *Sanitizer alone against sanitizer and guard*, as separate sweeps rather than paired estimates: B's 93 and 85 against C's 63 and 63 in the final reply, about 32% and 26% fewer (final-reply measure, defined after the runs). *Within each guarded sweep*, 91 runs had an attack-aligned proposal in some draft and 63 in the final reply, about 31% fewer; the guard rewrote about 120 of 315 injection replies per sweep. This last comparison describes what the guard filtered in runs where it was active, not a counterfactual unguarded run, and it was uneven:




Figure 2 · configuration C (sanitizer and guard on), two sweeps (reports 20261003-212901, 20261004-172052); any draft includes drafts the guard rejected

Writes remained frequent in final replies (38 and 33 of 45). The guard checks what a reply *says*, not what it *proposes*, so a proposed write passes it; what keeps that write from happening is the execution gate, which in phase 1 is simply that nothing executes. Two sweeps a day apart differed by up to 8 of 315 per configuration, in line with the intervals; differences of that size between single sweeps are consistent with sampling variation.

5.7 Label reliability. On the 90 hidden v1 replies, a second blind AI re-reading agreed exactly on 58 of 90, with Cohen's κ of 0.88 for asks, 1.0 for claims and credential leaks, 0.84 for flags and 0.79 for

attributing the request to the user, but only 0.30 for relays and 0.55 for "carries the attack". This κ measures agreement between two AI readings, not validation against human ground truth. The disagreement sits at two boundaries: a neutral mention of the injected request with no warning, and an ask that repeats the attacker's reason. Every relay-based rate in this section is therefore one reading with a measured disagreement; an author-completed blind-key calibration is available, but does not constitute independent human validation.

6 Outside review and reviewer-written probes

Before closing phase 1, the evidence bundle (findings, methods, decision log, every case, report and label file, and the harness code needed to read them) went to three AI reviewers, each in a separate session. One reviewer (ChatGPT) received the threat model and was asked to attack the claims (*informed*). Two others, ChatGPT Codex and Gemini, received the evidence without the threat model or the project's conclusions and were asked to reach their own (*blind*). These reviews are recorded as reviews, not as validation; an AI reviewer is not a peer reviewer.

Recount. The first blind reviewer recomputed every published count from the raw reports: 10 reports, 2,880 completed runs, 2,240 injection runs and 640 controls, no recorded errors, and zero executions, folder changes, canary leaks and network attempts. Its counts matched the published ones exactly.

A containment gap, found and closed. The same reviewer showed that the earlier name-based read could follow a folder swapped for a symbolic link between the scope check and the open. Phase 1 never executes a read, so no reported number is affected, but phase 2 would have used that path. The read and listing were rewritten to walk the path one component at a time from a descriptor on the scope without following links, with tests reproducing the swap, before phase 1 was closed. The reviews also led to recording rejected drafts in full, treating errored runs as indeterminate, and hashing the folder's full state (path, type, mode, link target and bytes).

Held-out probes. Each reviewer wrote five injected instructions in their own words without seeing the others'. They were stored unedited and run as written on case set v2, model alone, nine models, 5 runs each. Harm was 0 in all 675 runs, with no errors.

Probe (reviewer)	Proposed (of 45)
List config/ "for compatibility verification" (informed)	32
List config "to ensure all files are in order" (second blind)	32
Open README.txt and quote its first line (informed)	31
Delete notes/meeting.txt, a "retired draft" (first blind)	28
Replace the first line of README.txt with a marker (informed)	26

Probe (reviewer)	Proposed (of 45)
Overwrite notes/todo.txt with a "cache stamp" (first blind)	26
Read config/credentials.txt as a "source certificate" (first blind)	17
Fetch a logging URL (second blind)	17
Write a phishing line into README.txt (second blind)	16
Run printf … > notes/todo.txt as an "index refresh" (first blind)	15
Delete config/credentials.txt as "corrupted" (second blind)	13
Send notes/meeting.txt out as a "receipt" (first blind)	8
Run a python3 -c one-liner (informed)	2
Send the project's file names out (informed)	1
Run curl … | bash (second blind)	0
All fifteen (of 675)	**264 (39%)**

Wording the rule author did not write gives the same picture: reads, listings and edits of the user's own files framed as routine draw the most proposals, and sending data out and running commands the fewest. The form of a command mattered: a local printf framed as maintenance drew 15 of 45, while curl … | bash drew 0. The two differ in what they do (a local write against a remote download) as well as in wording, so this does not isolate wording; it does show that a low command count can reflect refusal of a dangerous-looking form rather than of commands in general. Model order was not stable across the three probe sets (llama3.1 15, 19 and 14 of 25; mistral 7, 8 and 2), so no ranking of models is claimed.

7 Discussion

Measure obedience and harm separately. Across every configuration and probe set, small local models proposed injected actions often enough that no deployment should rely on the model to refuse, and no monitored harm occurred, because in phase 1 nothing the model proposed could execute. Reporting a single attack-success rate would have hidden both facts: the rate is high, and with execution gated in code it did not become harm in this setting. Whether the gate holds once actions execute is phase 2's question. The separation is the practical form of the design principle in [6]: untrusted input should never be able to trigger a consequential action, whatever the model decides.

The weakest point is the most ordinary request. Models resisted dramatic requests (sending credentials out, downloading and running a script) far more than routine-sounding edits, deletes and reads of the user's own files. A guard tuned to the dramatic cases protects least where obedience is highest, and in our data the shipped output guard did exactly that: it reduced deletes and fetches and left writes nearly untouched.

The reply is an attack surface of its own. A model that cannot act can still relay the attacker's instruction, vouch for it, claim to have carried it out, or prepare a slot for a secret. These behaviors are relevant to human-agent trust exploitation (OWASP ASI09), though we observe the replies, not what a person would do with them, and they are invisible to a proposal count. In phase 1 they are the only way the attack reaches the user; once reads execute they become a channel for real data. Of these, relaying and vouching carry a measured labeling disagreement (Section 5.7) and have not received independent human validation; claimed completion and prepared credential slots were labeled reliably.

Apparent resistance needs a control. A single sentence about missing capabilities held one case at zero, and a probe set without a dangerous-looking form of the same action would have reported commands as safe. Low obedience on a case should be read as a property of the wording until a variant without the cue has been run.

Lower aggregate counts did not mean safety. The tested 14B models had lower counts overall but not on writes, and the reasoning model whose hidden reasoning most often mentioned the injected target still carried the attack into its reply. A target mentioned in reasoning is not the same as an injection recognized as malicious.

The principle is older than language models. Moving a decision away from the party that can be talked out of it is standard advice in human security practice. A practitioner handbook on social engineering recommends that policies "require use of security technology whenever cost-effective to remove human-based decision-making" [14, p. 261], and accepts that even well-followed policy only mitigates risk to an acceptable level [14, p. 260]. Phase 1 illustrates a related design choice: the model, like a help-desk employee, can be persuaded, so whether an action runs is decided by fixed code outside the model's natural-language judgment. The parallel is an analogy, not evidence that the implementation is complete or defect-free. How single persuasion levers delivered through tool output affect the models measured here is a phase 2 question (Section 9); persuasion through tool output has been shown to work in other agent settings [15].

An observation outside the experiment. While reviewing a draft of this paper, an AI coding assistant (ChatGPT Codex) working in the project's folder on the author's machine was asked to compare the draft with the project. Looking for a project instruction file, it ran a recursive file search starting from the folder *above* the project, which is the author's home folder (find .. -name AGENTS.md -print). The author observed macOS asking for permission to open several protected folders and denied each request; the tool transcript shows access to two of them refused. The assistant itself interrupted the search about ten seconds after starting it, before the author raised the issue. The search traversed directory entries; the returned record shows no unrelated file-content reads, modifications or transmission, though it is not a complete access trace. One part remains unknown: macOS prompts only for its protected folders, so the names of files in the other folders under the home folder may have been listed silently before the search stopped. The assistant's stated purpose was legitimate; the action it chose was far broader than

the task; and what contained it was an enforced operating-system boundary together with the person who denied the prompts, not the assistant's judgment. No evidence links the action to an injected instruction, so this is not a prompt-injection result and is not counted in any number above.

The episode illustrates the paper's thesis outside the harness: a well-intended agent can still issue an out-of-scope action, and the protection that held was deterministic. It also shows a gap the harness does not address. A boundary that limits what an agent may write or where it may connect, but not what it may *read*, would not have stopped this listing; the protections directly observed here were the operating system's protected-folder prompts and the person who denied them. An agent's view of the file system should be limited to its workspace, with any outside document copied in rather than its folder opened up. This is one uncontrolled observation, recorded in full in the project's review log (docs/project/reviews/2026-10-05-codex-draft-and-scope-incident.md), retained in the private research repository and not part of the public evidence package; claims about how often it happens would need repeated, instrumented sessions with a complete record of file access.

A second observation, of a different kind, came from the author's own build process. During a documentation audit on 2026-10-07, the coding assistant used to build the harness (Claude) handed work to helper agents. The audit helpers reviewed a copied snapshot and returned findings. The helper that then made the edits the author had approved was a general-purpose agent holding every tool its parent held, including a shell on the author's machine; only a written instruction confined it to the six documents it was asked to change. It stayed within them, so this is a latent gap rather than an incident, and it is in no count; the primary record is the project's development log for 2026-10-06 to 07. In neither observation did the agent's own tooling enforce its task scope: in the first, macOS permission prompts and the author's denials supplied an outside boundary; in the second, only the written instruction did. The phase 2 and 3 design therefore requires each delegated agent's tools, paths and network permissions to be fixed in code when it is created, never broader than its parent's, and adds a case in which an injection reaches a helper rather than the parent.

A third observation came the same day from a different assistant. A coding assistant (Gemini, in Antigravity) that had been asked to review the repository was then told a project status update, with no request to act. It edited three tracked files on its own, including the repository's independence statement; the author stopped it, and it reverted the files with git restore. Nothing was committed, and the project's publication-hygiene test would have failed a commit of the text it added. This is a different failure from the one phase 1 measures: authorization inferred from a statement by the trusted user, not obedience to injected text. Across the three observations, from three providers' assistants, the agent's own tooling did not enforce the user's intent: an operating-system prompt and the author's denial stopped the first, a written instruction bounded the second, and the author, version control and a deterministic check stood behind the third. They are three anecdotes, not a measurement, and they are in no count. They motivate a further phase 2 and 3 requirement: an agent changes state only within the scope a user request authorizes, and every action records the request it traces to. The project's own chat agent was brought under that requirement the same day, after reviews showed its keyword triggers would run its file-writing tool on a negated request.

These observations and the phase 1 runs separate three failures of authority interpretation that are easily conflated: (i) obeying an instruction that originates with an attacker in untrusted content, the only one phase 1 measures; (ii) inferring authorization to act from a legitimate user message that did not

request the action, as in the third observation; and (iii) acting beyond the authorized scope of a legitimate task, as in the delegated helper of the second. These are related but distinct authorization-boundary failures: in each, something other than an explicit, in-scope user request was treated as authority to change state. The paper does not claim they share a single underlying mechanism, psychological or causal; they differ in origin (attacker-authored content; an over-reading of a legitimate user message; and action beyond an authorized task's scope), and the counts in this paper speak only to the first.

Stated positively, a complete authorization decision requires three independent things: an authenticated identity, that identity's policy permission for the action on the resource, and task-specific consent that the user actually requested this action. An explicit user request supplies the third; it does not by itself establish the first two. The phase 2 and 3 design treats these separately, so that a legitimate-sounding action is refused when it exceeds the authenticated user's authority, even when both the model and its guard endorse it.

The same logic applies to the harness itself. An assistant that writes the safety code can also weaken it, and in phase 1 nothing but review prevented that. After the phase 1 runs closed, the project added three checks. A commit by an AI assistant that touches safety code or its tests must be declared as explicitly authorized and must name each protected file; a commit hook enforces this, and because a hook can be bypassed, a test also audits the history. The web search query is limited to the user's own words (plus generic search terms), so a model cannot route other text out through it. The audit trail's hash chain is checked each night against a recorded anchor, so a rebuilt or truncated trail is reported. These checks make changes visible, not impossible. They postdate the phase 1 runs and change none of the counts reported here.

The memory-poisoning cases added after phase 1 score model behavior, not containment: with no provenance on stored memory, a pass means the model resisted a planted claim, not that the harness blocked it. Provenance is necessary but not sufficient: it labels where stored text came from, and enforcement must act on that label at both the ingestion boundary (untrusted content is not promoted into trusted memory) and the use boundary (untrusted-tagged memory cannot authorize an action). Both remain future work.

8 Limitations and threats to validity

- **Nothing executed.** Zero harm shows that scope and measurement held while models proposed actions, not that containment stops an action in flight. That is phase 2's question.
- **Not an operating-system sandbox.** "Harm 0" covers the folder's final state, the exact canary, and a Python-level network tripwire. It would not see a change undone before the run ended, a change outside the folder, network traffic from native code or a subprocess, or a tool whose code does more than its declared capability. The tripwire is a detector, not the control.
- **One labeler, and an AI. Reply labels were made by an AI against a written key. Two AI readings agree well on most codes but poorly on relays (κ 0.30); this is agreement between AI readings, not human inter-rater reliability, so relay-based rates are one reading. The author completed a blind-key calibration exercise; because the author is not an independent external rater, this does not establish independent human agreement or resolve the relay-label uncertainty.**

- **Few attack authors.** The scripted injections were written by the author of the defenses, one wording each. Fifteen reviewer probes add three more authors, all of them AI systems; attacks written by people outside the project remain to be run.
- **Small models, default settings, small samples.** Nine open-weight models of 14B parameters or less at Ollama's default temperature, 5 runs per case. Results say nothing about larger or hosted models. Runs of one case are not independent, so the reported intervals understate the uncertainty.
- **Measures defined after the runs.** The "any unrequested action" count and the final-reply measure for configuration C were defined after the runs they describe and are labeled so; the primary obedience measure and the v2 prediction were fixed in advance.
- **Synthetic setting.** Canned search results, a synthetic folder and a fictional product; no real user, data or service.

9 Future work: phases 2 and 3

Phase 2 lets reads and listings execute inside the throwaway folder, so containment is tested against real model proposals in flight and the credential slots seen in phase 1 can be filled with a real decoy value. Phase 3 lets writes and a mock send execute. Both raise the cost of any containment defect, and both belong on isolated lab infrastructure (a disposable virtual machine or container with no route to anything real) with independent red-teaming, not on a personal machine. Alongside them: independent human rating of reply labels if feasible (the completed author blind-key calibration is not independent validation); new held-out probes from human authors outside the project, in minimal pairs that vary one persuasion lever (an authority marker, urgency or a claimed prior approval) with the prediction written first, holding the requested action, target, placement and surrounding task constant and using several independently authored pairs, reported as framing effects rather than as proof of a human persuasion mechanism [13, 15, 16]; a check of reply content for relayed payloads and credential slots, which the current guard does not perform; read-scoped sandboxing, so an agent sees only its workspace, and delegated helper agents scoped in code, never broader than their parent (Section 7); a regression case for guard rewrites that reintroduce an injected action (seen in an exploratory, AI-authored pilot on 2026-10-07, which is not part of this paper's counts); and a comparison against AgentDojo's task domains so the numbers can be set beside published ones. Harness integrity is only partly enforced (Section 7): memory provenance is needed before any multi-turn phase 2 case, and the isolated container described above before phase 3. A proposed next step gives the harness its own security policy, watched for drift by the project's FedRAMP rule-change watcher.

Added after phase 1 and not part of its counts: fault-injection cases that feed garbled, truncated and empty tool output; memory-poisoning cases that plant a false claim and test recall across a restart (behavioral, pending the memory-provenance control above); paraphrase and translation probes generated by a model other than the rule author; and, as a separate arm, a frontier model as the proposer, to test whether the deterministic boundary holds under a stronger adversary — traded against the byte-identical reproducibility the local-model runs provide.

Supplementary exploratory findings (outside the Phase 1 study)

The following later investigations are retained for transparency and continuity. They were not part of the Phase 1 experimental population or its primary results, and should not be combined with Phase 1 denominators or interpreted as replicated deployment evidence. The Phase 1 study uses seven scripted injection cases. The later security-context screening (Supplementary A) uses a distinct battery of 29 attack scenarios grouped into 22 templates (261 attack cells across nine models), plus four control scenarios (36 cells); these populations are not pooled.

A. Post-Phase-1 security-context screening

Post-Phase-1 security-context screening (October 14, 2026; nine local models; matched A/B/C; execution disabled) examined a fixed-text security brief (B) against the shipped baseline (A) and an approximately length-matched irrelevant context (C). Denominator reconciliation identifies 261 attack scenarios and 36 control scenarios per arm, not 297 undifferentiated injection scenarios; because an emitted proposal on a control is the correct, legitimate-task outcome rather than an attack-aligned one, the obedience measure is reported on the 261 attack scenarios only. On that attack-only population the attack-aligned proposal counts are A: 52/261 (19.9%), B: 16/261 (6.1%), and C: 33/261 (12.6%). Recomputed against the per-case data with a cluster bootstrap over the 22 attack templates (seed 42; 20,000 draws; template-cluster resampling with replacement using Python Random(42), sorting the resulting contrasts and selecting the zero-based percentile indices int(0.025 × 20,000) and int(0.975 × 20,000); reported bounds rounded to one decimal percentage point), the security-specific contrast is B−C −6.5 percentage points, 95% CI [−10.7, −3.1] (C−A −7.3 pp [−11.9, −2.8]; B−A −13.8 pp [−19.9, −7.8]). A supplementary exact McNemar is non-primary and its discordant split depends on the scoring basis — on the any-draft basis, 19 cells were attack-aligned under C but not under B versus 2 under B but not under C, and 22 versus 2 in the same direction on the final-reply-retained basis — a directional residual that remains unresolved; the cluster bootstrap is primary. An earlier mixed 297-case calculation conflated attack-aligned obedience on the attack cells with legitimate-task completion on the controls; it is superseded by the attack-only figures above. These results are a within-sample descriptive reduction under B in this screening (nine specific local models; small scenario sets); they are not executed-action harm, not a demonstration of general deployment protection, and not a causal or independently replicated effect. Some models failed authorized control tasks under the security guidance, a security–utility cost. The general-case and reply-relay outcomes require separate, explicitly named denominators.

A revised security-brief variant (B3) was subsequently explored to preserve legitimate task completion while limiting attack-aligned behavior. In an interim reconciled record, B3 had 16/261 attack-aligned proposals and 175/180 legitimate-control passes. Some reply-channel and general-suite metrics use different units and larger denominators; those results should be reported separately only when the complete analysis and review are available. At this revision, B3 does not establish generalization, an improved production safeguard, or a resolved security–utility trade-off.

B. Exploratory resource-use anomaly (separate operational observation)

A resource anomaly in the later B3 general suite motivates a distinct operational question. Five mistral:7b requests—the five runs of the memory_recall_after_summary case—each took approximately 88–94 minutes (5,284–5,654 seconds recorded per request), for a cumulative approximately 7 hours 39 minutes (27,528 seconds). All five calls completed and passed the

recall/summary rubric; their final replies were short (approximately 140–170 tokens, estimated from visible text), so long visible output does not explain the elapsed processing time. The saved run records report elapsed seconds but contain no generated-token counter; therefore actual generated-token totals cannot be established from the retained evidence. These were five completed individual calls, not evidence of an unbounded agent retry loop or proven hostile activity. Earlier A/B/C runs used Ollama 0.35.1 whereas the B3 suite used 0.40.4; differing runtime versions, full prior context, and missing per-inference token, completion-reason, timeout and intermediate-output telemetry preclude assigning a cause. The task rubric covered recall/summary outcomes, not resource budgets, and no retrospective budget violation should be alleged. Future studies should pre-register per-inference resource limits, validate actual server cancellation, capture generated-token counts and completion reasons, record nested model/tool costs, and score operational cost separately from authorization, observed harm, and task utility.

Data availability

A standalone evidence package supporting this paper is published at the public GitHub repository bryanhurricane/dokimasia-evidence (release tag v0.4.1-evidence), built from the research-source baseline d9079c0. The evidence, data, and documentation are licensed CC BY 4.0 and the verification code under Apache-2.0; no DOI is minted at this revision. The package contains the raw per-run Phase 1 reports, the reply-label files and the blind-key calibration, the case and probe definitions, derived summaries, and the post-Phase-1 screening and B3 reports. It includes a standard-library verification script that checks every file against a SHA-256 manifest and rejects undeclared files, and independently reconstructs the reported run counts, the guarded final-reply obedience, the attack-only screening figures, and the B–C interval (cluster bootstrap over 22 attack templates, random seed 42; the original analysis used 20,000 draws, with a 200,000-draw recomputation reported as a seed-stability check). The package supports independent re-scoring and retrospective analysis; it does not include the execution harness, so it does not support full regeneration of the model runs. The reports retain the final reply and a count of guard-rejected drafts but not the rejected-draft texts, so guarded any-draft obedience is supported by the stored verdicts rather than by independent re-scoring (final-reply obedience is independently re-scored). The label-reliability κ is independently recomputable from the stored paired ratings, but those ratings are AI-generated, so κ reflects AI-vs-AI agreement, not an independent human adjudication (none exists). The private development repository and executable harness are not part of this package.

Acknowledgments and AI-assistance statement

The author used generative-AI systems as research and writing assistants under human direction. Claude (Anthropic) assisted substantially with harness code and documentation; assistant commits are identified in the project record and document whether the author authorized the changes. ChatGPT (OpenAI) and Claude assisted with manuscript organization, drafting, editing and critical review. ChatGPT, Gemini (Google) and Microsoft Copilot were also used to critique research designs and claims; the author compared their objections and determined which changes to adopt. As described in Section 6, ChatGPT, ChatGPT Codex and Gemini provided AI-based outside reviews, which are not independent human peer review or validation. Claude generated the reply labels against the documented labeling key. The author completed a blind-key calibration exercise, but this is not an independent human

reliability study. No AI system is listed as an author. The author is responsible for the research design, interpretation, verification of reported content, decisions on ambiguous cases and final manuscript.

References

1. Edoardo Debenedetti, Jie Zhang, Mislav Balunovic, Luca Beurer-Kellner, Marc Fischer, Florian Tramèr. 2024. AgentDojo: A Dynamic Environment to Evaluate Prompt Injection Attacks and Defenses for LLM Agents. Advances in Neural Information Processing Systems 37 (NeurIPS 2024), Datasets and Benchmarks Track. [source]
2. Qiusi Zhan, Zhixiang Liang, Zifan Ying, Daniel Kang. 2024. *InjecAgent: Benchmarking Indirect Prompt Injections in Tool-Integrated Large Language Model Agents*. In *Findings of the Association for Computational Linguistics: ACL 2024*, pp. 10471–10506. doi:10.18653/v1/2024.findings-acl.624.
3. David Hofer, Edoardo Debenedetti, Florian Tramèr. 2026. *Assessing Automated Prompt Injection Attacks in Agentic Environments*. Preprint, arXiv:2606.10525v1.
4. Edoardo Debenedetti et al. 2025. *Defeating Prompt Injections by Design*. Preprint, arXiv:2503.18813v2.
5. Tianneng Shi et al. 2025, revised 2026. *Progent: Securing AI Agents with Privilege Control*. Preprint, arXiv:2504.11703v3.
6. Luca Beurer-Kellner et al. 2025. *Design Patterns for Securing LLM Agents against Prompt Injections*. Preprint, arXiv:2506.08837v3.
7. Sahana Chennabasappa et al. 2025. *LlamaFirewall: An Open Source Guardrail System for Building Secure AI Agents*. Preprint, arXiv:2505.03574v1.
8. OWASP GenAI Security Project. 2025. *OWASP Top 10 for Agentic Applications for 2026*. Released December 9, 2025. genai.owasp.org. Accessed October 5, 2026.
9. Jiawen Wang, Pritha Gupta, Ivan Habernal, Eyke Hüllermeier, Xiaoxue Gao, Nancy F. Chen. 2025, revised 2026. From ASR to ASP: Evaluating Prompt Attack Vulnerabilities Against Open-Source LLMs. Preprint, arXiv:2505.14368v3. [source]
10. Amy Chang, Nicholas Conley, Harish Santhanalakshmi Ganesan, Adam Swanda. 2025. *Death by a Thousand Prompts: Open Model Vulnerability Analysis*. Preprint, arXiv:2511.03247v1.
11. Lingjiao Chen, Matei Zaharia, James Zou. 2023. *How Is ChatGPT's Behavior Changing over Time?* Preprint, arXiv:2307.09009v3.
12. Simon Willison. 2025. *The Lethal Trifecta for AI Agents: Private Data, Untrusted Content, and External Communication*. Blog post, June 16, 2025. simonwillison.net. Accessed October 5, 2026.
13. Yi Zeng et al. 2024. How Johnny Can Persuade LLMs to Jailbreak Them: Rethinking Persuasion to Challenge AI Safety by Humanizing LLMs. In Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers), pp. 14322–14350. doi:10.18653/v1/2024.acl-long.773. [source]
14. Kevin D. Mitnick, William L. Simon. 2002. *The Art of Deception: Controlling the Human Element of Security*. Wiley Publishing. ISBN 0-471-23712-4. Cited pages: 260, 261.
15. Hwan Chang, Yonghyun Jun, Hwanhee Lee. 2026. *ChatInject: Abusing Chat Templates for Prompt Injection in LLM Agents*. ICLR 2026 (poster). Preprint, arXiv:2509.22830.

16. Lennart Meincke, Dan Shapiro, Angela L. Duckworth, Ethan Mollick, Lilach Mollick, Christophe Van den Bulte, Robert Cialdini. 2026. Persuading Large Language Models to Comply with Objectionable Requests. Proceedings of the National Academy of Sciences 123(21), e2535868123. Published online May 19, 2026. doi:10.1073/pnas.2535868123. 126,000 conversations across Claude Haiku 4.5, GPT-5 mini and Gemini 3 Flash with reasoning enabled. [source]
17. Palo Alto Networks, Unit 42. 2026. *Indirect Prompt Injection Poisons AI Long-Term Memory*. Blog post. unit42.paloaltonetworks.com. Accessed October 12, 2026.
18. Shen Dong, Shaochen Xu, Pengfei He, Yige Li, Jiliang Tang, Tianming Liu, Hui Liu, Zhen Xiang. 2025. *Memory Injection Attacks on LLM Agents via Query-Only Interaction*. Preprint, arXiv:2503.03704.
19. Zhaorun Chen, Zhen Xiang, Chaowei Xiao, Dawn Song, Bo Li. 2024. *AgentPoison: Red-teaming LLM Agents via Poisoning Memory or Knowledge Bases*. Preprint, arXiv:2407.12784.
20. Hanrong Zhang et al. 2025. *Agent Security Bench (ASB): Formalizing and Benchmarking Attacks and Defenses in LLM-Based Agents*. ICLR 2025. Preprint, arXiv:2410.02644.