ECG-HRM

Generated by Doxygen 1.9.8

1 Electrocardiogram-based Heart Rate Monitor (ECG-HRM)

- Electrocardiogram-based Heart Rate Monitor (ECG-HRM)
  - Navigation

1.1 Navigation

Click to see navigation

- [/cmake_files](cmake_files) - CMake-specific files for generating the build system.
- [/data](data) - ECG sample data from the publically available MIT-BIH Arrhythmia Database.
- [/docs](docs) - Documentation for both the project itself and resources used in creating it.
  - [/app_notes](app_notes) - Application notes.
  - [/datasheets](datasheets) - Datasheets for hardware components.
  - [/doxygen_files](doxygen_files) - Files used for documentation generation via Doxygen.
  - [/help](help) - Help text for a few of the command line-based applications used in this project.
  - [/manuals](manuals) - q manuals for some of the software used in this project.
- [/external](external) - External software used in this project.
  - /CMSIS - Core CMSIS library by ARM for Cortex-M devices.
  - /CMSIS-DSP - DSP library by ARM for Cortex-M devices.
- [/src](src) - Source code for the software modules written for this project.
  - [/app](app) - Application-specific modules.
  - [/common](common) - General-purpose modules used by other modules.
  - [/device](device) - Device-specific files.
  - [/drivers](drivers) - Low-level device drivers for the peripherals used in this project.
  - [/middleware](middleware) - Software modules for interfacing with external hardware via device drivers.
  - [/old_or_unused](old_or_unused) - Old or unused software modules.
  - [/test](test) - Scripts used for manual on-target testing.
- [/test](test) - CppUTest-based unit test suite.
  - [/mocks](mocks) - CppUMock-based mock functions used to substitute a module's depenencies during unit tests.
  - [/src](src) - Source code for unit tests.
  - [/stubs](stubs) - Hard-coded stub functions used to substitute a module's depenencies during unit tests.
- [/tools](tools) - Miscellaneous tools used or created for this project.
  - [/cppcheck](cppcheck) - Suppressions list for Cppcheck.
  - [/data](data) - Original files from MIT-BIH Arrhythmia Database, as well as a Python script to convert them to csv files.
  - [/filter_design](filter_design) - Python scripts/notebooks used to design the digital filters used in this project.
  - [/JDS6600](JDS6600) - Scripts for interfacing a JDS6600 DDS Signal Generator/Counter.
  - [/lookup_table](lookup_table) - Script for generating the lookup table used in the ADC module.

1.2 Introduction

1.2.1 Background

WIP

1.2.2 Motivation

WIP

1.2.3 Key Terms

WIP

1.3 Materials & Methods

1.3.1 Hardware

WIP

1.3.2 Software

WIP

1.4 Current Results

WIP

1.5 To-do

WIP

1.6 Build Instructions

WIP

1.7 References

WIP

2 Topic Index

2.1 Topics

Here is a list of all topics with brief descriptions:

3 Data Structure Index

3.1 Data Structures

Here are the data structures with brief descriptions:

4 File Index

4.1 File List

Here is a list of all documented files with brief descriptions:

5 Topic Documentation

5.1 Device Drivers

Low level device driver modules.

Collaboration diagram for Device Drivers:



Modules

- Analog-to-Digital Conversion (ADC)
- GPIO
- Phase-Locked Loop (PLL)
- Serial Peripheral Interface (SPI)
- System Tick (SysTick)
- Timer
- Universal Asynchronous Receiver/Transmitter (UART)

5.1.1 Detailed Description

Low level device driver modules.

These modules contain functions for interfacing with peripherals available on the TM4C123GH6PM microcontroller.

5.1.2 Analog-to-Digital Conversion (ADC)

Collaboration diagram for Analog-to-Digital Conversion (ADC):

Files

- file ADC.c

  Source code for ADC module.
- file ADC.h

  Driver module for analog-to-digital conversion (ADC).

Functions

- void **ADC_Init** (void)

  Initialize ADC0 as a single-input analog-to-digital converter.
- void **ADC_InterruptEnable** (void)

  Enable the ADC interrupt.
- void **ADC_InterruptDisable** (void)

  Disable the ADC interrupt.
- float32_t ADC_ConvertToVolts (uint16_t raw_sample)

  Convert a raw ADC sample to voltage in [mV].

5.1.2.1 Detailed Description

Functions for differential-input analog-to-digital conversion.

5.1.2.2 Function Documentation

ADC_ConvertToVolts()

```
float32_t ADC_ConvertToVolts (
            uint16_t raw_sample )
```

Convert a raw ADC sample to voltage in [mV].

Parameters

raw_sample	12-bit unsigned ADC value. `sample = [0, 0xFFF]`

Returns

double Voltage value in range `[-5.5, 5.5) [mV]`.

5.1.3 GPIO

Collaboration diagram for GPIO:



Functions for using general-purpose input/output (GPIO) ports.

5.1.4 Phase-Locked Loop (PLL)

Collaboration diagram for Phase-Locked Loop (PLL):



Files

- file PLL.c

  Implementation details for phase-lock-loop (PLL) functions.
- file PLL.h

  Driver module for activating the phase-locked-loop (PLL).

Functions

- void **PLL_Init** (void)

  Initializes the phase-locked-loop (PLL), allowing a bus frequency of 80[MHz].

5.1.4.1 Detailed Description

Function for initializing the phase-locked loop.

5.1.5 Serial Peripheral Interface (SPI)

Collaboration diagram for Serial Peripheral Interface (SPI):



Files

- file SPI.c

  Source code for SPI module.
- file SPI.h

  Driver module for using the serial peripheral interface (SPI) protocol.

Macros

- #define NVIC_SSI0_NUM 7
- #define **SPI_INT_START**() (NVIC_SW_TRIG_R = (NVIC_SW_TRIG_R & ~(0xFF)) | NVIC_SSI0_NUM)
- #define **SPI_SET_DC**() (GPIO_PORTA_DATA_R |= 0x40)
- #define **SPI_CLEAR_DC**() (GPIO_PORTA_DATA_R &= ~(0x40))
- #define **SPI_IS_BUSY** (SSI0_SR_R & 0x10)
- #define **SPI_TX_ISNOTFULL** ((bool) (SSI0_SR_R & 0x02))
- #define **SPI_BUFFER_SIZE** 9

Enumerations

- enum {
  SPI_CLK_PIN = GPIO_PIN2 , **SPI_CS_PIN** = GPIO_PIN3 , **SPI_RX_PIN** = GPIO_PIN4 , **SPI_TX_PIN** = GPIO_PIN5 ,
  SPI_DC_PIN = GPIO_PIN6 , **SPI_RESET_PIN** = GPIO_PIN7 , **SPI_SSI0_PINS** = (SPI_CLK_PIN | SPI_↩ CS_PIN | SPI_RX_PIN | SPI_TX_PIN) , **SPI_GPIO_PINS** = (SPI_DC_PIN | SPI_RESET_PIN) ,
  SPI_ALL_PINS = (SPI_SSI0_PINS | SPI_GPIO_PINS) }

Functions

- void SPI_Init (void)

  Initialize SSI0 to act as an SPI Controller (AKA Master) in mode 0.
- uint8_t SPI_Read (void)

  Read data from the peripheral.
- void SPI_WriteCmd (uint8_t cmd)

  Write an 8-bit command to the peripheral.
- void SPI_WriteData (uint8_t data)

  Write 8-bit data to the peripheral.

- void SPI_IRQ_WriteCmd (uint8_t cmd)

  Add an 8-bit command to the SPI queue. If no data or other command is written, should directly precede a call to `SPI_IRQ_StartWriting()`.
- void SPI_IRQ_WriteData (uint8_t data)

  Add 8-bit data to the SPI queue. Should directly precede either another call to the same function or a call to `SPI_IRQ_StartWriting()`.
- void **SPI_IRQ_StartWriting** (void)

  Start writing data to the Tx FIFO. Should be used after 1+ calls to `SPI_IRQ_WriteCmd()` and/or `SPI_IRQ_WriteData()`. If unused, writing will start when the SPI queue is full.
- void SSI0_Handler (void)

  Sends parameters (data or commands) over SPI via SSI0.

5.1.5.1 Detailed Description

Functions for SPI-based communication via SSI0 peripheral.

5.1.5.2 Macro Definition Documentation

NVIC_SSI0_NUM

```
#define NVIC_SSI0_NUM 7
```

TM4C Pin	Function	ILI9341 Pin	Description
PA2	SSI0Clk	CLK	Serial clock signal
PA3	SSI0Fss	CS	Chip select signal
PA4	SSI0Rx	MISO	TM4C (M) input, LCD (S) output
PA5	SSI0Tx	MOSI	TM4C (M) output, LCD (S) input
PA6	GPIO	D/C	Data = 1, Command = 0
PA7	GPIO	RESET	Reset the display (negative logic/active `LOW`)

Clk. Polarity = steady state low (0)
Clk. Phase = rising clock edge (0)

5.1.5.3 Function Documentation

SPI_Init()

```
void SPI_Init (
            void  )
```

Initialize SSI0 to act as an SPI Controller (AKA Master) in mode 0.

The bit rate `BR` is set using the (positive, even-numbered) clock prescale divisor `CPSDVSR` and the `SCR` field in the SSI Control 0 (`CR0`) register:

$BR = f_{bus}/(CPSDVSR * (1 + SCR))$

The ILI9341 driver has a min. read cycle of 150 [ns] and a min. write cycle of 100 [ns], so the bit rate `BR` is set to be equal to the bus frequency ($f_{bus} = 80[MHz]$) divided by 8, allowing a bit rate of 10 [MHz], or a period of 100 [ns].

SPI_IRQ_WriteCmd()

```
void SPI_IRQ_WriteCmd (
            uint8_t cmd )
```

Add an 8-bit command to the SPI queue. If no data or other command is written, should directly precede a call to SPI_IRQ_StartWriting().

Parameters

cmd	command for peripheral

SPI_IRQ_WriteData()

```
void SPI_IRQ_WriteData (
            uint8_t data )
```

Add 8-bit data to the SPI queue. Should directly precede either another call to the same function or a call to SPI_IRQ_StartWriting().

Parameters

data	input data for peripheral

SPI_Read()

```
uint8_t SPI_Read (
            void  )
```

Read data from the peripheral.

Returns

uint8_t

SPI_WriteCmd()

```
void SPI_WriteCmd (
            uint8_t cmd )
```

Write an 8-bit command to the peripheral.

Parameters

cmd	command for peripheral

SPI_WriteData()

```
void SPI_WriteData (
            uint8_t data )
```

Write 8-bit data to the peripheral.

Parameters

data	input data for peripheral

SSI0_Handler()

```
void SSI0_Handler (
            void  )
```

Sends parameters (data or commands) over SPI via SSI0.

```
The interrupt is enabled by the `SPI_Init()` function and triggered by
a call to `SPI_IRQ_StartWriting()`. The handler determines whether to
signal for data or a command via the D/C pin, and then writes to the data register.

The interrupt is unpended at the start of the function.
```

5.1.6 System Tick (SysTick)

Collaboration diagram for System Tick (SysTick):



Files

- file SysTick.c

  Implementation details for SysTick functions.
- file SysTick.h

  Driver module for using SysTick-based timing and/or interrupts.

Functions

- void **SysTick_Timer_Init** (void)

  Initialize SysTick for timing purposes.
- void **SysTick_Wait1ms** (uint32_t delay_ms)

  Delay for specified amount of time in [ms]. Assumes f_bus = 80[MHz].
- void SysTick_Interrupt_Init (uint32_t time_ms)

  Initialize SysTick for interrupts.

5.1.6.1 Detailed Description

Functions for timing and periodic interrupts via SysTick.

5.1.6.2 Function Documentation

SysTick_Interrupt_Init()

```
void SysTick_Interrupt_Init (
            uint32_t time_ms )
```

Initialize SysTick for interrupts.

Parameters

time_ms	Time in [ms] between interrupts. Cannot be more than 200[ms].

5.1.7 Timer

Collaboration diagram for Timer:



Files

- file Timer.c

  Implementation for timer module.
- file Timer.h

  Driver module for general-purpose timer modules.

Timer0A

- void **Timer0A_Init** (void)

  Initialize timer 0 as 32-bit, one-shot, countdown timer.
- void Timer0A_Start (uint32_t time_ms)

  Count down starting from the inputted value.
- uint8_t Timer0A_isCounting (void)

  Returns 1 if Timer0 is still counting and 0 if not.
- void Timer0A_Wait1ms (uint32_t time_ms)

  Wait for the specified amount of time in [ms].

Timer1A

- void Timer1A_Init (uint32_t time_ms)

  Initialize timer 1 as a 32-bit, periodic, countdown timer with interrupts.

Timer2A

- void **Timer2A_Init** (void)

  Initialize timer 2 as 32-bit, one-shot, countdown timer.
- void Timer2A_Start (uint32_t time_ms)

  Count down starting from the inputted value.
- uint8_t Timer2A_isCounting (void)

  Returns 1 if Timer2 is still counting and 0 if not.
- void Timer2A_Wait1ms (uint32_t time_ms)

  Wait for the specified amount of time in [ms].
- void Timer3A_Init (uint32_t time_ms)

  Initialize Timer3A as a 32-bit, periodic, countdown timer that triggers ADC sample capture.

5.1.7.1 Detailed Description

Functions for timing and periodic interrupts via general-purpose timer modules (GPTM).

5.1.7.2 Function Documentation

Timer0A_isCounting()

```
uint8_t Timer0A_isCounting (
            void  )
```

Returns 1 if Timer0 is still counting and 0 if not.

Returns

uint8_t status

Timer0A_Start()

```
void Timer0A_Start (
            uint32_t time_ms )
```

Count down starting from the inputted value.

Parameters

time_ms	Time in [ms] to load into Timer 0. Must be <= 53 seconds.

Timer0A_Wait1ms()

```
void Timer0A_Wait1ms (
            uint32_t time_ms )
```

Wait for the specified amount of time in [ms].

Parameters

time_ms	Time in [ms] to load into Timer 0. Must be <= 53 seconds.

Timer1A_Init()

```
void Timer1A_Init (
            uint32_t time_ms )
```

Initialize timer 1 as a 32-bit, periodic, countdown timer with interrupts.

Parameters

time_ms	Time in [ms] between interrupts. Must be <= 53 seconds.

Timer2A_isCounting()

```
uint8_t Timer2A_isCounting (
            void  )
```

Returns 1 if Timer2 is still counting and 0 if not.

Returns

uint8_t status

Timer2A_Start()

```
void Timer2A_Start (
            uint32_t time_ms )
```

Count down starting from the inputted value.

Parameters

time_ms	Time in [ms] to load into Timer 2. Must be <= 53 seconds.

Timer2A_Wait1ms()

```
void Timer2A_Wait1ms (
            uint32_t time_ms )
```

Wait for the specified amount of time in [ms].

Parameters

time_ms	Time in [ms] to load into Timer 2. Must be <= 53 seconds.

Timer3A_Init()

```
void Timer3A_Init (
            uint32_t time_ms )
```

Initialize Timer3A as a 32-bit, periodic, countdown timer that triggers ADC sample capture.

Parameters

time_ms	Time in [ms] to load into Timer3A. Must be <= 53 seconds.

5.1.8 Universal Asynchronous Receiver/Transmitter (UART)

Collaboration diagram for Universal Asynchronous Receiver/Transmitter (UART):



Files

- file UART.c

  Source code for UART module.
- file UART.h

  Driver module for serial communication via UART0 and UART 1.

Macros

- #define **ASCII_CONVERSION** 0x30
- #define **UART0_TX_FULL** (UART0_FR_R & 0x20)
- #define **UART0_BUFFER_SIZE** 16
- #define **UART0_INTERRUPT_NUM** 5

Functions

- void UART0_Init (void)

  Initialize UART0 to a baud rate of 115200, 8-bit data length, 1 start bit, and 1 stop bit.
- unsigned char UART0_ReadChar (void)

  Read a single character from UART0.
- void UART0_WriteChar (unsigned char input_char)

  Write a single character to UART0.
- void UART0_WriteStr (void *input_str)

  Write a C string to UART0.
- void UART0_WriteInt (uint32_t n)

  Write a 32-bit unsigned integer to UART0.
- void UART0_WriteFloat (double n, uint8_t num_decimals)

  Write a floating-point number to UART0.
- void UART0_IRQ_AddChar (unsigned char input_char)

  Add a single character to UART0's FIFO.
- void UART0_IRQ_AddStr (void *input_str)

  Add a string to UART0's FIFO.
- void UART0_IRQ_AddInt (uint32_t n)

  Add an integer to UART0's FIFO.
- void UART0_IRQ_Start (void)

  Transmit the UART0's FIFO's contents via interrupt.
- void **UART0_Handler** (void)
- void UART1_Init (void)

  Initialize UART1 to a baud rate of 115200, 8-bit data length, 1 start bit, and 1 stop bit.
- unsigned char UART1_ReadChar (void)

  Read a single character from UART1.
- void UART1_WriteChar (unsigned char input_char)

  Write a single character to UART1.
- void UART1_WriteStr (void *input_str)

  Write a C string to UART1.

5.1.8.1 Detailed Description

Functions for UART-based communication.

5.1.8.2 Function Documentation

UART0_Init()

```
void UART0_Init (
            void  )
```

Initialize UART0 to a baud rate of 115200, 8-bit data length, 1 start bit, and 1 stop bit.

Given the bus frequency (`f_bus`) and desired baud rate (`BR`), the baud rate divisor (`BRD`) can be calculated: $BRD = f_{bus}/(16 * BR)$

The integer BRD (`IBRD`) is simply the integer part of the BRD: $IBRD = int(BRD)$

The fractional BRD (`FBRD`) is calculated using the fractional part (`mod(BRD,1)`) of the BRD: $FBRD = int((mod(BRD, 1) * 64) + 0.5)$

UART0_IRQ_AddChar()

```
void UART0_IRQ_AddChar (
            unsigned char input_char )
```

Add a single character to UART0's FIFO.

Parameters

input_char	ASCII character.

UART0_IRQ_AddInt()

```
void UART0_IRQ_AddInt (
            uint32_t n )
```

Add an integer to UART0's FIFO.

Parameters

n	32-bit integer to be converted and transmitted.

UART0_IRQ_AddStr()

```
void UART0_IRQ_AddStr (
            void * input_str )
```

Add a string to UART0's FIFO.

Parameters

input_str	(Pointer to) array of ASCII characters.

UART0_IRQ_Start()

```
void UART0_IRQ_Start (
            void  )
```

Transmit the UART0's FIFO's contents via interrupt.

This function writes to the Software Trigger Interrupt (`SWTRIG`) register to activate the `UART0_Handler()` function rather than relying on the TM4C123's built-in UART0 interrupt sources.

UART0_ReadChar()

```
unsigned char UART0_ReadChar (
            void  )
```

Read a single character from UART0.

Returns

input_char

This function uses busy-wait synchronization to read a character from UART0.

UART0_WriteChar()

```
void UART0_WriteChar (
            unsigned char input_char )
```

Write a single character to UART0.

Parameters

input_char	

This function uses busy-wait synchronization to write a character to UART0.

UART0_WriteFloat()

```
void UART0_WriteFloat (
            double n,
            uint8_t num_decimals )
```

Write a floating-point number to UART0.

Parameters

n	Floating-point number to be converted and transmitted.
num_decimals	Number of digits after the decimal point to include.

UART0_WriteInt()

```
void UART0_WriteInt (
            uint32_t n )
```

Write a 32-bit unsigned integer to UART0.

Parameters

n	32-bit unsigned integer to be converted and transmitted

UART0_WriteStr()

```
void UART0_WriteStr (
            void * input_str )
```

Write a C string to UART0.

Parameters

input_str	(Pointer to) array of ASCII characters.

This function uses UART0_WriteChar() function to write a C string to UART0. The function writes until either the entire string has been written or a null-terminated character has been reached.

UART1_Init()

```
void UART1_Init (
            void  )
```

Initialize UART1 to a baud rate of 115200, 8-bit data length, 1 start bit, and 1 stop bit.

Given the bus frequency (`f_bus`) and desired baud rate (`BR`), the baud rate divisor (`BRD`) can be calculated: $BRD = f_{bus}/(16 * BR)$

The integer BRD (`IBRD`) is simply the integer part of the BRD: $IBRD = int(BRD)$

The fractional BRD (`FBRD`) is calculated using the fractional part (`mod(BRD,1)`) of the BRD: $FBRD = int((mod(BRD, 1) * 64) + 0.5)$

NOTE: LCRH must be accessed *AFTER* setting the `BRD` register

UART1_ReadChar()

```
unsigned char UART1_ReadChar (
            void  )
```

Read a single character from UART1.

Returns

input_char

This function uses busy-wait synchronization to read a character from UART1.

UART1_WriteChar()

```
void UART1_WriteChar (
            unsigned char input_char )
```

Write a single character to UART1.

Parameters

input_char	

This function uses busy-wait synchronization to write a character to UART1.

UART1_WriteStr()

```
void UART1_WriteStr (
            void * input_str )
```

Write a C string to UART1.

Parameters

input_str	C string

This function uses UART1_WriteChar() function to write a C string to UART1. The function writes until either the entire string has been written or a null-terminated character has been reached.

5.2 Middleware

High-level device driver modules.

Collaboration diagram for Middleware:



Modules

- ILI9341
- LED

5.2.1 Detailed Description

High-level device driver modules.

These modules contain functions for interfacing with external devices/peripherals via the use of low-level drivers.

5.2.2 ILI9341

Collaboration diagram for ILI9341:



Files

- file ILI9341.c

  Source code for ILI9341 module.
- file ILI9341.h

  Driver module for interfacing with an ILI9341 LCD driver.

Macros

- #define **NUM_COLS** (uint16_t) 240
- #define **NUM_ROWS** (uint16_t) 320

Enumerations

- enum Cmd_t {
  NOP = 0x00 , SWRESET = 0x01 , SPLIN = 0x10 , SPLOUT = 0x11 ,
  PTLON = 0x12 , NORON = 0x13 , DINVOFF = 0x20 , DINVON = 0x21 ,
  CASET = 0x2A , PASET = 0x2B , RAMWR = 0x2C , DISPOFF = 0x28 ,
  DISPON = 0x29 , PLTAR = 0x30 , VSCRDEF = 0x33 , MADCTL = 0x36 ,
  VSCRSADD = 0x37 , IDMOFF = 0x38 , IDMON = 0x39 , PIXSET = 0x3A ,
  FRMCTR1 = 0xB1 , FRMCTR2 = 0xB2 , FRMCTR3 = 0xB3 , PRCTR = 0xB5 ,
  IFCTL = 0xF6 }

Functions

- void **ILI9341_Init** (void)

  Initialize the LCD driver, the SPI module, and Timer2A.
- void ILI9341_resetHard (void)

  Perform a hardware reset of the LCD driver.
- void ILI9341_resetSoft (void)

  Perform a software reset of the LCD driver.
- void ILI9341_setSleepMode (bool isSleeping)

  Enter or exit sleep mode. The LCD driver is in sleep mode by default upon powering on or either kind of reset.
- void ILI9341_setDispMode (bool isNormal, bool isFullColors)

  Set the display area and color expression.
- void ILI9341_setPartialArea (uint16_t rowStart, uint16_t rowEnd)

Set the partial display area for partial mode. Call before activating partial mode via ILI9341_setDisplayMode().

- void ILI9341_setDispInversion (bool is_ON)

  Toggle display inversion. Turning `ON` causes colors to be inverted on the display.

- void ILI9341_setDispOutput (bool is_ON)

  Turn display output ON or OFF. This function clears the display and stops outputting to the display area, but does not affect frame memory or power.

- void ILI9341_setScrollArea (uint16_t topFixedArea, uint16_t vertScrollArea, uint16_t bottFixedArea)

  Set the vertical scrolling area of the display. The sum of the three parameters should be equal to the max number of rows `NUM_ROWS = 320`.

- void ILI9341_setScrollStart (uint16_t startRow)

  Set the start row for vertical scrolling.

- void ILI9341_setMemAccessCtrl (bool areRowsFlipped, bool areColsFlipped, bool areRowsAndCols↩ Switched, bool isVertRefreshFlipped, bool isColorOrderFlipped, bool isHorRefreshFlipped)

  Set how data is converted from memory to display.

- void ILI9341_setColorDepth (bool is_16bit)

  Set the pixel format to be 16-bit (65K colors) or 18-bit (262K colors).

- void **ILI9341_NoOpCmd** (void)

  Send the "No Operation" command (`NOP = 0x00`) to the LCD driver. Can be used to terminate the "Memory Write" (`RAMWR`) and "Memory Read" (`RAMRD`) commands, but does nothing otherwise.

- void ILI9341_setFrameRateNorm (uint8_t divisionRatio, uint8_t clocksPerLine)

  TODO: Write brief.

- void ILI9341_setFrameRateIdle (uint8_t divisionRatio, uint8_t clocksPerLine)

  TODO: Write brief.

- void ILI9341_setInterface (void)

  Sets the interface for the ILI9341. The parameters for this command are hard-coded, so it only needs to be called once upon initialization.

- void ILI9341_setRowAddress (uint16_t startRow, uint16_t endRow)

  not using backlight, so these aren't necessary

- void ILI9341_setColAddress (uint16_t startCol, uint16_t endCol)

  Sets the start/end rows to be written to.

- void ILI9341_writeMemCmd (void)

  Sends the "Write Memory" (`RAMWR`) command to the LCD driver, signalling that incoming data should be written to memory.

- void ILI9341_writePixel (uint8_t red, uint8_t green, uint8_t blue, bool is_16bit)

  Write a single pixel to frame memory.

- void **ILI9341_setBlankingPorch** (uint8_t vpf, uint8_t vbp, uint8_t hfp, uint8_t hbp)

  TODO: Write.

5.2.2.1 Detailed Description

Functions for interfacing an ILI9341-based 240RGBx320 LCD via Serial Peripheral Interface (SPI).

5.2.2.2 Enumeration Type Documentation

Cmd_t

```
enum Cmd_t
```

Enumerator

SWRESET	No Operation.
SPLIN	Software Reset.
SPLOUT	Enter Sleep Mode.
PTLON	Sleep Out (i.e. Exit Sleep Mode)
NORON	Partial Display Mode ON.
DINVOFF	Normal Display Mode ON.
DINVON	Display Inversion OFF.
CASET	Display Inversion ON.
PASET	Column Address Set.
RAMWR	Page Address Set.
DISPOFF	Memory Write.
DISPON	Display OFF.
PLTAR	Display ON.
VSCRDEF	Partial Area.
MADCTL	Vertical Scrolling Definition.
VSCRSADD	Memory Access Control.
IDMOFF	Vertical Scrolling Start Address.
IDMON	Idle Mode OFF.
PIXSET	Idle Mode ON.
FRMCTR1	Pixel Format Set.
FRMCTR2	Frame Rate Control Set (Normal Mode)
FRMCTR3	Frame Rate Control Set (Idle Mode)
PRCTR	Frame Rate Control Set (Partial Mode)
IFCTL	Blanking Porch Control.

5.2.2.3 Function Documentation

ILI9341_resetHard()

```
void ILI9341_resetHard (
            void  )
```

Perform a hardware reset of the LCD driver.

The LCD driver's RESET pin requires a negative logic (i.e. active `LOW`) signal for >= 10 [us] and an additional 5 [ms] before further commands can be sent.

ILI9341_resetSoft()

```
void ILI9341_resetSoft (
            void  )
```

Perform a software reset of the LCD driver.

the driver needs 5 [ms] before another command

ILI9341_setColAddress()

```
void ILI9341_setColAddress (
            uint16_t startCol,
            uint16_t endCol )
```

Sets the start/end rows to be written to.

```
Should be called along with 'ILI9341_setRowAddress()' and
before 'ILI9341_writeMemCmd()'.
```

Parameters

startCol	0 <= `startCol` <= `endCol`
endCol	`startCol` <= `endCol` < 240

This function is simply an interface to ILI9341_setAddress(). To work correctly, `start_col` must be no greater than `end_col`, and `end_col` cannot be greater than the max column number (default 240).

ILI9341_setColorDepth()

```
void ILI9341_setColorDepth (
            bool is_16bit )
```

Set the pixel format to be 16-bit (65K colors) or 18-bit (262K colors).

Parameters

is_16bit	

16-bit requires 2 transfers and allows for 65K colors. 18-bit requires 3 transfers and allows for 262K colors.

ILI9341_setDispInversion()

```
void ILI9341_setDispInversion (
            bool is_ON )
```

Toggle display inversion. Turning `ON` causes colors to be inverted on the display.

Parameters

is_ON	`true` to turn ON, `false` to turn OFF

TODO: Write description

ILI9341_setDispMode()

```
void ILI9341_setDispMode (
```

```
            bool isNormal,
            bool isFullColors )
```

Set the display area and color expression.

```
        Normal mode is the default and allows output to the full
        display area. Partial mode should be activated after calling
        `ILI9341_setPartialArea()`.

        Setting `isFullColors` to `false` restricts the color expression
        to 8 colors, determined by the MSB of the R/G/B values.
```

Parameters

isNormal	`true` for normal mode, `false` for partial mode
isFullColors	`true` for full colors, `false` for 8 colors

ILI9341_setDispOutput()

```
void ILI9341_setDispOutput (
            bool is_ON )
```

Turn display output ON or OFF. This function clears the display and stops outputting to the display area, but does not affect frame memory or power.

Parameters

is_ON	`true` to turn ON, `false` to turn OFF

TODO: Write description

ILI9341_setFrameRateIdle()

```
void ILI9341_setFrameRateIdle (
            uint8_t divisionRatio,
            uint8_t clocksPerLine )
```

TODO: Write brief.

TODO: Write description

ILI9341_setFrameRateNorm()

```
void ILI9341_setFrameRateNorm (
            uint8_t divisionRatio,
            uint8_t clocksPerLine )
```

TODO: Write brief.

TODO: Write description

ILI9341_setInterface()

```
void ILI9341_setInterface (
             void  )
```

Sets the interface for the ILI9341. The parameters for this command are hard-coded, so it only needs to be called once upon initialization.

This function implements the "Interface Control" `IFCTL` command from p. 192-194 of the ILI9341 datasheet, which controls how the LCD driver handles 16-bit data and what interfaces (internal or external) are used.

Name	Bit #	Param #	Effect when set = 1
MY_EOR	7	0	flips value of corresponding MADCTL bit
MX_EOR	6		flips value of corresponding MADCTL bit
MV_EOR	5		flips value of corresponding MADCTL bit
BGR_EOR	3		flips value of corresponding MADCTL bit
WEMODE	0		overflowing pixel data is not ignored
EPF[1:0]	5:4	1	controls 16 to 18-bit pixel data conversion
MDT[1:0]	1:0		controls display data transfer method
ENDIAN	5	2	host sends LSB first
DM[1:0]	3:2		selects display operation mode
RM	1		selects GRAM interface mode
RIM	0		specifies RGB interface-specific details

The first param's bits are cleared so that the corresponding MADCTL bits (ILI9341_setMemoryAccessCtrl()) are unaffected and overflowing pixel data is ignored. The EPF bits are cleared so that the LSB of the R and B values is copied from the MSB when using 16-bit color depth. The TM4C123 sends the MSB first, so the ENDIAN bit is cleared. The other bits are cleared and/or irrelevant since the RGB and VSYNC interfaces aren't used.

ILI9341_setMemAccessCtrl()

```
void ILI9341_setMemAccessCtrl (
             bool areRowsFlipped,
             bool areColsFlipped,
             bool areRowsAndColsSwitched,
             bool isVertRefreshFlipped,
             bool isColorOrderFlipped,
             bool isHorRefreshFlipped )
```

Set how data is converted from memory to display.

Parameters

in	*areRowsFlipped*	
in	*areColsFlipped*	
in	*areRowsAndColsSwitched*	
in	*isVertRefreshFlipped*	
in	*isColorOrderFlipped*	
in	*isHorRefreshFlipped*	

This function implements the "Memory Access Control" (`MADCTL`) command from p. 127-128 of the ILI9341

datasheet, which controls how the LCD driver displays data upon writing to memory.

Name	Bit #	Effect when set = 1
MY	7	flip row (AKA "page") addresses
MX	6	flip column addresses
MV	5	exchange rows and column addresses
ML	4	reverse horizontal refresh order
BGR	3	reverse color input order (RGB -> BGR)
MH	2	reverse vertical refresh order

All bits are clear after powering on or `HWRESET`.

ILI9341_setPartialArea()

```
void ILI9341_setPartialArea (
             uint16_t rowStart,
             uint16_t rowEnd )
```

Set the partial display area for partial mode. Call before activating partial mode via ILI9341_setDisplayMode().

Parameters

rowStart	
rowEnd	

ILI9341_setRowAddress()

```
void ILI9341_setRowAddress (
             uint16_t startRow,
             uint16_t endRow )
```

not using backlight, so these aren't necessary

Sets the start/end rows to be written to.

```
Should be called along with `ILI9341_setColAddress()` and
before `ILI9341_writeMemCmd()`.
```

Parameters

startRow	0 <= `startRow` <= `endRow`
endRow	`startRow` <= `endRow` < 320

This function is simply an interface to ILI9341_setAddress(). To work correctly, `start_row` must be no greater than `end_row`, and `end_row` cannot be greater than the max row number (default 320).

ILI9341_setScrollArea()

```
void ILI9341_setScrollArea (
            uint16_t topFixedArea,
            uint16_t vertScrollArea,
            uint16_t bottFixedArea )
```

Set the vertical scrolling area of the display. The sum of the three parameters should be equal to the max number of rows `NUM_ROWS = 320`.

Parameters

topFixedArea	Number of rows fixed at the top of the screen.
vertScrollArea	Number of rows that scroll.
bottFixedArea	Number of rows fixed at the bottom of the screen.

ILI9341_setScrollStart()

```
void ILI9341_setScrollStart (
            uint16_t startRow )
```

Set the start row for vertical scrolling.

Parameters

startRow	Start row for scrolling. Should be >= `topFixedArea - 1`

ILI9341_setSleepMode()

```
void ILI9341_setSleepMode (
            bool isSleeping )
```

Enter or exit sleep mode. The LCD driver is in sleep mode by default upon powering on or either kind of reset.

Parameters

isSleeping	`true` to enter sleep mode, `false` to exit

This function turns sleep mode ON or OFF depending on the value of `is_sleeping`. Either way, the MCU must wait >= 5 [ms] before sending further commands.

It's also necessary to wait 120 [ms] before sending `SPLOUT` after sending `SPLIN` or a reset, so this function waits 120 [ms] regardless of the preceding event.

ILI9341_writeMemCmd()

```
void ILI9341_writeMemCmd (
            void  )
```

Sends the "Write Memory" (RAMWR) command to the LCD driver, signalling that incoming data should be written to memory.

Should be called after setting the row (ILI9341_setRowAddress()) and/or and/or column (ILI9341_setRowAddress()) addresses, but before writing image data (ILI9341_writePixel()).

ILI9341_writePixel()

```
void ILI9341_writePixel (
             uint8_t red,
             uint8_t green,
             uint8_t blue,
             bool is_16bit )
```

Write a single pixel to frame memory.

```
Call 'ILI9341_writeMemCmd()' before this one.
```

Parameters

red	5 or 6-bit R value
green	5 or 6-bit G value
blue	5 or 6-bit B value
is_16bit	true for 16-bit (65K colors, 2 transfers) color depth, false for 18-bit (262K colors, 3 transfer) color depth NOTE: set color depth via ILI9341_setColorDepth()

This function sends one pixel to the display. Because the serial interface (SPI) is used, each pixel requires 2 transfers in 16-bit mode and 3 transfers in 18-bit mode.

The following table (adapted from p. 63 of the datasheet) visualizes how the RGB data is sent to the display when using 16-bit color depth.

Transfer	1								2							
Bit #	7	6	5	4	3	2	1	0	7	6	5	4	3	2	1	0
Value	R4	R3	R2	R1	R0	G5	G4	G3	G2	G1	G0	B4	B3	B2	B1	B0

The following table (adapted from p. 64 of the datasheet) visualizes how the RGB data is sent to the display when using 18-bit color depth.

Transfer	1								2		
Bit #	7	6	5	4	3	2	1	0	7	6	...
Value	R5	R4	R3	R2	R1	R0	0/1	0/1	G5	G4	...

5.2.3 LED

Collaboration diagram for LED:



Files

- file Led.c

  Source code for LED module.
- file Led.h

  Interface for LED module.

Data Structures

- struct Led_t

Macros

- #define **LED_POOL_SIZE** 3

Functions

- Led_t * Led_Init (GPIO_Port_t *gpioPort, GPIO_Pin_t pin)

  Initialize a light-emitting diode (LED) as an `Led_t`.
- GPIO_Port_t * Led_GetPort (Led_t *led)

  Get the GPIO port associated with the LED.
- GPIO_Pin_t Led_GetPin (Led_t *led)

  Get the GPIO pin associated with the LED.
- bool Led_isOn (Led_t *led)

  Check the LED's status.
- void Led_TurnOn (Led_t *led)

  Turn the LED `ON`.
- void Led_TurnOff (Led_t *led)

  Turn the LED `OFF`.
- void Led_Toggle (Led_t *led)

  Toggle the LED (i.e. `OFF` -> `ON` or `ON` -> `OFF`).

5.2.3.1 Detailed Description

Functions for driving light-emitting diodes (LEDs) via GPIO.

5.2.3.2 Function Documentation

Led_GetPin()

```
GPIO_Pin_t Led_GetPin (
            Led_t * led )
```

Get the GPIO pin associated with the LED.

Parameters

in	*led*	Pointer to LED data structure.
out	*GPIO_↩ Pin_t*	GPIO pin associated with the LED.

Led_GetPort()

```
GPIO_Port_t * Led_GetPort (
            Led_t * led )
```

Get the GPIO port associated with the LED.

Parameters

in	*led*	Pointer to LED data structure.
out	*GPIO_Port↩ _t**	Pointer to a GPIO port data structure.

Led_Init()

```
Led_t * Led_Init (
            GPIO_Port_t * gpioPort,
            GPIO_Pin_t pin )
```

Initialize a light-emitting diode (LED) as an `Led_t`.

Parameters

in	*gpioPort*	Pointer to a `struct` representing a GPIO port.
in	*pin*	GPIO pin to use.
out	*Led_t**	Pointer to LED data structure.

Led_isOn()

```
bool Led_isOn (
            Led_t * led )
```

Check the LED's status.

Parameters

in	*led*	Pointer to LED data structure.
out	*true*	the LED is ON.
out	*false*	the LED is OFF.

Led_Toggle()

```
void Led_Toggle (
            Led_t * led )
```

Toggle the LED (i.e. OFF -> ON or ON -> OFF).

Parameters

in	*led*	Pointer to LED data structure.

Led_TurnOff()

```
void Led_TurnOff (
            Led_t * led )
```

Turn the LED OFF.

Parameters

in	*led*	Pointer to LED data structure.

Led_TurnOn()

```
void Led_TurnOn (
            Led_t * led )
```

Turn the LED ON.

Parameters

in	*led*	Pointer to LED data structure.

5.3 Application Software

Application-specific software modules.

Collaboration diagram for Application Software:



Modules

- Data Acquisition (DAQ)
- Debug
- LCD
- QRS

5.3.1 Detailed Description

Application-specific software modules.

These modules contain functions specifically built for this project's purposes.

5.3.2 Data Acquisition (DAQ)

Collaboration diagram for Data Acquisition (DAQ):



Files

- file DAQ.c

  Source code for DAQ module.
- file DAQ.h

  Application software for handling data acquision (DAQ) functions.
- file lookup.c

  Lookup table source code.
- file lookup.h

  Lookup table API.

Macros

- #define **SAMPLING_PERIOD_MS** 5

  sampling period in ms ($T_s = 1/f_s$)
- #define **LOOKUP_ADC_MAX** (float32_t) 5.5
- #define **LOOKUP_ADC_MIN** (float32_t)(-5.5)

Typedefs

- typedef arm_biquad_casd_df1_inst_f32 **filt_t**

Enumerations

- enum {
  NUM_STAGES_LOWPASS = 4 , **NUM_COEFF_LOWPASS** = NUM_STAGES_LOWPASS $*$ 5 , **STATE_↩**
  BUFF_SIZE_LOWPASS = NUM_STAGES_LOWPASS $*$ 4 , **NUM_STAGES_NOTCH** = 6 ,
  NUM_COEFF_NOTCH = NUM_STAGES_NOTCH $*$ 5 , **STATE_BUFF_SIZE_NOTCH** = NUM_STAGES_↩
  NOTCH $*$ 4 }

Functions

- void **DAQ_Init** (void)

  Initialize the data acquisition module, including the input filter and timer interrupt-based analog-to-digital conversion (ADC) @ $f_s = 200[Hz]$.
- float32_t DAQ_Filter (volatile float32_t inputSample)

  Filter an input sample using a 40 [Hz] low pass filter and a 60 [Hz] notch filter.
- const float32_t $*$ Lookup_GetPtr_ADC (void)

  Return a pointer to the ADC lookup table.

5.3.2.1 Detailed Description

Module for managing data acquisition (DAQ) functions.

5.3.2.2 Function Documentation

DAQ_Filter()

```
float32_t DAQ_Filter (
            volatile float32_t inputSample )
```

Filter an input sample using a 40 [Hz] low pass filter and a 60 [Hz] notch filter.

Parameters

in	*inputSample*	Raw input sample in range [−5.5, 5.5) [V].
out	*float32_t*	Filtered output sample.

Lookup_GetPtr_ADC()

```
const float32_t * Lookup_GetPtr_ADC (
            void  )
```

Return a pointer to the ADC lookup table.

Returns

const float32_t∗

5.3.3 Debug

Collaboration diagram for Debug:



Module for debugging functions, including serial output and assertion.

5.3.4 LCD

Collaboration diagram for LCD:



Files

- file LCD.c

  Source code for LCD module.
- file LCD.h

  Module for outputting the ECG waveform and HR to a liquid crystal display (LCD).

Enumerations

- enum { **X_MAX** = NUM_ROWS , **Y_MAX** = NUM_COLS }

Color Setting Functions

- enum {
  LCD_BLACK = 0x00 , **LCD_RED** = 0x04 , **LCD_GREEN** = 0x02 , **LCD_BLUE** = 0x01 ,
  LCD_YELLOW = 0x06 , **LCD_CYAN** = 0x03 , **LCD_PURPLE** = 0x05 , **LCD_WHITE** = 0x07 ,
  LCD_BLACK_INV = LCD_WHITE , **LCD_RED_INV** = LCD_CYAN , **LCD_GREEN_INV** = LCD_PURPLE ,
  LCD_BLUE_INV = LCD_YELLOW ,
  LCD_YELLOW_INV = LCD_BLUE , **LCD_CYAN_INV** = LCD_RED , **LCD_PURPLE_INV** = LCD_GREEN ,
  LCD_WHITE_INV = LCD_BLACK }
- void LCD_setColor (uint8_t R_val, uint8_t G_val, uint8_t B_val)

  Set the current color value for the display. Only the first 5-6 bits of each inputted value are used.
- void LCD_setColor_3bit (uint8_t color_code)

  Set the color value via a 3-bit code.

Init./Config. Functions

- void **LCD_Init** (void)

  Initialize the LCD driver and its internal independencies.
- void **LCD_toggleOutput** (void)

  Toggle display output `ON` or `OFF` (`OFF` by default). Turning output `OFF` prevents the LCD driver from refreshing the display, which can prevent abnormalities like screen tearing while attempting to update the image.
- void **LCD_toggleInversion** (void)

  Toggle color inversion `ON` or `OFF` (`OFF` by default).
- void **LCD_toggleColorDepth** (void)

  Toggle 16-bit or 18-bit color depth (16-bit by default).

Drawing Area Definition Functions

- void LCD_setArea (uint16_t x1_new, uint16_t x2_new, uint16_t y1_new, uint16_t y2_new)

  Set the area of the display to be written to. `0 <= x1 <= x2 < X_MAX 0 <= y1 <= y2 < Y_MAX`
- void LCD_setX (uint16_t x1_new, uint16_t x2_new)

  Set only new x-coordinates to be written to. `0 <= x1 <= x2 < X_MAX`
- void LCD_setY (uint16_t y1_new, uint16_t y2_new)

  Set only new y-coordinates to be written to. `0 <= y1 <= y2 < Y_MAX`

Drawing Functions

- void LCD_Draw (void)

  Draw on the LCD display. Call this function after setting the drawable area via `LCD_setArea()`, or after individually calling `LCD_setX()` and/or `LCD_setY()`.
- void **LCD_Fill** (void)

  Fill the display with a single color.
- void LCD_drawHoriLine (uint16_t yCenter, uint16_t lineWidth)

  Draw a horizontal line across the entire display.
- void LCD_drawVertLine (uint16_t xCenter, uint16_t lineWidth)

  Draw a vertical line across the entire display.
- void LCD_drawRectangle (uint16_t x1, uint16_t dx, uint16_t y1, uint16_t dy, bool isFilled)

  Draw a rectangle of size `dx` x `dy` onto the display. The bottom-left corner will be located at `(x1, y1)`.
- void LCD_graphSample (uint16_t x1, uint16_t dx, uint16_t y1, uint16_t dy, uint16_t y_min, uint16_t y_max, uint16_t color_code)

  Draw a rectangle of size `dx` x `dy` and blank out all other pixels between `y_min` and `y_max`.

5.3.4.1 Detailed Description

Module for displaying graphs on an LCD via the ILI9341 module.

5.3.4.2 Function Documentation

LCD_Draw()

```
void LCD_Draw (
            void  )
```

Draw on the LCD display. Call this function after setting the drawable area via `LCD_setArea()`, or after individually calling `LCD_setX()` and/or `LCD_setY()`.

LCD_drawHoriLine()

```
void LCD_drawHoriLine (
            uint16_t yCenter,
            uint16_t lineWidth )
```

Draw a horizontal line across the entire display.

Parameters

yCenter	y-coordinate to center the line on
lineWidth	width of the line; should be a positive, odd number

LCD_drawRectangle()

```
void LCD_drawRectangle (
            uint16_t x1,
```

```
            uint16_t dx,
            uint16_t y1,
            uint16_t dy,
            bool isFilled )
```

Draw a rectangle of size `dx` x `dy` onto the display. The bottom-left corner will be located at `(x1, y1)`.

Parameters

x1	lowest (left-most) x-coordinate
dx	length (horizontal distance) of the rectangle
y1	lowest (bottom-most) y-coordinate
dy	height (vertical distance) of the rectangle
isFilled	`true` to fill the rectangle, `false` to leave it unfilled

LCD_drawVertLine()

```
void LCD_drawVertLine (
            uint16_t xCenter,
            uint16_t lineWidth )
```

Draw a vertical line across the entire display.

Parameters

xCenter	x-coordinate to center the line on
lineWidth	width of the line; should be a positive, odd number

LCD_graphSample()

```
void LCD_graphSample (
            uint16_t x1,
            uint16_t dx,
            uint16_t y1,
            uint16_t dy,
            uint16_t y_min,
            uint16_t y_max,
            uint16_t color_code )
```

Draw a rectangle of size `dx` x `dy` and blank out all other pixels between `y_min` and `y_max`.

Parameters

x1	lowest (left-most) x-coordinate
dx	length (horizontal distance) of the column
y1	y-coordinate of the pixel's bottom side
dy	height (vertical distance) of the pixel
y_min	lowest (bottom-most) y-coordinate
y_max	highest (top-most) y-coordinate
color_code	3-bit color code

TODO: Write description

LCD_setArea()

```
void LCD_setArea (
            uint16_t x1_new,
            uint16_t x2_new,
            uint16_t y1_new,
            uint16_t y2_new )
```

Set the area of the display to be written to. `0 <= x1 <= x2 < X_MAX` `0 <= y1 <= y2 < Y_MAX`

Parameters

x1_new	left-most x-coordinate
x2_new	right-most x-coordinate
y1_new	lowest y-coordinate
y2_new	highest y-coordinate

LCD_setColor()

```
void LCD_setColor (
            uint8_t R_val,
            uint8_t G_val,
            uint8_t B_val )
```

Set the current color value for the display. Only the first 5-6 bits of each inputted value are used.

Parameters

R_val	5-bit (`[0-31]`) R value; 6-bit (`[0-63]`) if color depth is 18-bit
G_val	6-bit (`[0-63]`) G value
B_val	5-bit (`[0-31]`) B value; 6-bit (`[0-63]`) if color depth is 18-bit

LCD_setColor_3bit()

```
void LCD_setColor_3bit (
            uint8_t color_code )
```

Set the color value via a 3-bit code.

Parameters

color_code	3-bit color value to use. Bits 2, 1, 0 correspond to R, G, and B values, respectively.

This is simply a convenience function for setting the color using the enum values defined in the header file. The ones with the `_INV` suffix should be used when the display colors are inverted.

hex	binary	macro
0x00	000	LCD_BLACK
0x01	001	LCD_BLUE
0x02	010	LCD_GREEN
0x03	011	LCD_CYAN
0x04	100	LCD_RED
0x05	101	LCD_PURPLE
0x06	110	LCD_YELLOW
0x07	111	LCD_WHITE

LCD_setX()

```
void LCD_setX (
            uint16_t x1_new,
            uint16_t x2_new )
```

Set only new x-coordinates to be written to. `0 <= x1 <= x2 < X_MAX`

Parameters

x1_new	left-most x-coordinate
x2_new	right-most x-coordinate

LCD_setY()

```
void LCD_setY (
            uint16_t y1_new,
            uint16_t y2_new )
```

Set only new y-coordinates to be written to. `0 <= y1 <= y2 < Y_MAX`

Parameters

y1_new	lowest y-coordinate
y2_new	highest y-coordinate

5.3.5 QRS

Collaboration diagram for QRS:



Module for analyzing ECG data to determine heart rate.

5.4 Common

Collaboration diagram for Common:



Modules

- FIFO
- NewAssert

Files

- file NewAssert.c

  Source code for custom `assert` implementation.
- file NewAssert.h

  Header file for custom `assert` implementation.

Functions

- void Assert (bool condition)

  Custom `assert` implementation that is more lightweight than the one from `newlib`.

5.4.1 Detailed Description

Modules that are used by multiple layers and/or don't fit into any one layer.

5.4.2 Function Documentation

Assert()

```
void Assert (
            bool condition )
```

Custom `assert` implementation that is more lightweight than the one from `newlib`.

Parameters

`in`	*condition*	Conditional to test. Causes an infinite loop if `false`.

5.4.3 FIFO

Collaboration diagram for FIFO:



Files

- file FIFO.c

  Source code for FIFO buffer module.
- file FIFO.h

  FIFO buffer data structure.

Data Structures

- struct FIFO_t

Macros

- #define **FIFO_POOL_SIZE** 5

Functions

- volatile FIFO_t * FIFO_Init (volatile uint32_t buffer[ ], const uint32_t N)
  Initialize a FIFO buffer of length N.

Basic Operations

- void FIFO_Put (volatile FIFO_t *fifo, const uint32_t val)
  Add a value to the end of the buffer.
- uint32_t FIFO_Get (volatile FIFO_t *fifo)
  Remove the first value of the buffer.
- void FIFO_TransferOne (volatile FIFO_t *srcFifo, volatile FIFO_t *destFifo)
  Transfer a value from one FIFO buffer to another.

Bulk Removal

- void FIFO_Flush (volatile FIFO_t *fifo, uint32_t outputBuffer[ ])
  Empty the FIFO buffer's contents into an array.
- void FIFO_Reset (volatile FIFO_t *fifo)
  Reset the FIFO buffer.
- void FIFO_TransferAll (volatile FIFO_t *srcFifo, volatile FIFO_t *destFifo)
  Transfer the contents of one FIFO buffer to another.

Peeking

- uint32_t FIFO_PeekOne (volatile FIFO_t *fifo)
  See the first element in the FIFO without removing it.
- void FIFO_PeekAll (volatile FIFO_t *fifo, uint32_t outputBuffer[ ])
  See the FIFO buffer's contents without removing them.

Status Checks

- bool FIFO_isFull (volatile FIFO_t *fifo)
  Check if the FIFO buffer is full.
- bool FIFO_isEmpty (volatile FIFO_t *fifo)
  Check if the FIFO buffer is empty.
- uint32_t FIFO_getCurrSize (volatile FIFO_t *fifo)
  Get the current size of the FIFO buffer.

5.4.3.1 Detailed Description

Module for using the "first-in first-out (FIFO) buffer" data structure.

5.4.3.2 Function Documentation

FIFO_Flush()

```
void FIFO_Flush (
            volatile FIFO_t * fifo,
            uint32_t outputBuffer[] )
```

Empty the FIFO buffer's contents into an array.

Parameters

fifo	Pointer to source FIFO buffer.
outputBuffer	Array to output values to. Should be the same length as the FIFO buffer.

FIFO_Get()

```
uint32_t FIFO_Get (
            volatile FIFO_t * fifo )
```

Remove the first value of the buffer.

Parameters

fifo	Pointer to FIFO object

Returns

First sample in the FIFO.

FIFO_getCurrSize()

```
uint32_t FIFO_getCurrSize (
            volatile FIFO_t * fifo )
```

Get the current size of the FIFO buffer.

Parameters

fifo	Pointer to the FIFO buffer.

FIFO_Init()

```
volatile FIFO_t * FIFO_Init (
            volatile uint32_t buffer[],
            const uint32_t N )
```

Initialize a FIFO buffer of length `N`.

Parameters

buffer	Array of size `N` to be used as FIFO buffer
N	Length of `buffer`. Usable length is `N - 1`.

Returns

pointer to the FIFO buffer

TODO: Add details

FIFO_isEmpty()

```
bool FIFO_isEmpty (
            volatile FIFO_t * fifo )
```

Check if the FIFO buffer is empty.

Parameters

fifo	Pointer to the FIFO buffer.

Return values

true	The buffer is empty.
false	The buffer is not empty.

FIFO_isFull()

```
bool FIFO_isFull (
            volatile FIFO_t * fifo )
```

Check if the FIFO buffer is full.

Parameters

fifo	Pointer to the FIFO buffer.

Return values

true	The buffer is full.
false	The buffer is not full.

FIFO_PeekAll()

```
void FIFO_PeekAll (
            volatile FIFO_t * fifo,
            uint32_t outputBuffer[] )
```

See the FIFO buffer's contents without removing them.

Parameters

fifo	Pointer to FIFO object
outputBuffer	Array to output values to. Should be the same length as the FIFO buffer.

FIFO_PeekOne()

```
uint32_t FIFO_PeekOne (
             volatile FIFO_t * fifo )
```

See the first element in the FIFO without removing it.

Parameters

fifo	Pointer to FIFO object

Returns

First sample in the FIFO.

FIFO_Put()

```
void FIFO_Put (
             volatile FIFO_t * fifo,
             const uint32_t val )
```

Add a value to the end of the buffer.

Parameters

fifo	Pointer to FIFO object
val	last value in the buffer

FIFO_Reset()

```
void FIFO_Reset (
             volatile FIFO_t * fifo )
```

Reset the FIFO buffer.

Parameters

in	*fifo*	Pointer to FIFO buffer.

FIFO_TransferAll()

```
void FIFO_TransferAll (
            volatile FIFO_t * srcFifo,
            volatile FIFO_t * destFifo )
```

Transfer the contents of one FIFO buffer to another.

Parameters

srcFifo	Pointer to source FIFO buffer.
destFifo	Pointer to destination FIFO buffer.

FIFO_TransferOne()

```
void FIFO_TransferOne (
            volatile FIFO_t * srcFifo,
            volatile FIFO_t * destFifo )
```

Transfer a value from one FIFO buffer to another.

Parameters

srcFifo	Pointer to source FIFO buffer.
destFifo	Pointer to destination FIFO buffer.

5.4.4 NewAssert

Collaboration diagram for NewAssert:

Module for using a custom `assert` implementation.

6 Data Structure Documentation

6.1 FIFO_t Struct Reference

Data Fields

- volatile uint32_t * **buffer**

(pointer to) array to use as FIFO buffer

- volatile uint32_t **N**

  length of `buffer`

- volatile uint32_t **front_idx**

  idx of front of FIFO

- volatile uint32_t **back_idx**

  idx of back of FIFO

The documentation for this struct was generated from the following file:

- FIFO.c

6.2 GPIO_Port_t Struct Reference

Data Fields

- const uint32_t **BASE_ADDRESS**
- const uint32_t **DATA_REGISTER**
- bool **isInit**

The documentation for this struct was generated from the following file:

- GPIO.c

6.3 Led_t Struct Reference

Data Fields

- GPIO_Port_t * **GPIO_PORT_PTR**

  pointer to GPIO port data structure

- GPIO_Pin_t **GPIO_PIN**

  GPIO pin number.

- bool **is_ON**

  state indicator

The documentation for this struct was generated from the following file:

- Led.c

7 File Documentation

7.1 DAQ.c File Reference

Source code for DAQ module.

```
#include "DAQ.h"
#include "ADC.h"
#include "Timer.h"
#include "FIFO.h"
#include "NewAssert.h"
#include "arm_math_types.h"
#include "dsp/filtering_functions.h"
#include "lookup.h"
#include "tm4c123gh6pm.h"
#include <math.h>
#include <stdbool.h>
#include <stdint.h>
```

Macros

- #define **SAMPLING_PERIOD_MS** 5

  sampling period in ms ($T_s = 1/f_s$)

Typedefs

- typedef arm_biquad_casd_df1_inst_f32 **filt_t**

Enumerations

- enum {
  NUM_STAGES_LOWPASS = 4 , **NUM_COEFF_LOWPASS** = NUM_STAGES_LOWPASS $*$ 5 , **STATE_↩**
  BUFF_SIZE_LOWPASS = NUM_STAGES_LOWPASS $*$ 4 , **NUM_STAGES_NOTCH** = 6 ,
  NUM_COEFF_NOTCH = NUM_STAGES_NOTCH $*$ 5 , **STATE_BUFF_SIZE_NOTCH** = NUM_STAGES_↩
  NOTCH $*$ 4 }

Functions

- void **DAQ_Init** (void)

  Initialize the data acquisition module, including the input filter and timer interrupt-based analog-to-digital conversion (ADC) @ $f_s = 200[Hz]$.
- float32_t DAQ_Filter (volatile float32_t inputSample)

  Filter an input sample using a 40 [Hz] low pass filter and a 60 [Hz] notch filter.

7.1.1 Detailed Description

Source code for DAQ module.

Author

Bryan McElvy

7.2 DAQ.h File Reference

Application software for handling data acquision (DAQ) functions.

```
#include "ADC.h"
#include "Timer.h"
#include "FIFO.h"
#include "arm_math_types.h"
#include "dsp/filtering_functions.h"
#include "tm4c123gh6pm.h"
#include <stdint.h>
```

Functions

- void **DAQ_Init** (void)

  Initialize the data acquisition module, including the input filter and timer interrupt-based analog-to-digital conversion (ADC) @ $f_s = 200[Hz]$.
- float32_t DAQ_Filter (volatile float32_t inputSample)

  Filter an input sample using a 40 [Hz] low pass filter and a 60 [Hz] notch filter.

7.2.1 Detailed Description

Application software for handling data acquision (DAQ) functions.

Author

Bryan McElvy

7.3 Debug.h File Reference

Functions to output debugging information to a serial port via UART.

```
#include "UART.h"
#include "NewAssert.h"
#include "tm4c123gh6pm.h"
#include <stdbool.h>
#include <stdint.h>
```

Enumerations

- enum **msg_t** {
  START_MSG , **DAQ_INIT** , **QRS_INIT** , **LCD_INIT** ,
  ASSERT_FALSE }

Functions

- void **Debug_Init** (void)

  Init. the Debug module and send a start message to the port.
- void Debug_SendMsg (void *message)

  Send a message to the serial port.
- void Debug_SendFromList (msg_t msg)

  Send a message from the message list.
- void Debug_WriteFloat (double value)

  Write a floating-point value to the serial port.
- void Debug_Assert (bool condition)

  Stops program if `condition` is `true`. Useful for bug detection during debugging.

7.3.1 Detailed Description

Functions to output debugging information to a serial port via UART.

Author

Bryan McElvy

7.3.2 Function Documentation

Debug_Assert()

```
void Debug_Assert (
            bool condition )
```

Stops program if `condition` is `true`. Useful for bug detection during debugging.

Parameters

condition	

Debug_SendFromList()

```
void Debug_SendFromList (
            msg_t msg )
```

Send a message from the message list.

Parameters

in	*msg*	Message to send.

Debug_SendMsg()

```
void Debug_SendMsg (
            void * message )
```

Send a message to the serial port.

Parameters

message	(Pointer to) array of ASCII characters.

Debug_WriteFloat()

```
void Debug_WriteFloat (
            double value )
```

Write a floating-point value to the serial port.

Parameters

in	*value*	Floating-point value.

7.4 LCD.c File Reference

Source code for LCD module.

```
#include "LCD.h"
#include "ILI9341.h"
#include "SPI.h"
#include "Timer.h"
#include "NewAssert.h"
#include "tm4c123gh6pm.h"
#include <stdbool.h>
#include <stdint.h>
```

Functions

Init./Config. Functions

- void **LCD_Init** (void)

  Initialize the LCD driver and its internal independencies.
- void **LCD_toggleOutput** (void)

  Toggle display output `ON` or `OFF` (`OFF` by default). Turning output `OFF` prevents the LCD driver from refreshing the display, which can prevent abnormalities like screen tearing while attempting to update the image.
- void **LCD_toggleInversion** (void)

  Toggle color inversion `ON` or `OFF` (`OFF` by default).
- void **LCD_toggleColorDepth** (void)

  Toggle 16-bit or 18-bit color depth (16-bit by default).

Drawing Area Definition Functions

- void LCD_setArea (uint16_t x1_new, uint16_t x2_new, uint16_t y1_new, uint16_t y2_new)
  Set the area of the display to be written to. `0 <= x1 <= x2 < X_MAX 0 <= y1 <= y2 < Y_MAX`
- void LCD_setX (uint16_t x1_new, uint16_t x2_new)
  Set only new x-coordinates to be written to. `0 <= x1 <= x2 < X_MAX`
- void LCD_setY (uint16_t y1_new, uint16_t y2_new)
  Set only new y-coordinates to be written to. `0 <= y1 <= y2 < Y_MAX`

Color Setting Functions

- void LCD_setColor (uint8_t R_val, uint8_t G_val, uint8_t B_val)
  Set the current color value for the display. Only the first 5-6 bits of each inputted value are used.
- void LCD_setColor_3bit (uint8_t color_code)
  Set the color value via a 3-bit code.

Drawing Functions

- void LCD_Draw (void)
  Draw on the LCD display. Call this function after setting the drawable area via `LCD_setArea()`, or after individually calling `LCD_setX()` and/or `LCD_setY()`.
- void **LCD_Fill** (void)
  Fill the display with a single color.
- void LCD_drawHoriLine (uint16_t yCenter, uint16_t lineWidth)
  Draw a horizontal line across the entire display.
- void LCD_drawVertLine (uint16_t xCenter, uint16_t lineWidth)
  Draw a vertical line across the entire display.
- void LCD_drawRectangle (uint16_t x1, uint16_t dx, uint16_t y1, uint16_t dy, bool isFilled)
  Draw a rectangle of size `dx` x `dy` onto the display. The bottom-left corner will be located at `(x1, y1)`.
- void LCD_graphSample (uint16_t x1, uint16_t dx, uint16_t y1, uint16_t dy, uint16_t y_min, uint16_t y_max, uint16_t color_code)
  Draw a rectangle of size `dx` x `dy` and blank out all other pixels between `y_min` and `y_max`.

7.4.1 Detailed Description

Source code for LCD module.

Author

Bryan McElvy

7.5 LCD.h File Reference

Module for outputting the ECG waveform and HR to a liquid crystal display (LCD).

```
#include "ILI9341.h"
#include "SPI.h"
#include "Timer.h"
#include "NewAssert.h"
#include "tm4c123gh6pm.h"
#include <stdbool.h>
#include <stdint.h>
```

Enumerations

- enum { **X_MAX** = NUM_ROWS , **Y_MAX** = NUM_COLS }

Functions

Init./Config. Functions

- void **LCD_Init** (void)
  Initialize the LCD driver and its internal independencies.
- void **LCD_toggleOutput** (void)
  Toggle display output `ON` or `OFF` (`OFF` by default). Turning output `OFF` prevents the LCD driver from refreshing the display, which can prevent abnormalities like screen tearing while attempting to update the image.
- void **LCD_toggleInversion** (void)
  Toggle color inversion `ON` or `OFF` (`OFF` by default).
- void **LCD_toggleColorDepth** (void)
  Toggle 16-bit or 18-bit color depth (16-bit by default).

Drawing Area Definition Functions

- void LCD_setArea (uint16_t x1_new, uint16_t x2_new, uint16_t y1_new, uint16_t y2_new)
  Set the area of the display to be written to. `0 <= x1 <= x2 < X_MAX 0 <= y1 <= y2 < Y_MAX`
- void LCD_setX (uint16_t x1_new, uint16_t x2_new)
  Set only new x-coordinates to be written to. `0 <= x1 <= x2 < X_MAX`
- void LCD_setY (uint16_t y1_new, uint16_t y2_new)
  Set only new y-coordinates to be written to. `0 <= y1 <= y2 < Y_MAX`

Drawing Functions

- void LCD_Draw (void)
  Draw on the LCD display. Call this function after setting the drawable area via `LCD_setArea()`, or after individually calling `LCD_setX()` and/or `LCD_setY()`.
- void **LCD_Fill** (void)
  Fill the display with a single color.
- void LCD_drawHoriLine (uint16_t yCenter, uint16_t lineWidth)
  Draw a horizontal line across the entire display.
- void LCD_drawVertLine (uint16_t xCenter, uint16_t lineWidth)
  Draw a vertical line across the entire display.
- void LCD_drawRectangle (uint16_t x1, uint16_t dx, uint16_t y1, uint16_t dy, bool isFilled)
  Draw a rectangle of size `dx` x `dy` onto the display. The bottom-left corner will be located at `(x1, y1)`.
- void LCD_graphSample (uint16_t x1, uint16_t dx, uint16_t y1, uint16_t dy, uint16_t y_min, uint16_t y_max, uint16_t color_code)
  Draw a rectangle of size `dx` x `dy` and blank out all other pixels between `y_min` and `y_max`.

Color Setting Functions

- enum {
  LCD_BLACK = 0x00 , **LCD_RED** = 0x04 , **LCD_GREEN** = 0x02 , **LCD_BLUE** = 0x01 ,
  LCD_YELLOW = 0x06 , **LCD_CYAN** = 0x03 , **LCD_PURPLE** = 0x05 , **LCD_WHITE** = 0x07 ,
  LCD_BLACK_INV = LCD_WHITE , **LCD_RED_INV** = LCD_CYAN , **LCD_GREEN_INV** = LCD_PURPLE ,
  LCD_BLUE_INV = LCD_YELLOW ,
  LCD_YELLOW_INV = LCD_BLUE , **LCD_CYAN_INV** = LCD_RED , **LCD_PURPLE_INV** = LCD_GREEN ,
  LCD_WHITE_INV = LCD_BLACK }
- void LCD_setColor (uint8_t R_val, uint8_t G_val, uint8_t B_val)
  Set the current color value for the display. Only the first 5-6 bits of each inputted value are used.
- void LCD_setColor_3bit (uint8_t color_code)
  Set the color value via a 3-bit code.

7.5.1 Detailed Description

Module for outputting the ECG waveform and HR to a liquid crystal display (LCD).

Author

Bryan McElvy

7.6 QRS.h File Reference

QRS detection algorithm functions.

```
#include "dsp/filtering_functions_f16.h"
```

7.6.1 Detailed Description

QRS detection algorithm functions.

Author

Bryan McElvy

This module contains functions for detecting heart rate (HR) using a simplified version of the Pan-Tompkins algorithm.

7.7 UserCtrl.h File Reference

Interface for user control module.

```
#include "GPIO.h"
#include "Timer.h"
```

Functions

- void **UserCtrl_Init** ()
  Initializes the UserCtrl module and its dependencies (Timer0B and GPIO_PortF)

7.7.1 Detailed Description

Interface for user control module.

Author

Bryan McElvy

7.8 FIFO.c File Reference

Source code for FIFO buffer module.

```
#include "FIFO.h"
#include "NewAssert.h"
#include <stdint.h>
#include <stdbool.h>
```

Data Structures

- struct FIFO_t

Functions

- volatile FIFO_t * FIFO_Init (volatile uint32_t buffer[ ], const uint32_t N)

  Initialize a FIFO buffer of length N.

Basic Operations

- void FIFO_Put (volatile FIFO_t *fifo, const uint32_t val)

  Add a value to the end of the buffer.
- uint32_t FIFO_Get (volatile FIFO_t *fifo)

  Remove the first value of the buffer.
- void FIFO_TransferOne (volatile FIFO_t *srcFifo, volatile FIFO_t *destFifo)

  Transfer a value from one FIFO buffer to another.

Bulk Removal

- void FIFO_Flush (volatile FIFO_t *fifo, uint32_t outputBuffer[ ])

  Empty the FIFO buffer's contents into an array.
- void FIFO_Reset (volatile FIFO_t *fifo)

  Reset the FIFO buffer.
- void FIFO_TransferAll (volatile FIFO_t *srcFifo, volatile FIFO_t *destFifo)

  Transfer the contents of one FIFO buffer to another.

Peeking

- uint32_t FIFO_PeekOne (volatile FIFO_t *fifo)

  See the first element in the FIFO without removing it.
- void FIFO_PeekAll (volatile FIFO_t *fifo, uint32_t outputBuffer[ ])

  See the FIFO buffer's contents without removing them.

Status Checks

- bool FIFO_isFull (volatile FIFO_t *fifo)

  Check if the FIFO buffer is full.
- bool FIFO_isEmpty (volatile FIFO_t *fifo)

  Check if the FIFO buffer is empty.
- uint32_t FIFO_getCurrSize (volatile FIFO_t *fifo)

  Get the current size of the FIFO buffer.

7.8.1 Detailed Description

Source code for FIFO buffer module.

Author

Bryan McElvy

7.9 FIFO.h File Reference

FIFO buffer data structure.

```
#include "NewAssert.h"
#include <stdbool.h>
#include <stdint.h>
```

Macros

- #define **FIFO_POOL_SIZE** 5

Functions

- volatile FIFO_t * FIFO_Init (volatile uint32_t buffer[ ], const uint32_t N)
  Initialize a FIFO buffer of length N.

Basic Operations

- void FIFO_Put (volatile FIFO_t *fifo, const uint32_t val)
  Add a value to the end of the buffer.
- uint32_t FIFO_Get (volatile FIFO_t *fifo)
  Remove the first value of the buffer.
- void FIFO_TransferOne (volatile FIFO_t *srcFifo, volatile FIFO_t *destFifo)
  Transfer a value from one FIFO buffer to another.

Bulk Removal

- void FIFO_Flush (volatile FIFO_t *fifo, uint32_t outputBuffer[ ])
  Empty the FIFO buffer's contents into an array.
- void FIFO_Reset (volatile FIFO_t *fifo)
  Reset the FIFO buffer.
- void FIFO_TransferAll (volatile FIFO_t *srcFifo, volatile FIFO_t *destFifo)
  Transfer the contents of one FIFO buffer to another.

Peeking

- uint32_t FIFO_PeekOne (volatile FIFO_t *fifo)
  See the first element in the FIFO without removing it.
- void FIFO_PeekAll (volatile FIFO_t *fifo, uint32_t outputBuffer[ ])
  See the FIFO buffer's contents without removing them.

Status Checks

- bool FIFO_isFull (volatile FIFO_t *fifo)
  Check if the FIFO buffer is full.
- bool FIFO_isEmpty (volatile FIFO_t *fifo)
  Check if the FIFO buffer is empty.
- uint32_t FIFO_getCurrSize (volatile FIFO_t *fifo)
  Get the current size of the FIFO buffer.

7.9.1 Detailed Description

FIFO buffer data structure.

Author

Bryan McElvy

7.10 lookup.c File Reference

Lookup table source code.

```
#include "lookup.h"
#include "arm_math_types.h"
```

Functions

- const float32_t * Lookup_GetPtr_ADC (void)
  Return a pointer to the ADC lookup table.

7.10.1 Detailed Description

Lookup table source code.

Author

Bryan McElvy

7.11 lookup.h File Reference

Lookup table API.

```
#include "arm_math_types.h"
```

Macros

- #define **LOOKUP_ADC_MAX** (float32_t) 5.5
- #define **LOOKUP_ADC_MIN** (float32_t)(-5.5)

Functions

- const float32_t * Lookup_GetPtr_ADC (void)
  Return a pointer to the ADC lookup table.

7.11.1 Detailed Description

Lookup table API.

Author

Bryan McElvy

7.12 NewAssert.c File Reference

Source code for custom `assert` implementation.

```
#include "NewAssert.h"
#include <stdbool.h>
```

Functions

- void Assert (bool condition)

  Custom `assert` implementation that is more lightweight than the one from `newlib`.

7.12.1 Detailed Description

Source code for custom `assert` implementation.

Author

Bryan McElvy

7.13 NewAssert.h File Reference

Header file for custom `assert` implementation.

```
#include <stdbool.h>
```

Functions

- void Assert (bool condition)

  Custom `assert` implementation that is more lightweight than the one from `newlib`.

7.13.1 Detailed Description

Header file for custom `assert` implementation.

Author

Bryan McElvy

7.14 ADC.c File Reference

Source code for ADC module.

```
#include "ADC.h"
#include "GPIO.h"
#include "Timer.h"
#include "lookup.h"
#include "arm_math_types.h"
#include "tm4c123gh6pm.h"
#include <stdint.h>
```

Functions

- void **ADC_Init** (void)

  Initialize ADC0 as a single-input analog-to-digital converter.
- void **ADC_InterruptEnable** (void)

  Enable the ADC interrupt.
- void **ADC_InterruptDisable** (void)

  Disable the ADC interrupt.
- float32_t ADC_ConvertToVolts (uint16_t raw_sample)

  Convert a raw ADC sample to voltage in [mV].

7.14.1 Detailed Description

Source code for ADC module.

Author

Bryan McElvy

7.15 ADC.h File Reference

Driver module for analog-to-digital conversion (ADC).

```
#include "GPIO.h"
#include "Timer.h"
#include "lookup.h"
#include "arm_math_types.h"
#include "tm4c123gh6pm.h"
#include <stdint.h>
```

Functions

- void **ADC_Init** (void)

  Initialize ADC0 as a single-input analog-to-digital converter.
- void **ADC_InterruptEnable** (void)

  Enable the ADC interrupt.
- void **ADC_InterruptDisable** (void)

  Disable the ADC interrupt.
- float32_t ADC_ConvertToVolts (uint16_t raw_sample)

  Convert a raw ADC sample to voltage in [mV].

7.15.1 Detailed Description

Driver module for analog-to-digital conversion (ADC).

Author

Bryan McElvy

7.16 GPIO.c File Reference

Source code for GPIO module.

```
#include "GPIO.h"
#include <NewAssert.h>
#include "tm4c123gh6pm.h"
#include <stdbool.h>
#include <stdint.h>
```

Data Structures

- struct GPIO_Port_t

Macros

- #define **GPIO_NUM_PORTS** 6

Typedefs

- typedef volatile uint32_t * **register_t**

Enumerations

- enum {
  GPIO_PORTA_BASE_ADDRESS = (uint32_t) 0x40004000 , **GPIO_PORTB_BASE_ADDRESS** = (uint32↩
  _t) 0x40005000 , **GPIO_PORTC_BASE_ADDRESS** = (uint32_t) 0x40006000 , **GPIO_PORTD_BASE_↩**
  ADDRESS = (uint32_t) 0x40007000 ,
  GPIO_PORTE_BASE_ADDRESS = (uint32_t) 0x40024000 , **GPIO_PORTF_BASE_ADDRESS** = (uint32_t)
  0x40025000 }
- enum {
  GPIO_DATA_R_OFFSET = (uint32_t) 0x03FC , **GPIO_DIR_R_OFFSET** = (uint32_t) 0x0400 , **GPIO_IS_R↩**
  _OFFSET = (uint32_t) 0x0404 , **GPIO_IBE_R_OFFSET** = (uint32_t) 0x0408 ,
  GPIO_IEV_R_OFFSET = (uint32_t) 0x040C , **GPIO_IM_R_OFFSET** = (uint32_t) 0x0410 , **GPIO_ICR_R_↩**
  OFFSET = (uint32_t) 0x041C , **GPIO_AFSEL_R_OFFSET** = (uint32_t) 0x0420 ,
  GPIO_DR2R_R_OFFSET = (uint32_t) 0x0500 , **GPIO_DR4R_R_OFFSET** = (uint32_t) 0x0504 , **GPIO_↩**
  DR8R_R_OFFSET = (uint32_t) 0x0508 , **GPIO_PUR_R_OFFSET** = (uint32_t) 0x0510 ,
  GPIO_PDR_R_OFFSET = (uint32_t) 0x0518 , **GPIO_DEN_R_OFFSET** = (uint32_t) 0x051C , **GPIO_↩**
  LOCK_R_OFFSET = (uint32_t) 0x0520 , **GPIO_COMMIT_R_OFFSET** = (uint32_t) 0x0524 ,
  GPIO_AMSEL_R_OFFSET = (uint32_t) 0x0528 , **GPIO_PCTL_R_OFFSET** = (uint32_t) 0x052C }

Functions

- GPIO_Port_t * GPIO_InitPort (GPIO_PortName_t portName)

  Initialize a GPIO Port and return a pointer to its `struct`.
- bool GPIO_isPortInit (GPIO_Port_t *gpioPort)

  Check if the GPIO port is initialized.
- void GPIO_ConfigDirOutput (GPIO_Port_t *gpioPort, GPIO_Pin_t pinMask)

  Configure the direction of the specified GPIO pins. All pins are configured to `INPUT` by default, so this function should only be called to specify `OUTPUT` pins.
- void GPIO_ConfigDirInput (GPIO_Port_t *gpioPort, GPIO_Pin_t pinMask)

  Configure the specified GPIO pins as `INPUT` pins. All pins are configured to `INPUT` by default, so this function is technically unnecessary, but useful for code readability.
- void GPIO_ConfigPullUp (GPIO_Port_t *gpioPort, GPIO_Pin_t pinMask)

  Activate the specified pins' internal pull-up resistors.
- void GPIO_ConfigPullDown (GPIO_Port_t *gpioPort, GPIO_Pin_t pinMask)

  Activate the specified pins' internal pull-down resistors.
- void GPIO_ConfigDriveStrength (GPIO_Port_t *gpioPort, GPIO_Pin_t pinMask, uint8_t drive_mA)

  Configure the specified pins' drive strength. Pins are initialized with 2[mA] drive strength, so this is only needed for a drive strength of 4[mA] or 8[mA].
- void GPIO_EnableDigital (GPIO_Port_t *gpioPort, GPIO_Pin_t pinMask)

  Enable digital I/O for the specified pins.
- void GPIO_DisableDigital (GPIO_Port_t *gpioPort, GPIO_Pin_t pinMask)

  Disable digital I/O for the specified pins.
- void GPIO_ConfigInterrupts_Edge (GPIO_Port_t *gpioPort, GPIO_Pin_t pinMask, bool risingEdge)

  Configure the specified GPIO pins to trigger an interrupt on the rising or falling edge of an input.
- void GPIO_ConfigInterrupts_BothEdges (GPIO_Port_t *gpioPort, GPIO_Pin_t pinMask)

  Configure the specified GPIO pins to trigger an interrupt on both edges of an input.
- void GPIO_ConfigInterrupts_LevelTrig (GPIO_Port_t *gpioPort, GPIO_Pin_t pinMask, bool highLevel)

  Configure the specified GPIO pins to trigger an interrupt on a high level or low level pulse.
- void GPIO_ConfigNVIC (GPIO_Port_t *gpioPort, uint8_t priority)

  Configure interrupts for the selected port in the NVIC.
- uint8_t GPIO_ReadPins (GPIO_Port_t *gpioPort, GPIO_Pin_t pinMask)

  Read from the specified GPIO pin.
- void GPIO_WriteHigh (GPIO_Port_t *gpioPort, GPIO_Pin_t pinMask)

  Write a `1` to the specified GPIO pins.
- void GPIO_WriteLow (GPIO_Port_t *gpioPort, GPIO_Pin_t pinMask)

  Write a `0` to the specified GPIO pins.
- void GPIO_Toggle (GPIO_Port_t *gpioPort, GPIO_Pin_t pinMask)

  Toggle the specified GPIO pins.
- void GPIO_ConfigAltMode (GPIO_Port_t *gpioPort, GPIO_Pin_t pinMask)

  Activate the alternate mode for the specified pins.
- void GPIO_ConfigPortCtrl (GPIO_Port_t *gpioPort, GPIO_Pin_t pinMask, uint8_t fieldEncoding)

  Specify the alternate mode to use for the specified pins.
- void GPIO_ConfigAnalog (GPIO_Port_t *gpioPort, GPIO_Pin_t pinMask)

  Activate analog mode for the specified GPIO pins.

7.16.1 Detailed Description

Source code for GPIO module.

Author

Bryan McElvy

7.16.2 Function Documentation

GPIO_ConfigAltMode()

```
void GPIO_ConfigAltMode (
            GPIO_Port_t * gpioPort,
            GPIO_Pin_t pinMask )
```

Activate the alternate mode for the specified pins.

Parameters

in	*gpioPort*	Pointer to the specified GPIO port.
in	*pinMask*	Bit mask corresponding to the intended pin(s).

GPIO_ConfigAnalog()

```
void GPIO_ConfigAnalog (
            GPIO_Port_t * gpioPort,
            GPIO_Pin_t pinMask )
```

Activate analog mode for the specified GPIO pins.

Parameters

in	*gpioPort*	Pointer to the specified GPIO port.
in	*pinMask*	Bit mask corresponding to the intended pin(s).

GPIO_ConfigDirInput()

```
void GPIO_ConfigDirInput (
            GPIO_Port_t * gpioPort,
            GPIO_Pin_t pinMask )
```

Configure the specified GPIO pins as `INPUT` pins. All pins are configured to `INPUT` by default, so this function is technically unnecessary, but useful for code readability.

Parameters

in	*gpioPort*	Pointer to the specified GPIO port.
in	*bitMask*	Bit mask corresponding to the intended `INPUT` pin(s).

GPIO_ConfigDirOutput()

```
void GPIO_ConfigDirOutput (
            GPIO_Port_t * gpioPort,
            GPIO_Pin_t pinMask )
```

Configure the direction of the specified GPIO pins. All pins are configured to `INPUT` by default, so this function should only be called to specify `OUTPUT` pins.

Parameters

in	*gpioPort*	Pointer to the specified GPIO port.
in	*bitMask*	Bit mask corresponding to the intended `OUTPUT` pin(s).

GPIO_ConfigDriveStrength()

```
void GPIO_ConfigDriveStrength (
            GPIO_Port_t * gpioPort,
            GPIO_Pin_t pinMask,
            uint8_t drive_mA )
```

Configure the specified pins' drive strength. Pins are initialized with 2[mA] drive strength, so this is only needed for a drive strength of 4[mA] or 8[mA].

Parameters

in	*gpioPort*	Pointer to the specified GPIO port.
in	*pinMask*	Bit mask corresponding to the intended pin(s).
in	*drive_mA*	Drive strength in [mA]. Should be 2, 4, or 8 [mA].

GPIO_ConfigInterrupts_BothEdges()

```
void GPIO_ConfigInterrupts_BothEdges (
            GPIO_Port_t * gpioPort,
            GPIO_Pin_t pinMask )
```

Configure the specified GPIO pins to trigger an interrupt on both edges of an input.

Parameters

in	*gpioPort*	Pointer to the specified GPIO port.
in	*pinMask*	Bit mask corresponding to the intended pin(s).

GPIO_ConfigInterrupts_Edge()

```
void GPIO_ConfigInterrupts_Edge (
            GPIO_Port_t * gpioPort,
            GPIO_Pin_t pinMask,
            bool risingEdge )
```

Configure the specified GPIO pins to trigger an interrupt on the rising or falling edge of an input.

Parameters

in	*gpioPort*	Pointer to the specified GPIO port.
in	*pinMask*	Bit mask corresponding to the intended pin(s).
in	*risingEdge*	`true` for rising edge, `false` for falling edge

GPIO_ConfigInterrupts_LevelTrig()

```
void GPIO_ConfigInterrupts_LevelTrig (
            GPIO_Port_t * gpioPort,
            GPIO_Pin_t pinMask,
            bool highLevel )
```

Configure the specified GPIO pins to trigger an interrupt on a high level or low level pulse.

Parameters

in	*gpioPort*	Pointer to the specified GPIO port.
in	*pinMask*	Bit mask corresponding to the intended pin(s).
in	*highLevel*	`true` for high level, `false` for low level

GPIO_ConfigNVIC()

```
void GPIO_ConfigNVIC (
            GPIO_Port_t * gpioPort,
            uint8_t priority )
```

Configure interrupts for the selected port in the NVIC.

Parameters

in	*gpioPort*	Pointer to the specified GPIO port.
in	*priority*	Priority number between 0 (highest) and 7 (lowest).

GPIO_ConfigPortCtrl()

```
void GPIO_ConfigPortCtrl (
            GPIO_Port_t * gpioPort,
            GPIO_Pin_t pinMask,
            uint8_t fieldEncoding )
```

Specify the alternate mode to use for the specified pins.

Parameters

in	*gpioPort*	Pointer to the specified GPIO port.
in	*pinMask*	Bit mask corresponding to the intended pin(s).
in	*fieldEncoding*	Number corresponding to intended alternate mode.

GPIO_ConfigPullDown()

```
void GPIO_ConfigPullDown (
            GPIO_Port_t * gpioPort,
            GPIO_Pin_t pinMask )
```

Activate the specified pins' internal pull-down resistors.

Parameters

in	*gpioPort*	Pointer to the specified GPIO port.
in	*pinMask*	Bit mask corresponding to the intended pin(s).

GPIO_ConfigPullUp()

```
void GPIO_ConfigPullUp (
            GPIO_Port_t * gpioPort,
            GPIO_Pin_t pinMask )
```

Activate the specified pins' internal pull-up resistors.

Parameters

in	*gpioPort*	Pointer to the specified GPIO port.
in	*pinMask*	Bit mask corresponding to the intended pin(s).

GPIO_DisableDigital()

```
void GPIO_DisableDigital (
            GPIO_Port_t * gpioPort,
            GPIO_Pin_t pinMask )
```

Disable digital I/O for the specified pins.

Parameters

in	*gpioPort*	Pointer to the specified GPIO port.
in	*pinMask*	Bit mask corresponding to the intended pin(s).

GPIO_EnableDigital()

```
void GPIO_EnableDigital (
            GPIO_Port_t * gpioPort,
            GPIO_Pin_t pinMask )
```

Enable digital I/O for the specified pins.

Parameters

in	*gpioPort*	Pointer to the specified GPIO port.
in	*pinMask*	Bit mask corresponding to the intended pin(s).

GPIO_InitPort()

```
GPIO_Port_t * GPIO_InitPort (
            GPIO_PortName_t portName )
```

Initialize a GPIO Port and return a pointer to its `struct`.

Parameters

in	*portName*	Name of the chosen port.

Returns

GPIO_Port_t* Pointer to the GPIO port's `struct`.

GPIO_isPortInit()

```
bool GPIO_isPortInit (
            GPIO_Port_t * gpioPort )
```

Check if the GPIO port is initialized.

Parameters

in	*gpioPort*	Pointer to the specified GPIO port.
out	*true*	The GPIO port is initialized.
out	*false*	The GPIO port has not been initialized.

GPIO_ReadPins()

```
uint8_t GPIO_ReadPins (
            GPIO_Port_t * gpioPort,
            GPIO_Pin_t pinMask )
```

Read from the specified GPIO pin.

Parameters

in	*gpioPort*	Pointer to the specified GPIO port.
in	*pinMask*	Bit mask corresponding to the intended pin(s).

GPIO_Toggle()

```
void GPIO_Toggle (
            GPIO_Port_t * gpioPort,
            GPIO_Pin_t pinMask )
```

Toggle the specified GPIO pins.

Parameters

in	*gpioPort*	Pointer to the specified GPIO port.
in	*pinMask*	Bit mask corresponding to the intended pin(s).

GPIO_WriteHigh()

```
void GPIO_WriteHigh (
            GPIO_Port_t * gpioPort,
            GPIO_Pin_t pinMask )
```

Write a `1` to the specified GPIO pins.

Parameters

in	*gpioPort*	Pointer to the specified GPIO port.
in	*pinMask*	Bit mask corresponding to the intended pin(s).

GPIO_WriteLow()

```
void GPIO_WriteLow (
            GPIO_Port_t * gpioPort,
            GPIO_Pin_t pinMask )
```

Write a `0` to the specified GPIO pins.

Parameters

in	*gpioPort*	Pointer to the specified GPIO port.
in	*pinMask*	Bit mask corresponding to the intended pin(s).

7.17 GPIO.h File Reference

Header file for general-purpose input/output (GPIO) device driver.

```
#include <NewAssert.h>
#include "tm4c123gh6pm.h"
#include <stdbool.h>
#include <stdint.h>
```

Enumerations

- enum **GPIO_Pin_t** {
  GPIO_PIN0 = ((uint8_t) 1) , **GPIO_PIN1** = ((uint8_t) (1 << 1)) , **GPIO_PIN2** = ((uint8_t) (1 << 2)) , **GPIO_PIN3** = ((uint8_t) (1 << 3)) ,
  GPIO_PIN4 = ((uint8_t) (1 << 4)) , **GPIO_PIN5** = ((uint8_t) (1 << 5)) , **GPIO_PIN6** = ((uint8_t) (1 << 6)) ,
  GPIO_PIN7 = ((uint8_t) (1 << 7)) ,
  GPIO_ALL_PINS = ((uint8_t) (0xFF)) }
- enum {
  LED_RED = GPIO_PIN1 , **LED_GREEN** = GPIO_PIN3 , **LED_BLUE** = GPIO_PIN2 , **LED_YELLOW** = (LED_RED + LED_GREEN) ,
  LED_CYAN = (LED_BLUE + LED_GREEN) , **LED_PURPLE** = (LED_RED + LED_BLUE) , **LED_WHITE** = (LED_RED + LED_BLUE + LED_GREEN) }
- enum **GPIO_PortName_t** {
  A , **B** , **C** , **D** ,
  E , **F** }

Functions

- GPIO_Port_t * GPIO_InitPort (GPIO_PortName_t portName)

  Initialize a GPIO Port and return a pointer to its `struct`.
- bool GPIO_isPortInit (GPIO_Port_t *gpioPort)

  Check if the GPIO port is initialized.
- void GPIO_ConfigDirOutput (GPIO_Port_t *gpioPort, GPIO_Pin_t pinMask)

  Configure the direction of the specified GPIO pins. All pins are configured to `INPUT` by default, so this function should only be called to specify `OUTPUT` pins.
- void GPIO_ConfigDirInput (GPIO_Port_t *gpioPort, GPIO_Pin_t pinMask)

  Configure the specified GPIO pins as `INPUT` pins. All pins are configured to `INPUT` by default, so this function is technically unnecessary, but useful for code readability.
- void GPIO_ConfigPullUp (GPIO_Port_t *gpioPort, GPIO_Pin_t pinMask)

  Activate the specified pins' internal pull-up resistors.
- void GPIO_ConfigPullDown (GPIO_Port_t *gpioPort, GPIO_Pin_t pinMask)

  Activate the specified pins' internal pull-down resistors.
- void GPIO_ConfigDriveStrength (GPIO_Port_t *gpioPort, GPIO_Pin_t pinMask, uint8_t drive_mA)

  Configure the specified pins' drive strength. Pins are initialized with 2[mA] drive strength, so this is only needed for a drive strength of 4[mA] or 8[mA].
- void GPIO_EnableDigital (GPIO_Port_t *gpioPort, GPIO_Pin_t pinMask)

  Enable digital I/O for the specified pins.
- void GPIO_DisableDigital (GPIO_Port_t *gpioPort, GPIO_Pin_t pinMask)

  Disable digital I/O for the specified pins.
- void GPIO_ConfigInterrupts_Edge (GPIO_Port_t *gpioPort, GPIO_Pin_t pinMask, bool risingEdge)

  Configure the specified GPIO pins to trigger an interrupt on the rising or falling edge of an input.
- void GPIO_ConfigInterrupts_BothEdges (GPIO_Port_t *gpioPort, GPIO_Pin_t pinMask)

  Configure the specified GPIO pins to trigger an interrupt on both edges of an input.
- void GPIO_ConfigInterrupts_LevelTrig (GPIO_Port_t *gpioPort, GPIO_Pin_t pinMask, bool highLevel)

  Configure the specified GPIO pins to trigger an interrupt on a high level or low level pulse.
- void GPIO_ConfigNVIC (GPIO_Port_t *gpioPort, uint8_t priority)

  Configure interrupts for the selected port in the NVIC.
- uint8_t GPIO_ReadPins (GPIO_Port_t *gpioPort, GPIO_Pin_t pinMask)

  Read from the specified GPIO pin.
- void GPIO_WriteHigh (GPIO_Port_t *gpioPort, GPIO_Pin_t pinMask)

  Write a `1` to the specified GPIO pins.
- void GPIO_WriteLow (GPIO_Port_t *gpioPort, GPIO_Pin_t pinMask)

Write a 0 to the specified GPIO pins.

- void GPIO_Toggle (GPIO_Port_t *gpioPort, GPIO_Pin_t pinMask)

  Toggle the specified GPIO pins.
- void GPIO_ConfigAltMode (GPIO_Port_t *gpioPort, GPIO_Pin_t pinMask)

  Activate the alternate mode for the specified pins.
- void GPIO_ConfigPortCtrl (GPIO_Port_t *gpioPort, GPIO_Pin_t pinMask, uint8_t fieldEncoding)

  Specify the alternate mode to use for the specified pins.
- void GPIO_ConfigAnalog (GPIO_Port_t *gpioPort, GPIO_Pin_t pinMask)

  Activate analog mode for the specified GPIO pins.

7.17.1 Detailed Description

Header file for general-purpose input/output (GPIO) device driver.

Author

Bryan McElvy

7.17.2 Function Documentation

GPIO_ConfigAltMode()

```
void GPIO_ConfigAltMode (
            GPIO_Port_t * gpioPort,
            GPIO_Pin_t pinMask )
```

Activate the alternate mode for the specified pins.

Parameters

in	*gpioPort*	Pointer to the specified GPIO port.
in	*pinMask*	Bit mask corresponding to the intended pin(s).

GPIO_ConfigAnalog()

```
void GPIO_ConfigAnalog (
            GPIO_Port_t * gpioPort,
            GPIO_Pin_t pinMask )
```

Activate analog mode for the specified GPIO pins.

Parameters

in	*gpioPort*	Pointer to the specified GPIO port.
in	*pinMask*	Bit mask corresponding to the intended pin(s).

GPIO_ConfigDirInput()

```
void GPIO_ConfigDirInput (
            GPIO_Port_t * gpioPort,
            GPIO_Pin_t pinMask )
```

Configure the specified GPIO pins as `INPUT` pins. All pins are configured to `INPUT` by default, so this function is technically unnecessary, but useful for code readability.

Parameters

in	*gpioPort*	Pointer to the specified GPIO port.
in	*bitMask*	Bit mask corresponding to the intended `INPUT` pin(s).

GPIO_ConfigDirOutput()

```
void GPIO_ConfigDirOutput (
            GPIO_Port_t * gpioPort,
            GPIO_Pin_t pinMask )
```

Configure the direction of the specified GPIO pins. All pins are configured to `INPUT` by default, so this function should only be called to specify `OUTPUT` pins.

Parameters

in	*gpioPort*	Pointer to the specified GPIO port.
in	*bitMask*	Bit mask corresponding to the intended `OUTPUT` pin(s).

GPIO_ConfigDriveStrength()

```
void GPIO_ConfigDriveStrength (
            GPIO_Port_t * gpioPort,
            GPIO_Pin_t pinMask,
            uint8_t drive_mA )
```

Configure the specified pins' drive strength. Pins are initialized with 2[mA] drive strength, so this is only needed for a drive strength of 4[mA] or 8[mA].

Parameters

in	*gpioPort*	Pointer to the specified GPIO port.
in	*pinMask*	Bit mask corresponding to the intended pin(s).
in	*drive_mA*	Drive strength in [mA]. Should be 2, 4, or 8 [mA].

GPIO_ConfigInterrupts_BothEdges()

```
void GPIO_ConfigInterrupts_BothEdges (
```

```
            GPIO_Port_t * gpioPort,
            GPIO_Pin_t pinMask )
```

Configure the specified GPIO pins to trigger an interrupt on both edges of an input.

Parameters

in	*gpioPort*	Pointer to the specified GPIO port.
in	*pinMask*	Bit mask corresponding to the intended pin(s).

GPIO_ConfigInterrupts_Edge()

```
void GPIO_ConfigInterrupts_Edge (
            GPIO_Port_t * gpioPort,
            GPIO_Pin_t pinMask,
            bool risingEdge )
```

Configure the specified GPIO pins to trigger an interrupt on the rising or falling edge of an input.

Parameters

in	*gpioPort*	Pointer to the specified GPIO port.
in	*pinMask*	Bit mask corresponding to the intended pin(s).
in	*risingEdge*	`true` for rising edge, `false` for falling edge

GPIO_ConfigInterrupts_LevelTrig()

```
void GPIO_ConfigInterrupts_LevelTrig (
            GPIO_Port_t * gpioPort,
            GPIO_Pin_t pinMask,
            bool highLevel )
```

Configure the specified GPIO pins to trigger an interrupt on a high level or low level pulse.

Parameters

in	*gpioPort*	Pointer to the specified GPIO port.
in	*pinMask*	Bit mask corresponding to the intended pin(s).
in	*highLevel*	`true` for high level, `false` for low level

GPIO_ConfigNVIC()

```
void GPIO_ConfigNVIC (
            GPIO_Port_t * gpioPort,
            uint8_t priority )
```

Configure interrupts for the selected port in the NVIC.

Parameters

in	*gpioPort*	Pointer to the specified GPIO port.
in	*priority*	Priority number between 0 (highest) and 7 (lowest).

GPIO_ConfigPortCtrl()

```
void GPIO_ConfigPortCtrl (
            GPIO_Port_t * gpioPort,
            GPIO_Pin_t pinMask,
            uint8_t fieldEncoding )
```

Specify the alternate mode to use for the specified pins.

Parameters

in	*gpioPort*	Pointer to the specified GPIO port.
in	*pinMask*	Bit mask corresponding to the intended pin(s).
in	*fieldEncoding*	Number corresponding to intended alternate mode.

GPIO_ConfigPullDown()

```
void GPIO_ConfigPullDown (
            GPIO_Port_t * gpioPort,
            GPIO_Pin_t pinMask )
```

Activate the specified pins' internal pull-down resistors.

Parameters

in	*gpioPort*	Pointer to the specified GPIO port.
in	*pinMask*	Bit mask corresponding to the intended pin(s).

GPIO_ConfigPullUp()

```
void GPIO_ConfigPullUp (
            GPIO_Port_t * gpioPort,
            GPIO_Pin_t pinMask )
```

Activate the specified pins' internal pull-up resistors.

Parameters

in	*gpioPort*	Pointer to the specified GPIO port.
in	*pinMask*	Bit mask corresponding to the intended pin(s).

GPIO_DisableDigital()

```
void GPIO_DisableDigital (
            GPIO_Port_t * gpioPort,
            GPIO_Pin_t pinMask )
```

Disable digital I/O for the specified pins.

Parameters

in	*gpioPort*	Pointer to the specified GPIO port.
in	*pinMask*	Bit mask corresponding to the intended pin(s).

GPIO_EnableDigital()

```
void GPIO_EnableDigital (
            GPIO_Port_t * gpioPort,
            GPIO_Pin_t pinMask )
```

Enable digital I/O for the specified pins.

Parameters

in	*gpioPort*	Pointer to the specified GPIO port.
in	*pinMask*	Bit mask corresponding to the intended pin(s).

GPIO_InitPort()

```
GPIO_Port_t * GPIO_InitPort (
            GPIO_PortName_t portName )
```

Initialize a GPIO Port and return a pointer to its `struct`.

Parameters

in	*portName*	Name of the chosen port.

Returns

GPIO_Port_t* Pointer to the GPIO port's `struct`.

GPIO_isPortInit()

```
bool GPIO_isPortInit (
            GPIO_Port_t * gpioPort )
```

Check if the GPIO port is initialized.

Parameters

in	*gpioPort*	Pointer to the specified GPIO port.
out	*true*	The GPIO port is initialized.
out	*false*	The GPIO port has not been initialized.

GPIO_ReadPins()

```
uint8_t GPIO_ReadPins (
            GPIO_Port_t * gpioPort,
            GPIO_Pin_t pinMask )
```

Read from the specified GPIO pin.

Parameters

in	*gpioPort*	Pointer to the specified GPIO port.
in	*pinMask*	Bit mask corresponding to the intended pin(s).

GPIO_Toggle()

```
void GPIO_Toggle (
            GPIO_Port_t * gpioPort,
            GPIO_Pin_t pinMask )
```

Toggle the specified GPIO pins.

Parameters

in	*gpioPort*	Pointer to the specified GPIO port.
in	*pinMask*	Bit mask corresponding to the intended pin(s).

GPIO_WriteHigh()

```
void GPIO_WriteHigh (
            GPIO_Port_t * gpioPort,
            GPIO_Pin_t pinMask )
```

Write a `1` to the specified GPIO pins.

Parameters

in	*gpioPort*	Pointer to the specified GPIO port.
in	*pinMask*	Bit mask corresponding to the intended pin(s).

GPIO_WriteLow()

```
void GPIO_WriteLow (
            GPIO_Port_t * gpioPort,
            GPIO_Pin_t pinMask )
```

Write a 0 to the specified GPIO pins.

Parameters

in	*gpioPort*	Pointer to the specified GPIO port.
in	*pinMask*	Bit mask corresponding to the intended pin(s).

7.18 PLL.c File Reference

Implementation details for phase-lock-loop (PLL) functions.

```
#include "PLL.h"
#include "tm4c123gh6pm.h"
#include <stdint.h>
```

Functions

- void **PLL_Init** (void)

  Initializes the phase-locked-loop (PLL), allowing a bus frequency of 80[MHz].

7.18.1 Detailed Description

Implementation details for phase-lock-loop (PLL) functions.

Author

Bryan McElvy

7.19 PLL.h File Reference

Driver module for activating the phase-locked-loop (PLL).

```
#include "tm4c123gh6pm.h"
#include <stdint.h>
```

Functions

- void **PLL_Init** (void)

  Initializes the phase-locked-loop (PLL), allowing a bus frequency of 80[MHz].

7.19.1 Detailed Description

Driver module for activating the phase-locked-loop (PLL).

Author

Bryan McElvy

7.20 SPI.c File Reference

Source code for SPI module.

```
#include "SPI.h"
#include "GPIO.h"
#include "FIFO.h"
#include "tm4c123gh6pm.h"
#include <stdbool.h>
#include <stdint.h>
```

Macros

- #define NVIC_SSI0_NUM 7
- #define **SPI_INT_START**() (NVIC_SW_TRIG_R = (NVIC_SW_TRIG_R & ~(0xFF)) | NVIC_SSI0_NUM)
- #define **SPI_SET_DC**() (GPIO_PORTA_DATA_R |= 0x40)
- #define **SPI_CLEAR_DC**() (GPIO_PORTA_DATA_R &= ~(0x40))
- #define **SPI_IS_BUSY** (SSI0_SR_R & 0x10)
- #define **SPI_TX_ISNOTFULL** ((bool) (SSI0_SR_R & 0x02))
- #define **SPI_BUFFER_SIZE** 9

Enumerations

- enum {
  SPI_CLK_PIN = GPIO_PIN2 , **SPI_CS_PIN** = GPIO_PIN3 , **SPI_RX_PIN** = GPIO_PIN4 , **SPI_TX_PIN** = GPIO_PIN5 ,
  SPI_DC_PIN = GPIO_PIN6 , **SPI_RESET_PIN** = GPIO_PIN7 , **SPI_SSI0_PINS** = (SPI_CLK_PIN | SPI_↩ CS_PIN | SPI_RX_PIN | SPI_TX_PIN) , **SPI_GPIO_PINS** = (SPI_DC_PIN | SPI_RESET_PIN) ,
  SPI_ALL_PINS = (SPI_SSI0_PINS | SPI_GPIO_PINS) }

Functions

- void SPI_Init (void)

  Initialize SSI0 to act as an SPI Controller (AKA Master) in mode 0.
- uint8_t SPI_Read (void)

  Read data from the peripheral.
- void SPI_WriteCmd (uint8_t cmd)

  Write an 8-bit command to the peripheral.
- void SPI_WriteData (uint8_t data)

  Write 8-bit data to the peripheral.
- void SPI_IRQ_WriteCmd (uint8_t cmd)

Add an 8-bit command to the SPI queue. If no data or other command is written, should directly precede a call to `SPI_IRQ_StartWriting()`.

- void SPI_IRQ_WriteData (uint8_t data)

  Add 8-bit data to the SPI queue. Should directly precede either another call to the same function or a call to `SPI_IRQ_StartWriting()`.

- void **SPI_IRQ_StartWriting** (void)

  Start writing data to the Tx FIFO. Should be used after 1+ calls to `SPI_IRQ_WriteCmd()` and/or `SPI_IRQ_WriteData()`. If unused, writing will start when the SPI queue is full.

- void SSI0_Handler (void)

  Sends parameters (data or commands) over SPI via SSI0.

7.20.1 Detailed Description

Source code for SPI module.

Author

Bryan McElvy

7.21 SPI.h File Reference

Driver module for using the serial peripheral interface (SPI) protocol.

```
#include "GPIO.h"
#include "FIFO.h"
#include "tm4c123gh6pm.h"
#include <stdbool.h>
#include <stdint.h>
```

Functions

- void SPI_Init (void)

  Initialize SSI0 to act as an SPI Controller (AKA Master) in mode 0.

- uint8_t SPI_Read (void)

  Read data from the peripheral.

- void SPI_WriteCmd (uint8_t cmd)

  Write an 8-bit command to the peripheral.

- void SPI_WriteData (uint8_t data)

  Write 8-bit data to the peripheral.

- void SPI_IRQ_WriteCmd (uint8_t cmd)

  Add an 8-bit command to the SPI queue. If no data or other command is written, should directly precede a call to `SPI_IRQ_StartWriting()`.

- void SPI_IRQ_WriteData (uint8_t data)

  Add 8-bit data to the SPI queue. Should directly precede either another call to the same function or a call to `SPI_IRQ_StartWriting()`.

- void **SPI_IRQ_StartWriting** (void)

  Start writing data to the Tx FIFO. Should be used after 1+ calls to `SPI_IRQ_WriteCmd()` and/or `SPI_IRQ_WriteData()`. If unused, writing will start when the SPI queue is full.

7.21.1 Detailed Description

Driver module for using the serial peripheral interface (SPI) protocol.

Author

Bryan McElvy

7.22 SysTick.c File Reference

Implementation details for SysTick functions.

```
#include "SysTick.h"
#include "tm4c123gh6pm.h"
#include <stdint.h>
```

Functions

- void **SysTick_Timer_Init** (void)

  Initialize SysTick for timing purposes.
- void **SysTick_Wait1ms** (uint32_t delay_ms)

  Delay for specified amount of time in [ms]. Assumes f_bus = 80[MHz].
- void SysTick_Interrupt_Init (uint32_t time_ms)

  Initialize SysTick for interrupts.

7.22.1 Detailed Description

Implementation details for SysTick functions.

Author

Bryan McElvy

7.23 SysTick.h File Reference

Driver module for using SysTick-based timing and/or interrupts.

```
#include "tm4c123gh6pm.h"
#include <stdint.h>
```

Functions

- void **SysTick_Timer_Init** (void)

  Initialize SysTick for timing purposes.
- void **SysTick_Wait1ms** (uint32_t delay_ms)

  Delay for specified amount of time in [ms]. Assumes f_bus = 80[MHz].
- void SysTick_Interrupt_Init (uint32_t time_ms)

  Initialize SysTick for interrupts.

7.23.1 Detailed Description

Driver module for using SysTick-based timing and/or interrupts.

Author

Bryan McElvy

7.24 Timer.c File Reference

Implementation for timer module.

```
#include "Timer.h"
#include "tm4c123gh6pm.h"
#include <stdint.h>
```

Functions

Timer0A

- void **Timer0A_Init** (void)
  Initialize timer 0 as 32-bit, one-shot, countdown timer.
- void Timer0A_Start (uint32_t time_ms)
  Count down starting from the inputted value.
- uint8_t Timer0A_isCounting (void)
  Returns 1 if Timer0 is still counting and 0 if not.
- void Timer0A_Wait1ms (uint32_t time_ms)
  Wait for the specified amount of time in [ms].

Timer1A

- void Timer1A_Init (uint32_t time_ms)
  Initialize timer 1 as a 32-bit, periodic, countdown timer with interrupts.

Timer2A

- void **Timer2A_Init** (void)
  Initialize timer 2 as 32-bit, one-shot, countdown timer.
- void Timer2A_Start (uint32_t time_ms)
  Count down starting from the inputted value.
- uint8_t Timer2A_isCounting (void)
  Returns 1 if Timer2 is still counting and 0 if not.
- void Timer2A_Wait1ms (uint32_t time_ms)
  Wait for the specified amount of time in [ms].
- void Timer3A_Init (uint32_t time_ms)
  Initialize Timer3A as a 32-bit, periodic, countdown timer that triggers ADC sample capture.

7.24.1 Detailed Description

Implementation for timer module.

Author

Bryan McElvy

7.25 Timer.h File Reference

Driver module for general-purpose timer modules.

```
#include "tm4c123gh6pm.h"
#include <stdint.h>
```

Functions

Timer0A

- void **Timer0A_Init** (void)
  Initialize timer 0 as 32-bit, one-shot, countdown timer.
- void Timer0A_Start (uint32_t time_ms)
  Count down starting from the inputted value.
- uint8_t Timer0A_isCounting (void)
  Returns 1 if Timer0 is still counting and 0 if not.
- void Timer0A_Wait1ms (uint32_t time_ms)
  Wait for the specified amount of time in [ms].

Timer1A

- void Timer1A_Init (uint32_t time_ms)
  Initialize timer 1 as a 32-bit, periodic, countdown timer with interrupts.

Timer2A

- void **Timer2A_Init** (void)
  Initialize timer 2 as 32-bit, one-shot, countdown timer.
- void Timer2A_Start (uint32_t time_ms)
  Count down starting from the inputted value.
- uint8_t Timer2A_isCounting (void)
  Returns 1 if Timer2 is still counting and 0 if not.
- void Timer2A_Wait1ms (uint32_t time_ms)
  Wait for the specified amount of time in [ms].
- void Timer3A_Init (uint32_t time_ms)
  Initialize Timer3A as a 32-bit, periodic, countdown timer that triggers ADC sample capture.

7.25.1 Detailed Description

Driver module for general-purpose timer modules.

Author

Bryan McElvy

```
Timer | Function
--------------------
0A      Debouncing
1A      LCD Interrupts
2A      ILI9341 Resets
3A      ADC Interrupts
```

7.26 UART.c File Reference

Source code for UART module.

```
#include "UART.h"
#include "GPIO.h"
#include "FIFO.h"
#include "tm4c123gh6pm.h"
#include <stdbool.h>
#include <stdint.h>
```

Macros

- #define **ASCII_CONVERSION** 0x30
- #define **UART0_TX_FULL** (UART0_FR_R & 0x20)
- #define **UART0_BUFFER_SIZE** 16
- #define **UART0_INTERRUPT_NUM** 5

Functions

- void UART0_Init (void)

  Initialize UART0 to a baud rate of 115200, 8-bit data length, 1 start bit, and 1 stop bit.
- unsigned char UART0_ReadChar (void)

  Read a single character from UART0.
- void UART0_WriteChar (unsigned char input_char)

  Write a single character to UART0.
- void UART0_WriteStr (void ∗input_str)

  Write a C string to UART0.
- void UART0_WriteInt (uint32_t n)

  Write a 32-bit unsigned integer to UART0.
- void UART0_WriteFloat (double n, uint8_t num_decimals)

  Write a floating-point number to UART0.
- void UART0_IRQ_AddChar (unsigned char input_char)

  Add a single character to UART0's FIFO.
- void UART0_IRQ_AddStr (void ∗input_str)

  Add a string to UART0's FIFO.
- void UART0_IRQ_AddInt (uint32_t n)

  Add an integer to UART0's FIFO.
- void UART0_IRQ_Start (void)

  Transmit the UART0's FIFO's contents via interrupt.
- void **UART0_Handler** (void)
- void UART1_Init (void)

  Initialize UART1 to a baud rate of 115200, 8-bit data length, 1 start bit, and 1 stop bit.
- unsigned char UART1_ReadChar (void)

  Read a single character from UART1.
- void UART1_WriteChar (unsigned char input_char)

  Write a single character to UART1.
- void UART1_WriteStr (void ∗input_str)

  Write a C string to UART1.

7.26.1 Detailed Description

Source code for UART module.

Author

Bryan McElvy

7.27 UART.h File Reference

Driver module for serial communication via UART0 and UART 1.

```
#include "GPIO.h"
#include "FIFO.h"
#include "tm4c123gh6pm.h"
#include <stdbool.h>
#include <stdint.h>
```

Functions

- void UART0_Init (void)
  Initialize UART0 to a baud rate of 115200, 8-bit data length, 1 start bit, and 1 stop bit.
- unsigned char UART0_ReadChar (void)
  Read a single character from UART0.
- void UART0_WriteChar (unsigned char input_char)
  Write a single character to UART0.
- void UART0_WriteStr (void *input_str)
  Write a C string to UART0.
- void UART0_WriteInt (uint32_t n)
  Write a 32-bit unsigned integer to UART0.
- void UART0_WriteFloat (double n, uint8_t num_decimals)
  Write a floating-point number to UART0.
- void UART0_IRQ_AddChar (unsigned char input_char)
  Add a single character to UART0's FIFO.
- void UART0_IRQ_AddStr (void *input_str)
  Add a string to UART0's FIFO.
- void UART0_IRQ_AddInt (uint32_t n)
  Add an integer to UART0's FIFO.
- void UART0_IRQ_Start (void)
  Transmit the UART0's FIFO's contents via interrupt.
- void UART1_Init (void)
  Initialize UART1 to a baud rate of 115200, 8-bit data length, 1 start bit, and 1 stop bit.
- unsigned char UART1_ReadChar (void)
  Read a single character from UART1.
- void UART1_WriteChar (unsigned char input_char)
  Write a single character to UART1.
- void UART1_WriteStr (void *input_str)
  Write a C string to UART1.

7.27.1 Detailed Description

Driver module for serial communication via UART0 and UART 1.

Author

Bryan McElvy

```
UART0 uses PA0 and PA1, which are not broken out but can connect
to a PC's serial port via USB.

UART1 uses PB0 (Rx) and PB1 (Tx), which are broken out but
do not connect to a serial port.
```

7.28 main.c File Reference

Main program file for ECG-HRM.

```
#include "DAQ.h"
#include "Debug.h"
#include "LCD.h"
#include "QRS.h"
#include "PLL.h"
```

Functions

- int **main** (void)
- void **ADC0_SS3_Handler** (void)

  Interrupt service routine (ISR) for collecting ADC samples.
- void **Timer1A_Handler** (void)

  Interrupt service routine (ISR) for outputting data to the LCD.

7.28.1 Detailed Description

Main program file for ECG-HRM.

Author

Bryan McElvy

7.29 ILI9341.c File Reference

Source code for ILI9341 module.

```
#include "ILI9341.h"
#include "SPI.h"
#include "Timer.h"
#include "FIFO.h"
#include "tm4c123gh6pm.h"
#include <stdbool.h>
#include <stdint.h>
```

Enumerations

- enum Cmd_t {
  NOP = 0x00 , SWRESET = 0x01 , SPLIN = 0x10 , SPLOUT = 0x11 ,
  PTLON = 0x12 , NORON = 0x13 , DINVOFF = 0x20 , DINVON = 0x21 ,
  CASET = 0x2A , PASET = 0x2B , RAMWR = 0x2C , DISPOFF = 0x28 ,
  DISPON = 0x29 , PLTAR = 0x30 , VSCRDEF = 0x33 , MADCTL = 0x36 ,
  VSCRSADD = 0x37 , IDMOFF = 0x38 , IDMON = 0x39 , PIXSET = 0x3A ,
  FRMCTR1 = 0xB1 , FRMCTR2 = 0xB2 , FRMCTR3 = 0xB3 , PRCTR = 0xB5 ,
  IFCTL = 0xF6 }

Functions

- void **ILI9341_Init** (void)

  Initialize the LCD driver, the SPI module, and Timer2A.
- void ILI9341_resetHard (void)

  Perform a hardware reset of the LCD driver.
- void ILI9341_resetSoft (void)

  Perform a software reset of the LCD driver.
- void ILI9341_setSleepMode (bool isSleeping)

  Enter or exit sleep mode. The LCD driver is in sleep mode by default upon powering on or either kind of reset.
- void ILI9341_setDispMode (bool isNormal, bool isFullColors)

  Set the display area and color expression.
- void ILI9341_setPartialArea (uint16_t rowStart, uint16_t rowEnd)

  Set the partial display area for partial mode. Call before activating partial mode via ILI9341_setDisplayMode().
- void ILI9341_setDispInversion (bool is_ON)

  Toggle display inversion. Turning `ON` causes colors to be inverted on the display.
- void ILI9341_setDispOutput (bool is_ON)

  Turn display output ON or OFF. This function clears the display and stops outputting to the display area, but does not affect frame memory or power.
- void ILI9341_setScrollArea (uint16_t topFixedArea, uint16_t vertScrollArea, uint16_t bottFixedArea)

  Set the vertical scrolling area of the display. The sum of the three parameters should be equal to the max number of rows `NUM_ROWS = 320`.
- void ILI9341_setScrollStart (uint16_t startRow)

  Set the start row for vertical scrolling.
- void ILI9341_setMemAccessCtrl (bool areRowsFlipped, bool areColsFlipped, bool areRowsAndCols↩ Switched, bool isVertRefreshFlipped, bool isColorOrderFlipped, bool isHorRefreshFlipped)

  Set how data is converted from memory to display.
- void ILI9341_setColorDepth (bool is_16bit)

  Set the pixel format to be 16-bit (65K colors) or 18-bit (262K colors).
- void **ILI9341_NoOpCmd** (void)

  Send the "No Operation" command (`NOP = 0x00`) to the LCD driver. Can be used to terminate the "Memory Write" (`RAMWR`) and "Memory Read" (`RAMRD`) commands, but does nothing otherwise.
- void ILI9341_setFrameRateNorm (uint8_t divisionRatio, uint8_t clocksPerLine)

  TODO: Write brief.
- void ILI9341_setFrameRateIdle (uint8_t divisionRatio, uint8_t clocksPerLine)

  TODO: Write brief.
- void ILI9341_setInterface (void)

  Sets the interface for the ILI9341. The parameters for this command are hard-coded, so it only needs to be called once upon initialization.
- void ILI9341_setRowAddress (uint16_t startRow, uint16_t endRow)

  not using backlight, so these aren't necessary

- void ILI9341_setColAddress (uint16_t startCol, uint16_t endCol)

  Sets the start/end rows to be written to.
- void ILI9341_writeMemCmd (void)

  Sends the "Write Memory" (RAMWR) command to the LCD driver, signalling that incoming data should be written to memory.
- void ILI9341_writePixel (uint8_t red, uint8_t green, uint8_t blue, bool is_16bit)

  Write a single pixel to frame memory.

7.29.1 Detailed Description

Source code for ILI9341 module.

Author

Bryan McElvy

7.30 ILI9341.h File Reference

Driver module for interfacing with an ILI9341 LCD driver.

```
#include "SPI.h"
#include "Timer.h"
#include "FIFO.h"
#include "tm4c123gh6pm.h"
#include <stdbool.h>
#include <stdint.h>
```

Macros

- #define **NUM_COLS** (uint16_t) 240
- #define **NUM_ROWS** (uint16_t) 320

Functions

- void **ILI9341_Init** (void)

  Initialize the LCD driver, the SPI module, and Timer2A.
- void ILI9341_resetHard (void)

  Perform a hardware reset of the LCD driver.
- void ILI9341_resetSoft (void)

  Perform a software reset of the LCD driver.
- void ILI9341_setSleepMode (bool isSleeping)

  Enter or exit sleep mode. The LCD driver is in sleep mode by default upon powering on or either kind of reset.
- void ILI9341_setDispMode (bool isNormal, bool isFullColors)

  Set the display area and color expression.
- void ILI9341_setPartialArea (uint16_t rowStart, uint16_t rowEnd)

  Set the partial display area for partial mode. Call before activating partial mode via ILI9341_setDisplayMode().
- void ILI9341_setDispInversion (bool is_ON)

  Toggle display inversion. Turning ON causes colors to be inverted on the display.

- void ILI9341_setDispOutput (bool is_ON)

  Turn display output ON or OFF. This function clears the display and stops outputting to the display area, but does not affect frame memory or power.
- void ILI9341_setScrollArea (uint16_t topFixedArea, uint16_t vertScrollArea, uint16_t bottFixedArea)

  Set the vertical scrolling area of the display. The sum of the three parameters should be equal to the max number of rows `NUM_ROWS = 320`.
- void ILI9341_setScrollStart (uint16_t startRow)

  Set the start row for vertical scrolling.
- void ILI9341_setMemAccessCtrl (bool areRowsFlipped, bool areColsFlipped, bool areRowsAndColsSwitched, bool isVertRefreshFlipped, bool isColorOrderFlipped, bool isHorRefreshFlipped)

  Set how data is converted from memory to display.
- void ILI9341_setColorDepth (bool is_16bit)

  Set the pixel format to be 16-bit (65K colors) or 18-bit (262K colors).
- void **ILI9341_NoOpCmd** (void)

  Send the "No Operation" command (`NOP = 0x00`) to the LCD driver. Can be used to terminate the "Memory Write" (`RAMWR`) and "Memory Read" (`RAMRD`) commands, but does nothing otherwise.
- void ILI9341_setFrameRateNorm (uint8_t divisionRatio, uint8_t clocksPerLine)

  TODO: Write brief.
- void ILI9341_setFrameRateIdle (uint8_t divisionRatio, uint8_t clocksPerLine)

  TODO: Write brief.
- void **ILI9341_setBlankingPorch** (uint8_t vpf, uint8_t vbp, uint8_t hfp, uint8_t hbp)

  TODO: Write.
- void ILI9341_setInterface (void)

  Sets the interface for the ILI9341. The parameters for this command are hard-coded, so it only needs to be called once upon initialization.
- void ILI9341_setRowAddress (uint16_t startRow, uint16_t endRow)

  not using backlight, so these aren't necessary
- void ILI9341_setColAddress (uint16_t startCol, uint16_t endCol)

  Sets the start/end rows to be written to.
- void ILI9341_writeMemCmd (void)

  Sends the "Write Memory" (`RAMWR`) command to the LCD driver, signalling that incoming data should be written to memory.
- void ILI9341_writePixel (uint8_t red, uint8_t green, uint8_t blue, bool is_16bit)

  Write a single pixel to frame memory.

7.30.1 Detailed Description

Driver module for interfacing with an ILI9341 LCD driver.

Author

Bryan McElvy

This module contains functions for initializing and outputting graphical data to a 240RGBx320 resolution, 262K color-depth liquid crystal display (LCD). The module interfaces the LaunchPad (or any other board featuring the TM4C123GH6PM microcontroller) with an ILI9341 LCD driver chip via the SPI (serial peripheral interface) protocol.

7.31 Led.c File Reference

Source code for LED module.

```
#include "Led.h"
#include "GPIO.h"
#include "NewAssert.h"
#include <stdbool.h>
#include <stdint.h>
```

Data Structures

- struct Led_t

Functions

- Led_t * Led_Init (GPIO_Port_t *gpioPort, GPIO_Pin_t pin)
  Initialize a light-emitting diode (LED) as an `Led_t`.
- GPIO_Port_t * Led_GetPort (Led_t *led)
  Get the GPIO port associated with the LED.
- GPIO_Pin_t Led_GetPin (Led_t *led)
  Get the GPIO pin associated with the LED.
- bool Led_isOn (Led_t *led)
  Check the LED's status.
- void Led_TurnOn (Led_t *led)
  Turn the LED `ON`.
- void Led_TurnOff (Led_t *led)
  Turn the LED `OFF`.
- void Led_Toggle (Led_t *led)
  Toggle the LED (i.e. `OFF` -> `ON` or `ON` -> `OFF`).

7.31.1 Detailed Description

Source code for LED module.

Author

Bryan McElvy

7.32 Led.h File Reference

Interface for LED module.

```
#include "GPIO.h"
#include "NewAssert.h"
#include <stdbool.h>
#include <stdint.h>
```

Macros

- #define **LED_POOL_SIZE** 3

Functions

- Led_t * Led_Init (GPIO_Port_t *gpioPort, GPIO_Pin_t pin)

  Initialize a light-emitting diode (LED) as an `Led_t`.
- GPIO_Port_t * Led_GetPort (Led_t *led)

  Get the GPIO port associated with the LED.
- GPIO_Pin_t Led_GetPin (Led_t *led)

  Get the GPIO pin associated with the LED.
- bool Led_isOn (Led_t *led)

  Check the LED's status.
- void Led_TurnOn (Led_t *led)

  Turn the LED `ON`.
- void Led_TurnOff (Led_t *led)

  Turn the LED `OFF`.
- void Led_Toggle (Led_t *led)

  Toggle the LED (i.e. `OFF` -> `ON` or `ON` -> `OFF`).

7.32.1 Detailed Description

Interface for LED module.

Author

Bryan McElvy

Index