



# Discover our embedded software solutions

## - ST, third parties and open source -

STM32 and STM8 microcontrollers

February 2019



# A full portfolio and several models

2

- Extensive embedded software ecosystem around the STM32 and STM8 microcontrollers
- You will find your solution, fitting your requirements in terms of price, license and support

## ST-designed software

- Built in-house, making the most of the STM32 and STM8 microcontrollers
- Source code or binaries
- Supported by ST

## Open source

- Proposed by community or third parties
- Source code, from BSD or GPL licenses to commercial products
- Supported by open-source community or third parties

## Third parties

- Generic solutions proposed by many companies, portable to/from other platforms
- Source code or binaries
- Supported by third parties

# A large community of third parties... and growing !

3




# STM32 MCUs Embedded Software Offer - Overview

4

Several solutions mixing levels of Portability and Abstraction



STM32 Embedded Software




STM32 Portability




Arm® Cortex-M  
Portability

Any MCU Portability

# Solutions at all levels 8



Select the area of interest for more details



# Hardware abstraction layer (HAL)

# Hardware abstraction layer 7

This layer is the first one to interact with the MCU hardware

- **Consistent programming interface**
  - When microcontrollers have different hardware implementations
- **Full microcontroller coverage**
  - All peripherals are handled



# STM32 - Hardware abstraction layer

8

Provider	Solution name	Model	Cost	Availability												
				WB	F0	G0	F1	F2	F3		F4	F7	H7	L0	L1	L4 /L4 +
									F30x	F37x						
ST	<a href="#">STM32Snippets</a>	Source	Free	N <sup>1</sup>	Y	N <sup>1</sup>							Y	N <sup>1</sup>		
ST	Standard peripheral library	Source	Free	N <sup>1</sup>	<u>Y</u>	N <sup>1</sup>	<u>Y</u>	<u>Y</u>	<u>Y</u>	<u>Y</u>	<u>Y</u>	N <sup>1</sup>	N <sup>1</sup>	N <sup>1</sup>	<u>Y</u>	N <sup>1</sup>
ST	 <a href="#">STM32Cube - HAL Hardware Abstraction Layer</a>	Open Source	Free (BSD)	Y	Y	Y	Y	Y	Y		Y	Y	Y	Y	Y	Y
ST	 <a href="#">STM32Cube – LL Low-Layer</a>	Open Source	Free (BSD)	Y	Y	Y	Y	Y	Y		Y	Y	Y	Y	Y	Y

1/ Not plan to make it available

More details about hardware abstraction layer solutions: [STM32 Embedded Software overview](#)






# STM8 - Hardware abstraction layer

9

Provider	Solution name	Model	Cost	Availability		
				STM8S STM8AF	STM8L10x	STM8Lx5x STM8Lx6x STM8AL
ST	Standard peripheral library	Source	Free	<u>Y</u>	<u>Y</u>	<u>Y</u>



# Middleware and application fields

# Middleware and Application fields

11

Middleware stacks fill the gap between hardware and your application.  
ST and third parties bring the required solutions.

ST also proposes application software bricks to speed up customer development.

- **All standard middleware covered**

- RTOS/kernel
- File system
- USB
- Security (crypto, SSL/TLS, secure boot)
- Connectivity (TCP/IP, Bluetooth, Wi-Fi, NFC, Cloud connectors...)
- Safety
- Industrial protocols
- Audio
- Motor Control
- ...

# Middleware – RTOS / kernel

12

This is the root component to share time between several tasks on a single core. It ensures task switching within a known and limited duration.

- **A multitude of solutions for STM32 and STM8 available now**



# STM32 – RTOS / kernel (1/3)


13

Provider	Solution name	Model	Cost	Availability											
				WB	F0	G0	F1	F2	F3	F4	F7	H7	L0	L1	L4 /L4+
Alibaba	<a href="#">Rhino RTOS</a>	Open Source (Apache 2.0)	Free	N	N	N	N	N	N	Y	Y	N	Y	N	Y
arm	<a href="#">mbed OS<sup>5</sup></a>	Open Source (Apache 2.0)	Free	N	Y	N	Y	Y	Y	Y	Y	Y	Y	Y	Y
AWS	<a href="#">FreeRTOS kernel</a>	Source <sup>3</sup>	Free	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
AVIX-RT	<a href="#">AVIX</a>	Binaries	License	N	N	N	Y	Y	Y	Y	Y	N	N	Y	N
Chibios	<a href="#">ChibiOS/RT</a> <a href="#">ChibiOS/NIL</a>	Open source (GPL3) or Source	Free or License	N	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
CMX	<a href="#">CMX-RTX</a>	Source	License	N <sup>4</sup>	Y	N <sup>4</sup>	Y	Y	Y	Y	Y	Y	Y	Y	Y
CMX	<a href="#">CMX-Tiny+</a>	Source	License	N <sup>4</sup>	Y	N	Y	Y	Y	Y	Y	N	Y	Y	N
eCosCentric	<a href="#">eCosPro</a>	Modified GNU GPL or Source <sup>1</sup>	Free or License	N <sup>4</sup>	N	N <sup>4</sup>	Y	Y	Y	Y	Y	N <sup>4</sup>	N	Y	Y
eForce	<a href="#">µC3/Compact</a>	Source	License	N <sup>4</sup>	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
eForce	<a href="#">µC3/Standard</a>	Source	License	N	N	N	N	N	N	Y	Y	Y	N	N	N
Emcraft	<a href="#">uCLinux</a>	Open Source (GPL) <sup>2</sup>	Free <sup>2</sup>	N	N	N	N	N	N	Y	Y	N <sup>4</sup>	N	N	N
EUROS	<a href="#">EUROS</a>	Binaries or source	License	N <sup>4</sup>	Y	N <sup>4</sup>	Y	Y	Y	Y	Y	Y	Y	Y	Y



# STM32 – RTOS / kernel (2/3)

14

Provider	Solution name	Model	Cost	Availability											
				WB	F0	G0	F1	F2	F3	F4	F7	H7	L0	L1	L4/L4+
Express Logic	<a href="#">ThreadX<sup>5</sup></a>	Source	License	N <sup>2</sup>	Y	N <sup>2</sup>	Y	Y	Y	Y	Y	Y	Y	Y	Y
Green Hills	<a href="#">μ-velOSity</a>	Source	License	N <sup>2</sup>	Y	N <sup>2</sup>	Y	Y	Y	Y	Y	N <sup>2</sup>	Y	Y	Y
HCC	<a href="#">eTaskSync</a>	Source	License	N <sup>2</sup>	Y	N <sup>2</sup>	Y	Y	Y	Y	Y	N <sup>2</sup>	Y	Y	Y
Keil / arm	<a href="#">MDK-ARM</a>	Source	License	N <sup>2</sup>	Y	N <sup>2</sup>	Y	Y	Y	Y	Y	Y	Y	Y	Y
Mentor	<a href="#">Nucleus Kernel</a>	Source	License	N	N	N	Y	Y	Y	Y	Y	N <sup>2</sup>	N	Y	Y
Micrium	<a href="#">μC-OS</a>	Source	License	N <sup>2</sup>	Y	N <sup>2</sup>	Y	Y	Y	Y	Y	N <sup>2</sup>	Y	Y	Y
Micro Digital	<a href="#">SMX</a>	Source	License	N <sup>2</sup>	N <sup>2</sup>	N <sup>2</sup>	Y	Y	Y	Y	Y	N <sup>2</sup>	N <sup>2</sup>	N <sup>2</sup>	N <sup>2</sup>
NuttX	<a href="#">NuttX</a>	Open Source <sup>4</sup>	Free	Y	Y	N	Y	Y	Y	Y	Y	N	N	Y	Y
Prove & Run	<a href="#">ProvenCore-M</a>	Source	License	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
Quadros	<a href="#">RTXC Rtos</a>	Source	License	N	N	N	Y	Y	Y	Y	Y	Y	Y	Y	Y
Rowebots	<a href="#">Unison</a>	Source <sup>1</sup>	License	N	N	N	Y	Y	Y	Y	Y	Y	N	Y	Y
SEGGER	 <a href="#">embOS software expansion for STM32Cube (I-CUBE-EMBOS)</a>	Source	License	N <sup>6</sup>	N <sup>6</sup>	N <sup>6</sup>	N <sup>6</sup>	N <sup>6</sup>	N <sup>6</sup>	N <sup>6</sup>	Y	N <sup>6</sup>	N <sup>6</sup>	N <sup>6</sup>	N <sup>6</sup>
SEGGER	<a href="#">embOS</a>	Source	License	N <sup>2</sup>	Y	N <sup>2</sup>	Y	Y	Y	Y	Y	Y	Y	Y	Y
Sciopta	<a href="#">SCIOPTA 61508<sup>3</sup></a>	Source	License	N <sup>2</sup>	Y	N <sup>2</sup>	Y	Y	Y	Y	Y	Y	Y	Y	Y

1/ An open-source version with less features is also available

2/ Please contact supplier

3/ Safety certified RTOS for systems requiring certification

4/ BSD license


5/ ThreadX is part of the X-WARE IoT platform, which is [Thread](#) certified

6/ Available on STM32Cube, so porting is very easy



# STM32 – RTOS / kernel (3/3)

15

Provider	Solution name	Model	Cost	Availability											
				WB	F0	G0	F1	F2	F3	F4	F7	H7	L0	L1	L4/L4+
ST 	<a href="#">STM32Cube – FreeRTOS kernel</a>	Open source (MIT or modified GPL) <sup>5</sup>	Free	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
Wittenstein - High Integrity Systems	<a href="#">OpenRTOS</a> <sup>1</sup>	Source	License	N <sup>4</sup>	Y	N <sup>4</sup>	Y	Y	Y	Y	Y	N <sup>4</sup>	Y	Y	Y
Wittenstein - High Integrity Systems	<a href="#">SafeRTOS</a> <sup>2</sup>	Source	License	N <sup>4</sup>	Y	N <sup>4</sup>	Y	Y	Y	Y	Y	N <sup>4</sup>	N <sup>4</sup>	Y	Y
Wittenstein - High Integrity Systems	<a href="#">SafeRTOS CORE</a> <sup>3</sup>	Source	License	N <sup>4</sup>	Y	N <sup>4</sup>	Y	Y	Y	Y	Y	N <sup>4</sup>	N <sup>4</sup>	Y	Y
Zephyr	<a href="#">Zephyr kernel</a>	Open Source	Free <sup>6</sup>	N	Y	N	Y	Y	Y	Y	Y	N	Y	N	Y

1/ OpenRTOS is FreeRTOS with commercial support

2/ Safety certified RTOS for systems requiring certification

3/ SafeRTOS version without full safety certification/documentation

4/ Available on customer request. Please contact supplier

5/ FreeRTOS kernel license is MIT from V10, previous versions are under a modified GPL license. Included in STM32Cube MCU packages (Middleware\Third\_Party folder).

6/ Apache 2.0 license



# STM8 – RTOS / kernel

16

Provider	Solution name	Model	Cost	Availability	
				STM8S STM8AF	STM8L STM8AL
AtomThreads	<a href="#">AtomThreads RTOS</a>	Open source (BSD)	Free	Y	N <sup>1</sup>
Chibios	<a href="#">ChibiOS/RT</a>	Open source (GPL3) or Source	Free or License	Y	Y
CMX	<a href="#">CMX-Tiny+</a>	Source	License	Y	N <sup>1</sup>
SEGGER	<a href="#">embOS</a>	Source	License	Y	Y





Cryptology helps users ensure the security of data or authentication. This is a key element in ensuring the integrity of IoT applications for instance.

- **Many supported algorithms**

- Through third parties (some with certifications) or directly from ST

Often-seen acronyms	
Symmetric ciphering	Ciphering method that ensures the reuse of a unique key, both for encryption and decryption. Example: AES, DES, 3DES, ARC4, ...
Asymmetric ciphering	Ciphering method based on pair of key, a private and a public one. This also brings some kind of authentication: only the owner of private key can decrypt content that was encrypted with a public one. And people able to decrypt with public key can be sure it was encrypted by owner of private key. Example: ECDSA, RSA, ...
Hashing	Method to calculate a unique value for a given data content. This allows ensuring a content was not modified for instance. Example: MD5, SHA, ...



# STM32 – Crypto (1/2)


18

Provider	Solution name	Model	Cost	Availability											
				WB	F0	G0	F1	F2	F3	F4	F7	H7	L0	L1	L4/L4+
CypherBridge	<a href="#">uVPN SDK</a> IKEv1/IKEv2/IPsec	Source	License	N	N	N	N	N	N	Y	Y	N <sup>1</sup>	N	N	N
EUROS	<b>SSL/TLS</b> SSL v3, TLS 1.0, 1.1, 1.2	Binaries	License	N <sup>1</sup>	Y	N <sup>1</sup>	Y	Y	Y	Y	Y	Y	Y	Y	Y
EUROS	Cryptographic library, Verifiable Encryption manager 1. Encryption methods: - ARC4, - Blowfish, - Camellia, - CAST5 - DES, - DAS, - ECC, - MD4, - MD5 - RSA, - SHA1, - SHA256, - SHA512 - TwoFish, - Whirlpool, - HMAC96 - HMAC256 2. Coding: - Rice, - RLE (Run-length encoding) 3. Compression: - zlib, - libbz2, - LZ77, - LZW based (ZIP, GZ) - Huffman, - Shannon-Fano	Binaries	License	N <sup>1</sup>	Y	N <sup>1</sup>	Y	Y	Y	Y	Y	Y	Y	Y	Y
HCC	<b>Verifiable Encryption manager</b> AES, 3DES, DSS, EDH, MD5, RSA, SHA1, SHA256	Source	License	N <sup>1</sup>	Y	N <sup>1</sup>	Y	Y	Y	Y	Y	Y	Y	Y	Y
Oryx Embedded	<a href="#">CycloneCrypto</a> <b>Lite:</b> MD2, MD4, MD5, SHA-1, SHA-2, HMAC, RC4, DES, triple DES, AES, ECB, CBC, CFB, OFB, CTR, RSA, X.509 <b>Pro:</b> RIPEMD-128/160, Tigger/192, RC6, IDEA, Camellia, SEED, ARIA, CCM, GCM, Diffie-Hellman, DSA <b>Ultimate:</b> SHA-3, Keccak, CkaCha, Poly1305, ChaCha20Poly1305 AEAD, PKCS #5, ECC, ECDSA, ECDH, NIST-P, Brainpool	Open source (GPL2) or Source	Free or license	N <sup>1</sup>	Y	N <sup>1</sup>	Y	Y	Y	Y	Y	Y	Y	Y	Y
Rowebots	<a href="#">UNISON SSL/TLS Stack</a> AES, Blowfish, Triple-DES (3DES), DES, ARC4, Camellia, XTEA ECB, CBC, CFB, CTR, GCM, CCM MD2, MD4, MD5, SHA-1, SHA-224, SHA-256, SHA-384, SHA-512, RIPEMD-160 ECC	Source	License	N	N	N	Y	Y	Y	Y	Y	Y	N	Y	Y



# STM32 – Crypto (2/2)

19

Provider	Solution name	Model	Cost	Availability											
				WB	F0	G0	F1	F2	F3	F4	F7	H7	L0	L1	L4/L4+
SEGGER	<a href="#">emSecure</a> signatures	Source	License	N <sup>4</sup>	Y	N <sup>4</sup>	Y	Y	Y	Y	Y	Y	Y	Y	Y
SEGGER	<a href="#">emLib AES</a> and <a href="#">emLib DES</a>	Source	License	N <sup>4</sup>	Y	N <sup>4</sup>	Y	Y	Y	Y	Y	Y	Y	Y	Y
SEGGER	<a href="#">emFile encryption</a>	Source	License	N <sup>4</sup>	Y	N <sup>4</sup>	Y	Y	Y	Y	Y	Y	Y	Y	Y
ST	<a href="#">STM32 Cryptographic library</a> <sup>1, 2</sup> AES, DES, 3DES, ARC4, MD5, SHA1, SHA2, RSA sig, ECC Key gen, ECDSA, ...	Binaries	Free	N	N	N	Y	Y	Y	Y	N	N	N	Y	N
ST 	<a href="#">X-CUBE-CRYPTOLIB</a>	Binaries	Free	N <sup>5</sup>	Y	N <sup>5</sup>	Y	Y	Y	Y	Y	<u>Y</u> <sup>3</sup>	Y	Y	Y
wolfSSL	<a href="#">wolfCrypt</a> <sup>1</sup> , part of wolfSSL MD2, MD4, MD5, SHA-1, SHA-256, SHA-384, SHA-512, BLAKE2b, RIPEMD-160, Poly1305 AES (CBC, CTR, GCM, CCM), Camellia, DES, 3DES, ARC4, RABBIT, HC-128, ChaCha20 RSA, DSS (DSA), DH, EDH, NTRU ECDH-ECDSA, ECDHE-ECDSA, ECDH-RSA, ECDHE-RSA	Open source (GPL2) or Source	Free or license	N	N	N	N	Y	N	Y	Y	Y	Y	Y	Y

1/ Can benefit from hardware acceleration when available.

2/ Subject to trade regulations. See website.

3/ delivered as a patch

4/ please contact supplier

5/ Available on STM32Cube, so porting is very easy



# Middleware – SSL/TLS (1/2)


20

- Transport Layer Security (TLS) and its predecessor, Secure Sockets Layer (SSL), are cryptographic protocols that provide communications security.
- The Transport Layer Security protocol aims primarily to provide privacy and data integrity between a client and a server



# STM32 – SSL/TLS solutions

21

Provider	Solution name	Model	Cost	Availability						
				WB	F1	F2	F4	F7	H7	L4/L4+
arm	<a href="#">Mbed TLS<sup>1</sup></a>	Open source	Free	N	Y	Y	Y	Y	Y	Y
CypherBridge	<a href="#">Embedded TLS SDK (uSSL™)</a>	Source	License	N	N	Y	Y	Y	N <sup>2</sup>	N <sup>2</sup>
HCC	<a href="#">Verifiable SSL/TLS</a>	Source	License	N <sup>2</sup>	Y	Y	Y	Y	N <sup>2</sup>	N <sup>2</sup>
Oryx Embedded	<a href="#">CycloneSSL</a>	Open source (GPL2) or Source	Free or license	N <sup>2</sup>	Y	Y	Y	Y	Y	N <sup>2</sup>
SEGGER	<a href="#">emSSL</a>	Source	License	N <sup>2</sup>	Y	Y	Y	Y	N <sup>2</sup>	N <sup>2</sup>
ST 	<a href="#">STM32Cube – mbed TLS<sup>3</sup></a>	Open source	Free	N <sup>4</sup>	Y	Y	Y	Y	Y	Y
wolfSSL	<a href="#">Embedded SSL Library</a>	Open source (GPL2) or Source	Free or license	N <sup>2</sup>	N	Y	Y	Y	N <sup>2</sup>	Y

1/ Formerly known as PolarSSL. Apache 2.0 open source or GPL 2.0 open source license

2/ Please contact supplier

3/ Apache 2.0 license, included in STM32Cube MCU packages (\Middlewares\Third\_Party folder)

4/ Available on STM32Cube, so porting is very easy



# STM32 – SSL/TLS solution details

22

Provider	Solution name	Details
arm	<a href="#">Mbed TLS</a>	SSL version 3, TLS version 1.0, 1.1, 1.2, <a href="#">More...</a>
CypherBridge	<a href="#">Embedded TLS SDK (uSSL™)</a>	IETF standard SSL 3.0/TLS 1.2 protocols. Supported crypto and hash functions include: RSA, DSS, PKCSv1.5, OAEP, DES, 3DES, AES, RC4, SHA1, SHA2, MD2, MD4, MD5, RNG, X.509 certificate Processing
HCC	<a href="#">Verifiable SSL/TLS</a>	TLS 1.0, 1.1, 1.2 (RFC 5246), SSL3.0, DTLS 1.2 (RFC6347), 1.0 (RFC 4347), RFC 6520, HTTP over TLS (RFC 2818), HTTPS, FTPS, embedded encryption manager for full certificate management, cipher suites: DH/DHE/DSS/ECDHE/RSA, AES/RC4/3DES, SHA/Md5
Oryx Embedded	<a href="#">CycloneSSL</a>	Server and/or client operation, Supports TLS 1.0, 1.1, 1.2, 1.3 and SSL 3.0, Supports DTLS 1.0 and DTLS 1.2, Robust and efficient implementation, Supports ECC (Elliptic Curve Cryptography), Rich set of TLS cipher suites (including Suite B profile), RSA, Diffie-Hellman and ECDH key exchange algorithms, PSK (Pre-Shared Key) cipher suites, Supports stream ciphers, CBC block ciphers as well as AEAD ciphers (CCM and GCM), ChaCha20Poly1305 AEAD, Cryptographic library for common encryption algorithms (RC4, IDEA, DES, 3DES, AES, Camellia, SEED and ARIA), Supports MD5, SHA-1, SHA-256 and SHA-384 hash algorithms, SSL/TLS session resumption, PKIX path validation, Compliant with BSD socket API, Supports hardware accelerated encryption engines (when available), Flexible memory footprint. Built-time configuration to embed only the necessary features, Portable architecture (no processor dependencies), The library is distributed as a full ANSI C and highly maintainable source code
SEGGER	<a href="#">emSSL</a>	TLS 1.0, 1.1 and 1.2. <a href="#">More...</a>
ST	<a href="#">STM32Cube – mbed TLS</a>	SSL version 3, TLS version 1.0, 1.1, 1.2, <a href="#">More...</a>
wolfSSL	<a href="#">Embedded SSL Library</a>	SSL version 3.0 and TLS versions 1.0, 1.1, 1.2, and 1.3 (client and server), DTLS 1.0, 1.2 support (client and server) <a href="#">More...</a>

# Middleware – Bootloader / Secure Boot

23

A bootloader aims to enable firmware update in the field through a communication interface.

STM32 devices embed a built-in bootloader in system memory, supporting UART, SPI, I2C, CAN, USB interfaces.




Alternatively, developers can implement their own bootloader in flash memory (also called In-Application Programming)

ST also proposes an example for Secure Boot and Secure Firmware Update



# STM32 – Bootloader / Secure Boot

24

Provider	Solution name	Model	Cost	Availability											
				WB	F0	G0	F1	F2	F3	F4	F7	H7	L0	L1	L4/L4+
ST 	<a href="#">X-CUBE-IAP-USART<sup>3</sup></a>	Source	Free	N <sup>2</sup>	N <sup>2</sup>	N <sup>2</sup>	Y	N <sup>2</sup>	N <sup>2</sup>	N <sup>2</sup>	N <sup>2</sup>	N <sup>2</sup>	Y	N <sup>2</sup>	Y
ST 	<a href="#">X-CUBE-IAP-SD<sup>3</sup></a>	Source	Free	N <sup>2</sup>	Y	N <sup>2</sup>	N <sup>2</sup>	N <sup>2</sup>	N <sup>2</sup>	N <sup>2</sup>	N <sup>2</sup>	N <sup>2</sup>	N <sup>2</sup>	N <sup>2</sup>	Y
ST 	<a href="#">X-CUBE-SBSFU<sup>4</sup></a>	Source	Free	N	N	Y	N	N	N	Y	Y	N	N	N	Y
CypherBridge	<a href="#">uLoadXL SDK</a>	Source	License	N	N	N	N	Y	N	Y	Y	N <sup>1</sup>	N	N	N
eCosCentric	<a href="#">RedBoot</a>	Source	License	N	N	N	Y	Y	Y	Y	Y	N <sup>1</sup>	N	Y	Y
EUROS	Bootloader	Binaries	License	N <sup>1</sup>	Y	N <sup>1</sup>	Y	Y	Y	Y	Y	Y	Y	Y	Y
Feaser	<a href="#">OpenBLT</a>	Open source (GPL3) or Source	Free or Licence	N <sup>1</sup>	Y	N <sup>1</sup>	Y	Y	Y	Y	Y	N <sup>1</sup>	N <sup>1</sup>	N <sup>1</sup>	Y
HCC	<a href="#">Bootloaders</a>	Source	License	N <sup>1</sup>	Y	N <sup>1</sup>	Y	Y	Y	Y	Y	N <sup>1</sup>	Y	Y	Y
Simma Software	<a href="#">ssBL-target, ssBL-PC</a>	Source	License	N <sup>1</sup>	Y	N <sup>1</sup>	Y	Y	Y	Y	Y	N <sup>1</sup>	N <sup>1</sup>	N <sup>1</sup>	Y

1/ Please contact supplier

2/ Available on STM32Cube, so porting is very easy

3/ In-application programming example


4/ Secure Boot + Secure Firmware Update solution, with example





# STM32 – Bootloader / Secure Boot details

25

Provider	Solution name	Details
ST 	<a href="#">X-CUBE-SBSFU</a>	Secure Boot / Root of Trust, Secure firmware loader, Dual image support for safe firmware programing, Single image support for maximized user application size, Asymmetric and symmetric cryptographic schemes supported, Cryptography with integrated firmware, Secure Engine services, STM32 security mechanisms
CypherBridge	<a href="#">uLoadXL SDK</a>	Software updates and secure boot loader for embedded platforms. Safe install, to manage multiple images for an update, activation and safe-boot to rollback or factory version. The integrated boot loader provides secure root of trust and software integrity checks
eCosCentric	<a href="#">RedBoot</a>	Debug and bootstrap firmware
Feaser	<a href="#">OpenBLT</a>	UART, CAN, TCP/IP, USB, SD-CARD External flash and serial EEPROM
HCC	<a href="#">Bootloaders</a>	Serial, USB Device, USB Host , FAT Fail-safety, AES encryption
Simma Software	<a href="#">ssBL-target, ssBL-PC</a>	Supported protocols include CAN, J1939, J1708, CANopen, UDS, Bluetooth, USB, and RS232



# STM8 – Bootloader

26

Provider	Solution name	Model	Cost	Availability	
				STM8S STM8AF	STM8L STM8AL
Simma Software	<a href="#">ssBL-target, ssBL-PC</a>	Source	License	Y	N <sup>1</sup>

A file system is the way in which files are named and how they are placed logically for storage and retrieval. Several standards exist, such as FAT and JFFS2

- **Safety solutions**

- Ensuring data is not corrupted in any way (power supply removal, ...)

- **NAND memory access solutions**

- With error correction and wear-leveling



# STM32 – File system (1/2)


28

Provider	Solution name	Model	Cost	Availability											
				WB	F0	G0	F1	F2	F3	F4	F7	H7	L0	L1	L4/L4+
AWS	<a href="#">FreeRTOS+™ FAT SL<sup>3</sup></a>	Source	Free	N <sup>4</sup>	Y	N <sup>4</sup>	Y	Y	Y	Y	Y	N <sup>4</sup>	Y	Y	Y
arm	<a href="#">Mbed LittleFileSystem</a> , <a href="#">FATFileSystem</a>	Open source	Free	N <sup>4</sup>	Y	N <sup>4</sup>	Y	Y	Y	Y	Y	N	Y	Y	Y
ChaN	<a href="#">FatFS</a>	Open source (BSD)	Free	N <sup>4</sup>	Y <sup>2</sup>	N <sup>4</sup>	Y <sup>2</sup>	Y <sup>2</sup>	Y <sup>2</sup>	Y <sup>2</sup>	Y <sup>2</sup>	Y <sup>2</sup>	Y <sup>2</sup>	Y <sup>2</sup>	Y <sup>2</sup>
CMX	<a href="#">CMX-FFS</a>	Source	License	N <sup>4</sup>	Y	N <sup>4</sup>	Y	Y	Y	Y	Y	Y	Y	Y	N
CypherBridge	<a href="#">uFile</a>	Source	License	N	N	N	N	Y	N	Y	Y	N <sup>4</sup>	N	N	N
EmCraft	<a href="#">JFFS2</a> , <a href="#">YaFFS</a> , <a href="#">FAT</a> , <a href="#">NFS</a> , etc..	Open source (GPL)	Free	N	N	N	N	Y	N	Y	Y	N <sup>4</sup>	N	N	N
eCosCentric	<a href="#">eCosPro-YAFFS<sup>1</sup></a> , <a href="#">MMFS</a> , <a href="#">JFFS2</a>	Source	License	N	N	N	Y	Y	Y	Y	Y	N <sup>4</sup>	N	Y	Y
eForce	<a href="#">μC3-FileSystem</a>	Source	License	N <sup>4</sup>	Y	N <sup>4</sup>	Y	Y	Y	Y	Y	N <sup>4</sup>	Y	Y	Y
Express Logic	<a href="#">FileX</a> + LevelX	Source	License	N <sup>4</sup>	Y	N <sup>4</sup>	Y	Y	Y	Y	Y	N <sup>4</sup>	Y	Y	Y
EUROS	<a href="#">FMS</a> , <a href="#">FAT</a> , <a href="#">SafeFAT</a>	Binaries	License	N <sup>4</sup>	Y	N <sup>4</sup>	Y	Y	Y	Y	Y	Y	Y	Y	Y
HCC	FAT FS: <a href="#">FAT</a> , <a href="#">THIN</a> , <a href="#">SafeFAT</a> Flash FS: <a href="#">SafeFlash</a> , <a href="#">TINY</a> Flash Translation Layer: <a href="#">SafeFTL</a>	Source	License	N <sup>4</sup>	Y	N <sup>4</sup>	Y	Y	Y	Y	Y	Y	Y	Y	Y



# STM32 – File system (2/2)

29

Provider	Solution name	Model	Cost	Availability											
				WB	F0	G0	F1	F2	F3	F4	F7	H7	L0	L1	L4/L4+
Wittenstein - High Integrity Systems	<a href="#">CONNECT File System</a>	Source	License	N <sup>1</sup>	Y	N <sup>1</sup>	Y	Y	Y	Y	Y	N <sup>1</sup>	Y	Y	Y
Green Hills	<a href="#">μ-velOSity File System</a>	Source	License	N	N	N	Y	Y	Y	Y	Y	N <sup>1</sup>	N	Y	Y
Keil / arm	<a href="#">MDK-ARM Flash</a>	Source	License	N <sup>1</sup>	Y	N <sup>1</sup>	Y	Y	Y	Y	Y	N <sup>1</sup>	Y	Y	Y
Mentor Embedded	<a href="#">Nucleus Storage</a>	Source	License	N	N	N	Y	Y	Y	Y	Y	N <sup>1</sup>	N	Y	Y
Micrium	<a href="#">μC/FS</a>	Source	License	N <sup>1</sup>	Y	N <sup>1</sup>	Y	Y	Y	Y	Y	N <sup>1</sup>	Y	Y	Y
Micro Digital	<a href="#">smxFS</a>	Source	License	N <sup>1</sup>	Y	N <sup>1</sup>	Y	Y	Y	Y	Y	N <sup>1</sup>	N <sup>1</sup>	N <sup>1</sup>	N <sup>1</sup>
Quadros	<a href="#">RTXCfatfile</a>	Source	License	N <sup>1</sup>	Y	N <sup>1</sup>	Y	Y	Y	Y	Y	N <sup>1</sup>	Y	Y	Y
Rowebots	<a href="#">Unison FAT File System</a>	Source	License	N	N	N	Y	Y	Y	Y	Y	N <sup>1</sup>	N	Y	Y
SEGGER	<a href="#">emFile</a>	Source	License	N <sup>1</sup>	Y	N <sup>1</sup>	Y	Y	Y	Y	Y	N <sup>1</sup>	Y	Y	Y
ST	 <a href="#">STM32Cube - FatFS<sup>2</sup></a>	Open source (BSD)	Free	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y



# STM8 – File system

30

Provider	Solution name	Model	Cost	Availability	
				STM8S STM8AF	STM8L STM8AL
ChaN	<a href="#">Petit FatFS</a>	Open source (BSD)	Free	N <sup>1</sup>	Y <sup>2</sup>
HCC	<a href="#">FAT THIN</a>	Source	License	Y	Y
SEGGER	<a href="#">emFile</a>	Source	License	Y	Y



# Middleware – USB

31

Universal Serial Bus requires a dedicated software stack. This serial bus is organized in a star topology with host and device roles, with the host organizing the traffic. Several device classes are specified, in order to ease communication in different application cases.

Often-seen acronyms	
OTG	On-The-Go: An OTG peripheral can switch host and device roles on the fly
HUB	Defines what protocols to implement to build a hub application
MS	Mass storage: Protocols to interact with storage block devices (for files)
HID	Human interface device: Protocols for peripherals interacting with humans (mouse, keyboard, etc.)
CDC	Communication device class: Protocols for serial communications, different sub-classes define details, for instance ACM for a standard COM port, or ECM for modems
Printer	Defines what protocols to implement to build a printer application
Audio	Defines what protocols to implement to build an audio application (microphone, headset, etc.)
DFU	Device firmware upgrade: Protocols to implement firmware upgrade ability
USB-PD	USB Power Delivery
TCPM	USB Type-C Port Manager



# STM32 – USB solutions (1/2)

32

Provider	Solution name	Model	Cost	Availability											
				WB	F0	G0	F1	F2	F3	F4	F7	H7	L0	L1	L4/L4+
Chibios	<a href="#">ChibiOS/HAL</a>	Open source (GPL3) or Source	Free or License	N <sup>1</sup>	Y	N <sup>1</sup>	Y	Y	Y	Y	Y	N <sup>1</sup>	Y	Y	Y
CMX	CMX-USB <a href="#">Device</a> , <a href="#">Host</a>	Source	License	N <sup>1</sup>	Y	N <sup>1</sup>	Y	Y	Y	Y	Y	N <sup>1</sup>	Y	Y	N
eCosCentric	<a href="#">eCosPro-Host</a> , <a href="#">Device</a>	Source	License	N <sup>1</sup>	N	N <sup>1</sup>	Y	Y	Y	Y	Y	N <sup>1</sup>	N	Y	Y
EUROS	<a href="#">USB Host &amp; Device</a>	Binaries	License	N <sup>1</sup>	Y	N <sup>1</sup>	Y	Y	Y	Y	Y	Y	N	Y	Y
EmCraft	<a href="#">Linux USB Host</a>	Open source (GPL)	Free	N	N	N	N	Y	N	Y	N	N <sup>1</sup>	N	N	N
Express Logic	<a href="#">USBX</a>	Source	License	N <sup>1</sup>	Y	N <sup>1</sup>	Y	Y	Y	Y	Y	N <sup>1</sup>	Y	Y	Y
HCC	<a href="#">HCC-USB</a> Host, Device	Source	License	N <sup>1</sup>	Y	N <sup>1</sup>	Y	Y	Y	Y	Y	N <sup>1</sup>	Y	Y	Y
Keil / arm	<a href="#">MDK-ARM USB</a>	Source	License	N <sup>1</sup>	Y	N <sup>1</sup>	Y	Y	Y	Y	Y	N <sup>1</sup>	Y	Y	Y
Mentor Embedded	<a href="#">Nucleus USB</a>	Source	License	N	N	N	Y	Y	Y	Y	Y	N <sup>1</sup>	N	Y	Y
Micrium	<a href="#">USB Host</a> , <a href="#">USB Device</a>	Source	License	N	Y	N	Y	Y	Y	Y	Y	N <sup>1</sup>	Y	Y	Y
Micro Digital	<a href="#">smxUSB</a>	Source	License	N <sup>1</sup>	Y	N <sup>1</sup>	Y	Y	Y	Y	Y	N <sup>1</sup>	N <sup>1</sup>	N <sup>1</sup>	N <sup>1</sup>
Quadros	<a href="#">RTXCusb</a>	Source	License	N <sup>1</sup>	N <sup>1</sup>	N <sup>1</sup>	Y	Y	Y	N <sup>1</sup>	N <sup>1</sup>	N <sup>1</sup>	N <sup>1</sup>	N <sup>1</sup>	N <sup>1</sup>





# STM32 – USB solutions (2/2)

33

Provider	Solution name	Model	Cost	Availability												
				WB	F0	G0	F1		F2	F3	F4	F7	H7	L0	L1	L4/L4+
							Others	F105 F107								
Rowebots	<a href="#">Unison USB System</a>	Source	License	N	N	N	Y		Y	Y	Y	N	N <sup>1</sup>	Y	N	Y
SEGGER	<a href="#">emUSB Device, emUSB Host</a>	Source	License	N <sup>1</sup>	Y	N <sup>1</sup>	Y		Y	Y	Y	Y	N <sup>1</sup>	Y	Y	Y
ST	USB FS device library	Source	Free	N	<u>Y</u>	N	<u>Y</u>	N	N	<u>Y</u>	N	N	N <sup>1</sup>	N	<u>Y</u>	N
ST	USB FS&HS Host&Device lib	Source	Free	N	N	N	N	<u>Y</u>	<u>Y</u>	N	<u>Y</u>	N	N <sup>1</sup>	N	N	N
ST 	<a href="#">STM32Cube – USB Host&amp;Device<sup>4</sup></a>	Source	Free	Y <sup>2</sup>	Y <sup>2</sup>	N	Y <sup>2</sup>		Y	Y <sup>2</sup>	Y	Y	Y	Y <sup>2</sup>	Y <sup>2</sup>	Y <sup>2</sup>
ST 	<a href="#">STM32Cube – USB-C Power Delivery<sup>4</sup></a>	Source	Free	N	N	Y	N		N	N	N	N	N	N	N	N
ST	<a href="#">X-CUBE-USB-PD<sup>5</sup></a>	Binary	Free	N <sup>6</sup>	Y	N <sup>6</sup>	N <sup>6</sup>		N <sup>6</sup>	N <sup>6</sup>	N <sup>6</sup>	N <sup>6</sup>	N <sup>6</sup>	N <sup>6</sup>	N <sup>6</sup>	N <sup>6</sup>
Thesycon	<a href="#">Embedded USB Device</a>	Source	License	N <sup>1</sup>	N <sup>1</sup>	N <sup>1</sup>	N <sup>1</sup>		Y	N <sup>1</sup>	Y	Y	N <sup>1</sup>	N <sup>1</sup>	N <sup>1</sup>	N <sup>1</sup>
Zephyr	<a href="#">USB device stack</a>	Source	Free <sup>3</sup>	N	Y	N	Y		N	Y	Y	N	N	N	N	Y

1/ Please contact supplier

2/ Device only

3/ Apache 2.0 license

4/ Included in STM32Cube MCU packages (Middleware\Third\_Party folder)

5/ Examples for [P-NUCLEO-USB001](#) and [P-NUCLEO-USB002](#) Nucleo Packs, and for [ON-FUSB3-STM32](#)

6/ Available on STM32Cube, so porting is very easy



# STM32 – USB solutions details (1/2)



34

Provider	Solution name	Details
Chibios	<a href="#">ChibiOS/HAL</a>	Device: HID, MS, CDC
CMX	CMX-USB <a href="#">Device</a> , <a href="#">Host</a>	Device: HID, MS, CDC (ACM, ECM, RNDIS), Audio, Midi, MTP, PHDC Host: HID, MS, CDC (ACM, ECM, RNDIS, OBEX), Audio, Midi, Printer, HUB
eCosCentric	<a href="#">eCosPro-Host, Device</a>	Device: MS, CDC (ACM, ECM, EEM, RNDIS) Host: MS, CDC (ACM, ECM, EEM, RNDIS), Hub
EUROS	<a href="#">USB Host &amp; Device Stack</a>	Device: HID, MS, CDC (ACM, ECM) Host: HID, MS, CDC (ACM, ECM), HUB
Express Logic	<a href="#">USBX</a>	Device: HID, MS, CDC (ACM, ECM, RNDIS), Still Image, PTP, PictBridge, DFU, PIMA w/MTP Host: HID, MS, CDC (ACM, ECM), Audio, Printer, HUB, ASIX, PIMA, GSER, PROLIFIC
EmCraft	<a href="#">Linux USB Host</a>	Host: HID, MS, CDC (ACM, ECM), HUB
HCC	<a href="#">HCC-USB</a>	Device: Connectivity (HID), File System & Storage (Mass Storage), Ethernet & Serial Interface (RNDIS, CDC-ACM, CDC-ECM, CDC-EEM, CDC-NCM), Audio (AUDIO, MIDI), Multi-media & Printing (MTP, Pictbridge, Printer PCL), Healthcare (PHDC) Host: Connectivity (HID, Hub, lan7500, lan9500), File System & Storage (Mass Storage), Ethernet & Serial Interface (RNDIS, CDC-ACM, CDC-ECM, CDC-EEM, CDC-FTDI, CDC-NCM), Audio (AUDIO, MIDI), Multi-media & Printing (MTP, Printer)
Keil / arm	<a href="#">MDK-ARM USB</a>	Device: HID, MS, CDC (ACM), Audio Host: HID, MS
Mentor Embedded	<a href="#">Nucleus USB</a>	Device: HID, MS, CDC (ACM, ECM) Host: HID, MS, CDC (ACM, ECM), HUB



# STM32 – USB solutions details (2/2)

35

Provider	Solution name	Details
Micrium	<a href="#">USB Host</a> , <a href="#">USB Device</a>	Device: HID, MS, CDC (ACM), Audio, PHDC (Medical) Host: HID, MS, CDC (ACM), Audio, Printer, PHDC (Medical)
Micro Digital	<a href="#">smxUSB</a>	Device: HID, MS, CDC (ACM, RNDIS), Audio+Midi, Video, PTP, MTP, DFU Host: HID, MS, CDC (ACM, ECM, Ethernet Adapter, WiFi and wireless modem,), Audio+Midi, Video, Printer, HUB
Quadros	<a href="#">RTXCusb</a>	Device: MS, CDC (ACM, ECM, RNDIS) Host: HID, MS, CDC (ACM), HUB
Rowebots	<a href="#">Unison USB System</a>	Device: MS, CDC (ACM) Host: MS, CDC (ACM), HUB, others on demand (inc . PHDC)
SEGGER	<a href="#">emUSB Device</a> , <a href="#">emUSB Host</a>	Device: HID, MS, CDC (ACM), RNDIS, Printer, MTP Host: HID, MS, CDC (ACM), HUB
ST	<a href="#">USB FS device library</a>	Device: HID, MS, CDC (ACM), Audio, DFU
ST	<a href="#">USB FS&amp;HS Host&amp;Device</a>	Device: HID, MS, CDC (ACM), Audio, DFU Host: HID, MS
ST	 <a href="#">STM32Cube – USB Host&amp;Device</a>	Device: HID, MS, CDC (ACM), Audio, DFU Host: HID, MS, CDC (ACM), Audio, MTP
ST	 <a href="#">STM32Cube – USB-C Power Delivery<sup>4</sup></a>	USB PD 3.0, PPS, FRS, TCPi, TCPM, source, sink, DRP, USB Type-C CC logic
Thesycon	<a href="#">Embedded USB Device</a>	Device: Audio, CCID, Mass Storage, network, HID, CDC (ACM)
Zephyr	<a href="#">USB device stack</a>	Device: CDC (ACM), DFU



# Middleware – TCP/IP (1/2)

36

- TCP and IP were developed by a US Department of Defense research project to connect a number of different networks designed by different vendors into a network of networks (the Internet).
- It was initially successful because it delivered a few basic services that everyone needs (file transfer, electronic mail, remote logon) across a very large number of client and server systems, and is now widely deployed.



# Middleware – TCP/IP (2/2)

37

## Often-seen acronyms

ARP	Address resolution protocol: Provides physical address from IP address
IP	Internet protocol: Primary protocol in Internet Protocol Suite. 2 flavors: IPv4 and IPv6. IPv4 will disappear as it only supports up to $2^{32}$ addresses, not enough for future needs, while IPv6 supports $2^{128}$
6LoWPAN	IPv6 over low-power wireless personal area networks: Provides IPv6 connectivity to low-rate wireless networks
IPSec	Internet protocol security: Secured version of IP, using cryptography
TCP	Transmission control protocol: Provides reliable, ordered delivery of a stream of bytes
UDP	User datagram protocol: Provides unreliable service. Datagrams may arrive in any order, duplicated, or may be missing. Used for time-sensitive applications, when data drop is better than delay
DHCP	Dynamic host configuration protocol: Provides means to allocate IP address dynamically
DNS	Domain name system: Translates domain names meaningful to humans into numerical IP ones
FTP	File transfer protocol: Provides means to copy files from one host to another
TFTP	Trivial file transfer protocol: Similar to FTP, but based on UDP, and simpler (for example, no directory)
SMTP	Simple mail transfer protocol: Used to send e-mail to a server
POP	Post office protocol: Used to retrieve e-mail from a server
HTTP	Hypertext transfer protocol: Used by web browsers
SSL/TLS	Transport layer security: Secured container for application protocols using cryptography. Example: HTTPS means HTTP over SSL, FTPS, etc.. IPSec applies cryptography at a lower level than SSL/TLS, making it more universal. However SSL is widely used.



# STM32 – TCP/IP solutions (1/2)


38

Provider	Solution name	Model	Cost	Availability						
				WB	F1	F2	F4	F7	H7	L4/L4+
AWS	<a href="#">FreeRTOS+™ TCP<sup>2</sup></a>	Source	Free	N <sup>1</sup>	Y	Y	Y	Y	N <sup>1</sup>	N <sup>1</sup>
AWS	<a href="#">FreeRTOS+™ UDP<sup>2</sup></a>	Source	Free	N <sup>1</sup>	Y	Y	Y	Y	N <sup>1</sup>	N <sup>1</sup>
CMX	<a href="#">CMX-TCP/IP</a>	Source	License	N <sup>1</sup>	Y	Y	Y	Y	N <sup>1</sup>	N <sup>1</sup>
CMX	<a href="#">CMX-MicroNet</a>	Source	License	N <sup>1</sup>	Y	Y	Y	Y	N <sup>1</sup>	N <sup>1</sup>
CypherBridge	<a href="#">Embedded SSH SDK</a> (uSSH™)	Source	License	N <sup>1</sup>	N	Y	Y	Y	N <sup>1</sup>	N <sup>1</sup>
EUROS	<a href="#">TCP/IP stack</a>	Binaries	License	N <sup>1</sup>	Y	Y	Y	Y	Y	N <sup>1</sup>
Express Logic	<a href="#">NetX</a> and <a href="#">NetX Duo</a> IPv4/IPv6 and NetX Secure SSL/TLS/DTLS	Source	License	N <sup>1</sup>	Y	Y	Y	Y	N <sup>1</sup>	Y
eCosCentric	<a href="#">SecureSockets</a> , <a href="#">SecureShell</a> <a href="#">eCosPro stacks</a>	Source	License	N <sup>1</sup>	Y	Y	Y	Y	N <sup>1</sup>	N <sup>1</sup>
eForce	<a href="#">µNet3</a>	Source	License	N <sup>1</sup>	Y	Y	Y	Y	N <sup>1</sup>	N <sup>1</sup>
EmCraft	<a href="#">Linux TCP/IP stack</a>	Open source (GPL)	Free	N	N	Y	Y	Y	N <sup>1</sup>	N
Green Hills	<a href="#">µ-velOSity TCP/IP v4/v6</a>	Source	License	N <sup>1</sup>	Y	Y	Y	Y	N <sup>1</sup>	N <sup>1</sup>
Wittenstein - High Integrity Systems	<a href="#">CONNECT TCP</a>	Source	License	N <sup>1</sup>	Y	Y	Y	Y	N <sup>1</sup>	N <sup>1</sup>



# STM32 – TCP/IP solutions (2/2)

39

Provider	Solution name	Model	Cost	Availability						
				WB	F1	F2	F4	F7	H7	L4/L4+
HCC	<a href="#">MISRA HCC-TCP/IP v4/v6</a>	Source	License	N <sup>3</sup>	Y	Y	Y	Y	N <sup>3</sup>	Y
Keil / arm	<a href="#">MDK-ARM TCPNET</a>	Source	License	N <sup>3</sup>	Y	Y	Y	N <sup>1</sup>	N <sup>3</sup>	Y
Mentor Embedded	<a href="#">Nucleus Network</a>	Source	License	N <sup>3</sup>	Y	Y	Y	Y	N <sup>3</sup>	Y
Micrium	<a href="#">μC/TCP-IP</a>	Source	License	N <sup>3</sup>	Y	Y	Y	Y	N <sup>3</sup>	Y
Micro Digital	<a href="#">smxNS</a> and <a href="#">smxNS6 (Dual IPv6/v4)</a>	Source	License	N <sup>3</sup>	Y	Y	Y	Y	N <sup>3</sup>	N <sup>3</sup>
Oryx Embedded	<a href="#">CycloneTCP</a>	Open source (GPL2) or source	Free or license	N <sup>3</sup>	Y	Y	Y	Y	Y	Y
Quadros	<a href="#">RTXC Quadnet</a>	Source	License	N <sup>3</sup>	Y	Y	Y	Y	N <sup>3</sup>	N <sup>3</sup>
Rowebots	<a href="#">Unison TCP-IP/v4-v6</a>	Source	License	N <sup>3</sup>	N	Y	Y	Y	N <sup>3</sup>	N <sup>3</sup>
SEGGER	<a href="#">embOS/IP</a>	Source	License	N <sup>3</sup>	Y	Y	Y	Y	Y	Y
SICS	<a href="#">LwIP</a>	Open source (BSD)	Free	N	<u>Y</u> <sup>1</sup>	<u>Y</u> <sup>1</sup>	<u>Y</u> <sup>1</sup>	N	N	N
ST 	<a href="#">STM32Cube – LwIP<sup>2</sup></a>	Open source (BSD)	Free	N <sup>5</sup>	Y	Y	Y	Y	Y	Y
Zephyr	<a href="#">Zephyr Networking</a>	Source	Free <sup>4</sup>	N	Y	Y	Y	Y	Y	N

1/ A port to STM32 was implemented by ST

2/ A port to STM32 was implemented by ST, as part of STM32Cube, Licensing model cascaded to end-user.

Included in STM32Cube MCU packages (\Middlewares\Third\_Party folder)

3/ Please contact supplier

4/ Apache 2.0 license

5/ Available on STM32Cube, so porting is very easy



# STM32 – TCP/IP solution details (1/2)

40


Provider	Solution name	Details
AWS	<a href="#">FreeRTOS+™ TCP</a>	ARP, DHCP, DNS, LLNMR, NBNS, UDP
AWS	<a href="#">FreeRTOS+™ UDP</a>	ARP, DHCP and DNS
CMX	<a href="#">CMX-TCP/IP</a>	PPP, PPPoE, ARP, IGMP, ICMP, IPv4, UDP, TCP, DHCP(cs), DNS, FTP(cs), IMAP4, NAT, POP3(c), SMTP, SNMP, SNTP, Telnet(s), SSL/TLS, SSH, TFTP(cs), HTTP(s)
CMX	<a href="#">CMX-MicroNet</a>	PPP, ARP, IGMP, ICMP, IPv4, UDP, TCP, DHCP(c), DNS, FTP(cs), POP3(c), SMTP, SNMP, SNTP, Telnet(s), SSL/TLS, TFTP (c), HTTP(s)
CypherBridge	<a href="#">Embedded SSH SDK (uSSH™)</a>	SSH 2.0, Configurable DSS and RSA asymmetric session, Configurable crypto with 3DES AES and blowfish support, SCP, SFTP
EUROS	<a href="#">TCP/IP stack</a>	PPP, PPPoE, ARP, IGMP, ICMP, IPv4, IPv6, IPSec/IKE, UDP, TCP, DNS, DHCP(cs), FTP(cs), NAT, POP3(c), SMTP, SNMP, SNTP, Telnet(s), SSL/TLS, TFTP, HTTP(cs), SFTP, FTPS, SSH
Express Logic	<a href="#">NetX</a> and <a href="#">NetX Duo</a> IPv4/IPv6	PPP, ARP, IGMP, ICMP, IPv4, IPv6, IPSec/IKE, UDP, TCP, DNS, DHCP(c), FTP(cs), NAT, POP3(c), SMTP, SNMP, SNTP, Telnet(s), TFTP, HTTP(s)
eCosCentric	<a href="#">SecureSockets</a>	SSH2
eCosCentric	<a href="#">SecureShell</a>	SSL/TLS
eCosCentric	<a href="#">eCosPro stacks</a>	PPP, ARP, ICMP, UDP, TCP, IPv4, IPv6, DHCP, BOOTP, SMTP, TFTP, FTP(c+s), HTTP, SNMP, NTP, mDNS, Bonjour
eForce	<a href="#">uNet3</a>	PPP, ARP, IGMP, ICMP, IPv4, IPv6, UDP, TCP, DNS, DHCP(c), FTP(s), HTTP(cs), TFTP, SNMP, SNTP, Telnet(s), POP3(c), SMTP, SSL/TLS
EmCraft	<a href="#">Linux TCP/IP stack</a>	PPP, DNS, NAT, SSH (cs), DHCP (cs), SNMP (cs), Telnet (cs), FTP (cs), HTTP (cs)
HCC	<a href="#">MISRA HCC-TCP/IP v4/v6</a>	ARP, ICMP, IPv4, IPv6, UDP, TCP, DNS, DHCP(cs), FTP(cs), SMTP, TFTP(s), HTTP(s), SLIP, PPP, PPPoE, ARP, IGMP, ICMP, IPSec/IKE, NAT, POP3(c), SNMP, SNTP, Telnet(s), HTTP(s), RTP/RTCP
Wittenstein - High Integrity Systems	<a href="#">CONNECT TCP</a>	TCP, UDP, ARP, ICMP, IPv4, DNS, DHCP, FTP, TFTP, HTTP, LLNMR, NBNS, Auto-IP, standard sockets or callback interface





# STM32 – TCP/IP solution details (2/2)

41

Provider	Solution name	Details
Green Hills	<a href="#">μ-velOSity TCP/IP v4/v6</a>	ARP, ICMP, IGMP, IPv4, IPv6, IPv4/6, UDP, TCP, DNS, DHCP(c),
Keil / arm	<a href="#">MDK-ARM TCPNET</a>	SLIP, PPP, ARP, IPv4, ICMP, UDP, TCP, DNS, DHCP(c), FTP(s), SMTP, SNMP, Telnet(s), TFTP(s), HTTP(s)
SICS	<a href="#">LwIP</a>	PPP, ARP, ICMP, IPv4, UDP, TCP, DHCP(c), IPv6
Mentor Embedded	<a href="#">Nucleus Kernel</a>	PPP, PPPoE, ARP, IGMP, ICMP, IPv4, IPv6, IPSec/IKE, UDP, TCP, DHCP(c), FTP(cs), NAT, SNMP, SNTP, Telnet(cs), SSL/TLS, TFTP (cs), HTTP(cs)
Micrium	<a href="#">μC/TCP-IP</a> (and <a href="#">μC/SSL</a> )	ARP, ICMP, IPv4, UDP, TCP, DNS, DHCP(c), FTP(cs), SMTP, POP3(c), SNTP, Telnet(s), SSL/TLS, TFTP, HTTP(s)
Micro Digital	<a href="#">smxNS</a> and <a href="#">smxNS6</a> (Dual IPv6/v4)	SLIP, PPP, PPPoE, ARP, IGMP, ICMP, IPv4, IPv6, IPv4/6, UDP, TCP, DNS, mDNS, DHCP(cs), FTP(cs), NAT, POP3(c), SMTP, SNMP, SNTP, Telnet(s), SSL/TLS, TFTP, HTTP(cs), SSH
Oryx Embedded	<a href="#">CycloneTCP</a>	Dual stack (IPv4 and/or IPv6), Built-in support for multiple network interfaces, BSD style socket API, Blocking/non-blocking socket, operation and event-driven functions (select and poll), Efficient data transfer (zero copy), Well-crafted TCP module with selective ACK and congestion control, Raw socket interface, Multicast support (IGMPv2 and MLDv1), IP fragmentation and reassembly, Flexible memory footprint, Portable architecture, Host name resolution (DNS client), DHCP and SLAAC auto-configuration, SMTP client, FTP client and server, TFTP client and server, Web server with SSI and CGI scripting, HTTP/2 client, MQTT and MQTT-SN clients, CoAP client, SNMPv1/v2c/v3 agent, WebSocket client and server
Quadros	<a href="#">RTXC Quadnet</a>	PPP, PPPoE, ARP, IGMP, ICMP, IPv4, IPv6, IPSec/IKE, UDP, TCP, DNS, DHCP(cs), FTP(cs), NAT, POP3(c), SMTP, SNMP, SNTP, Telnet(s), SSL/TLS, TFTP, HTTP(cs), UPnP, Prioritized Packets Handling
Rowebots	<a href="#">Unison TCP-IP/v4-v6</a>	PPP, ARP, ICMP, IGMP, IPv4, IPv6, IPv4/6, 6LoWPan, IPSec, UDP, TCP, DNS, DHCP(cs), SMTP(c), SNMP, Telnet(s), TFTP(cs), HTTP(cs), NAT
SEGGER	<a href="#">embOS/IP</a>	PPP, PPPoE, ARP, ICMP, IGMP, IPv4, UDP, TCP, DNS, DHCP(cs), FTP(cs), SMTP(c), SNTP(c), Telnet(s), TFTP(cs), HTTP(s), PTP IEEE 1588
SICS	<a href="#">Contiki/uIP6</a>	IPv6, 6LoWPAN
ST	 <a href="#">STM32Cube - LwIP</a>	PPP, ARP, ICMP, IPv4, UDP, TCP, DHCP(c), IPv6
Zephyr	<a href="#">Zephyr Networking</a>	IPv4, IPv6 (dual stack support), ICMPv4, ICMPv6, UDP, TCP, HTTP, MQTT, CoAP, LWM2W, RPL, DNS/ 6LoWPAN



# Middleware – 2.4GHz – Bluetooth

42

Bluetooth is a wireless communication technology for exchanging data over short distances, typically used in the mobile world between phones and accessories.

- **Solutions with STM32WB or STM32 + Bluetooth transceiver**
  - Several solutions are available, using STM32WB or STM32 with SPBTLE-RF, BlueNRG-MS or other components

Often-seen acronyms	
Bluetooth Low Energy	(Also called Bluetooth Smart) very interesting for application running out of battery (coin cell type) as power consumption is very low, with a lower data rate and connection time
Classic Bluetooth	Original Bluetooth before Bluetooth Low Energy appearance. Still required for certain Audio applications.
Dual mode devices	Devices able to handle Classic Bluetooth, and Bluetooth Low Energy. Also called Bluetooth Smart ready
HCI	Host/controller interface: Standardized communication between controller and radio chips
SPP	Serial port profile: Profile that emulates serial line over Bluetooth
A2DP	Advanced audio distribution profile: Profile to stream high-quality audio
HSP	Headset profile: Profile to implement a basic headset application
HDP	Health device profile: Profile designed to facilitate transmission and reception of medical data
HFP	Hands-free profile: Typical profile used in cars for hands-free phone use



# STM32 – Bluetooth solutions

43

Provider	Solution name	Model	Cost	Availability											
				WB	F0	G0	F1	F2	F3	F4	F7	H7	L0	L1	L4/L4+
ST 	<a href="#">X-CUBE-BLE<sup>1</sup></a>	Binaries and Source	Free	N.A.	N <sup>1</sup>	N <sup>1</sup>	N <sup>1</sup>	N <sup>1</sup>	N <sup>1</sup>	Y	N <sup>1</sup>	N <sup>1</sup>	Y	N <sup>1</sup>	Y
ST	<a href="#">I-CUBE-nRF51DRV</a>	Binaries and Source	Free	N.A.	N <sup>1</sup>	N <sup>1</sup>	N <sup>1</sup>	N <sup>1</sup>	N <sup>1</sup>	N <sup>1</sup>	N <sup>1</sup>	N <sup>1</sup>	Y	N <sup>1</sup>	N <sup>1</sup>
ST 	<a href="#">STM32CubeL4-BLE<sup>2</sup></a>	Source	Free	N.A.	N <sup>1</sup>	N <sup>1</sup>	N <sup>1</sup>	N <sup>1</sup>	N <sup>1</sup>	N <sup>1</sup>	N <sup>1</sup>	N <sup>1</sup>	N <sup>1</sup>	N <sup>1</sup>	Y
ST 	<a href="#">STM32Cube – BLE<sup>3</sup></a>	Source	Free	Y	N	N	N	N	N	N	N	N	N	N	N

1/ STM32L0 + BlueNRG-MS. Available on STM32Cube so porting is very easy

2/ point to point and HeartRate profile example running on running on [B-L475E-IOT01A](#) with ST [SPBTLE-RF](#)

3/ Certified BLE stack + HCI, certified OpenThread binary stack, BLE/OpenThread concurrent stack, BLE profiles and services, certified 802.15.4 MAC included in STM32Cube MCU package (\Middlewares\ST folder)



# STM32 – Bluetooth solutions

44

Provider	Solution name	Model	Cost	Availability											
				WB	F0	G0	F1	F2	F3	F4	F7	H7	L0	L1	L4/L4+
arm	<a href="#">Mbed BLE<sup>4</sup></a>	Source	Free	N	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
Alpwise	<a href="#">OpenSynergy Blue SDK</a>	Binaries or Source	License + royalties	N	N <sup>2</sup>	N <sup>2</sup>	Y	Y	N <sup>2</sup>	Y	Y	N <sup>2</sup>	N <sup>2</sup>	N <sup>2</sup>	Y
Alpwise	<a href="#">BlueWiseLE® bluetooth 5 Link Layer stack</a>	Binaries or Source	License + royalties	N	Y	Y	Y	Y	Y	Y	Y	Y <sup>1</sup>	Y	Y	Y
A&W	<a href="#">PhoneLink</a>	Binaries or Source	License and/or royalties	N	N	N	Y	Y	N	Y	Y	Y <sup>1</sup>	N	N	N
Clarinox	<a href="#">ClarinoxBlue<sup>8</sup></a>	Binaries or Source	License and/or royalties	N	Y <sup>1</sup>	Y <sup>1</sup>	Y <sup>1</sup>	Y <sup>1</sup>	Y <sup>1</sup>	Y	Y <sup>1</sup>	Y <sup>1</sup>	Y <sup>1</sup>	Y <sup>1</sup>	Y <sup>1</sup>
EUROS	BLE stack <sup>6</sup>	Binaries	License	N	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
Rowebots	<a href="#">UNISON Bluetooth System</a>	Source	License	N	N	N	Y	Y	Y	Y	Y	Y <sup>1</sup>	N	Y	Y
SEARAN	<a href="#">dotStack</a>	Binaries or Source	License and/or royalties	N	Y	Y	Y	Y	Y	Y	Y	Y <sup>1</sup>	Y	Y	Y
Zephyr	<a href="#">Bluetooth</a>	Source	Free <sup>7</sup>	N	N	N	Y	N	Y	Y	N	N	N	N	Y

1/ Available on customer request. Please contact supplier

2/ Available on specific conditions. Please contact supplier

4/ Support BLE, Heart Rate Service, iBeacon on various ST boards including [DISCO-L475VG-IOT01A](#), [X-NUCLEO-IDB05A1](#) with STM32 Nucleo boards

6/ SmartBond™ DA14681 Bluetooth® low energy SoC adapted to the EUROS RTOS


7/ Apache 2.0 license

8/ ClarinoxBlue supports multiple RTOS and many wireless radio supporting HCI (UART, USB)



# STM32 – Bluetooth solution details

45

Provider	Solution name	Details
ST	<a href="#"><u>X-CUBE-BLE1</u></a>	BT4.0, BT4.1 All profiles supported
ST	<a href="#"><u>I-CUBE-nRF51DRV</u></a>	BT4.0, BT4.1 All profiles supported
ST 	<a href="#"><u>STM32Cube – BLE</u></a>	BT 5.0 PTS Profiles/Services: Client : Heart Rate Profile (HRP): Collector, Location and Navigation (LNP), Time Profile (TIP), Weight Scale Profile (WSP), Alert Notification Profile (ANP), Health thermometer Profile (HTP): Collector, Phone Alert Status Profile (PASP), Find Me Profile (FMP), Proximity Profile (Px Monitor, PXP), HID Over GATT Profile (HOGP): Boot Host, Report Host Server : Heart Rate Profile (HRP): Heart Rate Sensor, Device Information Service (DIS), Link Loss (LLS), Battery Service (BAS), Tx Power Service (TPS), Scan Parameters (ScPP), Location and Navigation (LNS), Immediate Alert (IAS), Next DST Change Service (NDCS), Reference Time Update Service (RTUS), Current Time Service (CTS), Weight Scale Profile (WSP), Alert Notification Profile (ANP), Environmental Sensing (ESS), Blood Pressure Profile (BLP), Bond Management Service (BMS), Cycling Power Profile (CPP), Cycling Speed and Cadence Profile (CSCP), Health thermometer Profile (HTP): Thermometer, Automation IO Service (AIO), HTTP Proxy Service (HPS), Phone Alert Service (PASS), Find Me Profile (FMP + IAS), Environmental Sensing (ESS) Proximity Profile (Px Reporter, PXP), Running and Speed Cadence Service (RSCS), HID Service (HIDS), Glucose Service (GLS).
Zephyr	<a href="#"><u>Bluetooth</u></a>	BT5.0, GAP, GATT, BR/EDR,



# STM32 – Bluetooth solution details

46

Provider	Solution name	Details
arm	<a href="#">Mbed BLE</a>	<a href="#">More...</a>
Alpwise	<a href="#">OpenSynergy Blue SDK</a>	BT 5.x BLE Dual-Mode Host Stack and Profiles (compliant with version v4.2 and as well as all earlier specification versions including v2.1+EDR, v3.0+High Speed and v4.0, and v4.1) classic profiles: HSP, HFP, MAP, PBAP, AVRCP, A2DP, VDP, SAP, OPP, FTP, BIP, BPP, GPP, CTN, HCRP, HID, PAN, HDP LE profiles: ATT and GATT, SPP-like, alert notification, battery service, device information service, proximity/FindMe, ID over GATT, Health thermometer profile, heart rate profile, transport discovery profile, internet protocol support (IPv6 w/6LoWPAN)
Alpwise	<a href="#">BlueWiseLE® bluetooth 5 Link Layer stack</a>	BT4.2 BLE Single Mode Host Stack Supported profiles over GAP, GATT: Blood Pressure, Phone Alert, HID over Gatt, iBeacon, Proximity, Alert Notification, Find me, Pulse Oximeter, Running Speed & Cadence Health Thermometer, Time, Heart Rate, Network Availability, Location & Navigation, Cycling Speed & Cadence, Cycling power, Glucose Meter, Weight Scale, and additional proprietary profiles, Data Exchange (Serial port over BLE), Cable Replacement, FOTA (Firmware update Over The Air), Voice over BLE...
A&W	<a href="#">PhoneLink</a>	BT2.1+EDR, BT4.0 Supported Profiles : HFP, HSP, PBAP, A2DP, AVRCP, HID, OBEX, FTP, OPP, SPP, PAN, MAP and more
Clarinox	<a href="#">ClarinoxBlue</a>	BT4.2, BT 4.1, BT4.0 + EDR + LE + Mesh Supported profiles: Classic Profiles (A2DP, AVRCP, BIP, BPP, CTN, DI, FTP, GAP, GAVDP, HCRP, HDP, HFP, HID, HSP, MAP, MPS, OPP, PAN, PBAP, SDAP, SPP), Classic Protocols (AVCTP, AVDTP, BNEP, HCI, L2CAP, MCAP, OBEX, RFCOMM, SDP), Smart Profiles / Services (AIOP, AIOS, ANP, ANS, BAS, BCS, BMS, BLP, BLS, CGMP, CGMS, CPP, CPS, CSCP, CSCS, CTS, DIS, ESP, ESS, FMP, GAP, GLP, GLS, HIDS, HOGP, HPS, HRP, HRS, HTP, HTS, IAS, IPS, IPSP, LLS, LNP, LNS, NDCS, OTP, OTS, PASP, PASS, PLXP, PLXS, PXP, RSCP, RSCS, RTUS, ScPP, SCPS, TIP, TDS, TPS, UDS, WSP, WSS, Mesh, Custom), Smart Protocols (ATT, GATT, SM, MESH)
SEARAN	<a href="#">dotStack</a>	BT2.1+EDR, BT4.0, BT4.1, BT 4.2, and 5.0 ready. Single and dual mode. Apps on iOS and Android BLE (GATT) - ANP/ANS, FMP, HIDS, HOGP, PASP/PASS, PXP, TIP, BAS, DIS, IAS, LLS, TPS, ANCS, BLP/BLS, GP, HTP, HRP/HRS BR/EDR - SPP, HID, PAN, MAP, FTP, HSP, HFP, A2DP, AVRCP, PBAP, iAP, HCRP



# Middleware – 2.4GHz – Thread

47

Thread is an IPv6-based, low-power mesh networking technology for IoT products. Thread uses 6LoWPAN and IEEE 802.15.4 wireless protocol with mesh communication,

- **Solutions with STM32WB**



# STM32 – Thread solutions

48

Provider	Solution name	Model	Cost	Availability											
				WB	F0	G0	F1	F2	F3	F4	F7	H7	L0	L1	L4/L4+
ST	 <u>STM32Cube – OpenThread<sup>1</sup></u>	Source	Free	Y	N	N	N	N	N	N	N	N	N	N	N





# Middleware – 2.4GHz – Wi-Fi™

49

Wi-Fi™ is an implementation of the IEEE 802.11 radio communication specification for wireless local area networking. It is usually used with a TCP/IP stack, so all TCP/IP bricks can be reused on Wi-Fi, adapting the lowest firmware layer

- **Solutions with STM32 + Wi-Fi transceiver**
  - Several solutions are available, using STM32 with modules (Espressif ESP8266, Inventek ISM43362-M3G-L44)



# STM32 – Wi-Fi™ solutions

50

Provider	Solution name	Model	Cost	Availability											
				WB	F0	G0	F1	F2	F3	F4	F7	H7	L0	L1	L4/L4+
arm	<a href="#">Mbed Wifi</a> <sup>5</sup>	Source	Free	N	Y	N	Y	Y	Y	Y	Y	Y	Y	Y	Y
Clarinox	<a href="#">ClarinoxWiFi</a> <sup>6</sup>	Binaries or Source	License and/or Royalties	N	N	N	N	N	N	Y	Y	Y	Y	Y	Y
ST	 <a href="#">STM32CubeL4/L4+–WiFi</a> <sup>2</sup>	Source	Free	N <sup>1</sup>	N <sup>1</sup>	N <sup>1</sup>	N <sup>1</sup>	N <sup>1</sup>	N <sup>1</sup>	N <sup>1</sup>	N <sup>1</sup>	N <sup>1</sup>	N <sup>1</sup>	N <sup>1</sup>	Y
ST	 <a href="#">STM32CubeF4 – WiFi</a> <sup>3</sup>	Source	Free	N <sup>1</sup>	N <sup>1</sup>	N <sup>1</sup>	N <sup>1</sup>	N <sup>1</sup>	N <sup>1</sup>	Y	N <sup>1</sup>	N <sup>1</sup>	N <sup>1</sup>	N <sup>1</sup>	N <sup>1</sup>
ST	 <a href="#">STM32CubeF7 – WiFi</a> <sup>4</sup>	Source	Free	N <sup>1</sup>	N <sup>1</sup>	N <sup>1</sup>	N <sup>1</sup>	N <sup>1</sup>	N <sup>1</sup>	N <sup>1</sup>	Y	N <sup>1</sup>	N <sup>1</sup>	N <sup>1</sup>	N <sup>1</sup>

1/ Available on STM32Cube, so porting is very easy

2/ Client Server application and HTTP Server application examples running on [B-L475E-IOT01A](#) with Inventek ISM43362-M3G-L44

3/ Client Server application and HTTP Server application examples running on [STM32F413H-DISCO](#) with Inventek ISM43362-M3G-L44

4/ In-Application programming client example running on [STM32F723E-DISCO](#) and [STM32F769I-DISCO](#)

5/ Support ST boards including [DISCO-L475VG-IOT01A](#), [DISCO-F413ZH](#)

6/ Clarinox WiFi protocol stack supports multiple RTOS, and SDIO, SPI, USB



LoRa® is a type of wireless telecommunication network designed to allow long range communications at a very low bit-rate and enabling long-life battery operated sensors. LoRaWAN™ defines the communication and security protocol that ensures the interoperability with the LoRa® network

## Solutions with STM32 + LoRa® radio

- Semtech SX1276MB1MAS, SX1276MB1LAS and SX1272MB2DAS LoRa® radio expansion boards
- Murata CMWX1ZZABZ-091 LoRa® module
- USI WM-SG-SM-42 LoRa® module
- RiSiNGHF® RHF0M003 modem for LoRa®
- CMWX1ZZABZ-xxx module for sigfox



# STM32 – LoRa<sup>®</sup> solution

52

Provider	Solution name	Model	Cost	Availability											
				WB	F0	G0	F1	F2	F3	F4	F7	H7	L0	L1	L4/L4+
ST 	<a href="#">I-CUBE-LRWAN<sup>2</sup></a>	Source	Free	N.A.	N <sup>1</sup>	N <sup>1</sup>	N <sup>1</sup>	N <sup>1</sup>	N <sup>1</sup>	N <sup>1</sup>	N <sup>1</sup>	N <sup>1</sup>	Y	Y	Y
arm	<a href="#">mbedOS LoRa<sup>3</sup></a>	Source	Free	N.A.	N	N	N	N	N	N	N	N	Y	N	N
StackForce	LoRaWAN stack	Source/Object	License/Royalties	N.A.	N	N	N	N	N	N	N	N	Y	N	N

1/ Available on STM32Cube, so porting is very easy

2/ Supports NUCLEO-L053R8, NUCLEO-L152RE and NUCLEO-L476RG with I-NUCLEO-LRWAN1  
B-L072Z-LRWAN1  
I-NUCLEO-LRWAN1  
P-NUCLEO-LRWAN1 (NUCLEO-L073RZ + I-NUCLEO-SX1272D)  
P-NUCLEO-LRWAN3

3/ Available on DISCO-L072CZ-LRWAN1



**sigfox**

# Middleware – Sub-1GHz – Sigfox™

53

Sigfox™ is a long range wireless area network allowing low-power sensors to benefit from a planetary network, enabling end devices with low BOM cost

## **Solutions with STM32 + radio**

- Murata CMWX1ZZABZ-xxx module



# STM32 – Sigfox™ solution

54

Provider	Solution name	Model	Cost	Availability											
				WB	F0	G0	F1	F2	F3	F4	F7	H7	L0	L1	L4/L4+
ST	 <a href="#">X-CUBE-SFOX</a>	Source	Free	N.A.	N <sup>1</sup>	N <sup>1</sup>	N <sup>1</sup>	N <sup>1</sup>	N <sup>1</sup>	N <sup>1</sup>	N <sup>1</sup>	N <sup>1</sup>	Y <sup>2</sup>	N <sup>1</sup>	N <sup>1</sup>

1/ Available on STM32Cube, so porting is very easy

2/ Supports Murata CMWX1ZZABZ-xxx module only in B-L072Z-LRWAN1

Sub 1GHz RF operates in the ISM spectrum bands below Sub 1GHz – typically in the 769 – 935 MHz , 315 MHz and the 468 MHz frequency range. This spectrum band below 1GHz is particularly useful for RF IOT applications

**Solutions with STM32WB or STM32 + radio (SPIRIT1)**



# STM32 – Sub-1GHz – Others

56

Provider	Solution name	Model	Cost	Availability											
				WB	F0	G0	F1	F2	F3	F4	F7	H7	L0	L1	L4/L4+
ST 	<a href="#">X-CUBE-SUBG</a> <sup>12</sup>	Source	Free	N.A.	N <sup>1</sup>	N <sup>1</sup>	N <sup>1</sup>	N <sup>1</sup>	N <sup>1</sup>	Y	N <sup>1</sup>	N <sup>1</sup>	Y	Y	N <sup>1</sup>
ST 	<a href="#">STM32Cube – 802.15.4</a> <sup>4</sup>	Source	Free	Y	N	N	N	N	N	N	N	N	N	N	N
StackForce	<a href="#">emb6 - 6LoWPAN based IoT stack</a> <sup>3</sup>	Source/Object	Free / License	N	N	N	N	N	N	N	N	N	Y	N	N
StackForce	<a href="#">WM-Bus stack</a> <sup>3</sup>	Source/Binaries	License	N	N	N	N	N	N	N	N	N	Y	N	N

1/ Available on STM32Cube, so porting is very easy

2/ Supports WM-bus with X-NUCLEO-IDS01A4, Contiki OS and Contiki 6LoWPAN protocol on STM32F4 and STM32L1

3/ STM32L0 + [SPIRIT1](#)

4/ Certified BLE stack + HCI, certified OpenThread binary stack, BLE/OpenThread concurrent stack, BLE profiles and services, certified 802.15.4 MAC included in STM32Cube MCU package (Middlewares\ST folder)



Complementary to other wireless technologies, Near Field Communication (NFC) is designed to execute short transactions between two devices in close proximity.

Operating in the 13.56 MHz (RFID) HF band, it is based on ISO/IEC 14443 & ISO/IEC 15693 RFID standards, and regulated by NFC Forum industry association

- **Solutions with STM32 + ST25 NFC / RFID Tag & Reader Ics**



- NFC / RFID reader Ics

- ST25R3911B high performance HF Reader/NFC initiator (ISO14443, ISO15693, FeliCa) with 1.4 W output power, supporting VHBR, capacitive sensitive wake up and Automatic Antenna Tuning (AAT)
    - Other product variant: ST25R3912, ST25R3913, ST25R3914 and ST25R3915
    - CR95HF entry level HF Reader/ NFC Initiator (ISO14443, ISO15693, FeliCa)

- Dynamic NFC tag Ics

- ST25DV dynamic RFID ISO15693 – NFC Type 5 Tag Ics
    - M24LR dynamic RFID ISO15693 / NFC compatible Tag ICs (M24LR04 is NFC Forum Type 5)
    - M24SR dynamic RFID ISO14443 type A – NFC Type 4 Tag ICs

Provider	Solution name	Model	Cost	Availability											
				WB	F0	G0	F1	F2	F3	F4	F7	H7	L0	L1	L4/L4+
ST	 <a href="#">X-CUBE-NFC1</a>	Source	Free	N <sup>1</sup>	Y	N <sup>1</sup>	Y	N <sup>1</sup>	Y	Y	N <sup>1</sup>	N <sup>1</sup>	Y	Y	Y
ST	 <a href="#">X-CUBE-NFC2</a>	Source	Free	N <sup>1</sup>	N <sup>1</sup>	N <sup>1</sup>	N <sup>1</sup>	N <sup>1</sup>	N <sup>1</sup>	Y	N <sup>1</sup>	N <sup>1</sup>	Y	N <sup>1</sup>	N <sup>1</sup>
ST	 <a href="#">X-CUBE-NFC3</a>	Source	Free	N <sup>1</sup>	N <sup>1</sup>	N <sup>1</sup>	Y	N <sup>1</sup>	N <sup>1</sup>	Y	N <sup>1</sup>	N <sup>1</sup>	N <sup>1</sup>	N <sup>1</sup>	N <sup>1</sup>
ST	 <a href="#">X-CUBE-NFC4</a>	Source	Free	N <sup>1</sup>	N <sup>1</sup>	N <sup>1</sup>	N <sup>1</sup>	N <sup>1</sup>	N <sup>1</sup>	Y	N <sup>1</sup>	N <sup>1</sup>	Y	N <sup>1</sup>	N <sup>1</sup>
ST	 <a href="#">X-CUBE-NFC5</a>	Source	Free	N <sup>1</sup>	N <sup>1</sup>	N <sup>1</sup>	N <sup>1</sup>	N <sup>1</sup>	N <sup>1</sup>	Y	N <sup>1</sup>	N <sup>1</sup>	N <sup>1</sup>	N <sup>1</sup>	Y

- NFC / RFID readers

- X-CUBE-NFC3: Drivers and Middleware (NFC Lib, NDEF Lib) for CR95HF, HF Reader/ NFC Initiator, packaged to run on X-NUCLEO-NFC03A1
- X-CUBE-NFC5: Drivers and Middleware (RFAL Lib) for ST25R3911B, HF Reader/ NFC Initiator, packaged to run on X-NUCLEO-NFC05A1

- Dynamic NFC tags

- X-CUBE-NFC1: Drivers and Middleware (NDEF Lib) for M24SR Dynamic NFC/RFID Tag IC, packaged to run on X-NUCLEO-NFC01A1
- X-CUBE-NFC2: Drivers and Middleware (NDEF Lib) for M24LR Dynamic NFC/RFID Tag IC, packaged to run on X-NUCLEO-NFC02A1
- X-CUBE-NFC4: Drivers and Middleware (NDEF Lib) for ST25DV Dynamic NFC/RFID Tag IC, packaged to run on X-NUCLEO-NFC04A1



Safety targets protection of people and equipment from danger and harm, through a set of counter-measures ensuring defined targets

- **Ready for certification offers on STM32**
  - Through third parties or directly from ST

Often-seen acronyms	
ClassB	The IEC 60730 safety standard defines the test and diagnostic methods that ensure the safe operation of embedded control hardware and software for household appliances. The IEC 60730 standard category Class B prevents unsafe operation of the controlled equipment.
SIL	Safety Integrity Level (SIL) is defined by the industry standard IEC 61508 as a relative level of risk-reduction provided by a safety function, or to specify a target level of risk reduction.
ASIL	ASIL is a risk classification scheme defined by the ISO 26262 - Functional Safety for Road Vehicles standard. This is an adaptation of the Safety Integrity Level used in IEC 61508 for the automotive industry.

Provider	Solution name	Model	Cost	Availability											
				WB	F0	G0	F1	F2	F3	F4	F7	H7	L0	L1	L4/L4+
ST	 <a href="#">X-CUBE-CLASSB</a>	Source	Free	N	Y	N	Y	Y	Y	Y	Y	N <sup>1</sup>	Y	Y	Y
ST	<a href="#">STM32-CLASSB-SPL</a>	Source	Free	N	Y	N	Y	Y <sup>3</sup>	N	Y <sup>3</sup>	N	N	N	Y <sup>3</sup>	N
ST	 <a href="#">X-CUBE-STL</a> <sup>4</sup>	Object	Free	N	Y	N	N	N	Y	Y	N <sup>1</sup>	N <sup>1</sup>	N	N	Y





# STM8 – Safety solutions

61

Provider	Solution name	Model	Cost	Availability		
				STM8S	STM8AF	STM8L STM8AL
ST	<a href="#">STM8-SafeCLASSB</a>	Source	Free	Y	Y	Y
ST	<a href="#">STM8A-SafeASIL</a>	Document	Free	N	Y	N





ST's MCUs can drive displays through serial or parallel interfaces.

- **Getting the most from hardware and software**

- ST has built a close relationship with third parties providing software solutions based on our microcontrollers. Customers can make the most of their hardware.

Often-seen acronyms	
Anti aliasing	Technique to minimize distortion artifacts known as aliasing when presenting a high-resolution image at a lower resolution. Aliased images show some stair effects on curves. Anti-aliasing removes this by modifying edge pixel colors.
Alpha blending	Alpha blending is the process of combining a translucent foreground color with a background color, thereby producing a new blended color.
GUI	Graphical user interface
bpp	Bits per pixel (also known as color depth: Number of bits used to represent the color of a single pixel in an image. 1 bpp corresponds to monochrome images.
Palette	Technique to lower image memory size by storing the set of colors used in a table and using this table for each pixel
JPEG	Commonly used method of lossy compression for digital image. The degree of compression can be adjusted, allowing a trade-off between storage size and image quality. JPEG typically achieves 10:1 compression with little perceptible loss in image quality.
RGB / ARGB	Color model in which red, green and blue are merged to reproduce a broad array of colors. "A" field in ARGB format handles transparency information.
Widgets	Element of a graphical user interface that can be changed by the user (such as text box, radio button)



# STM32 – Display solutions (1/2)

63

Provider	Solution name	Model	Cost	Availability											
				WB	F0	G0	F1	F2	F3	F4	F7	H7	L0	L1	L4/L4+
ST	<a href="#">STemWin</a>	Binaries	Free	N	N	N	Y	Y	Y	Y	Y	Y	N	Y	N
ST	 <a href="#">STM32Cube - STemWin</a>	Binaries	Free	N <sup>2</sup>	Y	N <sup>2</sup>	Y	Y	Y	Y	Y	Y	N	Y	Y
ST	 <a href="#">STM32Cube - TouchGFX</a>	Source	Free	N <sup>2</sup>	N	N	N <sup>2</sup>	N <sup>2</sup>	N	Y	Y	N <sup>2</sup>	N	N	N <sup>2</sup>
Altia	<a href="#">Altia Design and Deep screen</a>	Source	License	N <sup>1</sup>	Y	N <sup>1</sup>	Y	Y	Y	<u>Y</u>	Y	Y	N <sup>1</sup>	Y	N
Crank	<a href="#">Storyboard</a>	Binaries	License	N <sup>1</sup>	N	N <sup>1</sup>	N <sup>1</sup>	N <sup>1</sup>	Y	Y	Y	Y	N	N <sup>1</sup>	N
ST	<a href="#">TouchGFX</a>	Binaries /Source	Free	N	N	N	Y	Y	N	Y	Y	Y	N	N	Y
eCosCentric	<a href="#">eCosPro-PEG</a>	Source	License	N <sup>1</sup>	N <sup>1</sup>	N <sup>1</sup>	Y	Y	Y	Y	N <sup>1</sup>	N <sup>1</sup>	N <sup>1</sup>	N <sup>1</sup>	N <sup>1</sup>
Express Logic	<a href="#">GUIX</a>	Source	License	N <sup>1</sup>	Y	N <sup>1</sup>	Y	Y	Y	Y	Y	Y	Y	Y	Y



# STM32 – Display solutions (2/2)

64

Provider	Solution name	Model	Cost	Availability										
				WB	F0	G0	F1	F2	F3	F4	F7	L0	L1	L4/L4+
Korulab	<a href="#">Koru</a>	Binaries	License	N	N	N	N	N	N	Y	Y	N	N	Y
Micrium	<a href="#">µC/GUI</a>	Source	License	N	Y	N	Y	Y	Y	Y	Y	Y	Y	N
Micro Digital	<a href="#">PEG</a>	Source	License	N <sup>1</sup>	N <sup>1</sup>	N <sup>1</sup>	Y	Y	Y	Y	Y	N <sup>1</sup>	N <sup>1</sup>	N <sup>1</sup>
Rowebots	<a href="#">emWin GUI</a>	Source	License	N	N	N	Y	Y	Y	Y	Y	N	N	N
SEGGER	<a href="#">emWin</a>	Source	License	N <sup>1</sup>	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
Tara Systems	<a href="#">Embedded Wizard</a>	Binaries / Source	License	N	N	N	N	N	N	Y	Y	N	N	Y





# Middleware – Touch sensing

65

Capacitive touch sensing is an electrical cost-efficient technology, replacing conventional mechanical switches to detect user actions, to build modern GUI look and feel.

- **NRE/royalty-free C source code**
  - Complete solution for touch keys, linear and rotary touch sensors, with acquisition, post processing and API layers, debounce filtering and calibration functions


## Often-seen acronyms

Surface capacitance	The capacitance of a single ended electrode is modified when the finger gets close to it.
Projected capacitance	The capacitance between two sensing electrodes is modified when the finger gets close to them.
RC acquisition	Resistor-capacitor acquisition for surface capacitance only. It consists in measuring the charge and discharge time duration of a RC cell made of the electrode capacitance and a load resistor.
CT acquisition	Charge transfer acquisition for surface capacitance only. It consists in measuring the duration for charging the electrode capacitance and transferring part of the accumulated charge into a sampling capacitor. The CT acquisition is more robust than the RC one.



# STM32 – Touch-sensing solutions

66

Provider	Solution name	Acquisition	Model	Cost	Availability											
					WB	F0	G0	F1	F2	F3	F4	F7	H7	L0	L1	L4/L4+
ST	STM32 Touch Sensing Library	CT	Source	Free	N	<u>Y</u>	N	N	N	<u>Y</u>	N	N	N	N	<u>Y</u>	N
ST	 <a href="#">STM32Cube – Touch Sensing</a>	CT	Source	Free	Y	Y	N	N	N	Y	Y	N	N	Y	Y	Y



# STM8 – Touch-sensing solutions

67

Provider	Solution name	Acquisition	Model	Cost	Availability	
					STM8S / STM8AF	STM8L / STM8AL
ST	STM8 Touch Lib	RC + CT	Source	Free	<u>Y<sup>1</sup></u>	<u>Y<sup>1</sup></u>

# Middleware – Artificial Neural Networks

68

Thanks to a new set of Artificial Intelligence (AI) solutions from ST you now have the possibility to map and run pre-trained Artificial Neural Networks (ANN) on the broad STM32 microcontroller portfolio. The STM32Cube.AI is an extension pack of the widely used STM32CubeMX configuration and code generation tool enabling AI on STM32 Arm® Cortex®-M-based microcontrollers

Often-seen acronyms	
AI	Artificial Intelligence
ANN	Artificial Neural Networks



# STM32 – Artificial Neural Networks

69

Provider	Solution name	Model	Cost	Availability											
				WB	F0	G0	F1	F2	F3	F4	F7	H7	L0	L1	L4/L4+
ST	 <a href="#">X-CUBE-AI<sup>1</sup></a>	Source	Free	Y	N	N	N	Y	Y	Y	Y	Y	N	N	Y
ST	 <a href="#">FP-AI-SENSING<sup>12</sup></a>	Source	Free	N <sup>3</sup>	N	N	N	N <sup>3</sup>	N <sup>3</sup>	N <sup>3</sup>	N <sup>3</sup>	N <sup>3</sup>	N	N	Y

1/ Generation of an STM32-optimized library from pre-trained Neural Network models. Support various Deep Learning frameworks such as Keras, Caffe, ConvnetJS, and Lasagne

2/ STM32Cube function pack for ultra-low power IoT node with artificial intelligence (AI) application based on audio and motion sensing

3/ Available on STM32Cube, so porting is very easy



# STM32 – Instrumentation

70

Provider	Solution name	Model	Cost	Availability											
				WB	F0	G0	F1	F2	F3	F4	F7	H7	L0	L1	L4/L4+
AWS	FREERTOS+™ CLI <sup>1</sup>	Source	Free	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y

- Enabling your FreeRTOS application to process command line input



# Connectors to cloud providers

71

STM32 acts as an end device securely connected to cloud services providers

Connectors to cloud provider (Amazon AWS, Microsoft Azure, IBM Watson...)

## STM32Cube Expansion Packages

Amazon AWS, Google Cloud, IBM Watson, Microsoft Azure  
Exosite, Grovestream, AvSystem, Litmus Automation, Ubidots

- Configuration of the connectivity interfaces (WiFi, Ethernet...)
- Connection to the Internet and the cloud provider servers
- publication of messages
- Subscription over a variety of connectivity protocols (MQTT, HTTPS, ...)

Examples of end device applications using ST sensors and RFID/NFC tag and connecting to cloud providers

## STM32 ODE Functions packs


Amazon AWS, IBM Watson, Microsoft Azure

- Temperature and humidity sensor (HTS221)
- Pressure sensor (LPS25HB)
- Motion sensors (LIS3MDL, LSM303AGR, LSM6DS0, LSM6DSL, IIS2DH)
- Writing/reading the RFID/NFC tag (M24SR64-Y)



# STM32 - Connectors to cloud providers

72

Provider	Solution name	Model	Cost	Availability											
				WB	F0	G0	F1	F2	F3	F4	F7	H7	L0	L1	L4/L4+
ST 	<a href="#">X-CUBE-CLD-GEN<sup>1</sup></a>	Source	Free	N <sup>5</sup>	N <sup>5</sup>	N <sup>5</sup>	N <sup>5</sup>	N <sup>5</sup>	N <sup>5</sup>	Y	Y	N <sup>5</sup>	N <sup>5</sup>	N <sup>5</sup>	Y
	<a href="#">X-CUBE-AWS</a>	Source	Free	N <sup>5</sup>	N <sup>5</sup>	N <sup>5</sup>	N <sup>5</sup>	N <sup>5</sup>	N <sup>5</sup>	Y	Y	N <sup>5</sup>	N <sup>5</sup>	N <sup>5</sup>	Y
	<a href="#">X-CUBE-AZURE</a>	Source	Free	N <sup>5</sup>	N <sup>5</sup>	N <sup>5</sup>	N <sup>5</sup>	N <sup>5</sup>	N <sup>5</sup>	Y	Y	N <sup>5</sup>	N <sup>5</sup>	N <sup>5</sup>	Y
	<a href="#">X-CUBE-WATSON</a>	Source	Free	N <sup>5</sup>	N <sup>5</sup>	N <sup>5</sup>	N <sup>5</sup>	N <sup>5</sup>	N <sup>5</sup>	Y	Y	N <sup>5</sup>	N <sup>5</sup>	N <sup>5</sup>	Y
	<a href="#">X-CUBE-GCP</a>	Source	Free	N <sup>5</sup>	N <sup>5</sup>	N <sup>5</sup>	N <sup>5</sup>	N <sup>5</sup>	N <sup>5</sup>	Y	Y	N <sup>5</sup>	N <sup>5</sup>	N <sup>5</sup>	Y
	<a href="#">FP-CLD-AWS1</a>	Source	Free	N <sup>5</sup>	N <sup>5</sup>	N <sup>5</sup>	N <sup>5</sup>	N <sup>5</sup>	N <sup>5</sup>	Y	N <sup>5</sup>	N <sup>5</sup>	N <sup>5</sup>	N <sup>5</sup>	N <sup>5</sup>
	<a href="#">FP-CLD-AZURE1</a>	Source	Free	N <sup>5</sup>	N <sup>5</sup>	N <sup>5</sup>	N <sup>5</sup>	N <sup>5</sup>	N <sup>5</sup>	Y	N <sup>5</sup>	N <sup>5</sup>	N <sup>5</sup>	N <sup>5</sup>	Y
	<a href="#">FP-CLD-WASTON1</a>	Source	Free	N <sup>5</sup>	N <sup>5</sup>	N <sup>5</sup>	N <sup>5</sup>	N <sup>5</sup>	N <sup>5</sup>	Y	N <sup>5</sup>	N <sup>5</sup>	N <sup>5</sup>	N <sup>5</sup>	N <sup>5</sup>
AWS	<a href="#">Amazon FreeRTOS<sup>2</sup></a>	Source	Free <sup>3</sup>	N	N	N	N	N	N	N	N	N	N	N	Y
CypherBridge	<a href="#">uMQTT Toolkit</a>	Source	License	N	N	N	N	N	N	Y	Y	N	N	N	N
Express Logic	<a href="#">X-WARE IoT Platform</a>	Source	License	N <sup>6</sup>	Y	Y	Y	Y	Y	Y	Y	N <sup>5</sup>	N <sup>5</sup>	N <sup>5</sup>	N <sup>5</sup>
Keil / arm	<a href="#">IoT Client<sup>4</sup></a>	Source	License	N <sup>5</sup>	Y	N <sup>5</sup>	Y	Y	Y	Y	Y	Y	Y	Y	Y

1/ Supports [B-L475E-IOT01A](#), [32F413HDISCOVERY](#), [32F769IDISCOVERY](#), [P-L496G-CELL01](#) and [P-L496G-CELL02](#). Examples with Exosite, Grovestream, AvSystem, Litmus Automation and Ubidots cloud providers

2/ "Connect to AWS IoT" and "Connect to AWS Greengrass" packages are available for [STM32L4/L4+Discovery kit IoT node](#)

3/ MIT license

4/ Amazon AWS, Google Cloud, IBM Watson, Microsoft Azure

5/ Available on STM32Cube, so porting is very easy

6/ Please contact supplier





# Application field – Audio

73

- **A complete solution for all audio aspects**

- All audio aspects can be covered by solutions from ST or third parties

- **Optimized for ST products**

- Unlike open-source non-optimized solutions, ST works with third parties to propose optimized algorithms for ST platforms

## Often-seen acronyms

Codec	A codec is a program capable of encoding and decoding a digital data stream. The encoded stream can be compressed or not, with a lossy (MP3, WMA, ...) or lossless (FLAC, ALAC, ...) mechanism.
PCM	Pulse-code modulation: Digital representation of an analog signal, in which the magnitude of the analogue signal is sampled regularly, each sample being quantized to the nearest value within a range of digital steps.
AAC, MP3, WMA	Music codecs with patents. Royalties need to be paid to patent owners.
Speex	Open source, no royalties speech codec
G711	Simple codec with no royalties often used in telephony
G726	ADPCM (adaptive differential pulse code modulation): Simple compression of PCM data



# STM32 – Audio solutions

74

Provider	Solution name	Model	Cost	Availability												
				WB	F0	G0	F1	F105 F107	F2	F3	F4	F7	H7	L0	L1	L4/L4+
ST	<a href="#">ADPCM Vocoder</a> , <a href="#">Speex Vocoder</a>	Source	Free	N <sup>1</sup>	N	N	Y	N <sup>1</sup>	N <sup>1</sup>	N <sup>1</sup>	N <sup>1</sup>	N	N	N	Y	N <sup>1</sup>
ST	G711, G726, G726A Vocoders	Source	Free	N <sup>1</sup>	N	N	N <sup>1</sup>	N <sup>1</sup>	Y <sup>3</sup>	N <sup>1</sup>	Y <sup>3</sup>	N	N	N	N <sup>1</sup>	N <sup>1</sup>
ST	<a href="#">Audio Engine MP3 Decoder</a> With Channel Mixer, Equalizer and Loud	Binaries	Free	N <sup>1</sup>	N	N	N <sup>1</sup>	Y	Y	N <sup>1</sup>	Y	Y	Y	N	N <sup>1</sup>	N <sup>1</sup>
ST	<a href="#">Audio Engine MP3 Codec</a> With Channel Mixer, Equalizer and Loud	Binaries	Free	N <sup>1</sup>	N	N	N <sup>1</sup>	Y	Y	N <sup>1</sup>	Y	N	N	N	N <sup>1</sup>	N <sup>1</sup>
ST	<a href="#">Audio Engine WMA Decoder</a> With Channel Mixer, Equalizer and Loud	Binaries	Free	N <sup>1</sup>	N	N	N <sup>1</sup>	Y	Y	N <sup>1</sup>	Y	Y	N	N	N <sup>1</sup>	N <sup>1</sup>
ST	Audio Engine AAC Decoder AAC-LC, HE-AAC+ v1, HE-AAC+ v2	Binaries	Free	N <sup>1</sup>	N	N	N <sup>1</sup>	Y <sup>3</sup>	Y <sup>3</sup>	N <sup>1</sup>	Y <sup>3</sup>	N <sup>1</sup>	N <sup>1</sup>	N	N <sup>1</sup>	N <sup>1</sup>
ST	Audio Engine AC3 Decoder	Binaries	Free	N <sup>1</sup>	N	N	N	N	N	N	N <sup>1</sup>	N <sup>1</sup>	N <sup>1</sup>	N	N	N
ST	Audio Engine Post Processing Smart volume control, Equalizer, Sample rate converters, Stereo widening	Binaries	Free	N <sup>1</sup>	N	N	N	N	N	N <sup>1</sup>	Y	N <sup>1</sup>	N <sup>1</sup>	N	N	N
ST	Apple iAP Streaming Library (iPod/iPhone/iPad) <sup>2</sup>	Source	Free	N <sup>1</sup>	N	N	N	Y	Y	Y	Y	N <sup>1</sup>	N <sup>1</sup>	N	Y	N
ST	USB audio class and stream synchro. (feedback pipe, external PLL, ...)	Binaries	Free	N <sup>1</sup>	Y	N	N	Y	Y	N <sup>1</sup>	Y	Y	N	Y	N	N
ST	Source Rate Converter <sup>3</sup>	Binaries	Free	N <sup>1</sup>	N	N	Y	Y	Y	N <sup>1</sup>	Y	Y	N	N	N <sup>1</sup>	N

1/ The library will run immediately on these targets, even if not ported officially.

2/ Only available by request to local sales for companies being a licensee of Apple MFi (Made for iPod) program.

3/ Available on demand. Ask your local ST Sales office.



# STM32 – Audio solutions

75

Provider	Solution name	Model	Cost	Availability												
				WB	F0	G0	F1	F105 F107	F2	F3	F4	F7	H7	L0	L1	L4/L4+
ST 	<a href="#">X-CUBE-AUDIO<sup>3</sup></a>	Binaries	Free	N <sup>5</sup>	N	N	N <sup>5</sup>	N <sup>5</sup>	N <sup>5</sup>	N <sup>5</sup>	Y	Y	N <sup>5</sup>	N	N <sup>5</sup>	N <sup>5</sup>
ST 	<a href="#">X-CUBE-VS4A<sup>4</sup></a>	Source	Free	N	N	N	N	N	N	N	N	Y	N <sup>5</sup>	N	N	N
ST 	<a href="#">STM32Cube – PDM2PCM library<sup>6</sup></a>	Source	Free	N <sup>5</sup>	N <sup>5</sup>	N <sup>5</sup>	N <sup>5</sup>	N <sup>5</sup>	Y	N <sup>5</sup>	Y	Y	Y	N <sup>5</sup>	N <sup>5</sup>	N <sup>5</sup>
DSPConcept	<a href="#">Audio Weaver Algorithms</a>	Binaries	License	N	N	N	N	N	N	N	Y	Y	Y	N	N	N
Craftwork	<a href="#">Remote Speakers (DLNA Media Renderer)</a>	Binaries	License	N	N	N	N	N	N <sup>1</sup>	N	Y	N <sup>1</sup>	N <sup>1</sup>	N	N	N
Sensory	Voice recognition <sup>2</sup>	Binaries	License	N	N	N	N	N	N	N	Y	N <sup>1</sup>	N <sup>1</sup>	N	N	N
Vestec	Voice recognition <sup>2</sup>	Binaries	License	N	N	N	N	N	N	N	Y	N <sup>1</sup>	N <sup>1</sup>	N	N	N

1/ The library will run immediately on these targets, even if not ported officially.

2/ Available on demand. Ask your local ST Sales office.

3/ Audio processing components (BAM, BIQ, CDC, GAM, GREQ, HPV, SRC236, SRC441, OMNI2, SVC, SDR, SMR), MP3 decoder (Cortex-M7/M4/M3), MP3 encoder (Cortex-M3/M4)

4/ Framework for the Alexa Voice Service (AVS)

5/ Available on STM32Cube, so porting is very easy

6/ Included in STM32Cube MCU packages (Middlewares\ST folder).



# Focus – STM32 audio post-processing (1/2)

76

Modules Names	Quality	Measured MHz	Flash Memory	Static RAM	Dynamic RAM	Remarks
SRC441	Standard	13.7 MHz	3204 Bytes	232 Bytes	3228 Bytes	Sampling Rate Conversion from 44.1 to 48 kHz
	High Quality	20.4 MHz	3894 Bytes	360 Bytes	3676 Bytes	
SRC236	Standard	8->16: 4.4 MHz 48->96: 25.3 MHz 16->48: 12.5 MHz 8->48: 12.3 MHz 32->48: 12.7 MHz 24->16: 6.2 MHz	1740 Bytes	972 Bytes	3364 Bytes	Sampling Rate Conversion supporting ratios 2, 3, 6, 1/2, 1/3, 1/6, 3/2 and 2/3.
	High Quality	8->16: 7.1 MHz 48->96: 40.7 MHz 16->48: 20.4 MHz 8->48: 20.2 MHz 32->48: 20.5 MHz 24->16: 10.2 MHz	2238 Bytes	1932 Bytes	4804 Bytes	
Omnisurround – Stereo Widening	Enhanced Mono to Stereo	6.4 MHz	3660 Bytes	1992 Bytes	384 Bytes	Signal is sampled at 48 kHz
	SW 2.0 to 2.0	13.2 MHz				
	Closely Spaced Speakers	4.0 MHz				
Omnisurround – 7.1 Virtualizer	5.1 or 7.1 -> 2.0	25.6 MHz	4764 Bytes	3028 Bytes	1152 Bytes	Signal is sampled at 48 kHz

Figures of merit on STM32F4 target



# Focus – STM32 audio post-processing (2/2)

77

Modules Names	Quality	Measured MHz	Flash Memory	Static RAM	Dynamic RAM	Remarks
<b>Gfx Equalizer (GrEq)</b>	10-bands	14 MHz	4390 Bytes	552 Bytes	3840 Bytes	Graphical Equalizer. Signal is sampled at 48 kHz, 10 parallel bands with 6 available presets Can run in place (Input buf = Output buf)
<b>Biquad Filters</b>	10 Biquads	14.1 MHz	570 Bytes	600 Bytes	4 Bytes	Generic Biquads filter (used for Transducer Equalizer for instance) Signal is sampled at 48 kHz Can run in place (Input buf = Output buf)
<b>Bass Manager (BAM)</b>	with Limiter	17.1 MHz	9266 Bytes	2236 Bytes	5760 Bytes	Bass Manager. Up to +/- 24 dB, between 60 and 300Hz Can run in place (Input buf = Output buf)
	without Limiter	12.7 MHz				
<b>Smart Volume Control (SVC)</b>	Standard	6.2 MHz	6160 Bytes	2648 Bytes	4800 Bytes	Smart Volume Control (includes DRC) Signal is sampled at 48 kHz Can run in place (Input buf = Output buf)
	High Quality	10.9 MHz				
<b>Gain Manager (GAM)</b>	Standard	Stereo: 2.6 MHz	1472 Bytes	120 Bytes	1 Bytes	Gain Manager Signal is sampled at 48 kHz Can run in place (Input buf = Output buf)
		8 channels: 8.6 MHz				
<b>Panning</b>	L/R Panning F/R Balancing	8.4 MHz	5654 Bytes	6872 Bytes	7680 Bytes	Signal is sampled at 48 kHz 2.0 input, 4.0 output Contains Front and Rear Left/Right Panning, Front/Rear balancing.
	Sweet Spot Mode 1	4.2 MHz				
	Sweet Spot Mode 2 (Ambi)	4.7 MHz	7956 Bytes	6968 Bytes	7680 Bytes	Sweet Spot Mode for one user.

Figures of merit on STM32F4 target

# Application Field – Building Automation and Control

78

Building automation is the automatic centralized control of a building's heating, ventilation and air conditioning, lighting and other systems through a building management system or building automation system (BAS). A building controlled by a BAS is often referred to as a smart building or a smart home.

Often-seen acronyms	
BACnet	communications protocol for Building Automation and Control (BAC) networks that leverage the ASHRAE, ANSI, and ISO 16484-5 standard protocol. BACnet was designed to allow communication of building automation and control systems for applications such as heating, ventilating, and air-conditioning control (HVAC), lighting control, access control, and fire detection systems and their associated equipment. The BACnet protocol provides mechanisms for computerized building automation devices to exchange information, regardless of the particular building service they perform.
DALI	Digital Addressable Lighting Interface (DALI) is a trademark for network-based systems that control lighting in building automation. The underlying technology was established by a consortium of lighting equipment manufacturers as a successor for 0-10 V lighting control systems, and as an open standard alternative to Digital Signal Interface (DSI), on which it is based. DALI is specified by technical standards IEC 62386 and IEC 60929. Standards conformance ensures that equipment from different manufacturers will interoperate. The DALI trademark is allowed on devices that comply with the current standards when manufactured.
DLMS / COSEM	IEC 62056 is a set of standards for Electricity metering data exchange by International Electrotechnical Commission. The IEC 62056 standards are the International Standard versions of the DLMS/COSEM specification. DLMS or Device Language Message Specification (originally Distribution Line Message Specification[1]), is the suite of standards developed and maintained by the DLMS User Association and has been adopted by the IEC TC13 WG14 into the IEC 62056 series of standards. COSEM or Companion Specification for Energy Metering, includes a set of specifications that defines the Transport and Application Layers of the DLMS protocol
DMX-512	DMX512 (Digital Multiplex) is a standard for digital communication networks that are commonly used to control stage lighting and effects. It was originally intended as a standardized method for controlling light dimmers, which, prior to DMX512, had employed various incompatible proprietary protocols. It soon became the primary method for linking controllers (such as a lighting console) to dimmers and special effects devices such as fog machines and intelligent lights
KNX	KNX is a standardised (EN 50090, ISO/IEC 14543), OSI-based network communications protocol for building automation. KNX is the successor to, and convergence of, three previous standards: the European Home Systems Protocol (EHS), BatiBUS, and the European Installation Bus (EIB or Instabus)



# STM32 – Building Automation and Control

79

Provider	Solution name	Model	Cost	Availability											
				WB	F0	G0	F1	F2	F3	F4	F7	H7	L0	L1	L4/L4+
MBS	<a href="#">BACnet stack embedded</a>	Source	License	N <sup>3</sup>	Y	N <sup>3</sup>	Y	Y	Y	Y	Y	Y	Y	Y	Y
prizm.io	<a href="#">BACnet Stack</a>	Source	License	N <sup>3</sup>	Y	N <sup>3</sup>	Y	Y	Y	Y	Y	Y	Y	Y	Y
ST	DALI <sup>2</sup>	Source	Free	N <sup>3</sup>	N	N <sup>3</sup>	Y	N	N	N	N	N	N	Y	N
MBS	<a href="#">DALI stack</a>	Source	License	N <sup>3</sup>	Y	N <sup>3</sup>	Y	Y	Y	Y	Y	Y	Y	Y	Y
Andrea Informatique	<a href="#">DLMS / COSEM</a>	Binaries	License	N <sup>3</sup>	N <sup>3</sup>	N <sup>3</sup>	Y	Y	N <sup>3</sup>	Y	N <sup>3</sup>	N <sup>3</sup>	N <sup>3</sup>	Y	N <sup>3</sup>
ST	DMX-512 <sup>4</sup>	Source	Free	N <sup>1</sup>	N <sup>1</sup>	N <sup>1</sup>	Y	N <sup>1</sup>	N <sup>1</sup>	N <sup>1</sup>	N <sup>1</sup>	N <sup>1</sup>	N <sup>1</sup>	N <sup>1</sup>	N <sup>1</sup>
prizm.io	<a href="#">DMX-512 Stack</a>	Source	License	N <sup>3</sup>	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
TAPKO	<a href="#">KAstack KNX</a>	Binaries / source	License + royalties	N <sup>3</sup>	Y	Y	Y	Y	Y	Y	Y	Y	N <sup>3</sup>	N <sup>3</sup>	N <sup>3</sup>
Weinzierl	<a href="#">KNX</a>	Source	License	N <sup>3</sup>	Y	Y	Y	N <sup>1</sup>	N <sup>1</sup>	N <sup>1</sup>	N	N	N <sup>1</sup>	Y	N <sup>1</sup>

1/ Can be ported

2/ Provided on demand to sales office, supporting DALI slave only.

3/ Please contact supplier

4/ Provided on demand to sales office.



# STM8 – Building Automation and Control

80

Provider	Solution name	Application	Model	Cost	Availability	
					STM8S / STM8AF	STM8L / STM8AL
ST	<a href="#">DALI</a>	Lighting	Source	Free	Y	N <sup>1</sup>
TAPKO	<a href="#">KAlstack KNX</a>	Building automation	Binaries / source	License	N	Y






# Application field – Industrial protocols

81

Industrial market needs are very fragmented in terms of communication protocols. Many different protocols are available for different target applications in factory automation





# STM32 – Industrial protocols (1/8)

82

Provider	Solution name	Application	Model	Cost	Availability										
					F0	G0	F1	F2	F3	F4	F7	H7	L0	L1	L4/L4+
CMX	<a href="#">CMX-CANopen</a>	Automation, medical	Source	License	N	N	Y	Y	Y	Y	Y	N <sup>1</sup>	N	N	N <sup>1</sup>
eCosCentric	<a href="#">eCosPro-CAN</a>	Factory Automation	Source	License	N	N	Y	Y	Y	Y	Y	N <sup>1</sup>	N	N	Y
	<a href="#">CANopen</a>	Factory Automation	Source	License	N	N	Y	Y	Y	Y	Y	N <sup>1</sup>	N	N	Y
	<a href="#">eCosPro-ModbusTCP</a>	Factory Automation	Source	License	N	N	N	Y	Y	Y	Y	N <sup>1</sup>	N	N	Y
emtas	<a href="#">CANopen</a>	Automation, medical	Source	License	Y	Y	Y	Y	Y	Y	Y	Y	N	N	Y
	<a href="#">J1939</a>	Commercial vehicles	Source	License	Y	Y	Y	Y	Y	Y	Y	Y	N	N	Y
	<a href="#">EnergyBus</a>	Commercial vehicles	Source	License	Y	Y	Y	Y	Y	Y	Y	Y	N	N	Y
	<a href="#">EtherCAT<sup>2</sup></a>	Automation, medical	Source	License	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y



# STM32 – Industrial protocols (2/8)

83

Provider	Solution name	Application	Model	Cost	Availability										
					F0	G0	F1	F2	F3	F4	F7	H7	L0	L1	L4/L4+
EUROS	CANOpen	Automation	Binaries	License	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
	PROFINET	Automation	Binaries	License	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
	Modbus	Automation	Binaries	License	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
	EtherCAT <sup>1</sup>	Automation	Binaries	License	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
	Ethernet	Automation	Binaries	License	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
	OPC UA Server/Client	Automation	Binaries	License	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
	MQTT Client	Automation	Binaries	License	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y



# STM32 – Industrial protocols (3/8)

84

Provider	Solution name	Application	Model	Cost	Availability										
					F0	G0	F1	F2	F3	F4	F7	H7	L0	L1	L4/L4+
Hilscher	<a href="#">I-CUBE-NETX + PROFIBUS DP Slave</a> <sup>(1)</sup>	Fieldbus  Factory automation	Source + Binary <sup>(2)</sup>	License	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
	<a href="#">I-CUBE-NETX + CANopen Slave</a> <sup>(1)</sup>				Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
	<a href="#">I-CUBE-NETX + DeviceNet Slave</a> <sup>(1)</sup>				Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
	<a href="#">CC-Link Slave</a> <sup>(1)</sup>				Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
	<a href="#">OPC UA Server</a> <sup>(1)</sup>	IIoT	Source + Binary <sup>(2)</sup>	License	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
	<a href="#">MQTT Client</a> <sup>(1)</sup>				Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y

1/ Requires external hardware (netX52 or netX90).

2/ source for STM32, binary for external hardware.



# STM32 – Industrial protocols (4/8)

85

Provider	Solution name	Application	Model	Cost	Availability										
					F0	G0	F1	F2	F3	F4	F7	H7	L0	L1	L4/L4+
Hilscher	<a href="#">I-CUBE-NETX + PROFINET RT/IRT IO-Device</a> <sup>(1)</sup>	Industrial real-time Ethernet  Factory automation	Source + Binary <sup>(2)</sup>	License	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
	<a href="#">I-CUBE-NETX + EtherCAT Slave</a> <sup>(1)</sup>				Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
	<a href="#">I-CUBE-NETX + Ethernet/IP Adapter</a> <sup>(1)</sup>				Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
	<a href="#">I-CUBE-NETX + sercos Slave</a> <sup>(1)</sup>				Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
	<a href="#">I-CUBE-NETX + POWERLINK Controlled Node</a> <sup>(1)</sup>				Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
	<a href="#">I-CUBE-NETX + Varan Client</a> <sup>(1)</sup>				Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
	<a href="#">I-CUBE-NETX + Open ModbusTCP</a> <sup>(1)</sup>				Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y

1/ Requires external hardware (netX52 or netX90).

2/ source for STM32, binary for external hardware.



# STM32 – Industrial protocols (5/8)

86

Provider	Solution name	Application	Model	Cost	Availability										
					F0	G0	F1	F2	F3	F4	F7	H7	L0	L1	L4/L4+
HMS	<a href="#">IXXAT® CANopen</a>	Automation, medical	Source	License	N	N	Y	Y	Y	Y	Y	Y	N	N	Y <sup>1</sup>
	<a href="#">IXXAT® SAE J1939</a>	Transportation	Source	License	N	N	Y	Y	Y	Y	Y	Y	N	N	Y <sup>1</sup>
	<a href="#">EtherNet/IP Adapter</a>	Factory automation	Source	License	N	N	Y <sup>1</sup>	Y	N	Y	Y	Y	N	N	Y <sup>1</sup>
	<a href="#">EtherNet/IP Scanner</a>	Factory automation	Source	License	N	N	Y <sup>1</sup>	Y	N	Y	Y	Y	N	N	Y <sup>1</sup>
	<a href="#">IXXAT® IEEE1588</a>	Factory automation	Source	License	N	N	Y <sup>1</sup>	Y	N	Y	Y	Y	N	N	Y <sup>1</sup>
	<a href="#">IXXAT® Safety over EtherCAT</a>	Automation	Source	License	N	N	Y <sup>1</sup>	Y	N	Y	Y	Y	N	N	Y <sup>1</sup>
	<a href="#">IXXAT® CIP Safety (EtherNet/IP, sercos)</a>	Automation	Source	License	N	N	Y <sup>1</sup>	Y	N	Y	Y	Y	N	N	Y <sup>1</sup>



# STM32 – Industrial protocols (6/8)

87

Provider	Solution name	Application	Model	Cost	Availability										
					F0	G0	F1	F2	F3	F4	F7	H7	L0	L1	L4/L4+
Matrikon	<a href="#">OPC UA Server</a>	Factory automation	Source / Binaries	License	N	N	N	Y	N	Y	Y	Y	N	N	N
MESCO	<a href="#">HART Slave</a>	Process automation	Source	Lic. + Royal.	Y	Y	Y	Y	Y	Y	N <sup>2</sup>	N <sup>2</sup>	Y	Y	N <sup>2</sup>
MicroControl	<a href="#">CANopen</a>	Automation, medical	Source	License	Y	Y	Y	Y	Y	Y	Y	Y	N	N	Y
	<a href="#">J1939</a>	Commercial vehicles	Source	License	Y	Y	Y	Y	Y	Y	Y	Y	N	N	Y
	<a href="#">EtherCAT<sup>1</sup></a>	Factory automation	Source	License	Y <sup>1</sup>	Y <sup>1</sup>	Y <sup>1</sup>	Y <sup>1</sup>	Y <sup>1</sup>	Y <sup>1</sup>	Y <sup>1</sup>	Y <sup>1</sup>	Y <sup>1</sup>	Y <sup>1</sup>	Y <sup>1</sup>
	<a href="#">PROFINET</a>	Factory automation	Source	License	N	N	Y	Y	N	Y	Y	Y	N	N	N
Micrium	<a href="#">µC/Modbus</a>	Factory automation	Source	License	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y



# STM32 – Industrial protocols (7/8)

88

Provider	Solution name	Application	Model	Cost	Availability										
					F0	G0	F1	F2	F3	F4	F7	H7	L0	L1	L4/L4+
Port	<a href="#">CANopen</a>	Factory automation	Source	License	Y	Y	Y	Y	Y	Y	Y	Y	N	N	Y
	<a href="#">EtherCAT<sup>2</sup></a>	Factory automation	Source	License	Y <sup>1</sup>	Y <sup>1</sup>	Y <sup>1</sup>	Y <sup>1</sup>	Y <sup>1</sup>	Y <sup>1</sup>	Y <sup>1</sup>	Y <sup>1</sup>	N	N	Y <sup>1</sup>
	<a href="#">PROFINET</a>	Factory automation	Source	License	N	N	N	N	N	Y	Y	Y	N	N	N
	<a href="#">EtherNet/IP<sup>2</sup></a>	Factory automation	Source	License	N	N	N	N	N	Y	Y	Y	N	N	N
	<a href="#">POWERLINK</a>	Factory automation	Source	License	N	N	N	Y <sup>1</sup>	N	N	N	N	N	N	N
SEGGER	<a href="#">emModbus</a>	Factory automation	Source	License	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y





# STM32 – Industrial protocols (8/8)

89

Provider	Solution name	Application	Model	Cost	Availability										
					F0	G0	F1	F2	F3	F4	F7	H7	L0	L1	L4/L4+
TEConcept	<a href="#">IO-Link Device</a>	Factory automation	Source	License	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
	<a href="#">IO-Link Master</a>	Factory automation	Source	License	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
TMGTE TMGTE TMGTE TMGTE TMGTE	<a href="#">IO-Link Device</a>	Factory automation	Source	License	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
	<a href="#">IO-Link Master</a>	Factory automation	Source	License	N	N	Y	Y	Y	Y	Y	Y	N	N	N
	<a href="#">Profibus DP</a>	Factory automation	Source	License	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
	<a href="#">Profinet</a>	Factory automation	Source	License + royalties	N	N	N	Y	N	Y	Y	Y	N	N	N
	<a href="#">Ethernet/IP</a>	Factory automation	Source	License + royalties	N	N	N	Y	N	Y	Y	Y	N	N	N
Rowebots	<a href="#">UNISON Modbus</a>	Factory automation	Source	License	N	N	Y	Y	Y	Y	Y	Y	N	Y	Y



# STM8 – Industrial protocols

90

Provider	Solution name	Application	Model	Cost	Availability	
					STM8S / STM8AF	STM8L / STM8AL
SEGGER	<a href="#">emModbus</a>	Factory automation	Source	License	Y	Y
TEConcept	<a href="#">IO-Link Device</a>	Factory automation	Source	License	Y	Y
TMGTE	<a href="#">IO-Link Device</a>	Factory automation	Source	License	Y	Y



# Application field – Motor control

91


- **Control your 3-phase motor with top performance**

- STM32 microcontrollers offer the performance of the industry-standard Arm® Cortex®-M cores running either Vector control or FOC modes, widely used in high-performance drives for air conditioning, home appliances, drones, building and industrial automation, medical and e-bike applications. STM32 MC SDK (motor control software development kit) firmware (X-CUBE-MCSDK and X-CUBE-MCSDK-FUL) includes the Permanent-magnet synchronous motor (PMSM) firmware library (FOC control) and the STM32 Motor Control Workbench (to configure the FOC firmware library parameters), with its graphical user interface (GUI). STM32 Motor Control Workbench is PC software that reduces the design effort and time needed for the STM32 PMSM FOC firmware configuration. The user generates a project file through the GUI, and initializes the library according to the application needs. Some of the variables of the algorithm being used can be monitored and changed in real time.

Often-seen acronyms	
BLDC	Brushless DC: permanent magnet motor with trapezoidal shaped B-EMF, FOC applicable
PMSM	Permanent magnet synchronous motor: with sinusoidal shaped B-EMF, FOC applicable
ACIM	AC induction motor: type of motor, FOC applicable
FOC	Field-oriented control: Mathematical technique used to achieve decoupled control of the flux and torque in a 3-phase motor.
HFI, MTPA	High Frequency Injection: algorithm for very low speed and fast acceleration (air con, fridge) and increased efficiency for low- or zero-speed, full torque applications (washing machines, factory automation) <ul style="list-style-type: none"><li>• “Maximum Torque Per Ampere” (MTPA): optimizes the motor torque for each load and increases the efficiency,</li><li>• “Feed Forward”: improves the current control at high speed.</li></ul>



# STM32 – Motor control – PMSM

Provider	Solution name	Model	Cost	Availability										
				F0	G0	F1	F2	F3	F4	F7	H7	L0	L1	L4/ L4+
ST 	STM32 Motor Control Software Development Kit (MCSDK) v5.3.3 Software development kit including: <ul style="list-style-type: none"><li>• Motor control library (sensors, algorithms...), Single or Dual control</li><li>•PMSM library for FOC control</li><li>• Motor control application (implementation of library, high-level MC commands)</li><li>• ST Motor Control Workbench software tool</li><li>• Demo projects and utilities</li></ul>	<u><a href="#">X-CUBE-MCSDK</a></u> Source code except CORDIC, MTPA,...  <u><a href="#">X-CUBE-MCSDK-FUL</a></u> Full source code (Registration/approval required)	Free	Y <sup>1</sup>	Y	Y	N	Y	Y	Y	N	N	N	Y

1/ Supports also [STSPIN32F0](#)



# STM32 – Motor control - BLDC

93

Provider	Solution name	Model	Cost	Availability										
				F0	G0	F1	F2	F3	F4	F7	H7	L0	L1	L4/L4+
ST	<a href="#">Bipolar stepper motors driving</a>	Source	Free	N <sup>1</sup>	N <sup>1</sup>	Y	N <sup>1</sup>	N <sup>1</sup>	N <sup>1</sup>	N <sup>1</sup>	N <sup>1</sup>	N <sup>1</sup>	N <sup>1</sup>	N <sup>1</sup>
ST	<a href="#">STSW-IHM040V1</a> STM32 6-step FW example (STM32F100) <a href="#">STSW-IHM043V1</a> STM32 6-step FW example (STM32F0)	Source	Free	Y	N	Y	N	N	N	N	N	N	N	N
ST 	<a href="#">X-CUBE-SPN7</a> Three-phase brushless DC motor driver	Source	Free	Y	N <sup>2</sup>	Y	N <sup>2</sup>	Y	Y	N <sup>2</sup>	N <sup>2</sup>	N <sup>2</sup>	N <sup>2</sup>	N <sup>2</sup>


1/ Can be ported

2/ Available on STM32Cube, so porting is very easy



# STM32 – Motor control - Stepper

94

Provider	Solution name	Model	Cost	Availability										
				F0	G0	F1	F2	F3	F4	F7	H7	L0	L1	L4 /L4+
ST	<a href="#">STSW-STM32018</a> Driving bipolar stepper motors using STM32F103 microcontroller	Source	Free	N	N	Y	N	N	N	N	N	N	N	N
	<a href="#">X-CUBE-SPN1</a> Stepper bipolar motor driver software expansion for STM32Cube	Source	Free	Y	N <sup>1</sup>	N <sup>1</sup>	N <sup>1</sup>	Y	Y	N <sup>1</sup>	N <sup>1</sup>	Y	N <sup>1</sup>	N <sup>1</sup>
	<a href="#">X-CUBE-SPN2</a> Two axes stepper motor driver software expansion for STM32Cube	Source	Free	Y	N <sup>1</sup>	N <sup>1</sup>	N <sup>1</sup>	Y	Y	N <sup>1</sup>	N <sup>1</sup>	N <sup>1</sup>	N <sup>1</sup>	N <sup>1</sup>
	<a href="#">X-CUBE-SPN3</a> High-power stepper motor driver software expansion for STM32Cube	Source	Free	Y	N <sup>1</sup>	N <sup>1</sup>	N <sup>1</sup>	Y	Y	N <sup>1</sup>	N <sup>1</sup>	Y	N <sup>1</sup>	N <sup>1</sup>
	<a href="#">X-CUBE-SPN4</a> Dual-brush DC motor driver software expansion for STM32Cube	Source	Free	N <sup>1</sup>	N <sup>1</sup>	N <sup>1</sup>	N <sup>1</sup>	N <sup>1</sup>	Y	N <sup>1</sup>	N <sup>1</sup>	Y	N <sup>1</sup>	N <sup>1</sup>
	<a href="#">X-CUBE-SPN5</a> Stepper bipolar motor driver software expansion for STM32Cube	Source	Free	N <sup>1</sup>	N <sup>1</sup>	N <sup>1</sup>	N <sup>1</sup>	Y	Y	N <sup>1</sup>	N <sup>1</sup>	Y	N <sup>1</sup>	N <sup>1</sup>

1/ Available on STM32Cube, so porting is very easy



# STM8 – Motor control

95

Provider	Solution name	Model	Cost	Availability	
				STM8S / STM8AF	STM8L / STM8AL
ST	<a href="#">STSW-STM8020</a> STM8S and STM8A BLDC and ACIM motor control firmware library <ul style="list-style-type: none"><li>• Scalar control of induction motor control</li><li>• Scalar control (6-step) of permanent magnet brushless motors (BLDC and PMSM)</li></ul>	Source	Free	Y	N
ST	<a href="#">STSW-STM8042</a> STM8S motor control firmware library builder GUI	Binaries	Free	Y	N



# Application field – Automotive

96

- **More than hardware**

- In addition to microcontrollers dedicated to automotive equipment, ST proposes a set of firmware solutions

Often-seen acronyms	
J1939	Vehicle standard used for communication and diagnostics with vehicle components (e.g. agricultural machines).
J2602	USA variant of LIN
LIN	Local interconnect network: The LIN bus is a small and slow network system that is used as a cheap sub-network of a CAN bus to integrate intelligent sensor devices or actuators in today's cars. The LIN specification is enforced by the LIN-consortium, with the first exploited version being 1.1, released in 1999. Since then, the specification has evolved to version 2.1 and 2.2 to meet current networking needs. Bit rates vary within the range of 1 to 20 Kbit/s.
CAN	Controller-area network (CAN or CAN-bus): This is a standard vehicle bus designed to allow microcontrollers and devices to communicate with each other within a vehicle without a host computer. Possible bit rates from 125 Kbit/s up to 1 Mbit/s.
ASIL	ASIL is a risk classification scheme defined by the ISO 26262 - Functional Safety for Road Vehicles standard. This is an adaptation of the Safety Integrity Level used in IEC 61508 for the automotive industry.





# STM8 – Automotive solutions

97

Provider	Solution name	Model	Cost	Availability	
				STM8AF	STM8AL
ST	<a href="#">J2602 Driver</a>	Source	Free	Y	N <sup>1</sup>
	<a href="#">LIN 2.1 Driver</a>	Source	Free	Y	Y
	<a href="#">STM8A-SafeASIL</a>	Document	Free	Y	N <sup>1</sup>
Simma Software	<a href="#">ssCAN</a>	Source	License	Y	N.A. <sup>3</sup>
	<a href="#">ssJ1939</a>	Source	License	Y	N.A. <sup>3</sup>
	<a href="#">ssl15765</a>	Source	License	Y	N.A. <sup>3</sup>
	<a href="#">ssl14229 (UDS)</a>	Source	License	Y	N.A. <sup>3</sup>
	<a href="#">ssNMEA2000</a>	Source	License	Y	N.A. <sup>3</sup>
Vector	<a href="#">CANbedded</a>	Source	License	Y	N.A. <sup>3</sup>
	<a href="#">CANbedded LIN</a>	Source	License	Y	N <sup>2</sup>
	<a href="#">CANbedded J1939</a>	Source	License	Y	N.A. <sup>3</sup>



# STM32 – CAN / LIN solutions

98

- Warning: STM32 devices are not qualified for automotive, and thus must not be used in automotive application.

Provider	Solution name	Model	Cost	Availability										
				F0	G0	F1	F2	F3	F4	F7	H7	L0	L1	L4/L4+
IHR Gmbh	<a href="#">LIN 2.1 Driver</a>	Source	License	N <sup>1</sup>	N <sup>1</sup>	Y	N <sup>1</sup>	N <sup>1</sup>	Y <sup>2</sup>	Y <sup>3</sup>	N <sup>1</sup>	N <sup>1</sup>	N <sup>1</sup>	N <sup>1</sup>
Simma Software	<a href="#">ssCAN</a>	Source	License	Y	N <sup>1</sup>	Y	Y	Y	Y	Y	N <sup>1</sup>	N.A. <sup>4</sup>	N.A. <sup>4</sup>	Y
	<a href="#">ssJ1939</a>	Source	License	Y	N <sup>1</sup>	Y	Y	Y	Y	Y	N <sup>1</sup>	N.A. <sup>4</sup>	N.A. <sup>4</sup>	Y
	<a href="#">ssl15765</a>	Source	License	Y	N <sup>1</sup>	Y	Y	Y	Y	Y	N <sup>1</sup>	N.A. <sup>4</sup>	N.A. <sup>4</sup>	Y
	<a href="#">ssl14229 (UDS)</a>	Source	License	Y	N <sup>1</sup>	Y	Y	Y	Y	Y	N <sup>1</sup>	N.A. <sup>4</sup>	N.A. <sup>4</sup>	Y
	<a href="#">ssNMEA2000</a>	Source	License	Y	N <sup>1</sup>	Y	Y	Y	Y	Y	N <sup>1</sup>	N.A. <sup>4</sup>	N.A. <sup>4</sup>	Y

# Virtual Machines & Model-driven development

99

High-level languages are available in STM32 ecosystem, as well as model-driven development tools

- **Easier migration**

- ST and 3<sup>rd</sup> parties help customers migrate to these new environments



Environment	Meaning
Javascript	High Level Interpreted Language, typically used in HTML, internet and web related design
Python	High Level Language, interpreted or using a VM (Virtual Machine), popular within scientific community
.NET	C# object-oriented language and Microsoft Visual Studio development environment. This is Microsoft .NET Micro Framework for microcontrollers.
MATLAB/Simulink	Brands from MathWorks company, for software enabling model-driven approach



# STM32 – Virtual Machines and Model-driven development

100

Provider	Description	Model	Cost	Availability											
				WB	F0	G0	F1	F2	F3	F4	F7	H7	L0	L1	L4 /L4+
ST	<a href="#">STM32 Peripheral blocks for Matlab/Simulink</a>	License	Free	N	Y	N	Y	Y	Y	Y	Y	N	Y	Y	Y
Mountaineer	<a href="#">Microsoft .NET Micro Framework</a>	Open source Apache 2.0	Free	N	N	N	Y	Y	N	Y	N	N	N	N	N
Espruino	<a href="#">Javascript</a>	Open source MPLv2	Free	N	N	N	Y	N	N	Y	N	N	N	N	Y
JerryScript	<a href="#">Javascript</a>	Open source Apache 2.0	Free	N	N	N	N	N	N	Y	N	N	N	N	N
Duktape	<a href="#">Javascript</a>	Open source MIT	Free	N	N	N	N	N	N	Y	N	N	N	N	Y
Micropython	<a href="#">Python</a>	Open source MIT	Free	N	N	N	N	N	N	Y	Y	N	N	N	Y

*In addition to the Terms of Use, ST Sales Terms & Conditions and Privacy Policy contained in this Web Site, the following terms and conditions apply to all STMicroelectronics partner programs. Although STMicroelectronics has attempted to provide accurate information on the Web Site, STMicroelectronics assumes no responsibility for the accuracy of the information. All information provided by STMicroelectronics on this Web Site is provided "AS-IS", with all faults and without warranty of any kind, whether expressed, implied or statutory. STMicroelectronics may change or discontinue its partner programs or its products or services at any time and without notice. Any mention of non-STMicroelectronics products or services is for information purposes only and does not constitute an endorsement by STMicroelectronics. The use of the word or term "partner or partners" on this Web Site does not indicate or imply the existence of any partnership or agency relationship or any legal or fiduciary relationship of any kind between STMicroelectronics and any other company or that such company is an affiliate of STMicroelectronics in any way. The partners in STMicroelectronics partner programs provide separate licenses for purchase or use of their products and/or services and related technology with STMicroelectronics devices. Contact the appropriate partner directly for licensing terms, price, support any other information on such partner's product and/or services. The terms and conditions for such products and/or services may vary from partner to partner and are licensed directly and separately from such partner. STMicroelectronics makes no representations or warranties about the suitability of the products and services offered or provided by the partners and STMicroelectronics hereby disclaims all warranties and conditions, whether express, implied or statutory with respect to any product or services provided by the partners, including but not limited to any warranties and conditions of merchantability, fitness for a particular purpose, title, non-infringement or arising from a course of dealing, usage or trade practice. In no event shall STMicroelectronics be liable for any direct, indirect, incidental, special, exemplary, consequential or punitive damages or any damages whatsoever, including but not limited to loss of use, profit or revenue however caused and on any theory of liability, whether in contract, strict liability or tort (including negligence or otherwise) arising in any way out of or in connection with your participation in or your reliance of the partner program, your use or inability to use or purchase of products and/or services from the partners or the performance of such products and services, your relationship with the partner, your use or inability to use or reliance on STMicroelectronics portal or any information provided by STMicroelectronics therein, even if advised of the possibility of such damage. Links to third party Web Sites, when provided by STMicroelectronics, are not under the control of STMicroelectronics and STMicroelectronics is not responsible for any contents, materials, opinions, advice or statements or for the accuracy or reliability of any such contents and materials made on any linked site or any link contained in a linked site, or any changes or updates to such sites. STMicroelectronics is not responsible for any form of transmission received from any linked site, including but not limited to webcasting or audio transmission. Access to any linked site or any link contained in a linked site is at the user's own risk. STMicroelectronics is providing these links to you only as a convenience and the inclusion of any link does not imply any warranty (implied, express or otherwise) or any endorsement by STMicroelectronics of the third party Web Site.*

# Releasing your creativity

16



 [/STM32](https://www.facebook.com/STM32)

 [@ST\\_World](https://twitter.com/ST_World)

 [community.st.com](https://community.st.com)



[www.st.com/stm32](https://www.st.com/stm32)