

Ensemble

Method and Boosting

Son Nguyen

# Netflix Prize

- 1 million USD to any one that can improve Netflix's rating algorithm...

# Netflix Prize

- 1 million USD to any one that can improve Netflix's rating algorithm **by 10%**

# Netflix Prize

- **The winning team:**

# Netflix Prize

- **The winning team:** BellKor's Pragmatic Chaos, used **ensemble models**"

# Netflix Prize

- **The winning team:** BellKor's Pragmatic Chaos, used **ensemble models**"
- **The second-place team's name** is...

# Netflix Prize

- **The winning team:** BellKor's Pragmatic Chaos, used **ensemble models**"
- **The second-place team's name** is "The Ensemble"

# Netflix Prize

- "During the nearly 3 years of the Netflix competition, there were two main factors which improved the overall accuracy:
  - The quality of the individual algorithms, and
  - the **ensemble idea**"



# Ensemble Success

"XGBoost (an ensemble algorithm) is an algorithm that has recently been dominating applied machine learning and Kaggle competitions for structured or tabular data." [Link](#)

# Ensemble Success

Adaboost (an ensemble algorithm) won 2003 **Godel Prize**: AdaBoost demonstrated novel possibilities in analysing data and is a permanent contribution to science even beyond computer science. [Link](#)

# Ensemble Success

AdaBoost (with decision trees as the weak learners) is often referred to as the best out-of-the-box classifier. [Link](#)

# Ensemble Success

Leo Brieman, who invented "Bagging" and "Random Forest" crowned AdaBoost the "best off-the-shelf classifier in the world (2000).

# Ensemble Machine Learning Approach


- An ensemble is a composite model, combining a series of low performing **classifiers**(classification models) or **learners** with the aim of creating an improved classifier.

# Ensemble Machine Learning Approach

- An ensemble is a composite model, combining a series of low performing **classifiers**(classification models) or **learners** with the aim of creating an improved classifier.
- Three common ensemble:
  - Stacking
  - Bagging
  - Boosting


# Stacking

- Stacking combines multiple base learners predictions into a new data set.
- This new data are treated as the **input data** for another learner (meta learner).



# Bagging = Bootstrap Aggregating


- Step 1: Bootstrapping






# Bagging = Bootstrap Aggregating

- Step 2: Aggregating




# Boosting

- Weak learners are sequentially converted into a strong learner.




# Boosting

- Weak learners are sequentially converted into a strong learner.
- Each learner in the sequence tries to correct its predecessor.




# Boosting

- Weak learners are sequentially converted into a strong learner.
- Each learner in the sequence tries to correct its predecessor.
- Individually, Learner 1, Learner 2 and Learner 3 are **weak learners** (a little better than a coin toss).




# Boosting

- Weak learners are sequentially converted into a strong learner.
- Each learner in the sequence tries to correct its predecessor.
- Individually, Learner 1, Learner 2 and Learner 3 are **weak learners** (a little better than a coin toss).
- The learners are usually a tree with 2 leaves (**Stump**).




# Boosting


- Weak learners are sequentially converted into a strong learner.
- Each learner in the sequence tries to correct its predecessor.
- Individually, Learner 1, Learner 2 and Learner 3 are **weak learners** (a little better than a coin toss).
- The learners are usually a tree with 2 leaves (**Stump**).
- In  $D_2$ , the wrong misclassified of Learner 1 gets higher weights.
- In  $D_3$ , the wrong misclassified of Learner 2 gets higher weights.



# Boosting




# Bagging vs. Boosting





# Bagging vs. Boosting



# Types of Boosting

- Adaboost
- Gradient Boosting

# Adaboost









## Idea Behind Ada Boost

- Examples of high weight are shown more often at later rounds
- Face/nonface classification problem:

### Round 1

							
	1/7	1/7	1/7	1/7	1/7	1/7	1/7
best weak classifier:	✓	✗	✓	✓	✗	✓	✗
change weights:	1/16	1/4	1/16	1/16	1/4	1/16	1/4


### Round 2

										
best weak classifier:	✓	✓	✓	✗	✗	✗	✓	✓	✓	✓
change weights:		1/8	1/32	11/32		1/2		1/8	1/32	1/32

## Idea Behind Ada Boost

Round 3



- out of all available weak classifiers, we choose the one that works best on the data we have at round 3
- we assume there is always a weak classifier better than random (better than 50% error)
-  image is half of the data given to the classifier
- chosen weak classifier **has to** classify this image correctly

# Adaboost, Clearly Explained

- Demonstration by StatQuest
- [Link](#)