CISP 41

Programming in C#

Project Evaluation Sheet

Student Name: _____ Bryant Tunbutr _____ Project Number: _____4_____

Project Name: _____BtunbutrProject4_____ Visual Studio Version:___2008_____

Date Due: _____11/22/12_____ Date Turned In: _____11/22/12_____

Above to be completed by student

Points (____ Possible)

Correctness/Efficiency:

Output is accurate _____

Meets all requirements _____

Provide appropriate user interface _____

Logic is efficient _____

Documentation/Coding Style:

Project can be open from the submitted zip file _____

Folder is present and contains all necessary project files (no extra files) _____

Use required coding template _____

Use proper naming and spacing _____

Submit all requested information _____

Test Cases:

List all required test cases _____

Provide output forms for important test cases _____

Other issues: _____

Extra Credit: _____

Timeliness: _____

Project Score: _____

CISP 41 Programming in C#

Project specification

This software is intended to give the spark plug number that is equivalent to other brands.

It is designed to be run in Visual Studio 2008 using the C# coding.

It uses user input including the selected brand and number of the part.

It displays CCC brand number.

Used in the project are arrays, 2-dimensional arrays, methods, list boxes.

CISP 41 **Programming in C#**

Project status

The project is not complete.

I tried for many hours to get the text file into an array of structure.

I was successful in loading the file into string arrays using this code

```
            //Load text file
            TextReader tr = new StreamReader("C:\\Users\\bryantt\\Desktop\\project 4 3
test\\WindowsFormsApplication1\\bin\\Debug\\test.txt");

            //lines loaded
            int NumberOfLines = 5;

            //array for each line
            string[] ListLines = new string[NumberOfLines];

            //Read the number of lines and put them in the array
            for (int i = 1; i < NumberOfLines; i++)
            {
                ListLines[i] = tr.ReadLine();
            }

            //Make array for each line
            string[] ccc = ListLines[1].Split(new Char[] { ',' });
            string[] brandsA = ListLines[2].Split(new Char[] { ',' });
            string[] brandsB = ListLines[3].Split(new Char[] { ',' });
            string[] brandsC = ListLines[4].Split(new Char[] { ',' });

            // close the stream
            tr.Close();
```

However I was never able to get these string arrays to convert into a 2-dimensional array structure.

I tried parsing methods, I tried integer and character and string conversion without success. I also tried making using loops to create 2-dimensional arrays without success.

I also tried just using these arrays but was unable to do so successfully

I do know that these arrays worked in exporting the data from the text file because when used code like the following, I got successful results

```
textBox1.Text = brandsB[3].ToString();
```



I feel that the project is 95% complete, I am just missing one step of converting these string arrays into the 2-dimensional arrays that I used in the finalized project

CISP 41 **Programming in C#**

Sketch of user interface



CISP 41 **Programming in C#**

Objects and Properties Plan for __ BTunbutrProject 4_____Form

Object	Property	Setting
Look Up Button	Name Text	**Method**
Look Up	Name Text	**Button Click**
If loop	Text	**Method**
label	Name Text	**Part Number**
Combo text box	Text	**Drop down**
BTunbutrProject4	Name Text	**Form**
brandsString	Text	**array**
cccString	Text	**array**

CISP 41 **Programming in C#**

Event Plan for ___ BTunbutrProject 4_____Form

Object	Event	Action - Pseudocode
Look Up Button	Click	Call Look Up Button_Click. Display the part number. Run methods with arrays
Part number	Click	Use in method to match
List box	Click	Select array
ccc number	Click	Display method results

CISP 41 Programming in C#

Test cases and captured screens

Test case #1
Nothing selected





Test case #2a
Only a part number is entered



Test case #2b
Only a brand is selected



Test case #3


Christopher's Car Center
Part Number
R43N
Brand A
Brand C
Brand X
Look Up
CCC Part Number


Christopher's Car Center
Part Number
R43N
Brand A
Brand C
Brand X
Look Up
CCC Part Number
PR224

Test case #4

Part #14K44 with each of the brands selected







Test case #5

A non existing part number is entered





Test case #6



Test case #7



Test case #8



Source code

```
/*
* Project: BtunbutrProject4
* Programmer: Bryant Tunbutr
* Date: Nov 22 2012
* Description: Uses array of structures to match part number with brand number
 * I certify that the code below is my own work.
*/

using System;
using System.Collections.Generic;
using System.ComponentModel;
using System.Data;
using System.Drawing;
using System.Linq;
using System.Text;
using System.Windows.Forms;
using System.IO;

namespace WindowsFormsApplication1
{
    public partial class Form1 : Form
    {
        //Create arrays, 2 dimensional for brands
        string[,] brandsString = new string[9, 3];
        string[] cccString = new string[9];

        public Form1()
        {
            InitializeComponent();
        }

        private void lookUpButton_Click(object sender, EventArgs e)
        {
            //Organize by having each brand have same second integer,
            //i.e. Brand A has second integer of 0

            //Brand A
            brandsString[0, 0] = "MR43T";
            brandsString[1, 0] = "R43";
            brandsString[2, 0] = "R43N";
            brandsString[3, 0] = "R46N";
            brandsString[4, 0] = "R46TS";
            brandsString[5, 0] = "R46TX";
            brandsString[6, 0] = "S46";
            brandsString[7, 0] = "SR46E";
            brandsString[8, 0] = "47L";

            //Brand C
            brandsString[0, 1] = "RBL8";
            brandsString[1, 1] = "RJ6";
            brandsString[2, 1] = "RN4";
            brandsString[3, 1] = "RN8";
            brandsString[4, 1] = "RBL17Y";
            brandsString[5, 1] = "RBL12-6";
            brandsString[6, 1] = "J11";
            brandsString[7, 1] = "XEJ8";
            brandsString[8, 1] = "H12";

            //Brand X
            brandsString[0, 2] = "14K22";
```

```
            brandsString[1, 2] = "14K24";
            brandsString[2, 2] = "14K30";
            brandsString[3, 2] = "14K32";
            brandsString[4, 2] = "14K33";
            brandsString[5, 2] = "14K35";
            brandsString[6, 2] = "14K38";
            brandsString[7, 2] = "14K40";
            brandsString[8, 2] = "14K44";

            //CCC NUMBER
            cccString[0] = "PR214";
            cccString[1] = "PR223";
            cccString[2] = "PR224";
            cccString[3] = "PR246";
            cccString[4] = "PR247";
            cccString[5] = "PR248";
            cccString[6] = "PR324";
            cccString[7] = "PR326";
            cccString[8] = "PR444";

            int brandInteger = brandListBox.SelectedIndex;
            int lengthInteger = 9;

            //make sure user has selected and entered data
            if (partNumberTextBox.Text != "" && brandInteger != -1)

                for (int indexInteger = 0; indexInteger < lengthInteger; indexInteger++)
                {
                        //match part number with brand number.
                        if (partNumberTextBox.Text == brandsString[indexInteger,
brandInteger])
                        {
                                //display result.
                                cccPartNumberTextBox.Text = cccString[indexInteger];
                        }
                }

            //check for exeption.
            else
            {
                MessageBox.Show("Missing entry", "Incorrect");
            }
        }

    }
}
```