

# Improving the Efficiency and Scalability of Multi-Drone Coverage Systems

A Decentralized Approach

**Adit Shah**

The Athenian School

**Bryce Ferguson**

Department of Electrical and Computer Engineering  
University of California, Santa Barbara

RMP Research Symposium  
August 1, 2019



# Multi-Drone Coverage Systems





# Multi-Drone Coverage Systems



## Limited Resources

- Not enough drones to cover entire area
- Some areas are more important than others



# Multi-Drone Coverage Systems



## Limited Resources

- Not enough drones to cover entire area
- Some areas are more important than others

**Goal:** Distribute drones effectively based on the utility of each location




# Centralized vs Decentralized Control

## Centralized

One node decides optimal location for each drone, controls navigation


- More easily regulated
- Slower runtimes



## Decentralized

Each drone decides its own optimal location and navigation strategy

- More efficient and scalable
- Doesn't always find global optima



# Enhancing the Decentralized Algorithm




Develop multi-drone  
simulation

Implement and  
compare algorithms


Develop and verify  
enhancements

# Modeling the System



- Map of a region to be covered, where each cell has a utility (importance) value
- Each agent starts at either a random or pre-determined position
- The circle around each agent represents the sensing or coverage radius
- An agent is chosen at random to make a move within its movement radius
- Ultimate goal: maximize the sum of values of the covered cells

# Modeling the System



- Map of a region to be covered, where each cell has a utility (importance) value
- Each agent starts at either a random or pre-determined position
- The circle around each agent represents the sensing or coverage radius
- An agent is chosen at random to make a move within its movement radius
- Ultimate goal: maximize the sum of values of the covered cells



# Decentralized Algorithms



## **Greedy Algorithm** (Baseline approach)

Drones try solely to  
maximize their own  
coverage



## **Log-Linear Learning** (LLL)

Introduces randomness  
Drones occasionally take a  
suboptimal decision



## **LLL with Automatic Tau Generation**

Eliminates need for manual  
tuning of constants

# Decentralized Algorithms



## Greedy Algorithm (Baseline approach)

Drones try solely to  
maximize their own  
coverage

- Agents' only goal is to maximize their utility
- Moves are only made if the new location has a higher utility value:

$$a_i(t + 1) = \arg \max_{a_i \in A_i(t)} U_i(a_i, a_{-i})$$

- Can get stuck at local optima



### Log-Linear Learning (LLL)

Introduces randomness  
Drones occasionally take a  
suboptimal decision



### LLL with Automatic Tau Generation

Eliminates need for manual  
tuning of constants



# Decentralized Algorithms



## Log-Linear Learning (LLL)

Introduces randomness  
Drones occasionally take a suboptimal decision

- Actions chosen based on a probability distribution based on utilities of each action:

$$p_i^{a_i}(t) = \frac{e^{\frac{1}{\tau} U_i(a_i, a_{-i}(t-1))}}{\sum_{\bar{a}_i \in A_i} e^{\frac{1}{\tau} U_i(\bar{a}_i, a_{-i}(t-1))}}$$



## Greedy Algorithm (Baseline approach)

Drones try solely to maximize their own coverage



## LLL with Automatic Tau Generation

Eliminates need for manual tuning of constants

# Decentralized Algorithms



## Log-Linear Learning (LLL)

Introduces randomness  
Drones occasionally take a suboptimal decision

- Value  $\tau$  acts as a randomness or “exploration” constant
- As  $\tau \rightarrow 0$ : Acts as a greedy system
- As  $\tau \rightarrow \infty$ : Actions chosen uniformly at random
- At each time-step,  $\tau$  decays by 0.997



### Greedy Algorithm (Baseline approach)

Drones try solely to  
maximize their own  
coverage



### LLL with Automatic Tau Generation

Eliminates need for manual  
tuning of constants



# Decentralized Algorithms



## LLL with Automatic Tau Generation

Eliminates need for manual tuning of constants

- In LLL, starting  $\tau$  selected manually – can be automated
- Correlates with average map value, agent radius, starting configuration
- For random starting position:  $\tau = \frac{1}{2}\pi R^2 \cdot \bar{M}$
- For starting in one corner:  $\tau = \pi R^2 \cdot \bar{M}$



### Greedy Algorithm (Baseline approach)

Drones try solely to maximize their own coverage




### Log-Linear Learning (LLL)


Introduces randomness  
Drones occasionally take a suboptimal decision

# Algorithm Comparison

Random Starting Configuration




Initial State






# Algorithm Comparison

Random Starting Configuration




Greedy Algorithm




# Algorithm Comparison

Random Starting Configuration




LLL:  $\tau = 40$






# Algorithm Comparison

Random Starting Configuration




LLL:  $\tau = 130$




# Algorithm Comparison

Random Starting Configuration




LLL:  $\tau = 96$  (auto)






# Algorithm Comparison

Corner Starting Configuration




Initial State




# Algorithm Comparison

Corner Starting Configuration




Greedy Algorithm






# Algorithm Comparison

Corner Starting Configuration




LLL:  $\tau = 153$




# Algorithm Comparison

Corner Starting Configuration




LLL:  $\tau = 250$






# Algorithm Comparison

Corner Starting Configuration



LLL:  $\tau = 192$  (auto)



# Algorithm Comparison



## **Greedy Algorithm** (Baseline approach)

Drones try solely to  
maximize their own  
coverage



## **Log-Linear Learning (LLL)**

Introduces randomness  
Drones occasionally take a  
suboptimal decision



## **LLL with Automatic Tau Generation**

Eliminates need for manual  
tuning of constants

# Algorithm Comparison



## **Greedy Algorithm** (Baseline approach)

Drones try solely to  
maximize their own  
coverage



## **Log-Linear Learning (LLL)**

Introduces randomness  
Drones occasionally take a  
suboptimal decision



## **LLL with Automatic Tau Generation**

Eliminates need for manual  
tuning of constants



# Summary

- Simulated multi-agent coverage system
- Implemented and compared greedy, log-linear learning, and automatic  $\tau$  generation algorithms
- Demonstrated that LLL with automatic  $\tau$  generation has the best performance

# Future Work

- Test algorithms on maps with different characteristics
- Additional starting configurations
- Analyze effect of other variables on utility
  - Sensing radius, movement radius, number of agents, distance from other agents, and adding obstacles, limited communication
  - Take into account for  $\tau$  generation
- Verify algorithms on physical multi-drone systems

# Acknowledgements

- Bryce Ferguson (Mentor)
- Jason Marden (PI)
- A S M Iftekhar (TA)
- Dr. Michael Hughes (RMP)
- Dr. Lina Kim (RMP)
- Lab Peers: Siddharth Ganesan, Nischal Sinha

