

AI Interaction Log

Author: Bryce **Date:** 2026-09-25 **AI Tool:** Claude (Cowork)

Task / Prompt

A teammate pushed a UI change directly to `main`. Goal: get that commit off `main` and have the work live on a branch instead (“rebase it onto a newly created branch”).

Context / Findings

- The teammate’s commit `b9ef8fb` (“registration/login ui, profile/resume upload ui”) sat directly on top of `6c663a4` on `main` (a single commit; +10,046 lines, Angular `frontend/CareerConnect` scaffold + login/profile UI).
- That exact commit is **already** on the remote branch `registration-login-ui` (`registration-login-ui` and `main` pointed at the same SHA), so the UI work was already preserved on a branch — no new branch or rebase was actually required.
- Chosen approach: keep `registration-login-ui` as-is; reset `main` back to `6c663a4` and force-push (this rewrites shared history on `main`).

AI Output / Actions

- Inspected repo state; confirmed `registration-login-ui` contains `b9ef8fb`.
- Prepared the reset as a lease-protected force-push: `git push --force-with-lease origin 6c663a4:main`
- Could not execute the push from the AI sandbox: GitHub credentials live on the macOS host and are not reachable from that environment (HTTPS works, but no stored credential / SSH). The command was handed to Bryce to run locally.

Decision

Bryce: The Claude changes were manually verified to have the intended effect, and the suggested terminal commands were executed. Since this was a very small change, no further action was taken.

Reflection

Bryce: This interaction helped me understand how remote git repos are managed, and what commands to use in the future. I have some experience working in git with my own private repo, but being conscious of git best practices with other collaborators is new to me.