

AI Interaction Log

Author: Bryce **Date:** 2026-09-27 **AI Tool:** Claude (Cowork)

Task / Prompt

The replace-user-stories.sh run deleted the old stories fine but errored partway through creating the new ones. Diagnose and finish creating the replacement stories.

Context / Findings

- The delete section worked: old user stories #5-#21 were all removed.
- The create section had a bash bug: `$(cat <<'EOF' ... )` used as a function argument misparsed, causing skips (not corruption). Result: US-01, US-03, US-04, US-05 were created correctly (#38-#41, right titles/bodies/labels/assignees), but US-02 was skipped and US-06..US-10 never ran.
- Verified #38-#41 are complete and correct (labels + both assignees) — nothing to delete.

AI Output / Actions

- Root cause: inline `$(cat <<HEREDOC)` command substitution as a function arg is fragile; the first (working) issue script used `read -r -d ' ' B <<'EOF'` then passed “\$B”, which is robust.
- Produced `create-missing-user-stories.sh` using the reliable read-into-variable pattern, creating only the 6 missing stories: US-02, US-06, US-07, US-08, US-09, US-10 (US-10 assigned MahmoudAbdalla28 + gabibdods + bryceorchard; the rest the first two).
- Noted to re-run `setup-sprint1-board.sh` afterward to add all 10 to the board and regenerate `appendix-a.md`.

Decision

Bryce: Ran the follow-up script to create the six stories that got skipped, then re-ran the board setup so all ten ended up on the board and the appendix regenerated. Confirmed the first four that had already gone through correctly weren't touched.

Reflection

Bryce: The bug turned out to be a bash quoting issue rather than anything about the stories themselves, which was a good reminder that heredocs are fragile when you shove them straight into a command substitution. Good to know the read-into-variable pattern is the safer way to do this.