

TABLE II
NMAC (real-position) summary statistics

Metric	Mean (SA)	Mean (SA-ID)	Mean (Trust-RID)	Std (SA)	Std (SA-ID)	Std (Trust-RID)
Total NMACs (real-position)	3.750	3.750	11.817	3.939	3.939	9.303
Benign-Benign NMACs	3.517	3.517	7.975	3.857	3.857	5.869
Benign-Spoofers NMACs	0.233	0.233	3.842	0.480	0.480	4.199
Min distance to true spoofer (m)	75.226	75.226	38.886	27.398	27.398	15.660
SpoofingAware: chance-constraint violations	1.767	1.767	N/A	2.214	2.214	N/A
SpoofingAware: spoofer containment percent	0.757	0.757	N/A	0.234	0.234	N/A
SpoofingAware: detection reports processed	14.183	14.183	N/A	3.699	3.699	N/A
SpoofingAware: detection callbacks with MLAT attempted	13.483	13.483	N/A	3.101	3.101	N/A
SpoofingAware: detection callbacks skipped (receivers < 4)	0.700	0.700	N/A	1.074	1.074	N/A
SpoofingAware: skipped MLAT fraction during detection	0.040	0.040	N/A	0.059	0.059	N/A
SpoofingAware: raw RSSI/NLLS localization RMSE (m)	75.979	75.979	N/A	27.507	27.507	N/A
SpoofingAware: raw RSSI/NLLS localization MAE (m)	62.871	62.871	N/A	22.172	22.172	N/A