

TABLE II
NMAC (real-position) summary statistics

Metric	Mean (SA)	Mean (SA-ID)	Mean (Trust-RID)	Std (SA)	Std (SA-ID)	Std (Trust-RID)
Total NMACs (real-position)	3.800	3.800	11.817	3.901	3.901	9.303
Benign-Benign NMACs	3.533	3.533	7.975	3.828	3.828	5.869
Benign-Spoofers NMACs	0.267	0.267	3.842	0.498	0.498	4.199
Min distance to true spoofer (m)	74.038	74.038	38.886	28.204	28.204	15.660
SpoofingAware: chance-constraint violations	1.925	1.925	N/A	2.554	2.554	N/A
SpoofingAware: spoofer containment percent	0.733	0.733	N/A	0.270	0.270	N/A
SpoofingAware: detection reports processed	14.183	14.183	N/A	3.699	3.699	N/A
SpoofingAware: detection callbacks with MLAT attempted	13.483	13.483	N/A	3.101	3.101	N/A
SpoofingAware: detection callbacks skipped (receivers < 4)	0.700	0.700	N/A	1.074	1.074	N/A
SpoofingAware: skipped MLAT fraction during detection	0.040	0.040	N/A	0.059	0.059	N/A
SpoofingAware: raw RSSI/NLLS localization RMSE (m)	99.099	99.099	N/A	179.331	179.331	N/A
SpoofingAware: raw RSSI/NLLS localization MAE (m)	79.340	79.340	N/A	132.295	132.295	N/A