

TABLE II
NMAC (real-position) summary statistics

Metric	Mean (SA)	Mean (SA-ID)	Mean (Trust-RID)	Std (SA)	Std (SA-ID)	Std (Trust-RID)
Total NMACs (real-position)	3.275	3.275	4.025	3.341	3.341	3.890
Benign-Benign NMACs	3.092	3.092	2.942	3.236	3.236	3.080
Benign-Spoofers NMACs	0.183	0.183	1.083	0.449	0.449	1.050
Min distance to true spoofer (m)	79.489	79.489	44.907	26.397	26.397	22.827
SpoofingAware: chance-constraint violations	2.050	2.050	N/A	2.771	2.771	N/A
SpoofingAware: spoofer containment percent	0.754	0.754	N/A	0.239	0.239	N/A
SpoofingAware: detection reports processed	14.183	14.183	N/A	3.699	3.699	N/A
SpoofingAware: detection callbacks with MLAT attempted	13.483	13.483	N/A	3.101	3.101	N/A
SpoofingAware: detection callbacks skipped (receivers < 4)	0.700	0.700	N/A	1.074	1.074	N/A
SpoofingAware: skipped MLAT fraction during detection	0.040	0.040	N/A	0.059	0.059	N/A
SpoofingAware: raw RSSI/NLLS localization RMSE (m)	76.193	76.193	N/A	29.053	29.053	N/A
SpoofingAware: raw RSSI/NLLS localization MAE (m)	64.078	64.078	N/A	24.215	24.215	N/A