

Retrieving Data Using Http



Deborah Kurata


CONSULTANT | SPEAKER | AUTHOR | MVP | GDE

@deborahkurata | blogs.msmvps.com/deborahk/







Web Browser



Web Server



(http://mysite/api/products/5)

Response

Module Overview



Observables and Reactive Extensions


Sending an Http Request

Exception Handling

Subscribing to an Observable



Application Architecture



Observables and Reactive Extensions



Reactive Extensions (RxJS)

Help manage asynchronous data

Treat events as a collection

- An array whose items arrive asynchronously over time

Subscribe to receive notifications

Are used within Angular



Observable Operators



Methods on observables that compose new observables

Transform the source observable in some way

Process each value as it is emitted

Examples: map, filter, take, merge, ...

Observables


Interactive diagrams of Rx Observables



`map(x => 10 * x)`



Composing Operators



Compose operators with the pipe method
Often called "pipeable operators"

Composing Operators

Example

```
import { Observable, range } from 'rxjs';
import { map, filter } from 'rxjs/operators';

...

const source$: Observable<number> = range(0, 10);

source$.pipe(
  map(x => x * 3),
  filter(x => x % 2 === 0)
).subscribe(x => console.log(x));
```

Result

0
6
12
18
24



Promise vs Observable

Promise

Provides a single future value

Not lazy

Not cancellable

Observable

Emits multiple values over time


Lazy

Cancellable


Supports map, filter, reduce and similar operators



Application Architecture



Sending an Http Request



Sending an Http Request

product.service.ts

```
...
import { HttpClient } from '@angular/common/http';

@Injectable({
  providedIn: 'root'
})
export class ProductService {
  private productUrl = 'www.myWebService.com/api/products';

  constructor(private http: HttpClient) { }

  getProducts() {
    return this.http.get(this.productUrl);
  }
}
```




Registering the Http Service Provider

app.module.ts

```
...
import { HttpClientModule } from '@angular/common/http';

@NgModule({
  imports: [
    BrowserModule,
    FormsModule,
    HttpClientModule ],
  declarations: [
    AppComponent,
    ProductListComponent,
    ConvertToSpacesPipe,
    StarComponent ],
  bootstrap: [ AppComponent ]
})
export class AppModule { }
```





Sending an Http Request

product.service.ts

```
...
import { HttpClient } from '@angular/common/http';

@Injectable({
  providedIn: 'root'
})
export class ProductService {
  private productUrl = 'www.myWebService.com/api/products';

  constructor(private http: HttpClient) { }

  getProducts() {
    return this.http.get(this.productUrl);
  }
}
```


Sending an Http Request

product.service.ts

```
...
import { HttpClient } from '@angular/common/http';

@Injectable({
  providedIn: 'root'
})
export class ProductService {
  private productUrl = 'www.myWebService.com/api/products';

  constructor(private http: HttpClient) { }

  getProducts() {
    return this.http.get<IProduct[]>(this.productUrl);
  }
}
```

Sending an Http Request

product.service.ts

```
...
import { HttpClient } from '@angular/common/http';
import { Observable } from 'rxjs';

@Injectable({
  providedIn: 'root'
})
export class ProductService {
  private productUrl = 'www.myWebService.com/api/products';

  constructor(private http: HttpClient) { }

  getProducts(): Observable<IProduct[]> {
    return this.http.get<IProduct[]>(this.productUrl);
  }
}
```

Demo



Sending an Http Request



Exception Handling

product.service.ts

```
...
import { HttpClient, HttpResponse } from '@angular/common/http';
import { Observable } from 'rxjs';
import { catchError, tap } from 'rxjs/operators';
...

getProducts(): Observable<IProduct[]> {
  return this.http.get<IProduct[]>(this.productUrl).pipe(
    tap(data => console.log('All: ' + JSON.stringify(data))),
    catchError(this.handleError)
  );
}

private handleError(err: HttpResponse) {
}
```



Subscribing to an Observable



```
x.subscribe()
```

```
x.subscribe(Observer)
```

```
x.subscribe({  
  nextFn,  
  errorFn,  
  completeFn  
})
```

```
let sub = x.subscribe({  
  nextFn,  
  errorFn,  
  completeFn  
})
```



Subscribing to an Observable

product-list.component.ts

```
ngOnInit(): void {  
    this.productService.getProducts().subscribe({  
        next: products => this.products = products,  
        error: err => this.errorMessage = err  
    });  
}
```

```
ngOnInit(): void {  
    this.productService.getProducts().subscribe({  
        next(products) { this.products = products },  
        error(err) { this.errorMessage = err }  
    });  
}
```



Demo



Subscribing to an Observable



Http Checklist: Setup



Add HttpClientModule to the imports array of one of the application's Angular Modules

Http Checklist: Service



Import what we need

Define a dependency for the http client service

- Use a constructor parameter

Create a method for each http request

Call the desired http method, such as get

- Pass in the Url

Use generics to specify the returned type

Add error handling



Http Checklist: **Subscribing**



Call the subscribe method of the returned observable

Provide a function to handle an emitted item

- Normally assigns a property to the returned JSON object

Provide an error function to handle any returned errors

Learning More



Pluralsight Courses

- "Angular: Reactive Forms"
 - HTTP and CRUD
- "RxJS in Angular: Reactive Development"
 - RxJS and Observables
- "Angular HTTP Communication"
 - Intermediate HTTP Techniques

Summary



Observables and Reactive Extensions

Sending an Http Request

Exception Handling

Subscribing to an Observable



Application Architecture

