

RDF - Contenedores

Content

- RDF W3C Overview
- The basis of RDF
 - Internationalized Resource Identifier
 - Literals
 - Blank Nodes
- More features of RDF
- RDF Serialisations
 - Turtle
- RDF Vocabularies
- RDF on the Web
- RDF subtleties

Why IRIs (URIs)?

- IRIs naturally have a “global” scope, unique throughout the web.
 - Contrasts to, e.g., keys in rel. DB which are unique within a table.
- Helps to avoid name clashes.
- Example: merging two product catalogues.
 - <http://www.abc-company.com/category/item/123>
 - <http://www.xyz-company.com/product/123>

Why triples?

- Any information format can be transformed to triples.
- Examples:
 - Tabular (spreadsheets, DBs): row column cell
 - Trees (XML): parent path child
- Relationships are made explicit and elements in their own right.
 - The predicate, i.e., the relationship, is an element in the triple.
 - Unlike DB columns and binary predicates.
 - Can be described in RDF.

Why graphs?

- A single, but highly versatile, format.
 - Everything is on the same format: triples!
 - Since RDF graphs are just sets of triples, basic set operations are well-defined.
- Merging RDF graphs? Just take their union!
 - With tabular data, table dimensions must match.
 - With trees, a node can only have one parent.
 - Note that graphs need not be connected.
- Extending an RDF graph? Just add more triples!
 - Need not redefine the database table, or to restructure the XML schema.

Content

- RDF W3C Overview
- The basis of RDF
 - Internationalized Resource Identifier
 - Literals
 - Blank Nodes
- More features of RDF
- RDF Serialisations
 - Turtle
- RDF Vocabularies
- RDF on the Web
- RDF subtleties

Some more features of RDF

- Types of resources
- Containers
- Collections
- Reification

RDF – types of resources


- RDF has a special property for **is-a** relations: **rdf:type**
 - `<http://www.polleres.net/foaf.rdf#me> rdf:type ex:Person.`
 - `<http://www.polleres.net/foaf.rdf#me> is-a ex:Person.`
 - `ex:Ucuenca rdf:type ex:Universidad .`
 - `ex:Ucuenca is-a ex:Universidad .`

RDF Containers

- RDF provides 3 types of **Containers**
 - **rdf:Bag** Unordered list of resources or literals.
 - might be used to describe a group of part numbers in which the order of entry does not matter
 - **rdf:Sequence** Sequence, ordered list of resources or literals.
 - might be used to describe a group that must be maintained in alphabetical order
 - **rdf:Alt** Alternative, list of resources or literals that are alternatives for the (single) value.
 - might be used to describe alternative language translations for the title of a book


RDF Containers: example

- Course 6.001 has the students Amy, Mohamed, Johann, Maria, and Phuong
- What containers?
 - `rdf:Bag`



RDF Containers: example

- The source code for X11 may be found at `ftp.example.org`, `ftp1.example.org`, or `ftp2.example.org`
- What containers?
 - `rdf:Alt`




RDF Collection

- Similar to RDF containers, but resolves collection as a list structure
- This list structure is constructed using a predefined *collection vocabulary*
 - rdf:list
 - rdf:first
 - rdf:rest
 - rdf:nil

RDF Collection example

- The students in course 6.001 are Amy, Mohamed, and Johann



Reification

- Latin res ("Thing"), facere ("make")
 - an Explication
- In rdf statement about statements


"Peter says that Rome is the capital of Spain."

Implementation:


 - RDF Statements are considered resources themselves
 - Can be subject or object of other statements
- Reification can have multiple levels
 - "Peter says that Wikipedia states that Rome is the capital of Spain."

Reification in RDF

- "Peter says that Rome is the capital of Spain."



Implementing Reification as Standard RDF



Práctica 7