ARDUINO

+

THE WORLD

HID

ARDUINO -> COMPUTER

BUTTON INPUT



keyboard | Arduino 1.8.16

keyboard

```
#include "Keyboard.h"

const int BUTTON_PIN = 11;

void setup() {
  pinMode(BUTTON_PIN, INPUT_PULLUP);

  // initialize control as a keyboard
  Keyboard.begin();
}

void loop() {
  // read the pushbutton:
  int val = digitalRead(BUTTON_PIN);

  if (val == LOW) {
    Keyboard.print("x");
    delay(100);
  }
}
```

Done uploading.

```
done in 0.019 seconds
CPU reset.
```

17 Adafruit Feather M0 Express, Small (-Os) (standard), Arduino, Off on /dev/cu.usbmodem14201

TRANSLATE BUTTON PRESS INTO KEYBOARD PRESS

RESPOND TO KEYBOARD PRESSES



POTENTIOMETER (OR OTHER ANALOG SENSOR) INPUT



WRITE VALUES VIA SERIAL WITH ARDUINO





READ VALUES VIA SERIAL WITH PROCESSING

SERIAL

ARDUINO -> PROCESSING

PRINT MESSAGE VIA SERIAL



BUTTON INPUT



WRITE VALUES VIA SERIAL WITH ARDUINO



READ VALUES VIA SERIAL WITH PROCESSING

button_in | Processing 4.0b2

Java ▾

button_in

```
1  import processing.serial.*;
2
3  Serial port;
4  int val = 0;
5
6  void setup() {
7    size(200, 200);
8    noStroke();
9
10   printArray(Serial.list());
11   String portName = Serial.list()[2];
12   port = new Serial(this, portName, 9600);
13 }
14
15 void draw() {
16   background(255);
17   if (val == 1) {
18     fill(255, 0, 0);
19   } else {
20     fill(0);
21   }
22   rect(50, 50, 100, 100);
23 }
24
25 void serialEvent(Serial port) {
26   val = port.read();
27 }
28
29
```

Console Errors Updates 3

POTENTIOMETER (OR OTHER ANALOG SENSOR) INPUT



WRITE VALUES VIA SERIAL WITH ARDUINO





READ VALUES VIA SERIAL WITH PROCESSING

PROCESSING -> ARDUINO

PWM LED OUTPUT



WRITE VALUES VIA SERIAL WITH PROCESSING



READ VALUES VIA SERIAL WITH ARDUINO