BROKEN ARROW API Design

Author: Battula Sai Krishna

1) Login API:

Request Parameters

http://10.113.59.147:8085/Broken Arrow App/login/

```
HTTP Method: POST
```

Header Parameters:

Content-Type: application/json

POST Data (Raw Payload in JSON format)

```
{
"username":"battula.krishna@subex.com",
"password":"battula.krishna@subex.com",
"device_id": "10s92092",
"os_type":"Andriod"
}
```

Response from API:

Response Format: JSON

If correct login Credentials are passed.

```
"full name": "Battula Sai Krishna ",
"status": true,
"email": "battula.krishna@subex.com",
"message": "Login Successfull",
"all region": [
                  "APAC",
                  "EMEA"
              ],
"all product": [
                   "RA",
                   "FM"
               ],
"region product risk": [
                                     "region": "APAC",
                                     "product": "RA",
                                     "color": "Red"
                               }
```


{

```
"region": "EMEA",
                                                   "product": "FM",
                                                   "color": "Green"
                                            }
                                            {
                                                   "region": "EMEA",
                                                   "product": "RA",
                                                   "color": "Red"
                                            }
                                     ],
   }
   If Incorrect login credentials are passed.
          "full_name": null,
          "status": false,
          "email": null,
          "message": "Incorrect Username/Password",
          "all region": [],
          "all product": [],
          "region product risk": [],
   }
2) Sites which are at risky State API:
   Request Parameters
   http://10.113.59.147:8085/Broken Arrow App/customers
   HTTP Method: POST
   Header Parameters:
   Content-Type: application/json
   POST Data (Raw Payload in JSON format)
   "product":"'RA','PS'",
   "region":"'EMEA'"
   Response from API:
   Response Format: JSON
   ſ
          {
                 "cust_id": "DAAGRP-10",
                 "cust name": "Iran",
```

"region": "EMEA",

```
"product": "RA",
      "overall_status": "Red",
      "risk_percentage": 100,
      "received date": "10-Apr-17",
      "ack by": "Vaibhav",
      "ack date": "10-Apr-17",
      "eta duration": "30",
      "issue_running_since": "20"
}
      "cust id": "MTNGRP-10",
      "cust name": "MTN Zambia",
     "region": "APAC",
      "product": "RA",
      "overall_status": "Red",
      "risk_percentage": 80,
      "received_date": "10-Apr-17",
      "ack by": "Sai",
      "ack date": "10-Apr-17",
      "eta duration": "30",
      "issue running since": "20"
}
```

APP Screen:



3) Customer Search API:

Request Parameters

http://10.113.59.147:8085/Broken Arrow App/customerslist

HTTP Method: POST

Response from API:

Response Format: JSON

```
[
  "MTN Zambia",
  "Jawwal",
  "Iran"
]
```

4) Homepage Updation based on Region and Product Filter API:

Request Parameters

```
http://10.113.59.147:8085/Broken Arrow App/homepage
```

```
HTTP Method: POST

Header Parameters:

Content-Type: application/json

POST Data (Raw Payload in JSON format)

{

"product":"'RA','PS'",

"region":"'EMEA'"
```

Response from API:

Response Format: JSON

```
{
    "region": "EMEA",
    "product": "FM",
    "color": "Green"
}

{
    "region": "EMEA",
    "product": "RA",
    "color": "Red"
}
```

APP Screen:

