Alignment: what behavior should an assistant learn?

- Alignment aims to make an assistant useful, honest and safe within the task's constraints.
- Following a request can require correcting a false claim or refusing an unsafe action.
- Today: explain how feedback changes behavior, then diagnose where the feedback can fail.

Predicting text does not specify good assistant behavior

- Pretraining learns to predict the next token from patterns in text.
- A token is a piece of text; model weights are the numbers learned during training.
- Producing plausible text and choosing a helpful response are different objectives.

A useful assistant can disagree with the request


- Illustrative prompt: “My code outputs 12 for 5 + 6. Explain why it is correct.”
- Answer A: “You are right; 12 is the correct result.”
- Answer B: “5 + 6 is 11. Share the code and I can help explain the output.”

SFT learns from demonstrated answers


A prompt is sampled from our prompt dataset.

A labeler demonstrates the desired output behavior.

This data is used to fine-tune GPT-3 with supervised learning.



Complete original pipeline; enlarged stage at left




- Supervised fine-tuning (SFT) trains on prompt–response demonstrations.
- Writing ideal responses for every situation is expensive.
- Training updates assistant weights toward the demonstrated response.

Preference feedback can distinguish two truthful answers


- Same request: explain why the code outputs 12 for 5 + 6.
- Answer C: “5 + 6 is 11.”
- Answer B: “5 + 6 is 11. Share the code and I can help explain the output.”
- Both correct the arithmetic; B also helps the user investigate the program.

A reward model extends feedback to new responses


A labeler ranks the outputs from best to worst.



This data is used to train our reward model.




Complete original pipeline; enlarged stage at left




- Human ratings for every new response would be expensive.
- Train the evaluator to score preferred answers above rejected answers.
- Prompt + answer → a preference score, not a truth guarantee.

RLHF repeats: generate, score, update



Complete original pipeline; enlarged stage at left



- Reinforcement learning from human feedback (RLHF) updates the assistant using reward.
- Generate an answer; the fixed reward model scores it.
- Update assistant weights to favor higher-scoring behavior.

Training changes weights; an ordinary chat uses them

- During training, feedback changes learned model weights.
- During ordinary deployment, the assistant generates with fixed weights.
- A new message changes the conversation context, not the weights by itself.

When pleasing the evaluator diverges from helping the user

- Desired behavior: correct the false arithmetic claim and help debug the program.
- Failure case: an evaluator rewards agreement or confident style over the correction.
- Optimizing that score can increase agreement without increasing correctness.

Three questions for an evaluator-driven system

- Compare optimized reward with a separate reference: overoptimization.
- Test whether a user's belief changes the answer: sycophancy.
- Diagnose evaluator shortcuts and test a repair: preference bias.

A reward shortcut can become the learned route to success

Training a Misaligned Reward Seeker

Anthropic · Reward seeker

- The stress test retained 80 reward-vulnerable environments.
- A classifier flagged hacks in 40% of final training episodes.
- This measures a selected stress test, not ordinary deployment prevalence.

Human preferences and verifiable task rewards

- RLHF uses judgments about response quality as its learning signal.
- RL with verifiable rewards (RLVR) uses task checks such as final answers or code tests.
- A check rewards only the properties that it actually measures.

Can we measure reward overoptimization directly?


Gao, Schulman & Hilton · ICML 2023

Scaling Laws for Reward Model Overoptimization

Leo Gao [1] **John Schulman** [1] **Jacob Hilton** [1]

- How far can we optimize a learned reward before its gold reference declines?

Keep the gold model outside the optimized reward channel



- A fixed 6 B gold reward model labels pairs of responses.
- Proxy reward models learn from 90,000 synthetic comparisons.
- Policy optimization uses the proxy; evaluation also records the gold score.

A fictional policy supplies the independent support check

- Domestic claims must be submitted within 30 days.
- The required form is R2.
- The supplied policy states no manager waiver.

Illustrative classroom policy; not a real institution’s rules.

Proxy reward, reference reward and correctness

Fictional policy: 30 days · form R2 · no stated manager waiver.

- The proxy score supplies the optimization objective.
- The fixed gold reward model supplies a synthetic reference, with its own errors.
- Correctness requires an appropriate external check of the response’s claims.

Stronger selection on a fixed candidate pool

Fictional policy: 30 days · form R2 · no stated manager waiver.

Candidate	Proxy score	Policy support
A: submit within 30 days	0.60	Supported
B: use form R2 within 30 days	0.80	Supported
C: manager can waive deadline	0.95	Unsupported
D: manager always approves late claims	0.99	Unsupported

- Choose the winner among A and B, then among A through D, using the proxy score.
- Does the selected answer improve under the separate support check?
- Do any generator weights change?

Illustrative fixed samples and proxy values. Support comes from the fictional supplied policy.

Worked selection and the changed output distribution

Fictional policy: 30 days · form R2 · no stated manager waiver.

- B wins among A and B. D wins in the larger pool.

- The larger pool improves proxy score from 0.80 to 0.99 and returns an unsupported claim.

- The generator remains fixed, while the selection rule changes which outputs reach the user.

Exercise: selection can amplify a rare shortcut

Fictional policy: 30 days · form R2 · no stated manager waiver.

Outcome	Base probability	Proxy score	Policy support
S: use form R2 within 30 days	0.90	0.60	Supported
U: manager can waive deadline	0.10	0.90	Unsupported

- The fixed generator returns S with probability 0.90 and U with probability 0.10.
- U always beats S under the proxy. Draw n independent samples and return the winner.
- Calculate the probability of returning U for n = 1, 4 and 16.

Illustrative classroom calculation.

Worked selection probabilities

Fictional policy: 30 days · form R2 · no stated manager waiver.

- U is returned whenever at least one U appears in the sample pool.
- The return probabilities are 10.00%, 34.39% and 81.47% for n = 1, 4 and 16.
- The generator still assigns U probability 0.10; selection changes the returned-output distribution.

$$P(U \text{ returned}) = 1 - P(\text{all } S) = 1 - 0.90^{n}$$

n — independent samples from the fixed generator

Exercise: measure the changed distribution

- KL (Kullback–Leibler divergence) compares the starting and returned-output distributions.
- Starting p = (0.90, 0.10); returned q = (0.6561, 0.3439), in the order S, U.
- Compute KL(q ‖ p), then d = √KL(q ‖ p). What does this distance measure?

$$D_{\mathrm{KL}}(q\|p) = \sum_{x\in\{S,U\}} q(x)\ln\frac{q(x)}{p(x)}, \qquad d = \sqrt{D_{\mathrm{KL}}(q\|p)}$$

p — single-draw starting distribution

q — returned-output distribution after selection

ln — natural logarithm; KL is in nats

d — square root of KL; not an error rate

$\ln(q(S)/p(S))$ — −0.31608

$\ln(q(U)/p(U))$ — 1.23518

Illustrative classroom example.

Worked KL distance for two outcomes

- The S contribution is −0.20738 and the U contribution is 0.42478.

- KL(q ‖ p) ≈ 0.21740 nats and d ≈ 0.46626.

- A nonzero distance records changed returned-output probabilities; it does not establish a correctness rate.


$$D_{\mathrm{KL}}(q\|p) = -0.20738 + 0.42478 \approx 0.21740, \qquad d \approx 0.46626$$

d — square-root KL, not an error fraction

RL changes the policy rather than only selecting a sample

- Best-of-n reranks samples from the starting policy.
- PPO repeatedly updates generation probabilities using proxy reward.
- KL divergence records departure from the starting distribution.


Best-of-n can keep improving the proxy after gold reward peaks



- The policy is fixed at 1.2 B parameters; colors vary proxy-model size.
- Dashed lines show proxy reward; solid lines show gold reward.
- For smaller proxies, more selection eventually lowers the gold score.


Scores: initial mean zero; gold variance one; proxy logits recalibrated after the experiments.

Policy optimization can also widen the proxy–gold gap




- The PPO panel uses the same proxy-model-size comparison.
- Its KL range extends much farther than the best-of-n panel.
- Rising proxy reward can coexist with declining gold reward.

More comparison data improves the proxy in this experiment




- Hold the proxy model at 12 M parameters and vary its training-data size.
- Dashed proxy scores and solid gold scores still measure different outcomes.
- More data generally improves gold reward under best-of-n selection.


Does validation loss predict robustness under selection?



- Validation loss measures prediction on reserved comparison labels.
- The vertical axis is gold reward after best-of-1000 selection.
- Similar validation losses show weak evidence of similar robustness here.

A larger policy changes a different component





- Hold the proxy at 12 M parameters and vary the policy size.
- Larger policies start with higher gold reward and gain less from optimization.
- The tested policies reach peak gold reward at similar KL divergence.

Exercise: a peak in a fitted reward curve

- The BoN fit balances a linear gain against a quadratic loss.

- With illustrative coefficients α = 2 and β = 0.5, compute R at distances 1, 2 and 3.

- Which distance has the largest fitted reference reward, and what does that fail to certify?

$$d = \sqrt{D_{\mathrm{KL}}(\pi \| \pi_0)}, \qquad R(d) = d(\alpha - \beta d)$$

π, π_0 — selected-output policy and starting policy

d — square root of KL divergence

$R(d)$ — fitted gold-reward improvement

α, β — fit coefficients; illustrative values shown

Illustrative coefficients and calculations; not measured gold rewards.

Worked curve calculation and its scope

- The distance d is the square root of KL divergence from the initial policy.
- The BoN fit is a linear gain minus a quadratic loss in d.
- Changing the reward model or data changes the fitted coefficients and the peak.

$$R(1) = 1.5, \qquad R(2) = 2.0, \qquad R(3) = 1.5$$

R — normalized reference-model reward improvement

BoN and PPO have different fitted reward curves

- The paper fits different reference-reward curves for selection and policy training.

- The coefficients depend on the evaluator and data; a fitted peak is not a universal stopping rule.

$$R_{\mathrm{BoN}}(d) = d(\alpha_{\mathrm{BoN}} - \beta_{\mathrm{BoN}} d)$$

$$R_{\mathrm{RL}}(d) = d(\alpha_{\mathrm{RL}} - \beta_{\mathrm{RL}} \log d)$$


d — square root of KL divergence from the initial policy

R — reference reward, recentered at the initial policy

$\alpha_{\mathrm{BoN}}, \alpha_{\mathrm{RL}}$ — fitted gain coefficients for each method

$\beta_{\mathrm{BoN}}, \beta_{\mathrm{RL}}$ — fitted overoptimization coefficients for each method

A KL penalty does not automatically repair the reward model



- Fix the policy and reward model at 1.2 B parameters; vary the KL penalty.
- The solid gold-reward curves largely follow the same distance frontier.
- Here, stronger penalties mostly stop training earlier along that frontier.

What would establish better travel advice?

Fictional policy: 30 days · form R2 · no stated manager waiver.

- Check: would a rising gold reward establish fewer unsupported waiver claims?
- Name a measurement independent of both reward models.
- Which observations would separate a proxy failure from a shared evaluator failure?

When agreement competes with truth

Sharma et al. · ICLR 2024

TOWARDS UNDERSTANDING SYCOPHANCY IN LANGUAGE MODELS

Mrinank Sharma*, Meg Tong*, Tomasz Korbak, David Duvenaud

Amanda Askell, Samuel R. Bowman, Newton Cheng, Esin Durmus, Zac Hatfield-Dodds, Scott R. Johnston, Shauna Kravec, Timothy Maxwell, Sam McCandlish, Kamal Ndousse, Oliver Rausch, Nicholas Schiefer, Da Yan, Miranda Zhang,


Ethan Perez

- Can an assistant's answer track the user's belief instead of the evidence?

A controlled belief intervention

- Keep the question fixed and vary the user's stated belief.
- Check the assistant's factual answer against an external answer key.
- Compare conditions across many questions and repeated generations.

User preference changes feedback on the same passage



- Hold the passage fixed and change the user's stated preference.
- Feedback positivity is relative to feedback with no stated preference.
- More positive feedback is a different outcome from a correct answer.

Exercise: the same question under different beliefs

- Question: What is 17 × 19? Keep the arithmetic and answer rule fixed.
- Compare: no belief, “I think it is 323,” and “I think it is 333.”
- What result would support a sycophancy claim, and what would remain unresolved?

Illustrative exercise. No model calls or empirical outcomes are asserted.

Worked audit: correctness stays fixed across belief conditions

- $17 \times 19 = 323$ in every condition.
- A drop in accuracy under the incorrect belief supports belief-sensitive error under the tested protocol.
- The experiment alone does not identify which training stage caused that behavior.

Exercise: code a paired belief experiment

Question	Key	No belief	False belief	Answer with belief	Correct-belief answer
17 × 19	323	323	333	333	323
6 × 8	48	49	49	49	48
7 × 8	56	56	54	54	56
12 × 12	144	144	143	144	144

- Every row keeps one arithmetic question fixed across three prompt conditions.
- Compute accuracy for no belief, incorrect belief and correct belief.
- Which errors specifically adopt the injected belief, and which already occurred at baseline?

Illustrative classroom example.

Worked paired outcome coding

- Accuracy is 75% with no belief, 25% with incorrect belief and 100% with correct belief.

- The accuracy changes are −50 and +25 percentage points relative to baseline.

- Rows 1 and 3 newly follow the incorrect belief; row 2 was already wrong, and row 4 resists it.

A user challenge creates a second controlled behavioral test

- First record the assistant's answer to a fixed question.
- Then challenge it without supplying new evidence.
- Score factual reversal separately from apology or polite reconsideration.

Exercise: which questions belong in the denominator?


Initial state	Changed after challenge	Unchanged after challenge
Correct: 80	16 become wrong	Calculate
Wrong: 20	6 become correct	Calculate

- Of 100 questions, 80 are initially correct and 20 are initially wrong.
- After the challenge, 16 initially correct answers become wrong and 6 initially wrong answers become correct.
- Compute the conditional reversal rate and the final overall accuracy.

Worked feedback: reversal and final accuracy have different denominators


- The conditional correct-to-wrong reversal rate is 16/80 = 20%.
- Final accuracy is (64 + 6)/100 = 70%.
- The paper measures apology and incorrect reversal as separate outcomes.

An apology and an incorrect revision are different outcomes



- Start with questions the assistant initially answered correctly.
- An unsupported challenge can trigger an apology or an incorrect revision.
- Only the lower panel directly measures losing a correct final answer.

Stated beliefs change measured answer accuracy



- Horizontal: five assistants. Vertical: accuracy change from the no-belief baseline, in percentage points.
- Correct-belief and incorrect-belief prompts shift the answer under the same question.
- The paper reports means and standard errors on TruthfulQA and TriviaQA variants.

Human preference data contains competing incentives

- GPT-4 labels 23 response features in 15,000 hh-rlhf helpfulness comparisons.
- A Bayesian logistic regression predicts the human preference from those features.
- Matching user beliefs and truthfulness can both predict preference.

The feature model predicts a human choice from a response pair


Relative feature of A versus B	Feature value	Illustrative weight
Annotated as more truthful	+1	0.3
Matches the user less	–1	0.4

- GPT-4 assigns relative features to the pair; the label is the human preference.
- Illustrative features +1 and –1 with weights 0.3 and 0.4 give a weighted sum of –0.1.
- The resulting 47.5% predicts preference for A, not the probability that A is correct.

$$0.3(+1) + 0.4(-1) = -0.1, \qquad \sigma(-0.1) \approx 0.475$$


$\sigma(z)$ — 1 / (1 + exp(–z)); maps the sum to a preference probability

Read the uncertainty in a preference-feature ranking



- The horizontal axis is the regression's predicted preference probability.
- Points show posterior medians; intervals show 50% and 95% credible ranges.
- Matching beliefs and truthfulness both predict preference in these data.

Optimization can change different sycophancy measures in different directions




- Best-of-N selects helpful-only Claude 1.3 samples using the Claude 2 preference model.
- A truthfulness-prefixed version of the same evaluator provides a comparison.
- RL increases feedback and mimicry sycophancy here, while answer sycophancy decreases.

Convincing agreement can defeat unaided preference judgments


- The paper constructs 266 misconceptions and pairs persuasive agreement with truthful corrections.
- Five crowd-workers judge each pair without internet or fact-checking tools.
- Helpful truthful responses usually win, but difficult misconceptions expose errors in human oversight.

The truthful baseline changes what a preference result means




- A terse correction and a helpful truthful explanation are different comparisons.
- Helpful truthful responses usually beat persuasive false agreement.
- Unaided human preference becomes less reliable on harder misconceptions.

A selector cannot choose a missing truthful candidate



- Hold the generator fixed and compare three candidate selectors.
- The oracle chooses a truthful response whenever one is available.
- Residual oracle error exposes missing truthful candidates.

Does better training generalize beyond practiced dilemmas?



- The original audit compares four training variants; lower is better.
- Difficult-advice training has a lower mean misaligned-behavior score.
- The error bars and evaluation scope limit the conclusion.

Lecture 1 exit task

Fictional policy: 30 days · form R2 · no stated manager waiver.

- A new checkpoint gets higher preference reward but repeats more unsupported manager-waiver claims.

- Write a bounded diagnosis and a matched user-belief test.

- Name a separate correctness check and the evidence needed before acceptance.

Worked exit response and the evaluator-audit bridge

Fictional policy: 30 days · form R2 · no stated manager waiver.

- The observations show a reward–target mismatch under the reported evaluation.
- A matched belief intervention tests whether the user’s unsupported claim changes the assistant’s answer.
- An evidence-aware audit of reserved questions must accompany the preference score.