

USV Modeling

Brian Bingham¹

I. INTRODUCTION

The goal of this effort is to develop a USV model that

- Is appropriate for design and evaluation of control algorithms
- Balances fidelity with capacity for empirical parameter estimation
- Can be identified using static tests and maneuvering trials with a USV and on board sensors
- Makes use of physically measurable quantities (mass and inertia)
- Enables prediction of dynamics with and without water current

II. BACKGROUND

Below is a survey of a small number of the relevant prior work on modeling USVs for control.

A. [Fossen, 1994] and [Fossen, 2011]

The maneuvering models described by Fossen appear to be the basis for most of the USV work. The references contain a number of different generic models and extensions of these models for specific cases. The focus tends to be on full-sized surface ships and platforms, but are relevant to small USVs.

B. [Sonnenburg et al., 2010] and [Sonnenburg and Woolsey, 2013]

[Sonnenburg and Woolsey, 2013] and [Sonnenburg et al., 2010] examine model for USV with steerable outboard motor (vectored thrust) where sideslip is a major concern. Uses notation and maneuvering model from [Fossen, 1994].

- Full vessel model is includes linear and quadratic damping
- All models are then linearized (perturbation dynamics) for the purpose of identification where the coefficients are parameterized by the states (surge, sway and yaw-rate)
- Actuation model thrust as a linear and quadratic with velocity dependence.

¹ Brian Bingham is with the Department of Mechanical and Aerospace Engineering, Naval Postgraduate School, Monterey, CA 93950, USA. bbingham@nps.edu

Model identification appears to throw out the physical model and rely on identification of linear models (perturbation models) and a set of discrete speeds.

- Model identification includes open-loop maneuvers to identify steady-state parameters and closed-loop maneuvers to identify dynamic parameters.
 - 1) Steady-state values are identified by as linear relationships between yaw-rate, side-slip angle and side-slip speed. The coefficients of these a relationships are determined for a set of discrete, constant speeds. The values of these coefficients change significantly over the range of forward speeds and now functional relationship is offered.
 - 2) Thruster model conflates both the thrust relationship and the inertia of the system. Model is identified by measuring initial acceleration during step changes in engine RPM and identifying the two linear coefficients of a linear model. This single model is constant over the range of speeds. Sparse data at higher speeds.
 - 3) Speed/surge is modeled as first-order model parameterized over speed range.
 - 4) Steering model (first order Nomoto model with sideslip) is identified by minimizing a quadratic cost function of sideslip angle and yaw-rate over close-loop time histories. Again, the linearized models have coefficients that change with speed. The results again show significant changes over the speed envelope without offering a functional relationship.

C. [Caccia et al., 2008]

Uses the nonlinear model of Blanke [Blanke, 1981] as reported in [Fossen, 1994]. Speed/surge model:

- Neglects added mass term based on Blanke comments. Blanke suggests that the surge added mass term “will typically be less than 5%” [Fossen, 1994].
- Neglects r^2 terms, as suggested by Blanke, based on assuming reasonable low yaw-rate ($\dot{\psi}$ 10 degrees/s).
- Assumes linear+quadratic drag. The Blanke model reported in [Fossen, 1994] includes only the quadratic term.
- Neglects the Coriolis terms based on assuming negligible sway velocity. The experimental evidence from [Sonnenburg and Woolsey, 2013] and [Sonnenburg et al., 2010] indicate that there is a significant sideslip angle, hence a significant sway velocity.

Steering model

- Neglects added mass in surge and yaw.

Sway (sideslip) was not observable in experiments! Used only GPS and heading for identification making making many of the estimated quantities unreliable or unobservable.

Thrust model neglects speed of advance, assumes thrust is independent of vessel speed.

III. SIMPLIFIED MODELS FOR CONTROL

The horizontal-plane maneuvering model uses the state vector $\nu = [u, v, r]^T$ where the velocities u , v and r are in the surge, sway and yaw directions respectively.

Euler angles for angular displacements/velocities are

- roll ϕ , $p = \dot{\phi}$
- pitch θ , $q = \dot{\theta}$
- yaw ψ , $r = \dot{\psi}$

We consider control to regulate the forward speed (u) and the yaw angle (ψ) simultaneously.

A. Linear Models

This is the simplest model and is useful as a benchmark for control performance.

- linear dynamics
- linear thrust model
- unbounded thrust
- uncoupled dynamics (surge/sway/yaw)

Control inputs:

- X_c is total control force in the surge direction.
- N_c is the total control torque in the yaw direction.

Surge model

$$m\dot{u} + X_u u = X_c$$

where m is the total mass, both rigid body and added mass, and X_u is the linear drag.

Yaw model

$$I_z \ddot{\psi} + N_r \dot{\psi} = N_c$$

where I_z is the total inertia in the yaw direction and N_r is the linear drag.

Here are some rough physical parameters to use.

- $m = 28 \text{ kg}$: based on weight specified by clearpath. Ignores added-mass. Should weigh our actual USV to verify.
- $X_u = \frac{1.5 \text{ m/s}}{40 \text{ N}} = 0.0375 \text{ m/Ns}$: based on linear interpretation of Figure 2.
- $I_z = 28 \text{ kg}(0.5 \text{ m})^2 = 6.25 \text{ kgm}^2$: based on approximation of USV as thin disc.
- $N_r = \frac{0.25 \text{ rad/s}}{8 \text{ Nm}} = 0.0313 \text{ rad/Nms}$: based on linear interpretation of Figure 3.

1) *Linear Model Control: PID*: With this specific model, we can apply build a two PID controllers - one for the surge model (PI control) and one of the yaw model (PD control). Use Zeigler-Nichols, or similar, tuning process to standardize the tuning. Use this as a baseline for closed-loop performance.

2) *Linear Model Control: PID+*: Consider adding a feedforward term to the surge PI controller to anticipate drag. (This isn't really applicable to the yaw controller.) See [Caccia and Veruggio, 2000] for an example of such an architecture, which includes both feedforward and gain scheduling. We'll only deal with feedforward for now.

- How much does adding feedforward change the performance?

B. Uncoupled Non-Linear Models

- non-linear (quadratic) drag
- non-linear thruster model
- thrust saturation

May want to address these issues one-at-a-time.

Look into specific ways to design PID with saturation.

IV. MANEUVERING MODELS

A. Nonlinear Maneuvering Model based on Second-order Modulus Functions

This model contains second-order (linear and quadratic) terms for the dissipative terms. In this section we follow the notation and process detailed in [Fossen, 2011], Chapter 7. The horizontal-plane maneuvering model uses the state vector $\boldsymbol{\nu} = [u, v, r]^T$ where the velocities u , v and r are in the surge, sway and yaw directions respectively. The velocities are considered to be relative to an irrotational constant ocean current. The nonlinear maneuvering equations from [Fossen, 2011] are

$$\underbrace{\mathbf{M}_{RB}\dot{\boldsymbol{\nu}} + \mathbf{C}_{RB}(\boldsymbol{\nu})\boldsymbol{\nu}}_{\text{rigid-body forces}} + \underbrace{\mathbf{M}_A\dot{\boldsymbol{\nu}}_r + \mathbf{C}_A(\boldsymbol{\nu}_r)\boldsymbol{\nu}_r + \mathbf{D}(\boldsymbol{\nu}_r)\boldsymbol{\nu}_r}_{\text{hydrodynamic forces}} = \boldsymbol{\tau} + \boldsymbol{\tau}_{wind} + \boldsymbol{\tau}_{waves} \quad (1)$$

where $\boldsymbol{\nu}_r$ is the velocity vector relative to an irrotational water current $\boldsymbol{\nu}_c$, i.e., $\boldsymbol{\nu} = \boldsymbol{\nu}_r + \boldsymbol{\nu}_c$. The rigid body kinetics are represented by the rigid body mass \mathbf{M}_{RB}

$$\mathbf{M}_{RB} = \begin{bmatrix} m & 0 & 0 \\ 0 & m & mx_g \\ 0 & mx_g & I_z \end{bmatrix}, \quad (2)$$




Fig. 1. Relationship between thrust command a total measured thrust force.

where m is the mass of the vehicle, I_z is the moment of inertia about the body-centered z-axis and x_g is distance along the x-axis from the origin of the body-centered frame to the center of gravity of the vessel. The second rigid body term is the Coriolis-centripetal matrix,

$$\mathbf{C}_{RB}(\boldsymbol{\nu}) = \begin{bmatrix} 0 & 0 & -m(x_g r + v) \\ 0 & 0 & mu \\ m(x_g r + v) & -mu & 0 \end{bmatrix}. \quad (3)$$

Note that $\mathbf{C}_{RB}(\boldsymbol{\nu})$ is skew-symmetric, i.e., $\mathbf{C}_{RB}(\boldsymbol{\nu}) = -\mathbf{C}_{RB}^T(\boldsymbol{\nu})$. The hydrodynamic effects are represented by the added mass matrix

$$\mathbf{M}_A = \begin{bmatrix} -X_{\dot{u}} & 0 & 0 \\ 0 & -Y_{\dot{v}} & -Y_{\dot{r}} \\ 0 & -Y_{\dot{r}} & -N_{\dot{r}} \end{bmatrix}. \quad (4)$$




Fig. 2. Steady-state forward velocity vs. total thrust force.

and the Coriolis-centripetal matrix for the added mass

$$\mathbf{C}_A(\boldsymbol{\nu}_r) = \begin{bmatrix} 0 & 0 & Y_{\dot{v}}v_r + Y_{\dot{r}}r \\ 0 & 0 & -X_{\dot{u}}u_r \\ -Y_{\dot{v}}v_r - Y_{\dot{r}}r & X_{\dot{u}}u_r & 0 \end{bmatrix}. \quad (5)$$

It is worth noting that \mathbf{C}_A includes the nonlinear Munk moment (see [Fossen, 2011] p.121). Following [Fossen, 2011] the SNAME notation for the hydrodynamic derivatives.

The linear and quadratic drag terms

$$\mathbf{D}(\boldsymbol{\nu}_r) = \begin{bmatrix} X_u + X_{u|u}|u| & 0 & 0 \\ 0 & Y_v + Y_{v|v}|v| & Y_r + Y_{r|r}|r| \\ 0 & N_v + N_{v|v}|v| & N_r + N_{r|r}|r| \end{bmatrix}. \quad (6)$$

Equivalently we can express the same model in non-matrix form, where the speed equation in the surge direction is

$$\underbrace{m\dot{u}}_{\text{RB inertia}} - \underbrace{mx_g r^2}_{\text{RB centripetal}} - \underbrace{mvr}_{\text{RB Coriolis}} = \underbrace{X_{\dot{u}}\dot{u}_r}_{\text{AM inertia}} + \underbrace{Y_{\dot{v}}v_r r}_{\text{AM Coriolis}} + \underbrace{Y_{\dot{r}}r^2}_{\text{AM centripetal}} + \underbrace{X_u u + X_{u|u}|u|u}_{\text{Drag}} + \underbrace{\tau}_{\text{Thrust}} \quad (7)$$




Fig. 3. Steady-state yaw angular velocity vs. total torque.

and the coupled steering questions in the sway direction

$$\underbrace{m\dot{v} + mx_g\dot{r}}_{\text{RB inertia}} + \underbrace{mur}_{\text{RB Coriolis}} - \underbrace{Y_{\dot{v}}\dot{v} - Y_{\dot{r}}\dot{r}}_{\text{AM inertia}} = + \underbrace{Y_v v + Y_{v|v}|v|v}_{\text{Drag}} + \underbrace{Y_r r + Y_{r|r}|r|r}_{\text{Coupled Drag}} \quad (8)$$

and yaw directions

$$\underbrace{I_z\dot{r} + mx_g\dot{v}}_{\text{RB inertia}} + \underbrace{mx_g r u}_{\text{RB Coriolis}} - \underbrace{Y_{\dot{r}}\dot{v} - N_{\dot{r}}\dot{r}}_{\text{AM inertia}} - \underbrace{\overbrace{Y_{\dot{v}}v_r u + X_{\dot{u}}u_r v - Y_{\dot{r}}ru}_{\text{Monk Moment}}}_{\text{AM Coriolis}} - \underbrace{N_v v + N_{v|v}|v|v}_{\text{Coupled Drag}} + \underbrace{N_r r + N_{r|r}|r|r}_{\text{Drag}} = + \underbrace{\tau}_{\text{Torque}} \quad (9)$$

B. Nonlinear Model of Blanke

As reported by [Fossen, 1994], this model “retains the most important terms for steering and propulsion”. Formulating these equations for a rudder-less vessel, the speed equation becomes

$$(m - X_{\dot{u}})\dot{u} = X_{u|u}|u|u + (m + X_{vr})vr + (mx_g + X_{rr})r^2 + \tau \quad (10)$$

Comparing (7) and (10), noting that $Y_{\dot{v}}$ from (7) is equivalent to X_{vr} in (10), we can see that the only difference between these models is that the full model in (7) includes both linear and quadratic drag terms, while Blanke's model includes only a quadratic term. The linear term is important because it forces the system to converge to zero surge. Furthermore, results of other experiments suggest that the drag is not purely quadratic.

Blanke's steering model in sway, without rudder terms, is

$$(m - Y_{\dot{v}})\dot{v} + (mx_g - Y_{\dot{r}})\dot{r} = -(m - Y_{ur})ur + Y_{uv}uv + Y_{v|v|}|v|v + Y_{v|r}|v|r. \quad (11)$$

Comparing (8) and (11) we note the following differences

- The “Coupled Drag” term in (8) is neglected in the Blanke model. **What is the affect of neglecting these coupled drag terms? Appears fairly commonly in simplified models.**
- The linear component of cross-flow drag (8) is neglected in the Blanke model
- The following second-order cross-coupling terms are present in Blanke that are not represented in (8)
 - $Y_{ur}ur$ - which appears as an added mass Coriolis term
 - $Y_{uv}uv$
 - $Y_{v|r}|v|r$
 - **What is the consequence of neglecting these? Ditto for the yaw eqn.**

The steering equation for yaw is

$$(mx_g - N_{\dot{v}})\dot{v} + (I_z - N_{\dot{r}})\dot{r} = -(mx_g - N_{ur})ur + N_{uv}uv + N_{v|v|}|v|v + N_{v|r}|v|r \quad (12)$$

What/Why is the quadratic yaw drag expressed as $N_{v|v|}|v|v$? Seems like it would be $N_{r|r}|r|r$.

Comparing (9) and (12), we note that the Monk moment has been collapsed into a single term $N_{uv}uv$ in (12). We note the following differences

- The “Coupled Drag” term in (9) is neglected in the Blanke model
- The linear component of yaw drag (8) is neglected in the Blanke model
- The second-order cross-coupling term $N_{v|r}|v|r$ is present in Blanke model and not represented in (9).

C. Simplified Model of Blanke from [Caccia et al., 2008]

In [Caccia et al., 2008] the Blanke model is used, with the addition of linear drag terms, and the following assumptions are made:

- Speed: Surge

- Added mass in surge ($X_{\dot{u}}$) is negligible - less than 5% of vessel mass. This seem reasonable, but is not really necessary since the mass and added mass are lumped together in the identification.
- The Coriolis terms $(m + X_{vr})vr$, both rigid body and added mass contributions, are negligible because the sway speed is negligible. **This would seem to limit the sideslip.** The experiments in [Sonnenburg et al., 2010] suggest the sideslip would be an important component for this type of vehicle.
- The centripetal terms $(mx_g + X_{rr})r^2$ are neglected on the assumption of a low turn rate. This is probably reasonable?
- Steering: Sway and Yaw
 - Added mass in both directions is neglected. Again, probably not necessary since the identification estimates the combination of rigid body and added mass.
 - Although the author's don't make it explicit(!), they neglect the rigid body and added mass coupling terms **I believe this is equivalent to assuming that the principle axes of inertia for the vessel (the body-centered coordinate frame) are co-located with the center of mass of the vessel.**
 - * $(mx_g - Y_{\dot{r}})\dot{r}$ in the sway equation
 - * $(mx_g - N_{\dot{v}})\dot{v}$ in the yaw equation
 - Again, this is not explicit, but the authors omit the Coriolis terms, both rigid body and added mass, $-(mx_g - N_{ur})ur$. The reason for omission is not provided in the text.
 - The “coupled drag terms are neglected because v and r are typically small”. We can only assume they are referring to the following terms - **Are these correctly identified as “coupling drag terms”? Are they negligible?**
 - * $Y_{uv}uv$ and $Y_{|v|r}|v|r$ are negligible in sway
 - * $N_{uv}uv$ and $N_{|v|r}|v|r$ are negligible in yaw
 - The quadratic term $N_{|v|v}|v|v$ in the Blanke model is substituted with a linear and quadratic term as a function of yaw, $N_r r + N_{|r|r}|r|r$. **As indicated previously, I'm not clear why this term is related to the sway velocity in the first place.**

For our vessel this would be equivalent to the following speed and steering equations

$$m\dot{u} = X_u u X_{|u|u}|u|u + \tau \quad (13)$$

$$(m)\dot{v} = -(m - Y_{ur})ur + Y_v v + Y_{|v|v}|v|v. \quad (14)$$

$$I_z \dot{r} = N_r r + N_{|r|r}|r|r + \tau \quad (15)$$

This model is greatly simplified. **Us such a high degree of simplification justified?**

D. [Muske et al., 2008]

The model in [Muske et al., 2008] supposedly comes from [Fossen, 1994] (although I haven't found it yet). This model includes a power-law drag model in each direction, combined rigid body and added mass terms and (unlike the simplified Blanke model from [Caccia et al., 2008]) includes the Coriolis terms. The equations of motion are

$$m_{11}\dot{u} - m_{22}vr + d_1u^{\alpha_1} = \tau_{Thrust} \quad (16)$$

$$m_{22}\dot{v} + m_{11}ur + d_2v^{\alpha_2} = 0 \quad (17)$$

$$m_{33}\dot{r} + (m_{22} - m_{11})uv + d_3r^{\alpha_3} = \tau_{Torque} \quad (18)$$

$$(19)$$

Comparing this model to the nonlinear maneuvering model in (7) (8) (9) we see that

- Rigid body mass and added mass are combined in all terms
- They assume the body-axis and center of mass are collocated
- All centripetal terms are neglected
- Drag modeled as a power law, which may be more general (with the same number of parameters) as the linear+quadratic model.
- There are some additional assumptions here to make this work out - i.e., deriving this from the original nonlinear model.

E. Thrust Model

Two options:

Assume thrust is independent of speed (as done in the Caccia papers).

Or assume and unknown, linear decrease in thrust with speed.

$$T = T_o(1 - au)$$

where a is the linear speed reduction

F. Speed model

Consider the surge state of the model above where

$$\underbrace{m\dot{u}}_{\text{RB inertia}} - \underbrace{mx_g r^2}_{\text{RB centripetal}} - \underbrace{mvu}_{\text{RB Coriolis}} = \underbrace{X_u \dot{u}}_{\text{AM inertia}} + \underbrace{Y_v v r}_{\text{AM Coriolis}} + \underbrace{Y_r r^2}_{\text{AM centripetal}} + \underbrace{X_u u + X_{u|u}|u|u}_{\text{Drag}} + \underbrace{T}_{\text{Thrust}} \quad (20)$$

Following [Caccia et al., 2008], based on [Fossen, 1994], we neglect the second-order centripetal terms

$$m\dot{u} - mvu = X_{\dot{u}}\dot{u} + Y_{\dot{v}}v_r r + X_u u + X_{u|u}|u|u + T \quad (21)$$

For steady state forward motion ($\dot{u} = v = r = 0$) in stationary water ($v_r = 0$)

$$0 = +X_u u + X_{u|u}|u|u + T \quad (22)$$

We can estimate X_u and $X_{u|u}$ from steady state forward motion trials with known thrust input by testing at a series of known forward speeds and measuring u .

Considering forward-only acceleration

$$m\dot{u} = X_{\dot{u}}\dot{u} + X_u u + X_{u|u}|u|u + T \quad (23)$$

we can identify the added mass ($X_{\dot{u}}$) by either estimating the initial acceleration (see [Sonnenburg et al., 2010]) or by examining the 'time constant' for such tests.

This leaves the coefficient $Y_{\dot{v}}$, related to the added-mass Coriolis force, as the single unknown.

V. PROPOSED MODEL

A. Actuation Model

The thrust provided by each motor is a function of the command input (α) provided to the motor controller. The total thrust applied to the vessel is twice the motor thrust, so

$$\tau_{thrust} = 2(f(\alpha)). \quad (24)$$

Torque is applied to the vessel by a torque command (β) applied equal and opposite to the two thrusters separated by a distance of d , so

$$\tau_{torque} = d(f(\beta)). \quad (25)$$

We assume that any lag between the command inputs and the resulting thrust and torque is small compared to the dynamics of the vessel.

B. Maneuvering Model

We start with the maneuvering model from [Fossen, 2011] Chapter 7, in (1—9). We make the following assumptions

- The center of mass of the vehicle and the origin of the principle axes are co-located. Therefore x_g can be neglected.
- Centripetal terms can be neglected because of typically small yaw rates.

- The coupled terms in the added mass matrix ($Y_{\dot{r}}$) are sufficiently small to be neglected.
- The coupling in the drag matrix can be neglected.
- The values for the mass (m) and inertia (I_z) of the vessel can be measured directly
- For the purposes of model identification, the water current velocity is zero so that $\mathbf{nu} = \mathbf{nu}_r$.

Applying these assumptions, we can formulate the maneuvering model as follows. The mass matrix becomes the diagonal matrix

$$\mathbf{M} = \begin{bmatrix} m - X_{\dot{u}} & 0 & 0 \\ 0 & m - Y_{\dot{v}} & 0 \\ 0 & 0 & I_z - N_{\dot{r}} \end{bmatrix}. \quad (26)$$

The Coriolis matrix reduces to

$$\mathbf{C}(\boldsymbol{\nu}) = \begin{bmatrix} 0 & 0 & -(m - Y_{\dot{v}})v \\ 0 & 0 & (m - X_{\dot{u}})u \\ (m - Y_{\dot{v}})v & -(m - X_{\dot{u}})u & 0 \end{bmatrix}. \quad (27)$$

The linear and quadratic drag matrix becomes

$$\mathbf{D}(\boldsymbol{\nu}_r) = \begin{bmatrix} X_u + X_{u|u}|u| & 0 & 0 \\ 0 & Y_v + Y_{v|v}|v| & 0 \\ 0 & 0 & N_r + N_{r|r}|r| \end{bmatrix}. \quad (28)$$

VI. MODEL IDENTIFICATION TESTS

A. Physical Measurements

- Measure the mass (m) directly.
- Measure the moment of inertia (I_z) using a bifilar pendulum.

B. Thrust Characterization

Bollard tests in the tank to measure thrust force (at zero velocity) as a function of motor command. Use a load cell to measure the steady state force generated by the thrusters when attached to the tank. Measure the force at a number of thrust commands (e.g., 10 steps between 0-1.0 and -1.0-0). Fit a curve to the resulting command vs. thrust relationship to identify the function in (24).

C. Steady-State Tests

- Yaw: Measure the steady-state yaw rate at variety of torque inputs to identify the yaw drag terms. Direct estimate of N_r and $N_{r|r}$.
- Surge: Measure the steady-state speed at a variety of thrust inputs to identify the drag terms. Direct estimate of X_u and $X_{u|u}$.

D. Open-Loop Dynamic Tests

- Yaw: Measure step response to torque to estimate added mass/inertia in yaw. Direct estimate of $N_{\dot{r}}$.
- Surge: Measure step response to forward thrust (with heading control?) to estimate added surge mass. Direct estimate of $X_{\dot{u}}$.

E. Maneuvering Tests

We are left with the following parameters to identify

- $Y_{\dot{v}}$: Added-mass in sway
- Y_v and $Y_{v|v|}$: Linear and quadratic drag in sway

We can isolate the drag parameters by performing “turning circle” tests there the vehicle is moved in a circle with constant speed and yaw rate. Performing this test at different levels of thrust and torque should all for direct estimation of the linear and quadratic drag terms.

The last test is a set of step changes in speed and/or heading while executing the steady-state turning circle. This should allow an estimate of $Y_{\dot{v}}$.

REFERENCES

- [Blanke, 1981] Blanke, M. (1981). *Ship propulsion losses related to automated steering and prime mover control*. PhD thesis, The Technical University of Denmark,.
- [Caccia et al., 2008] Caccia, M., Bruzzone, G., and Bono, R. (2008). A practical approach to modeling and identification of small autonomous surface craft. *Oceanic Engineering, IEEE Journal of*, 33(2):133–145.
- [Caccia and Veruggio, 2000] Caccia, M. and Veruggio, G. (2000). Guidance and control of a reconfigurable unmanned underwater vehicle. *Control Engineering Practice*, 8(1):21 – 37.
- [Fossen, 1994] Fossen, T. I. (1994). *Guidance and Control of Ocean Vehicles*. Wiley.
- [Fossen, 2011] Fossen, T. I. (2011). *Handbook of Marine Craft Hydrodynamics and Motion Control*. Wiley.
- [Muske et al., 2008] Muske, K. R., Ashrafiuon, H., Haas, G., McCloskey, R., and Flynn, T. (2008). Identification of a control oriented nonlinear dynamic usv model. In *2008 American Control Conference*, pages 562–567.
- [Sonnenburg et al., 2010] Sonnenburg, C., Gadre, A., Kragelund, D. H. S., Marcus, A., Stilwell, D. J., and Woolsey, C. A. (2010). Control-oriented planar motion modeling of unmanned surface vehicles. Technical report, Virginia Center for Autonomous Systems.
- [Sonnenburg and Woolsey, 2013] Sonnenburg, C. R. and Woolsey, C. A. (2013). Modeling, identification, and control of an unmanned surface vehicle. *Journal of Field Robotics*, 30(3):371–398.