

ENGG1003 - Monday Week 6

Interpolation, Assignment 1 and Mid-term quiz

Steve Weller

University of Newcastle

29 March 2021

Last compiled: March 28, 2021 7:36pm +11:00

Lecture overview

- 1 Interpolation
- 2 Assignment 1
- 3 Mid-term quiz

The story so far

- variables and data types
- arrays (using `numpy`)
- plotting (using `matplotlib`)
- flow control
 - ▶ `if`
 - ▶ `while`
 - ▶ `for`
- functions

Most of ENGG1003 from here uses these elements of Python to solve Engineering problems

1) Interpolation

Two common forms of *curve-fitting* in Engineering applications:

1 *interpolation*

- ▶ today's lecture


2 *regression*

- ▶ considered in detail later in ENGG1003

- we now demonstrate both curve-fitting methods applied to the same dataset


Curve-fitting dataset

Week6Mon.py




- 11 pairs of data points $(t_i, y_i), i = 0, 1, 2, \dots, 10$
 $(0, 51.29), (10, 65.24), (20, 124.89), \dots, (100, 361.32)$

Interpolation



Regression



Interpolation vs. regression

- **interpolation:** joining the dots
 - ▶ obtain value of y at some intermediate point
- **regression:** fitting a straight line
 - ▶ when there's "too much data", simplify
 - ▶ here, simplifying to a straight line
 - ▶ we return to choosing "best" straight line later in ENGG1003
 - ▶ no more regression in this lecture
- both interpolation & regression involve creating a function (blue line) from data (red dots)


Functions

- in maths, you've seen functions written as follows:

$$y = f(t)$$


- function f , takes *argument* t and returns a *value* which is assigned to y
- ... and last week we saw Python uses the same terminology with functions

The interpolation problem



Given: data points $(t_0, y(t_0))$ & $(t_1, y(t_1))$ and t_*
Calculate: interpolated value $\hat{y}(t_*)$

Linear interpolation



- interpolated value $\hat{y}(t_*)$ lies on straight line connecting $(t_0, y(t_0))$ & $(t_1, y(t_1))$

Linear interpolation using `interp1d`

- `interp1d` function from `scipy.interpolate`
- `pip install scipy` at console first
- call to `interp1d` returns a function
- use the function in console
- live demo

Linear interpolation in Python


Week6MonLinear.py

```
1 import numpy as np
2 import matplotlib.pyplot as plt
3 from scipy.interpolate import interp1d
4
5 # seed random number generator to reproduce lecture results
6 np.random.seed(27101967)
7
8 N = 11
9 t = np.linspace(0,100,11)           # 0,10,20,...,100
10 tnew = np.linspace(0,100,100*N)    # 0,0.1,0.2,...,100
11 n = np.random.uniform(-25,25,N)    # noise on linear function
12
13 m = 3                               # gradient
14 b = 50                             # intercept
15 y = m*t + b + n                    # dataset is straight line + noise
```

Linear interpolation in Python (ctd.)

```
1 # INTERPOLATION
2 f = interp1d(t, y)
3
4 # PLOT RESULTS
5 plt.plot(t, y, 'ro')
6 plt.xlabel('t')
7 plt.ylabel('y(t)')
8 plt.plot(tnew, f(tnew), 'b')
9 plt.title('Linear interpolation')
10 plt.show()
```

Linear interpolation



- “stitches together” straight line segments

Beyond linear interpolation

Problem: slopes of adjacent straight lines change abruptly at data points

Cubic splines

- degree 1 is linear, degree 2 is parabola, degree 3 is cubic
- we're hiding lots of maths here, but we can use Python to implement without needing that maths
- maths is interesting!

Cubic spline in Python code

```
1 # INTERPOLATION
2 f3 = interp1d(t, y, 'cubic')
3
4 # PLOT RESULTS
5 plt.plot(t, y, 'ro')
6 plt.xlabel('t')
7 plt.ylabel('y(t)')
8 plt.plot(tnew, f3(tnew), 'b')
9 plt.title('Cubic spline interpolation')
10 plt.show()
```

Linear interpolation:


```
1 f = interp1d(t, y)
```

Cubic spline interpolation:

```
1 f3 = interp1d(t, y, 'cubic')
```

- Live demo of `Week6MonCubic.py`

Cubic spline interpolation



- “stitches together” *cubic* polynomials

2) Assignment 1

- released today, Monday 29 March 2021
- upload Python file to BB no later than 9:00 am, Monday 19 April
- counts for 20% of course grade
- each student will be assessed by demonstrator in week 7 face-face computer lab (after recess)

2) Assignment 1

- basic idea in assignment: analysis of GPS data
- in more detail:
 - ▶ GPS data collected during a mountain bike ride
 - ▶ GPS track log is presented in a `csv` file containing timestamps, latitude, longitude, and elevation columns recorded at 1 second intervals
 - ▶ project asks you to analyse GPS data, eg: fitness trackers
 - ▶ use interpolation where GPS signal was lost
- computer labs this week:
 - ▶ there is no week 6 lab sheet
 - ▶ get started on assignment in place of lab sheet

3) Mid-term quiz

- Thursday 1 April, 4–5pm
 - ▶ during scheduled lecture time
 - ▶ mid-term quiz instead of lecture this week so...
 - ▶ **NO Zoom or YouTube livestream on 1 April**
- 50-minute quiz
- open-book
- quiz will appear on BB at 4:05 pm
... and will disappear at 4:55 pm
- counts for 15% of course grade

What to expect, and how to prepare

- the quiz will ask you to write Python code to:
 - ▶ load a `CSV` file
 - ▶ perform some calculations on a specified column of the file ie: array processing
(each student gets assigned a unique column in the file)
- once your program is complete, you do two things:
 - 1 enter the results of your program into BB
 - 2 upload your Python code to BB
- **there is a practice quiz NOW on BB**
 - ▶ you can practice as many times as you like!
- live demo of how the mid-term quiz will run

Lecture summary

- Interpolation
 - ▶ linear interpolation
 - straight line “join the dots”
 - ▶ cubic spline interpolation
 - smoothly connects data points
- Assignment 1
 - ▶ released today
 - ▶ submissions due on BB by 9:00 am, Monday 19 April
 - ▶ worth 20%
- Mid-term quiz
 - ▶ **there is a practice quiz NOW on BB**
 - ▶ done on BB at 4:00 pm, Thursday 1 April
 - ▶ worth 15%