

ENGG1003 - Tuesday Week 7

File I/O
More Pointers
2D Arrays

Brenton Schulz

University of Newcastle

April 9, 2019

Che C Documentation

- ▶ Linux systems have a program called “man”
 - ▶ Short for “manual”
- ▶ It is used to display a wide variety of documentation called “man pages”
- ▶ To install it type this in the terminal:

```
sudo apt update  
sudo apt install man
```

and press `y` (or `<enter>`) when prompted to confirm installation

- ▶ Afterwards, C documentation can be accessed by typing `man <topic>`

Che C Documentation

- ▶ For example, all library functions have a man page you can read by typing:
`man <function name>`
- ▶ eg, try:
 - ▶ `man fopen`
 - ▶ `man printf`
 - ▶ `man sin`
 - ▶ `man string`
 - ▶ etc..

Correction: String Initialisation

- ▶ This is totally fine:

```
1 char string[] = "initial value";
```

- ▶ The compiler copies the string literal into `string[]`
- ▶ The length is automatically calculated
 - ▶ You may specify a length *longer* than necessary:

```
1 char string[1024] = "initial value";
```

Correction: String Initialisation

- ▶ This is totally fine:

```
1 char string[] = "initial value";
```

- ▶ The compiler copies the string literal into `string[]`
- ▶ The length is automatically calculated
 - ▶ You may specify a length *longer* than necessary:

```
1 char string[1024] = "initial value";
```

- ▶ A constant string is created with:

```
1 char *str = "some string";
```

- ▶ We will study this *pointer* syntax later

File I/O

- ▶ A stream is kept in a variable of type `FILE` *
- ▶ Read as “pointer to `FILE`” or “`FILE`-star”
- ▶ Three already exist in your C programs:
 - ▶ `stdin`
 - ▶ `stdout`
 - ▶ `stderr`
- ▶ Additional streams are declared like other variables, eg:

```
1 FILE *input, *output;
```

File I/O - Quick Review

- ▶ Before a file can be accessed you must *open* it with the `fopen()` function
- ▶ In order to open files you need two pieces of information:
 - ▶ The file's name
 - ▶ The data direction (mode)
 - ▶ Reading
 - ▶ Writing
 - ▶ Both

File I/O

- ▶ `fopen()`'s function prototype is:

```
1 FILE *fopen(const char *name, const char *mode);
```

- ▶ `const char *name` is a string holding the file's name
- ▶ `const char *mode` is a string describing the desired data direction
- ▶ Both of these can be passed as variable strings or hard-coded

File I/O

- ▶ The `*mode` argument can be one of the following:
 - ▶ `"r"` (reading)
 - ▶ `"r+"` (reading and writing)
 - ▶ `"w"` (writing)
 - ▶ `"w+"` (reading and writing, file truncated)
 - ▶ `"a"` (appending)
 - ▶ `"a+"` (reading and appending)
- ▶ Read [documentation](#) for details
- ▶ `fopen()` example:

```
1 FILE *input;  
2 input = fopen("data.txt", "r");
```

fopen() Errors

- ▶ The return value of `fopen()` is `NULL` on error
- ▶ Check it! Attempting to access a `NULL` stream will result in a segmentation fault!

```
1 FILE *input;  
2 input = fopen("data", "r");  
3 if(input == NULL) {  
4     perror("fopen()");  
5     return;  
6 }
```

- ▶ `perror()` prints a user-friendly error message

File I/O

- ▶ Once opened, a file can be accessed with:
 - ▶ `fscanf()`
 - ▶ `fprintf()`
- ▶ These functions behave just like `scanf()` and `printf()` except they take an extra argument:

```
1 int fscanf(FILE *stream, const char *format,  
    ...);
```

- ▶ The first argument is a `FILE *`
- ▶ The rest is identical to `printf()` and `scanf()`

File I/O - Position Indicators

- ▶ Concept: bytes in files have an address known as a *position indicator*
- ▶ The address is the number of bytes, starting at zero, from the start of the file
- ▶ Unless otherwise controlled, files are only read from and written to *sequentially*
- ▶ The position indicator automatically increments when a byte is read or written

File I/O - Position Indicators

- ▶ Some useful functions:
 - ▶ `ftell()` - Returns the position indicator
 - ▶ `fseek()` - Sets the position indicator
 - ▶ `feof()` - Returns TRUE if the position indicator is at the end of the file
- ▶ For example, to process data until the end of file is reached:

```
1 FILE *stream;  
2 // open file etc  
3 while(!feof(stream)) {  
4     // Read from file  
5     // Do stuff  
6 }
```

File I/O Example

Write a C program which opens a file, `test.txt`, and prints its contents to `stdout`, reading and writing one character at a time.

File I/O Example

Write a C program which opens a file, `test.txt`, and prints its contents to `stdout`, reading and writing one character at a time.

► Declare `FILE *input;`

File I/O Example

Write a C program which opens a file, `test.txt`, and prints its contents to `stdout`, reading and writing one character at a time.

- ▶ Declare `FILE *input;`
- ▶ Use `fopen()` to open it for reading

File I/O Example

Write a C program which opens a file, `test.txt`, and prints its contents to `stdout`, reading and writing one character at a time.

- ▶ Declare `FILE *input;`
- ▶ Use `fopen()` to open it for reading
- ▶ Write a loop which reads and writes characters until the whole file has been read
 - ▶ Read with: `fscanf(input, "%c", &c);`
 - ▶ Write with: `printf("%c", c);`

File I/O Example 1

Write a C program which opens a file, `input.txt`, then reads and prints each character to the console on a new line, indicating the position indicator's value *after* reading each character.

File I/O Example 2

Write a C program which copies a file, `input.txt`, into a new file, `output.txt`. While copying, the program should count how many spaces there are in the input and print the final count to the terminal before exiting.

File I/O Example 3

Write a C program which opens a file, `input.txt`, and counts the number of times the string "the" appears.

The program should include a function, `isThe()`, which tests if a string is equal to "the" or not.

Pointers

- ▶ A *pointer* is the memory address of a variable
 - ▶ This includes “first element of an array” pointers
- ▶ Pointers can be stored in variables of type “pointer to data type”
 - ▶ Declaration syntax:
`data_type *variable_name;`
 - ▶ eg: `int *p;`
- ▶ Pointers also implicitly exist when using arrays
- ▶ All pointers are the same size
 - ▶ The memory address of a `char` is the same size as the memory address of a `double`

Pointers - Why?

- ▶ In ENGG1003:
 - ▶ Passing a pointer to a function lets the function modify the variable
 - ▶ This lets functions “return” more than one value (ie: modify multiple variables given as pointer arguments)
 - ▶ String functions mostly accept `char *`s
 - ▶ Help you understand computer memory organisation
 - ▶ Pointers are the only way to send “large” amounts of data to a function

Pointers - Why?

- ▶ Beyond ENGG1003:
 - ▶ Pointer “casting” can be used to interpret one variable as a different type in a specific way
 - ▶ eg: break a 32 bit `int` into two 16 bit chunks for transmission on an SPI bus
 - ▶ Interpreting “file header” data chunks as complex data structures
 - ▶ Pointers are required for dynamic memory allocation
 - ▶ For getting large amounts of RAM after a program has begun executing
 - ▶ Pointers are required to build advanced memory structures such as trees and linked lists

Pointer Terminology

- ▶ A pointer is *declared* with the syntax:

```
1 datatype *pointerName;
```

- ▶ A pointer is *assigned* with the syntax:

```
1 pointerName = &variable;
```

- ▶ A pointer is *dereferenced* with the syntax:

```
1 *pointerName = 12;
```

- ▶ This allocates 12 to the variable `pointerName` is pointing to

Pointer Declaration

- ▶ Declaring a pointer variable allows you to store and manipulate pointers
- ▶ Declaration examples:

```
1 int *p; // Pointer to an integer
2 char c, *a; // char c and pointer-to-char a
3 char * str = "string" // Pointer to string
```

- ▶ Explicit declaration like this is mostly beyond ENGG1003
 - ▶ We will mostly just use them as function arguments

Pointer Assignment

- ▶ A pointer is “created” by using the & operator before a variable name:

```
1 int k, *x;  
2 k = &x; // k holds the address of x
```

- ▶ Array names are implicitly pointers

```
1 char string[] = "Hello";  
2 char *p = string; // Pointer to string[0]
```

Pointers and Strings

- ▶ When using double quotes "..." pointers are created by the compiler
 - ▶ The pointer is of type `const char *`
 - ▶ The string data gets stored in the program
 - ▶ ie: in the same area of memory as the binary machine code
 - ▶ The compiler creates a pointer to that memory address
- ▶ Example: `printf()` has a prototype:

```
1 int printf(const char *format, ...);
```

- ▶ `const` implies that `printf()` won't modify a string passed to it

Pointers and Strings

- ▶ Example 2: `fopen()`'s prototype is:

```
1 FILE *fopen(const char *pathname, const char *mode);
```

- ▶ The string arguments are both `char *`
- ▶ We can use constant strings:

```
1 fopen("input.txt", "r");
```

- ▶ Or we can use string arrays:

```
1 FILE *input;  
2 char fn[256];  
3 scanf("%s", fn); // Read filename from user  
4 input = fopen(fn, "r");
```

Pointer Dereferencing

- ▶ This is the conceptually tricky one:
 - ▶ If `p` is a pointer to `x`, then `*p` makes it “appear” as `x`

```
1 int *p, x;  
2 p = &x;  
3 *p = 12; // Makes x 12
```

- ▶ Be careful: the function of the `*` character is context dependent!
 - ▶ It could multiply
 - ▶ It could declare a pointer type
 - ▶ it could dereference a pointer

Pointer Example

(Toy example) What will this code print?

```
1 #include <stdio.h>
2
3 int main() {
4     int x = 5; *p;
5     p = &x;
6     x++;
7     printf("%d\n", *p);
8     *p++;
9     printf("%d\n", x);
10    return 0;
11 }
```

Pointer Types

- ▶ Pointers to different types are all “the same”, right?
 - ▶ They are all memory addresses
 - ▶ Memory addresses are all the same size

Pointer Types

- ▶ Pointers to different types are all “the same”, right?
 - ▶ They are all memory addresses
 - ▶ Memory addresses are all the same size
- ▶ So why do pointers have different types?

Pointer Types

- ▶ Pointers to different types are all “the same”, right?
 - ▶ They are all memory addresses
 - ▶ Memory addresses are all the same size
- ▶ So why do pointers have different types?
- ▶ When *dereferencing* the type is crucial!
- ▶ The type controls how much data will be read beyond the pointer
 - ▶ eg: an `int` is typically 4 bytes
 - ▶ An `int *` points to the *first* of the 4 bytes
 - ▶ Dereferencing an `int *` reads all 4 bytes

Pointers and Functions

- ▶ A pointer function argument uses the same syntax as an array argument:

```
1 void f(int *x); // Pointer to int argument
```

- ▶ Aside: This is often just read as “int star”
- ▶ Inside the function the thing x points to can be modified or accessed with $*x$:

```
1 void f(int *x) {  
2     y = 2 + *x;  
3     *x = 2 * (*x); // This syntax is painful  
4 }                 // ()'s for clarity
```

Pointers and Functions

- ▶ Wait, is used *exactly the same* syntax as an array argument?

Pointers and Functions

- ▶ Wait, is used *exactly the same* syntax as an array argument?
 - ▶ Yes! Array arguments are a pointer to the first element
 - ▶ This is the same amount (and type of) data as a pointer to a single variable
 - ▶ It is up to you, the programmer, to interpret pointer arguments correctly!

Toy Example

Write a C function which takes two unsigned integers as arguments and zeros the one holding the larger value.

Function prototype:

```
1 void zeroLarger(unsigned int *a, unsigned int *b);
```

Better Example

Write a C function which takes two integer arguments and swaps them.

Function prototype:

```
1 void swap(int *a, int *b);
```

Advanced Pointer Example

- ▶ When using command line arguments, `main()` is written as:

```
1 int main(int argc, char *argv[])
```

- ▶ What on Earth is `char *argv[]`?!?!?

Advanced Pointer Example

- ▶ When using command line arguments, `main()` is written as:

```
1 int main(int argc, char *argv[])
```

- ▶ What on Earth is `char *argv[]`?!?!?
- ▶ `char *` means it points to chars

Advanced Pointer Example

- ▶ When using command line arguments, `main()` is written as:

```
1 int main(int argc, char *argv[])
```

- ▶ What on Earth is `char *argv[]`?!?!?
- ▶ `char *` means it points to chars
- ▶ `argv[]` means it is an array

Advanced Pointer Example

- ▶ When using command line arguments, `main()` is written as:

```
1 int main(int argc, char *argv[])
```

- ▶ What on Earth is `char *argv[]`?!?!?
- ▶ `char *` means it points to chars
- ▶ `argv[]` means it is an array
- ▶ All together: `char *argv[]` is an array of pointers to chars
- ▶ Interpretation: it holds an array of strings!

Advanced Pointer Example

- ▶ Syntactically:

- ▶ `argv[0]` is a pointer to a string
- ▶ `argv[1]` is a pointer to a different string
- ▶ ...etc

- ▶ So, you can do things like:

```
1 printf("First argument: %s\n", argv[0]);
```

- ▶ Or use `atoi()` to convert a numerical string to an `int`:

```
1 int x;  
2 x = atoi(argv[1]);
```

Command Line Arguments Example

Write a C program which opens a file and prints the first 10 words from the file to `stdout`. The filename should be given as a single command line argument.

Multidimensional Arrays

- ▶ So far, all arrays have been 1D
- ▶ What if you want to store a matrix or image?

Multidimensional Arrays

- ▶ So far, all arrays have been 1D
- ▶ What if you want to store a matrix or image?
- ▶ In C, arrays can have multiple *dimensions*
- ▶ 2D example:

```
1 int x[3][3]; // a 3x3 matrix
```

- ▶ 3D example:

```
1 int y[10][3][3]; // 90 ints in 3 dimensions
```

- ▶ There is no *theoretical* dimension limit but compilers will have limits

Multidimensional Arrays

- ▶ Each unique combination of dimension indices indexes a unique element:

```
1 int x[2][2]; // four integers total
2 x[0][0] = 1;
3 x[0][1] = 2;
4 x[1][0] = 3;
5 x[1][1] = 4;
```

- ▶ This is one way of holding greyscale image data
- ▶ We will use this in the second programming assignment

Multidimensional Arrays

- ▶ Images typically use the RGB colour space
- ▶ Each pixel gets a red, green, and blue intensity
- ▶ An RGB image can therefore be stored as a 3D array:

```
1 unsigned char image[xres][yres][3]
```

- ▶ Here, a image of size `xres` by `yres` can have 3 `unsigned char` values for each pixel
- ▶ The red, green, and blue channels each have 255 intensity levels
 - ▶ Each `unsigned char` is 8 bits
 - ▶ $3 \times 8 = 24\text{b}$ per pixel

2D Array Example

Write a C program which reads a 5x5 array from a file and finds the maximum value in the array. The file stores `float` data in csv format. Each line contains 10 `floats`, separated by commas. There are 10 lines in the file. There are no commas at the end of lines.

You may assume that the file does not contain errors.