

OpenSUSE Kubic

Installation

Jason Evans jsevans@opensuse.org

Publication Date: 2019-04-10

Contents

- 1 Section 1: Setup the Clone Master 2
- 2 Section 2: Clone the VMs 5
- 3 Section 3: Configure the Master and Worker VMs 6
- 4 Section 4: Bootstrap the Cluster 8
- 5 License 11

1 Section 1: Setup the Clone Master



Note

This tutorial was written using Virtualbox 6.0. It contains step by step instructions for the installation process. However it is assumed that the user knows how to install and use Virtualbox on the operating system of their choice.

Description:

In this section you will set up a Kubic Clone Master which will make it easier to create new nodes.

1.1 Task 1: Download the installation media

 Go to the following url and download the current version of the Kubic url: http://download.opensuse.org/tumbleweed/iso/openSUSE-Tumbleweed-Kubic-DVD-x86_64-Current.iso.mirrorlist

1.2 Task 2: Set up NAT Network

- 1. Open VirtualBox and Click on File and then Preferences:
- 2. Click on the Network Icon
- 3. Click on the first icon on the right that Adds new NAT network
- 4. Click on the third icon on the right that Edits selected NAT network The Network CIDR should be: 10.0.2.0/24 Leave the rest of the settings as their default values Click OK to close this screen
- 5. Click OK to close the preferences screen

1.3 Task 3: Set up a new VM

- 1. Open VirtualBox and Click on the New icon:
- 2. In the Name field, enter a name: Kubic-CloneMaster
- 3. In the Version field, choose **OpenSUSE 64-bit** Click Next
- 4. Allow for 2048MB RAM Click Next
- 5. Choose **Create a virtual hard disk now** Click Next
- 6. Choose VDI (Virtual Disk Image) Click Next
- 7. Choose **Dynamically allocated** Click Next
- 8. Allow for 30GB Click Create
- 9. Click on the Settings icon on the right
- 10. Go to the Network icon
- 11. Change Attached to

NAT Network Name: NatNetwork

- 1. Go to the System icon and click on the Processor tab
- 2. Change the number of processors to 2
- 3. Click OK

1.4 Task 4: Start Installation

- 1. On the main Virtualbox screen, choose **Kubic-CloneMaster** and click on the Start icon You will be prompted to Select a start-up disk
- 2. Click on the folder icon: Choose the current iso file that you downloaded in Task 1
- 3. Click start
- 4. When the virtual machine boots, choose the installation option.
- 5. On the license screen, click next if you agree
- 6. Choose kubeadm Node Click Next

7. Enter an NTP server local to you or use the default one that is provided Click Next



Go to http://ntp.org **孝** for more information.

- 8. Enter a root password and then confirm it Click Next
- 9. Click Install

1.5 Task 5: Post-Installation setup

- 1. After the installation has finished, the VM will reboot. Choose Boot from Hard Disk
- 2. Choose the first option: openSUSE Tumbleweed Kubic
- 3. Log into the command line:

Userid: root Password: [your root password]

- 1. Eject the installation media: eject /dev/sr0
- 2. Install Yast for easier network configuration: transactional-update pkg install
 yast2-network
- 3. Reboot your vm: reboot
- 4. Repeat steps 1-3 in this task:
- 5. Start the curses version of yast to configure networking yast2 lan
- 6. Use the **F4 key** on your keyboard to edit:



You can use the tab key to navigate the screen

- 7. Click alt t on your keyboard to change to Statically Assigned IP Address
- 8. In the IP Address field, enter: 10.0.2.10 Use the tab key to go to the next field
- 9. In the Subnet Mask field, enter: /24

- 10. Use the **F10 key** on your keyboard to go to the next screen
- 11. Click alt s on your keyboard to change the Hostname/DNS
- 12. In the hostname field, enter: **clone-master** Use the **tab key** to go to the **Name Server** 1 field
- 13. Enter the generic Google DNS or substitute another if you prefer: 8.8.8.8
- 14. Click alt u on your keyboard to change the Routing
- 15. In the **Default IPv4 Gateway** field, enter: **10.0.2.2**
- 16. Select click alt i on your keyboard to select Enable IPv4 Forwarding
- 17. Use the **F10 key** to finish.
- 18. Ping the gateway. If you get a positive response, then you have set up the network correctly: ping 10.0.2.2
- 19. Ping an internet website. If you get a positive response, then you have set up the DNS correctly: ping opensuse.org
- 20. If either step 19 or 20 gives an error, review the steps in this task.
- 21. Shut down the VM: halt -p

Description: In this section you set up a new Kubic VM which will be used as a template for creating further VMs.

2 Section 2: Clone the VMs

Description:

In this section you will create VMs for your Kubic cluster.

2.1 Task 1: Create the Kubic Master Node

- 1. Right-click on the Kubic-CloneMaster VM and choose Clone
- 2. In the Name field, enter: Kubic-Master

- 3. In the Mac Address Policy field, choose: Generate new MAC addresses for all network adapters
- 4. On the Clone type screen, choose Linked Clone Click Clone

2.2 Task 2: Create a Kubic Worker Node

- 1. Right-click on the **Kubic-CloneMaster** VM and choose **Clone**
- 2. In the Name field, enter: Kubic-Worker1
- 3. In the Mac Address Policy field, choose: Generate new MAC addresses for all network adapters
- 4. On the **Clone type** screen, choose **Linked Clone** Click **Clone**
- 5. Repeat this task once more and create **Kubic_Worker2**. You may repeat as many times as you like as long as you have memory and disk space for each node.



Note

The **Kubic-CloneMaster** VM can be deleted at this point if you don't think you will need more nodes or it can be left as a template. If it is deleted, it can always be recreated using the steps in the previous section.

Summary:

In this section you created additional VMs that will be used as Master and Worker nodes in an openUSE Kubic Kubernetes cluster.

3 Section 3: Configure the Master and Worker VMs

Description:

In this section, you will change the IP addresses on the Master and Worker VMs to be unique.

3.1 Task 1: Configure the Kubic-Master VM

- 1. From the main Virtualbox screen, choose the **Kubic-Master** VM and click on the down arrow next to the start icon. Click on Detachable Start
- 2. Log into the command line:

Userid: root

Password: [your root password]

- Start the curses version of yast to configure networking yast2 lan
- 4. Use the **F4** key on your keyboard to edit
- 5. Use the **tab** key to navigate around the screen
- 6. Change the IP address to 10.0.2.11
- 7. Change the Hostname to kubic-master
- 8. Use the F10 key to go the next screen
- 9. User the alt s keys to go to the Hostname/DNS screen
- 10. Change the Hostname to kubic-master
- 11. Use the F10 key to finish:

3.2 Task 2: Configure the Kubic-Worker1 VM

- 1. From the main Virtualbox screen, choose the **Kubic-Worker1** VM and click on the down arrow next to the start icon. Click on Detachable Start
- 2. Log into the command line:

Userid: root

Password: [your root password]

- 3. Start the curses version of yast to configure networking yast2 lan
- 4. Use the F4 key on your keyboard to edit
- 5. Use the **tab** key to navigate around the screen

- 6. Change the IP address to 10.0.2.12
- 7. Change the Hostname to **kubic-worker1**
- 8. Use the **F10** key to go the next screen
- 9. User the alt s keys to go to the Hostname/DNS screen
- 10. Change the Hostname to kubic-worker1
- 11. Use the **F10** key to finish

Repeat Task 2 for each worker node. Add 1 to the IP address and hostname for each node that you configure using the pattern in this section.

All nodes should be able to ping 10.0.2.2, each other, and an internet website.

Summary:

In this section you changed the IP addresses on each node to be unique so they are ready to create a Kubernetes cluster

Section 4: Bootstrap the Cluster

Description:

In this section you will bootstrap your Kubic Kubernetes cluster

Task 1: Set up Kubic-Master 4.1

1. Login into the **Kubic-Master** VM if you have not already done so:

Userid: root

Password: [your root password]

2. Run the following command to configure this as a Kubernetes master node:

init --cri-socket=/var/run/crio/crio.sock **kubeadm** --pod-networkcidr=10.244.0.0/16

You should see some output and at the end, you will see this:

You can now join any number of machines by running the following on each node as root:

kubeadm join 10.0.2.11:6443 --token ...



Save this command. You will need it later!

4.2 Task 2: (optional) Add a second network interface to Kubic-Master VM

1. Power off the Kubic-Master VM

halt -p

- 2. From the main Virtualbox screen, choose the Kubic-Master VM and click on Settings
- 3. Click on the Network icon
- 4. Click on the Adaptor 2 tab

Change Attached to to Bridged Adaptor

Name should automatically change to whatever physical network adaptor you are using.

- 5. From the main Virtualbox screen, choose the **Kubic-Master** VM and click on the down arrow next to the start icon. Click on Detachable Start
- 6. Log into the command line:

Userid: root

Password: [your root password]

7. Start the curses version of yast to configure networking on the new nic

yast2 lan

- 8. Use the F4 key on your keyboard to edit the new nic
- 9. Click on **alt y** on your keyboard to change this nic to DHCP. If your network does not have DHCP, set a static IP instead.
- 10. Click on F10 on your keyboard to exit this screen
- 11. Click on F10 on your keyboard to exit yast
- 12. Find your new IP addresses

ip a

You should now be able to log into the Kubic-Master using the terminal or application of your choice. You can also now copy and paste from this book.

4.3 Task 3: Set up the Kubic-Workers

1. Login to the Kubic-Worker1 VM if you have not already done so:

Userid: root

scriu. 100t

Password: [your root password]

2. Run the output command from Task 1 and add

--cri-socket=/var/run/crio/crio.sock

to the end of the command

3. Repeat this task for every worker VM

4.4 Task 4: Set up the kubectl

1. On the **Kubic-Master** VM, copy and set up the config file so that kubectl can interact with the cluster:

mkdir -p \$HOME/.kube

sudo cp -i /etc/kubernetes/admin.conf \$HOME/.kube/config

sudo chown \$(id -u):\$(id -g) \$HOME/.kube/config

2. Check on your nodes

kubectl get nodes

You should have 3 nodes. All of them should be in a NotReady status

4.5 Task 5: Set up Flannel

1. Run the following command to install flannel on your cluster:

kubectl apply -f https://0y.at/kubicflannel

2. Check on your nodes

watch kubectl get nodes

In 1-2 minutes all of them should be in a Ready status. Click on $\mathbf{Ctrl}\ \mathbf{c}$ on your keyboard to exit this screen.

You now have a fully functional Kubernetes cluster! You can add more worker nodes at any time and then bootstrap them in like you did above.

Summary:

In this section you completed your Kubic Kubernetes cluster. It is now fully functional and ready to be used.

5 License

This work is licensed under a Creative Commons Attribution-ShareAlike 4.0 International License. (https://creativecommons.org/licenses/by-sa/4.0/)

✓

You are free to:

Share — copy and redistribute the material in any medium or format

Adapt — remix, transform, and build upon the material for any purpose, even commercially.

This license is acceptable for Free Cultural Works.

The licensor cannot revoke these freedoms as long as you follow the license terms. Under the following terms:

Attribution — You must give appropriate credit, provide a link to the license, and indicate if changes were made. You may do so in any reasonable manner, but not in any way that suggests the licensor endorses you or your use.

ShareAlike — If you remix, transform, or build upon the material, you must distribute your contributions under the same license as the original.

No additional restrictions — You may not apply legal terms or technological measures that legally restrict others from doing anything the license permits.

Notices:

You do not have to comply with the license for elements of the material in the public domain or where your use is permitted by an applicable exception or limitation. No warranties are given. The license may not give you all of the permissions necessary for your intended use. For example, other rights such as publicity, privacy, or moral rights may limit how you use the material.