

## // Procedural Terrain.shader

```
_IntensityMultiplier("Intensity Multiplier", Range(0.0001, 0.02)) = 0.015
```

```
_RedChannel ("Red Channel", Range(0, 1)) = 0  
_GreenChannel("Green Channel", Range(0, 1)) = 1  
_BlueChannel ("Blue Channel", Range(0, 1)) = 0
```

```
}
```

```
...
```

```
float _IntensityMultiplier;
```

```
float _RedChannel;  
float _GreenChannel;  
float _BlueChannel;
```

```
...
```

By now...  
these lines...  
and these lines...  
should be familiar

## // Procedural Terrain.shader

```
_IntensityMultiplier("Intensity Multiplier", Range(0.0001, 0.02)) = 0.015
```

```
_RedChannel ("Red Channel", Range(0, 1)) = 0  
_GreenChannel("Green Channel", Range(0, 1)) = 1  
_BlueChannel ("Blue Channel", Range(0, 1)) = 0
```

```
}
```

```
...
```

```
float _IntensityMultiplier;
```

```
float _RedChannel;
```

```
float _GreenChannel;
```

```
float _BlueChannel;
```

```
...
```

```
float r = 0;
```

```
float g = 1;
```

```
float b = 0;
```

```
float r = _RedChannel;
```

```
float g = _GreenChannel;
```

```
float b = _BlueChannel;
```

```
...
```

By now...

these lines...

and these lines...

should be familiar

All we do here is assign the **r**, **g**, and **b** variables to our exposed properties instead of hard-coded values