

// MinTuts/Procedural Terrain.shader

```
Shader "MinTuts/Procedural Terrain" {
    SubShader {
        Pass {
            CGPROGRAM

            #pragma vertex    vert
            #pragma fragment frag

            #include "UnityCG.cginc"

            struct v2f {
                float4 pos      : SV_POSITION;
                float3 wpos     : POSITION1;
            };

            v2f vert(float4 vertex : POSITION) {
                v2f o;

                o.pos = UnityObjectToClipPos(vertex);
                o.wpos = mul(unity_ObjectToWorld, vertex);

                return o;
            }

            float4 frag(v2f i) : COLOR {
                float  p = i.wpos.y * 0.015;
                float3 y = float3(p, p, p);

                return float4(y, 1);
            }

        }
    }
}
```

We use this **float3** as the first 3 arguments...
to the **float4** constructor

The 4th argument we hard code to 1; the
4th channel is the opacity/transparency channel
Since this is a single-pass shader transparency
is not supported

Hard coding the opacity/transparency channel to
1 makes it clear that we do not want this shader
to support transparency

Now that our **float4** (with a **semantic** of **COLOR**
and channels for red, green, blue, and alpha) is
constructed, we return it

NOTE: **vert** can manipulate the local/clip/world
space coordinates of vertices (it can even add
or remove vertices) but **frag**'s only purpose is to
take in data from **vert**...

and return...

a **float4**...

with the **COLOR** semantic

// MinTuts/Procedural Terrain.shader

```
Shader "MinTuts/Procedural Terrain" {
    SubShader {
        Pass {
            CGPROGRAM

            #pragma vertex    vert
            #pragma fragment frag

            #include "UnityCG.cginc"

            struct v2f {
                float4 pos      : SV_POSITION;
                float3 wpos     : POSITION1;
            };

            v2f vert(float4 vertex : POSITION) {
                v2f o;

                o.pos = UnityObjectToClipPos(vertex);
                o.wpos = mul(unity_ObjectToWorld, vertex);

                return o;
            }

            float4 frag(v2f i) : COLOR {
                float  p = i.wpos.y * 0.015;
                float3 y = float3(p, p, p);

                return float4(y, 1);
            }
        }
    }
}
```

We use this **float3** as the first 3 arguments...
to the **float4** constructor

The 4th argument we hard code to 1; the
4th channel is the opacity/transparency channel
Since this is a single-pass shader transparency
is not supported

Hard coding the opacity/transparency channel to
1 makes it clear that we do not want this shader
to support transparency

Now that our **float4** (with a **semantic** of **COLOR**
and channels for red, green, blue, and alpha) is
constructed, we return it

NOTE: **vert** can manipulate the local/clip/world
space coordinates of vertices (*it can even add*
or remove vertices) but **frag**'s only purpose is to
take in data from **vert**...

and return...

a **float4**...

with the **COLOR semantic**

NOTE: There are many ways to determine the
COLOR to return; we'll look at two over the
next two commits