

// MinTuts/Procedural Terrain.shader

```
Shader "MinTuts/Procedural Terrain" {
```

```
    SubShader {
```

```
        Pass {
```

```
            CGPROGRAM
```

```
                #pragma vertex    vert
```

```
                #pragma fragment frag
```

```
                #include "UnityCG.cginc"
```

```
                struct v2f {
```

```
                    float4 pos    : SV_POSITION;
```

```
                    float3 wpos   : POSITION1;
```

```
                };
```

```
                v2f vert(float4 vertex : POSITION) {
```

```
                    v2f o;
```

```
                    o.pos = UnityObjectToClipPos(vertex);
```

```
                    o.wpos = mul(unity_ObjectToWorld, vertex);
```

```
                    return o;
```

```
                }
```

```
                float4 frag(v2f i) : COLOR {
```

```
                    float  p = i.wpos.y * 0.015;
```

```
                    float3 y = float3(p, p, p);
```

```
                    return float4(y, 1);
```

```
                }
```

```
            ENDCG
```

```
        }
```

```
    }
```

```
}
```

The **Shader** section specifies the name (aka location in a Material's **Shader** drop-down menu in Unity)

This **Shader** would be located in the Procedural Terrain submenu under the MinTuts root menu item

// MinTuts/Procedural Terrain.shader

```
Shader "MinTuts/Procedural Terrain" {
```

```
    SubShader {
```

```
        Pass {
```

```
            CGPROGRAM
```

```
                #pragma vertex    vert
```

```
                #pragma fragment frag
```

```
                #include "UnityCG.cginc"
```

```
                struct v2f {
```

```
                    float4 pos    : SV_POSITION;
```

```
                    float3 wpos   : POSITION1;
```

```
                };
```

```
                v2f vert(float4 vertex : POSITION) {
```

```
                    v2f o;
```

```
                    o.pos = UnityObjectToClipPos(vertex);
```

```
                    o.wpos = mul(unity_ObjectToWorld, vertex);
```

```
                    return o;
```

```
                }
```

```
                float4 frag(v2f i) : COLOR {
```

```
                    float  p = i.wpos.y * 0.015;
```

```
                    float3 y = float3(p, p, p);
```

```
                    return float4(y, 1);
```

```
                }
```

```
            ENDCG
```

```
        }
```

```
    }
```

```
}
```

The **SubShader** section(s) specify all variants of our shader

This shader has a single **SubShader** - meaning all platforms (*PS4, mobile, PC, etc*) will use the same **SubShader**

We'll look at targeting specific platforms using multiple **SubShader** sections in a future Tut