

Preliminary analysis

Samuel Pawel, Björn Siepe, František Bartoš

11 August 2023

Visualizations

```
## libraries  
library(dplyr)
```

```
##  
## Attache Paket: 'dplyr'  
  
## Die folgenden Objekte sind maskiert von 'package:stats':  
##  
##     filter, lag  
  
## Die folgenden Objekte sind maskiert von 'package:base':  
##  
##     intersect, setdiff, setequal, union
```

```
library(tidyr)  
library(ggplot2)  
library(colorspace)  
library(ggpubr)  
library(stringr)  
library(forcats)  
library(knitr)  
library(kableExtra)
```

```
##  
## Attache Paket: 'kableExtra'  
  
## Das folgende Objekt ist maskiert 'package:dplyr':  
##  
##     group_rows
```

```
library(sysfonts)  
library(showtext)
```

```
## Lade nötiges Paket: showtextdb
```

```
library(here)
```

```
## here() starts at C:/Users/Bjoern/nondrive-academia/Projects/SimPsychReview
```

```
library(Hmisc)
```

```
##
```

```
## Attache Paket: 'Hmisc'
```

```
## Die folgenden Objekte sind maskiert von 'package:dplyr':
```

```
##
```

```
##      src, summarize
```

```
## Die folgenden Objekte sind maskiert von 'package:base':
```

```
##
```

```
##      format.pval, units
```

```
# devtools::install_github("kupietz/kableExtra")
```

```
theme_set(theme_bw() +  
  theme(legend.position = "top",  
        panel.grid.minor = element_blank()))
```

```
## pal <- "Harmonic" # change palette here
```

```
## ## colorspace::hcl_palettes("qualitative", plot = TRUE)
```

```
cols <- c("BRM" = "#E69F00", "MBR" = "#009E73", "PM" = "#0072B2")
```

```
# cols <- c("BRM" = "#E69F00", "MBR" = "#56B4E9", "PM" = "#009E73")
```

```
# Alternative font
```

```
theme_bs <- function(){
```

```
  # add google font
```

```
  sysfonts::font_add_google("News Cycle", "news")
```

```
  # use showtext
```

```
  showtext::showtext_auto()
```

```
  # theme
```

```
  ggplot2::theme_bw(base_family = "news") +
```

```
  ggplot2::theme(  
    legend.position = "top",  
    panel.grid.minor = element_blank(),  
  
    # Title and Axis Texts  
    plot.title = ggplot2::element_text(size = ggplot2::rel(1.2), hjust = 0.5),  
    plot.subtitle = ggplot2::element_text(size = ggplot2::rel(1.1), hjust = 0.5),  
    axis.title = ggplot2::element_text(size = ggplot2::rel(1.2)),  
    axis.text = ggplot2::element_text(size = ggplot2::rel(1.25)),  
    axis.text.x = ggplot2::element_text(margin = ggplot2::margin(5, b = 10))  
  )  
}
```

```
theme_set(theme_bs())
```

```
## data
```


```

sim_res_fac_full <- readRDS(file = here("data/sim_res_fac.RDS"))
sim_res_num_full <- readRDS(file = here("data/sim_res_num.RDS"))

# subset assessment only
sim_res_fac <- sim_res_fac_full %>%
  filter(simstudy_q1 == "yes",
         coding_type == "assessment")
sim_res_num <- sim_res_num_full %>%
  filter(simstudy_q1 == "yes",
         coding_type == "assessment")

## proportion of simulation studies by journal
sim_res_fac_full %>%
  filter(coding_type == "assessment" | is.na(coding_type)) %>%
  group_by(journal) %>%
  dplyr::summarize(propSim = mean(simstudy_q1 == "yes"),
                  n = n()) %>%
  mutate(journalLab = paste0(journal, " (n = ", n, ")")) %>%
  ggplot(aes(x = journalLab, y = propSim)) +
  geom_bar(stat = "identity", col = 1) +
  scale_y_continuous(labels = scales::percent, limits = c(0, 1)) +
  labs(x = NULL, title = "Journal", y = "Proportion of simulation studies") +
  theme(panel.grid.major.x = element_blank())

```



```

sim_res_fac_full %>%
  filter(coding_type == "assessment" | is.na(coding_type),
         year == 2022) %>%
  dplyr::summarize(propSim = mean(simstudy_q1 == "yes"),
                  sim = sum(simstudy_q1 == "yes"),
                  n = n())

```

```
## # A tibble: 1 x 3
```


```
##   propSim   sim     n
##   <dbl> <int> <int>
## 1   0.343    85   248
```

```
sim_res_fac_full %>%
  filter(coding_type == "assessment" | is.na(coding_type),
         year == 2022) %>%
  group_by(journal) %>%
  dplyr::summarize(propSim = mean(simstudy_q1 == "yes"),
                  sim = sum(simstudy_q1 == "yes"),
                  n = n())
```


```
## # A tibble: 3 x 4
##   journal propSim   sim     n
##   <fct>     <dbl> <int> <int>
## 1 BRM       0.156    24   154
## 2 MBR       0.814    35    43
## 3 PM        0.510    26    51
```

```
## Morris et al. (2019) find
## "264 articles of which 199 (75\%) included at least one simulation study"
```


```
## year
ggplot(data = sim_res_fac, aes(x = factor(year))) +
  geom_bar(col = 1) +
  labs(x = NULL, title = "Year") +
  theme(panel.grid.major.x = element_blank())
```



```
## journal
ggplot(data = sim_res_fac, aes(x = journal)) +
  geom_bar(col = 1) +
  labs(x = NULL, title = "Journal") +
  theme(panel.grid.major.x = element_blank())
```




```
## reviewer
ggplot(data = sim_res_fac, aes(x = reviewer)) +
  geom_bar(col = 1) +
  labs(x = NULL, title = "Reviewer") +
  theme(panel.grid.major.x = element_blank())
```




```
## Q2 number of simulation studies
# scale max for plot
q2_plot_max <- max(table(sim_res_fac$nsimstudies_q2)) + 5

q2 <- ggplot(data = sim_res_fac, aes(x = nsimstudies_q2, fill = journal)) +
  geom_bar(col = 1) +
  labs(x = NULL, title = "Number of simulation studies in article", fill = "Journal") +
  # scale_fill_discrete_qualitative(palette = pal) +
  scale_fill_manual(values = cols) +
  scale_y_continuous(limits = c(0, q2_plot_max), expand = c(0,0))+
  theme(panel.grid.major.x = element_blank())+
  labs(y = NULL)
q2
```




```
## Q3 are the aims of the study defined
q3 <- sim_res_fac %>%
  mutate(aimsdefined_q3 = factor(aimsdefined_q3,
                                levels = c("yes", "no", "unclear"))) %>%
ggplot(aes(x = aimsdefined_q3, fill = journal)) +
  geom_bar(col = 1) +
  labs(x = NULL, title = "Aims of the study defined?", fill = "Journal") +
  scale_fill_manual(values = cols) +
  theme(panel.grid.major.x = element_blank())
q3
```



```
## Q4 type of DGP
q4_plot_max <- max(table(sim_res_fac$dgptype_q4)) + 5

q4 <- sim_res_fac %>%
  mutate(dgptype_q4 = factor(dgptype_q4,
                             levels = c("parametric thin-air",
                                           "parametric based on actual data",
                                           "resampled"),
                             labels = c("parametric \ncustomized",
                                         #"parametric \nthin-air",
                                         "parametric \nbased on data",
                                         "resampled"))) %>%
  mutate(dgptype_q4 = reorder(dgptype_q4, dgptype_q4, length, decreasing = TRUE)) %>%
  ggplot(aes(x = dgptype_q4, fill = journal)) +
  geom_bar(col = 1) +
  labs(x = NULL, y = NULL, title = "Type of data-generating mechanism", fill = "Journal") +
  scale_fill_manual(values = cols) +
  scale_y_continuous(limits = c(0, q4_plot_max), expand = c(0,0)) +
  theme(panel.grid.major.x = element_blank())

q4
```



```
## from Morris: "97 simulation studies used some form of parametric model to
## generate data while three used resampling methods. Of the 97 that simulated
## from a parametric model, 27 based parameter values on data, one based
## parameter values partly on data, and the remaining 69 on no data. Of these
## 97, 91 (94%) provided the parameters used." (p. 2079)
```

```
## Q5 DGP parameters provided?
q5 <- sim_res_fac %>%
  mutate(dgpparameters_q5 = factor(dgpparameters_q5,
```




```

                                levels = c("yes", "no", "unclear")))) %>%
ggplot(aes(x = dgpparameters_q5, fill = journal)) +
  geom_bar(col = 1) +
  labs(x = NULL, title = "Are DGP parameters provided?", fill = "Journal") +
  scale_fill_manual(values = cols) +
  theme(panel.grid.major.x = element_blank())

```

q5



```

## Q6 How many conditions?
summary(sim_res_num$nconds_q6)

```

```

##      Min. 1st Qu.  Median    Mean 3rd Qu.    Max.     NA's
##      1.0     5.0    16.0   185.8   96.0   6000.0         1

```

```

breaks <- c(1, 10, 100, 1000, 10000)
labels <- c("1^phantom(1)", "10^1", "10^2", "10^3", "10^4")
q6 <- ggplot(data = sim_res_num, aes(x = log(nconds_q6), fill = journal)) +
  geom_histogram(breaks = seq(0, log(10000), 0.5), col = 1) +
  scale_x_continuous(breaks = log(breaks), labels = parse(text = labels)) +
  scale_y_continuous(breaks = seq(0, 12, 2), limits = c(0,13), expand = c(0,0)) +
  scale_fill_manual(values = cols) +
  labs(x = NULL, y = NULL,
       title = "How many simulation conditions?", fill = "Journal")


```

q6

```


## Warning: Removed 1 rows containing non-finite values ('stat_bin()').

```




```
## Q7 How many factors?
q7a_plot_max <- max(table(sim_res_fac$factorsvaried_q7)) + 5

q7a <- sim_res_num %>%
  mutate(factorsvaried_q7_fac = ifelse(is.na(factorsvaried_q7),
                                       "unclear", factorsvaried_q7)) %>%
  ggplot(aes(x = factorsvaried_q7_fac, fill = journal)) +
  geom_bar(col = 1) +
  labs(x = NULL, y = NULL,
       title = "How many factors varied?", fill = "Journal") +
  scale_fill_manual(values = cols) +
  scale_y_continuous(limits = c(0, q7a_plot_max), expand = c(0,0))+
  theme(panel.grid.major.x = element_blank())
q7a
```



```
## Q7 Fully factorial?
q7b_plot_max <- max(table(sim_res_fac$dgmfactorial_q7)) + 5

q7b <- sim_res_fac %>%
  mutate(dgmfactorial_q7 = factor(dgmfactorial_q7,
    levels = c("fully-factorial",
               "one-at-a-time",
               "partially-factorial"),
    # changed labels here after introduction of terminology "scattershot"
    labels = c("fully\nfactorial",
               "Scattershot",
               "partially/\none-at-a-time"))) %>%
  mutate(dgmfactorial_q7 = reorder(dgmfactorial_q7, dgmfactorial_q7,
    length, decreasing = TRUE)) %>%
  ggplot(aes(x = dgmfactorial_q7, fill = journal)) +
  geom_bar(col = 1) +
  labs(x = NULL, y = NULL,
       title = "How are factors varied?", fill = "Journal") +
  scale_fill_manual(values = cols) +
  scale_y_continuous(limits = c(0, q7b_plot_max), expand = c(0,0)) +
  theme(panel.grid.major.x = element_blank())
q7b
```




```
## # double check consistency here: how was a single varied factor treated?
## sim_res_fac %>%
##   filter(factorsvaried_q7 == 1) %>%
##   select(reviewer, factorsvaried_q7, dgmfactorial_q7) %>%
##   View()
```

```
## Q8 How many repetitions?
summary(sim_res_num$nsim_q8)
```

```
##      Min. 1st Qu.  Median    Mean 3rd Qu.    Max.     NA's
##         1      100      900  12198    1000 1000000         6
```


```
breaks <- c(1, 10, 100, 1000, 10000, 100000, 1000000)
labs <- c("1^phantom(1)", "10^1", "10^2", "10^3", "10^4", "10^5", "10^6")
q8 <- ggplot(data = sim_res_num, aes(x = log(nsim_q8), fill = as.factor(journal))) +
  geom_histogram(breaks = seq(0, log(2000000), 0.5), col = 1) +
  labs(x = NULL, y = NULL,
       title = "How many repetitions?", fill = "Journal") +
  scale_x_continuous(breaks = log(breaks), labels = parse(text = labs)) +
  scale_fill_manual(values = cols) +
  scale_y_continuous(limits = c(0,33), expand = c(0,0))
q8
```

```
## Warning: Removed 6 rows containing non-finite values ('stat_bin()').
```




```
## Q9 Are the number of repetitions justified?
q9_plot_max <- max(table(sim_res_fac$nsimjustified_q9)) + 5

q9 <- ggplot(data = sim_res_fac, aes(x = nsimjustified_q9, fill = journal)) +
  geom_bar(col = 1) +
  labs(x = NULL, y = NULL,
       title = "Are the number of repetitions justified?", fill = "Journal") +
  scale_fill_manual(values = cols) +
  scale_y_continuous(limits = c(0, q9_plot_max), expand = c(0,0))+
  theme(panel.grid.major.x = element_blank())
q9
```



```
## Q10 Is the estimand stated?
q10 <- ggplot(data = sim_res_fac, aes(x = estimandstated_q10, fill = journal)) +
  geom_bar(col = 1) +
  labs(x = NULL, y = NULL,
       title = "Is the estimand stated?", fill = "Journal") +
  scale_fill_manual(values = cols) +
  theme(panel.grid.major.x = element_blank())
q10
```




```
## Q11 How many estimands?
summary(sim_res_num$nestimands_q11)
```


```
##      Min. 1st Qu.  Median    Mean 3rd Qu.    Max.     NA's
##         1         2         4      22     15     384        10
```

```
breaks <- c(1, 3, 10, 30, 100, 300)
q11 <- ggplot(data = sim_res_num, aes(x = log(nestimands_q11), fill = journal)) +
  geom_histogram(breaks = seq(0, log(500), 0.4), col = 1) +
  scale_x_continuous(breaks = log(breaks), labels = breaks) +
  scale_y_continuous(limits = c(0, 23), expand = c(0,0)) +
  scale_fill_manual(values = cols) +
  labs(x = NULL, y = NULL,
       title = "How many estimands?", fill = "Journal")
q11
```

```
## Warning: Removed 10 rows containing non-finite values ('stat_bin()').
```



```
## Q12 Are estimands aggregated?
q12 <- ggplot(data = sim_res_fac, aes(x = estimandsagg_q12, fill = journal)) +
  geom_bar(col = 1) +
  labs(x = NULL, title = "Are estimands aggregated?", fill = "Journal") +
  scale_fill_manual(values = cols) +
  theme(panel.grid.major.x = element_blank())
q12
```




```
## Q13 How are the true parameters specified?
q13 <- ggplot(data = sim_res_fac, aes(x = truetheta_q13, fill = journal)) +
  geom_bar(col = 1) +
```

```

labs(x = NULL, y = NULL,
      title = "How are the true parameters specified?", fill = "Journal") +
scale_fill_manual(values = cols) +
theme(panel.grid.major.x = element_blank())
q13

```



```

## Q14 How many methods are included?
summary(sim_res_num$nmethoq14)

```

```

##      Min. 1st Qu.  Median    Mean 3rd Qu.    Max.
##      1.00   2.00   3.00   5.63   5.00  192.00


```

```

q14_plot_max <- max(table(sim_res_fac$nmethoq14)) + 3


q14 <- ggplot(data = sim_res_num, aes(x = factor(nmethoq14), fill = journal)) +
  geom_bar(col = 1) +
  ## scale_x_continuous(breaks = seq(1, 14), limits = c(0.5, 14.5)) +
  labs(x = NULL, y = NULL, title = "How many methods are included?", fill = "Journal") +
  scale_fill_manual(values = cols) +
  scale_y_continuous(limits = c(0, q14_plot_max), expand = c(0,0))+
  theme(panel.grid.major.x = element_blank())
q14

```

```
## Q15 What is the evaluation target of the simulation?
q15_plot_max <- max(table(sim_res_fac$target_q15)) + 5


q15a <- sim_res_fac %>%
  mutate(target_q15 = as.factor(target_q15)) %>%
  mutate(target_q15 = reorder(target_q15, target_q15, length)) %>%
  mutate(target_q15 = gsub("model selection", "model\\nselection", target_q15)) %>%
  ggplot(aes(x = target_q15, fill = journal)) +
  geom_bar(col = 1) +
  labs(x = NULL, y = NULL, title = "What is the statistical task?", fill = "Journal") +
  scale_fill_manual(values = cols) +
  scale_y_continuous(limits = c(0, q15_plot_max), expand = c(0,0))+
  theme(panel.grid.major.y = element_blank()) +
  coord_flip()
q15a
```



to keep it consistent with other questions, also spread apart results here

```
q15a_new <- sim_res_fac %>%
  separate_wider_delim(target_q15,
    delim = ",",
    names_sep = "_",
    too_few = "align_start") %>%
  pivot_longer(cols = contains("target"),
    names_to = NULL,
    values_to = "target",
    values_drop_na = TRUE) %>%
  mutate(target = str_trim(target)) %>%
  mutate(target = gsub("model selection", "model\\nselection", target)) %>%
  mutate(target = gsub("testing", "hypothesis\\ntesting", target)) %>%
  mutate(target = as.factor(target)) %>%
  mutate(target = reorder(target, target, length)) %>%
  ggplot(aes(x = target, fill = journal)) +
  geom_bar(col = 1) +
  labs(x = NULL, y = NULL, title = "What is the statistical task?",
    fill = "Journal") +
  scale_fill_manual(values = cols) +
  scale_y_continuous(limits = c(0, q15_plot_max + 10), expand = c(0,0)) +
  theme(panel.grid.major.y = element_blank()) +
  coord_flip()
```

q15a_new



```
## Q15 Which performance measures were used?
# Spread "Other" apart
q15_other <- sim_res_fac %>%
  separate_wider_delim(pmother_q15,
    delim = ",",
    names_sep = "_",
    too_few = "align_start") %>%
  pivot_longer(cols = contains("pmother"),
    names_to = NULL,
    values_to = "pmother",
    values_drop_na = TRUE) %>%
  dplyr::select(pmother, journal) %>%
  # remove whitespace
  mutate(pmother = str_trim(pmother)) %>%
  mutate(pmother = str_replace(pmother, ".*correlation.*", "Correlation")) %>%
  # mutate(pmother = str_replace(pmother, ".*standard deviation.*", "SD")) %>%
  mutate(pmother = str_replace(pmother, ".*bias.*", "Bias")) %>%
  mutate(pmother = as.factor(pmother)) %>%
  mutate(pmother = forcats::fct_lump_n(pmother, 2)) %>%
  group_by(journal) %>%
  count(pmother) %>%
  rename(PM = pmother,
    count = n)

# Visualize
q15b <- sim_res_fac %>%
  group_by(journal) %>%
  summarise("Convergence" = sum(pmconvergence_q15 == "yes"),
    "Bias" = sum(pmbias_q15 == "yes"),
    "Empirical SE" = sum(pmempse_q15 == "yes"),
    "(R)MSE" = sum(pm_r_mse_q15 == "yes"),
    "Coverage" = sum(pmcover_q15 == "yes"),
    "Type I error" = sum(pmtypeierror_q15 == "yes"),
```


```

    "Power" = sum(pmpower_q15 == "yes"),
    "CI width" = sum(pmciwidth_q15 == "yes")) %>%
gather(key = "PM", value = "count", "Convergence", "Bias", "(R)MSE",
       "Empirical SE", "Coverage", "Type I error",
       "Power", "CI width") %>%
bind_rows(q15_other) %>%
mutate(PM = as.factor(PM)) %>%
mutate(PM = reorder(PM, count, sum)) %>%
group_by(journal, PM) %>%
summarise(count = sum(count)) %>%
ggplot(aes(x = PM, y = count, fill = journal)) +
geom_bar(stat = "identity", col = 1) +
labs(x = NULL,
     y = NULL,
     title = "Performance measure",
     fill = "Journal") +
scale_fill_manual(values = cols) +
scale_y_continuous(limits = c(0,70), expand = c(0,0),
                   breaks = c(20, 40, 60))+
theme(panel.grid.major.y = element_blank()) +
coord_flip()

```

'summarise()' has grouped output by 'journal'. You can override using the
'.groups' argument.

q15b



```

# Double check if absolute/relative bias ever occur with bias rated as "no"
sim_res_fac %>%
  separate_wider_delim(pmother_q15,

```

```

        delim = ",",
        names_sep = "_",
        too_few = "align_start") %>%
pivot_longer(cols = contains("pmother"),
             names_to = NULL,
             values_to = "pmother",
             values_drop_na = TRUE) %>%
mutate(pmother = str_trim(pmother)) %>%
# mutate(pmother = str_replace(pmother, ".*bias.*", "bias")) %>%
filter(grepl("bias", pmother)) %>%
dplyr::select(reviewer, pmbias_q15, pmother)

```

```

## # A tibble: 18 x 3
##   reviewer pmbias_q15 pmother
##   <fct>    <fct>    <chr>
## 1 FB      yes      absolute bias
## 2 FB      yes      relative bias
## 3 FB      yes      relative bias
## 4 FB      no       absolute bias
## 5 FB      yes      bias of standard errors
## 6 FB      no       relative bias
## 7 FB      yes      relative bias
## 8 FB      no       relative bias
## 9 FB      no       relative bias of standard errors
## 10 FB     no       relative bias
## 11 FB     no       relative bias
## 12 FB     no       relative bias
## 13 FB     no       relative bias of se
## 14 FB     no       relative bias
## 15 FB     no       absolute relative bias
## 16 FB     yes      relative bias of se
## 17 FB     no       relative bias
## 18 BS     yes      SD of SE bias (as uncertainty)

```

```

# What is included in "Standard Deviation"?
sim_res_fac %>%
  separate_wider_delim(pmother_q15,
                      delim = ",",
                      names_sep = "_",
                      too_few = "align_start") %>%
pivot_longer(cols = contains("pmother"),
             names_to = NULL,
             values_to = "pmother",
             values_drop_na = TRUE) %>%
mutate(pmother = str_trim(pmother)) %>%
# mutate(pmother = str_replace(pmother, ".*bias.*", "bias")) %>%
filter(grepl("standard deviation", pmother)) %>%
dplyr::select(pmother)

```

```

## # A tibble: 8 x 1
##   pmother
##   <chr>
## 1 means and standard deviations of the estimates

```


```
## 2 efficiency (standard deviation of estimates)
## 3 standard deviations
## 4 standard deviations
## 5 standard deviation
## 6 efficiency (standard deviation of estimates)
## 7 standard deviation
## 8 standard deviation over aggregated estimates
```

```
## Q16 Is Monte Carlo uncertainty reported anywhere?
```

```
q16_plot_max <- max(table(sim_res_fac$merrors_q16)) + 10
```

```
q16 <- sim_res_fac %>%
  separate_wider_delim(merrors_q16,
    delim = ",",
    names_sep = "_",
    too_few = "align_start") %>%
  pivot_longer(cols = contains("merrors"),
    names_to = NULL,
    values_to = "merrors",
    values_drop_na = TRUE) %>%
  mutate(merrors = str_trim(merrors)) %>%
  mutate(merrors = gsub("boxplot", "plot", merrors)) %>%
  mutate(merrors = gsub("quantile plots", "plot", merrors)) %>%
  mutate(merrors = gsub("figures", "plot", merrors)) %>%
  mutate(merrors = gsub("tables", "table", merrors)) %>%
  mutate(merrors = as.factor(merrors)) %>%
  mutate(merrors = reorder(merrors, merrors, length)) %>%
  ggplot(aes(x = merrors, fill = journal)) +
    geom_bar(col = 1) +
    labs(x = NULL, y = NULL,
      title = "Is Monte Carlo uncertainty reported anywhere?", fill = "Journal") +
    scale_fill_manual(values = cols) +
    theme(panel.grid.major.x = element_blank()) +
    scale_y_continuous(limits = c(0, q16_plot_max), expand = c(0,0))+
    coord_flip()
```


```
q16
```




```
# Same plot, only yes/no
q16_yn <- sim_res_fac %>%
  mutate(mcerrors_q16 = ifelse(mcerrors_q16 == "nowhere",
                                "no",
                                "yes")) %>%

  mutate(mcerrors_q16 = as.factor(mcerrors_q16)) %>%
  # mutate(mcerrors_q16 = reorder(mcerrors_q16, mcerrors_q16, length)) %>%
  ggplot(aes(x = mcerrors_q16, fill = journal)) +
    geom_bar(col = 1) +
    labs(x = NULL, y = NULL,
         title = "Is Monte Carlo uncertainty reported anywhere?", fill = "Journal") +
    scale_fill_manual(values = cols) +
    theme(panel.grid.major.x = element_blank()) +
    scale_y_continuous(limits = c(0, q16_plot_max), expand = c(0,0))
  # coord_flip()
q16_yn
```


Is Monte Carlo uncertainty reported anywhere?



```
## Q17 In which way are the results reported?
q17 <- sim_res_fac %>%
  group_by(journal) %>%
  summarise("Figure" = sum(resultsfigure_q17 == "yes"),
            "Table" = sum(resultstable_q17 == "yes"),
            "Text" = sum(resultstext_q17 == "yes"),
            "Other" = sum(resultsother_q17 == "yes")) %>%
  gather(key = "Type", value = "count", "Figure", "Table", "Text", "Other") %>%
  # omit "Other" category for plot
  filter(Type != "Other") %>%
  mutate(Type = as.factor(Type)) %>%
  mutate(Type = reorder(Type, count, sum, decreasing = TRUE)) %>%
  ggplot(aes(x = Type, y = count, fill = journal)) +
  geom_bar(stat = "identity", col = 1) +
  labs(x = NULL, y = NULL,
       title = "In which way are the results reported?", fill = "Journal") +
  scale_fill_manual(values = cols) +
  scale_y_continuous(limits = c(0,100), expand = c(0,0)) +
  theme(panel.grid.major.x = element_blank())
q17
```


```
## Q18 Which software was used to conduct the simulation?
q18_plot_max <- max(table(sim_res_fac$software_1_q18)) + 10
q18a <- ggplot(data = sim_res_fac, aes(x = software_1_q18, fill = journal)) +
  geom_bar(col = 1) +
  labs(x = NULL, y = NULL,
       title = "Which primary software was used?", fill = "Journal") +
  scale_y_continuous(limits = c(0, q18_plot_max), expand = c(0,0)) +
  scale_fill_manual(values = cols) +
  theme(panel.grid.major.y = element_blank()) +
  coord_flip()
q18a
```



```

# add information from software_2_q18 and software_3_q18
q18b <- sim_res_fac %>%
  dplyr::select(starts_with("software"), journal) %>%
  pivot_longer(cols = starts_with("software"),
               names_to = NULL,
               values_to = "software",
               values_drop_na = TRUE) %>%
  mutate(software = as.factor(software)) %>%
  mutate(software = reorder(software, software, length)) %>%
  ggplot(aes(x = software, fill = journal)) +
  geom_bar(col = 1) +
  labs(x = NULL, y = NULL, title = "Which software was used?", fill = "Journal") +
  scale_fill_manual(values = cols) +
  scale_y_continuous(limits = c(0, q18_plot_max), expand = c(0,0)) +
  theme(panel.grid.major.y = element_blank()) +
  coord_flip()
q18b


```



```

## Q19 Are there userwritten commands/packages/macros?
q19 <- ggplot(data = sim_res_fac, aes(x = userwritten_q19, fill = journal)) +
  geom_bar(col = 1) +
  labs(x = NULL, title = "Are there userwritten commands/packages/macros?", fill = "Journal") +
  scale_fill_manual(values = cols) +
  theme(panel.grid.major.x = element_blank())
q19

```




```
## Q20 Is code provided?
q20_plot_max <- max(table(sim_res_fac$codeprovided_q20)) + 5

# Reordered this such that negative is on the left to stay consistent
q20 <- sim_res_fac %>%
  mutate(codeprovided_q20 = as.factor(codeprovided_q20)) %>%
  mutate(codeprovided_q20 = reorder(codeprovided_q20, codeprovided_q20,
                                    length, decreasing = TRUE)) %>%
  ggplot(aes(x = codeprovided_q20, fill = journal)) +
  geom_bar(col = 1, col = 1) +
  labs(x = NULL, y = NULL, title = "Is code provided?", fill = "Journal") +
  scale_fill_manual(values = cols) +
  scale_y_continuous(limits = c(0, q20_plot_max), expand = c(0,0)) +
  theme(panel.grid.major.x = element_blank())
```

```
## Warning in geom_bar(col = 1, col = 1): Ignoring unknown parameters: 'col'
```

```
q20
```




```
## Q21 If code is provided, is a seed provided?
q21 <- ggplot(data = sim_res_fac, aes(x = seedprovided_q21, fill = journal)) +
  geom_bar(col = 1) +
  labs(x = NULL, title = "If code is provided, is a seed provided?", fill = "Journal") +
  scale_fill_manual(values = cols) +
  theme(panel.grid.major.x = element_blank())

# Compute as conditional on code provided
q21 <- sim_res_fac %>%
  filter(codeprovided_q20 == "accessible online") %>%
  ggplot(aes(x = seedprovided_q21, fill = journal)) +
  geom_bar(col = 1) +
  labs(x = NULL,
       y = NULL,
       title = "If code is provided, is a seed provided?", fill = "Journal") +
  scale_fill_manual(values = cols) +
  theme(panel.grid.major.x = element_blank())
sim_res_fac %>%
  filter(codeprovided_q20 == "accessible online") %>%
  count(seedprovided_q21)
```


```
## # A tibble: 2 x 2
##   seedprovided_q21      n
##   <fct>            <int>
## 1 not found         15
## 2 yes               21
```

```
q21
```




```
## Q22 Is information on the computational environment provided?
q22_plot_max <- max(table(sim_res_fac$compenvironment_q22)) + 7


q22 <- sim_res_fac %>%
  mutate(compenvironment_q22 = factor(compenvironment_q22,
                                     levels = c("no", "minimal", "partially", "fully"))) %>%
  ggplot(aes(x = compenvironment_q22, fill = journal)) +
  geom_bar(col = 1) +
  labs(x = NULL, y = NULL,
       title = "Is information on computational environment provided?",
       fill = "Journal") +
  scale_fill_manual(values = cols) +
  scale_y_continuous(limits = c(0, q22_plot_max), expand = c(0,0)) +
  theme(panel.grid.major.x = element_blank())
q22
```



```
## Q23 Is information on the operating system provided?
q23 <- sim_res_fac %>%
  mutate(compos_q23 = factor(compos_q23,
                             levels = c("no", "partially", "fully"))) %>%
  ggplot(aes(x = compos_q23, fill = journal)) +
  geom_bar(col = 1) +
  labs(x = NULL, y = NULL,
       title = "Is information on the operating system provided?",
       fill = "Journal") +
  scale_fill_manual(values = cols) +
  theme(panel.grid.major.x = element_blank())
q23
```



```
## Q24 How confident was reviewer in coding of the article?
q24 <- sim_res_fac %>%
  mutate(coding_confidence = factor(coding_confidence,
                                     levels = c("poor", "medium", "great"))) %>%
  ggplot(aes(x = coding_confidence, fill = journal)) +
  geom_bar(col = 1) +
  labs(x = NULL,
       y = NULL,
       title = "How confident was reviewer in coding of the article?",
       fill = "Journal") +
  scale_fill_manual(values = cols) +
  theme(panel.grid.major.x = element_blank())
q24
```



```
## composite plot 1 - problematic questions
plotList1 <- lapply(X = list(q9, q16_yn, q20, q22),
  ## this plot requires a different title size
  FUN = function(plot) {
    plot+
    scale_y_continuous(limits = c(0, 105), expand = c(0,0)) +
    theme(axis.text.x = element_text(size = rel(1.2)),
          plot.title = element_text(size = rel(1.35)),
          legend.title = element_text(size = rel(1.6)),
          legend.text = element_text(size = rel(1.6)),
          legend.spacing = unit(1.5, "cm"))
  })
```

```
## Scale for y is already present.
## Adding another scale for y, which will replace the existing scale.
## Scale for y is already present.
## Adding another scale for y, which will replace the existing scale.
```

```

## Scale for y is already present.
## Adding another scale for y, which will replace the existing scale.
## Scale for y is already present.
## Adding another scale for y, which will replace the existing scale.

fig1 <- ggpubr::ggarrange(plotlist = plotList1, labels = LETTERS[1:4], ncol = 2, nrow = 2,
  common.legend = TRUE, align = "h")
ggsave("fig1.pdf", fig1, path = here("figures/"), width = 10.5, height = 7)

## composite plot 2 - descriptives
plotList2 <- lapply(X = list(q2, q4, q6, q7a, q7b, q8, q14,
  q15a_new, q11, q15b, q17, q18b),
  ## this plot requires a different title size
  FUN = function(plot) {
    plot +
      theme(axis.text.x = element_text(size = rel(1.4)),
        axis.text.y = element_text(size = rel(1.2)),
        axis.title = element_text(size = rel(1.4)),
        plot.title = element_text(size = rel(2)),
        legend.title = element_text(size = rel(2.2)),
        legend.text = element_text(size = rel(2.2)),
        legend.spacing = unit(1.5, "cm"))
  })
names <- LETTERS[1:length(plotList2)]
fig2 <- ggpubr::ggarrange(plotlist = plotList2, labels = names,
  ncol = 3, nrow = 4, common.legend = TRUE, align = "h",
  font.label = list(size = 18, color = "black", face = "bold",
    family = NULL))

## fig2
scale <- 0.94
ggsave("fig2.pdf", fig2, path = here("figures/"), width = scale*17, height = scale*22)

```

Descriptives

Show descriptives grouped by journal, then ungrouped.

```

# detailed per-journal descriptives
journal_describe <- sim_res_fac %>%
  split(.$journal) %>%
  purrr::map(~Hmisc::describe(.x))

# In a tidy way for long summary table
summary_vars <- c(
  "reviewer", "simstudy_q1",
  "nsimstudies_q2", "whichsim", "aimsdefined_q3",
  "dgptype_q4",
  # "dgpparameters_q5",
  # "nconds_q6",
  "factorsvaried_q7", "dgmfactorial_q7",
  # "nsim_q8",
  "nsimjustified_q9",

```



```

"estimandstated_q10",
# "nestimands_q11",
"estimandsagg_q12", "truetheta_q13",
"nmethods_q14",
"target_q15",
"pmconvergence_q15", "pmbias_q15", "pmempse_q15", "pm_r_mse_q15",
"pmcover_q15", "pmtypeierror_q15", "pmpower_q15", "pmciwidth_q15",
"pmsclear_q15", "mcerrors_q16",
"resultsfigure_q17", "resultstable_q17", "resultstext_q17",
"resultsother_q17", "software_1_q18", "software_2_q18",
"software_3_q18", "software", "userwritten_q19",
"codeprovided_q20", "seedprovided_q21",
"compenvironment_q22", "compos_q23",
"coding_confidence"
)

sim_res_fac %>%
  as.data.frame() %>%
  group_by(journal) %>%
  pivot_longer(cols = starts_with("software"),
               names_to = NULL,
               values_to = "software",
               values_drop_na = TRUE) %>%
  mutate(software = as.factor(software)) %>%
  pivot_longer(cols = any_of(summary_vars),
               names_to = "col", values_to = "response") %>%
  select(doi, journal, col, response) %>%
  # get distinct responses per paper %>%
  group_by(doi, col) %>%
  distinct(response, .keep_all = TRUE) %>%
  ungroup() %>%
  group_by(journal, col) %>%
  count(response) %>%
  # filter(!is.na(response)) %>%
  # View()
  pivot_wider(id_cols = c(col, response),
              names_from = journal,
              values_from = n,
              values_fill = 0) %>%
  arrange(factor(col, levels = summary_vars)) %>%
  rowwise() %>%
  mutate(Sum = sum(BRM, MBR, PM)) %>%
  knitr::kable("latex", longtable = TRUE, caption = "Grouped by Journal") %>%
  kableExtra::column_spec(1, bold = TRUE) %>%
  kableExtra::collapse_rows(columns = 1:2, valign = "top")

```

Table 1: Grouped by Journal

col	response	BRM	MBR	PM	Sum
reviewer	BS	9	13	10	32
	FB	5	15	14	34
	SP	18	7	9	34

simstudy_q1	yes	32	35	33	100
nsimstudies_q2	1	21	24	18	63
	2	5	8	11	24
	3	4	3	4	11
	5	1	0	0	1
	6	1	0	0	1
whichsim	1	25	23	25	73
	NA	7	11	7	25
	2	0	1	0	1
	3	0	0	1	1
aimsdefined_q3	no	1	1	1	3
	unclear	2	1	0	3
	yes	29	33	32	94
dgptype_q4	parametric based on actual data	3	5	7	15
	parametric thin-air	29	29	25	83
	resampled	0	1	1	2
factorsvaried_q7	1	6	9	13	28
	2	3	2	8	13
	3	9	12	1	22
	4	7	6	4	17
	5	3	3	3	9
	6	2	2	2	6
	7	2	0	2	4
	unclear	0	1	0	1
dgmfactorial_q7	fully-factorial	24	19	15	58
	one-at-a-time	1	4	0	5
	partially-factorial	7	12	18	37
nsimjustified_q9	no	28	34	30	92
	yes	4	1	3	8
estimandstated_q10	no	6	3	2	11
	unclear	3	3	0	6
	yes	23	29	29	81
	not applicable	0	0	2	2
estimandsagg_q12	no	26	27	26	79
	unclear	1	3	0	4
	yes	5	5	7	17
truetheta_q13	estimated	2	3	2	7
	known	30	32	29	91
	not applicable	0	0	2	2
	1	7	10	7	24
	10	1	0	1	2
	11	2	0	2	4
	192	1	0	0	1
	2	7	10	6	23
	3	5	6	7	18
	4	2	3	2	7
	5	4	0	1	5
	6	2	2	3	7
	7	1	0	1	2
	10?	0	1	0	1
	14	0	1	0	1
	8	0	1	0	1
	9	0	1	1	2
	11+	0	0	1	1

	13	0	0	1	1
target_q15	design	1	1	2	4
	estimation	14	20	22	56
	estimation, testing	5	4	0	9
	model selection	2	4	1	7
	other	2	0	3	5
	prediction	2	1	1	4
	testing	6	2	4	12
	design, estimation	0	1	0	1
	estimation, model selection	0	2	0	2
pmconvergence_q15	no	28	28	23	79
	yes	4	7	8	19
	unclear	0	0	2	2
pmbias_q15	no	20	12	23	55
	yes	12	23	10	45
pmempse_q15	no	30	31	24	85
	yes	2	4	9	15
pm_r_mse_q15	no	21	18	22	61
	yes	11	17	11	39
pmcover_q15	no	24	25	25	74
	yes	8	10	8	26
pmtypeierror_q15	no	22	28	23	73
	yes	10	7	10	27
pmpower_q15	no	25	28	23	76
	yes	7	7	10	24
pmciwidth_q15	no	30	30	32	92
	yes	2	5	1	8
pmsclear_q15	no	2	1	2	5
	unclear	3	0	2	5
	yes	27	34	29	90
mcerrors_q16	boxplot	1	3	2	6
	nowhere	25	27	26	78
	plot	1	0	0	1
	plot, table	1	0	0	1
	standard deviation	3	1	0	4
	text	1	0	1	2
	figures	0	1	0	1
	reference intervals	0	1	0	1
	tables, text	0	2	0	2
	quantile plots	0	0	1	1
	ranges	0	0	1	1
	table	0	0	2	2
resultsfigure_q17	no	6	16	17	39
	yes	26	19	16	61
resultstable_q17	no	14	7	9	30
	yes	18	28	24	70
resultstext_q17		32	33	31	96
resultsother_q17	no	0	2	2	4
	yes	28	31	29	88
	C++	1	0	0	1
	JAGS	1	0	1	2
	Java	1	0	0	1
	MATLAB	3	2	1	6

	Mplus	2	2	3	7
	Python	3	1	0	4
	R	22	26	29	77
	SAS	2	2	0	4
	unclear	3	4	2	9
	Stan	0	1	1	2
	Ox	0	0	1	1
	Stata	0	0	1	1
	flexMIRT	0	0	1	1
userwritten_q19	no	18	19	10	47
	unclear	3	2	3	8
	yes	11	14	20	45
codeprovided_q20	accessible online	16	6	14	36
	not accessible	16	29	19	64
seedprovided_q21	not found	24	30	25	79
	yes	8	5	8	21
compenvironment_q22	fully	1	0	1	2
	minimal	15	22	23	60
	no	9	9	6	24
	partially	7	4	3	14
compos_q23	fully	2	1	1	4
	no	29	33	31	93
	partially	1	1	1	3
coding_confidence	great	20	18	24	62
	medium	9	15	8	32
	poor	3	2	1	6

```

# Ungrouped and with proportions
sim_res_fac %>%
  as.data.frame() %>%
  # pivot_longer(cols = starts_with("software"),
  #             names_to = NULL,
  #             values_to = "software",
  #             values_drop_na = TRUE) %>%
  # mutate(software = as.factor(software)) %>%
  pivot_longer(cols = any_of(summary_vars),
              names_to = "col", values_to = "response") %>%
  select(col, response) %>%
  group_by(col) %>%
  count(response) %>%
  arrange(factor(col, levels = summary_vars)) %>%
  knitr::kable("latex", longtable = TRUE, caption = "Ungrouped") %>%
  kableExtra::column_spec(1, bold = TRUE) %>%
  kableExtra::collapse_rows(columns = 1:2, valign = "top")

```

Table 2: Ungrouped

col	response	n
reviewer	BS	32
	FB	34
	SP	34
simstudy_q1	yes	100
	1	63

nsimstudies_q2	2	24
	3	11
	5	1
	6	1
whichsim	1	73
	2	1
	3	1
	NA	25
aimsdefined_q3	no	3
	unclear	3
	yes	94
dgptype_q4	parametric based on actual data	15
	parametric thin-air	83
	resampled	2
factorsvaried_q7	1	28
	2	13
	3	22
	4	17
	5	9
	6	6
	7	4
	unclear	1
dgmfactorial_q7	fully-factorial	58
	one-at-a-time	5
	partially-factorial	37
nsimjustified_q9	no	92
	yes	8
estimandstated_q10	no	11
	not applicable	2
	unclear	6
	yes	81
estimandsagg_q12	no	79
	unclear	4
	yes	17
truetheta_q13	estimated	7
	known	91
	not applicable	2
nmethods_q14	1	24
	10	2
	10?	1
	11	4
	11+	1
	13	1
	14	1
	192	1
	2	23
	3	18
	4	7
	5	5
	6	7
	7	2
	8	1
	9	2

target_q15	design	4
	design, estimation	1
	estimation	56
	estimation, model selection	2
	estimation, testing	9
	model selection	7
	other	5
	prediction	4
	testing	12
pmconvergence_q15	no	79
	unclear	2
	yes	19
pmbias_q15	no	55
	yes	45
pmempse_q15	no	85
	yes	15
pm_r_mse_q15	no	61
	yes	39
pmcover_q15	no	74
	yes	26
pmtypeierror_q15	no	73
	yes	27
pmpower_q15	no	76
	yes	24
pmciwidth_q15	no	92
	yes	8
pmsclear_q15	no	5
	unclear	5
	yes	90
mcerrors_q16	boxplot	6
	figures	1
	nowhere	78
	plot	1
	plot, table	1
	quantile plots	1
	ranges	1
	reference intervals	1
	standard deviation	4
	table	2
	tables, text	2
	text	2
resultsfigure_q17	no	39
	yes	61
resultstable_q17	no	30
	yes	70
resultstext_q17	no	4
	yes	96
resultsother_q17	no	88
	yes	12
	C++	1
	JAGS	1
	Java	1
	MATLAB	5
	Mplus	1

	Ox	1
	Python	2
	R	76
	SAS	3
	unclear	9
software_2_q18	JAGS	1
	MATLAB	1
	Mplus	6
	Python	2
	R	1
	SAS	1
	Stan	2
	Stata	1
	flexMIRT	1
	NA	84
software_3_q18		100
userwritten_q19	no	47
	unclear	8
	yes	45
codeprovided_q20	accessible online	36
	not accessible	64
seedprovided_q21	not found	79
	yes	21
compenvironment_q22	fully	2
	minimal	60
	no	24
	partially	14
compos_q23	fully	4
	no	93
	partially	3
coding_confidence	great	62
	medium	32
	poor	6

Analyses of individual questions:

```
# Q8:
sim_res_num$nsim_q8 %>%
  table()
```

```
## .
##      1      10      25      30      50      60      100      200      400      500      800      1000      2000
##      1       2       1       3       1       1       17       5       1       14       1       29       3
## 2500 3000 5000 10000 1e+06
##      1       1       5       7       1
```

```
# Q15a:
sim_res_fac %>%
  separate_wider_delim(target_q15,
                        delim = ",",
                        names_sep = "_",
                        too_few = "align_start") %>%
  pivot_longer(cols = contains("target"),
```

```

names_to = NULL,
values_to = "target",
values_drop_na = TRUE) %>%
mutate(target = str_trim(target)) %>%
mutate(target = as.factor(target)) %>%
count(target) %>%
arrange(desc(n))

```

```

## # A tibble: 6 x 2
##   target      n
##   <fct>    <int>
## 1 estimation    68
## 2 testing      21
## 3 model selection    9
## 4 design         5
## 5 other          5
## 6 prediction       4

```

```

# Q15:
sim_res_fac %>%
  group_by(journal) %>%
  summarise("Convergence" = sum(pmconvergence_q15 == "yes"),
            "Bias" = sum(pmbias_q15 == "yes"),
            "Empirical SE" = sum(pmempse_q15 == "yes"),
            "(R)MSE" = sum(pm_r_mse_q15 == "yes"),
            "Coverage" = sum(pmcover_q15 == "yes"),
            "Type I error rate" = sum(pmtypeierror_q15 == "yes"),
            "Power" = sum(pmpower_q15 == "yes"),
            "CI width" = sum(pmcwidth_q15 == "yes"),
            "Other" = sum(!is.na(pmother_q15))) %>%
  gather(key = "PM", value = "count", "Convergence", "Bias", "(R)MSE",
         "Empirical SE", "Coverage", "Type I error rate",
         "Power", "CI width", "Other") %>%
  bind_rows(q15_other) %>%
  group_by(PM) %>%
  dplyr::summarize(sum = sum(count)) %>%
  arrange(desc(sum))

```

```

## # A tibble: 10 x 2
##   PM      sum
##   <chr>  <int>
## 1 Other    125
## 2 Bias     63
## 3 (R)MSE   39
## 4 Type I error rate  27
## 5 Coverage  26
## 6 Power    24
## 7 Convergence  19
## 8 Empirical SE  15
## 9 CI width    8
## 10 Correlation    6

```


sessionInfo()

```
## R version 4.3.1 (2023-06-16 ucrt)
## Platform: x86_64-w64-mingw32/x64 (64-bit)
## Running under: Windows 11 x64 (build 22621)
##
## Matrix products: default
##
## locale:
## [1] LC_COLLATE=German_Germany.utf8  LC_CTYPE=German_Germany.utf8
## [3] LC_MONETARY=German_Germany.utf8 LC_NUMERIC=C
## [5] LC_TIME=German_Germany.utf8
##
## time zone: Europe/Berlin
## tzcode source: internal
##
## attached base packages:
## [1] stats      graphics  grDevices  utils      datasets  methods   base
##
## other attached packages:
## [1] Hmisc_5.1-1      here_1.0.1      showtext_0.9-6
## [4] showtextdb_3.0   sysfonts_0.8.8  kableExtra_1.3.4.9000
## [7] knitr_1.44       forcats_1.0.0   stringr_1.5.0
## [10] ggpubr_0.6.0     colorspace_2.1-0 ggplot2_3.4.4
## [13] tidyr_1.3.0      dplyr_1.1.3
##
## loaded via a namespace (and not attached):
## [1] gtable_0.3.4      xfun_0.40       htmlwidgets_1.6.2 rstatix_0.7.2
## [5] vctrs_0.6.3       tools_4.3.1     generics_0.1.3    curl_5.1.0
## [9] tibble_3.2.1      fansi_1.0.5     cluster_2.1.4     pkgconfig_2.0.3
## [13] data.table_1.14.8 checkmate_2.2.0 webshot_0.5.5     lifecycle_1.0.3
## [17] farver_2.1.1      compiler_4.3.1  textshaping_0.3.6 munsell_0.5.0
## [21] carData_3.0-5     htmltools_0.5.6.1 yaml_2.3.7        htmlTable_2.4.1
## [25] Formula_1.2-5     pillar_1.9.0    car_3.1-2         rpart_4.1.19
## [29] abind_1.4-5       tidyselect_1.2.0 rvest_1.0.3       digest_0.6.33
## [33] stringi_1.7.12    purrr_1.0.2     labeling_0.4.3    cowplot_1.1.1
## [37] rprojroot_2.0.3   fastmap_1.1.1   grid_4.3.1        cli_3.6.1
## [41] magrittr_2.0.3    base64enc_0.1-3 utf8_1.2.3        broom_1.0.5
## [45] foreign_0.8-84    withr_2.5.1     scales_1.2.1      backports_1.4.1
## [49] rmarkdown_2.25    httr_1.4.7      nnet_7.3-19       gridExtra_2.3
## [53] ggsignif_0.6.4    ragg_1.2.5      evaluate_0.22     viridisLite_0.4.2
## [57] rlang_1.1.1       glue_1.6.2      xml2_1.3.5        jsonlite_1.8.7
## [61] svglite_2.1.1     rstudioapi_0.15.0 R6_2.5.1          systemfonts_1.0.5
```