1

`error_reporting(E_ALL);`
`ini_set('display_errors', 1);`
`//to display errors`
 	
`$stmt->error`
	`session_start();`
	`require 'db.php';`
	`if(!isset($_SESSION['user_id'])){`
	`  header("Location: login.php");`
	`  exit();`
	`}`
	`//to start a session for each pg`

CREATE

```
if(isset($_POST['submit'])){
    $user_id = $_SESSION['user_id'];
    $title = $_POST['title'];
    $mood = $_POST['mood'];
    $content = $_POST['content'];
    $entryDate = $_POST['date'];

    $stmt = $conn->prepare("INSERT INTO entries(user_id, title, mood, content, entry_date)
    VALUES (?,?,?,?,?)");
    $stmt->bind_param("issss", $user_id, $title, $mood, $content, $entryDate);

    if($stmt->execute()){
        echo 'Journal entry successfully added. Redirecting to Read Entries';
        header("refresh:3;url=read.php");
    }else{
        echo 'Error adding record' . $stmt->error;
    }
}
```

2

```
<h1>Create a new Journal entry here!</h1>
<form method="POST" action=" ">
    <table>
        <tr>
            <td><label>Title</label></td>
            <td><input type="text" name="title" required></td>
        </tr>
        <tr>
            <td><label>Mood</label></td>
            <td>
            <?php
                $options = ['Happy', 'Neutral', 'Sad', 'Anxious', 'Excited'];
            ?>
            <select name="mood" required>
                <?php
                    foreach($options as $option){
                        echo "<option>$option</option>";
                    }
                ?>
            </select>
            </td>
        </tr>
        <tr>
            <td><label>Content</label></td>
            <td><input type="text" name="content" required></td>
        </tr>
        <tr>
            <td><label>Entry Date</label></td>
            <td><input type="date" name="date" required></td>
        </tr>
        <tr>
            <td><button type="submit" name="submit">Submit entry</button></td>
        </tr>
    </table>
</form>
```

3

READ

```php
$user_id = $_SESSION['user_id'];
$stmt = $conn->prepare("SELECT * FROM entries WHERE user_id = ? ORDER BY entry_date");
$stmt->bind_param("i", $user_id);

if($stmt->execute()){
    $result = $stmt->get_result();
}else{
    echo "Error retrieving your journal entries" . $stmt->error;
}
```

```php
<h1>Read your Journal Entries here!</h1>
<table>
    <tr>
        <th>Title</th>
        <th>Mood</th>
        <th>Content</th>
        <th>Entry Date</th>
        <th>Functions</th>
    </tr>
    <tr>
        <?php
            $total_records = 0;
            while($row = $result->fetch_assoc()){
                echo "<tr>";
                echo "<td>{$row['title']}</td>";
                echo "<td>{$row['mood']}</td>";
                echo "<td>{$row['content']}</td>";
                echo "<td>{$row['entry_date']}</td>";
                echo "<td> <a href='update.php?id={$row['id']}'>Edit</a> </td>";
                echo "<td> <a href='delete.php?id={$row['id']}'>Delete</a> </td>";
                echo "</tr>";
                $total_records++;
            }
        ?>
    </tr>
    <th></th>
</table>
<p>Total number of entries: <?php echo $total_records ?></p>
```

4

UPDATE

```php
$user_id = $_SESSION['user_id'];
$entry_id = $_GET['id'];
$stmt = $conn->prepare("SELECT * FROM entries WHERE user_id = ? AND id = ?");
$stmt->bind_param("ii", $user_id, $entry_id);

if($stmt->execute()){
    $result = $stmt->get_result();
    $row = $result->fetch_assoc();
    if(!($row['user_id'] == $user_id)){
        echo "You are not authorized to view this";
        header("refresh:2;url=read.php");
    }

}else{
    echo "Error retrieving your journal entries" . $stmt->error;
}
```

```php
<h1>Update your Journal Entries here!</h1>
<!-- Best not to put action if the php is in itself -->
<form method="POST" action=" ">
    <table>
        <tr>
            <td><label>Title</label></td>
            <td><input type="text" name="title" value="<?php echo $row['title']; ?>" required></td>
        </tr>
        <tr>
            <td><label>Mood</label></td>
            <td>
            <select name="mood" required>
                <?php
                $options = ['Happy', 'Neutral', 'Sad', 'Anxious', 'Excited'];

                foreach ($options as $option) {
                    // If the database value matches this option, add the 'selected' attribute
                    $selected = ($row['mood'] == $option) ? 'selected' : '';
                    echo "<option value=\"$option\" $selected>$option</option>";
                }
                ?>
            </select>
            </td>
        </tr>
        <tr>
            <td><label>Content</label></td>
            <td><input type="text" name="content" value="<?php echo $row['content']; ?>"  required></td>
        </tr>
        <tr>
            <td><label>Entry Date</label></td>
            <td><input type="date" name="date" value="<?php echo date('Y-m-d', strtotime($row['entry_date'])); ?>" required></td>
        </tr>
        <tr>
            <td><button type="submit" name="update">Update entry</button></td>
        </tr>
    </table>
</form>
```

5

```php
<?php
if(isset($_POST['update'])){
    $title = $_POST["title"];
    $mood = $_POST["mood"];
    $content = $_POST["content"];
    $entryDate = $_POST["date"];

    $stmt2 = $conn->prepare("UPDATE entries  SET title = ?, mood = ?, content = ?, entry_date = ? WHERE id = ? AND user_id = ?");
    $stmt2->bind_param("ssssii", $title, $mood, $content, $entryDate, $entry_id, $user_id);

    if($stmt2->execute()){
        echo "Entry updated successfully. Redirecting back to Read.php in 2 seconds";
        header("refresh:2;url=read.php");
    }else{
        echo "Error updating entry" . $stmt2->error();

    }
}
?>
```

DELETE

```php
$user_id = $_SESSION['user_id'];
$entry_id = $_GET['id'];
$stmt = $conn->prepare("DELETE FROM entries WHERE user_id = ? AND id = ?");
$stmt->bind_param("ii", $user_id, $entry_id);

if($stmt->execute()){
    echo "Entry deleted successfully. Redirecting to read.php";
    header("refresh:2;url=read.php");
}else{
    echo "Error deleting your journal entry" . $stmt->error;
}
```

6

LOGIN

```php
<?php
session_start();
require 'db.php';
$error = '';

if ($_SERVER['REQUEST_METHOD'] === 'POST') {
    $username = mysqli_real_escape_string($conn, trim($_POST['username']));
    $password = $_POST['password'];

    $result = mysqli_query($conn,
        "SELECT id, username, password FROM users WHERE username = '$username'");

    if ($row = mysqli_fetch_assoc($result)) {
        if (password_verify($password, $row['password'])) {
            $_SESSION['user_id']  = $row['id'];
            $_SESSION['username'] = $row['username'];
            header("Location: read.php");
            exit();
        }
    }
    $error = "Invalid username or password.";
}
?>
<!DOCTYPE html>
<html lang="en">
<head>
    <meta charset="UTF-8">
    <title>Login - My Journal</title>
    <link rel="stylesheet" href="style.css">
</head>
<body>
<div class="auth-container">
    <h2>Login</h2>
    <?php if ($error): ?>
        <p class="error">&lt;?= htmlspecialchars($error) ?&gt;</p>
    <?php endif; ?>
    <form method="POST">
        <label>Username</label>
        <input type="text" name="username" required>
        <label>Password</label>
        <input type="password" name="password" required>
        <button type="submit">Login</button>
    </form>
    <p>Don't have an account? <a href="register.php">Sign Up</a></p>
</div>
</body>
</html>
```

LOGOUT

```php
<?php
session_start();
session_destroy();
header("Location: login.php");
exit();
?>
```

7

REGISTER

```php
<?php
session_start();
require 'db.php';
$error = $success = '';

if ($_SERVER['REQUEST_METHOD'] === 'POST') {
    $username = mysqli_real_escape_string($conn, trim($_POST['username']));
    $password = $_POST['password'];

    if (empty($username) || empty($password)) {
        $error = "All fields are required.";
    } else {
        $check = mysqli_query($conn,
            "SELECT id FROM users WHERE username = '$username'");

        if (mysqli_num_rows($check) > 0) {
            $error = "Username already taken.";
        } else {
            $hashed = mysqli_real_escape_string($conn, password_hash($password, PASSWORD_DEFAULT));
            $sql = "INSERT INTO users (username, password) VALUES ('$username', '$hashed')";
            if (mysqli_query($conn, $sql)) {
                $success = "Registration successful! <a href='login.php'>Log in here</a>.";
            } else {
                $error = "Registration failed. Please try again.";
            }
        }
    }
}
?>
```

```html
<!DOCTYPE html>
<html lang="en">
<head>
    <meta charset="UTF-8">
    <title>Register - My Journal</title>
    <link rel="stylesheet" href="style.css">
</head>
<body>
<div class="auth-container">
    <h2>Create Account</h2>
    <?php if ($error): ?>
        <p class="error"><?= htmlspecialchars($error) ?></p>
    <?php endif; ?>
    <?php if ($success): ?>
        <p class="success"><?= $success ?></p>
    <?php endif; ?>
    <form method="POST">
        <label>Username</label>
        <input type="text" name="username" required>
        <label>Password</label>
        <input type="password" name="password" required>
        <button type="submit">Sign Up</button>
    </form>
    <p>Already have an account? <a href="login.php">Login</a></p>
</div>
</body>
</html>
```

STYLING

```
* {/* 1. RESET & BASE: Removes default browser gaps and sets font */
   margin: 0;
   padding: 0;
   box-sizing: border-box; /* Crucial: padding won't increase element width */
   font-family: 'Segoe UI', Tahoma, Geneva, Verdana, sans-serif;
}
body {
   background-color: #f4f7f6;
   padding: 20px;
   color: #333;
}
.navbar {/* 2. NAVBAR: Fixed top or simple horizontal bar */
   background: #2c3e50;
   padding: 15px;
   margin-bottom: 30px;
   border-radius: 8px;
   text-align: center;
}
.navbar span {
   margin: 0 15px;
}
.navbar a {
   color: white;
   text-decoration: none;
   font-weight: bold;
}
.navbar a:hover {
   color: #3498db; /* Visual feedback for the user */
}
h1 {/* 3. THE FORM CONTAINER: Standard layout for centering */
   text-align: center;
   margin-bottom: 20px;
}
form {
   background: white;
   max-width: 500px;
   margin: 0 auto; /* Centers the form horizontally */
   padding: 25px;
   border-radius: 10px;
   box-shadow: 0 4px 6px rgba(0,0,0,0.1); /* Adds depth */
```

```
}

table {/* 1. TABLE STRUCTURE: The foundation */
   width: 100%;
   margin-top: 20px;
   border-collapse: collapse; /* CRITICAL: Merges double borders into single lines */
   background-color: white;
}
th, td {/* 2. HEADERS & CELLS: Alignment and Spacing */
   border: 1px solid #ddd;   /* Adds the grid lines */
   padding: 12px 15px;       /* Adds "breathing room" inside cells */
   text-align: left;         /* Forces headers and content to align left */
}
th {/* 3. HEADER SPECIFICS: Make the top row stand out */
   background-color: #2c3e50;
   color: white;
   font-weight: bold;
   text-transform: uppercase;
   font-size: 13px;
}
tr:nth-child(even) {/* 4. STRIPED ROWS: Improves readability for long lists */
   background-color: #f9f9f9;
}
tr:hover {/* 5. HOVER EFFECT: Helps track which row you are looking at */
   background-color: #f1f1f1;
}
td a {/* 6. LINK STYLING: Fixes the blue 'Edit/Delete' links */
   text-decoration: none;
   color: #3498db;
   font-weight: bold;
   margin-right: 10px;
}
td a:hover {
   text-decoration: underline;
}
label {
   font-weight: 600;
}
/* 5. INPUTS & SELECTS: Make them look modern and uniform */
input[type="text"],
input[type="date"],
select {
```

```
    width: 100%;
    padding: 10px;
    border: 1px solid #ddd;
    border-radius: 5px;
    font-size: 14px;
}

/* Focus state: accessibility and "active" look */
input:focus, select:focus {
    outline: none;
    border-color: #3498db;
    box-shadow: 0 0 5px rgba(52, 152, 219, 0.3);
}

/* 6. BUTTON: Full width and interactive */
button[type="submit"] {
    width: 100%;
    background-color: #27ae60;
    color: white;
    border: none;
    padding: 12px;
    border-radius: 5px;
    cursor: pointer;
    font-size: 16px;
    transition: background 0.3s ease; /* Smooth hover effect */
}

button[type="submit"]:hover {
    background-color: #219150;
}
```