Constrained Application Protocol

(RFC 6690, RFC 7252, RFC 7959, RFC 7641)

The Constrained Application Protocol (CoAP) is a specialized web transfer protocol for use with constrained nodes and constrained (e.g., low-power, lossy) networks.

CoAP Message Format



Ver: Version, T: Type, TKL: Token Length

Message types

į	Type	ļ	Name	
	0 1 2 3		CONfirmable NON-confirmable ACKnowledgement ReSeT	

Method codes

0.00 EMPTY +	Code	Name	į
0.02 POST 0.03 PUT	0.00		į
1 111 1	0.02	POST	

0 1 2 3 4 5 6 7

Response codes

+	+
Code	Description
2.01 (65) 2.02 (66) 2.03 (67) 2.04 (68) 2.05 (69) 2.31 (95) 4.00 (128) 4.01 (129) 4.02 (130) 4.03 (131) 4.04 (132) 4.05 (133) 4.06 (134) 4.08 (134) 4.19 (140) 4.11 (141) 4.15 (141) 4.15 (143) 4.15 (143)	Created Deleted Valid Changed Content Continue Bad Request Unauthorized Bad Option Forbidden Not Found Method Not Allowed Not Acceptable Request Entity Incomplete Precondition Failed Request Entity Too Large Unsupported Content-Format
5.00 (160)	Internal Server Error
5.00 (160) 5.01 (161) 5.02 (162)	Not Implemented Bad Gateway
5.03 (163) 5.04 (164) 5.05 (165)	Service Unavailable Gateway Timeout Proxying Not Supported
+	·+

Options

+	+	+	+	++	+	+	+	++
No.	C	U	N	R	Name	Format	Length	Default
1 1	+ x	+· 	+· 	 x	If-Match	opaque	 0-8	(none)
i 3	ĺх	ĺх	i -	i	Uri-Host	string	1-255	(see note 1)
4	i	i	i	x	ETag	opaque	1-8	(none)
i 5	ĺх	i	i	i	If-None-Match	empty	0	(none)
7	×	×	i -	i	Uri-Port	uint	0-2	(see note 1)
j 8	i	i	i	x	Location-Path	string	0-255	(none)
j 11	İх	x	i -	x	Uri-Path	string	0-255	(none)
j 12	i	i	i	i i	Content-Format	uint	0-2	(none)
j 14	İ	x	i -	i	Max-Age	uint	0-4	60 j
15	×	X	j -	x	Uri-Query	string	0-255	(none)
j 17	İχ	İ	İ	i	Accept	uint	0-2	(none)
20	İ	İ	İ	x	Location-Query	string	0-255	(none)
28	ĺ	ĺ	x		Size2	uint	0-4	(none)
35	×	×	j -	i i	Proxy-Uri	string	1-1034	(none)
39	×	×	-	i i	Proxy-Scheme	string	1-255	(none)
60	ĺ	ĺ	×	i i	Size1	uint	0-4	(none)
+	+	+	+	++	+	+		++

C=Critical, U=Unsafe, N=No-Cache-Key, R=Repeatable

Note 1: taken from destination address/port of request message

Content-Formats

Media type	Id.
text/plain;charset=utf-8	0
application/link-format	40
application/xml	41
application/octet-stream	42
application/exi	47
application/json	50
application/cbor	60

URI schemes

```
coap-URI = "coap:" "//" host [ ":" port ] path-abempty [ "?" query ] coaps-URI = "coaps:" "//" host [ ":" port ] path-abempty [ "?" query ]
```

Transmission parameters

4	
name	default value
ACK_TIMEOUT ACK_RANDOM_FACTOR MAX_RETRANSMIT NSTART DEFAULT_LEISURE PROBING_RATE	2 seconds

Link Format .well-known/core

Link format can be used to describe hosted resources, their attributes, and other relationships between links. Example:

```
REQ: GET /.well-known/core

RES: 2.05 Content

</sensors>;ct=40;title="Sensor Index",
</sensors/temp>;rt="temperature-c";if="sensor",
</sensors/light>;rt="light-lux";if="sensor",
```

ABNF:

```
/ ( "rt" "=" relation-types )
                   / ( "if" "=" relation-types )
/ ( "sz" "=" cardinal )
                   / ( link-extension ) )
link-extension = ( parmname [ "=" ( ptoken / quoted-string ) ] )
/ ( ext-name-star "=" ext-value )
ext-name-star = parmname "*"; reserved for RFC-2231-profiled
                                      ; extensions. Whitespace NOT
                                      ; allowed in between.
                   = 1*ptokenchar
                  = 1*ptoxencnar
= "!" / "#" / "$" / "%" / "&" / "'" / "("
/ ")" / "*" / "+" / "-" / "." / "/" / DIGIT
/ ":" / "?" / "=" / ">" / "?" / "@" / ALPHA
/ "]" / "]" / "/" / "." / "(" / "," | "
ptokenchar
media-type
                   = type-name "/" subtype-name
quoted-mt
                   = DQUOTE media-type DQUOTE
relation-types = relation-type
                   / DQUOTE relation-type *( 1*SP relation-type ) DQUOTE
relation-type = reg-rel-type / ext-rel-type
reg-rel-type = LOALPHA *( LOALPHA / DIGIT / "." / "-" )
ext-rel-type = URI
cardinal
                   = "0" / ( %x31-39 *DIGIT )
LOALPHA = %x61-7A ; a-z
quoted-string = <defined in [RFC2616]>
                   = <defined in [RFC3986]>
URI-Reference = <defined in [RFC3986]>
type-name
                   = <defined in [RFC4288]>
                   = <defined in [RFC4288]>
subtype-name
                   = <defined in [W3C.HTML.4.01]>
MediaDesc
Language-Tag
                   = <defined in [RFC5646]>
ext-value
                   = <defined in [RFC5987]>
                   = <defined in [RFC5987]>
```

Block

In order to transfer larger payloads with CoAP — for instance, for firmware updates — the Block option can be used.

+++++++++++	R Name	Format Length	Default
23 x x -	- Block2	uint	(none)
27 x x -	- Block1		(none)

Observe

In order to follow state changes of CoAP resources the Observe option can be used.

No.	C	UΪ	N	R	Name	Format	Length	Default
6	ĺ	x	-		Observe	uint	0-3 B	(none)

References

This cheatsheet is based on and heavily stole from the following documents:

```
Link-format: http://tools.ietf.org/html/rfc6690
CoAP: http://tools.ietf.org/html/rfc7552
Block: http://tools.ietf.org/html/rfc7959
Observe: http://tools.ietf.org/html/rfc7641
```