# **Constrained Application Protocol**

(RFC 6690, draft-ietf-core-coap-12, draft-ietf-core-block-10, draft-ietf-core-observe-07)

The Constrained Application Protocol (CoAP) is a specialized web transfer protocol for use with constrained nodes and constrained (e.g., low-power, lossy) networks.

### **CoAP Message Format**

							3 5 6 7 8 9 0 1
Ver  T	OC	Ī	Code	1		Message 1	:+-+-+-+-+-+ ID
Option	s (if	any)					.+_+_+_+
Payloa	d (if	any)					.+-+-+-+-+-+

Ver: Version, T: Type, OC: Option Count

## **Method types**

Type	Name	
0   1   2   3	CONfirmable NON-confirmable ACKnowledgement ReSeT	

### **Method codes**

+	Name	İ
1   2   3	PUT	

0 1 2 3 4 5 6 7

+-+-+-+-+-+-+-+

## **Response codes**

+	·
Code	Description
65	2.01 Created
66	2.02 Deleted
j 67 j	2.03 Valid
j 68 j	2.04 Changed
69	2.05 Content
128	4.00 Bad Request
129	4.01 Unauthorized
130	4.02 Bad Option
131	4.03 Forbidden
132	4.04 Not Found
133	4.05 Method Not Allowed
134	4.06 Not Acceptable
140	4.12 Precondition Failed
141	4.13 Request Entity Too Large
143	4.15 Unsupported Content-Format
160	5.00 Internal Server Error
	5.01 Not Implemented
	5.02 Bad Gateway
	5.03 Service Unavailable
	5.04 Gateway Timeout
165	5.05 Proxying Not Supported

### **Options**

	No.	C	   U	+   N	   R	Name	+   Format	Length	Default
-				+			+		+
	1	Х			x	If-Match	opaque	0-8	(none)
	3	X	X			Uri-Host	string	1-255	(see
									below)
	4				x	ETag	opaque	1-8	(none)
	5	X				If-None-Match	empty	0	(none)
	7	X	X			Uri-Port	uint	0-2	(see
									below)
	8				x	Location-Path	string	0-255	(none)
	11	Х	X		x	Uri-Path	string	0-255	(none)
	12					Content-Format	uint	0-2	(none)
	14		X			Max-Age	uint	0-4	60
	15	X	X		x	Uri-Query	string	1-255	(none)
	16				x	Accept	uint	0-2	(none)
	19	X	X			Token	opaque	1-8	(empty)
	20				x	Location-Query	string	0-255	(none)
	35	X	x			Proxy-Uri	string	1-1034	(none)
-				+			+		

C=Critical, U=Unsafe, N=No-Cache-Key, R=Repeatable

#### **Content-Formats**

Media type	Id.
text/plain;charset=utf-8	0
application/link-format	40
application/xml	41
application/octet-stream	42
application/exi	47
application/json	50

#### **URI** schemes

```
coap-URI = "coap:" "//" host [ ":" port ] path-abempty [ "?" query ]
coaps-URI = "coaps:" "//" host [ ":" port ] path-abempty [ "?" query ]
```

## **Transmission parameters**

name	default value
ACK_TIMEOUT ACK_RANDOM_FACTOR MAX_RETRANSMIT NSTART DEFAULT_LEISURE PROBING_RATE	2 seconds   1.5   4   1   5 seconds   1 Byte/second

### Link Format .well-known/core

Link format can be used to describe hosted resources, their attributes, and other relationships between links. Example:

```
/ ( "if" "=" relation-types )
/ ( "sz" "=" cardinal )
                   / ( link-extension ) )
link-extension = ( parmname [ "=" ( ptoken / quoted-string ) ] )
// ( ext-name-star "=" ext-value )
ext-name-star = parmname "*"; reserved for RFC-2231-profiled
                                      ; extensions. Whitespace NOT
                                      ; allowed in between.
                    = 1*ptokenchar
                   = 1*proxenchar
= "!" / "#" / "$" / "%" / "&" / "." / "("
/ ")" / "*" / "+" / "-" / "." / "/" / DIGIT
/ ":" / ";" / "=" / ">" / "?" / "@" / ALPHA
/ "]" / "]" / "," / "," / "," / "," / "," | "," | "," |
ptokenchar
                   = type-name "/" subtype-name
media-type
auoted-mt
                   = DQUOTE media-type DQUOTE
relation-types = relation-type
                   / DQUOTE relation-type *( 1*SP relation-type ) DQUOTE
relation-type
                  = reg-rel-type / ext-rel-type
= LOALPHA *( LOALPHA / DIGIT / "." / "-" )
reg-rel-type
ext-rel-type
                   = URI
                   = "0" / ( %x31-39 *DIGIT )
cardinal
LOALPHA = %x61-7A ; a-z
quoted-string = <defined in [RFC2616]>
                   = <defined in [RFC3986]>
URI-Reference
                    = <defined in [RFC3986]>
                   = <defined in [RFC4288]>
type-name
                   = <defined in [RFC4288]>
MediaDesc
                   = <defined in [W3C.HTML.4.01]>
Language-Tag
                   = <defined in [RFC5646]>
ext-value
                   = <defined in [RFC5987]>
                    = <defined in [RFC5987]>
parmname
```

#### **Block**

In order to transfer larger payloads with CoAP — for instance, for firmware updates — the Block option can be used.

+++++   No.	Name	Format	Length	Default
23   x   x	Block2   Block1   Size	uint   uint   uint   uint	0-3 B   0-3 B   0-4 B	(none) (none) (none)

### Observe

0 1 2 3 4 5 6 7

In order to follow state changes of CoAP resources the Observe option can be used.

İ	No.	C	U	N	R	Name	Format	Length	Default	İ
Ì	6	i	х	x	Ī	Observe	empty/uint	0 B/0-3 B	(none)	ĺ

### References

This cheatsheet is based on and heavily stole from the following documents:

```
Link-format: http://tools.ietf.org/html/rfc6690
CoAP.http://tools.ietf.org/html/draft-ietf-core-coap-12
Block: http://tools.ietf.org/html/draft-ietf-core-block-10
Observe: http://tools.ietf.org/html/draft-ietf-core-observe-07
```