

IP7361

Network Bullet Camera

Outdoor • 2-megapixel • Day&Night



VIVOTEK IP7361 is a high-end 2-megapixel network bullet camera for outdoor surveillance. With high resolution and a combination of outdoor-specific features such as concealed wiring to prevent tampering, the IP7361 is the camera of choice for applications such as parking lots, gas stations, and building entrances.

The IP7361 boasts high-definition 2-megapixel (1600 x 1200) resolution, allowing for the delivery of extremely detailed images and coverage 6 times larger than a VGA camera. To maximize the benefit of the 2-megapixel sensor, the IP7361 employs several innovative technologies for optimized bandwidth efficiency. The ePTZ function enables users to quickly move to a target area for close-up shots without moving the camera physically. Users can also receive only the portions of the images they are interested in via the cropping function. Furthermore, multiple video streams can be delivered simultaneously in different resolutions, frame rates, and image qualities for viewing on different platforms so as to meet different needs or bandwidth constraints. The IP7361 also offers activity adaptive streaming support that dynamically allocates bandwidth according to the video content and trigger state.

Aimed at outdoor surveillance, the IP7361 features auto-iris capability to protect the lens from damage induced by direct sunlight. To adapt to light changes throughout the day, the camera is furnished with a removable IR-cut filter and IR illuminators for superior image quality around the clock. The IP7361 also comes with an IP66-rated housing that offers protection against rain and dust to ensure functional operation in all types of weather conditions. For easy management and protection against tempering and vandalism, the IP7361 is also equipped with a mounting bracket that conceals all cables within the bracket.

With other advanced features such as tamper detection, 802.3af compliant PoE, SD/SDHC card on-board storage, and two-way audio via SIP protocol, the IP7361 is a full-fledged surveillance solution for outdoor environments

Features

- > 2-megapixel CMOS Sensor
- > 3 ~ 9 mm Vari-focal, Auto-iris Lens
- > Removable IR-cut Filter for Day & Night Function
- > Built-in IR Illuminators, effective up to 25 Meters
- > Real-time MPEG-4 and MJPEG Compression (Dual Codec)
- > Multiple Streams Simultaneously
- > ePTZ for Data Efficiency
- > Activity Adaptive Streaming for Dynamic Frame Rate Control
- > Weather-proof IP66-rated Housing
- > Built-in 802.3af Compliant PoE
- > Two-way Audio via SIP Protocol
- > Built-in SD/SDHC Card Slot for On-board Storage
- > Digital I/O for External Sensor and Alarm

System	<ul style="list-style-type: none"> CPU: Mozart 120 SoC Flash: 16MB RAM: 128MB + 128MB Embedded OS: Linux 2.6 	Weight	<ul style="list-style-type: none"> TBD
Lens	<ul style="list-style-type: none"> Board lens, vari-focal, f = 3 ~ 9 mm, F1.2 (wide), F2.1 (tele), auto-iris Removable IR-cut filter for day & night function 	LED Indicator	<ul style="list-style-type: none"> System restore status indicator
Angle of View	<ul style="list-style-type: none"> 31.7° ~ 93.0° (horizontal) 23.8° ~ 68.4° (vertical) 	Power	<ul style="list-style-type: none"> 12V DC 24V AC Power consumption: TBD 802.3af compliant Power-over-Ethernet
Shutter Time	<ul style="list-style-type: none"> 1/5 sec. to 1/40,000 sec. 	Housing	<ul style="list-style-type: none"> Weather-proof IP66-rated housing
Image Sensor	<ul style="list-style-type: none"> 1/3.2" CMOS sensor in 1600x1200 resolution 	Approvals	<ul style="list-style-type: none"> CE, LVD, FCC, VCCI, C-Tick
Minimum Illumination	<ul style="list-style-type: none"> TBD 0 Lux / F1.2 (IR LED on) 	Operating Environments	<ul style="list-style-type: none"> Temperature: -20 ~ 60 °C (-4 ~ 140 °F) Humidity: 90% RH
IR Illuminators	<ul style="list-style-type: none"> Built-in IR illuminators, effective up to 25 meters 	Viewing System Requirements	<ul style="list-style-type: none"> OS: Microsoft Windows 2000/XP/Vista Browser: Mozilla Firefox, Internet Explorer 6.x or above Cell phone: 3GPP player Real Player: 10.5 or above Quick Time: 6.5 or above
Video	<ul style="list-style-type: none"> Compression: MJPEG & MPEG-4 Streaming: <ul style="list-style-type: none"> Simultaneous multiple streams MPEG-4 streaming over UDP, TCP, HTTP or HTTPS MPEG-4 multicast streaming MJPEG streaming over HTTP or HTTPS Supports activity adaptive streaming for dynamic frame rate control Supports video cropping for bandwidth saving Supports ePTZ for data efficiency Supports 3GPP mobile surveillance Frame rates: <ul style="list-style-type: none"> MPEG-4: up to 30 fps at 800x600 up to 10 fps at 1600x1200 MJPEG: up to 30 fps at 800x600 up to 15 fps at 1600x1200 	Installation, Management, and Maintenance	<ul style="list-style-type: none"> Mounting bracket w/ cable concealment RS-485 interface for scanners, pan/tilts Installation Wizard 2 32-CH ST7501 central management software Supports firmware upgrade
Image Settings	<ul style="list-style-type: none"> Adjustable image size, quality, and bit rate Time stamp and text caption overlay Flip & mirror Configurable brightness, contrast, saturation, sharpness, white balance and exposure AGC, AWB, AES Automatic, manual, or scheduled day/night mode BLC (Backlight Compensation) Supports privacy masks 	Applications	<ul style="list-style-type: none"> SDK available for application development and system integration
Audio	<ul style="list-style-type: none"> Compression: <ul style="list-style-type: none"> GSM-AMR speech encoding, bit rate: 4.75 kbps to 12.2 kbps MPEG-4 AAC audio encoding, bit rate: 16 kbps to 128 kbps Interface: <ul style="list-style-type: none"> External microphone input Audio output Supports two-way audio via SIP protocol Supports audio mute 	Warranty	<ul style="list-style-type: none"> 24 months
Networking	<ul style="list-style-type: none"> 10/100 Mbps Ethernet, RJ-45 Protocols: IPv4, IPv6, TCP/IP, HTTP, HTTPS, UPnP, RTSP/RTP/RTCP, IGMP, SMTP, FTP, DHCP, NTP, DNS, DDNS, PPPoE, CoS, QoS, SNMP and 802.1X 		
Alarm and Event Management	<ul style="list-style-type: none"> Triple-window video motion detection Tamper detection One D/I and one D/O for external sensor and alarm Event notification using HTTP, SMTP or FTP Local recording of MP4 file 		
On-board Storage	<ul style="list-style-type: none"> SD/SDHC card slot Stores snapshots and video clips 		
Security	<ul style="list-style-type: none"> Multi-level user access with password protection IP address filtering HTTPS encrypted data transmission 802.1X port-based authentication for network protection 		
Users	<ul style="list-style-type: none"> Live viewing for up to 10 clients 		
Dimension	<ul style="list-style-type: none"> TBD 		

All specifications are subject to change without notice. Copyright©2009 VIVOTEK INC. All rights reserved.

Distributed by: