# MQTT Version 6.0 — Industrial Stream & Advanced Queuing Extension

Draft Proposal — March 2026

*Bill Sommers, AI Solutions Lead, HiveMQ, Inc.*


- Executive Summary: MQTT Version 6.0
  - What Is This?
  - The Problem
  - The Solution
    - 1. 32-bit Stream Sequence Numbers
    - 2. Stream Epoch
    - 3. Named Durable Queues ( `$queue/` namespace)
    - 4. Pull-Based Flow Control (FETCH)
    - 5. Single-Queue Multi-Consumer (SQMC) Semantics
  - Business Impact
  - Compatibility Strategy
  - Implementation Path for HiveMQ
  - Recommendation
- Why MQTT v6.0? Motivation, Rationale, and Intended Audience
  - 0. Important Context: What This Proposal Is Not
  - 1. Who This Is For
    - Primary Use Cases
    - Primary Audience
    - Who Should Stay on MQTT v5.0
  - 2. The Problem Statement: What MQTT v5.0 Cannot Do
    - 2.1 No Durable, Session-Independent Queues
    - 2.2 No Message Ordering Guarantee Across Sessions
    - 2.3 No Pull-Based Flow Control
    - 2.4 No Cluster-Aware Sequence Numbers
    - 2.5 Shared Subscriptions Have Loose Delivery Semantics
  - 3. Why Not Use Kafka or AMQP?
    - At the Edge (Sensors, RTUs, PLCs, Smart Meters)
    - At the Broker Tier (The Gap MQTT v6.0 Fills)
  - 4. Design Principles
    - Principle 1: The Protocol Must Survive Broker Restarts

- Principle 2: Consumers Control Their Own Rate
- Principle 3: Sequence Numbers Are a First-Class Protocol Citizen
- Principle 4: Cluster Failover Must Be Transparent to Well-Behaved Clients
- Principle 5: Backward Compatibility Is a Non-Negotiable Constraint
- 5. Expected Benefits
  - For Industrial Operators
  - For Platform Engineers
  - For the MQTT Ecosystem
- 6. Explicit Non-Goals
- 7. Relationship to the MQTT v5.0 Specification
  - Compatibility Boundaries

MQTT v6.0 — Addressing Criticisms and Defending the Proposal
- A Note on Where This Comes From
  - Why Standardize Now — Not “Ship an Extension First”
- What This Proposal Is Not
- “MQTT v5.0 Already Does This” — Point-by-Point
  - Section 2.1: “That’s a Shared Subscription”
  - Section 2.2: Packet Identifiers and Message Ordering
  - Section 2.3: “Receive Maximum Already Provides Flow Control”
  - Section 2.4: “Cluster-Aware Sequence Numbers” — On the Epoch
  - Section 2.5: Shared Subscription Semantics — Exclusive Consumer / Hot Standby
- “This Should Be Handled at the Application Level”
  - What I Have Seen in Customer Deployments
  - The Historical Precedent
- “Do You Think MQTT Should Be a Message Queue?”
  - My Direct Answer
  - Why Not Kafka (The Answer That Never Changes)
- “Too Much HOW, Not Enough WHAT and WHY”
- Summary of Responses
- References

MQTT Version 6.0
- Industrial Stream and Advanced Queuing Extension
- 1. Introduction
  - 1.1 Conformance
  - 1.2 Terminology
  - 1.3 Normative References
  - 1.4 Data Representation
- 2. MQTT Control Packet Format
  - 2.1 Fixed Header
  - 2.2 Variable Header Properties
- 3. MQTT Control Packets
  - 3.1 CONNECT – Connection Request
  - 3.2 CONNACK – Connect Acknowledgement

- 3.3 PUBLISH – Publish Message
- 3.4 SUBSCRIBE – Subscribe Request
- 3.5 FETCH – Pull Request (Type 16) [NEW]
- 4. Operational Behavior
  - 4.1 The `$queue/` Namespace
  - 4.2 Pull-Based Flow Control
  - 4.3 Cluster Consistency (Shared-Nothing Architecture)
  - 4.4 Single-Queue Multi-Consumer (SQMC)
- 5. Summary of Changes: v5.0 vs. v6.0
- 6. Compatibility Layer
  - 6.1 Negotiation
  - 6.2 Feature Mapping (Native → Compat)
  - 6.3 Broker Requirements for Compat Mode
- 7. Security
- Annex A: SECS/GEM Mapping
  - A.1 Critical Scenario: Process Start Command (S2F21)
- Annex B: New Reason Codes

Alternative Approaches to MQTT v6.0

- 1. The Core Design Choice: Breaking vs. Non-Breaking
- 2. Alternative A: Pure MQTT v5.0 Extension (Property-Based Shim)
  - Description
  - Implementation
  - Pros
  - Cons
  - The Fragmentation Risk
  - Verdict
- 3. Alternative B: MQTT v5.0 with Reserved Property IDs (0x30–0x45)
  - Description
  - Implementation
  - Pros
  - Cons
  - Verdict
- 4. Alternative C: Native v6.0 with New Packet Type (Chosen Approach)
  - Description
  - Implementation
  - Pros
  - Cons
  - Verdict
- 5. Alternative D: Replace MQTT Entirely (Kafka / AMQP 1.0 / NATS JetStream)
  - Description
  - Comparison
  - Analysis
  - Verdict

- 6. Alternative E: Extend MQTT Shared Subscriptions (v5.0 `$share/`)
  - Description
  - Pros
  - Cons
  - Why `$share/` Is Not a Durable Queue
  - Verdict
- 7. Design Decision Matrix

Critical Perspectives, Rebuttals & Technical Pitfalls
- Part 1: Standards Committee & Architecture Critique
  - Criticism 1: “MQTT’s success is its simplicity. v6.0 turns it into a bloated Kafka clone.”
  - Criticism 2: “The `$queue/` namespace breaks topic hierarchy semantics.”
  - Criticism 3: “The FETCH packet (Type 16) is a hard break that undermines the whole ‘compatible’ story.”
- Part 2: Software Engineering & Performance Critique
  - Criticism 4: “The original proposal’s Leader Node model contradicts HiveMQ’s masterless architecture.”
  - Criticism 5: “Replication lag will cause data loss in the replication gap window.”
  - Criticism 6: “Persistent queues on the broker will cause storage bloat and operational nightmares.”
- Part 3: SRE & Operational Critique
  - Criticism 7: “The FETCH mechanism adds latency compared to push delivery.”
  - Criticism 8: “Custom property IDs in the reserved range could conflict with future OASIS standardization.”
- Technical Pitfalls
  - Pitfall 1: Sequence Wraparound at 2^32
  - Pitfall 2: Idempotency Table Growth
  - Pitfall 3: Competing Consumer Fairness
  - Pitfall 4: Epoch Reset as a DoS Vector
  - Pitfall 5: Virtual FETCH Overhead (Compat Mode)
  - Pitfall 6: `$queue/` Namespace Collision with Existing Topics
- Summary: Risk Matrix

Critical Analyses of MQTT v6.0
- Part 1 — Security Analyst Perspective
  - 1.1 Executive Verdict
  - 1.2 Threat Model Gaps
  - 1.3 Missing Security Primitives
  - 1.4 Positive Security Properties
- Part 2 — OT SRE Perspective
  - 2.1 Executive Verdict
  - 2.2 Operational Concerns
  - 2.3 Deployment Readiness Assessment
  - 2.4 What OT SREs Actually Need
- Part 3 — Arlen Nipper Perspective
  - 3.1 Opening Statement
  - 3.2 The Core Argument: Protocol Creep Destroys Interoperability
  - 3.3 The Right Tool Exists

- 3.4 The MQTT Gateway Pattern Is the Correct Architecture
- 3.5 The Constrained Device Problem
- 3.6 A Constructive Alternative
- Summary Comparison

MQTT v6.0 Performance Analysis: High-Volume Use Cases

1. Workload Profile
2. Performance Bottlenecks in the Current Proposal
   - 2.1 CAS Counter Contention at Scale
   - 2.2 High-Watermark Inadequacy Under Burst
   - 2.3 Quorum Write Latency vs. Real-Time Telemetry
   - 2.4 FETCH Batch Size Tuning for Burst Recovery
   - 2.5 Rate Limiting Granularity
   - 2.6 Epoch Reset Thundering Herd
3. Updated Property Table
4. Namespace Additions
5. Summary: Adaptations for DEP Scale

MQTT v6.0 Architecture Diagrams

1. System Context (C4)
2. Container View: HiveMQ v6.0 (C4)
3. Feature Layers
4. New v6.0 Properties

MQTT v6.0 Packet Flow Diagrams

1. Connection Negotiation
2. Publish → Sequence Assignment (masterless)
3. Native FETCH (Protocol Level 6)
4. Virtual FETCH (Compat Mode)
5. Competing Consumer — Failover
6. Exclusive Consumer — Hot-Standby
7. Gap Detection + Exactly-Once
8. Epoch Reset on Cluster Failover

Cluster Failover & Epoch Management Diagrams

1. Masterless Cluster — Any Node Sequences Any Publish (C4)
2. Sequence Assignment — Distributed Counter
3. Node Crash — No Election Required
4. Partition Event — When Epoch Increments
5. Failure Outcomes Decision Tree
6. Client Reconnect Decision Tree
7. Tiered Storage
8. Epoch Timeline

# Executive Summary: MQTT Version 6.0

## What Is This?

**MQTT v6.0** is a proposed evolutionary extension to the MQTT v5.0 protocol that adds **targeted industrial queuing primitives** to the broker tier — without changing the edge protocol that millions of devices already run.

It is **not** a general-purpose upgrade. It is **not** "MQTT trying to become Kafka." It targets a specific tier of deployment: **semiconductor manufacturing (SECS/GEM), energy grid SCADA (IEC 61850), and large-scale industrial IoT** — environments where MQTT v5.0 is already deployed at the edge but operators are forced to bolt on Kafka or AMQP at the broker tier to get durable queuing, ordered delivery, and consumer group semantics. v6.0 eliminates that bridge.

**Why standardize now rather than ship vendor extensions first?** Because the extension-first path leads to fragmentation — just as `$SYS/` was implemented differently by every broker and remains unstandardized 15 years later. Standardizing these patterns at the protocol level before vendors fragment gives the ecosystem a single interoperable wire representation. See Why Standardize Now for the full argument.

For a detailed response to criticisms including "v5.0 already does this" and "this should be application-level," see Addressing Criticisms.

---

## The Problem

MQTT v5.0 is excellent for lightweight telemetry and command delivery. However, it has structural limitations that force enterprise users to embed reliability logic inside application payloads — a pattern already codified by Eclipse Sparkplug B with its application-layer sequence numbers, and replicated ad-hoc by every industrial MQTT deployment that needs message ordering guarantees:

- **No global message ordering.** The 16-bit Packet Identifier is per-session, transient, and recycled — making it impossible for a consumer to detect gaps caused by broker restarts or cluster failovers.
- **Push-only delivery.** The broker pushes all messages to consumers as fast as they arrive. A slow consumer cannot apply backpressure without complex out-of-band coordination.
- **Session-bound queues.** Messages are only held for a client while its session exists. There is no way to create a durable queue that outlives client connections.
- **Loose shared subscription semantics.** MQTT's `$share/` mechanism provides load balancing but lacks strict exclusive-consumer and message-locking semantics needed for transactional processing.
- **No cluster-aware consistency.** When a HiveMQ node fails and a client reconnects to a new node, the protocol has no mechanism to detect what was lost or resume from an exact point.

These gaps are currently “solved” by embedding sequence numbers, idempotency keys, and acknowledgment logic in message payloads — a non-standard, non-interoperable approach.

---

## The Solution

MQTT v6.0 introduces five targeted additions to the protocol, all backward-compatible with existing v5.0 parsers:

### 1. 32-bit Stream Sequence Numbers

A new Property ( `0x30` ) carrying a monotonic, cluster-wide 32-bit integer is attached to every message in the `$queue/` namespace. This allows consumers to detect gaps ( `received Seq 1002 but expected 1001` ), perform deduplication, and implement application-level exactly-once processing without embedding logic in payloads.

### 2. Stream Epoch

A new Property ( `0x35` ) that tracks the “era” of a queue. When a HiveMQ cluster suffers a catastrophic failure and cannot guarantee sequence continuity, the Epoch is incremented. Consumers that detect an Epoch change know they must discard local idempotency state and re-synchronize — analogous to a SECS/GEM Establish Communications (S1F13) reset.

### 3. Named Durable Queues ( `$queue/` namespace)

Topics prefixed with `$queue/` are treated as first-class queue entities: persisted to non-volatile storage, sequenced, and retained indefinitely until consumed or expired — independent of any client session. This replaces the implicit, session-bound queue model of v5.0.

### 4. Pull-Based Flow Control (FETCH)

A new `FETCH` Control Packet (Type 16) lets consumers explicitly request batches of messages from the broker. The broker holds messages in the persistent queue and releases them only when asked. This eliminates the “thundering herd” problem where a recovering consumer is flooded with backlogged messages. For v5.0-compat environments, a Virtual FETCH mechanism uses a `$SYS/` control topic instead.

### 5. Single-Queue Multi-Consumer (SQMC) Semantics

An extension to `SUBSCRIBE` that adds two new consumer modes beyond the loose `$share/` model: - **Competing:** Messages are distributed to exactly one consumer via round-robin, with strict message locking and immediate failover if the consumer disconnects before acknowledging. - **Exclusive:** One designated consumer receives all messages; others are hot standbys that take over instantly on failure, preserving strict ordering.

## Business Impact

| Use Case | v5.0 Risk | v6.0 Benefit |
|---|---|---|
| Semiconductor FAB (SECS/GEM) | Broker restart can silently lose a “Process Start” (S2F21) command, ruining a wafer | Epoch resync + sequence gaps ensure the command is detected as lost and retried |
| Industrial FDC Data Collection | High-frequency sensor data floods the host system, causing crashes | FETCH-based backpressure keeps the broker as the buffer; host processes at its own rate |
| Financial Message Bus | Duplicate processing of payment events due to lack of idempotency primitives | 32-bit Sequence as an idempotency key, checked before executing business logic |
| Multi-node HiveMQ Cluster | Client failover to a new node silently re-delivers or loses messages | Last Received Seq in CONNECT allows new node to resume delivery from exact position |
| High-availability IoT Gateways | Primary/backup consumer logic must be hand-coded in application layer | Exclusive consumer mode with automatic hot-standby failover built into the protocol |

---

## Compatibility Strategy

MQTT v6.0 is backward-compatible with MQTT v5.0 for all unchanged v5.0 use cases: existing packet types, properties, topics, and semantics continue to work as before. A v5.0 or v3.1.1 client connecting to a v6.0 broker for standard pub/sub sees no difference in behavior.

Compatibility is not wire-transparent for v6.0-only features (FETCH, `$queue/`, Stream Sequence properties, `last-seq` / `epoch`); those require either Protocol Level 6 or the specified v5.0 compatibility mode. Specifically:

- All new properties use IDs in the reserved range ( `0x30–0x45` ) that v5.0 brokers and clients are required to ignore — no harm to v5.0 peers.
- The `$queue/` namespace is ACL-protected; v5.0 clients that have not completed the v6.0 handshake are rejected.
- A **Compatibility Layer** maps every native v6.0 feature to v5.0 User Properties and system topics, enabling mixed-version deployments.

- A negotiation handshake (`mqtt-ext: v6.0` in CONNECT/CONNACK) allows clients and brokers to detect v6.0 support and fall back gracefully.

**The key guarantee:** if you do not use `$queue/`, FETCH, or Stream Sequence properties, your deployment is fully compatible with v5.0 — no behavioral changes, no additional overhead, no migration required. See Compatibility Boundaries for the full scenario matrix.

---

## Implementation Path for HiveMQ

The broker-side implementation uses the HiveMQ Extension SDK:

| Feature | HiveMQ API |
|---|---|
| Sequence injection | `PublishInboundInterceptor` |
| Client throttling | `ClientService.blockClient()` / `unblockClient()` |
| Queue persistence | `ManagedPersistenceService` |
| Cluster epoch management | `ClusterService` + consistent hashing on queue names |

A proof-of-concept can be built today using a HiveMQ Extension alongside a Python `gmqtt` client shim, without any changes to the core broker binary.

---

## Recommendation

Adopt MQTT v6.0 as a **two-phase rollout**:

1. **Phase 1 — Compatible Extension:** Deploy the HiveMQ Extension Plugin that intercepts `v6-*` user properties. Migrate clients to the Python/Java shim. Zero broker downtime required.
2. **Phase 2 — Native v6.0:** Once the ecosystem supports Protocol Level 6, deprecate the shim layer and use native FETCH packets with full binary efficiency.

This proposal is production-ready as a HiveMQ extension today and provides a clear path to a formal OASIS standardization submission.

# Why MQTT v6.0? Motivation, Rationale, and Intended Audience

> **Status:** Part of the MQTT v6.0 Draft Proposal — March 2026

---

## 0. Important Context: What This Proposal Is Not

**This is not "MQTT trying to become Kafka."** This is not a general-purpose upgrade. Most MQTT deployments do not need v6.0 and should remain on v5.0.

This proposal targets a specific problem: **industrial operators who already use MQTT at the edge but are forced to bolt on Kafka, AMQP, or Redis at the broker tier** to get durable queuing and ordered delivery. The edge devices cannot change — they run constrained firmware with MQTT baked in. The bridge architecture (MQTT → Kafka → Consumer) adds operational cost, a second failure domain, and a second protocol stack. v6.0 eliminates the bridge by extending the MQTT broker with the specific queuing primitives these operators need, without changing the edge protocol.

Every feature in v6.0 is already being implemented at the application layer by industrial MQTT users — sequence numbers in payloads, idempotency tables in databases, consumer group coordination in custom code. Eclipse Sparkplug B is the most prominent example: it defines application-layer sequencing on top of MQTT precisely because MQTT v5.0 does not provide these primitives natively. v6.0 proposes to move these proven patterns from the payload into the protocol where brokers can optimize for them and client libraries can handle them automatically.

**Why not ship these as vendor extensions first?** Because the extension-first path leads to fragmentation, not standardization. If HiveMQ ships `$queue/` as a proprietary extension, EMQX, Mosquitto, and AWS IoT Core will build incompatible versions — just as every broker implemented `$SYS/` differently, creating a mess that remains unstandardized 15 years later. HiveMQ's own Declared Shared Subscriptions — a proprietary workaround for the durable queue gap in `$share/` — is proof that extension-driven solutions do not converge on interoperability. Standardizing early, before fragmentation, is cheaper than standardizing late.

For a detailed response to specific criticisms (including "this is Kafka," "v5.0 already does shared subscriptions," and "this should be application-level"), see Addressing Criticisms — Point-by-Point Rebuttals.

---

# 1. Who This Is For

MQTT v6.0 is targeted at a specific tier of industrial and enterprise IoT deployments that have **outgrown what MQTT v5.0 was designed to provide**. It is not a general-purpose upgrade for all MQTT users.

## Primary Use Cases

**Semiconductor Manufacturing (SECS/GEM):** Semiconductor fabs run the SEMI E30 (GEM) protocol for equipment communication. A lost `S2F21` (Remote Process Start) command can ruin a wafer worth $10K–$50K. Today, fabs using MQTT must embed sequence numbers and idempotency keys in application payloads because MQTT v5.0 has no protocol-level mechanism to detect a gap caused by a broker restart. Every equipment vendor implements this differently.

**Energy and Grid SCADA (IEC 61850):** Distributed energy providers operate millions of smart meters, PMUs, RTUs, and substation gateways. MQTT is increasingly used as the edge transport for IEC 61850 telemetry, but downstream data pipelines require ordered, durable queues with 90-day regulatory retention. Today this means an MQTT-to-Kafka bridge — a second system, a second failure domain, a second team.

## Primary Audience

| Audience | Why They Need v6.0 |
|---|---|
| **Large-scale industrial operators** — energy utilities, grid SCADA, semiconductor fabs, process manufacturing | Need ordered, durable message queues that survive broker restarts and client disconnections; need competing consumer patterns for high-availability pipelines |
| **IIoT platform engineers** | Building middleware that must guarantee message delivery ordering across distributed broker clusters without application-layer workarounds |
| **Data pipeline architects** | Connecting MQTT edge data to downstream analytics, historians, and SCADA systems; need pull-based flow control so consumers can dictate their own ingestion rate |
| **HiveMQ extension developers** | Implementing advanced queuing semantics today via custom extensions; v6.0 standardises and formalises these patterns |
| **MQTT broker implementers** | Seeking a standardised wire protocol for durable queuing so customers are not locked into proprietary extension APIs |

### Who Should Stay on MQTT v5.0

MQTT v6.0 is designed as a strict superset of MQTT v5.0: existing publish-subscribe use cases continue to work unchanged, while deployments that require durable queues and ordered replay can opt into the new capabilities. If your deployment matches any of the following profiles, v5.0 is the right choice and v6.0 adds complexity without benefit:

- Simple telemetry from sensors to a single backend consumer
- Devices with less than 256 KB available memory
- Short message lifetimes where loss is acceptable (dashboards, live monitoring)
- No requirement for competing consumers or consumer group semantics
- Broker infrastructure managed by a single operator with no cluster failover requirements

These deployments can connect to a v6.0 broker without modification — the broker serves v5.0 and v3.1.1 clients identically to a v5.0 broker. The v6.0 extensions are only activated when a client explicitly opts in via the v6.0 handshake.

---

## 2. The Problem Statement: What MQTT v5.0 Cannot Do

MQTT v5.0 is a well-designed protocol for lightweight publish-subscribe messaging. It was not designed to be a message queue. Five specific limitations emerge at scale in industrial deployments:

### 2.1 No Durable, Session-Independent Queues

MQTT v5.0 sessions are bound to a client identifier and a broker node. When a client disconnects: - Clean session (`cleanStart=true`): all queued messages are discarded - Persistent session (`cleanStart=false`): messages are held *for that specific client*, not for a named consumer group

**The result:** If a downstream analytics pipeline (one of ten competing consumers) disconnects for maintenance, its share of the message backlog is either lost or held indefinitely in a single-consumer session — neither behaviour is correct for an industrial pipeline.

**What operators do today:** They build application-layer queuing on top of MQTT using Redis, Kafka, or proprietary HiveMQ extensions. The MQTT broker becomes a thin transport layer and the real queuing logic lives outside the protocol. This defeats the purpose of using a standardised protocol.

### 2.2 No Message Ordering Guarantee Across Sessions

MQTT v5.0 includes a Packet Identifier, but it is not a message sequence number. It exists only for QoS delivery handshakes, is scoped to a single client session, is reused after acknowledgement, and resets when the session reconnects. It therefore cannot be used to determine message ordering or detect gaps across sessions.

MQTT v6.0 introduces a broker-assigned, monotonic sequence number (Property `0x30`) that identifies the message itself rather than the delivery attempt.

MQTT v5.0 uses a 16-bit Packet Identifier that resets per session. Messages across sessions cannot be ordered. If a consumer reconnects mid-stream, it cannot determine which messages it has already processed and which it has not — not without an application-layer sequence number that the publisher must attach manually.

**The result:** Exactly-once processing at the application layer requires every publisher and consumer pair to implement bespoke deduplication logic. In a system with 50 publishers and 20 consumers, this is 1,000 pairwise agreements — none of them standardised.

**What "1,000 pairwise agreements" means in practice:**

When sequence numbers live in the payload rather than the protocol, every publisher and every consumer must agree on the payload format — and that agreement must happen pair by pair. Consider a semiconductor fab with 50 tools (publishers) sending messages to 20 downstream systems (consumers) — historians, MES, FDC analyzers, dashboards:

- Tool A sends `{"seq": 123, "data": ...}` (JSON, field name `seq`)
- Tool B sends a Sparkplug protobuf with a `sequence_number` field
- Tool C uses a custom binary header with bytes 0–3 as a big-endian sequence counter

Every consumer that wants to do deduplication or gap detection on messages from Tool A needs to know Tool A's format. And Tool B's format. And Tool C's format. Each publisher-consumer pair is a "pairwise agreement" about how to find the sequence number in the payload.

50 publishers × 20 consumers = 1,000 pairs that each need to agree on a schema. In practice, teams reduce this by picking a common format — but that common format is itself non-standard. It is a company-internal convention, not a protocol guarantee. Different companies, different vendors, and different integrations all pick different conventions. The result is that interoperability between organizations requires yet another translation layer.

**The v6.0 fix:** The broker assigns the sequence number as a protocol property (`0x30`). Every publisher's message gets a sequence number automatically — the publisher does not even need to be aware of it. Every consumer reads it from the same property, regardless of payload format. The 1,000 pairwise agreements collapse to zero. The protocol is the agreement.

Put simply: **when reliability metadata is in the payload, everyone has to agree on the payload format. When it is in the protocol, the protocol is the agreement.**

**But Wait — Doesn't MQTT 5.0 Already Have a Sequence Number?**

MQTT v5.0 does include a Packet Identifier, but it is not a message sequence number in the sense required for ordering or replay.

The Packet Identifier: - Is 16-bit and wraps frequently - Exists only for QoS handshake state, not for message identity - Is scoped to a single client session - Is reused once the QoS exchange completes - Resets on reconnect

Because of these properties, the Packet Identifier cannot be used to determine message ordering across sessions or after reconnect. If a consumer disconnects and reconnects, the next message may reuse an earlier Packet Identifier, making it impossible to determine whether the message is new, duplicated, or missing.

In other words, **the Packet Identifier tracks delivery acknowledgement state, not message position in a stream.**

This is why industrial deployments that require ordering or deduplication add their own application-layer sequence numbers in the payload. Sparkplug B, for example, defines its own `seq` field precisely because MQTT provides no protocol-level sequence for messages.

MQTT v6.0 introduces a true message sequence number: - **Broker-assigned** — publishers do not need to maintain counters - **Cluster-wide** — valid across all nodes, not scoped to a single connection - **Monotonic** — always increasing within a queue's lifetime - **Immutable once assigned** — the sequence number is permanent - **Stable across client sessions** — persists through disconnections and reconnections

This sequence number (Property `0x30`) identifies **the message itself**, not the delivery attempt.

The distinction is crucial:

| | MQTT v5.0 Packet Identifier | MQTT v6.0 Stream Sequence Number |
|---|---|---|
| **Purpose** | Tracks QoS handshake state | Tracks message position in the stream |
| **Scope** | Per-session | Cluster-wide |
| **Lifecycle** | Reused and reset | Monotonic and immutable |
| **Ordering** | Not usable for ordering | Basis for ordering, deduplication, and replay |

## 2.3 No Pull-Based Flow Control

MQTT v5.0 is push-only. The broker delivers messages to subscribers as fast as they arrive. Consumer-side flow control is limited to: - `Receive Maximum` — caps the in-flight window but does not let the consumer control *when* it receives the next batch - Disconnecting and reconnecting — a destructive and operationally expensive throttle

**The result:** A slow consumer — one doing a database write per message — is flooded. The broker's delivery queue fills the consumer's memory until it crashes. Consumer crashes trigger reconnects, which trigger session resumption, which floods the consumer again. This cycle is well-known in industrial MQTT deployments and is solved today by external rate limiters, message buffers, or complete replacement of the push model with polling.

### 2.4 No Cluster-Aware Sequence Numbers

MQTT v5.0 has no concept of cluster topology. If a client is connected to Node A and Node A fails, the client reconnects to Node B. From the protocol's perspective, this is a new session — there is no way to tell Node B "I had processed up to message X on Node A; please resume from X+1."

**The result:** After any broker failover, consumers must either: - Re-process all messages from the beginning of the session (duplicate processing) - Trust that the application layer tracked its own position (requires external state) - Accept a gap (message loss)

None of these outcomes are acceptable for regulatory data, safety-critical commands, or financial telemetry.

### 2.5 Shared Subscriptions Have Loose Delivery Semantics

MQTT v5.0 introduced Shared Subscriptions ( `$share/` ) for competing consumers. However: - There is no guaranteed round-robin; delivery order within a group is implementation-defined - There is no concept of exclusive access (hot-standby primary/backup) - If a consumer in the group disconnects mid-processing, the in-flight message may be re-delivered to any other consumer — but only if the broker's session timeout has not expired

**The result:** Building a reliable competing consumer pipeline on `$share/` requires extensive application-layer coordination that must be re-implemented for each new deployment.

---

## 3. Why Not Use Kafka or AMQP?

This is the most frequently raised objection. The answer depends on **where in the architecture** the problem exists.

### At the Edge (Sensors, RTUs, PLCs, Smart Meters)

Kafka and AMQP are not viable at the edge: - Kafka's minimum client footprint requires a full JVM stack with multi-GB RAM — not compatible with microcontrollers or constrained devices - AMQP 1.0 is a complex framing protocol — correct implementation requires significant expertise and is poorly suited to constrained devices - Kafka requires TCP connections with persistent state; many OT networks have unreliable connectivity and require disconnect-tolerant protocols - MQTT v5.0 is already deployed on hundreds of millions of devices with battle-tested client libraries for C, MicroPython, Java, and Go

**Conclusion:** At the edge, MQTT remains the right protocol. The question is what happens to messages *after* they reach the broker cluster.

### At the Broker Tier (The Gap MQTT v6.0 Fills)

Today, industrial deployments solve the queuing problem with a pattern like this:

```
[Edge device MQTT v5.0] → [MQTT Broker] → [Bridge to Kafka/AMQP] → [Consumer]
```

This architecture requires: - A bridge component that must be deployed, scaled, and maintained - Two separate protocol stacks, two separate failure domains - Message translation overhead at the bridge - Kafka or AMQP client libraries in every downstream consumer

MQTT v6.0 eliminates the bridge by extending the MQTT broker to natively support the queuing semantics that consumers need. The edge devices continue to speak MQTT v5.0 unchanged. The downstream consumers get ordered, pull-based, durable message queues — without a separate message queue system.

```
[Edge device MQTT v5.0] → [HiveMQ v6.0 Broker — native queuing] → [Consumer via FETCH]
```

This is not “MQTT trying to become Kafka.” It is MQTT extending its native durability semantics to the broker tier where the queuing problem actually lives.

---

## 4. Design Principles

MQTT v6.0 is built on five explicit principles, each derived from a lesson learned in large-scale industrial deployments:

### Principle 1: The Protocol Must Survive Broker Restarts

A `$queue/` message that has been published MUST be retained by the broker cluster regardless of individual node failures. The protocol defines what “retained” means (quorum write), when sequence continuity can be guaranteed (same Epoch), and when it cannot (Epoch increment on counter quorum loss).

This is a departure from v5.0’s “retained message” feature, which is per-topic and not queue-semantics aware.

### Principle 2: Consumers Control Their Own Rate

Pull-based FETCH (not push) is the default for `$queue/` consumption. A consumer that is slow, restarting, or catching up a backlog is never flooded. It fetches when it is ready. This is an intentional departure from v5.0’s push-all model — but it applies **only to `$queue/` topics**, not to standard pub/sub.

Push subscriptions remain available for all non-queue topics and for use cases where push semantics are correct (live telemetry monitoring, real-time dashboards). A v6.0 broker serving standard pub/sub traffic behaves identically to a v5.0 broker.

### Principle 3: Sequence Numbers Are a First-Class Protocol Citizen

Every `$queue/` message has a broker-assigned, cluster-wide monotonic sequence number (Property `0x30`). Publishers do not assign sequence numbers — the broker does, atomically, with no routing constraints. Sequence numbers are: - Immutable once assigned - Cluster-wide (not per-session or per-node) - The basis for exactly-once deduplication at the consumer - The basis for gap detection and recovery

### Principle 4: Cluster Failover Must Be Transparent to Well-Behaved Clients

A client that stores its `last-seq` and `epoch` values can reconnect to *any* node in the cluster after any failure and resume processing from exactly where it left off — provided the cluster maintained quorum. If quorum was lost (an Epoch increment event), the protocol signals this explicitly so the client can decide how to recover.

No application-layer failover logic is required. No broker-specific reconnect APIs. The protocol carries all the state the client needs.

### Principle 5: Backward Compatibility Is a Non-Negotiable Constraint

MQTT v6.0 is backward-compatible with MQTT v5.0 for all unchanged v5.0 use cases: existing packet types, properties, topics, and semantics continue to work as before. Specifically:

- A v6.0 broker can serve v5.0 and v3.1.1 clients without modification — these clients see no difference in behavior
- A v5.0 broker can serve v6.0 clients in compatibility mode (via User Properties and Virtual FETCH)
- The migration from v5.0 to v6.0 does not require a flag-day cutover

Compatibility is not wire-transparent for v6.0-only features: FETCH (Type 16), `$queue/` persistence semantics, Stream Sequence properties, and `last-seq` / `epoch` reconnection require either Protocol Level 6 or the specified v5.0 compatibility mode. See §7 Compatibility Boundaries for exact details.

The compatibility layer is specified precisely enough that it can be implemented as a HiveMQ Extension Plugin without modifying the core broker.

---

## 5. Expected Benefits

### For Industrial Operators

| Benefit | Mechanism |
|---|---|
| Message loss eliminated for `$queue/` topics | Quorum write + HWM-based exactly-once |

| Benefit | Mechanism |
|---|---|
| Consumer restart is safe — no re-processing required | `last-seq` + `epoch` in CONNECT; broker resumes from N+1 |
| Slow consumers cannot be flooded | Pull-based FETCH; consumer controls batch size and timing |
| Competing consumers with correct failover | SQMC competing mode: in-flight locks re-dispatched on consumer crash |
| Hot-standby consumer for safety-critical commands | SQMC exclusive mode: single active consumer with automatic promotion |
| Broker failover transparent to clients | Epoch-based resync protocol |

### For Platform Engineers

| Benefit | Mechanism |
|---|---|
| Eliminates MQTT-to-Kafka bridge for queue use cases | Native `$queue/` semantics in the broker |
| Standardised competing consumer semantics | SQMC spec replaces bespoke `$share/` orchestration |
| Sequence numbers enable cross-system correlation | `Seq` + `Epoch` = immutable event identifier for audit, replay, join |
| No external state required for exactly-once | HWM tracked by broker + client; no Redis or database required |

### For the MQTT Ecosystem

| Benefit | Mechanism |
|---|---|
| Clear upgrade path from v5.0 | Compatibility layer; no flag-day migration |
| Standardised semantics reduce broker lock-in | Wire protocol defines queue behaviour, not just transport |
| Opens MQTT to new use cases | Financial telemetry, ERP integration, command-and-control audit trails |

---

# 6. Explicit Non-Goals

MQTT v6.0 explicitly does not aim to:

- Replace Kafka or RabbitMQ for server-to-server batch processing at data centre scale
- Provide full AMQP 1.0 semantics (routing topologies, exchanges, dead-letter queues)
- Support messages larger than the current MQTT maximum (256 MB per PUBLISH)
- Implement stream processing or CEP (complex event processing)
- Define a management API or REST interface for broker administration
- Mandate a specific cluster topology or replication protocol (the spec defines *what* must be guaranteed, not *how*)

---

# 7. Relationship to the MQTT v5.0 Specification

MQTT v6.0 is a **strict superset of MQTT v5.0**: existing publish-subscribe use cases continue to work unchanged, while deployments that require durable queues and ordered replay can opt into the new capabilities. Every feature defined in the OASIS MQTT v5.0 specification remains valid and unchanged. The additions in v6.0 are:

1. **New packet type**: FETCH (Control Packet Type 16) — absent from v5.0
2. **New property identifiers**: `0x30` through `0x35`, `0x41` through `0x42` — reserved ranges not used by v5.0
3. **New topic namespace**: `$queue/` — conventionally reserved (similar to `$SYS/`) but now formally specified
4. **New connection negotiation**: Protocol Level `6` in CONNECT; `mqtt-ext: v6.0` User Property for compat mode
5. **New CONNECT fields**: `last-seq` and `epoch` for stateful reconnection

No existing v5.0 packet types, property identifiers, or semantics are modified or removed.

## Compatibility Boundaries

MQTT v6.0 is backward-compatible with MQTT v5.0 for all unchanged v5.0 use cases. The following table defines exactly when compatibility is guaranteed and when compatibility mode is required:

| Scenario | Compatible? | Notes |
|---|---|---|
| v5.0 client → v6.0 broker, standard pub/sub | **Yes — fully transparent** | Client sees no difference. No v6.0 features activated. |
| v3.1.1 client → v6.0 broker, standard pub/sub | **Yes — fully transparent** | Same as above. |

| Scenario | Compatible? | Notes |
|---|---|---|
| v6.0 client → v6.0 broker, `$queue/` + FETCH | **Yes — native mode** | Protocol Level 6. Full binary efficiency. |
| v6.0 client → v5.0 broker, compatibility mode | **Yes — via compat layer** | Client uses Protocol Level 5 + `mqtt-ext: v6.0` User Property. FETCH tunneled via `$SYS/queues/*/fetch`. Seq/Epoch carried as User Properties. Requires v6.0-aware extension on the v5.0 broker. |
| v6.0 client → v5.0 broker, native FETCH packet | **No — connection rejected** | v5.0 broker rejects Protocol Level 6 with Reason Code `0x84`. Client MUST fall back to compatibility mode. |
| v5.0 client → v6.0 broker, `$queue/` topics | **No — rejected by ACL** | v6.0 broker MUST reject `$queue/` access from clients that have not completed the v6.0 handshake. |
| v6.0 properties on non-queue topics | **Ignored** | v5.0 clients and brokers MUST ignore unknown property IDs per the v5.0 spec. No harm, no benefit. |

**The key guarantee:** If you do not use `$queue/`, FETCH, Stream Sequence, or `last-seq` / `epoch`, your deployment is fully compatible with v5.0 — no behavioral changes, no additional overhead, no migration required. The v6.0 extensions activate only when explicitly opted into.

# MQTT v6.0 — Addressing Criticisms and Defending the Proposal

> **Author:** Bill Sommers, AI Solutions Lead, HiveMQ, Inc. **Context:** Response to internal review feedback from Georg and Simon — March 2026

# A Note on Where This Comes From

Before I get into the point-by-point responses, I want to be clear about what drives this proposal: **two and a half years as a TAM in Customer Success at HiveMQ.**

I have spent that time on calls with customers who are building exactly the systems this proposal targets — semiconductor fabs running SECS/GEM over MQTT, energy providers pushing IEC 61850 telemetry through HiveMQ clusters, automotive OEMs streaming diagnostic data from factory floors. These are not hypothetical use cases. These are customers I have worked with directly, and the pain points in this proposal are patterns I have seen repeated across multiple engagements.

The common thread: **every one of these customers has built the same set of application-layer workarounds on top of MQTT v5.0.** Sequence numbers in payloads. Idempotency tables in Redis. Consumer group coordination in custom microservices. Checkpoint reconciliation jobs that run after every broker restart. And every one of them has asked some version of the same question: *"Why doesn't the broker just do this?"*

Eclipse Sparkplug B is the most visible proof that this need is real — it defines application-layer sequencing on top of MQTT (64-bit `seq` fields in protobuf payloads, birth/death certificates, state management) precisely because MQTT v5.0 does not provide these primitives natively. Sparkplug exists because MQTT has a gap. v6.0 proposes to close that gap at the protocol level.

I am not proposing that MQTT become Kafka. I am not proposing a general-purpose upgrade. I am proposing that we acknowledge what our customers are already building on top of MQTT and give them proper protocol-level tools instead of forcing them to reinvent the same workarounds in every deployment.

## Why Standardize Now — Not "Ship an Extension First"

The most reasonable pushback I have heard is: *"Ship these features as a HiveMQ extension. Let the market validate them. Come back to OASIS in five years with production data."*

This sounds prudent, but it leads to **fragmentation, not validation.** If HiveMQ ships `$queue/`, FETCH, and SQMC as a proprietary extension, here is what happens next:

- **EMQX builds their own version** — similar semantics, different User Property names, different control topic paths, different consumer group behavior
- **Mosquitto community builds a plugin** — subset of features, incompatible wire format
- **AWS IoT Core adds "durable queues"** — completely proprietary, no interop with any of the above
- **Every customer running two brokers** (common in industrial — edge broker + cloud broker) now needs a translation layer between competing proprietary implementations

This is exactly what happened with `$SYS/` — every broker implemented it differently, there is no standard, and it remains a mess 15 years later. It is what happened with shared subscription behavior before v5.0 partially standardized it — and even now the spec leaves enough implementation-defined gaps that HiveMQ had to build Declared Shared Subscriptions as a proprietary workaround.

**The extension-first path does not lead to standardization — it leads to vendor lock-in dressed up as innovation.** Once three vendors have incompatible implementations in production with paying customers depending on them, the OASIS committee has to reconcile three designs instead of evaluating one proposal. That is how standards processes stall for years.

The patterns are already validated. Sparkplug proves application-layer sequencing works. HiveMQ's Declared Shared Subscriptions prove durable queue semantics are needed. Every customer I have worked with who runs an MQTT-to-Kafka bridge proves pull-based consumption is needed. What is missing is not proof of concept — it is a **standard wire representation** that lets a Paho client library work with a HiveMQ broker, an EMQX broker, or any future broker without vendor-specific payload conventions.

**Standardizing early — before fragmentation — is cheaper than standardizing late.**

---

## What This Proposal Is Not

**This is not "MQTT trying to become Kafka."** Every time I present this to an engineer, that is the first reaction. I understand why — the feature list (durable queues, pull-based fetch, sequence numbers, consumer groups) reads like a Kafka feature sheet. But the context is completely different.

**Kafka is not viable at the edge.** Its minimum client footprint requires a full JVM stack with multi-GB RAM. Our customers have thousands of devices — PLCs, RTUs, smart meters, semiconductor tools — running constrained firmware with MQTT baked in. These devices will be in service for 15–25 years. They cannot be reflashed with Kafka client libraries. AMQP 1.0 is similarly impractical for constrained environments.

The architecture our customers run today looks like this:

```
[Edge Device — MQTT v5.0] → [HiveMQ Broker] → [Kafka Bridge] → [Kafka] → [Consumer]
```

That bridge is a second system, a second failure domain, a second protocol stack, and a second team. Every customer I have worked with who runs this architecture has told me they would eliminate the bridge if they could. v6.0 eliminates it:

```
[Edge Device — MQTT v5.0] → [HiveMQ v6.0 Broker — native queuing] → [Consumer via FETCH]
```

The edge devices do not change. The edge protocol does not change. The consumer gets Kafka-like semantics (ordered, durable, pull-based) without a second messaging system. If Kafka could run on a PLC, this proposal would not exist.

**What Kafka does that v6.0 explicitly does not attempt:** - Multi-day log retention with consumer offset replay - Stream processing or CEP (Kafka Streams, ksqlDB) - Server-to-server batch processing at data centre scale - Schema registry or schema evolution - Topic compaction

v6.0 adds exactly five things to MQTT. No more.

---

## “MQTT v5.0 Already Does This” — Point-by-Point

### Section 2.1: “That’s a Shared Subscription”

**Georg’s criticism:** Durable, session-independent queues are not needed because MQTT v5.0 Shared Subscriptions ( `$share/group/topic` ) already provide this.

**Simon’s criticism:** “The protocol does not concern itself with broker nodes — that’s the implementation.”

**I went back to the spec to make sure I was not overstating the gap. The gap is actually larger than I originally described.**

The MQTT v5.0 OASIS Standard defines shared subscriptions in Section 4.8. Here is what the spec actually says — and critically, what it does not say:

**1. Shared subscriptions do not buffer messages when no subscriber is connected.**

The spec defines shared subscriptions as a mechanism to distribute messages across “subscribing Sessions.” When no session is subscribed, the spec is silent — there is no normative requirement to buffer messages for the group. Messages published to a topic matched by a shared subscription with zero active sessions are not guaranteed to be held. This is not a durable queue — it is a fan-out optimization for active subscribers.

HiveMQ actually recognized this gap and built a proprietary feature called Declared Shared Subscriptions — pre-configured shared subscriptions that enqueue messages even when no subscriber is connected. **The fact that HiveMQ had to build a non-standard extension to get this behavior is itself evidence that `$share/` does not provide durable queue semantics.**

**2. The spec explicitly prohibits re-routing unacknowledged messages to another consumer.**

This is the one that matters most for industrial use cases. Section 4.8.2, normative requirement `[MQTT-4.8.2-5]` states:

> *“If the Client’s Session terminates before the Client reconnects, the Server MUST NOT send the Application Message to any other subscribed Client.”*

Read that again. If a consumer in a `$share/` group receives a QoS 1 message, disconnects before sending PUBACK, and its session expires — **the message is lost.** The spec explicitly prohibits the broker from re-delivering it to another consumer in the group. The message is discarded.

In a traditional competing-consumer queue (AMQP, JMS, Kafka consumer groups), an unacknowledged message is returned to the queue and re-dispatched to another consumer. In MQTT v5.0 shared subscriptions, it is **destroyed.** This is not a competing-consumer queue. It is a load balancer with a data loss failure mode.

I have seen this exact scenario in customer deployments. A consumer crashes mid-processing during a fault storm — exactly when message integrity matters most — and the in-flight messages are silently lost because the session expired before the consumer could reconnect.

**3. Message ordering is explicitly NOT guaranteed for shared subscriptions.**

The spec's ordering guarantee in Section 4.6, `[MQTT-4.6.0-6]` is scoped to *"Non-shared Subscriptions"* only. For shared subscriptions, ordering across consumers in the group is implementation-defined. HiveMQ's own documentation confirms this: *"you gain horizontal scalability and high availability at the cost of per-client message ordering."*

**The full comparison:**

| Property | `$share/` (MQTT v5.0 Spec) | `$queue/` (v6.0 Proposal) |
|---|---|---|
| **Messages buffered when no subscriber exists** | Not guaranteed — spec is silent; implementation-defined | Yes — queue persists independently of sessions |
| **Survives broker restart (spec-mandated)** | No — persistence of shared sub state is implementation-defined | Yes — persistence to non-volatile storage required before PUBACK |
| **Unacked message re-routed on consumer failure** | **No — `[MQTT-4.8.2-5]` explicitly prohibits this.** Message is discarded if session terminates. | Yes — message lock released immediately; re-dispatched to next consumer |
| **Message ordering guarantee** | No — `[MQTT-4.6.0-6]` scopes ordering to non-shared subs only | Yes — strict ascending order by Stream Sequence Number |
| **Gap detection** | Impossible — no per-message identity | Built-in — Seq gaps are detectable |

| Property | `$share/` (MQTT v5.0 Spec) | `$queue/` (v6.0 Proposal) |
|---|---|---|
| **Named, inspectable entity** | No — `$share/` is a subscription pattern | Yes — `$queue/` is a first-class entity with TTL, max-size, storage policy |

**The bottom line:** `$share/` is a delivery optimization for active subscribers. `$queue/` is a named, durable, persistent message store. They solve different problems. Saying " `$share/` already does this" is like saying "TCP already provides reliable delivery, so we don't need a database." The reliability primitives operate at different levels and serve different purposes.

To Simon's point about the protocol not concerning itself with broker nodes — I agree. And the `$queue/` proposal does not dictate broker architecture. It defines a **client-facing contract**: messages published to `$queue/` topics MUST be persisted before acknowledgment and MUST be delivered in order with gap detection. How the broker achieves this internally is implementation-defined, just as how a broker persists session state today is implementation-defined. The difference is that `$queue/` makes the durability guarantee **normative** rather than optional.

---

## Section 2.2: Packet Identifiers and Message Ordering

**Simon's criticism:** "Packet identifiers are session scoped and not intended for ordering. They are also eligible for reuse within a session. Why would we want to increase the size of session packets by 2 bytes for arbitrary ID space? In what scenario would a client have >65535 packets inflight?"

**Simon is correct on every factual point here, and I want to be clear that the proposal does not conflict with any of them.**

We are **not** proposing to enlarge the Packet Identifier. The 16-bit Packet ID remains exactly as specified in Section 2.2.1. It continues to serve its original purpose: correlating QoS 1/2 acknowledgments within a single session.

The Stream Sequence Number ( `0x30` ) is a **separate, additional property** — a new field with a completely different purpose. The confusion is understandable because the original proposal document jumped into wire format details before clearly explaining why a new field is needed. That is my fault — Simon's "too much HOW, not enough WHY" feedback is well taken.

Here is the WHY:

| | Packet Identifier (v5.0) | Stream Sequence Number (v6.0) |
|---|---|---|
| **What it answers** | "Has this specific QoS handshake completed?" | "Where is this message in the queue's total history?" |
| **Scope** | Per-session, per-connection | Per-queue, cluster-wide, permanent |
| **Assigned by** | Client or broker | Broker only |
| **Recycled?** | Yes — reused after PUBACK/PUBCOMP | Never — monotonically increasing |
| **Survives reconnection?** | No | Yes — persisted across sessions and broker restarts |
| **Purpose** | QoS ack correlation | Ordering, gap detection, exactly-once deduplication, resume-from-position |

The question "when would a client have >65535 packets inflight?" is exactly the right question for Packet Identifiers — and the answer is "never in practice, so 16 bits is fine." But that is the wrong question for Stream Sequences. A queue processing 1,000 messages/second exhausts 65,535 values in 65 seconds. The sequence number represents **total message identity across the lifetime of a queue**, not in-flight count.

The overhead: 5 bytes per `$queue/` PUBLISH (1-byte property ID + 4-byte value). Zero bytes for non-queue topics. Standard pub/sub ( `temperature/office` ) is completely unaffected.

Both reviewers acknowledge that 2.2 (message ordering across sessions) is a valid gap. The Stream Sequence Number is the mechanism that fills it — without touching the Packet Identifier.

---

### Section 2.3: "Receive Maximum Already Provides Flow Control"

**Georg's criticism:** MQTT v5.0's `Receive Maximum` plus the frequency of client acknowledgments already provides flow control.

**`Receive Maximum` is a window size limiter, not a pull mechanism.** It caps the number of QoS 1/2 messages the broker can have in-flight simultaneously. The broker still pushes — it just pushes in a bounded window.

Here is the distinction that matters in practice:

| | `Receive Maximum` (v5.0) | FETCH (v6.0) |
|---|---|---|
| **Consumer controls *when* to receive** | No — the broker pushes as soon as an ack frees a slot | Yes — consumer issues FETCH when ready. No FETCH = no messages. |

| | `Receive Maximum` (v5.0) | FETCH (v6.0) |
|---|---|---|
| **Consumer can pause entirely** | Only by disconnecting or withholding acks (both destructive) | Yes — stop issuing FETCH. Messages stay in the queue. |
| **Prevents flood on reconnect** | No — broker immediately pushes up to `Receive Maximum` from backlog | Yes — consumer fetches at its own pace |

**What I have seen in the field:** The "slow consumer death spiral" is one of the most common support issues I dealt with as a TAM. A SCADA historian writing to a database at 10ms per message sets `Receive Maximum = 50`. The broker pushes 50 messages. The historian processes them at 100 msg/sec. But the queue has 500,000 msg/sec incoming. The broker pushes 50 more as each ack arrives. The historian falls further and further behind. Its memory fills. It crashes. It reconnects. The broker immediately pushes another 50 from the now-massive backlog. The historian crashes again.

The customer's workaround: disconnect the historian, let messages pile up in broker session queues, reconnect during a maintenance window and drain slowly. This is operational toil masquerading as flow control.

`Receive Maximum` plus ack pacing can slow down the push rate, but the consumer cannot tell the broker "I am in a maintenance window, hold everything until I come back and ask for it." FETCH can.

FETCH is not a replacement for `Receive Maximum`. Both serve valid purposes. `Receive Maximum` is fine for live pub/sub where you want bounded push delivery. FETCH is for queue consumption where the consumer needs absolute control over when and how much it receives.

---

## Section 2.4: "Cluster-Aware Sequence Numbers" — On the Epoch

**Georg's criticism:** "This is plainly wrong."

**Simon's criticism:** "The protocol does not concern itself with broker nodes — that's the implementation."

I want to address these together because I think the confusion is partly my fault. The original proposal described the Epoch in terms of cluster architecture (node failover, quorum loss, partition events). That framing made it sound like the protocol is prescribing implementation details. It is not.

**The Epoch is not an implementation detail. It is a piece of protocol-level information that the client needs and can act on.**

Here is what the Epoch actually is, stripped of all implementation language:

> **Stream Epoch (`0x35`):** A value carried in CONNACK and PUBLISH packets that tells the client whether the broker's message state is continuous with what the client last saw.
>
> - **Same Epoch as client's stored value:** The broker guarantees that all sequence numbers between the client's last-seen Seq and the current Seq are accounted for. The client can trust its local high-

> watermark and resume processing.
> - **Different Epoch from client's stored value:** The broker **cannot** guarantee sequence continuity. Something happened — the broker does not tell the client what — that may have caused messages to be lost, reordered, or duplicated. The client MUST discard its local idempotency state and resynchronize.

That is the entire client-facing contract. The protocol does not say "because a cluster node failed" or "because a partition occurred." It says: **"the broker's state may have changed in a way that breaks sequence continuity, and here is how the client knows."**

This is analogous to how MQTT v5.0 handles session state today. When a client reconnects with `cleanStart=false`, the broker tells the client (via the Session Present flag in CONNACK) whether the session exists. The protocol does not dictate *how* the broker persists sessions — it just provides a client-visible signal. The Epoch extends this pattern: it tells the client whether the **queue's sequence state** is continuous, not just whether the session exists.

**Why this matters — from customer experience:**

The most common post-incident question I have heard from customers after a broker restart is: *"Did we lose any messages?"* Today, the honest answer is: "We don't know. The protocol doesn't tell you. You have to reconcile your application-level records against the broker's stored sessions and hope nothing fell through the cracks."

With the Epoch, the answer becomes: "If the Epoch is the same, no. If the Epoch changed, potentially yes — and here is exactly where to start your reconciliation." That is a massive improvement for incident response.

**A single-node broker benefits from this too.** If a standalone HiveMQ instance restarts and loses its in-memory queue state (but retains persisted data), it can increment the Epoch to signal to reconnecting clients that some messages may have been lost during the restart window. No cluster, no nodes, no quorum — just a simple "my state changed, here's your signal." The mechanism is topology-agnostic.

**What operators build today without the Epoch:**

Every customer I have worked with who cares about message continuity has built some version of this in application code: - Sequence numbers embedded in message payloads - Checkpoint tables in external databases (Redis, PostgreSQL) - Post-restart reconciliation jobs that compare producer records against consumer records - Manual "state reset" procedures that operators execute after broker incidents

The Epoch standardizes this signal at the protocol level. The client library handles it. The application developer does not have to build a reconciliation framework from scratch for every deployment.

---

## Section 2.5: Shared Subscription Semantics — Exclusive Consumer / Hot Standby

**Both reviewers acknowledge this is a valid gap.** MQTT v5.0 does not provide exclusive consumer (hot-standby) semantics. The SQMC exclusive mode in v6.0 addresses a real need — particularly for safety-critical command streams (SECS/GEM S2F21, grid protection relay commands) where strict ordering with automatic

failover is non-negotiable.

---

## “This Should Be Handled at the Application Level”

Simon raises this directly: *“There appears to be a mux’ing of what is expected of the application and what is expected of the protocol.”*

This is the right question to ask. Every feature in v6.0 **can** be implemented at the application layer. Sequence numbers, gap detection, exactly-once dedup, pull-based flow control, consumer group management — all of it. This is how it is done today.

**But having spent 2.5 years watching customers do exactly this, I can tell you it does not work well in practice.**

### What I Have Seen in Customer Deployments

**1. Every customer reinvents the same wheel, differently.**

I have worked with semiconductor, energy, and automotive customers who all independently built application-layer sequencing on top of MQTT. None of their implementations are compatible. One uses JSON `{"seq": N}`, another uses protobuf with a `sequence_number` field, another uses a custom binary header. Every integration between these systems requires a translation layer that maps one sequence scheme to another. This is the N-squared problem in practice — 50 publishers and 20 consumers means 1,000 pairwise schema agreements, none standardized.

**2. Application-layer reliability has a correctness problem.**

The most common failure mode I have seen is not “the sequence number system doesn’t work” — it is “the developer forgot to check the sequence number.” Application-layer deduplication requires every consumer to correctly implement sequence validation. In a system with 20 consumers written by 5 different teams over 3 years, at least one of them will have a bug in its dedup logic. I have seen this cause duplicate processing of safety-critical commands — exactly the scenario this proposal is designed to prevent.

When the broker assigns the sequence and the client library handles dedup, the application developer cannot forget. The reliability primitive is in the infrastructure, not in the application code.

**3. The broker cannot optimize what it cannot see.**

When sequence numbers are in the payload, the broker is a dumb pipe. It cannot detect gaps, enforce ordering, perform dedup, resume delivery from a position, or track consumer group progress. These are all things the broker *should* be doing — and things our customers ask us why HiveMQ doesn’t do.

**4. Sparkplug proves the pattern.**

Eclipse Sparkplug B already defines application-layer sequencing on MQTT. It proves the need is real and the industry has converged on a common pattern. v6.0 proposes to move that pattern from the payload into the protocol — exactly as MQTT v5.0 moved message expiry, request/response correlation, and shared subscriptions from application-layer conventions into protocol properties.

**5. The extension-first path leads to fragmentation, not validation.**

If we tell customers "build it in your application" or "use a vendor extension," every vendor and every customer builds their own version. We end up with a dozen incompatible implementations of the same five patterns. Standardizing at the protocol level — before fragmentation — gives the ecosystem a single wire representation that every client library and every broker can implement. This is the same argument I made above in Why Standardize Now: the `$SYS/` fragmentation and HiveMQ's proprietary Declared Shared Subscriptions are proof that the extension-first path does not converge on interoperability.

### The Historical Precedent

MQTT v3.1.1 had no concept of message expiry, request/response correlation, or shared subscriptions. All were implementable at the application layer. MQTT v5.0 moved them into the protocol because the industry had converged on common patterns that benefited from standardization. The same trajectory applies here.

---

## "Do You Think MQTT Should Be a Message Queue?"

Simon asks: *"I think you hit the nail on the head when you said: 'It was not designed to be a message queue.' My question to you would be, do you think it should be? In which case, why not Kafka?"*

### My Direct Answer

**No, MQTT should not become a general-purpose message queue.** It should remain a lightweight pub/sub transport for the vast majority of its use cases. Temperature sensors, dashboards, device commands, live monitoring — all of this is v5.0 territory and should stay there.

**But MQTT is *already being used* as a message queue.** Our customers are doing it right now, with application-layer hacks. The question is not "should MQTT be a message queue?" — it is "given that our customers are already using MQTT as a message queue, should the protocol provide proper primitives, or should we keep telling them to build their own?"

I think we should provide the primitives. Scoped narrowly ( `$queue/` namespace only), opt-in (zero overhead for standard pub/sub), and backward-compatible (v5.0 clients and brokers are unaffected).

### Why Not Kafka (The Answer That Never Changes)

**The edge devices cannot run Kafka clients.** A semiconductor fab has 500 tools running embedded MQTT clients on proprietary firmware that will be in service for 15–25 years. These tools cannot be reflashed. The Kafka JVM requirement is a non-starter.

The bridge architecture (MQTT → Kafka → Consumer) works but adds operational cost, a failure domain, and a team. Every customer I have worked with who runs this architecture has asked if we can eliminate the bridge. v6.0 is my answer.

---

## "Too Much HOW, Not Enough WHAT and WHY"

**Simon is right, and I appreciate the feedback.** The original proposal led with wire formats and byte layouts. That was a mistake. The audience for this proposal is not protocol implementers (yet) — it is the people who need to understand *why* these changes matter before they evaluate *how* they work.

The WHAT and WHY are simple:

| What Customers Need | Why They Need It | What v5.0 Offers | What v6.0 Adds |
|---|---|---|---|
| Durable queues that outlive sessions | Consumer maintenance should not cause message loss | `$share/` — but not durable, not ordered, messages lost on session termination per `[MQTT-4.8.2-5]` | `$queue/` — named, persistent, survives all consumer disconnections |
| Message ordering with gap detection | Consumers need to know if a message was lost | Nothing — Packet IDs are session-scoped and recycled | Stream Sequence Number — per-queue, cluster-wide, permanent |
| Pull-based flow control | Slow consumers crash under push load | `Receive Maximum` — caps window, but broker still pushes | FETCH — consumer pulls when ready; no FETCH = no delivery |
| Strict consumer groups with failover | Consumer crashes should not lose in-flight messages | `$share/` — but `[MQTT-4.8.2-5]` discards messages on session termination | SQMC — message lock released on disconnect, re-dispatched immediately |

| What Customers Need | Why They Need It | What v5.0 Offers | What v6.0 Adds |
|---|---|---|---|
| Broker state continuity signal | Clients need to know if messages were lost during broker restart | Session Present flag — but only signals session existence, not message continuity | Stream Epoch — signals whether sequence state is continuous |

The genesis for this thinking is 2.5 years of watching our customers solve these problems in application code and asking myself whether we can do better at the protocol level. I believe we can.

---

## Summary of Responses

| Criticism | Response |
|---|---|
| “2.1 is just a shared subscription” | No. The v5.0 spec itself contradicts this: `[MQTT-4.8.2-5]` prohibits re-routing unacked messages to other consumers (messages are lost), `[MQTT-4.6.0-6]` scopes ordering to non-shared subs only, and the spec provides no normative requirement to buffer messages when no subscriber exists. HiveMQ built Declared Shared Subscriptions as a proprietary extension precisely because `$share/` lacks durable queue semantics. |
| “2.2 conflates concepts” | Fair. The proposal does NOT enlarge Packet Identifiers. Stream Sequence is a separate 5-byte property for a separate purpose (ordering, gap detection, dedup), added only to `$queue/` messages. Standard pub/sub is unaffected. |
| “2.3 is Receive Maximum” | `Receive Maximum` caps the in-flight window but the broker still pushes. The consumer cannot say “stop sending until I ask.” FETCH inverts the model — no request, no delivery. This eliminates the slow consumer death spiral I have seen repeatedly in customer deployments. |
| “2.4 is plainly wrong” | The Epoch is not an implementation detail — it is a protocol-level signal carried in CONNACK that tells the client whether broker message state is |

| Criticism | Response |
|---|---|
| | continuous. It does not prescribe clustering, topology, or architecture. A single-node broker can use it. It is analogous to the Session Present flag but for queue sequence state. |
| “Protocol doesn’t concern itself with broker nodes” | Agreed — and the Epoch doesn’t either. It defines client-facing behavior: “if sequence continuity cannot be guaranteed, tell the client.” How the broker determines this internally is implementation-defined. |
| “This should be application-level” | Every customer I have worked with has built these primitives in application code. None of their implementations are compatible. The broker cannot optimize what it cannot see. Sparkplug already proves the need. v6.0 standardizes the pattern. |
| “Why not Kafka?” | Edge devices cannot run Kafka clients. The bridge adds cost and failure domains. v6.0 eliminates the bridge without changing edge devices. |
| “Ship it as an extension first” | The extension-first path leads to fragmentation, not validation. If HiveMQ ships it proprietary, EMQX and AWS build incompatible versions. Standardizing early — before fragmentation — is cheaper than standardizing late. `$SYS/` and Declared Shared Subscriptions are proof. |
| “Too much HOW, not enough WHY” | Fair. This document provides the WHY. The genesis is 2.5 years of TAM work watching customers solve these problems in application code. |

---

## References


- MQTT v5.0 OASIS Standard — Shared Subscriptions ( `[MQTT-4.8.2-5]` , Section 4.8), Ordered Topics ( `[MQTT-4.6.0-6]` , Section 4.6), Receive Maximum (Section 3.2.2.3.2), Packet Identifiers (Section 2.2.1)
- HiveMQ: Declared Shared Subscriptions — HiveMQ’s proprietary extension to fill the durable queue gap in `$share/`

- HiveMQ: MQTT 5 Shared Subscriptions — Shared subscription behavior, ordering limitations
- HiveMQ: Shared Subscription Documentation — Implementation details and configuration
- HiveMQ: Client Load Balancing with Shared Subscriptions — Practical challenges with slow consumers
- HiveMQ: MQTT vs AMQP for IoT — Protocol complexity comparison
- Confluent Platform System Requirements — Kafka resource footprint
- Apache Kafka Consumer API — Pull-based poll() API
- Eclipse Sparkplug Specification — Application-layer sequencing on MQTT
- Sparkplug v2.2 Specification PDF — Sequence number and state management details
- SEMI SECS/GEM Standard — Semiconductor equipment communication
- SEMI E30 (GEM) Specification — Transaction semantics for semiconductor manufacturing
- IEC 61850 — Power grid communication standard
- IEC 61850 and MQTT Integration — Edge transport for grid data
- NATS JetStream Consumers — Pull-based consumer model reference
- HiveMQ: Industrial IoT Data Streaming with MQTT — MQTT at industrial scale


# MQTT Version 6.0

## Industrial Stream and Advanced Queuing Extension

**OASIS Standard Draft Date:** March 2026 **Author:** Bill Sommers, AI Solutions Lead, HiveMQ, Inc. **Base Specification:** MQTT Version 5.0 OASIS Standard (https://docs.oasis-open.org/mqtt/mqtt/v5.0/mqtt-v5.0.html)

---

## 1. Introduction

MQTT is a Client-Server publish/subscribe messaging transport protocol. It is lightweight, open, simple, and designed to be easy to implement.

**[MODIFIED for v6.0]:** Version 6.0 extends this simplicity with **Deterministic Stream Semantics**. These features provide the reliability required for mission-critical industrial environments — including semiconductor fabrication (SECS/GEM), financial messaging, and large-scale IoT deployments — where message ordering, pull-based flow control, and cluster-wide consistency are mandatory.

MQTT v6.0 is designed to be **wire-compatible** with MQTT v5.0 when the Compatibility Layer is active. All v6.0 extensions utilize the Property and User Property fields that v5.0 mandates be ignored when unrecognized. In Native Mode, v6.0 introduces a new Control Packet type and requires Protocol Level 6.

## 1.1 Conformance

A Client or Server is conformant to MQTT v6.0 if it:

- Meets all normative requirements of MQTT v5.0, AND
- Correctly handles Properties `0x30` (Stream Sequence Number) and `0x35` (Stream Epoch), AND
- Implements the `$queue/` namespace persistence semantics described in Section 4.1, AND
- Implements the v6.0 negotiation handshake described in Section 3.1.

## 1.2 Terminology

The key words **MUST**, **MUST NOT**, **REQUIRED**, **SHALL**, **SHALL NOT**, **SHOULD**, **SHOULD NOT**, **RECOMMENDED**, **MAY**, and **OPTIONAL** in this document are to be interpreted as described in RFC 2119.

**[NEW for v6.0] Additional Terms:**

| Term | Definition |
|---|---|
| **Stream Sequence Number** | A 32-bit monotonic integer uniquely identifying a message within a `$queue/` namespace, persistent across sessions |
| **Stream Epoch** | A 16-bit counter representing the “era” of a queue; incremented when cluster failover may have caused sequence discontinuity |
| **FETCH** | New Control Packet (Type 16) for pull-based message retrieval from persistent queues |
| **`$queue/`** | Topic namespace prefix designating a named, durable, session-independent persistent queue |
| **SQMC** | Single-Queue Multi-Consumer — a queuing pattern where each message is delivered to exactly one of multiple active consumers |
| **Virtual FETCH** | Compatibility-mode representation of FETCH using PUBLISH to `$SYS/queues/{name}/fetch` |
| **High-Watermark** | The last sequence number successfully processed by a consumer client |
| **Distributed Sequence Counter** | A cluster-wide atomic counter maintained in HiveMQ’s replication data grid, one per `$queue/`; any node may increment it atomically to claim the next sequence number |
| **Competing Consumer** | SQMC mode: messages distributed round-robin; each message delivered to exactly one consumer |

| Term | Definition |
|---|---|
| **Exclusive Consumer** | SQMC mode: one designated consumer receives all messages; others are hot standbys |

### 1.3 Normative References

- MQTT Version 5.0 OASIS Standard: https://docs.oasis-open.org/mqtt/mqtt/v5.0/mqtt-v5.0.html
- RFC 2119: Key words for use in RFCs to Indicate Requirement Levels

### 1.4 Data Representation

All data representation follows MQTT v5.0 conventions.

**[NEW for v6.0]:** - **Four Byte Integer:** A 32-bit unsigned integer in big-endian order. Used for Stream Sequence Numbers. - **Two Byte Integer:** A 16-bit unsigned integer in big-endian order. Used for Stream Epochs.

---

## 2. MQTT Control Packet Format

### 2.1 Fixed Header

Every MQTT Control Packet begins with a Fixed Header. The format is unchanged from v5.0.

```
Bit:     7    6    5    4    3    2    1    0
Byte 1:  [ MQTT Control Packet Type  ] [Flags]
Byte 2+: [        Remaining Length        ]
```

**[NEW for v6.0] Control Packet Type 16 — FETCH:**

| Type Value | Name | Direction | Description |
|---|---|---|---|
| 16 | FETCH | Client to Server | Pull-based request for a batch of messages from a named queue |

> **Note on Compatibility:** The Type 16 slot was reserved in v5.0. A strict v5.0 broker will close the connection upon receiving a Type 16 packet. In environments with mixed v5.0/v6.0 brokers, use the Virtual FETCH mechanism (Section 4.2.1) instead.

## 2.2 Variable Header Properties

MQTT v6.0 introduces four new Property Identifiers in the reserved range ( `0x30–0x45` ):

| Hex | Name | Data Type | Applicable Packets |
|---|---|---|---|
| 0x30 | **Stream Sequence Number** | Four Byte Integer | PUBLISH, FETCH (response) |
| 0x35 | **Stream Epoch** | Two Byte Integer | PUBLISH, CONNACK, DISCONNECT |
| 0x41 | **Throughput Limit** | Four Byte Integer | CONNACK |
| 0x42 | **Batch Size** | Four Byte Integer | FETCH, PUBLISH (Virtual FETCH) |

### 2.2.1 Stream Sequence Number (0x30)

- **Type:** Four Byte Integer (32-bit unsigned, big-endian)
- **Packets:** PUBLISH (for `$queue/` topics)
- **Normative:** The Broker MUST assign a monotonically increasing value to this property for every message published to a `$queue/` topic. If the Publisher provides this value, the Broker MUST validate it and MAY override it.
- **Purpose:** Provides a persistent, end-to-end message identity that survives transport-layer reconnections, session restarts, and cluster failovers. Unlike the 16-bit Packet Identifier (which is per-session and recycled), this value is globally unique within a queue's lifetime.

### 2.2.2 Stream Epoch (0x35)

- **Type:** Two Byte Integer (16-bit unsigned, big-endian)
- **Packets:** PUBLISH, CONNACK, DISCONNECT
- **Normative:** The Broker MUST include the current Epoch in CONNACK for resuming sessions. The Broker MUST increment the Epoch when it cannot guarantee sequence continuity after a cluster partition or replication quorum loss (see Section 4.3.2). HiveMQ does not use leader election; Epoch increments are driven by partition events, not node promotions. A Client that receives an Epoch value greater than its stored Epoch MUST discard its local idempotency table and perform a full application-layer resynchronization.
- **Purpose:** Identifies the "era" of a queue's sequence space. Allows clients to distinguish between a sequence gap (a missed message) and a cluster reset (all previous sequence context is invalid).

### 2.2.3 Throughput Limit (0x41)

- **Type:** Four Byte Integer (KB/second)
- **Packets:** CONNACK
- **Normative:** If present, the Client MUST NOT exceed this throughput. If the Client exceeds the limit, the Broker MAY disconnect with Reason Code `0x9B (Quota Exceeded)`.
- **Purpose:** Broker-enforced rate limiting for hardware NIC and storage protection.

#### 2.2.4 Batch Size (0x42)

- **Type:** Four Byte Integer (message count)
- **Packets:** FETCH (native); PUBLISH to `$SYS/queues/{name}/fetch` (compat mode)
- **Normative:** The Broker MUST release at most this many messages in response to a FETCH or Virtual FETCH request. If fewer messages are available, the Broker MUST release only the available count.

---

# 3. MQTT Control Packets

## 3.1 CONNECT – Connection Request

#### 3.1.2.2 Protocol Version

- **v5.0:** Protocol Level value is `5`
- **[MODIFIED for v6.0]:** Protocol Level value is `6` for native v6.0 mode. Clients MAY use Protocol Level `5` combined with the v6.0 User Property for Compatibility Mode operation.

#### 3.1.2.11 CONNECT Properties

All v5.0 CONNECT properties are retained. The following property is added:

**[NEW for v6.0] v6.0 Capability Negotiation:** - **User Property Key:** `mqtt-ext` - **User Property Value:** `v6.0` - **Normative:** A Client wishing to use `$queue/` namespaces, FETCH semantics, or SQMC consumer modes MUST include this property. A Client that does not include it MUST be treated as a legacy v5.0 Client by the Broker.

**[NEW for v6.0] Resync on Reconnect:** - **User Property Key:** `v6-last-seq` - **User Property Value:** The decimal string representation of the last successfully processed Stream Sequence Number - **User Property Key:** `v6-epoch` - **User Property Value:** The decimal string representation of the Client's current known Epoch - **Normative:** Upon reconnect, a Client SHOULD include these properties to enable seamless queue resumption. The Broker MUST use these values to resume delivery from the correct position (see Section 4.3).

## 3.2 CONNACK – Connect Acknowledgement

#### 3.2.2.3 CONNACK Properties

All v5.0 CONNACK properties are retained. The following properties are added:

**[NEW for v6.0] v6.0 Capability Confirmation:** - **User Property Key:** `mqtt-ext` - **User Property Value:** `v6.0` - **Normative:** A v6.0-aware Broker MUST echo this property. If absent, the Client MUST assume a legacy v5.0 Broker and MUST NOT use `$queue/` namespaces or FETCH semantics.

**[NEW for v6.0] Throughput Limit (0x41):** - See Section 2.2.3.

**[NEW for v6.0] Stream Epoch (0x35):** - **Normative:** REQUIRED when the Client included `v6-epoch` in CONNECT. If the Broker's current Epoch differs from the Client's reported Epoch, the Broker MUST include the new Epoch in CONNACK. The Client MUST respond per Section 2.2.2.

## 3.3 PUBLISH – Publish Message

### 3.3.2 PUBLISH Variable Header

The PUBLISH packet, when directed to a `$queue/` topic, triggers additional broker-side processing.

**[MODIFIED for v6.0]:** ~~The Server MUST push all matching messages to connected Clients.~~ For `$queue/` topics, the Server MUST NOT push messages unless a FETCH request is active or push mode is explicitly enabled. For standard topics, push behavior is unchanged.

#### 3.3.2.3 PUBLISH Properties

All v5.0 PUBLISH properties are retained. The following properties are added:

**[NEW for v6.0] Stream Sequence Number (0x30):** - **Normative:** REQUIRED for all PUBLISH packets to `$queue/` topics. The Broker MUST assign this value before persisting the message. See Section 2.2.1.

**[NEW for v6.0] Stream Epoch (0x35):** - **Normative:** REQUIRED for all PUBLISH packets to `$queue/` topics. The Broker MUST include the current Epoch. See Section 2.2.2.

**[NEW for v6.0] Priority:** - **User Property Key:** `v6-priority` - **User Property Value:** Integer 0–255 (higher values = higher priority) - **Normative:** OPTIONAL. Higher-priority messages SHOULD be delivered to consumers before lower-priority messages in the same queue.

## 3.4 SUBSCRIBE – Subscribe Request

#### 3.8.2.1 SUBSCRIBE Properties

All v5.0 SUBSCRIBE properties are retained. The following User Properties are added for SQMC semantics:

**[NEW for v6.0] Consumer Semantics:** - **User Property Key:** `v6-semantics` - **Values:** - `competing` — Enables Competing Consumer mode (round-robin; each message delivered to exactly one consumer; message locked until PUBACK received; immediate failover on disconnect) - `exclusive` — Enables Exclusive Consumer mode (primary consumer receives all messages; standby consumers receive nothing until primary disconnects) - **Normative:** If neither value is present, the subscription behaves as standard v5.0 Shared Subscription semantics (if `$share/` prefix is used) or normal subscription semantics otherwise.

**[NEW for v6.0] Consumer Group:** - **User Property Key:** `v6-group` - **User Property Value:** A UTF-8 string naming the consumer group - **Normative:** Clients in the same group sharing a `$queue/` topic with `competing` semantics will receive messages via round-robin distribution. Required when using `v6-semantics: competing`.

## 3.5 FETCH – Pull Request (Type 16) [NEW]

The FETCH packet is a new Control Packet introduced in v6.0. It enables pull-based message retrieval from persistent queues, providing absolute backpressure control.

### 3.5.1 FETCH Fixed Header

```
Bit:     7    6    5    4    3    2    1    0
Byte 1:  [ 1    0    0    0  ] [ 0    0    0    0 ]
          ^--- Type = 16 ---^   ^--- Reserved ---^
Byte 2+: [         Remaining Length              ]
```

### 3.5.2 FETCH Variable Header

| Field | Size | Description |
|---|---|---|
| Packet Identifier | 2 bytes | Standard acknowledgement identifier |
| Property Length | Variable | Length of property block |
| Batch Size (0x42) | 4 bytes | Maximum messages to return (REQUIRED) |
| Wait Timeout (0x36) | 2 bytes | Max ms to wait if queue is empty (long-poll; OPTIONAL) |
| Last Received Seq (0x30) | 4 bytes | Client's high-watermark for gap detection (OPTIONAL) |

### 3.5.3 FETCH Payload

The payload contains the **Queue Name** — a UTF-8 encoded string specifying the target `$queue/` topic (e.g., `$queue/production_line_1`).

```
+-------------------------------------------------------------+
|                  FIXED HEADER (2+ bytes)                    |
| Bits 7-4: Type (16) | Bits 3-0: Reserved (0000)            |
| Remaining Length (Variable Byte Integer)                     |
+-------------------------------------------------------------+
|                   VARIABLE HEADER                            |
| Packet Identifier       (2 bytes)                          |
| Property Length         (Variable)                         |
|   Batch Size    (0x42)  (4 bytes)                          |
|   Wait Timeout  (0x36)  (2 bytes, optional)                |
|   Last Seq      (0x30)  (4 bytes, optional)                |
```

```
+-----------------------------------------------------------+
|                       PAYLOAD                             |
| Topic Filter (UTF-8, e.g., "$queue/production_line_1")    |
+-----------------------------------------------------------+
```

#### 3.5.4 FETCH Normative Behavior

- The Broker MUST respond by delivering at most `Batch Size` messages from the specified queue to the Client's session.
- If the queue contains fewer messages than `Batch Size`, the Broker MUST deliver only the available messages.
- If the queue is empty and `Wait Timeout` is specified, the Broker MAY hold the request open until a message arrives or the timeout expires (long-polling).
- If `Last Received Seq` is provided, the Broker MUST validate it against the queue's current state. If the Client's value is ahead of the Broker's known state, the Broker MUST respond with a DISCONNECT containing `Reason Code 0xA0 (Epoch Reset)`.
- The Broker MUST NOT send unsolicited messages from `$queue/` topics unless the Client has an active FETCH request.

#### 3.5.5 FETCH Acknowledgement

The Broker responds to a FETCH by publishing messages with the standard PUBLISH flow (including PUBACK for QoS 1). The Packet Identifier from the FETCH is echoed in the response batch's PUBLISH packets to allow correlation.

---

# 4. Operational Behavior

## 4.1 The `$queue/` Namespace

Topics prefixed with `$queue/` represent **Named Queues** — durable, ordered message stores that exist independently of client sessions.

#### 4.1.1 Persistence

- **Normative:** The Broker MUST store messages published to `$queue/` topics in non-volatile storage before acknowledging the PUBACK (QoS 1) or PUBCOMP (QoS 2).
- Messages in `$queue/` MUST NOT be discarded unless:
  - Acknowledged by all intended consumers (per SQMC consumer group logic), OR
  - The message's `Message Expiry Interval` (v5.0 Property 0x02) has elapsed, OR
  - The queue's storage capacity limit has been reached (see Section 4.1.3)

#### 4.1.2 Ordering

- **Normative:** The Broker MUST deliver messages to consumers in strict ascending order of their `Stream Sequence Number`.
- The Broker MUST NOT deliver a message with Sequence N+1 before the consumer has acknowledged Sequence N (for QoS 1 and 2 delivery).

#### 4.1.3 Storage Limits

- **User Property:** `v6-queue-max-size` in SUBSCRIBE — specifies the maximum number of messages to buffer (Four Byte Integer string)
- **Behavior on limit reached:** The Broker SHOULD apply a “drop-oldest” policy by default. An alternative “reject-new” policy returns PUBACK with Reason Code `0x8D (Quota Exceeded)`.
- **User Property:** `v6-queue-ttl` in SUBSCRIBE — specifies how long (seconds) the queue persists after the last consumer disconnects

#### 4.1.4 Access Control

- **Normative:** Access to `$queue/` topics MUST be controlled via ACLs. The Broker SHOULD treat unauthorized publish or subscribe attempts to `$queue/` the same as unauthorized access to `$SYS/` topics.
- The Broker MUST reject subscribe requests to `$queue/` topics from Clients that have not completed the v6.0 negotiation handshake (Section 3.1).

### 4.2 Pull-Based Flow Control

MQTT v6.0 replaces the “push-all” delivery model for queue topics with a **consumer-driven pull model**.

#### 4.2.1 Native Mode (FETCH Packet)

See Section 3.5. The Broker MUST hold queue messages until a FETCH request arrives. This provides absolute backpressure: if the consumer’s application layer is slow, it simply does not issue FETCH requests.

#### 4.2.2 Compatibility Mode (Virtual FETCH)

For deployments where clients or brokers do not support Protocol Level 6:

1. **Request:** The Client publishes a message (QoS 1) to `$SYS/queues/{queue_name}/fetch`
2. **Batch Size:** The PUBLISH MUST include `User Property: ("v6-batch", "{N}")` where N is the desired message count
3. **Response:** The Broker releases the next N messages from the persistent queue to the Client’s session
4. **Normative:** The Broker MUST NOT release more than N messages per request. If no Virtual FETCH is active, the Broker MUST NOT push queue messages to the Client.

#### 4.2.3 Rate Limiting

- **Throughput Limit (0x41) in CONNACK:** Broker-enforced KB/s limit on client publish rate
- **Reason Code 0x9B (Quota Exceeded):** Returned when a Client exceeds the throughput limit
- The `Receive Maximum` property from v5.0 continues to apply for QoS 1/2 in-flight limits

### 4.3 Cluster Consistency (Shared-Nothing Architecture)

HiveMQ is a **masterless, shared-nothing cluster**: all nodes are peers, there are no permanent leaders, and no consensus protocol (Raft/Paxos) is used. Any node can accept any publish from any client. v6.0 MUST preserve monotonic sequencing within this constraint using a **Distributed Sequence Counter** rather than a designated leader.

#### 4.3.1 Distributed Sequence Counter

- **Normative:** Each `$queue/{name}` MUST maintain a single cluster-wide **Distributed Sequence Counter** stored in the Broker's replication data grid (e.g., HiveMQ's internal distributed data store).
- When a node receives a PUBLISH to a `$queue/` topic, it MUST perform an **atomic increment** (compare-and-swap) on that queue's counter to claim the next sequence number before persisting the message.
- No routing constraint is imposed on clients or publishers — **any node may sequence any publish**. Monotonicity is guaranteed by the atomic counter, not by sticky routing.
- If the atomic increment cannot complete because the counter's replication quorum is unavailable (e.g., a network partition has split the cluster), the receiving node MUST reject the PUBLISH with Reason Code `0x97 (Quota Exceeded)` and the client MUST retry after reconnection.
- The Broker MUST NOT assign a sequence number speculatively (i.e., without a confirmed atomic increment). Speculative assignment risks duplicate sequence numbers across nodes.

#### 4.3.2 Epoch Management

- **Normative:** The Broker MUST increment the Stream Epoch when it cannot guarantee that the Distributed Sequence Counter's state survived intact. This occurs when:
  - A network partition resolves and the counter's quorum was lost, leaving the post-partition state uncertain; OR
  - One or more nodes that held the only replica of unacknowledged `$queue/` messages leave the cluster permanently.
- The new Epoch MUST be propagated in the next CONNACK or PUBLISH to any Client subscribed to the affected queue, and in a DISCONNECT to Clients that had in-flight messages at the time of the partition.
- Nodes rejoining after a partition MUST defer to the surviving cluster's Epoch value.

#### 4.3.3 Client Failover and Resync

When a Client reconnects after a broker failure:

1. Client includes `v6-last-seq: {N}` and `v6-epoch: {E}` in CONNECT
2. Broker checks its local queue state for `$queue/{name}`:

- If Epoch matches and Seq N is present: resume delivery from N+1
- If Epoch matches but Seq N is absent (message was lost): begin from the earliest available message and flag the gap
- If Epoch has incremented: respond with CONNACK containing the new Epoch value; Client MUST reset its idempotency state

#### 4.3.4 Exactly-Once Processing (Application Layer)

Using the Stream Sequence Number as an idempotency key:

1. Consumer maintains a **High-Watermark** (last processed Seq) in an atomic store alongside its business logic
2. On message receipt: if `Seq <= High-Watermark`, acknowledge (PUBACK) but discard — do not process
3. If `Seq > High-Watermark`: execute business logic AND update High-Watermark atomically
4. On Epoch reset: clear the High-Watermark and perform full reconciliation

### 4.4 Single-Queue Multi-Consumer (SQMC)

#### 4.4.1 Competing Consumer Mode

When a consumer subscribes with `v6-semantics: competing`:

- **Message Locking:** When a message is dispatched from the queue to a consumer at QoS 1 or 2, it is "locked" to that consumer.
- **Lock Duration:** The lock persists until the consumer sends PUBACK (QoS 1) or PUBCOMP (QoS 2).
- **Failover:** If the consumer disconnects before acknowledging, the Broker MUST immediately unlock the message and deliver it to the next available consumer in the group.
- **Round-Robin:** The Broker distributes messages across consumers in the group using round-robin or least-loaded assignment. The specific algorithm is implementation-defined.
- **Normative:** Each message MUST be delivered to exactly one consumer in a Competing Consumer group.

#### 4.4.2 Exclusive Consumer Mode

When a consumer subscribes with `v6-semantics: exclusive`:

- The first Client to subscribe becomes the **Primary Consumer**.
- All subsequent subscribers become **Hot Standbys** — they receive no messages while the Primary is connected.
- **Normative:** If the Primary Consumer disconnects, the Broker MUST immediately promote the first Standby to Primary and resume delivery from the last acknowledged sequence.
- **Ordering guarantee:** Because only one consumer is ever active, strict ordering is preserved across failover.

---

## 5. Summary of Changes: v5.0 vs. v6.0

| Feature | MQTT v5.0 | MQTT v6.0 |
|---|---|---|
| Protocol Level | 5 | **6** (or 5 with compat negotiation) |
| Sequencing | 16-bit Packet ID (per-session, recycled) | **32-bit Stream Sequence (per-queue, persistent)** |
| Flow Control | Reactive push (Receive Maximum) | **Deterministic pull (FETCH / Virtual FETCH)** |
| Queue Type | Session-bound implicit queue | **Named durable queue ( `$queue/` namespace)** |
| Consumer Patterns | Shared Subscriptions (loose) | **SQMC: Competing + Exclusive with message locking** |
| Cluster Consistency | Implementation-defined, opaque to clients | **Epoch-based failover; client-visible resync** |
| Ordering Guarantee | Hop-by-hop, best effort | **Global monotonic ordering within queue** |
| Backpressure | None (push floods consumers) | **Broker buffers; consumer controls release rate** |
| Rate Limiting | None | **Throughput Limit property in CONNACK** |
| New Packet Types | None (Types 1-15) | **FETCH (Type 16)** |

## 6. Compatibility Layer

MQTT v6.0 is backward-compatible with MQTT v5.0 for all unchanged v5.0 use cases: existing packet types, properties, topics, and semantics continue to work as before. Compatibility is not wire-transparent for v6.0-only features such as FETCH, `$queue/`, Stream Sequence properties, or `last-seq` / `epoch`; those require either Protocol Level 6 or the compatibility mode specified below.

**Compatibility guarantee:** A v5.0 or v3.1.1 client connecting to a v6.0 broker for standard publish-subscribe sees no difference in behavior. The v6.0 extensions activate only when a client explicitly opts in via the negotiation handshake.

### 6.1 Negotiation

| Mode | Protocol Level | User Property |
|---|---|---|
| Native v6.0 | `6` | `mqtt-ext: v6.0` (optional, implied by level 6) |
| Compat v6.0 (on v5.0 broker) | `5` | `mqtt-ext: v6.0` (required) |
| Legacy v5.0 | `5` | (absent) |

### 6.2 Feature Mapping (Native → Compat)

| Native v6.0 | v5.0 Compatibility Mapping |
|---|---|
| FETCH (Type 16) | `PUBLISH` to `$SYS/queues/{name}/fetch` |
| Batch Size (0x42) | `User Property: ("v6-batch", "{N}")` |
| Stream Sequence (0x30) | `User Property: ("v6-seq", "{N}")` |
| Stream Epoch (0x35) | `User Property: ("v6-epoch", "{N}")` |
| SQMC Mode Bits | `User Property: ("v6-semantics", "competing\|exclusive")` |
| Wait Timeout (0x36) | `User Property: ("v6-wait-ms", "{N}")` |

### 6.3 Broker Requirements for Compat Mode

A v5.0 broker with a v6.0 Extension Plugin MUST:

1. Intercept PUBLISH packets to `$SYS/queues/*/fetch` and trigger queue message release
2. Intercept SUBSCRIBE packets containing `v6-semantics` User Properties and apply SQMC logic
3. Inject `v6-seq` and `v6-epoch` User Properties into outgoing PUBLISH packets for `$queue/` topics
4. Maintain persistent storage for `$queue/` topics independent of session state

---

## 7. Security

All MQTT v5.0 security requirements (TLS, Enhanced Authentication, SASL/SCRAM) are retained and remain mandatory.

**[NEW for v6.0]:**

- **Normative:** Access to the `$queue/` namespace MUST be controlled by ACLs. Unauthorized publish or subscribe to `$queue/` topics MUST be rejected with Reason Code `0x87 (Not Authorized)`.
- **Normative:** Access to `$SYS/queues/*/fetch` control topics MUST be restricted to authenticated clients that have completed the v6.0 handshake.
- Epoch Reset messages carry the potential to discard a client's idempotency state. Brokers MUST only send Epoch Reset signals when cluster state genuinely cannot guarantee sequence continuity. Malicious or misconfigured Epoch Resets constitute a denial-of-service vector.

---

# Annex A: SECS/GEM Mapping

For semiconductor manufacturing environments using SECS/GEM (SEMI Equipment Communications Standard):

| SECS/GEM Concept | MQTT v6.0 Mapping |
|---|---|
| Transaction ID (TID) | Stream Sequence Number (0x30) |
| S1F13/S1F14 (Establish Comms) | CONNECT/CONNACK with v6.0 negotiation + Epoch check |
| S2F21 (Remote Start) | PUBLISH to `$queue/secsgem/{device_id}/S2F21` with `v6-semantics: exclusive` |
| S6Fx (Event Reports / FDC) | PUBLISH to `$queue/secsgem/{device_id}/events` + Virtual FETCH for backpressure |
| Multi-block messages | Segmented PUBLISH with sequence continuation; reassembled via Batch Size |
| Link Test (Heartbeat) | FETCH with `Wait Timeout` as a "proof of life" pull |
| Equipment Model Reset | Epoch Reset → Client performs S1F13 re-establishment |

## A.1 Critical Scenario: Process Start Command (S2F21)

In SECS/GEM, S2F21 (Remote Start) is mission-critical. Loss of this command can ruin a wafer.

**Without v6.0:** If broker Node A crashes after accepting S2F21 but before delivery, the command may be silently lost.

**With v6.0:** 1. Host publishes S2F21 with `Sequence: 5001, Epoch: 1` to `$queue/secsgem/tool_001/S2F21` 2. Broker Node A persists to non-volatile storage and assigns Seq 5001 3. Node A crashes; its replica is gone but the Distributed Sequence Counter and message data survive in other nodes' data grid replicas 4. Tool reconnects

with `v6-last-seq: 5000` in CONNECT 5. Node B checks persistent queue: Seq 5001 exists and was never acknowledged 6. Node B resumes delivery: tool receives S2F21 exactly once

---

## Annex B: New Reason Codes

| Code | Name | Description |
|---|---|---|
| `0xA0` | Epoch Reset | Cluster failover caused sequence discontinuity; client must reset idempotency state |
| `0x9B` | Quota Exceeded | Client exceeded Throughput Limit |
| `0x8D` | Queue Full | Queue storage limit reached; message rejected |

# Alternative Approaches to MQTT v6.0

This document explores the design alternatives considered during the development of MQTT v6.0, explains the trade-offs, and justifies the chosen approach.

---

## 1. The Core Design Choice: Breaking vs. Non-Breaking

The central tension in extending MQTT is between **expressiveness** and **compatibility**. Every proposed feature was evaluated on a spectrum:

```
[Pure v5.0 Extension] ←———————————————→ [New Protocol Version]
   (User Properties)      (New Properties)      (New Packet Types)
      No breaks               Safe                  Breaking
```

---

# 2. Alternative A: Pure MQTT v5.0 Extension (Property-Based Shim)

## Description

All v6.0 features encoded entirely as `User Properties` within existing v5.0 packets. No new property IDs, no new packet types.

## Implementation

- Sequence numbers as `User Property: ("v6-seq", "12345")`
- Epoch as `User Property: ("v6-epoch", "2")`
- FETCH as `PUBLISH` to `$SYS/queues/{name}/fetch` with `User Property: ("v6-batch", "100")`
- Consumer modes as `User Property: ("v6-semantics", "competing")`

## Pros

- **Zero compatibility risk.** Works on any MQTT v5.0 broker, any client library, today.
- **No broker changes required.** Logic lives entirely in a HiveMQ Extension Plugin.
- **Fastest time to production.** Can be deployed as a library/plugin without protocol changes.

## Cons

- **Not standardizable.** User properties are opaque strings — no binary parser optimization is possible. This is a permanent workaround, not a standard.
- **Parsing overhead.** Sequence numbers as strings ("4294967295") cost 10 bytes; as 4-byte integers they cost 4 bytes + 1 ID byte = 5 bytes.
- **No protocol-level enforcement.** A broker cannot distinguish a v6.0 sequence-aware publish from a regular publish at the binary level without inspecting all user properties.
- **No `FETCH` semantics at the broker level.** The broker cannot natively throttle push delivery; it requires application-level hacks.

## The Fragmentation Risk

Shipping these features as vendor-specific User Property conventions (without standardization) creates the exact problem standardization prevents. If HiveMQ uses `v6-seq`, EMQX uses `x-seq-number`, and AWS IoT Core uses `aws-sequence`, every customer running multiple brokers needs a translation layer. This is how `$SYS/` became fragmented across brokers — every vendor implemented it differently, and 15 years later there is still no standard. Standardizing the wire representation early prevents this.

## Verdict

**Viable as a transitional shim.** Adopted as the Compatibility Layer (Track B). Not suitable as the long-term specification because it prevents standardization and invites vendor fragmentation.

# 3. Alternative B: MQTT v5.0 with Reserved Property IDs (0x30–0x45)

## Description

Use the unused/reserved property ID space ( `0x30` – `0x45` ) to define new typed properties. No new packet types. Protocol Level remains 5.

## Implementation

- `0x30` : Stream Sequence Number (Four Byte Integer)
- `0x35` : Stream Epoch (Two Byte Integer)
- `0x41` : Throughput Limit (Four Byte Integer)
- `0x42` : Batch Size (Four Byte Integer)
- FETCH still implemented as Virtual FETCH (control topic publish)

## Pros

- **Binary-efficient.** Fixed-width integers instead of string user properties.
- **Fully backward-compatible.** MQTT v5.0 mandates that unknown Property IDs MUST be silently ignored by non-v6 clients and brokers.
- **Minimal parser changes.** Any existing MQTT parser that follows the spec will skip unrecognized properties safely.
- **Works without Protocol Level change.** Mixed v5.0/v6.0 deployments are seamless.

## Cons

- **No native FETCH.** Without a new packet type, pull semantics must still be simulated through control topics, adding round-trip overhead.
- **Subscription option bits still blocked.** MQTT v5.0 mandates bits 6-7 of the SUBSCRIBE options byte MUST be zero; exclusive/competing modes cannot be encoded natively in the packet — only in user properties.
- **Protocol-level ambiguity.** A “Protocol Level 5 client with v6 properties” is technically a v5.0 client; there is no way to formally signal v6.0 conformance without a new level.

## Verdict

**Adopted as the Compatibility Extension profile.** This is what Track B uses. The reserved property IDs are the right mechanism; the missing piece is the FETCH packet.

---

# 4. Alternative C: Native v6.0 with New Packet Type (Chosen Approach)

## Description

Full protocol version bump to Level 6. Introduces FETCH as Control Packet Type 16 — previously reserved in v5.0. New subscription option bits for SQMC modes.

## Implementation

- Protocol Level `6` in CONNECT
- `FETCH` packet (Type 16) as a first-class pull mechanism
- Properties `0x30`, `0x35`, `0x41`, `0x42` as typed binary fields
- SUBSCRIBE options bits 6-7 used for Competing/Exclusive flags
- `$queue/` namespace with mandatory persistence semantics

## Pros

- **Full expressiveness.** Every v6.0 feature has a dedicated, binary-efficient representation.
- **Broker-level enforcement.** A v6.0 broker can natively identify `$queue/` publishes, FETCH requests, and SQMC subscriptions at the parser level without inspecting application data.
- **Formal standardizability.** A clean Protocol Level 6 specification can be submitted to OASIS as a distinct standard.
- **Performance.** FETCH as a dedicated packet eliminates the round-trip overhead of the “publish to a control topic” pattern.

## Cons

- **Breaking change for v5.0 brokers.** A strict v5.0 broker closes the connection immediately upon receiving a Type 16 packet.
- **Breaking change for subscription bits.** A v5.0 broker rejects SUBSCRIBE packets with non-zero reserved bits.
- **Requires ecosystem update.** Client libraries (paho, gmqtt, Eclipse Mosquitto) must be updated to support Level 6.
- **Deployment risk.** Mixed v5.0/v6.0 environments require the Compatibility Layer.

## Verdict

**Chosen as the canonical v6.0 specification.** The breaking changes are manageable with the Compatibility Layer (Alternative B) and negotiation handshake. The long-term correctness of a formal protocol is worth the transition cost.

---

# 5. Alternative D: Replace MQTT Entirely (Kafka / AMQP 1.0 / NATS JetStream)

## Description

Instead of extending MQTT, adopt a different messaging protocol that already provides the required industrial features.

## Comparison

| Feature | MQTT v6.0 | Apache Kafka | AMQP 1.0 | NATS JetStream |
|---|---|---|---|---|
| Lightweight clients | Yes | No | Partial | Yes |
| Edge/IoT footprint | Excellent | Poor | Moderate | Good |
| Named durable queues | Yes (v6.0) | Yes (Topics) | Yes | Yes |
| Pull-based consumption | Yes (FETCH) | Yes (Poll API) | Yes | Yes |
| 32-bit+ sequencing | Yes (v6.0) | Yes (Offset) | No native | Yes |
| Cluster consistency | Epoch-based | ISR/Leader | Partition leader | Raft consensus |
| Existing MQTT ecosystem | Full compatibility | None | Partial bridge | None |
| SECS/GEM mapping | Native | Requires adapter | Requires adapter | Requires adapter |
| Standard body | OASIS | Apache/Confluent | AMQP WG | CNCF |

### Analysis

Kafka provides everything v6.0 proposes, but: - Kafka clients are heavyweight (JVM, 50MB+). Not viable for edge devices or microcontrollers. - The existing investment in MQTT infrastructure (broker, client libraries, security tooling) is significant. - SECS/GEM integration with non-MQTT protocols requires a translation adapter, introducing latency and another failure point. - NATS JetStream is compelling for cloud-native workloads but lacks the industrial IoT ecosystem MQTT has built.

### Verdict

**Not adopted.** The v6.0 extensions preserve the edge/IoT deployment model of MQTT while adding the industrial reliability features. Replacing MQTT would abandon its core advantage in constrained environments.

---

## 6. Alternative E: Extend MQTT Shared Subscriptions (v5.0 `$share/`)

### Description

Enhance the existing MQTT v5.0 `$share/group/topic` mechanism to add message locking, exclusive consumer semantics, and failover logic — without changing the core protocol.

### Pros

- Uses an existing, widely-supported mechanism
- No new packet types or property IDs required
- Implementable today as a broker plugin

### Cons

- `$share/` groups are still session-dependent — the queue vanishes when the last client disconnects. Shared subscriptions distribute messages to active subscribers; they do not buffer messages when no subscriber is connected.
- No way to add explicit sequencing or gap detection within the `$share/` spec — there is no per-message identity that survives across sessions
- No standardized way to express “exclusive” (hot-standby) mode in the subscription syntax
- Consumer failover behavior (what happens when a consumer disconnects mid-processing) is implementation-defined, not standardized
- Extending `$share/` syntax creates a non-standard variation that other broker implementations won’t support
- Message ordering within a shared subscription group is not guaranteed by the spec

### Why `$share/` Is Not a Durable Queue

This is the most common misconception. `$share/` and `$queue/` solve fundamentally different problems:

| Property | `$share/` (v5.0) | `$queue/` (v6.0) |
|---|---|---|
| Survives all consumers disconnecting | No | Yes |
| Survives broker restart (spec-mandated) | No | Yes |
| Message ordering guarantee | No | Yes |
| Gap detection | Impossible | Built-in |
| Named, inspectable entity | No | Yes |

A shared subscription is a **delivery optimization for active subscribers**. A named queue is a **persistent message store**. See Addressing Criticisms for full analysis.

### Verdict

**Partially adopted.** The conceptual model of consumer groups and competing delivery from `$share/` inspired the SQMC design. But v6.0 requires named queue persistence and sequencing that `$share/` fundamentally cannot provide without a new namespace.

---

## 7. Design Decision Matrix

| Criterion | Pure User Props | Reserved Props (0x30+) | Native v6.0 | Kafka/NATS | $share/ Ext |
|---|---|---|---|---|---|
| v5.0 Wire Compat | ✅ Full | ✅ Full | ⚠️ Breaking | ❌ None | ✅ Full |
| Binary Efficiency | ❌ Poor | ✅ Good | ✅ Best | ✅ Best | ✅ Good |
| Native FETCH | ❌ No | ❌ No | ✅ Yes | ✅ Yes | ❌ No |
| Standardizable | ❌ No | ⚠️ Partial | ✅ Yes | ✅ Yes | ❌ No |
| Edge/IoT Viable | ✅ Yes | ✅ Yes | ✅ Yes | ❌ No | ✅ Yes |

| Criterion | Pure User Props | Reserved Props (0x30+) | Native v6.0 | Kafka/NATS | $share/ Ext |
|---|---|---|---|---|---|
| SQMC Enforcement | ❌ App-layer | ⚠️ Partial | ✅ Protocol | ✅ Protocol | ⚠️ Partial |
| Queue Persistence | ❌ Plugin only | ⚠️ Plugin only | ✅ Spec-mandated | ✅ Spec-mandated | ❌ No |
| Time to Deploy | ✅ Immediate | ✅ Immediate | ⚠️ Ecosystem update | ❌ Full migration | ✅ Immediate |

**Recommendation:** Native v6.0 for new deployments with a full MQTT v6.0 ecosystem. Compatibility Layer (Reserved Props) for transitional deployments. Pure User Props shim for proof-of-concept and testing only.

# Critical Perspectives, Rebuttals & Technical Pitfalls

This document provides an honest assessment of the MQTT v6.0 proposal from multiple perspectives: MQTT standards committee members, IoT architects, software engineers, and SREs. For each criticism, a rebuttal and/or mitigation is provided.

---

## Part 1: Standards Committee & Architecture Critique

### Criticism 1: "MQTT's success is its simplicity. v6.0 turns it into a bloated Kafka clone."

**From:** MQTT protocol purists, standards committee members

**The Argument:** MQTT succeeded precisely because it fits in 128KB of RAM and works on a microcontroller. By adding 32-bit sequencing, Epochs, persistent queues, and FETCH semantics, we are violating the core design principle. The protocol will lose its competitive advantage against AMQP and become yet another "enterprise messaging platform."

**Rebuttal:**

1. **"Context Isolation" Defense:** These features are strictly opt-in. A temperature sensor publishing to `temperature/office` uses MQTT v6.0 identically to MQTT v3.1.1 — no sequence numbers, no epochs, no FETCH. The protocol grows upward, not outward. A compliant v6.0 client that doesn't use `$queue/` is binary-indistinguishable from a v5.0 client.

2. **"Standardization of Hacks" Argument:** Every major industrial MQTT deployment has already built these features — in the payload. Sequence IDs, idempotency keys, and consumer group logic are already in production payloads at industrial scale. v6.0 moves these de-facto requirements into the protocol header where brokers can optimize for them. The complexity exists; v6.0 just standardizes it.

3. **Scope Comparison:** The jump from v5.0 to v6.0 is smaller than the jump from v3.1.1 to v5.0. The v5.0 spec added Properties, Reason Codes, Shared Subscriptions, User Properties, and Will Delay — all of which "bloated" the protocol by the same argument. The ecosystem absorbed it; industrial users demanded it.

4. **Standardize Early or Fragment Forever.** The alternative — "ship it as a vendor extension first" — sounds prudent but leads to fragmentation. If HiveMQ ships `$queue/` as a proprietary extension, EMQX, Mosquitto, and AWS IoT Core will build incompatible versions. `$SYS/` is the cautionary tale: every broker implemented it differently, and it remains unstandardized 15 years later. HiveMQ's own Declared Shared Subscriptions are proof that extension-driven solutions do not converge on interoperability. Once three vendors have paying customers on incompatible implementations, the OASIS committee must reconcile three designs instead of evaluating one proposal — and standards processes stall for years. Standardizing before fragmentation is cheaper than standardizing after.

---

### Criticism 2: "The `$queue/` namespace breaks topic hierarchy semantics."

**From:** MQTT architects, broker implementers

**The Argument:** MQTT topics are flat strings with hierarchical separators. The `$` prefix convention is fragile — `$SYS/` is implementation-specific, `$share/` is standard but limited. Creating a new `$queue/` namespace adds confusion, may conflict with existing broker topic trees, and is a "soft break" for v5.0 brokers that might route or reject it incorrectly.

**Rebuttal:**

1. **Existing precedent.** The `$SYS/` and `$share/` namespaces already demonstrate that `$`-prefixed topics are an accepted mechanism for protocol-level semantics. `$queue/` follows the same pattern.

2. **Explicit negotiation mitigates misrouting.** The v6.0 handshake (Section 3.1 of the spec) requires clients to confirm broker v6.0 support before using `$queue/`. If the broker does not confirm, the client MUST NOT use `$queue/` — preventing silent misrouting.

3. **ACL isolation.** The spec mandates `$queue/` access be controlled via ACLs, just like `$SYS/`. A v5.0 broker that doesn't understand `$queue/` will simply apply its default ACL policy (typically: reject `$`-prefixed topics from unprivileged clients), preventing message loss by failing loudly.

**Remaining Risk:** A misconfigured v5.0 broker with open ACLs COULD treat `$queue/foo` as a literal topic and accept publishes, creating a silent reliability hole. **Mitigation:** Document that `$queue/` topics MUST be ACL-blocked on v5.0 brokers.

---

### Criticism 3: "The FETCH packet (Type 16) is a hard break that undermines the whole 'compatible' story."

**From:** Standards committee, library maintainers

**The Argument:** Type 16 was reserved in v5.0 specifically to indicate an error. A v5.0 broker receiving a Type 16 packet MUST close the connection. In a heterogeneous environment with mixed v5.0 and v6.0 brokers, a single misrouted FETCH packet causes cascading disconnections.

**Rebuttal:**

1. **The Compatibility Layer exists for this reason.** The Virtual FETCH mechanism (Section 4.2.2) provides identical semantics using standard v5.0 PUBLISH packets. No environment is forced to use native FETCH.
2. **Protocol-level negotiation prevents misrouting.** A client sets Protocol Level 6 in CONNECT. A v5.0 broker will reject the connection at the CONNECT stage with `Reason Code 0x84 (Unsupported Protocol Version)` — before any FETCH packet is ever sent. The client then falls back to Compatibility Mode. There is no scenario where a FETCH packet reaches a v5.0 broker in a correctly implemented client.
3. **Clean version separation.** Having a Level 6 that is truly distinct from Level 5 is better long-term than a "v5.1" that silently extends in ways that break some brokers but not others. The break is explicit and managed.

---

## Part 2: Software Engineering & Performance Critique

### Criticism 4: "The original proposal's Leader Node model contradicts HiveMQ's masterless architecture."

**From:** HiveMQ engineers, distributed systems architects

**The Argument:** The early draft proposed assigning a "Leader Node" per `$queue/` via consistent hashing, with all publishes routing through that node. HiveMQ is explicitly masterless — all nodes are peers, no consensus protocol (Raft/Paxos) is used, and no node "owns" a topic. The Leader Node model would require HiveMQ to fundamentally change its architecture.

**Resolution (accepted — the proposal was updated):**

This criticism is **correct**. The Leader Node model was removed from the specification in favour of a **Distributed Sequence Counter** approach that is native to HiveMQ's actual architecture:

1. **Distributed Sequence Counter.** Each `$queue/` maintains a single cluster-wide atomic counter in HiveMQ's replication data grid. Any node can increment it atomically (compare-and-swap) to claim the next sequence number. No routing changes are required; any node handles any publish. HiveMQ's existing data grid already provides the distributed primitives needed.

2. **No leader election, no Raft/Paxos.** The atomic counter replaces the entire leader/follower model. Split-brain sequencing (two nodes issuing the same Seq) is prevented by the CAS semantics of the counter, not by funneling all traffic through one node.

3. **Epoch triggers change.** Instead of "leader failover triggers Epoch++", the trigger is "replication quorum loss" — i.e., when a network partition resolves and the counter's replicated state cannot be verified. This maps directly to HiveMQ's partition detection events, which the Extension SDK already exposes.

4. **Hot-queue scaling still works.** If a single `$queue/` becomes a throughput bottleneck, the correct mitigation is application-level sharding ( `$queue/line_1_A` , `$queue/line_1_B` ) — exactly as you would shard a Kafka topic into multiple partitions. The counter CAS overhead per message is negligible compared to the NVMe write latency.

---

### Criticism 5: "Replication lag will cause data loss in the replication gap window."

**From:** SREs, database engineers

**The Argument:** Node A received a publish and incremented the sequence counter to Seq 100, but crashes before the message is replicated to other nodes. Node B has no record of Seq 100. A client that was tracking Seq 100 will detect a gap, but the message is unrecoverable.

**Rebuttal:**

1. **Quorum write prevents the gap.** The spec requires the PUBACK to the publisher only after the message is confirmed on `N` replicas (configurable `Replication-Factor` ). With `Replication-Factor: 2` , Node A crashing never loses the message because Node B already has it before the publisher received its PUBACK.

2. **The atomic counter and quorum write are decoupled.** The sequence number is claimed first (atomic CAS on the counter), then the message is written to quorum. If Node A crashes between those two steps, the claimed Seq number is "orphaned." This creates a one-time gap. The Epoch does NOT need to increment in this case — the surviving cluster knows the gap exists and can communicate it to consumers when they request that sequence range.

3. **Epoch for partition events only.** Epoch increments only when the entire counter quorum is lost (partition event) — not for individual node crashes. This reduces spurious full-resyncs that would otherwise be triggered by routine node restarts.

4. **The v5.0 baseline is worse.** A v5.0 broker silently loses the message with no signal to the client. v6.0 makes the gap explicit, auditable, and recoverable at the application layer.

---

### Criticism 6: "Persistent queues on the broker will cause storage bloat and operational nightmares."

**From:** SREs, operations teams

**The Argument:** If every `$queue/` is persisted to non-volatile storage forever, brokers will eventually run out of disk space. "Leaked queues" (queues no one is reading) will accumulate indefinitely. This is an operational disaster in a long-running production system.

**Rebuttal:**

1. **Mandatory TTL and max-size properties.** The spec requires `v6-queue-ttl` (how long to hold the queue after last consumer disconnect) and `v6-queue-max-size` (message count limit). Both default to implementation-defined values but MUST be configurable. The spec also requires a "drop-oldest" or "reject-new" policy when limits are reached — no silent unbounded growth.
2. **"Tiered Storage" implementation model.** Production brokers (analogous to HiveMQ or Kafka) should implement hot/cold storage: recent messages in RAM (or NVMe), deep backlogs tiered to object storage (S3/GCS). The broker is a transient buffer with bounded local cost.
3. **Operational observability.** 32-bit sequences make "leaked queue" detection trivial: an SRE can query `MAX(Seq) - Last_Consumer_ACK_Seq` to calculate exact backlog depth per queue in real-time. This is far better than the current situation where session-bound queues silently accumulate with no tooling to measure them.

---

## Part 3: SRE & Operational Critique

### Criticism 7: "The FETCH mechanism adds latency compared to push delivery."

**From:** Performance engineers, real-time systems architects

**The Argument:** A FETCH round-trip adds 2× the one-way latency compared to a push delivery. For real-time applications, this is unacceptable.

**Rebuttal:**

1. **Scope clarification.** FETCH is exclusively for `$queue/` topics — durable industrial queues. Standard pub/sub topics (real-time sensor telemetry, command delivery to online devices) continue to use push delivery unchanged. The proposal does not change push semantics for non-queue topics.
2. **Cost-benefit for industrial queues.** In semiconductor FDC or financial messaging, "missing a message" is infinitely more expensive than 5ms of added latency. The FETCH mechanism prevents the host system from crashing under data spikes — which is the #1 cause of unplanned downtime in industrial MQTT deployments.

3. **Long-polling mitigates latency for near-real-time queues.** The `Wait Timeout` property in the FETCH packet enables long-polling: the broker holds the connection open and responds immediately when a new message arrives. Effective latency is near-zero for well-paced queues.

---

### Criticism 8: "Custom property IDs in the reserved range could conflict with future OASIS standardization."

**From:** Standards committee members, protocol engineers

**The Argument:** Properties `0x30` – `0x45` are currently unassigned in MQTT v5.0, but they could be assigned by a future OASIS revision. If v6.0 squats on these IDs and a future v5.1/v6.x assigns different semantics to the same IDs, we have a compatibility disaster.

**Rebuttal:**

1. **This is exactly why we need formal standardization.** The solution to "these IDs might be assigned later" is to submit v6.0 to OASIS and have the IDs formally reserved. The alternative — using User Properties forever — permanently forecloses binary optimization.
2. **The proposal is already in "draft OASIS" format.** The spec is structured to be submitted as an OASIS draft. Early submission reserves the property IDs before any conflict can arise.
3. **Interim risk is manageable.** During the pre-standardization period, the Compatibility Layer (User Properties) can be used exclusively. The reserved property IDs are only activated in native v6.0 brokers that understand the spec. A v5.0 broker will silently ignore them, not misinterpret them.

---

## Technical Pitfalls

### Pitfall 1: Sequence Wraparound at 2^32

**Description:** A 32-bit sequence number wraps around after 4,294,967,295 messages. A high-throughput queue generating 100,000 messages/second exhausts the sequence space in ~43,000 seconds (~12 hours).

**Mitigation:** - For high-throughput queues, the broker MUST handle wraparound gracefully by treating `Seq 0` after `Seq 0xFFFFFFFF` as a continuation (not a gap). - For disambiguation, wraparound can be coupled with an Epoch increment — a full 32-bit cycle increments the Epoch. This gives an effective 48-bit sequence space. - A future revision may introduce 64-bit sequences for ultra-high-throughput use cases (see Annex B of the spec).

---

### Pitfall 2: Idempotency Table Growth

**Description:** Consumers maintaining a “processed messages” idempotency table (for exactly-once semantics) may grow the table unboundedly if sequence numbers are not garbage-collected.

**Mitigation:** - The High-Watermark model (store only the latest processed Seq) is sufficient for in-order delivery queues — O(1) storage. - Only out-of-order delivery (not expected from ordered `$queue/` topics) requires a full set-based idempotency table. - Epoch Resets provide natural garbage-collection boundaries: on Epoch change, discard the entire idempotency table.

---

### Pitfall 3: Competing Consumer Fairness

**Description:** Round-robin distribution may create consumer starvation if one consumer processes messages slowly. Slow consumers receive fewer messages but still hold “locks” on in-flight messages, blocking queue throughput.

**Mitigation:** - The spec allows brokers to implement “least-loaded” instead of strict round-robin: distribute the next message to the consumer with the fewest unacknowledged messages. - A per-consumer `Receive Maximum` limit (inherited from v5.0) caps the number of in-flight locks per consumer. - Consumers that are consistently slow should be flagged via broker metrics and operator intervention.

---

### Pitfall 4: Epoch Reset as a DoS Vector

**Description:** A compromised or misconfigured broker could send spurious Epoch Reset signals, causing all connected clients to discard their idempotency state and re-synchronize simultaneously — a thundering herd.

**Mitigation:** - The spec requires Epoch increments only when the broker cannot guarantee sequence continuity (Section 4.3.2). Any other Epoch increment is a protocol violation. - Clients SHOULD implement Epoch change rate limiting: more than N Epoch changes per hour is anomalous and should trigger an alert and/or connection refusal. - Epoch changes MUST be logged with timestamps and node identifiers for forensic auditing.

---

### Pitfall 5: Virtual FETCH Overhead (Compat Mode)

**Description:** The Virtual FETCH mechanism publishes a message to `$SYS/queues/{name}/fetch` and waits for the broker to respond with the batch. This is two round-trips per batch plus the overhead of the control topic publish.

**Mitigation:** - Use the `Wait Timeout` user property with long-polling to reduce idle round-trips. - For high-throughput applications, pipeline FETCH requests (send the next FETCH before the current batch is fully acknowledged). - This overhead is the explicit trade-off of Compatibility Mode. Native v6.0 FETCH eliminates it;

operators should plan to migrate to Protocol Level 6 for production high-throughput deployments.

---

### Pitfall 6: `$queue/` Namespace Collision with Existing Topics

**Description:** Deployments that already use topic paths containing the string `queue` (e.g., `myapp/queue/events`) may have topic tree management issues or operator confusion.

**Mitigation:** - The `$queue/` prefix begins with `$`, which is already a reserved character in MQTT (standard topics never start with `$`). No collision with user-defined topic spaces is possible. - Operator documentation should clearly distinguish `$queue/` (protocol-level named queues) from `myapp/queue/` (application-level topic paths).

---

## Summary: Risk Matrix

| Criticism / Pitfall | Severity | Probability | Mitigation Quality |
|---|---|---|---|
| Type 16 breaks v5.0 brokers | High | High (mixed env) | ✅ Full (compat layer) |
| Leader node model (removed) | High | Resolved | ✅ Full (distributed counter) |
| Replication lag / data loss | High | Low (with quorum) | ✅ Good (epoch + quorum) |
| Storage bloat | Medium | Medium | ✅ Good (TTL + limits) |
| Sequence wraparound (32-bit) | Low | Low (normal scale) | ✅ Good (epoch cycle) |
| Epoch Reset DoS | Medium | Low | ⚠️ Partial (rate limiting) |
| SUBSCRIBE bits break v5.0 | High | High (native mode) | ✅ Full (user props) |
| Property ID conflict (OASIS) | Medium | Low | ✅ Good (formalize early) |
| Idempotency table growth | Low | Low (ordered queue) | ✅ Good (high-watermark) |
| Virtual FETCH overhead | Low | High (compat mode) | ⚠️ Partial (pipeline) |

# Critical Analyses of MQTT v6.0

> Three independent perspectives critiquing the MQTT v6.0 proposal.
>
> **See also:** Addressing Criticisms — Point-by-Point Rebuttals for responses to specific feedback from HiveMQ internal reviewers, including why `$share/` is not a durable queue, why `Receive Maximum` is not pull-based flow control, and the case for protocol-level vs. application-level reliability primitives.

---

# Part 1 — Security Analyst Perspective

*Authored from the perspective of an industrial cybersecurity engineer with SCADA/ICS background, focused on OT/IT convergence risks.*

---

## 1.1 Executive Verdict

MQTT v6.0 introduces meaningful architectural improvements for industrial messaging but expands the attack surface in ways the proposal does not adequately address. **The proposal is not ready for security-conscious deployment without significant additions to the specification.** The gaps are not fatal, but they are non-trivial.

---

## 1.2 Threat Model Gaps

### 1.2.1 Sequence Number as an Oracle

The Stream Sequence Number ( `0x30` ) is a monotonically increasing, cluster-wide counter assigned to every `$queue/` message. Any authenticated client that can publish and read the PUBACK Seq value gains **exact knowledge of global queue throughput**, message volume, and burst patterns — without consuming a single message.

A threat actor with read-only access to `$queue/scada/events` can infer: - Production rates across a facility - Fault event frequency and duration - Whether a process halt has occurred (Seq stops incrementing)

The proposal does not classify Seq values as sensitive metadata, does not propose per-consumer Seq obfuscation, and does not restrict Seq visibility to consumers. For regulated industries (NERC CIP, IEC 62443), publishing operational telemetry rates to all authenticated clients via a side-channel is a material information disclosure risk.

**Recommendation:** The spec should require that PUBACK Seq values are visible only to the publishing client, not leaked to other clients via CONNACK negotiation or shared subscription acknowledgements. Brokers should support `Seq-Blind` consumer mode where Seq is replaced with a client-local opaque token.

### 1.2.2 Epoch Reset as a Denial-of-Service Vector

Section 4.3.2 specifies that an Epoch increment forces all consumers to clear their High-Watermark and perform a full resync. The Epoch value is carried in CONNACK and PUBLISH packets — it is visible to any client that can connect to the broker.

A threat actor who can induce a cluster partition — or who can forge a CONNACK packet on a weakly-secured network segment (common in OT brownfield) — can trigger mass resync across all consumers, effectively causing a **denial of service on the consumer tier** for the duration of the resync window.

The proposal's mitigation ( `v6-resync-jitter-ms` ) addresses the thundering herd from legitimate partitions but does not address adversarial Epoch injection.

**Recommendation:** Epoch values in CONNACK MUST be authenticated via a broker-signed MAC or HMAC-SHA256, allowing clients to detect forged Epoch increments. This requires TLS mutual authentication (mTLS) to be normative for `$queue/` operations, not advisory.

### 1.2.3 `$SYS/queues/*/fetch` as an Unauthenticated Control Plane

The Virtual FETCH mechanism tunnels FETCH requests through `PUBLISH $SYS/queues/{name}/fetch`. In the compat-mode deployment, the broker extension reads this topic to release message batches.

The proposal does not specify authorization rules for `$SYS/queues/` writes. In most MQTT deployments, `$SYS/` is read-only for clients by convention. However, the proposal requires clients to *publish* to this namespace, which reverses the convention and may bypass ACL rules that blanket-deny `$SYS/` writes to non-admin clients.

A malicious client that can publish to `$SYS/queues/targetqueue/fetch` with `last-seq=0` can force the broker to stream the entire queue history to any consumer group — a data exfiltration path through the broker's own FETCH mechanism.

**Recommendation:** `$SYS/queues/*/fetch` MUST be protected by per-client, per-queue ACL identical to the `$queue/` subscription ACL. The spec must state this explicitly rather than deferring to broker implementation.

### 1.2.4 HWM Manipulation via Message Replay

The exactly-once deduplication relies entirely on the client's in-memory High-Watermark. The spec states that `Seq ≤ HWM → PUBACK but discard`. HWM is not persisted to durable storage in the base spec — it is reconstructed on reconnect.

If a client reconnects after a crash and the broker is still holding in-flight Seq values below the new HWM (derived from the last acknowledged FETCH), the client may re-process messages it already handled, violating exactly-once semantics. The gap between "last Seq the client persisted to its own DB" and "last Seq the broker tracks as committed" is an integrity risk in safety-critical command pipelines.

For `$queue/safety/interlocks` carrying process start/stop commands, duplicate processing of a "process start" command is a physical safety issue, not merely a data integrity issue.

**Recommendation:** Exactly-once guarantees for QoS=1 MUST require broker-side, per-consumer-group committed-HWM persistence (described in performance-analysis.md section 2.2) as normative, not optional. The base spec should not permit a compliant broker to hold HWM only in memory.

---

### 1.3 Missing Security Primitives

| Gap | Risk Level | Mitigation Required |
|---|---|---|
| No mandatory mTLS for `$queue/` | High | Normative mTLS requirement in §4 |
| No Seq visibility access control | Medium | Per-consumer Seq masking option |
| No Epoch authentication | High | Broker-signed Epoch in CONNACK |
| `$SYS/queues/` write ACL undefined | High | Explicit ACL requirement in compat spec |
| HWM not persisted by default | Medium–High | Normative broker-side HWM persistence |
| No message integrity field | Medium | Optional HMAC User Property recommendation |
| No audit trail for SQMC group membership changes | Medium | Mandatory SQMC group change event to `$SYS/` |

---

### 1.4 Positive Security Properties

To be balanced: the proposal does introduce features that *improve* security posture relative to v5.0:

- **Named durable queues** make message provenance auditable (queue name + Seq = immutable event ID for 90-day regulatory retention).

- **Competing consumer mode** eliminates shared subscription race conditions that can cause message loss in QoS=1 — a correctness improvement that benefits audit trails.
- **Epoch tracking** provides a tamper-evident marker: if the Epoch advances unexpectedly, consumers can detect cluster disruption that might indicate an infrastructure attack.

The framework is sound. The spec needs hardening before it is appropriate for IEC 62443 Security Level 2+ environments.

---

# Part 2 — OT SRE Perspective

*Authored from the perspective of a senior site reliability engineer responsible for operational technology infrastructure at a large industrial facility — substations, PLCs, DCS, SCADA, and the middleware connecting them.*

---

## 2.1 Executive Verdict

MQTT v6.0 solves the right problems but creates new operational burdens that the proposal underestimates. **The migration cost for existing OT deployments is significantly higher than the proposal acknowledges.** For brownfield facilities running MQTT v3.1.1 at the edge, v6.0 is a multi-year programme, not a phased upgrade.

---

## 2.2 Operational Concerns

### 2.2.1 The “Two Tracks” Problem Creates Indefinite Parallel Operations

The proposal defines Track A (native v6.0) and Track B (compat extension), recommending “Native v6.0 with an optional Compatibility Layer for hybrid deployments.” In practice, industrial facilities do not retire protocol versions on a planned schedule — brownfield devices stay in service for 10–25 years.

**What this means in the field:** An OT team will run Track B (compat) indefinitely, not as a transition, but as a permanent parallel stack. The compat layer then becomes load-bearing infrastructure that must be maintained across HiveMQ major versions.

Track B is not a “transition path” — it is a *permanent architecture tier* for any facility that cannot replace embedded MQTT clients on PLCs, RTUs, or smart meters. The proposal should acknowledge this and commit to long-term compat layer support with explicit SLA guarantees.

#### 2.2.2 Epoch Reset Operational Impact is Unquantified

Section 4.3.2 specifies that an Epoch reset requires all consumers to perform a full resync from Seq=0. For a `$queue/` with 90 days of regulatory data at 500k msg/sec:

```
90 days × 86,400 sec/day × 500,000 msg/sec = ~3.9 × 10^12 messages
```

A full resync of 3.9 trillion messages is not a recovery operation — it is a service restoration incident measured in **days to weeks**, not minutes. The proposal's staggered resync jitter ( `v6-resync-jitter-ms` ) prevents the thundering herd but does not address the total volume of data that consumers must re-read.

The proposal needs: 1. A normative upper bound on how far back a "full resync" actually reads (e.g., "from the last `committed_hwm`, not from Seq=0"). 2. A mechanism for consumers to declare their own recovery horizon (e.g., "I only need messages from the last 24 hours for real-time dashboards"). 3. Documented broker-side resync budgeting — how many concurrent resyncs can a broker support without degrading live traffic?

#### 2.2.3 `$stream/` and `$log/` Durability Tiers Require New Operational Runbooks

The performance analysis introduces `$stream/` (async) and `$log/` (eventual) namespaces. From an OT operations perspective, these three namespaces have fundamentally different failure modes:

- `$queue/` : Message is either committed or rejected. No ambiguity.
- `$stream/` : Message appears committed (PUBACK issued) but may be lost on node failure before replication. Ops team must assume messages are "probably there."
- `$log/` : PUBACK on local write, eventual consistency, gaps are possible. Ops team must build gap-tolerant consumers for every `$log/` subscriber.

OT operators who are accustomed to a single namespace ( `$queue/` ) with deterministic guarantees now have three namespaces with three different reliability contracts. **Misconfiguring a safety-critical sensor stream from `$queue/` to `$stream/` is a silent reliability regression** — the system continues to operate normally until a node fails, at which point data loss occurs with no alarm.

**Recommendation:** The spec should mandate a mandatory `Durability-Confirmed` property in CONNACK for any client subscribing to `$stream/` or `$log/` , explicitly informing the client of the durability tier. Brokers should refuse `$stream/` subscriptions from clients that have not acknowledged the reduced durability guarantee.

#### 2.2.4 Adaptive Batch Size Tuning Is Not Observable

The `v6-batch-target-ms` property asks the broker to calculate batch size based on "queue throughput." There is no mechanism in the proposal for a consumer to inspect what batch size the broker actually chose, nor to observe the broker's throughput estimate.

In OT environments, when message processing falls behind (a common condition during fault storms), the ops team needs to answer: "Is the broker delivering batches correctly, or is our consumer too slow?" Without visibility into the broker's batch-size calculation, this is a black box diagnostic problem.

**Recommendation:** Add a `v6-batch-actual` User Property to FETCH response PUBLISH packets, reporting the actual batch size used and the broker's throughput estimate at time of dispatch.

#### 2.2.5 SQMC Group Membership Has No Health Signal

The SQMC competing consumer model tracks group membership at the broker. If a consumer silently stalls (network partition at the consumer, not the broker), the broker may continue dispatching messages to the stalled consumer's in-flight lock set indefinitely — blocking the `committed_hwm` from advancing for the entire group.

The proposal does not specify: - A per-consumer in-flight timeout (how long can a lock be held before the broker considers the consumer failed and re-dispatches?) - A SQMC health status endpoint or `$SYS/` topic for group membership monitoring - Alerting or operator notification when `committed_hwm` stalls

In a production SCADA environment, a stalled HWM is a high-severity incident. It must be observable.

---

### 2.3 Deployment Readiness Assessment

| Scenario | v6.0 Readiness | Concern |
|---|---|---|
| Greenfield broker + new OT devices | Ready | Ideal target environment |
| Greenfield broker + legacy MQTT v3 devices | Partial | Track B required indefinitely |
| Existing HiveMQ + v5 clients, upgrade broker | Partial | Extension plugin needed; Epoch semantics change |
| Multi-vendor broker environment | Not ready | SQMC and Epoch semantics are HiveMQ-specific |
| Air-gapped OT network, infrequent updates | Not ready | HWM persistence and Epoch reset recovery not defined for offline operation |

---

### 2.4 What OT SREs Actually Need

The proposal solves the engineering problems well. What is missing is the **operational layer**:

1. **Health and observability APIs** — SQMC group health, HWM progress, resync status, broker-side batch stats, all exposed via `$SYS/` topics or a new `$MGMT/` namespace.
2. **Operational runbooks** for Epoch reset recovery — including expected duration at various queue depths.
3. **Durability tier migration tooling** — safe procedure for moving a topic from `$queue/` to `$stream/` without data loss.
4. **Long-term compat layer commitment** — explicit version support matrix for Track B.

---

# Part 3 — Arlen Nipper Perspective

*Authored from the perspective of Arlen Nipper, co-inventor of MQTT, arguing against the adoption of MQTT v6.0.*

*Note: The views expressed here are a constructed argument representing this perspective for design evaluation purposes. They do not represent statements made by Arlen Nipper.*

---

## 3.1 Opening Statement

I have spent thirty years watching MQTT succeed precisely because it does one thing exceptionally well: it moves small messages reliably over unreliable networks with minimal overhead. The protocol fits in a 128KB microcontroller. It runs over satellite links at 9600 baud. It works in a refinery where the network engineer left the company in 2011 and no one knows what hardware is in the ceiling.

MQTT v6.0 proposes to solve problems that are real, but the solutions it proposes are not MQTT solutions. They are message queue solutions borrowed from AMQP and Kafka and dressed in MQTT clothing. The result is a protocol that will be too complex for the constrained devices MQTT was designed to serve, while being less capable than the systems it is trying to imitate.

---

## 3.2 The Core Argument: Protocol Creep Destroys Interoperability

MQTT's greatest strength is that every compliant broker and client is interoperable. A Mosquitto broker, a HiveMQ cluster, a tiny RTOS client on an ESP32, and an enterprise application on AWS IoT Core all speak the same language. You can replace any component without changing any other.

MQTT v6.0 breaks this in two ways.

**First**, it introduces a new packet type (FETCH, Type 16) that is not backward-compatible. Any broker that does not support FETCH cannot serve v6.0 consumers. Any v6.0 consumer that requires FETCH cannot fall back to a v5.0 broker. The Track B compat layer is explicitly a workaround for this fragmentation, not a solution.

**Second**, it introduces broker-side semantics — SQMC group membership, distributed sequence counters, sliding window HWMs — that are not part of the wire protocol but are required for correct operation. Two brokers that both claim MQTT v6.0 compliance may behave entirely differently when a consumer crashes mid-batch, because the spec leaves the in-flight timeout undefined. This is not interoperability. This is vendor lock-in with a standardised handshake.

---

### 3.3 The Right Tool Exists

Every feature in MQTT v6.0 already exists in a mature, production-proven system. The proposal is asking MQTT to become a subset of these systems:

| v6.0 Feature | Existing Solution |
|---|---|
| Named durable queues | RabbitMQ AMQP queues, since 2007 |
| Pull-based FETCH with batch control | Apache Kafka consumer poll API, since 2011 |
| Competing consumer with exactly-once | AMQP 1.0 link credits + settlement modes |
| Sequence numbering + gap detection | Kafka topic partition offsets |
| Cluster-wide atomic sequence counter | Zookeeper / etcd distributed counter |
| Epoch-based failover signalling | Kafka group coordinator epoch |

The industrial customers who need these features should be using Kafka, RabbitMQ, or AMQP 1.0 at the tier where these features matter — the data historian, the analytics pipeline, the command-and-control system. These are server-to-server or server-to-cloud links where running a Kafka client is entirely feasible.

At the edge — the RTU, the PLC, the smart meter — MQTT v5.0 is entirely sufficient. These devices do not need FETCH semantics. They need to publish telemetry and receive commands. MQTT v5.0 does this well.

---

### 3.4 The MQTT Gateway Pattern Is the Correct Architecture

The proposal acknowledges that many edge devices will remain on MQTT v3.1.1 or v5.0 indefinitely. It responds by creating a compat layer. I would respond differently: **use a gateway**.

```
[Edge Device MQTT v5.0] → [Edge Broker (HiveMQ/Mosquitto)]
                                        ↓
                            [Protocol Bridge / Gateway]
                                        ↓
                      [Kafka / RabbitMQ / AMQP 1.0 — full semantics]
```

```
                                    ↓
                        [Analytics / SCADA / Cloud]
```

This architecture: - Keeps edge devices on the protocol they already run - Provides full queue semantics at the tier that needs them - Does not require edge firmware updates - Does not introduce new MQTT broker implementations - Uses battle-tested systems for the queue layer

The proposal essentially reinvents this architecture within a single protocol. That is not simplification — it is complexity concealment.

---

### 3.5 The Constrained Device Problem

Section 3.1 of the proposal states that “all three tiers ( `$queue/` , `$stream/` , `$log/` ) use the same FETCH, Seq, and Epoch semantics.” A compliant v6.0 client must:

1. Track a High-Watermark (or sliding window HWM) persistently across power cycles
2. Detect Epoch changes and discard HWM on Epoch mismatch
3. Issue FETCH packets (or Virtual FETCH via `$SYS/` ) with correct `last-seq` values
4. Handle gap alerts (Seq N missing, resume from N+1)
5. Implement exactly-once deduplication via HWM comparison

This is not a protocol that fits in 128KB. This is not a protocol that a firmware engineer at a meter manufacturer can implement correctly in six months without dedicated protocol expertise. MQTT’s original success came from the fact that a competent embedded developer could read the spec in a day and write a correct client in a week.

The reference Python shim in this proposal is 300 lines of non-trivial async code. That is the minimum viable client. The Java extension is longer. The constrained device story is “use the compat layer and pretend it’s MQTT” — which is precisely what the gateway pattern achieves without protocol fragmentation.

---

### 3.6 A Constructive Alternative

I am not arguing that HiveMQ should not build these features. I am arguing that these features should not be called MQTT v6.0, and should not require an OASIS standards process that will take years, produce inevitable compromises, and lock in design decisions that may not survive first contact with production deployments.

**What I would recommend instead:**

1. **HiveMQ Extension v2 for Advanced Queuing** — implement `$queue/` , SQMC, sequence numbers, and FETCH as a first-class HiveMQ extension, not a protocol revision. Ship it. Let the market validate the semantics. Allow competitors to implement compatible extensions.

2. **An OASIS MQTT Best Current Practice (BCP) document** — define the User Property schema (`v6-seq`, `v6-epoch`, `v6-semantics`) as a standardised extension pattern. This enables interoperability without a wire protocol break.

3. **Five years of production data** — if the HiveMQ extension proves out at DEP scale, with demonstrated adoption across multiple vendors, then bring it to OASIS as a v6.0 proposal with real-world validation behind it.

MQTT became the dominant IoT protocol because it was simple, stable, and widely implemented. Those properties are worth more than any individual feature. The right way to honour that legacy is not to add features — it is to build the features where they belong, at the system layer, and let MQTT remain what it has always been: a lightweight, reliable, interoperable publish-subscribe transport.

> **Author's response:** This is the most reasonable objection to the proposal, and it deserves a direct answer. The extension-first path sounds prudent, but it leads to **fragmentation, not validation.** If HiveMQ ships `$queue/` as a proprietary extension, EMQX, Mosquitto, and AWS IoT Core will each build incompatible versions — similar semantics, different wire formats, different User Property names, different consumer group behavior. This is exactly what happened with `$SYS/`: every broker implemented it differently, and it remains unstandardized 15 years later. HiveMQ's own Declared Shared Subscriptions — built because `$share/` lacks durable queue semantics — are proof that extension-driven solutions do not converge on interoperability without a standard to converge on.
>
> The patterns themselves are already validated. Sparkplug proves application-layer sequencing works. Declared Shared Subscriptions prove durable queue semantics are needed. Every MQTT-to-Kafka bridge in production proves pull-based consumption is needed. What is missing is not proof of concept — it is a standard wire representation. Standardizing early, before vendors fragment, is cheaper than reconciling three incompatible implementations at OASIS five years from now. See Addressing Criticisms — Why Standardize Now for the full argument.

---

## Summary Comparison

| Dimension | Security Analyst | OT SRE | Arlen Nipper |
|---|---|---|---|
| Overall verdict | Needs hardening | Migration cost underestimated | Wrong layer for these features |
| Top concern | Seq as info oracle, Epoch injection | Epoch reset at scale, compat permanence | Protocol fragmentation, constrained device burden |
| Fatal flaw? | No — addressable | No — operational | Yes — misplaced complexity |

| Dimension | Security Analyst | OT SRE | Arlen Nipper |
|---|---|---|---|
| | | gaps | |
| Would adopt? | Yes, with security addendum | Yes, greenfield only | No — gateway pattern preferred |
| Primary ask | Normative mTLS + Seq ACL + Epoch MAC | Observability APIs + resync runbooks | Ship as HiveMQ extension first |

# MQTT v6.0 Performance Analysis: High-Volume Use Cases

> **Focus:** Large distributed energy providers (DEPs), grid SCADA, and industrial IoT at scale — characterised by millions of sensors, sub-second telemetry, burst fault events, and mandatory regulatory audit trails.

---

## 1. Workload Profile

| Dimension | Typical DEP Scale |
|---|---|
| Sensors / endpoints | 1M–10M (smart meters, PMUs, RTUs, substations) |
| Steady-state throughput | 500k–3M msg/sec cluster-wide |
| Burst (fault/storm event) | 10×–50× steady state for 30–120 seconds |
| Message size | 64–512 bytes (telemetry); 1–50KB (commands, recipes) |
| Latency requirement | <10ms for control commands; 100–500ms acceptable for telemetry |
| Retention | 90 days regulatory minimum; 7 years for audit |
| Consumer count | 10–200 competing consumers per queue (analytics pipelines) |

---

# 2. Performance Bottlenecks in the Current Proposal

## 2.1 CAS Counter Contention at Scale

**Mechanism:** The Distributed Sequence Counter requires an atomic CAS increment on the cluster data grid for every `$queue/` PUBLISH. Under contention, CAS degrades from O(1) to O(retries × RTT) as threads spin on the atomic variable.

**Impact at DEP scale:** A single `$queue/scada/events` receiving 500k msg/sec from 50k RTUs means ~10k CAS operations per second per broker node competing for the same counter. At 1ms inter-node RTT, contention-driven retry cycles will cap throughput well below the theoretical maximum.

**Proposed fix — Partitioned Sequence Spaces:**

Assign each broker node a pre-allocated sequence range of size `W` (the "window size"). Nodes increment locally without cross-node CAS until they exhaust their window, then claim the next window atomically.

```
Node 1 window: Seq 1 – 1,000,000        (local counter, no CAS)
Node 2 window: Seq 1,000,001 – 2,000,000 (local counter, no CAS)
Node 3 window: Seq 2,000,001 – 3,000,000 (local counter, no CAS)
```

- Window claiming (CAS) is amortized across `W` messages — at W=1M and 500k msg/sec, each node claims a new window every ~2 seconds.
- Gaps between windows are valid: Seq 1,000,000 → 1,000,001 is a valid "gap" — consumers must tolerate intra-window ordering while the global order is maintained at window boundaries.
- Window size `W` should be a configurable queue property (`v6-seq-window-size`).

**New spec normative:** The Stream Sequence Number MUST be monotonically increasing within a node's assigned window. Global monotonicity across windows is RECOMMENDED but not REQUIRED — consumers MUST treat any Seq > HWM as processable regardless of gap size when the queue uses partitioned sequence windows.

---

## 2.2 High-Watermark Inadequacy Under Burst

**Current spec:** Consumer maintains a single `High-Watermark` integer (last processed Seq). Works for ordered, serial consumption.

**Problem at DEP scale:** During a grid fault event, 50 competing consumers receive messages in parallel. In-flight Seq values span a wide range simultaneously:

```
Consumer 1: processing Seq 10,001 (slow – database write)
Consumer 2: processing Seq 10,050 (fast)
```

```
Consumer 3: processing Seq 10,100 (fast)
```

If Consumer 2 and 3 finish before Consumer 1, their HWM would advance past Consumer 1's in-flight message. If Consumer 1 then crashes, the group HWM is ambiguous — "did we process 10,001?"

**Proposed fix — Sliding Window HWM:**

Replace the single HWM integer with a **min/max window** tracked per consumer group at the broker:

```
Group HWM = {
  committed:  10,000   (all Seq ≤ this are acknowledged by all group members)
  in_flight:  [10,001, 10,002, ..., 10,150]  (dispatched, awaiting PUBACK)
  max_dispatched: 10,150
}
```

- `committed` advances only when all Seq below the next gap are acknowledged.
- The broker tracks in-flight locks as a bitset bounded by `Receive Maximum`.
- Consumer crash recovery: any in-flight Seq belonging to the crashed consumer is re-dispatched to the next available consumer.
- Client-side HWM for exactly-once deduplication remains a single integer (`committed`), not the full window.

**New spec normative:** Brokers implementing SQMC competing consumer mode MUST track a per-group `committed_hwm` (the highest Seq for which all lower Seqs are acknowledged) in addition to the per-consumer in-flight lock set.

---

## 2.3 Quorum Write Latency vs. Real-Time Telemetry

**Current spec:** All `$queue/` PUBLISH operations require a quorum write before PUBACK. At replication factor 2 and 1ms inter-node RTT, this adds 2–5ms per message.

**Impact at DEP scale:** PMU (Phasor Measurement Unit) data arrives at 60 samples/sec per device. A 2–5ms PUBACK delay is acceptable. But for 50k PMUs generating 3M msg/sec total, quorum write serialisation creates head-of-line blocking in the broker's replication pipeline — effective throughput drops by 40–60% compared to async replication.

**Proposed fix — Durability Tier Namespaces:**

Split the `$queue/` namespace into three tiers with different durability contracts:

| Namespace | Durability | Write Path | Use Case |
|---|---|---|---|
| `$queue/` | Synchronous quorum | PUBACK after N replicas | Commands, audit, SECS/GEM S2F21 |

| Namespace | Durability | Write Path | Use Case |
|---|---|---|---|
| `$stream/` | Async replication | PUBACK after local write; replication in background | High-frequency telemetry, PMU data |
| `$log/` | Append-only, eventual | PUBACK immediately; batched replication | FDC data, bulk sensor history |

- The same FETCH, Seq, and Epoch semantics apply to all three tiers.
- `$stream/` and `$log/` topics carry a `Durability` property ( `0x43` ) in PUBLISH indicating the tier: `0x01` = sync quorum, `0x02` = async, `0x03` = eventual.
- Consumers subscribing to `$stream/` or `$log/` MUST tolerate occasional Seq gaps (due to async write failures) and SHOULD NOT use exactly-once semantics based on Seq alone.

---

## 2.4 FETCH Batch Size Tuning for Burst Recovery

**Current spec:** `Batch Size` is a fixed integer per FETCH request.

**Problem:** During burst recovery (after a 60-second grid storm event), a consumer with a 10M-message backlog issuing `batch=100` requests requires 100k round-trips to drain the queue. At 10ms RTT, that is 16 minutes of drain time.

**Proposed fix — Adaptive Batch Size:**

Add two optional FETCH properties:

- `v6-batch-max` : Upper bound on batch size the consumer will accept (consumer protection).
- `v6-batch-target-ms` : Target delivery window in milliseconds. The broker calculates the batch size needed to fill the window based on queue throughput, bounded by `v6-batch-max` .

For a consumer that wants “deliver as many as I can process in 500ms”, the broker calculates:

```
batch = min(v6-batch-max, queue_throughput_per_ms × 500)
```

This eliminates the need for consumers to manually tune batch sizes as queue depth fluctuates.

---

## 2.5 Rate Limiting Granularity

**Current spec:** Throughput Limit (Property `0x41` ) is per-connection in KB/s.

**Problem for DEPs:** A DEP SCADA system has thousands of client connections sharing the same broker. A per-connection limit cannot prevent a single rogue data pipeline from saturating broker NIC bandwidth while legitimate control traffic is dropped.

**Proposed fixes:**

1. **Per-queue rate limit:** Add a `v6-queue-rate-limit` User Property to SUBSCRIBE, specifying max msgs/sec the broker will release from that queue to this consumer group — independent of connection-level limits.

2. **Priority-based admission:** High-priority messages ( `v6-priority: 255` ) bypass the rate limiter. This ensures S2F21 (process start) commands are never delayed by FDC data storms.

3. **Credit-based flow control:** Replace the token-bucket CONNACK approach with an explicit credit system:

   - Broker sends `CREDIT {queue_name, msgs_per_sec}` in CONNACK or a new control topic.
   - Consumer sends `CREDIT_RETURN` when it can accept more.
   - This is analogous to AMQP 1.0's link credits and prevents both flooding and starvation.

---

## 2.6 Epoch Reset Thundering Herd

**Current spec:** On Epoch reset, all consumers connected to the affected queue simultaneously discard their HWMs and begin full resyncs.

**Problem at DEP scale:** With 200 competing consumers on `$queue/grid/events` , a single partition event triggers 200 simultaneous full resyncs — each reading the queue from Seq=0. This is a thundering herd that can exhaust broker I/O for minutes.

**Proposed fix — Staggered Resync:**

Add a `v6-resync-jitter-ms` property to DISCONNECT (Reason Code 0xA0). Each consumer receives a different jitter value (e.g., uniformly distributed over 0–30,000ms). Consumers delay their CONNECT retry and resync by this value. The broker staggers the resyncs, preventing I/O saturation.

For the broker to generate useful jitter values:

```
jitter_for_consumer_i = (consumer_group_size × resync_window_ms / N) × i
```

where `i` is the consumer's ordinal within the group (known from SQMC group membership).

---

## 3. Updated Property Table

| ID | Name | Type | Packets | Purpose |
|---|---|---|---|---|
| `0x30` | Stream Sequence | 4B Int | PUBLISH | Monotonic message ID |
| `0x35` | Stream Epoch | 2B Int | PUBLISH, CONNACK | Cluster era |
| `0x41` | Throughput Limit | 4B Int (KB/s) | CONNACK | Per-connection rate cap |
| `0x42` | Batch Size | 4B Int | FETCH | Max messages per batch |
| `0x43` | **Durability Tier** | 1B Enum | PUBLISH | `0x01` sync, `0x02` async, `0x03` eventual |
| `0x44` | **Batch Target Ms** | 2B Int | FETCH | Target delivery window for adaptive batching |
| `0x45` | **Resync Jitter Ms** | 2B Int | DISCONNECT (0xA0) | Staggered resync delay |

---

## 4. Namespace Additions

| Namespace | Durability | Sequence | Exactly-Once |
|---|---|---|---|
| `$queue/` | Sync quorum | Strict monotonic | Supported |
| `$stream/` | Async replicated | Best-effort monotonic | Not guaranteed |
| `$log/` | Eventual / append | Monotonic within node | Not supported |
| `$SYS/queues/*/fetch` | N/A (control) | N/A | N/A |

---

## 5. Summary: Adaptations for DEP Scale

| Problem | Scale Trigger | Fix |
|---|---|---|
| CAS counter contention | >100k msg/sec per queue | Partitioned sequence windows ( `v6-seq-window-size` ) |
| Single-integer HWM inadequate | >10 competing consumers | Sliding window HWM — committed + in-flight bitset |
| Quorum write latency | >1M msg/sec telemetry | Durability tier namespaces ( `$stream/` , `$log/` ) |
| Slow backlog drain | Post-burst recovery | Adaptive batch size ( `v6-batch-target-ms` ) |
| Per-connection rate limit too coarse | Thousands of connections | Per-queue rate limit + priority admission bypass |
| Epoch reset thundering herd | >50 consumers, partition event | Staggered resync with `v6-resync-jitter-ms` |

# MQTT v6.0 Architecture Diagrams

# 1. System Context (C4)

```
%%{init:{'theme':'base','themeVariables':
{'primaryColor':'#FFFFFF','primaryTextColor':'#212121','primaryBorderColor':'#212121','lineColor
C4Context
    title MQTT v6.0 — System Context

    Person(pub, "Publisher", "Sends sequenced messages to named queues")
    Person(con, "Consumer", "Pulls batches via FETCH; tracks high-watermark")

    System_Boundary(b1, "HiveMQ v6.0 Cluster") {
        System(broker, "Broker", "Assigns Seq/Epoch; enforces $queue/ persistence and SQMC
delivery")
    }

    SystemDb_Ext(store, "Tiered Storage", "Hot (RAM) → Warm (NVMe) → Cold (Object Store)")

    Rel(pub, broker, "PUBLISH + Seq/Epoch", "MQTT v6")
    Rel(con, broker, "FETCH batch=N / SUBSCRIBE", "MQTT v6")
    Rel(broker, con, "PUBLISH Seq+Epoch batch", "MQTT v6")
    Rel(broker, store, "Persist / Evict", "Internal")

    UpdateLayoutConfig($c4ShapeInRow="3", $c4BoundaryInRow="1")
```

---

# 2. Container View: HiveMQ v6.0 (C4)

```
%%{init:{'theme':'base','themeVariables':
{'primaryColor':'#FFFFFF','primaryTextColor':'#212121','primaryBorderColor':'#212121','lineColor
C4Container
    title HiveMQ v6.0 — Internal Containers

    Person(client, "Client", "Publisher or Consumer")

    Container_Boundary(ext, "v6.0 Extension Plugin") {
        Container(intercept, "Publish Interceptor", "Java / HiveMQ SDK", "Injects Seq (0x30)
+ Epoch (0x35)")
        Container(fetch, "FETCH Handler", "Java / HiveMQ SDK", "Releases message batches on
request")
        Container(sqmc, "SQMC Engine", "Java / HiveMQ SDK", "Competing + Exclusive consumer
```

```
logic")
        Container(epoch, "Epoch Manager", "ClusterService", "Detects quorum loss / partition;
increments Epoch")
    }

    Container_Boundary(stor, "Storage") {
        ContainerDb(hot, "Hot Queue", "RAM / NVMe", "$queue/ — active messages")
        ContainerDb(cold, "Cold Archive", "Object Store", "Deep backlog / audit")
    }

    Rel(client, intercept, "PUBLISH $queue/", "MQTT")
    Rel(client, fetch, "FETCH / Virtual FETCH", "MQTT")
    Rel(intercept, hot, "Persist + assign Seq", "")
    Rel(fetch, hot, "Read batch", "")
    Rel(hot, cold, "Evict old messages", "async")
    Rel(epoch, intercept, "Current Epoch", "")
    Rel(fetch, client, "PUBLISH Seq+Epoch batch", "MQTT")
    Rel(sqmc, fetch, "Route by consumer mode", "")

    UpdateLayoutConfig($c4ShapeInRow="4", $c4BoundaryInRow="2")
```

---

## 3. Feature Layers

```
%%{init:{'theme':'base','themeVariables':
{'primaryColor':'#FFFFFF','primaryTextColor':'#212121','primaryBorderColor':'#212121','lineColor
graph LR
    subgraph v5["v5.0 Core (unchanged)"]
        A[PUBLISH / SUBSCRIBE]
        B[CONNECT / CONNACK]
        C[QoS 0 / 1 / 2]
        D[Properties System]
    end

    subgraph v6["v6.0 Extension"]
        E["0x30 Stream Sequence 32-bit"]
        F["0x35 Stream Epoch 16-bit"]
        G["0x41 Throughput Limit"]
        H["0x42 Batch Size"]
        I["FETCH — Type 16"]
        J["$queue/ Namespace"]
```

```
        K["SQMC Competing / Exclusive"]
    end

    subgraph compat["Compat Layer — v5.0 fallback"]
        L["User Props: v6-seq v6-epoch"]
        M["Virtual FETCH via $SYS/"]
    end

    v5 --> v6
    v6 -.->|downgrade| compat

    classDef highlight fill:#FFD600,stroke:#212121,color:#212121
    class I,J highlight
```

---

## 4. New v6.0 Properties

```
%%{init:{'theme':'base','themeVariables':
{'primaryColor':'#FFFFFF','primaryTextColor':'#212121','primaryBorderColor':'#212121','lineColor
block-beta
    columns 3
    block:v6["v6.0 New Property Identifiers"]:3
        p30["0x30  Stream Sequence<br/>Four Byte Int · PUBLISH"]
        p35["0x35  Stream Epoch<br/>Two Byte Int · PUBLISH / CONNACK"]
        p36["0x36  Wait Timeout<br/>Two Byte Int · FETCH"]
        p41["0x41  Throughput Limit<br/>Four Byte Int · CONNACK"]
        p42["0x42  Batch Size<br/>Four Byte Int · FETCH"]
        space
    end

    style p30 fill:#FFD600,stroke:#212121,color:#212121
    style p35 fill:#FFD600,stroke:#212121,color:#212121
    style p36 fill:#FFFFFF,stroke:#212121,color:#212121
    style p41 fill:#FFFFFF,stroke:#212121,color:#212121
    style p42 fill:#FFFFFF,stroke:#212121,color:#212121
```

# MQTT v6.0 Packet Flow Diagrams

## 1. Connection Negotiation

```
%%{init:{'theme':'base','themeVariables':
{'primaryColor':'#FFFFFF','primaryTextColor':'#212121','primaryBorderColor':'#212121','lineColor
sequenceDiagram
    participant C as Client
    participant B as Broker

    C->>B: CONNECT level=6 mqtt-ext=v6.0 last-seq=1234 epoch=2
    alt v6.0 broker
        B-->>C: CONNACK 0x00 mqtt-ext=v6.0 epoch=2 limit=5000KB/s
    else v5.0 + extension
        B-->>C: CONNACK 0x84
        C->>B: CONNECT level=5 mqtt-ext=v6.0
        B-->>C: CONNACK 0x00 mqtt-ext=v6.0
    else legacy v5.0
        B-->>C: CONNACK 0x00
        Note over C: fallback — no v6 features
    end
```

## 2. Publish → Sequence Assignment (masterless)

```
%%{init:{'theme':'base','themeVariables':
{'primaryColor':'#FFFFFF','primaryTextColor':'#212121','primaryBorderColor':'#212121','lineColor
sequenceDiagram
    participant P as Publisher
    participant N as Any Peer Node
    participant C as Cluster Counter
    participant R as Replica Nodes

    P->>N: PUBLISH QoS=1 $queue/line payload
    N->>C: CAS increment → Seq=1001 claimed (atomic)
    N->>N: Persist Seq=1001 Epoch=2 to NVMe
    par quorum write
        N->>R: Replicate Seq=1001
        R-->>N: ACK
```

```
    end
    N-->>P: PUBACK Seq=1001
```

---

## 3. Native FETCH (Protocol Level 6)

```
%%{init:{'theme':'base','themeVariables':
{'primaryColor':'#FFFFFF','primaryTextColor':'#212121','primaryBorderColor':'#212121','lineColor
sequenceDiagram
    participant C as Consumer
    participant B as Broker

    C->>B: SUBSCRIBE $queue/line v6-semantics=competing
    B-->>C: SUBACK

    C->>B: FETCH Type=16 batch=10 last-seq=995
    B-->>C: PUBLISH Seq=996 Epoch=2
    B-->>C: PUBLISH Seq=997 Epoch=2
    B-->>C: PUBLISH Seq=998 Epoch=2
    Note right of B: up to 10 messages per FETCH
    C-->>B: PUBACK 996..998
    Note left of C: HWM → 998
    C->>B: FETCH batch=10 last-seq=998
```

---

## 4. Virtual FETCH (Compat Mode)

```
%%{init:{'theme':'base','themeVariables':
{'primaryColor':'#FFFFFF','primaryTextColor':'#212121','primaryBorderColor':'#212121','lineColor
sequenceDiagram
    participant C as Consumer (shim)
    participant B as Broker + Extension

    C->>B: PUBLISH $SYS/queues/line/fetch v6-batch=10 last-seq=995
    B->>B: Extension reads 10 msgs from $queue/line
    B-->>C: PUBLISH $queue/line v6-seq=996 v6-epoch=2
    B-->>C: PUBLISH v6-seq=997
    Note right of B: up to 10 messages
```

```
    C-->>B: PUBACK 996..997
    C->>B: next fetch request
```

---

## 5. Competing Consumer — Failover

```
%%{init:{'theme':'base','themeVariables':
{'primaryColor':'#FFFFFF','primaryTextColor':'#212121','primaryBorderColor':'#212121','lineColor
sequenceDiagram
    participant B as Broker
    participant C1 as Consumer 1
    participant C2 as Consumer 2
    participant C3 as Consumer 3

    B->>C1: PUBLISH Seq=100 [locked]
    B->>C2: PUBLISH Seq=101 [locked]
    B->>C3: PUBLISH Seq=102 [locked]
    C2-->>B: PUBACK 101 ✓
    C3-->>B: PUBACK 102 ✓
    C1-xB: DISCONNECT (no PUBACK)
    B->>B: unlock Seq=100
    B->>C2: PUBLISH Seq=100 [re-delivered]
    C2-->>B: PUBACK 100 ✓
```

---

## 6. Exclusive Consumer — Hot-Standby

```
%%{init:{'theme':'base','themeVariables':
{'primaryColor':'#FFFFFF','primaryTextColor':'#212121','primaryBorderColor':'#212121','lineColor
sequenceDiagram
    participant B as Broker
    participant C1 as Primary
    participant C2 as Standby

    B->>C1: PUBLISH Seq=200
    B->>C1: PUBLISH Seq=201
    B--xC2: (no delivery)
    C1-->>B: PUBACK 200..201
```

```
    C1-xB: DISCONNECT
    B->>B: promote C2 → Primary
    B->>C2: PUBLISH Seq=202
    C2-->>B: PUBACK 202
```

---

## 7. Gap Detection + Exactly-Once

```
%%{init:{'theme':'base','themeVariables':
{'primaryColor':'#FFFFFF','primaryTextColor':'#212121','primaryBorderColor':'#212121','lineColor
sequenceDiagram
    participant B as Broker
    participant C as Consumer

    B->>C: Seq=500 · process · HWM=500
    B->>C: Seq=501 · process · HWM=501
    Note over B,C: Seq=502 lost in transit
    B->>C: Seq=503 · GAP ALERT (502 missing) · HWM=503
    B->>C: Seq=502 [QoS=1 retry]
    Note over C: 502 ≤ HWM — DISCARD
    C-->>B: PUBACK 502 (discarded)
```

---

## 8. Epoch Reset on Cluster Failover

```
%%{init:{'theme':'base','themeVariables':
{'primaryColor':'#FFFFFF','primaryTextColor':'#212121','primaryBorderColor':'#212121','lineColor
sequenceDiagram
    participant C as Consumer
    participant A as Node A (peer)
    participant B as Node B (peer)

    C->>A: FETCH last-seq=5000 epoch=1
    A-->>C: PUBLISH Seq=5001 Epoch=1 · HWM=5001
    A-xC: Partition — counter quorum lost · B isolated

    C->>B: CONNECT last-seq=5001 epoch=1
    B->>B: Counter quorum was lost · Epoch → 2
```

```
    B-->>C: CONNACK Epoch=2
    Note over C: clear HWM · full resync
    C->>B: FETCH last-seq=0 epoch=2
    B-->>C: PUBLISH Seq=1 Epoch=2
```

# Cluster Failover & Epoch Management Diagrams

> **Architecture note:** HiveMQ is a **masterless, shared-nothing cluster** — all nodes are peers with no permanent leaders and no consensus protocol (Raft/Paxos). Sequence monotonicity is guaranteed by a **Distributed Sequence Counter** (atomic CAS) in HiveMQ's replication data grid, not by sticky routing to a leader node.

---

## 1. Masterless Cluster — Any Node Sequences Any Publish (C4)

```
%%{init:{'theme':'base','themeVariables':
{'primaryColor':'#FFFFFF','primaryTextColor':'#212121','primaryBorderColor':'#212121','lineColor
C4Context
    title HiveMQ v6.0 — Masterless Cluster (all nodes are peers)

    Person(pub, "Publisher")
    Person(con, "Consumer")

    System_Boundary(cluster, "HiveMQ Cluster — no leaders, no routing constraints") {
        System(n1, "Node 1", "Peer node · handles any publish or FETCH")
        System(n2, "Node 2", "Peer node · handles any publish or FETCH")
        System(n3, "Node 3", "Peer node · handles any publish or FETCH")
        System(counter, "Distributed Seq Counter", "Cluster data grid · atomic CAS per
$queue/")
    }

    Rel(pub, n1, "PUBLISH $queue/line", "any node")
    Rel(pub, n2, "PUBLISH $queue/events", "any node")
    Rel(con, n3, "FETCH $queue/line", "any node")
    Rel(n1, counter, "CAS increment → claim Seq N", "")
    Rel(n2, counter, "CAS increment → claim Seq N", "")
    Rel(n1, n2, "Replicate message+Seq", "data grid")
    Rel(n2, n3, "Replicate message+Seq", "data grid")
```

```
    UpdateLayoutConfig($c4ShapeInRow="4", $c4BoundaryInRow="1")
```

---

## 2. Sequence Assignment — Distributed Counter

```
%%{init:{'theme':'base','themeVariables':
{'primaryColor':'#FFFFFF','primaryTextColor':'#212121','primaryBorderColor':'#212121','lineColor
sequenceDiagram
    participant P as Publisher
    participant N as Any Node
    participant C as Cluster Counter
    participant R as Replica Nodes

    P->>N: PUBLISH $queue/line payload
    N->>C: CAS increment → claim Seq=1001
    C-->>N: Seq=1001 confirmed (atomic)
    N->>N: Persist msg+Seq=1001 locally
    par quorum write
        N->>R: Replicate Seq=1001
        R-->>N: ACK (quorum met)
    end
    N-->>P: PUBACK Seq=1001
    Note over N,C: Concurrent publish on any node gets Seq=1002
```

---

## 3. Node Crash — No Election Required

```
%%{init:{'theme':'base','themeVariables':
{'primaryColor':'#FFFFFF','primaryTextColor':'#212121','primaryBorderColor':'#212121','lineColor
sequenceDiagram
    participant P as Publisher
    participant A as Node A
    participant C as Cluster Counter
    participant B as Node B (peer)

    P->>A: PUBLISH $queue/line
    A->>C: CAS → Seq=1099 claimed
```

```
    A->>A: Persist Seq=1099 (quorum write to B)
    A-->>P: PUBACK 1099
    A-xC: Node A crashes
    Note over B: B already has Seq=1099 via quorum write<br/>Epoch unchanged — no resync
needed
    P->>B: PUBLISH $queue/line (reconnects to B)
    B->>C: CAS → Seq=1100 claimed
    B-->>P: PUBACK 1100
```

---

## 4. Partition Event — When Epoch Increments

```
%%{init:{'theme':'base','themeVariables':
{'primaryColor':'#FFFFFF','primaryTextColor':'#212121','primaryBorderColor':'#212121','lineColor
sequenceDiagram
    participant P as Publisher
    participant A as Node A (partitioned)
    participant B as Node B (surviving)
    participant C as Cluster Counter

    Note over A,B: Network partition splits cluster
    P->>A: PUBLISH (partition side)
    A->>A: Cannot reach quorum for CAS
    A-->>P: PUBLISH rejected — 0x97 Quota Exceeded
    Note over A: CAS refused — quorum unreachable

    Note over A,B: Partition heals
    B->>C: Counter state verified
    Note over B: Quorum lost → Epoch++, notify consumers<br/>Quorum intact → Epoch unchanged
```

---

## 5. Failure Outcomes Decision Tree

```
%%{init:{'theme':'base','themeVariables':
{'primaryColor':'#FFFFFF','primaryTextColor':'#212121','primaryBorderColor':'#212121','lineColor
flowchart TD
    FAIL["Node crash or<br/>partition heals"] --> Q1{"Quorum write<br/>completed for<br/>all
in-flight msgs?"}
```

```
    Q1 -->|Yes| OK["Same Epoch<br/>Peers have full data<br/>No client action"]
    Q1 -->|No — orphaned Seq| Q2{"Counter quorum<br/>survived?"}

    Q2 -->|Yes| GAP["Gap in sequence range<br/>Epoch unchanged<br/>Consumers notified
of<br/>missing Seq range"]
    Q2 -->|No — partition split counter| EPOCH["Epoch++<br/>Broadcast new Epoch<br/>Clients
full-resync"]

    classDef highlight fill:#FFD600,stroke:#212121,color:#212121
    classDef critical fill:#212121,stroke:#212121,color:#FFFFFF

    class OK highlight
    class EPOCH critical
```

---

## 6. Client Reconnect Decision Tree

```
%%{init:{'theme':'base','themeVariables':
{'primaryColor':'#FFFFFF','primaryTextColor':'#212121','primaryBorderColor':'#212121','lineColor
flowchart TD
    RC["Client reconnects<br/>last-seq=N epoch=E<br/>(any peer node)"] -->
E{"Epoch<br/>matches?"}

    E -->|Yes| S{"Seq N in<br/>data grid?"}
    E -->|No — incremented| RESET["CONNACK new Epoch<br/>Client clears HWM<br/>Full resync
from Seq=0"]

    S -->|Yes| RESUME["Resume from N+1<br/>No disruption"]
    S -->|No — orphaned Seq| GAP["Resume from earliest<br/>Flag gap range to client<br/>Epoch
unchanged"]

    classDef highlight fill:#FFD600,stroke:#212121,color:#212121
    classDef critical fill:#212121,stroke:#212121,color:#FFFFFF

    class RESUME highlight
    class RESET critical
```

---

## 7. Tiered Storage

```
%%{init:{'theme':'base','themeVariables':
{'primaryColor':'#FFFFFF','primaryTextColor':'#212121','primaryBorderColor':'#212121','lineColor
graph LR
    subgraph Broker
        HOT["HOT<br/>RAM / NVMe<br/>~1k msgs · sub-ms"]
        WARM["WARM<br/>NVMe SSD<br/>~1M msgs · ~1ms"]
    end
    COLD["COLD<br/>Object Store<br/>unlimited · ~100ms"]

    PUB["Publisher"] -->|write| HOT
    HOT -->|evict| WARM
    WARM -->|evict| COLD

    CON1["Consumer<br/>(recent)"] -->|FETCH| HOT
    CON2["Consumer<br/>(backlog)"] -->|FETCH| WARM
    AUD["Audit / Replay"] -->|read| COLD

    classDef highlight fill:#FFD600,stroke:#212121,color:#212121
    class HOT highlight
```

## 8. Epoch Timeline

```
%%{init:{'theme':'base','themeVariables':
{'primaryColor':'#FFFFFF','primaryTextColor':'#212121','primaryBorderColor':'#212121','lineColor
timeline
    title $queue/production_line · Epoch History
    section Epoch 1
        Seq 1–5000  : All nodes healthy · quorum writes succeed
        Node A crash : Quorum on B+C intact · data preserved · Epoch unchanged
        Seq 5001+   : B and C continue without interruption
    section Epoch 2
        Partition event : Counter quorum lost · Epoch incremented to 2
        Seq 0+      : All consumers resync to new epoch
```