



INFORMATION  
TECHNOLOGY  
UNIVERSITY

## Software Development & Construction

### Quiz 2

### Docker & Kubernetes Challenge

**Muhammad Hamza**

**BSSE23001**

**Muhammad Sarmad**

**BSSE23013**

**Hafiz Azfar Umar Sheikh**

**BSSE23064**


# PHASE 1: Container Bootcamp

## Nginx image container:

```
PS C:\Users\Azfar> docker ps
CONTAINER ID IMAGE COMMAND CREATED STATUS PORTS NAMES
f35ae4dcbb6c nginx "/docker-entrypoint..." 2 minutes ago Up 2 minutes 0.0.0.0:8081->80/tcp, ::1:8081->80/tcp temp-nginx
PS C:\Users\Azfar> docker stop f35ae4dcbb6c
f35ae4dcbb6c
PS C:\Users\Azfar>
```

## V1 of custom nginx:

```
PS C:\Users\Azfar\Documents\GitHub\SCD-quizz2\phase-1> docker ps
CONTAINER ID IMAGE COMMAND CREATED STATUS PORTS NAMES
720b589439ea c-nginx:v1 "/docker-entrypoint..." 56 seconds ago Up About a minute 0.0.0.0:8082->80/tcp, ::1:8082->80/tcp custom-app
PS C:\Users\Azfar\Documents\GitHub\SCD-quizz2\phase-1>
```




Hello from my Custom Container!

This is the initial version (v1).

## Changing content while container is running:

```
PS C:\Users\Azfar\Documents\GitHub\SCD-quizz2\phase-1> docker exec -it custom-app /bin/bash
root@720b589439ea:/# echo "<h1>CHALLENGE COMPLETE!</h1><p>I changed this content while the container was running.</p>" > /usr/share/nginx/html/index.html
root@720b589439ea:/# cat index.html
<h1>CHALLENGE COMPLETE!</h1><p>I changed this content while the container was running.</p>
root@720b589439ea:/# exit
exit
```




CHALLENGE

changed this content while the container was running.

## Rebuilt v2 image:

REPOSITORY	SIZE	TAG	IMAGE ID	CREATED
c-nginx	225MB	v2	9334293812d4	About a minu
c-nginx	225MB	v1	55075d8e557a	26 minutes a
go	225MB	latest	553f64aecdc3	11 days ago
nginx	223MB	v1	18b4753178ba	12 days ago
cicd-demo				

CONTAINER ID	IMAGE	COMMAND	CREATED	STATUS	PORTS	NAMES
b95671a46743	c-nginx:v2	"/docker-entrypoint...."	About a minute ago	Up About a minute	0.0.0.0:8083->80/tcp, [::]:8083->80/tcp	custom-app-v2




**Hello from my Custom Container!**

**This is the newer version (v2).**

## Phase 2: App to Containers

### Pushing image:

PS D:\Github\Projects\SCD-quiz2\app> cd .. /
PS D:\Github\Projects\SCD-quiz2> docker tag devops-fortune:v2 mhamza0987/devops-fortune:v2
PS D:\Github\Projects\SCD-quiz2> docker push mhamza0987/devops-fortune:v2
The push refers to repository [docker.io/mhamza0987/devops-fortune]
5fld80ddf2c5: Pushed
f18232174bc9: Pushed
5b917ff1eb75: Pushed
c89ee076f3e5: Pushed
1e5a4c89ceef: Pushed
cc09213fdal2: Pushed
3ed637fd8ff0: Pushed
dd71dde834b5: Pushed
25ff2da83641: Pushed
V2: digest: sha256:4e1b4823c6d6507d8372ee87cf4b6e61bb3eb6409074855df312fe6627ce9419 size: 856
PS D:\Github\Projects\SCD-quiz2> -



## Yaml files:

```
kubernetes > app-service.yaml
 1  apiVersion: v1
 2  kind: Service
 3  metadata:
 4    name: fortune-service
 5  spec:
 6    type: NodePort
 7    selector:
 8      app: fortune-app
 9    ports:
10      - port: 80
11        targetPort: 3000
12        nodePort: 30007
```


```
5 index.html      app-service.yaml  app-deployment.yaml X redis-deployment.y
kubernetes > app-deployment.yaml
1  apiVersion: apps/v1
2  kind: Deployment
3  metadata:
4    name: fortune-app
5  spec:
6    replicas: 2
7    selector:
8      matchLabels:
9        app: fortune-app
10   template:
11     metadata:
12       labels:
13         app: fortune-app
14   spec:
15     containers:
16       - name: fortune-app
17         image: mhamza0987/devops-fortune:latest
18         imagePullPolicy: Always
19         ports:
20           - containerPort: 3000
21         env:
22           - name: REDIS_HOST
23             value: "redis-db"
```

```
index.html X app-service.yaml app-deployment.yaml redis-deployment.yaml X
kubernetes > redis-deployment.yaml
1  apiVersion: apps/v1
2  kind: Deployment
3  metadata:
4    name: redis-deployment
5  spec:
6    replicas: 1
7    selector:
8      matchLabels:
9        app: redis
10   template:
11     metadata:
12       labels:
13         app: redis
14     spec:
15       containers:
16         - name: redis
17           image: redis:alpine
18         ports:
19           - containerPort: 6379
20   ---
21   apiVersion: v1
22   kind: Service
23   metadata:
24     name: redis-db
25   spec:
26     selector:
27       app: redis
28     ports:
29       - protocol: TCP
30         port: 6379
31         targetPort: 6379
```

## Pods:

```
PS D:\Github\Projects\SCD-quiz2> kubectl apply -f kubernetes/redis-deployment.yaml
deployment.apps/redis-deployment created
service/redis-db created
PS D:\Github\Projects\SCD-quiz2> kubectl apply -f kubernetes/app-deployment.yaml
deployment.apps/fortune-app created
PS D:\Github\Projects\SCD-quiz2> kubectl apply -f kubernetes/app-service.yaml
service/fortune-service created
PS D:\Github\Projects\SCD-quiz2> kubectl get pods
NAME           READY   STATUS    RESTARTS   AGE
fortune-app-74855f4c46-ctbwp   1/1     Running   0          7s
fortune-app-74855f4c46-qqcccd  0/1     ContainerCreating   0          7s
redis-deployment-78f87f4588-2bg95 1/1     Running   0          13s
PS D:\Github\Projects\SCD-quiz2> kubectl get pods
NAME           READY   STATUS    RESTARTS   AGE
fortune-app-74855f4c46-ctbwp   1/1     Running   0          10s
fortune-app-74855f4c46-qqcccd  1/1     Running   0          10s
redis-deployment-78f87f4588-2bg95 1/1     Running   0          16s
PS D:\Github\Projects\SCD-quiz2>
```

```
PS D:\Github\Projects\SCD-quiz2> kubectl port-forward svc/fortune-service 8080:80
Forwarding from 127.0.0.1:8080 -> 3000
Forwarding from [::1]:8080 -> 3000
Handling connection for 8080
Handling connection for 8080
Handling connection for 8080
```



## Phase 3 Multi-Service App

Docker-compose.yml:

```
↳ docker-compose.yml ✘
  ↳ docker-compose.yml
  1   version: '3.8'
  2
  3   services:
  4     app:
  5       build: ./app
  6       ports:
  7         - "3000:3000"
  8       environment:
  9         - REDIS_HOST=redis_db
 10      depends_on:
 11        - redis_db
 12      networks:
 13        - devops-net
 14
 15      redis_db:
 16        image: redis:alpine
 17        container_name: redis_container
 18        ports:
 19          - "6379:6379"
 20        networks:
 21          - devops-net
 22        volumes:
 23          - redis-data:/data
 24
 25      networks:
 26        devops-net:
 27          driver: bridge
 28
 29      volumes:
 30        redis-data:
```

## Building docker-compose up:

```
PS O:\Github\Projects\SCD-quizz> docker-compose up -d --build
time="2023-11-30T10:41:03+05:00" level=warning msg="O:\Github\Projects\SCD-quizz\docker-compose.yml: the attribute 'version' is obsolete, it will be ignored, please remove it to avoid potential confusion"
[+] Building 4.4s (13/13) FINISHED
   ⠄ [internal] load local base definitions
   ⠄ ⠄ reading from file .env
   ⠄ ⠄ [internal] load .env variables from file .env
   ⠄ ⠄ [internal] transfer Dockerfile to ./app
   ⠄ ⠄ [internal] load metadata for docker.io/library/node:18-alpine
   ⠄ ⠄ [auth] library/docker@sha256:890c480c504c28fd3ebc49833f249011d118943588d0a31cc90c480ca29d5e
   ⠄ ⠄ [internal] load .dockerignore
   ⠄ ⠄ [internal] load build context
   ⠄ ⠄ ⠄ [internal] copy files to cache
   ⠄ ⠄ ⠄ [cache] 74/5  WORKDIR /usr/src/app
   ⠄ ⠄ ⠄ [cache] 74/5  COPY package.json
   ⠄ ⠄ ⠄ [cache] 74/5  RUN npm install
   ⠄ ⠄ ⠄ [cache] 74/5  COPY .
   ⠄ ⠄ ⠄ [internal] exporting to image
   ⠄ ⠄ ⠄ [internal] exporting manifest sha256:f44ec01c42e627321fc43b7fb8ca126d93f90b882011a777fb023627062a08
   ⠄ ⠄ ⠄ [internal] exporting config sha256:61278771ed01f88aef2b44e88a2029ff073a64ef590d2f109f81716687
   ⠄ ⠄ ⠄ [internal] exporting secrets sha256:40375561e811254ff2d9e779a5e81137672e513b00d10c49a61d35c120e9891c01
   ⠄ ⠄ ⠄ [internal] saving to docker.io/library/scd-quizz:app:latest
   ⠄ ⠄ ⠄ [internal] untagging to docker.io/library/scd-quizz:app:latest
   ⠄ ⠄ ⠄ [internal] resolving provenance for metadata file
scd-quizz-app          up-to-date
network scd-quizz-devops-net      created
volume scd-quizz_redis-data      created
container redis-container        started
container scd-quizz-app-1        started
PS O:\Github\Projects\SCD-quizz>
```


```
PS O:\Github\Projects\SCD-quizz> docker-compose logs -f app
time="2023-11-30T10:43:47+05:00" level=warning msg="O:\Github\Projects\SCD-quizz\docker-compose.yml: the attribute 'version' is obsolete, it will be ignored, please remove it to avoid potential confusion"
app-1 | Devops Fortune App listening at http://localhost:3000
app-1 | connected to Redis
```

## Removing and restarting service:

```
PS O:\Github\Projects\SCD-quizz> docker-compose rm -f --force redis_db
time="2023-11-30T10:46:08+05:00" level=warning msg="O:\Github\Projects\SCD-quizz\docker-compose.yml: the attribute 'version' is obsolete, it will be ignored, please remove it to avoid potential confusion"
Container redis_container stopped
going to remove redis_container
[+] Removing 1/1
Container redis_container removed
PS O:\Github\Projects\SCD-quizz> docker-compose up
time="2023-11-30T10:47:40+05:00" level=warning msg="O:\Github\Projects\SCD-quizz\docker-compose.yml: the attribute 'version' is obsolete, it will be ignored, please remove it to avoid potential confusion"
Container redis_container started
container scd-quizz-app-1 running
PS O:\Github\Projects\SCD-quizz>
```

## Killing backend and recovery:

```
PS D:\Github\Projects\SCD-quiz2> docker kill $(docker ps -qf "name=scd-quiz2-app")
2086027532a7
PS D:\Github\Projects\SCD-quiz2>
```



```
PS D:\Github\Projects\SCD-quiz2> docker-compose up --no-color --force-recreate
time="2023-11-30T10:53:51+05:00" level=warning msg="D:\Github\Projects\SCD-quiz2\docker-compose.yml: the attribute `version` is obsolete, it will be ignored, please remove it to avoid potential confusion"
  container: redis_container
  container: scd-quiz2-app-1
PS D:\Github\Projects\SCD-quiz2>
```



## Phase 4: CI/CD War Zone

## Initializing:

The screenshot shows two Jenkins web pages side-by-side.

The top page is titled "New credentials - Jenkins" and shows the configuration for a "Username with password" credential. The fields filled are:

- Scope:** Global (Jenkins, nodes, items, all child items, etc.)
- Username:** mihirreddy
- Password:** mihirreddy
- ID:** dockerhub-cred-id
- Description:** DockerHub Credential

A blue "Create" button is at the bottom.

The bottom page is titled "New Item - Jenkins" and shows the "New Item" dialog. It has the following details:

- Error on item name:** Fortune-App-OCID
- Select an item type:** Pipeline

The "Pipeline" option is highlighted and described as:

Pipeline  
Distributes long-running activities that span multiple build agents. Suitable for building pipelines (formerly known as workflow) and/or organizing complex activities that don't easily fit in freestyle job-type.

The other options shown are:

- Freestyle project:** Classic, general-purpose job-type that checks out from up to one SCM repository build steps serially followed by post-build steps like archiving artifacts and sending email notifications.
- Multi-configuration project:** Suitable for projects that need a large number of different configurations, such as testing on multiple environments, platform-specific builds, etc.
- Folder:** Creates a container that stores related items in it. Useful for grouping things together. Unlike view, which is just a filter, a folder creates a separate navigation, so you can have multiple things of the same name as long as they are in different folders.

A blue "OK" button is at the bottom of the dialog.

Jenkins Fortune-App-CDI Configuration

General Triggers Pipeline Advanced

**Triggers**

Set up automated actions that start your build based on specific events, like code changes or scheduled times.

Build after other projects are built...  Build periodically...  GitHub Branches  GitHub Pull Requests...  GitHub hook trigger for GITScm polling...  Poll SCM...  Schedule...  ....

No schedule, so will only run due to SCM changes if triggered by a post commit hook.

Ignore post commit hooks...  Trigger builds remotely (e.g., from sshd)...

**Save** **Apply**

Jenkins Fortune-App-CDI Configuration

General Triggers Pipeline Advanced

**Pipeline**

Define your Pipeline using Groovy (Directly or pull it from source control).

**Definition**

Pipeline script from SCM

SCM

GR

Repositories


Repository URL: https://github.com/hansj3064/SCD-quozpt

Credentials

none

Advanced


**Save** **Apply**



The screenshot shows the Jenkins Pipeline configuration page for a pipeline named 'Fortune-App-CI\_CD'. The left sidebar has tabs for 'General', 'Triggers', 'Pipeline', and 'Advanced'. The 'Pipeline' tab is selected. The main area has sections for 'Additional Behaviours' (with a '+ Add' button), 'Script Path' (containing 'Jenkinsfile'), and 'Lightweight checkout' (which is checked). Below these are sections for 'Postfix Syntax' and 'Advanced' (with a dropdown menu showing 'Advanced'). At the bottom are 'Save' and 'Apply' buttons.

**Note:** The pipeline checks the repo after every min and if there is a commit then it triggers the ci/cd

## Jenkinsfile:



```
git commit -am "ci/cd test"
git push origin master

jenkinsfile
  pipeline {
    stages {
      stage('Build Docker Image') {
        steps {
          script {
            docker.withRegistry('', registryCredential) {
              dockerImage.run()
              dockerImage.push('latest')
            }
          }
        }
      }
      stage('Push to Registry') {
        steps {
          script {
            docker.withRegistry('', registryCredential) {
              dockerImage.push('latest')
            }
          }
        }
      }
      stage('Deploy to Kubernetes') {
        steps {
          sh 'kubectl apply -f kubernetes/app-deployment.yaml'
          sh 'kubectl apply -f kubernetes/app-service.yaml'
          sh 'kubectl apply -f kubernetes/redis-deployment.yaml'
          sh 'kubectl set image deployment/fortune-app=dockerhub/fortune-app:$(DOCKER_IMAGE):${env.BUILD_NUMBER}'
          sh 'kubectl rollout status deployment/fortune-app'
        }
      }
    }
  }
```

Jenkins Fortune-App-OCI

Stage View

	Declarative Checkout SCM	Checkout Code	Build Docker Image	Push to Hub	Deploy to Kubernetes
Average stage time: (last run time: ~3min 32s)	2s	5s	7s	2min 56s	22s
Run 30	1	2s	5s	2min 56s	27s
Run 31	1	2s	5s	5min 23s	17s

Builds

- #3 7:21AM
- #2 10:48AM
- #1 11:17AM

Permalinks

REST API Jenkins 2.58.2

## Making a commit:

```

commit 5e030000
Author: [REDACTED] <[REDACTED]>
Date:   Mon Mar 12 11:17:00 2018 +0000

Code Change and Updated

```

Changes

src/app/app.module.ts

```


app.get('/hello/:name', (req, res) => {
  const randomName = fortunes[Math.floor(Math.random() * fortunes.length)];
  res.send(`{
    "name": "${randomName}",
    "text": "Hello ${req.params.name}!"}
  `);
});

export default app;

```

git commit -am "Code Change and Updated"

git push origin master



## Pipeline trigger:

The screenshot shows two Jenkins pages for the 'Fortune-App-CDI' pipeline.

**Stage View:** This view displays the stages of the pipeline: Declarative Checkout SCM, Checkout Code, Build Docker Image, Push to Hub, and Deploy to Kubernetes. Each stage has a progress bar and a duration. The 'Push to Hub' stage is currently active.

Stage	Declarative Checkout SCM	Checkout Code	Build Docker Image	Push to Hub	Deploy to Kubernetes
Declarative Checkout SCM	2s	9s	12s	1min 23s	24s
Checkout Code	2s	9s	12s	20s	24s
Build Docker Image	1s	9s	37s	20s	23s
Push to Hub	2s	9s	9s	18s	41s
Deploy to Kubernetes	2s	2s	8s	1min 23s	17s

**Build #6:** This view provides detailed information about the latest successful build. It includes the build number (#6), timestamp (Nov 30, 2025, 7:59:29 AM), and a note that it was triggered by an SCM change. It also shows the run script, git revision, repository URL, and changes made.

Build #6 (Nov 30, 2025, 7:59:29 AM)

Started 3 min 47 sec ago  
Took 1 min 0 sec

Marked by an SCM change

This run spent:

- 4.8 sec waiting
- 1 min 2 sec build duration
- 1 min 7 sec total from scheduled to completion

git Revision: 0daaf51d35bfbef32a7bd9f1138badcde8e691  
Repository: https://github.com/nishantkumar4/CDI-poc2.git  
Changes:  
1. Code Changed and Updated (details / githubdiff)  
2. updated (details / githubdiff)

## Pods and deployments:

The screenshot shows the Docker Desktop interface with the Kubernetes dashboard open. The left sidebar has 'Kubernetes' selected. The main area is divided into three sections: Deployments, Pods, and Nodes/Services.

Name	Status	Pods	Name	Status
fortune-app	Available	2/2	redis-deployment-7bf874588-jjhx	Running
redis-deployment	Available	1/1	fortune-app-5cfb458f7-gn9t4	Running
			fortune-app-5cfb458f7-lrbsk	Running

Name	Status	Name	Cluster IP	Ports
docker-desktop	Ready	kubernetes	10.96.0.1	443/TCP
		fortune-service	10.106.251.188	80/TCP
		redis-db	10.96.19.60	6379/TCP

## Cleanup:

Windows PowerShell

```
PS D:\Github\Projects\SCD-quiz2> kubectl delete deployment --all
deployment.apps "fortune-app" deleted from default namespace
deployment.apps "redis-deployment" deleted from default namespace
PS D:\Github\Projects\SCD-quiz2> kubectl delete services --all
service "fortune-service" deleted from default namespace
service "kubernetes" deleted from default namespace
service "redis-db" deleted from default namespace
PS D:\Github\Projects\SCD-quiz2>
```

The screenshot shows the Docker Desktop interface with the Images tab selected in the sidebar. It displays a list of images from the 'My Hub' section, including 'inhamza0987/fortune-app' and 'inhamza0987/cafe-app'.

Tags	OS	Vulnerabilities	Last pushed	Size	Actions
v1	Linux	0	2 minutes ago	47.87 MB	[Pull] [Delete]
v2	Linux	0	2 minutes ago	47.87 MB	[Pull] [Delete]
v3	Linux	0	2 minutes ago	47.87 MB	[Pull] [Delete]
v4	Linux	0	2 minutes ago	47.87 MB	[Pull] [Delete]
v5	Linux	0	11 minutes ago	47.87 MB	[Pull] [Delete]
v6	Linux	0	2 days ago	62.50 MB	[Pull] [Delete]

**GITHUB LINK:** <https://github.com/bsse23064/SCD-quiz2>