### **NAME**

CUTEST\_ugrdh\_threaded - CUTEst tool to evaluate the gradient and Hessian matrix.

#### **SYNOPSIS**

CALL CUTEST\_ugrdh\_threaded( status, n, X, G, lh1, H\_val, thread )

## DESCRIPTION

The CUTEST\_ugrdh\_threaded subroutine evaluates the gradient and Hessian matrix of the objective function of the problem decoded from a SIF file by the script *sifdecode* at the point X. This Hessian matrix is stored as a dense matrix.

The problem under consideration is to minimize or maximize an objective function f(x) over all  $x \in \mathbb{R}^n$  subject to the simple bounds  $x^l \le x \le x^u$ . The objective function is group-partially separable.

#### **ARGUMENTS**

The arguments of CUTEST\_ugrdh\_threaded are as follows

### status [out] - integer

the outputr status: 0 for a successful call, 1 for an array allocation/deallocation error, 2 for an array bound error, 3 for an evaluation error, 4 for an out-of-range thread,

### n [in] - integer

the number of variables for the problem,

## **X** [in] - real/double precision

an array which gives the current estimate of the solution of the problem,

## G [out] - real/double precision

an array which gives the value of the gradient of the objective function evaluated at X,

## lh1 [in] - integer

the actual declared size of the leading dimension of H\_val (with lh1 no smaller than N),

## H\_val [out] - real/double precision

a two-dimensional array which gives the value of the Hessian matrix of the objective function evaluated at X,

# thread [inout] - integer

thread chosen for the evaluation; threads are numbered from 1 to the value threads set when calling CUTEST\_usetup\_threaded.

## NOTE

Calling this routine is more efficient than separate calls to CUTEST\_ugr\_threaded and CUTEST\_udh\_threaded.

#### **AUTHORS**

I. Bongartz, A.R. Conn, N.I.M. Gould, D. Orban and Ph.L. Toint

#### SEE ALSC

CUTEr (and SifDec): A Constrained and Unconstrained Testing Environment, revisited,

N.I.M. Gould, D. Orban and Ph.L. Toint,

ACM TOMS, 29:4, pp.373-394, 2003.

CUTE: Constrained and Unconstrained Testing Environment, I. Bongartz, A.R. Conn, N.I.M. Gould and Ph.L. Toint, TOMS, 21:1, pp.123-160, 1995.

cutest\_cgrdh\_threaded(3M), sifdecode(1).

### **NAME**

CUTEST\_ugrdh\_threaded - CUTEst tool to evaluate the gradient and Hessian matrix.

#### **SYNOPSIS**

CALL CUTEST\_ugrdh\_threaded( status, n, X, G, lh1, H\_val, thread )

## DESCRIPTION

The CUTEST\_ugrdh\_threaded subroutine evaluates the gradient and Hessian matrix of the objective function of the problem decoded from a SIF file by the script *sifdecode* at the point X. This Hessian matrix is stored as a dense matrix.

The problem under consideration is to minimize or maximize an objective function f(x) over all  $x \in \mathbb{R}^n$  subject to the simple bounds  $x^l \le x \le x^u$ . The objective function is group-partially separable.

#### **ARGUMENTS**

The arguments of CUTEST\_ugrdh\_threaded are as follows

### status [out] - integer

the outputr status: 0 for a successful call, 1 for an array allocation/deallocation error, 2 for an array bound error, 3 for an evaluation error, 4 for an out-of-range thread,

### n [in] - integer

the number of variables for the problem,

## **X** [in] - real/double precision

an array which gives the current estimate of the solution of the problem,

## G [out] - real/double precision

an array which gives the value of the gradient of the objective function evaluated at X,

## lh1 [in] - integer

the actual declared size of the leading dimension of H\_val (with lh1 no smaller than N),

## H\_val [out] - real/double precision

a two-dimensional array which gives the value of the Hessian matrix of the objective function evaluated at X,

# thread [inout] - integer

thread chosen for the evaluation; threads are numbered from 1 to the value threads set when calling CUTEST\_usetup\_threaded.

## NOTE

Calling this routine is more efficient than separate calls to CUTEST\_ugr\_threaded and CUTEST\_udh\_threaded.

#### **AUTHORS**

I. Bongartz, A.R. Conn, N.I.M. Gould, D. Orban and Ph.L. Toint

#### SEE ALSC

CUTEr (and SifDec): A Constrained and Unconstrained Testing Environment, revisited,

N.I.M. Gould, D. Orban and Ph.L. Toint,

ACM TOMS, 29:4, pp.373-394, 2003.

CUTE: Constrained and Unconstrained Testing Environment, I. Bongartz, A.R. Conn, N.I.M. Gould and Ph.L. Toint, TOMS, 21:1, pp.123-160, 1995.

cutest\_cgrdh\_threaded(3M), sifdecode(1).