## **NAME**

CUTEST\_uofg - CUTEst tool to evaluate function value and possibly gradient.

### **SYNOPSIS**

CALL CUTEST\_uofg( data, status, n, X, f, G, grad )

### DESCRIPTION

The CUTEST\_uofg subroutine evaluates the value of the objective function of the problem decoded from a SIF file by the script *sifdecode* at the point X, and possibly its gradient.

The problem under consideration is to minimize or maximize an objective function f(x) over all  $x \in \mathbb{R}^n$  subject to the simple bounds  $x^l \le x \le x^u$ . The objective function is group-partially separable.

### **ARGUMENTS**

The arguments of CUTEST\_uofg are as follows

**data** [inout] - CUTEST\_data\_type derived type problem-specific private data,

status [out] - integer

the outputr status: 0 for a successful call, 1 for an array allocation/deallocation error, 2 for an array bound error, 3 for an evaluation error,

n [in] - integer

the number of variables for the problem,

X [in] - real/double precision

an array which gives the current estimate of the solution of the problem,

f [out] - real/double precision

the value of the objective function evaluated at X,

G [out] - real/double precision

an array which gives the value of the gradient of the objective function evaluated at X,

grad [in] - logical

a logical variable which should be set to .TRUE. if the gradient of the objective function is required and .FALSE. otherwise.

### NOTE

A call to CUTEST\_uofg is more efficient than two separate calls to CUTEST\_ufn and CUTEST\_ugr.

### **AUTHORS**

I. Bongartz, A.R. Conn, N.I.M. Gould, D. Orban and Ph.L. Toint

# **SEE ALSO**

CUTEr (and SifDec): A Constrained and Unconstrained Testing Environment, revisited,

N.I.M. Gould, D. Orban and Ph.L. Toint,

ACM TOMS, 29:4, pp.373-394, 2003.

*CUTE: Constrained and Unconstrained Testing Environment*, I. Bongartz, A.R. Conn, N.I.M. Gould and Ph.L. Toint, TOMS, **21**:1, pp.123-160, 1995.

cutest\_cofg(3M), sifdecode(1).

## **NAME**

CUTEST\_uofg - CUTEst tool to evaluate function value and possibly gradient.

### **SYNOPSIS**

CALL CUTEST\_uofg( data, status, n, X, f, G, grad )

### DESCRIPTION

The CUTEST\_uofg subroutine evaluates the value of the objective function of the problem decoded from a SIF file by the script *sifdecode* at the point X, and possibly its gradient.

The problem under consideration is to minimize or maximize an objective function f(x) over all  $x \in \mathbb{R}^n$  subject to the simple bounds  $x^l \le x \le x^u$ . The objective function is group-partially separable.

### **ARGUMENTS**

The arguments of CUTEST\_uofg are as follows

**data** [inout] - CUTEST\_data\_type derived type problem-specific private data,

status [out] - integer

the outputr status: 0 for a successful call, 1 for an array allocation/deallocation error, 2 for an array bound error, 3 for an evaluation error,

n [in] - integer

the number of variables for the problem,

X [in] - real/double precision

an array which gives the current estimate of the solution of the problem,

f [out] - real/double precision

the value of the objective function evaluated at X,

G [out] - real/double precision

an array which gives the value of the gradient of the objective function evaluated at X,

grad [in] - logical

a logical variable which should be set to .TRUE. if the gradient of the objective function is required and .FALSE. otherwise.

### NOTE

A call to CUTEST\_uofg is more efficient than two separate calls to CUTEST\_ufn and CUTEST\_ugr.

### **AUTHORS**

I. Bongartz, A.R. Conn, N.I.M. Gould, D. Orban and Ph.L. Toint

# **SEE ALSO**

CUTEr (and SifDec): A Constrained and Unconstrained Testing Environment, revisited,

N.I.M. Gould, D. Orban and Ph.L. Toint,

ACM TOMS, 29:4, pp.373-394, 2003.

*CUTE: Constrained and Unconstrained Testing Environment*, I. Bongartz, A.R. Conn, N.I.M. Gould and Ph.L. Toint, TOMS, **21**:1, pp.123-160, 1995.

cutest\_cofg(3M), sifdecode(1).